

New Quantum Algorithms for Computing Quantum Entropies and Distances

Qisheng Wang^{*} Ji Guan[†] Junyi Liu[‡] Zhicheng Zhang[§]
Mingsheng Ying[¶]

Abstract

We propose a series of quantum algorithms for computing a wide range of quantum entropies and distances, including the von Neumann entropy, quantum Rényi entropy, trace distance, and fidelity. The proposed algorithms significantly outperform the best known (and even quantum) ones in the low-rank case, some of which achieve exponential speedups. In particular, for N -dimensional quantum states of rank r , our proposed quantum algorithms for computing the von Neumann entropy, trace distance and fidelity within additive error ε have time complexity of $\tilde{O}(r^2/\varepsilon^2)$, $\tilde{O}(r^5/\varepsilon^6)$ and $\tilde{O}(r^{6.5}/\varepsilon^{7.5})$ ¹, respectively. In contrast, the known algorithms for the von Neumann entropy and trace distance require quantum time complexity of $\Omega(N)$ [AISW19, GL20, GHS21], and the best known one for fidelity requires $\tilde{O}(r^{21.5}/\varepsilon^{23.5})$ [WZC⁺21].

The key idea of our quantum algorithms is to extend block-encoding from unitary operators in previous work to quantum states (i.e., density operators). It is realized by developing several convenient techniques to manipulate quantum states and extract information from them. In particular, we introduce a novel technique for eigenvalue transformation of density operators and their (non-integer) positive powers, based on the powerful quantum singular value transformation (QSVT) [GSLW19]. The advantage of our techniques over the existing methods is that no restrictions on density operators are required; in sharp contrast, the previous methods usually require a lower bound of the minimal non-zero eigenvalue of density operators. In addition, we provide some techniques of independent interest for trace estimation, linear combinations, and eigenvalue threshold projectors of (subnormalized) density operators, which will be, we believe, useful in other quantum algorithms.

Keywords: Quantum Computing, Quantum Algorithms, Quantum Entropy, Trace Distance, Quantum Fidelity.

^{*}Department of Computer Science and Technology, Tsinghua University, China. Email: QishengWang1994@gmail.com

[†]State Key Laboratory of Computer Science, Institute of Software, Chinese Academy of Sciences, China. Email: guanji1992@gmail.com

[‡]State Key Laboratory of Computer Science, Institute of Software, Chinese Academy of Sciences, China; University of Chinese Academy of Sciences, China. Email: liujy@ios.ac.cn

[§]Centre for Quantum Software and Information, University of Technology Sydney, Australia. Email: iszczhang@gmail.com

[¶]State Key Laboratory of Computer Science, Institute of Software, Chinese Academy of Sciences, China; Department of Computer Science and Technology, Tsinghua University, China. Email: yingms@ios.ac.cn

¹ $\tilde{O}(\cdot)$ suppresses polylogarithmic factors of r , ε and N .

1 Introduction

Quantum entropies and distances are basic concepts [NC10] in quantum physics and quantum information. Quantum entropies characterize the randomness of a quantum system, while quantum distances measure the closeness of quantum systems. It is important to compute their values in many important applications, from the estimation of the capacity of quantum communication channels and verification of the outcomes of quantum computation to the characterization of quantum physical systems (see, e.g., [OP04, ZLW⁺21, Kuz21]). Several kinds of quantum algorithms for computing quantum entropies and distances have been proposed under different computational resources, e.g., quantum algorithms with access to copies of quantum states [BOW19, AISW19, WZW22], quantum algorithms with purified quantum query access [GL20, GHS21, SH21, WZC⁺21], and variational quantum algorithms [CPCC20, CSZW20, TV21].

A main consideration of some quantum algorithms for computing quantum entropies and distances is the number of copies of quantum states used in the algorithms. For example, [BOW19] provided a method of testing the closeness of N -dimensional mixed quantum states with respect to trace distance and fidelity using $O(N/\varepsilon^2)$ and $O(N/\varepsilon)$ copies, respectively, based on quantum spectrum testing [OW15] and efficient quantum tomography [OW16, OW17, HHJ⁺17]. [AISW19] introduced a method of computing the von Neumann and quantum Rényi entropies of an N -dimensional quantum state using $O(N^2/\varepsilon^2)$ and $O(N^{2/\alpha}/\varepsilon^{2/\alpha})$ copies, respectively. Recently, a new method of computing the von Neumann and quantum Rényi entropies was proposed in [WZW22] using $\tilde{O}(\kappa^2/\varepsilon^5)$ copies, where $\kappa > 0$ is given such that $\Pi/\kappa \leq \rho \leq I$ for some projector Π . A distributed quantum algorithm for computing $\text{tr}(\rho\sigma)$, i.e., the fidelity of pure quantum states, was proposed in [ALL21] using $O(\max\{\sqrt{N}/\varepsilon, 1/\varepsilon^2\})$ copies.

Another class of quantum algorithms for computing quantum entropies and distances utilize the conventional “purified quantum query access” model, where mixed quantum states are given by quantum oracles that prepare their purifications. [GL20] developed quantum algorithms for computing the von Neumann entropy and trace distance with query complexity $O(N/\varepsilon^{1.5})$ and $O(N/\varepsilon)$, respectively, both of which have complexity exponential in the number of qubits. Recently, [GHS21] proposed a quantum algorithm for computing the von Neumann entropy within a multiplicative factor, which can reproduce the result of [GL20] within additive error. [SH21] found a method of computing the quantum α -Rényi entropy using $O\left(\frac{\kappa}{(x\varepsilon)^2} \log\left(\frac{N}{\varepsilon}\right)\right)$ queries to the oracle, where $\kappa > 0$ is given such that $I/\kappa \leq \rho \leq I$ and $x = \text{tr}(\rho^\alpha)/N$.

The quantum algorithms with purified quantum query access mentioned above are developed in the general framework of quantum singular value transformation (QSVT) [GSLW19]. The powerful technique of QSVT on unitary operators developed by [GSLW19] has been successfully applied in improving a wide range of quantum algorithms, including Grover’s search algorithm [Gro96], the quantum walk algorithms [Amb04, Sze04], the HHL algorithm for solving systems of linear equations [HHL09], and Hamiltonian simulation [LC17]. The original QSVT deals with unitary operators, but a Hamiltonian variant of the QSVT was proposed in [LKAS⁺21], which is then used in quantum polar decomposition [LBDP⁺20, QR21].

Except for unitary operators and Hamiltonians, density operators (mixed quantum states) are another important class of objects we need to deal with in quantum computation. [LC19] developed a technique to implement a unitary operator that block-encodes a (purified) density operator. This technique has been employed in quantum algorithms for semidefinite programming [vAG19] and quantum fidelity estimation [WZC⁺21]. Conversely, however, it seems difficult to prepare a quantum state given as a density operator block-encoded in a unitary operator.

A natural idea of extracting information from a density operator is to directly manipulate the

quantum state itself rather than a unitary operator that encodes it. This leads us to extend the definition of block-encoding proposed originally for unitary operators [LC19, GSLW19, CGJ19] to that for general operators (see Definition 2.1), especially for quantum states (i.e., density operators). Regarding quantum states as block-encodings, we are able to design new quantum algorithms for computing a wide range of quantum entropies and distances, such as the von Neumann entropy, quantum Rényi entropy, quantum Tsallis entropy, trace distance, and fidelity. These quantum algorithms significantly outperform the best known ones in the low-rank case, and some of them can even achieve exponential speedups. Here, the low-rank case means that the rank of N -dimensional quantum states is much smaller than N , e.g., $r = \text{polylog}(N)$, which is of great interest in both theoretical (e.g., [GLF⁺10, EHC22]) and experimental (e.g., [BGK15]) physics.

In the remainder of this Introduction, we will first present our main results in Section 1.1. The new techniques that enable us to achieve our results will be outlined in Section 1.2. Then related works will be reviewed in Section 1.3, and a discussion will be given in Section 1.4.

1.1 Main Results

Let us first set the stage for presenting our main results. In order to manipulate quantum states, we extend the definition of block-encoding for unitary operators to that for general operators (see Definition 2.1), and use this extended definition of block-encoding to describe our quantum algorithms. In our quantum algorithms, a mixed quantum state is given by a quantum unitary operator (oracles) which prepares a purification of the state (see Definition 2.2). This conventional model is known as the “purified quantum query access” model and has been widely used in developing quantum algorithms [BKL⁺19, vAG19, GL20, GLM⁺20, ARSW21, GHS21, SH21].

Throughout this paper, the quantum query complexity of a quantum query algorithm means the number of queries to the given quantum oracles. The time complexity of a quantum query algorithm is the sum of its quantum query complexity and the number of elementary quantum gates used in it. When quantum algorithms are compared with classical algorithms, quantum oracles are given as classical descriptions of quantum circuits. The actual number of elementary quantum gates performed in the quantum algorithm only has a polynomial overhead compared to its “time complexity” defined here. Then our main results can be summarized in the following:

Theorem 1.1 (Informal). *Given “purified quantum query access” quantum oracles that prepare N -dimensional mixed quantum states of rank r , there are quantum query algorithms that compute*

- *von Neumann entropy,*
- *quantum α -Rényi entropies for $\alpha \in (0, 1) \cup (1, +\infty)$,*
- *quantum α -Tsallis entropies for $\alpha \in (0, 1) \cup (1, +\infty)$,*
- *α -trace distance for $\alpha > 0$ (defined by Equation (1), including the trace distance), and*
- *α -fidelity for $0 < \alpha < 1$ (defined by Equation (2), including the fidelity)*

within additive error ε with time complexity $\text{poly}(\log(N), r, 1/\varepsilon)$, where the time complexity hides a constant which depends only on α .²

²A few days after this paper was submitted to arXiv, the concurrent work of Gilyén and Poremba [GP22] appeared. They proposed a quantum algorithm for fidelity estimation using identical copies of quantum states based on density matrix exponentiation [LMR14, KLL⁺17]. We note that their techniques of converting identical copies to unitary block-encodings (Corollary 21 in [GP22]) can be applied to our quantum algorithms in Theorem 1.1. As a result, we can obtain quantum algorithms for computing these quantum entropies and distances using $\text{poly}(r, 1/\varepsilon)$ copies of quantum states, which only has a polynomial overhead compared to the query complexity of our algorithms.

Our quantum algorithms are compared with the existing algorithms for the same problems in Table 1. In particular, our algorithms outperform the best known ones in the low-rank case, e.g., $r = \text{polylog}(N)$. More precisely:

- For the von Neumann entropy, quantum Rényi entropy and trace distance, our quantum algorithms are exponentially faster than those given in [AISW19, BOW19, GL20, SH21] in the low-rank case (although they are designed for the general case).
- For the quantum algorithms in [SH21] and [WZW22] that attempt to reduce the dependence on N , they introduce an extra dependence on κ , where κ is the reciprocal of the minimal non-zero eigenvalue of quantum states. Our quantum algorithms can be easily adapted to their settings by taking $r = O(\kappa)$, but the converse seems not applicable ³.
- For the fidelity, our quantum algorithm achieves a polynomial speedup over the one given in [WZC⁺21].

Table 1: Our quantum algorithms vs. prior works

Quantum Information Quantity	Best Prior Sample Complexity	Best Prior Query Complexity	Our Query Complexity
Von Neumann Entropy	$O(N^2/\varepsilon^2)$ [AISW19]	$\tilde{O}(N/\varepsilon^{1.5})$ [GL20]	$\tilde{O}(r^2/\varepsilon^2)$
Quantum α -Rényi Entropy (for non-integer $\alpha > 0$)	$O((N/\varepsilon)^{\max\{2/\alpha, 2\}})$ [AISW19]	$\tilde{O}(\kappa N^{\max\{2\alpha, 2\}}/\varepsilon^2)$ [SH21]	$\tilde{O}\left(\frac{r^{\alpha-1+\alpha/\{\frac{\alpha-1}{2}\}}}{\varepsilon^{1+1/\{\frac{\alpha-1}{2}\}}}\right)$
Trace Distance	$O(N/\varepsilon^2)$ ⁴ [BOW19]	$\tilde{O}(N/\varepsilon)$ [GL20]	$\tilde{O}(r^5/\varepsilon^6)$
Fidelity	$O(N/\varepsilon)$ ⁴ [BOW19]	$\tilde{O}(r^{21.5}/\varepsilon^{23.5})$ ⁵ [WZC ⁺ 21]	$\tilde{O}(r^{6.5}/\varepsilon^{7.5})$

N is the dimension of quantum states. ε is the desired additive error. r is (an upper bound of) the rank of quantum states. $\{x\} = x - \lfloor x \rfloor$ denotes the decimal part of x . κ is the parameter associated with mixed quantum state ρ such that $I/\kappa \leq \rho \leq I$, which only appears in the best prior query complexity of quantum α -Rényi entropy.

We will further discuss about the above results for quantum entropies in Section 1.1.1 and those for closeness (i.e. trace distance and fidelity) of quantum states in Section 1.1.2.

1.1.1 Computing quantum entropies

In quantum information theory, the entropy of a (mixed) quantum state is a measure of its uncertainty, and computing its value is crucial when characterizing and verifying an unknown quantum system. After von Neumann [vN32] introduced the famous von Neumann entropy

$$S(\rho) = -\text{tr}(\rho \ln(\rho)),$$

³This is because κ implies an upper bound $r \leq \kappa$ of rank, but r does not imply any upper bound of κ .

⁴This is the sample complexity of testing the closeness of quantum states with respect to the trace distance (resp. fidelity). It is worth mentioning that testing the closeness can be solved by computing the closeness, but the converse seems difficult.

⁵In the concurrent work of Gilyén and Poremba [GP22], they presented a different quantum algorithm for fidelity estimation with a better query complexity $\tilde{O}(r^{2.5}/\varepsilon^5)$.

which is a natural generalization of the classical Shannon entropy [Sha48], several other entropies have been proposed, e.g., Rényi entropy [Rén61, LMW13, MLDS⁺13, WWY14], Tsallis entropy [Tsa88, Aud07, PV15], Min and Max (Hartley) entropies [vDH02, Dat09, KRS09], and the unified entropy [HY06, Ras11]. The quantum α -Rényi entropy and the quantum α -Tsallis entropy are defined by

$$S_\alpha^R(\rho) = \frac{1}{1-\alpha} \ln(\text{tr}(\rho^\alpha)), \quad S_\alpha^T(\rho) = \frac{1}{1-\alpha} (\text{tr}(\rho^\alpha) - 1)$$

for $\alpha \in (0, 1) \cup (1, +\infty)$, respectively. It is easy to see that the von Neumann entropy is a limit case of the Rényi entropy [MLDS⁺13] and the Tsallis entropy [Tsa88]:

$$S(\rho) = \lim_{\alpha \rightarrow 1} S_\alpha^R(\rho) = \lim_{\alpha \rightarrow 1} S_\alpha^T(\rho).$$

For $\alpha = 0$, the quantum Tsallis entropy degenerates to the rank of quantum states:

$$S_0^T(\rho) = \text{rank}(\rho) - 1$$

and the quantum Rényi entropy becomes the logarithm of the rank, i.e., the quantum Max (Hartley) entropy:

$$S^{\max}(\rho) = S_0^R(\rho) = \ln(\text{rank}(\rho)).$$

Overview Given a quantum unitary oracle that prepares a mixed quantum state (see Definition 2.2). We develop quantum algorithms for computing several quantum entropies. Their quantum query complexities are collected in Table 2, which are also their quantum time complexities up to polylogarithmic factors. Most of our algorithms do not require any restrictions on the lower bound of the eigenvalues of quantum states except those for computing the quantum Max entropy and the rank of quantum states, where $\Pi/\kappa \leq \rho$ is required for some projector Π and $\kappa > 0$.

Table 2: Quantum query complexity for computing quantum entropies.

Parameter α		Quantum Rényi Entropy $S_\alpha^R(\rho)$	Quantum Tsallis Entropy $S_\alpha^T(\rho)$
$\alpha = 0$		$\tilde{O}(\kappa^2/\varepsilon)$ (Theorem 3.6) (Max Entropy)	$\tilde{O}(\kappa^3)$ (Corollary 3.5) (Rank)
$0 < \alpha < 1$		$\tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right)$ (Theorem 3.8 and 3.9)	
$\alpha = 1$ (Von Neumann Entropy)		$\tilde{O}(r^2/\varepsilon^2)$ (Theorem 3.1)	
$\alpha > 1$	$\alpha \equiv 1 \pmod{2}$	$O(r^{\alpha-1}/\varepsilon)$ (Theorem 3.8)	$O(1/\varepsilon)$ (Theorem 3.9)
	$\alpha \not\equiv 1 \pmod{2}$	$\tilde{O}\left(r^{\alpha-1+\alpha/\{\frac{\alpha-1}{2}\}}/\varepsilon^{1+1/\{\frac{\alpha-1}{2}\}}\right)$ (Theorem 3.8 and 3.9)	

r is (an upper bound of) the rank of quantum states. ε is the desired additive error. $\{x\} = x - \lfloor x \rfloor$ denotes the decimal part of x . κ is the parameter associated with mixed quantum state ρ such that $\Pi/\kappa \leq \rho$ for some projector Π , which is only used in the case $\alpha = 0$.

The previous best known quantum algorithms for computing von Neumann entropy [AISW19, GL20, GHS21] and quantum Rényi entropy [AISW19, SH21] have time complexity $\Omega(N)$ even for rank $r = 2$. Compared to them, our quantum algorithms are exponentially faster in the low-rank case.

It is worth mentioning that for odd integer $\alpha > 1$, the query complexity of computing the quantum Tsallis entropy $S_\alpha^T(\rho)$ does not depend on rank r . In this case, there is a simple SWAP test-like quantum algorithm that computes $\text{tr}(\rho^\alpha)$ using $O(1/\varepsilon^2)$ copies [EAO⁺02, KLL⁺17]. Compared to it, our algorithm (Theorem 3.7) yields a quadratic speedup (see Section 3.3 for more discussions). For non-integer α , we are not aware of any approach for computing the quantum Tsallis entropy with complexity better than quantum state tomography.

Lower bounds We are able to give a lower bound $\tilde{\Omega}(r^c)$ for computing the quantum Rényi entropy $S_\alpha^R(\rho)$ including the von Neumann entropy $S(\rho)$ in terms of rank r , where $c \geq 1/3$ is a constant depending only on α (see Theorem 3.11). This lower bound is simply derived from the quantum query complexity for computing the Rényi (and Shannon) entropy of classical probability distributions [LW19, BKT20].

1.1.2 Computing quantum distances

Distance measures of quantum states are basic quantities in quantum computation and quantum information. Two of the most important distance measures are the trace distance and fidelity. For each of them, we propose quantum algorithms that compute it and its extensions. Here, we assume that there are two quantum oracles U_ρ and U_σ that prepare the density operators ρ and σ , respectively. The query complexity of a quantum algorithm means the total number of queries to both U_ρ and U_σ .

Trace distance The α -trace distance of two quantum states ρ and σ is defined by

$$T_\alpha(\rho, \sigma) = \text{tr} \left(\left| \frac{\rho - \sigma}{2} \right|^\alpha \right) = \left\| \frac{\rho - \sigma}{2} \right\|_{S, \alpha}^\alpha, \quad (1)$$

where $\|A\|_{S, \alpha} = (\text{tr}(|A|^\alpha))^{1/\alpha}$ is the Schatten α -norm. Here, the 1-trace distance is the well-known trace distance $T(\rho, \sigma) = T_1(\rho, \sigma)$.

Table 3: Quantum query complexity for computing α -trace distance.

Parameter α	$T_\alpha(\rho, \sigma)$ (Theorem 4.1)
$0 < \alpha < 1$	$\tilde{O}(r^{5/\alpha + (1-\alpha)/2} / \varepsilon^{5/\alpha + 1})$
$\alpha \equiv 0 \pmod{2}$	$\tilde{O}(r^3 / \varepsilon^4)$
$\alpha \geq 1$ and $\alpha \not\equiv 0 \pmod{2}$	$\tilde{O}(r^{3+1/\{\alpha/2\}} / \varepsilon^{4+1/\{\alpha/2\}})$
$\alpha = 1$ (Trace Distance)	$\tilde{O}(r^5 / \varepsilon^6)$

r is (an upper bound of) the higher rank of the two quantum states. ε is the desired additive error. $\{x\} = x - \lfloor x \rfloor$ denotes the decimal part of x .

We develop quantum algorithms for computing α -trace distance for $\alpha > 0$, with their complexities shown in Table 3. As a special case, our quantum algorithm (Theorem 4.1) for computing the trace distance (i.e., the 1-trace distance) has time complexity of $\tilde{O}(r^5 / \varepsilon^6)$, which, in the low-rank case, is exponentially faster than the closeness-testing with respect to trace distance in [GL20] with query complexity $O(N/\varepsilon)$. Moreover, only the closeness testing of the α -trace distances of quantum states for integer α , e.g., the 1-, 2- and 3-trace distances, was studied in [GL20]. For other cases of α , we are not aware of any approaches to compute the α -trace distance with complexity better than quantum state tomography.

Fidelity The α -fidelity of two quantum states ρ and σ is defined by

$$F_\alpha(\rho, \sigma) = \exp((\alpha - 1)D_\alpha(\rho\|\sigma)) = \text{tr} \left(\left(\sigma^{\frac{1-\alpha}{2\alpha}} \rho \sigma^{\frac{1-\alpha}{2\alpha}} \right)^\alpha \right), \quad (2)$$

where $D_\alpha(\rho\|\sigma)$ is the sandwiched quantum Rényi relative entropy [WWY14, MLDS⁺13]. Here, the 1/2-fidelity is the well-known fidelity $F(\rho, \sigma) = F_{1/2}(\rho, \sigma)$ [Joz94].

We develop quantum algorithms for computing the α -fidelity for $0 < \alpha < 1$, with their complexities shown in Table 4). As a special case, our quantum algorithm (Theorem 4.5) for computing the fidelity (i.e., the 1/2-fidelity) has a time complexity $\tilde{O}(r^{6.5}/\varepsilon^{7.5})$, which is a polynomial speedup over the best known $\tilde{O}(r^{21.5}/\varepsilon^{23.5})$ in [WZC⁺21]. For other cases of α , we do not know any approach to compute the α -fidelity with complexity better than quantum state tomography.

Table 4: Quantum query complexity for computing α -fidelity.

Parameter $\beta = (1 - \alpha)/2\alpha$	$F_\alpha(\rho, \sigma)$ (Theorem 4.5)
$\beta \in \mathbb{N}$	$\tilde{O}\left(r^{\frac{3-\alpha}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right)$
$\beta \notin \mathbb{N}$	$\tilde{O}\left(r^{\frac{3-\alpha}{2\alpha} + \frac{1}{\alpha\{\beta\}}}/\varepsilon^{\frac{3+\alpha}{2\alpha} + \frac{1}{\alpha\{\beta\}}}\right)$
$\alpha = \beta = 1/2$ (Fidelity)	$\tilde{O}(r^{6.5}/\varepsilon^{7.5})$

r is (an upper bound of) the lower rank of the two quantum states. ε is the desired additive error. $\{x\} = x - \lfloor x \rfloor$ denotes the decimal part of x .

Lower bounds and hardness Our quantum algorithms for computing the fidelity and trace distance have a time complexity polynomial in the rank r . We show that there is no quantum algorithm that computes the fidelity or trace distance with time complexity $\text{poly}(\log(r), 1/\varepsilon)$ unless $\text{BQP} = \text{QSZK}$ (see Theorem 4.7), based on the result of [Wat02] that (α, β) -Quantum State Distinguishability is QSZK -complete for $0 \leq \alpha < \beta^2 \leq 1$.

Our quantum algorithms for computing the fidelity and trace distance achieve a significant speedup under the low-rank assumption. One might wonder whether our algorithms can be “dequantized” through quantum-inspired low-rank techniques such as [Tan19, GLT18, CGL⁺20]. We argue that our algorithms are unlikely to be dequantized due to the DQC1 -hardness of computing the fidelity and trace distance (see Theorem 4.8). It was shown in [FKM⁺18] that DQC1 is not (classically) weakly simulatable unless the polynomial hierarchy collapses to the second level, i.e., $\text{PH} = \text{AM}$.

1.2 Techniques

In this subsection, we give an overview of the techniques that enable us to achieve the results presented in the above subsection.

1.2.1 Quantum states as block-encodings

The key idea of our quantum algorithms is to regard quantum states as block-encodings. To this end, we extend the definition of block-encoding proposed for unitary operators to that for general ones (see Definition 2.1). Suppose that a unitary operator U_A prepares a subnormalized density operator A (see Definition 2.2). In this framework, we provide a convenient way to manipulate the subnormalized density operator A and extract information from it as follows.

- **Evolution:** If U is a unitary operator, which is a block-encoding of an operator B , we can prepare a subnormalized density operator BAB^\dagger (see Lemma 2.2). This evolution of the subnormalized density operator can be seen as a generalization of quantum unitary operation $\rho \mapsto U\rho U^\dagger$ for (normalized) density operator ρ .
- **Trace Estimation:** We provide an efficient method to estimate the trace of A based on quantum amplitude estimation [BHMT02] (see Lemma 2.15). As will be seen, trace estimation is an important subroutine in our quantum algorithms (see Section 1.1.1 and Section 1.1.2).
- **Linear Combinations:** As an analog of Linear-Combination-of-Unitaries (LCU) algorithm through a series of work [SOG⁺02, CW12, Kot14, BCC⁺15, BCK15, CKS17, GSLW19], we also provide a technique to prepare a linear (convex) combination of subnormalized density operators (see Lemma 2.17). This technique will be used in computing the trace distance (see Section 1.1.2 and Theorem 4.1).

The technique of “trace estimation” is the cornerstone in developing our quantum algorithms. To compute the values of quantum entropies and distances, the key part has the form $\text{tr}(\varrho)$, where ϱ is a (subnormalized) density operator. Our strategy is to prepare a quantum state, which is a block-encoding of ϱ , through the technique of “evolution”. Roughly speaking, we prepare the subnormalized density operator ϱ up to a scaling factor; we will use the phrase “prepare ϱ ” regardless of the scaling factor in the following discussion of this section. For example, we prepare $-\rho \ln(\rho)$ for the von Neumann entropy, and prepare ρ^α for the quantum α -Rényi and Tsallis entropies. To achieve this, we develop techniques for eigenvalue transformation of density operators based on QSVT as follows.

- **Eigenvalue Transformation:** Based on the evolution, if we can construct a unitary operator U , which is a block-encoding of $P(A)$ for some polynomial $P(\cdot)$ as in QSVT [GSLW19], we can transform A to another subnormalized density operator $A(P(A))^2$ (see Theorem 2.4).
- **Positive Powers:** We develop a technique to prepare the subnormalized density operator A^c for $0 < c < 1$ without any restrictions on A (see Lemma 2.8). Inspired by this, we can also obtain a unitary operator, which is a block-encoding of $|A|^c$, using queries to a unitary operator U , which is a block-encoding of Hermitian operator A (see Lemma 2.13). In order to obtain block-encodings of powers of A , previously known methods [CGJ19, GSLW19, GLM⁺20] usually require a lower bound of the minimal non-zero eigenvalues of density operators; for example, $I/\kappa \leq A \leq I$ for some $\kappa > 0$ in [CGJ19]. This technique for positive powers of subnormalized density operators will be frequently used in our quantum algorithms for computing quantum entropies, fidelity and trace distance (see Section 1.1.1 and Section 1.1.2), in order to avoid restrictions on density operators.

We also provide a method to block-encode the eigenvalue threshold projector $\Pi_{\text{supp}(A)}$ of A in a quantum state, where $\text{supp}(A)$ is the support of A , and Π_S is the projector onto subspace S .

- **Eigenvalue threshold projector:** We propose a method to (approximately) block-encode the eigenvalue threshold projector $\Pi_{\text{supp}(A)}$ of A in a subnormalized density operator (see Lemma 2.19). We note that [vAG19] also provided a technique for block-encoding eigenvalue threshold projectors, but they required that $A \geq q\Pi$ for some projector Π and the value of $q > 0$ is known in advance. In contrast, our method does not impose any restriction on A . This method will be used in computing the trace distance (see Section 1.1.2 and Theorem 4.1).

A comparison between density operators and unitary operators as block-encodings is given in Table 5.

Table 5: Comparison between density operators and unitary operators as block-encodings.

Operation Type	Density Operators $\rho \approx \begin{bmatrix} A & \cdot \\ \cdot & \cdot \end{bmatrix}$	Unitary Operators $U \approx \begin{bmatrix} A & \cdot \\ \cdot & \cdot \end{bmatrix}$
Evolution	$A \rightarrow BAB^\dagger$	$A \rightarrow AB \text{ or } BA$
Trace Estimation	$\text{tr}(A)$	$\text{tr}(A)/2^a$ ⁶
Linear Combination	$\alpha_1 A_1 + \dots + \alpha_k A_k \ (\alpha_i \in \mathbb{R}^+)$	$\alpha_1 A_1 + \dots + \alpha_k A_k \ (\alpha_i \in \mathbb{C})$
Eigenvalue Transformation	$A \rightarrow A(P(A))^2$	$A \rightarrow P(A)$
Positive Powers	$A \rightarrow A^c \ (0 < c < 1)$	$A \rightarrow A ^c \ (0 < c < 1)$
Eigenvalue Threshold Projector	$A \rightarrow (\text{scaled}) \Pi_{\text{supp}(A)}$	$A \rightarrow \Pi_{\text{supp}(A)}$

A is an Hermitian operator block-encoded in a density ρ or a unitary operator U . B is block-encoded in a unitary operator. $P(\cdot)$ is a polynomial.

1.2.2 Example: computing trace distance

To give the reader a flavor, we take the quantum algorithm for computing the trace distance (see Theorem 4.1 for details) as an illustrative example. The key observation to compute the trace distance is that

$$T(\rho, \sigma) = \text{tr} \left(|\nu|^{1/2} \Pi_{\text{supp}(\mu)} |\nu|^{1/2} \right),$$

where $\nu = (\rho - \sigma)/2$, $\mu = (\rho + \sigma)/2$. The idea is to prepare $\eta = |\nu|^{1/2} \Pi_{\text{supp}(\mu)} |\nu|^{1/2}$ (up to a scaling factor), and then estimate $\text{tr}(\eta)$ through the technique of “trace estimation” (Lemma 2.15). The computation process is shown in Figure 1.

$$\left. \begin{array}{l} \text{Density: } \rho, \sigma \rightarrow \mu = (\rho + \sigma)/2 \rightarrow \hat{\Pi} \approx \Pi_{\text{supp}(\mu)} \\ \downarrow \\ \text{Unitary: } \rho, \sigma \rightarrow \nu = |\rho - \sigma|/2 \rightarrow \hat{\nu} \approx |\nu|^{1/2} \end{array} \right\} \rightarrow \hat{\nu} \hat{\Pi} \hat{\nu}^\dagger \rightarrow \text{tr} \left(\hat{\nu} \hat{\Pi} \hat{\nu}^\dagger \right) \approx \text{tr}(\eta) = T(\rho, \sigma)$$

Figure 1: The computation process of computing trace distance.

To (approximately) prepare η , we first prepare $\hat{\Pi} \approx \Pi_{\text{supp}(\mu)}$ through the technique of “eigenvalue threshold projector” (Lemma 2.19). Here, $\mu = (\rho + \sigma)/2$ can be prepared through the technique of “linear combinations” (Lemma 2.17). Then we only need to construct a unitary operator, which is a block-encoding of $\hat{\nu} \approx |\nu|^{1/2}$. After that, by the technique of “evolution” (Lemma 2.2), we can prepare $\hat{\nu} \hat{\Pi} \hat{\nu}^\dagger \approx |\nu|^{1/2} \hat{\Pi} |\nu|^{1/2} \approx \eta$.

In order to construct a unitary operator as a block-encoding of $|\nu|^{1/2}$, we first use the LCU technique (Theorem 2.18) to block-encode $\nu = (\rho - \sigma)/2$ in a unitary operator U_ν . Then applying the technique of “positive powers” (Lemma 2.13) on U_ν , we can construct a unitary operator which is a block-encoding of $\hat{\nu} \approx |\nu|^{1/2}$.

⁶Suppose A is an a -qubit Hermitian operator block-encoded in unitary operator U . Then $\text{tr}(A)/2^a = \text{tr}(|0\rangle\langle 0| \otimes \frac{I_a}{2^a} U)$ can be computed through the Hadamard test [EAO⁺02].

To get an estimation of the trace distance between ρ and σ , we should just note that $T(\rho, \sigma) = \text{tr}(\eta) \approx \text{tr}(\hat{\nu}\hat{\Pi}\hat{\nu}^\dagger)$, where we have already prepared $\hat{\nu}\hat{\Pi}\hat{\nu}^\dagger$ through the above process. Strictly speaking, we have prepared a mixed quantum state, whose density operator is a block-encoding of $\hat{\nu}\hat{\Pi}\hat{\nu}^\dagger$ up to a scaling factor. After carefully selecting appropriate parameters that determine the errors in the above process, we obtain a quantum algorithm for computing the trace distance with query complexity $\tilde{O}(r^5/\varepsilon^6)$, where r is (an upper bound of) the rank of quantum states ρ and σ , and ε is the desired additive error. Here, $\tilde{O}(\cdot)$ suppresses the polylogarithmic factor of N , where N is the dimension of the Hilbert space of ρ and σ .

1.3 Related Works

Classical property testing The problems considered in this paper can be thought of as a quantum analog of testing properties of probability distributions. Classical algorithms for testing properties of probability distributions have been widely studied since the beginning of this century. [BFR⁺00] first proposed an algorithm for the closeness testing of probability distributions in ℓ^1 distance using $\tilde{O}(N^{2/3}/\varepsilon^4)$ samples, which was then improved to use $\tilde{O}(N^{2/3}/\varepsilon^{8/3})$ samples [BFR⁺13]. Later, [CDVV14] proved the optimal sample complexity $\Theta(\max\{N^{2/3}/\varepsilon^{4/3}, N^{1/2}/\varepsilon^2\})$ for this problem, and also the optimal sample complexity $\Theta(1/\varepsilon^2)$ for closeness testing in ℓ^2 distance. The identity testing is a special case of the closeness testing given that one of the distributions is known. [BFF⁺01] showed that $\tilde{O}(N^{1/2}/\varepsilon^4)$ samples are sufficient for the identity testing in ℓ^1 distance, which was improved to optimal $\Theta(N^{1/2}/\varepsilon^2)$ in [Pan08]. The independence testing, i.e., whether a distribution on $[N] \times [M]$ ($N \geq M$) is or ε -far from a product distribution in ℓ^1 distance, was shown to have sample complexity $\tilde{O}(N^{2/3}M^{1/3}) \cdot \text{poly}(1/\varepsilon)$ [BFF⁺01]. Recently, [DK16] proposed a modular reduction-based approach that covers the closeness, identity and independence testing. They also gave a tight sample complexity $\Theta(\max\{N^{2/3}M^{1/3}/\varepsilon^{4/3}, (NM)^{1/2}/\varepsilon^2\})$ for the independence testing. In addition, the monotonicity testing was also shown to have sample complexity $\tilde{O}(N^{1/2}/\varepsilon^4)$ [BKR04].

Apart from property testing between distributions, properties of a single distribution are well studied in the literature, e.g., [BDKR05, Pan03, Pan04]. An algorithm that computes the Shannon entropy using $O\left(\frac{N}{\varepsilon \log(N)}\right)$ samples for $\varepsilon = \Omega(N^{0.03})$ was proposed in [VV11a, VV11b]. After that, [JVHW15] and [WY16] gave the optimal estimator of Shannon entropy using $\Theta\left(\frac{N}{\varepsilon \log(N)} + \frac{(\log(N))^2}{\varepsilon^2}\right)$ samples. Instead, [JVHW15] provided an estimator for $\exp((1 - \alpha)S_\alpha^R(p))$, where $S_\alpha^R(p)$ is the α -Rényi entropy of distribution p .

Quantum property testing The emerging topic of quantum property testing (see [MdW16]) studies the quantum advantage in testing classical statistical and quantum information properties.

Quantum advantages in testing classical statistical properties have been extensively studied. Quantum algorithms for testing properties of classical distributions was first studied in [BHH11], which gave quantum query complexity $O(N^{1/2}/\varepsilon^6)$ for the closeness testing, and $O(N^{1/3}/\varepsilon^{4/3})$ for identity testing (to the uniform distribution) in ℓ^1 distance. Later, [CFMdW10] improved the quantum query complexity for the identity testing (to a known distribution) to $\tilde{O}(N^{1/3}/\varepsilon^5)$, and [Mon15] improved that for the closeness testing in ℓ^1 distance to $\tilde{O}(N^{1/2}/\varepsilon^{2.5})$. Recently, [LW19] studied the quantum query complexity for computing the Shannon entropy and the Rényi entropy; especially, an $\tilde{O}(N^{1/2}/\varepsilon^2)$ quantum query complexity was shown for the Shannon entropy.

There are also some quantum algorithms for testing quantum information properties not mentioned above. [KLL⁺17] showed that testing orthogonality of pure quantum states needs $\Theta(1/\varepsilon)$

copies, promised that either they are orthogonal or their fidelity $\geq \varepsilon$. Recently, [Yu21] showed that quantum identity testing only requires $O(N^{3/2}/\varepsilon^2)$ copies with the help of random choice of independent measurements.

1.4 Discussion

In this paper, we suggest a generalized definition of block-encoding, with which we can directly manipulate subnormalized density operators and extract information from them. Based on this, we develop new quantum algorithms that compute a large class of quantum entropies and distances, which achieve a significant speedup over the best known ones in the low-rank case. Several interesting problems remain open:

- Our upper and lower bounds are far from being tight. Can we find more efficient algorithms or improve the lower bounds?
- It would be interesting to study other distance measures of quantum states, e.g., the relative von Neumann entropy [NC10] (the quantum generalization of the Kullback–Leibler divergence [KL51])

$$S(\rho\|\sigma) = \text{tr}(\rho(\ln(\rho) - \ln(\sigma))).$$

- Can we apply the idea of manipulating quantum states to problems other than computing quantum entropies and distances?

1.5 Organization of This Paper

Section 2 introduces the idea that regards quantum states as block-encodings, and provides a series of basic techniques for manipulating them. Section 3 presents quantum algorithms that compute quantum entropies, including the von Neumann entropy, quantum Rényi entropy and quantum Tsallis entropy. Section 4 presents quantum algorithms that compute the trace distance, fidelity and their extensions.

2 Quantum States as Block-Encodings

Since the introduction of qubitization in Hamiltonian simulation [LC19], block-encodings have been widely used as a basic notion in quantum algorithms, e.g., [CGJ19, GSW19]. In the existing research, block-encodings are unitary operators that block-encode smaller ones.

Quantum states (i.e., density operators) are often used to contain necessary information in quantum algorithms. For this purpose, [LC19] provided a technique to implement a unitary operator that block-encodes a mixed quantum state. However, to the best of our knowledge, there is no known method to do the inverse, that is, to prepare a mixed quantum state whose density operator is block-encoded in a unitary operator. As a result, it could be difficult to extract information from operators that are block-encoded in unitary operators. This motivate us to regard quantum states as block-encodings. As will be seen later in this section, it is convenient to extract information from the operators block-encoded in quantum states as well as to manipulate them.

In this section, we will extend the definition of block-encoding proposed for unitary operators as in [LC19, GSW19, CGJ19] to that for general operators, especially for density operators (i.e., quantum states). Then we show the possibility that information can be stored in and extracted from quantum states as block-encodings. Also, we can manipulate the information block-encoded in quantum states. Here, the “information” block-encoded in quantum states (i.e., density operators) is essentially subnormalized density operators.

2.1 Subnormalized density operators

We will use the language of the conventional block-encoding. Here, we give the definition of block-encoding for ordinary quantum operators as follows.

Definition 2.1 (Block-encoding). *Suppose A is an n -qubit operator, $\alpha, \varepsilon \geq 0$ and $a \in \mathbb{N}$. An $(n+a)$ -qubit operator B is said to be an (α, a, ε) -block-encoding of A , if*

$$\|\alpha_a \langle 0|B|0\rangle_a - A\| \leq \varepsilon.$$

Intuitively, A is represented by the matrix in the upper left corner of B , i.e.

$$B \approx \begin{bmatrix} A/\alpha & * \\ * & * \end{bmatrix}.$$

Here, we write $|0\rangle_a$ to denote $|0\rangle^{\otimes a}$, where the subscript a indicates which (and how many) qubits are involved in the Dirac symbol. For example, if a system consists of two subsystems of a qubits and b qubits and it is in state $|0\rangle^{\otimes(a+b)}$, we can represent it as $|0\rangle_{a+b}$ or $|0\rangle_a |0\rangle_b$.

We are interested in matrices block-encoded in a mixed quantum state (density operator), which are indeed subnormalized density operators.

Definition 2.2 (Subnormalized density operator). *A subnormalized density operator A is a semidefinite operator with $\text{tr}(A) \leq 1$. A (normalized) density operator is a subnormalized density operator with trace 1. An $(n+a+b)$ -qubit unitary operator U is said to prepare an n -qubit subnormalized density operator A , if it prepares the purification $|\rho\rangle = U|0\rangle_{n+a+b}$ of a density operator $\rho = \text{tr}_b(|\rho\rangle\langle\rho|)$, which is a $(1, a, 0)$ -block-encoding of A .*

Given a subnormalized density operator A prepared by a unitary operator U , we usually need to construct another unitary operator \tilde{U} which is a block-encoding of A . This technique was first introduced by [LC19], then generalized for subnormalized density operators by [vAG19, GSLW19].

Lemma 2.1 (Block-encoding of subnormalized density operators [LC19, vAG19, GSLW19]). *Suppose U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit subnormalized density operator A . Then there is a $(2n+a)$ -qubit unitary operator \tilde{U} which is a $(1, n+a, 0)$ -block-encoding of A , using 1 query to U and U^\dagger and $O(a)$ elementary quantum gates.*

2.2 Generalized evolution

It is well-known that after applying a unitary operator U on a mixed quantum state ρ , it will become another state $U\rho U^\dagger$. Here, we extend the basic unitary evolution to the case of subnormalized density operators, which transforms a subnormalized density operator A to BAB^\dagger , where B is block-encoded in a unitary operator.

Lemma 2.2 (Evolution of subnormalized density operators). *Suppose*

1. *U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit subnormalized density operator A , and*
2. *V is an $(n+b)$ -qubit unitary operator which is a $(1, b, 0)$ -block-encoding of B .*

Then $\tilde{U} = (V \otimes I_a)(U \otimes I_b)$ is an $(n+a+b)$ -qubit unitary operator that prepares an n -qubit subnormalized density operator BAB^\dagger .

Proof. Let $a = a_1 + a_2$ such that U prepares an $(n + a_1)$ -qubit density operator ρ , which is a $(1, a_1, 0)$ -block-encoding of A . Suppose

$$A = \sum_j \lambda_j |u_j\rangle \langle u_j|.$$

Then we have

$$|\rho\rangle_{n+a_1+a_2} = \sum_j \sqrt{\lambda_j} |u_j\rangle_n |0\rangle_{a_1} |\psi_j\rangle_{a_2} + |\perp_{a_1}\rangle_{n+a_1+a_2},$$

where $|\psi_j\rangle$ is an orthogonal basis, and $\left\|_{a_1} \langle 0 | \perp_{a_1} \rangle_{n+a_1+a_2} \right\| = 0$. Note that

$$\begin{aligned} \tilde{U} |0\rangle_{n+a+b} &= (V \otimes I_a) |\rho\rangle_{n+a_1+a_2} |0\rangle_b \\ &= \sum_j \sqrt{\lambda_j} |0\rangle_{a_1} |\psi_j\rangle_{a_2} (V |u_j\rangle_n |0\rangle_b) + V |\perp_{a_1}\rangle_{n+a_1+a_2} |0\rangle_b =: |\tilde{\rho}\rangle. \end{aligned}$$

Let $\tilde{\rho} = \text{tr}_{a_2}(|\tilde{\rho}\rangle \langle \tilde{\rho}|)$, then ${}_{a_1+b} \langle 0 | \tilde{\rho} | 0 \rangle_{a_1+b} = \text{tr}_{a_2} ({}_{a_1+b} \langle 0 | \tilde{\rho} \rangle \langle \tilde{\rho} | 0 \rangle_{a_1+b})$, where

$${}_{a_1+b} \langle 0 | \tilde{\rho} \rangle = \sum_j \sqrt{\lambda_j} |\psi_j\rangle_{a_2} \otimes ({}_b \langle 0 | V | 0 \rangle_b) |u_j\rangle_n = \sum_j \sqrt{\lambda_j} |\psi_j\rangle_{a_2} \otimes B |u_j\rangle_n.$$

We have that

$${}_{a_1+b} \langle 0 | \tilde{\rho} | 0 \rangle_{a_1+b} = \sum_j \lambda_j B |u_j\rangle_n \langle u_j| B^\dagger = BAB^\dagger.$$

□

2.3 Polynomial eigenvalue transformation

Now we show how a subnormalized density operator A can be transformed to a new subnormalized density operator $A(P(A))^2$, where $P(x)$ is a polynomial. To this end, we recall the polynomial eigenvalue transformation of unitary operators in [GSLW19], and extend it to the case of preparing subnormalized density operators.

Theorem 2.3 (Polynomial eigenvalue transformation of unitary operators [GSLW19]). *Suppose*

1. U is an $(n + a)$ -qubit unitary operator, which is a $(1, a, 0)$ -block-encoding of an Hermitian operator A .
2. $P \in \mathbb{R}[x]$ ⁷ is a degree- d polynomial such that $\|P\|_{[-1,1]} \leq \frac{1}{2}$ ⁸. Moreover, if P is even or odd, the condition can be relaxed to $\|P\|_{[-1,1]} \leq 1$.

Then for every $\delta > 0$, there is a quantum circuit \tilde{U} ⁹ such that

1. \tilde{U} is a $(1, a + 2, \delta)$ -block-encoding of $P(A)$.

⁷Let $\tilde{\mathbb{R}} \subseteq \mathbb{R}$ be the set of polynomial-time computable real numbers. That is, for every real number $x \in \tilde{\mathbb{R}}$, there is a polynomial-time (classical) Turing machine M such that $|M(1^n) - x| < 2^{-n}$, where $M(1^n)$ denotes the output floating point real number of M on input 1^n . Throughout this paper, we only consider polynomial-time computable real numbers, and for any $S \subseteq \mathbb{R}$, we write S to denote $S \cap \tilde{\mathbb{R}}$ for convenience. Especially, we just write \mathbb{R} for $\tilde{\mathbb{R}}$.

⁸For a function $f : \mathbb{R} \rightarrow \mathbb{C}$ and a set $I \subseteq \mathbb{R}$, we define $\|f\|_I = \sup \{f(x) | x \in I\}$.

⁹Throughout this paper, without explicitly explanation, quantum circuits are uniform. Here, a uniform quantum circuit is a family of quantum circuits whose descriptions can be computed by a polynomial-time (classical) Turing machine.

2. \tilde{U} uses d queries to U and U^\dagger , 1 query to controlled- U and $O((a+1)d)$ elementary quantum gates.
3. A description of \tilde{U} can be computed by a (classical) Turing machine in $O(\text{poly}(d, \log(1/\delta)))$ time.

In the following, combining Theorem 2.3 and Lemma 2.2, we develop a technique of polynomial eigenvalue transformation of subnormalized density operators.

Theorem 2.4 (Polynomial eigenvalue transformation of subnormalized density operators). *Suppose*

1. U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit subnormalized density operator A .
2. $P \in \mathbb{R}[x]$ is a degree- d polynomial such that $\|P\|_{[-1,1]} \leq \frac{1}{2}$. Moreover, if P is even or odd, the condition can be relaxed to $\|P\|_{[-1,1]} \leq 1$.

Then for every $\delta \in (0, 1)$, there is a quantum circuit \tilde{U} such that

1. \tilde{U} prepares an n -qubit subnormalized density operator B , and B is a $(1, 0, \delta)$ -block-encoding of $A(P(A))^2$.
2. \tilde{U} uses $O(d)$ queries to U and U^\dagger , 1 query to controlled- U and controlled- U^\dagger , and $O((n+a)d)$ elementary quantum gates.
3. A description of \tilde{U} can be computed by a (classical) Turing machine in $O(\text{poly}(d, \log(1/\delta)))$ time.

Proof. By Lemma 2.1, there is a quantum circuit V that is a $(1, O(n+a), 0)$ -block-encoding of A , which consists of 1 query to U and U^\dagger and $O(n+a)$ elementary quantum gates. Then by Theorem 2.3, there is a quantum circuit \tilde{V} , which is a $(1, b, \delta)$ -block-encoding of $P(A)$, with d queries to V and V^\dagger , 1 query to controlled- V , and $O((n+a)d)$ elementary quantum gates, where $b = O(n+a)$.

We claim that $\tilde{U} = (\tilde{V} \otimes I_a)(U \otimes I_b)$ is desired. To see this, by Lemma 2.2, \tilde{U} prepares an n -qubit subnormalized density operator $\left({}_b\langle 0|\tilde{V}|0\rangle_b \right) A \left({}_b\langle 0|\tilde{V}|0\rangle_b \right)^\dagger$. On the other hand,

$$\begin{aligned}
\left\| \left({}_b\langle 0|\tilde{V}|0\rangle_b \right) A \left({}_b\langle 0|\tilde{V}|0\rangle_b \right)^\dagger - A(P(A))^2 \right\| &\leq \left\| \left({}_b\langle 0|\tilde{V}|0\rangle_b - P(A) \right) A \left({}_b\langle 0|\tilde{V}|0\rangle_b \right)^\dagger \right\| + \\
&\quad \left\| P(A) A \left(\left({}_b\langle 0|\tilde{V}|0\rangle_b \right)^\dagger - P(A) \right) \right\| \\
&\leq \delta \|A\| (\|P(A)\| + \delta) + \|P(A)\| \|A\| \delta \\
&\leq \frac{5}{2} \delta = \Theta(\delta).
\end{aligned}$$

We conclude that \tilde{U} prepares the purification $|\tilde{\rho}\rangle$ of $\tilde{\rho}$, which is a $(1, O(n+a), \Theta(\delta))$ -block-encoding of $A(P(A))^2$, which yields the proof. \square

By Theorem 2.4, we are able to transform a subnormalized density operator A to $A(f(A))^2$ for a large range of $f(x)$, provided $f(x)$ can be efficiently approximated by a polynomial.

Theorem 2.5 (Eigenvalue transformation of subnormalized density operators). *Suppose*

1. U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit subnormalized density operator A .
2. $f : [-1, 1] \rightarrow \mathbb{R}$ can be approximated by a degree- d polynomial $P \in \mathbb{R}[x]$ such that there are two parameters $\delta, \varepsilon \in (0, \frac{1}{2}]$, it holds that $\|P(x) - f(x)\|_{[\delta, 1]} \leq \varepsilon$ and $\|P\|_{[-1, 1]} \leq \frac{1}{2}$. Moreover, if P is even or odd, the latter condition can be relaxed to $\|P\|_{[-1, 1]} \leq 1$.

Then there is a quantum circuit \tilde{U} such that

1. \tilde{U} prepares an n -qubit subnormalized density operator B , and B is a $\left(1, 0, \Theta\left(\varepsilon + \delta + \|x(f(x))^2\|_{[0, \delta]}\right)\right)$ -block-encoding of $A(f(A))^2$.
2. \tilde{U} uses $O(d)$ queries to U and U^\dagger , 1 query to controlled- U and controlled- U^\dagger , and $O((n+a)d)$ elementary quantum gates.
3. A description of \tilde{U} can be computed by a (classical) Turing machine in $O(\text{poly}(d, \log(1/\delta)))$ time.

Proof. Let \tilde{U} be the quantum circuit obtained by Theorem 2.4, which prepares an n -qubit subnormalized density operator B as a $(1, 0, \delta)$ -block-encoding of $A(P(A))^2$. We analyze the error by the fact that

$$\|x(P(x))^2 - x(f(x))^2\|_{[0, 1]} \leq \Theta\left(\varepsilon + \delta + \|x(f(x))^2\|_{[0, \delta]}\right).$$

We consider two cases.

Case 1. $x \in [\delta, 1]$.

$$|x(P(x))^2 - x(f(x))^2| \leq |x| |P(x) + f(x)| |P(x) - f(x)| \leq (1 + \varepsilon)\varepsilon \leq 2\varepsilon = \Theta(\varepsilon).$$

Case 2. $x \in [0, \delta]$.

$$|x(P(x))^2 - x(f(x))^2| \leq |x(P(x))^2| + |x(f(x))^2| \leq \delta + \|x(f(x))^2\|_{[0, \delta]}.$$

Then we have

$$\begin{aligned} \|B - A(f(A))^2\| &\leq \|B - A(P(A))^2\| + \|A(P(A))^2 - A(f(A))^2\| \\ &\leq \delta + \Theta\left(\varepsilon + \delta + \|x(f(x))^2\|_{[0, \delta]}\right) = \Theta\left(\varepsilon + \delta + \|x(f(x))^2\|_{[0, \delta]}\right). \end{aligned}$$

□

As will be seen, Theorem 2.5 can be used to develop a technique of preparing positive powers of Hermitian operators (see Section 2.4).

2.4 Positive powers

We will use Theorem 2.5 to develop an efficient approach for implementing positive powers of Hermitian matrix A , which removes the dependence on κ that $I/\kappa \leq A \leq I$ as in [CGJ19] (see Lemma 10 of its full version). To this end, we recall some results of polynomial approximations of power functions.

Lemma 2.6 (Polynomial approximation of positive power functions [Gil19, CGJ19]). *Let $\delta, \varepsilon \in (0, \frac{1}{2}]$, $c \in (0, 1)$ and $f(x) = \frac{1}{2}x^c$. Then there is an even/odd degree- $O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$ polynomial ¹⁰ $P \in \mathbb{R}[x]$ such that $\|P(x) - f(x)\|_{[\delta, 1]} \leq \varepsilon$ and $\|P\|_{[-1, 1]} \leq 1$.*

Lemma 2.7 (Polynomial approximation of negative power functions [Gil19, CGJ19, GSLW19]). *Let $\delta, \varepsilon \in (0, \frac{1}{2}]$, $c > 0$ and $f(x) = \frac{\delta^c}{2}x^{-c}$. Then there is an even/odd degree- $O(\frac{c+1}{\delta} \log(\frac{1}{\varepsilon}))$ polynomial $P \in \mathbb{R}[x]$ such that $\|P(x) - f(x)\|_{[\delta, 1]} \leq \varepsilon$ and $\|P\|_{[-1, 1]} \leq 1$.*

First, we develop a method of implementing positive powers of Hermitian matrix A , which is given as block-encoded in a density operator ρ . Here, the purification of ρ can be prepared by a unitary operator U .

Lemma 2.8 (Positive powers block-encoded in density operators). *Suppose*

1. U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit subnormalized density operator A .
2. $\delta, \varepsilon \in (0, \frac{1}{2}]$ and $c \in (0, 1)$.

Then there is a quantum circuit \tilde{U} such that

1. \tilde{U} prepares an n -qubit subnormalized density operator B , and B is a $(4\delta^{c-1}, 0, \Theta(\delta^c + \varepsilon\delta^{c-1}))$ -block-encoding of A^c .
2. \tilde{U} uses $O(d)$ queries to U and U^\dagger , 1 query to controlled- U and controlled- U^\dagger , and $O((n+a)d)$ elementary quantum gates, where $d = O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$.
3. A description of \tilde{U} can be computed by a (classical) Turing machine in $O(\text{poly}(d))$ time.

Proof. Let $f(x) = \frac{\delta^c}{2}x^{-c}$, where $c \in (0, \frac{1}{2})$. Then $x(f(x))^2 = \frac{\delta^{2c}}{4}x^{1-2c}$, and $\|x(f(x))^2\|_{[0, \delta]} \leq \frac{\delta}{4} = \Theta(\delta)$. By Lemma 2.7, we can obtain an even/odd polynomial $P(x)$ of degree $O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$ such that $\|P - f\|_{[\delta, 1]} \leq \varepsilon$ and $\|P\|_{[-1, 1]} \leq 1$. By Theorem 2.5, there is a quantum circuit \tilde{U} , which prepares an n -qubit subnormalized density operator B , which is a $(1, 0, \Theta(\delta + \varepsilon))$ -block-encoding of $A(f(A))^2 = \frac{\delta^{2c}}{4}A^{1-2c}$. In other words, B is a $(4\delta^{-2c}, 0, \Theta(\delta^{1-2c} + \varepsilon\delta^{-2c}))$ -block-encoding of A^{1-2c} . These yield the proof by letting $c' = 1 - 2c$. \square

Next, inspired by the above observation, we extend the result to the case that A is given as block-encoded in a unitary operator. Here, we need to implement a threshold projector. The following lemma is Corollary 16 of [GSLW19].

Lemma 2.9 (Polynomial approximation of threshold projectors [GSLW19]). *Let $\delta, \varepsilon \in (0, \frac{1}{2})$ and $t \in [0, 1]$ such that $0 < t - \delta < t + \delta < 1$. There is an even polynomial $P \in \mathbb{R}[x]$ of degree $O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$ such that*

1. $\|P\|_{[-1, 1]} \leq 1$,
2. $P(x) \in [1 - \varepsilon, 1]$ for $x \in [-t + \delta, t - \delta]$, and

¹⁰In this paper, a degree- d polynomial means a uniform family of (polynomial-time computable) polynomials with parameter d . That is, suppose $P_d(x) = \sum_{k=0}^d a_k x^k$, where a_k is a polynomial-time computable real number for $0 \leq k \leq d$, then there is a polynomial-time classical Turing machine that, on input 1^d , outputs descriptions M_k of a_k for $0 \leq k \leq d$, where M_k is a polynomial-time classical Turing machine that, on input 1^n , output a_k within additive error 2^{-n} .

3. $P(x) \in [0, \varepsilon]$ for $x \in [-1, -t - \delta] \cup [t + \delta, 1]$.

We take some special cases of Lemma 2.9 as follows, which will be often used to design our quantum algorithms.

Corollary 2.10. *Let $\delta, \varepsilon \in (0, \frac{1}{4}]$. Then there is an even degree- $O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$ polynomial $R \in \mathbb{R}[x]$ such that $\|R\|_{[-1,1]} \leq 1$ and*

$$R(x) \in \begin{cases} [1 - \varepsilon, 1] & x \in [-1, -2\delta] \cup [2\delta, 1] \\ [0, \varepsilon] & x \in [-\delta, \delta] \end{cases}.$$

Corollary 2.11. *Let $\delta, \varepsilon \in (0, \frac{1}{4}]$. Then there is an even degree- $O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$ polynomial $R \in \mathbb{R}[x]$ such that $\|R\|_{[-1,1]} \leq 1$ and*

$$R(x) \in \begin{cases} [1 - \varepsilon, 1] & x \in [-1 + 2\delta, 1 - 2\delta] \\ [0, \varepsilon] & x \in [-1, -1 + \delta] \cup [1 - \delta, 1] \end{cases}.$$

We also need the following lemma to multiply block-encoded matrices.

Lemma 2.12 (Product of block-encoded matrices [GSLW19]). *Suppose*

1. U is an $(n + a)$ -qubit unitary operator that is a (α, a, δ) -block-encoding of an n -qubit operator A .
2. V is an $(n + b)$ -qubit unitary operator that is a (β, b, ε) -block-encoding of an n -qubit operator B .

Then there is a quantum circuit \tilde{U} such that

1. \tilde{U} is an $(\alpha\beta, a + b, \alpha\varepsilon + \beta\delta)$ -block-encoding of AB .
2. \tilde{U} uses 1 query to each of U and V .

With the approximation of threshold functions, we are able to implement positive powers of Hermitian matrix A , which is given as block-encoded in a unitary operator.

Lemma 2.13 (Positive powers block-encoded in unitary operators). *Suppose*

1. U is an $(n + a)$ -qubit unitary operator which is a $(1, a, 0)$ -block-encoding of an n -qubit Hermitian operator A .
2. $\delta, \varepsilon \in (0, \frac{1}{4}]$ and $c \in (0, 1)$.

Then there is a quantum circuit W such that

1. W is a $(2, O(a + 1), \Theta(\varepsilon + \delta^c))$ -block-encoding of $|A|^c$.
2. W uses $O(Q)$ queries to U and U^\dagger , $O(1)$ query to controlled- U and $O((a + 1)Q)$ elementary quantum gates, where $Q = O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$.
3. A description of W can be computed by a (classical) Turing machine in $\text{poly}(Q)$ time.

Proof. Let $f(x) = \frac{1}{2}|x|^c$ be an even function and $\delta, \varepsilon \in (0, \frac{1}{4}]$. By Lemma 2.6, there is an even degree- d_P polynomial $P \in \mathbb{R}[x]$, where $d_P = O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$, such that $\|P(x) - f(x)\|_{[\delta, 1]} \leq \varepsilon$, $\|P(x) - f(x)\|_{[-1, -\delta]} \leq \varepsilon$ and $\|P\|_{[-1, 1]} \leq 1$. By Theorem 2.3, for $\delta_U > 0$, there is a quantum circuit \tilde{U} such that

1. \tilde{U} is a $(1, a+2, 0)$ -block-encoding of B , and B is a $(1, 0, \delta_U)$ -block-encoding of $P(A)$.
2. \tilde{U} uses d_P queries to U and U^\dagger , 1 query to controlled- U and $O((a+1)d_P)$ elementary quantum gates.
3. A description of \tilde{U} can be computed by a (classical) Turing machine in $\text{poly}(d_P, \log(1/\delta_U))$ time.

Let $R \in \mathbb{R}[x]$ be the even degree- d_R polynomial in Corollary 2.10, where $d_R = O(\frac{1}{\delta} \log(\frac{1}{\varepsilon}))$, such that $\|R\|_{[-1, 1]} \leq 1$ and

$$R(x) \in \begin{cases} [1 - \varepsilon, 1] & x \in [-1, -2\delta] \cup [2\delta, 1] \\ [0, \varepsilon] & x \in [-\delta, \delta] \end{cases}.$$

By Theorem 2.3, for $\delta_V > 0$, there is a quantum circuit \tilde{V} such that

1. \tilde{V} is a $(1, a+2, 0)$ -block-encoding of C , and C is a $(1, 0, \delta_V)$ -block-encoding of $R(A)$.
2. \tilde{V} uses d_R queries to U and U^\dagger , 1 query to controlled- U and $O((a+1)d_R)$ elementary quantum gates.
3. A description of \tilde{V} can be computed by a (classical) Turing machine in $\text{poly}(d_R, \log(1/\delta_V))$ time.

By Lemma 2.12, using one query to each of \tilde{U} and \tilde{V} , we can obtain a quantum circuit W , which is a $(1, 2a+4, 0)$ -block-encoding of BC . In the following, we will show that $\|BC - f(A)\| \leq \Theta(\varepsilon + \delta^c)$. We note that

$$\|P(x)R(x) - f(x)\|_{[0, 1]} \leq \Theta(\varepsilon + \delta^c).$$

This is seen by the following three cases:

1. $|x| > 2\delta$. We have $|P(x)R(x) - f(x)| \leq |(P(x) - f(x))R(x)| + |f(x)(R(x) - 1)| \leq \Theta(\varepsilon)$.
2. $|x| < \delta$. We have $|P(x)R(x) - f(x)| \leq |P(x)| |R(x)| + |f(x)| \leq \Theta(\varepsilon + \delta^c)$.
3. $\delta \leq |x| \leq 2\delta$. We have $|P(x)R(x) - f(x)| \leq |(P(x) - f(x))R(x)| + |f(x)| |R(x) - 1| \leq \Theta(\varepsilon + \delta^c)$.

Note that A is Hermitian, we have $\|P(A)R(A) - f(A)\| \leq \Theta(\varepsilon + \delta^c)$. Finally,

$$\|BC - f(A)\| \leq \|BC - P(A)R(A)\| + \|P(A)R(A) - f(A)\| \leq \Theta(\delta_U + \delta_V + \varepsilon + \delta^c).$$

These conclude that W is a $(1, 2a+4, \Theta(\varepsilon + \delta^c))$ -block-encoding of $f(A)$ by setting $\delta_U = \delta_V = \varepsilon$, and therefore a $(2, O(n+a), \Theta(\varepsilon + \delta^c))$ -block-encoding of $|A|^c$. \square

By setting $\kappa = \frac{1}{\delta}$, Lemma 2.13 reproduces the result of [CGJ19] (see Lemma 10 of its full version). The strength of Lemma 2.13 is to allow implement positive powers of A , regardless of whether the condition $I/\kappa \leq A \leq I$ holds.

2.5 Trace estimation

In this subsection, we will provide a method of estimating the trace of an Hermitian matrix which is block-encoded in a density operator. Before that, we recall the quantum amplitude estimation [BHMT02].

Theorem 2.14 (Quantum amplitude estimation, [BHMT02]). *Suppose U is an $(a+b)$ -qubit unitary operator such that*

$$U |0\rangle_{a+b} = \sqrt{p} |0\rangle_a |\phi_0\rangle_b + \sqrt{1-p} |1\rangle_a |\phi_1\rangle_b,$$

where $|\phi_0\rangle$ and $|\phi_1\rangle$ are normalized (pure) quantum states and $p \in [0, 1]$. There is a quantum algorithm that outputs $\tilde{p} \in [0, 1]$ such that

$$|\tilde{p} - p| \leq \frac{2\pi\sqrt{p(1-p)}}{M} + \frac{\pi^2}{M^2}$$

with probability $\geq \frac{8}{\pi^2}$, using $O(M)$ queries to U and U^\dagger .

If we know an upper bound B of p , then we can take $M = \left\lceil 2\pi \left(\frac{2\sqrt{B}}{\varepsilon} + \frac{1}{\sqrt{\varepsilon}} \right) \right\rceil = \Theta \left(\frac{\sqrt{B}}{\varepsilon} + \frac{1}{\sqrt{\varepsilon}} \right)$ to guarantee that $|\tilde{p} - p| \leq \varepsilon$.

Based on quantum amplitude estimation, we develop the trace estimation of subnormalized density operators as shown below, which will be useful to design quantum algorithms, see Section 3 and Section 4.

Lemma 2.15 (Trace estimation of subnormalized density operators). *Suppose U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit subnormalized density operator A , and $B > 0$ is a known constant that $\text{tr}(A) \leq B$. For every $\varepsilon > 0$, there is a quantum algorithm that estimates $\text{tr}(A)$ within additive error ε with $O \left(\frac{\sqrt{B}}{\varepsilon} + \frac{1}{\sqrt{\varepsilon}} \right)$ queries to U and U^\dagger .*

Proof. Let $a = a_1 + a_2$ such that U prepares an $(n + a_1)$ -qubit density operator ρ , which is a $(1, a_1, 0)$ -block-encoding of A . Suppose

$$A = \sum_j \lambda_j |u_j\rangle \langle u_j|.$$

Then we have

$$U |0\rangle_{n+a_1+a_2} = |\rho\rangle_{n+a_1+a_2} = \sum_j \sqrt{\lambda_j} |u_j\rangle_n |0\rangle_{a_1} |\psi_j\rangle_{a_2} + |\perp_{a_1}\rangle_{n+a_1+a_2}$$

where $|\psi_j\rangle$ is an orthogonal basis, and $\left\| \langle 0 | \perp_{a_1} \rangle_{n+a_1+a_2} \right\| = 0$. Moreover, we have

$$U |0\rangle_{n+a_1+a_2} = \sqrt{p} |0\rangle_{a_1} |\phi_0\rangle_{n+a_2} + \sqrt{1-p} |1\rangle_{a_1} |\phi_1\rangle_{n+a_2}$$

for some (pure) quantum states $|\phi_0\rangle$ and $|\phi_1\rangle$, where $p = \text{tr}(A)$.

If we know an upper bound B of $\text{tr}(A)$, then let $M = \left\lceil 2\pi \left(\frac{2\sqrt{B}}{\varepsilon} + \frac{1}{\sqrt{\varepsilon}} \right) \right\rceil = \Theta \left(\frac{\sqrt{B}}{\varepsilon} + \frac{1}{\sqrt{\varepsilon}} \right)$, and by Theorem 2.14, we can compute \tilde{p} such that

$$|\tilde{p} - p| \leq \frac{2\pi\sqrt{p(1-p)}}{M} + \frac{\pi^2}{M^2} \leq \varepsilon$$

with success probability $\geq \frac{8}{\pi^2}$, using M queries to U and U^\dagger . □

2.6 Linear combinations

We will provide a technique (Lemma 2.17) that prepares a linear combination of subnormalized density operators, which is a natural analog of Linear-Combination-of-Unitaries (LCU) algorithm through a series of work [SOG⁺02, CW12, Kot14, BCC⁺15, BCK15, CKS17, GSLW19].

Before stating our linear combination result of subnormalized density operators, we introduce a technique that embeds a density operator in a larger space.

Lemma 2.16. *Suppose U is an $(n + a)$ -qubit unitary operator that prepares an n -qubit density operator ρ . For every $b \geq 0$, there is an $(n + a + b)$ -qubit unitary operator $U^{(b)} = U \otimes I_b$ such that*

1. $U^{(b)}$ prepares an $(n + b)$ -qubit density operator $\rho^{(b)}$, and $\rho^{(b)}$ is a $(1, b, 0)$ -block-encoding of ρ .
2. $U^{(b)}$ uses 1 query to U .

Proof. Let $|\psi\rangle_{n+a} = U |0\rangle_{n+a}$ and then $\rho_n = \text{tr}_a(|\psi\rangle_{n+a} \langle\psi|)$. Let $U^{(b)} = U \otimes I_b$ and $|\psi^{(b)}\rangle_{n+a+b} = U^{(b)} |0\rangle_{n+a+b} = |\psi\rangle_{n+a} |0\rangle_b$. We have

$$\rho^{(b)} = \text{tr}_a \left(|\psi^{(b)}\rangle_{n+a+b} \langle\psi^{(b)}| \right) = \text{tr}_a (|\psi\rangle_{n+a} \langle\psi| \otimes |0\rangle_b \langle 0|) = \rho_n \otimes |0\rangle_b \langle 0|.$$

The proof is completed by noting that ${}_b\langle 0|\rho^{(b)}|0\rangle_b = \rho_n$. \square

Now we are ready to show the technique to prepare a linear combination of subnormalized density operators. The basic idea is to prepare a linear combination of (normalized) density operators, but a careful qubit alignment is needed with the help of Lemma 2.16.

Lemma 2.17 (Linear combination of subnormalized density operators). *Suppose*

1. V is an m -qubit unitary operator such that $V |0\rangle = \sum_{k \in [2^m]} \sqrt{\alpha_k} |k\rangle$ ¹¹.
2. For every $k \in [2^m]$, U_k is an $(n + a_k + b_k)$ -qubit unitary operator that prepares an $(n + a_k)$ -qubit density operator ρ_k , and ρ_k is a $(1, a_k, 0)$ -block-encoding of an n -qubit subnormalized density operator A_k .

Let $a = \max_{k \in [2^m]} \{a_k\}$ and $b = \max_{k \in [2^m]} \{b_k\}$. Then there is an $(m + n + a + b)$ -qubit unitary operator U such that

1. $U (V \otimes I_{n+a+b})$ prepares an n -qubit subnormalized density operator

$$A = \sum_{k \in [2^m]} \alpha_k A_k.$$

2. U uses 1 query to each U_k for $k \in [2^m]$.

Proof. Let $a'_k = a - a_k$, $b'_k = b - b_k$, and

$$U = \sum_{k \in [2^m]} |k\rangle \langle k| \otimes U_k^{(a'_k + b'_k)}$$

be an $(m + n + a + b)$ -qubit unitary operator, where $U^{(b)} = U \otimes I_b$ is defined as in Lemma 2.16. Here, $U_k^{(a'_k + b'_k)}$ acts on $n + a + b$ qubits. To be precise, if we split the $n + a + b$ qubits into three

¹¹Here, we use the notation $[n] = \{0, 1, 2, \dots, n - 1\}$.

parts: (i) n qubits, (ii) a qubits and (iii) b qubits, then $U_k^{(a'_k+b'_k)}$ uses 1 query to U_k which acts on: (i) the whole n qubits, (ii) the first a_k qubits and (iii) the first b_k qubits.

Let $|\psi_k\rangle_{n+a_k+b_k} = U_k |0\rangle_{n+a_k+b_k}$. Then we note that

$$\begin{aligned} |\psi\rangle &= U (V \otimes I_{n+a+b}) |0\rangle_m |0\rangle_n |0\rangle_a |0\rangle_b \\ &= U \sum_{k \in [2^m]} \sqrt{\alpha_k} |k\rangle_m |0\rangle_n |0\rangle_a |0\rangle_b \\ &= \sum_{k \in [2^m]} \sqrt{\alpha_k} |k\rangle_m \left(U_k^{(a'_k+b'_k)} |0\rangle_n |0\rangle_a |0\rangle_b \right) \\ &= \sum_{k \in [2^m]} \sqrt{\alpha_k} |k\rangle_m |\psi_k\rangle_{n+a_k+b_k} |0\rangle_{a'_k} |0\rangle_{b'_k}, \end{aligned}$$

and

$$\begin{aligned} \rho &= \text{tr}_{m+b} (|\psi\rangle \langle \psi|) = \sum_{k \in [2^m]} \alpha_k \text{tr}_b \left(|\psi_k\rangle_{n+a_k+b_k} \langle \psi_k| \otimes |0\rangle_{a'_k+b'_k} \langle 0| \right) \\ &= \sum_{k \in [2^m]} \alpha_k \text{tr}_{b_k} \left(|\psi_k\rangle_{n+a_k+b_k} \langle \psi_k| \right) \otimes |0\rangle_{a'_k} \langle 0| \\ &= \sum_{k \in [2^m]} \alpha_k (\rho_k)_{n+a_k} \otimes |0\rangle_{a'_k} \langle 0| \\ &= \sum_{k \in [2^m]} \alpha_k \left(\rho_k^{(a'_k)} \right)_{n+a}, \end{aligned}$$

where $\rho^{(b)} = \rho \otimes |0\rangle_b \langle 0|$ is defined as in Lemma 2.16. To see that ρ is a $(1, a, 0)$ -block-encoding of $A = \sum_{k \in [2^m]} A_k$, we note that

$${}_a \langle 0 | \rho | 0 \rangle_a = \sum_{k \in [2^m]} \alpha_k {}_{a_k} \langle 0 | (\rho_k)_{n+a_k} | 0 \rangle_{a_k} = \sum_{k \in [2^m]} \alpha_k A_k = A.$$

Therefore, $U (V \otimes I_a \otimes I_b)$ prepares a subnormalized density operator A . \square

As will be also used to design quantum algorithms in this paper, we provide the LCU algorithm for comparison. Here, we use the notion as in the full version of [GSLW19].

Definition 2.3 (State preparation pair). *Let $y \in \mathbb{C}^m$ with $\|y\|_1 \leq \beta$, and $\varepsilon \geq 0$. A pair of unitary operator (P_L, P_R) is called a (β, b, ε) -state-preparation-pair if $P_L |0\rangle_b = \sum_{j \in [2^b]} c_j |j\rangle$ and $P_R |0\rangle_b = \sum_{j \in [2^b]} d_j |j\rangle$ such that $\sum_{j \in [m]} |\beta c_j^* d_j - y_j| \leq \varepsilon$ and $c_j^* d_j = 0$ for all $m \leq j < 2^b$.*

Theorem 2.18 (Linear combination of unitary operators [GSLW19]). *Suppose*

1. $y \in \mathbb{C}^m$ with $\|y\|_1 \leq \beta$, and (P_L, P_R) is a $(\beta, b, \varepsilon_1)$ -state-preparation-pair for y .
2. For every $k \in [m]$, U_k is an $(n+a)$ -qubit unitary operator that is an (α, a, ε) -block-encoding of an n -qubit operator A_k .

Then there is an $(n+a+b)$ -qubit quantum circuit \tilde{U} such that

1. W is a $(\alpha\beta, a+b, \alpha\varepsilon_1 + \alpha\beta\varepsilon_2)$ -block-encoding of $A = \sum_{k \in [m]} y_k A_k$.
2. W uses 1 query to each of P_L^\dagger , P_R and (controlled-) U_k for $k \in [m]$, and $O(b^2)$ elementary quantum gates.

2.7 Eigenvalue threshold projector

In this subsection, we show how to block-encode an eigenvalue threshold projector $\Pi_{\text{supp}(A)}$ of a subnormalized density operator A in another. We note that [vAG19] also provided a technique for block-encoding eigenvalue threshold projectors in subnormalized density operators. The major difference is that our approach does not have any further requirements on the subnormalized density operator A , while [vAG19] requires that $A \geq q\Pi$ for some projector Π and the value of $q > 0$ is known in advance.

First, we introduce the notion of truncated support. Let $\delta > 0$ and A be an Hermitian operator with spectral decomposition $A = \sum_j \lambda_j |\psi_j\rangle \langle \psi_j|$. The δ -support of A is

$$\text{supp}_\delta(A) = \text{span}\{|\psi_j\rangle : |\lambda_j| > \delta\}.$$

Note that $\text{supp}_\delta(A) \subseteq \text{supp}_0(A) = \text{supp}(A)$. Here, we write Π_S to denote the projector onto a subspace S .

Lemma 2.19 (Eigenvalue threshold projector). *Suppose*

1. U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit subnormalized density operator A .
2. $\delta, \epsilon \in (0, \frac{1}{10}]$ and $32\epsilon^2 \leq \delta$.

For every $\delta' > 0$, there is a quantum circuit \tilde{U} such that

1. \tilde{U} prepares an n -qubit subnormalized density operator, which is a $(1, 0, \delta')$ -block-encoding of B such that

$$\left(\frac{\delta}{4}(1 - 2\epsilon) - \delta^{1/2}\epsilon\right) \Pi_{\text{supp}_{2\delta}(A)} \leq B \leq \left(\frac{\delta}{4} + \epsilon^2 + \delta^{1/2}\epsilon\right) \Pi_{\text{supp}(A)}.$$

2. \tilde{U} uses $O(d)$ queries to U and U^\dagger , 1 query to controlled- U and $O((n+a)d)$ elementary quantum gates, where $d = O\left(\frac{1}{\delta} \log\left(\frac{1}{\epsilon}\right)\right)$.
3. A description of \tilde{U} can be computed by a (classical) Turing machine in $\text{poly}(d, \log(1/\delta'))$ time.

Proof. Let $f(x) = \frac{\delta^{1/2}}{2}x^{-1/2}$, and by Lemma 2.7, there is a degree- $O\left(\frac{1}{\delta} \log\left(\frac{1}{\epsilon}\right)\right)$ even polynomial $P \in \mathbb{R}[x]$ such that $\|P - f\|_{[\delta, 1]} \leq \epsilon$ and $\|P\|_{[-1, 1]} \leq 1$. By Corollary 2.10, there is a degree- $O\left(\frac{1}{\delta} \log\left(\frac{1}{\epsilon}\right)\right)$ even polynomial $R \in \mathbb{R}[x]$ such that $\|R\|_{[-1, 1]} \leq 1$ and

$$R(x) \in \begin{cases} [1 - \epsilon, 1] & x \in [-1, -2\delta] \cup [2\delta, 1] \\ [0, \epsilon] & x \in [-\delta, \delta] \end{cases}.$$

Note that $Q = PR \in \mathbb{R}[x]$ is a degree- d even polynomial, where $d = O\left(\frac{1}{\delta} \log\left(\frac{1}{\epsilon}\right)\right)$. By Theorem 2.3, for $\delta_Q > 0$, there is a quantum circuit U_Q such that

1. U_Q is a $(1, O(n+a), 0)$ -block-encoding of A_1 , and A_1 is a $(1, 0, \delta_Q)$ -block-encoding of $Q(A)$.
2. U_Q uses d queries to U and U^\dagger , 1 query to controlled- U and $O((n+a)d)$ elementary quantum gates.
3. A description of U_Q can be computed by a (classical) Turing machine in $\text{poly}(d, \log(1/\delta_Q))$ time.

By Lemma 2.2, using 1 query to each of U_Q and U , we obtain a unitary operator \tilde{U} that prepares $A_1 A A_1^\dagger$. We note that

$$\left\| A_1 A A_1^\dagger - A(Q(A))^2 \right\| \leq \left\| A_1 A A_1^\dagger - Q(A) A A_1^\dagger \right\| + \left\| Q(A) A A_1^\dagger - Q(A) A Q(A) \right\| \leq 2\delta_Q.$$

Moreover, $A_1 A A_1^\dagger$ can be regarded as a (scaled) projector. To see this, let $\mathbb{1}_S$ be the indicator function that

$$\mathbb{1}_S(x) = \begin{cases} 1 & x \in S \\ 0 & \text{otherwise} \end{cases}.$$

Then $\Pi_{\text{supp}_\delta(A)} = \mathbb{1}_{[\delta, 1]}(A)$. We note that if $32\varepsilon^2 \leq \delta$, then

$$\left(\frac{\delta}{4}(1 - 2\varepsilon) - \delta^{1/2}\varepsilon \right) \Pi_{\text{supp}_{2\delta}(A)} \leq A(Q(A))^2 \leq \left(\frac{\delta}{4} + \varepsilon^2 + \delta^{1/2}\varepsilon \right) \Pi_{\text{supp}(A)}. \quad (3)$$

We need to show that

$$\left(\frac{\delta}{4}(1 - 2\varepsilon) - \delta^{1/2}\varepsilon \right) \mathbb{1}_{[2\delta, 1]}(x) \leq x(Q(x))^2 \leq \left(\frac{\delta}{4} + \varepsilon^2 + \delta^{1/2}\varepsilon \right) \mathbb{1}_{(0, 1]}(x)$$

for every $x \in [0, 1]$. This is seen by the following four cases.

1. $x = 0$. This case is trivial as each hand side is equal to 0.
2. $x \in (0, \delta]$. We have $0 \leq x(Q(x))^2 \leq x(R(x))^2 \leq x\varepsilon^2 \leq \delta\varepsilon^2$.
3. $x \in (\delta, 2\delta]$. We have

$$0 \leq x(Q(x))^2 \leq x(P(x))^2 \leq x(f(x) + \varepsilon)^2 = x(f(x))^2 + x\varepsilon^2 + 2xf(x)\varepsilon \leq \frac{\delta}{4} + \varepsilon^2 + \delta^{1/2}\varepsilon.$$

4. $x \in (2\delta, 1]$. The right hand side is $x(Q(x))^2 \leq \frac{\delta}{4} + \varepsilon^2 + \delta^{1/2}\varepsilon$ is similar to Case 3. The left hand side is as follows.

$$\begin{aligned} x(Q(x))^2 &\geq x(P(x))^2(1 - \varepsilon)^2 \\ &\geq x(f(x) - \varepsilon)^2(1 - \varepsilon)^2 \\ &\geq x((f(x))^2 - 2f(x)\varepsilon)(1 - 2\varepsilon) \\ &= \left(\frac{\delta}{4} - \delta^{1/2}x^{1/2}\varepsilon \right) (1 - 2\varepsilon) \\ &\geq \frac{\delta}{4}(1 - 2\varepsilon) - \delta^{1/2}\varepsilon. \end{aligned}$$

Therefore, we conclude that Eq. (3) holds. We claim the lemma by setting $B = A(Q(A))^2$ and $\delta' = 2\delta_Q$. \square

3 Quantum Entropies

In the Introduction, we have already introduced several quantum entropies such as the von Neumann entropy, quantum Rényi entropy and quantum Tsallis entropy. In addition to this, the quantum

Min entropy $S^{\min}(\rho)$ and the quantum Max (Hartley) entropy $S^{\max}(\rho)$ are defined as limits of Rényi entropies by

$$S^{\min}(\rho) = S_{\infty}^R(\rho) = \lim_{\alpha \rightarrow \infty} S_{\alpha}^R(\rho) = -\ln(\|\rho\|),$$

$$S^{\max}(\rho) = S_0^R(\rho) = \lim_{\alpha \rightarrow 0} S_{\alpha}^R(\rho) = \ln(\text{rank}(\rho)).$$

The unified entropy [HY06] is defined by

$$S_{\alpha}^s(\rho) = \frac{1}{(1-\alpha)s} ((\text{tr}(\rho^{\alpha}))^s - 1)$$

for $\alpha \in (0, 1) \cup (1, +\infty)$ and $s \neq 0$, which includes the von Neumann entropy $S(\rho) = \lim_{\alpha \rightarrow 1} S_{\alpha}^s(\rho)$, the Rényi entropy $S_{\alpha}^R(\rho) = \lim_{s \rightarrow 0} S_{\alpha}^s(\rho)$ and the Tsallis entropy $S_{\alpha}^T(\rho) = S_{\alpha}^1(\rho)$.

In this section, we will propose a series of quantum algorithms for computing several quantum entropies. Section 3.1 provides a quantum algorithm for computing the von Neumann entropy. Section 3.2 is for the Max entropy. Section 3.3 is for the quantum Rényi and Tsallis entropies.

3.1 Von Neumann Entropy

The von Neumann entropy is one of the most important quantum information quantities. As mentioned above, both quantum algorithms for estimating von Neumann entropy provided by [AISW19] and [GL20] have time complexity exponential in the number $n = \log_2(N)$ of qubits of the quantum state. Here, we provide a different approach that exponentially improves the dependence on n given that the density operator of the mixed quantum state is low-rank. Our key technique used here is different from that of [GL20], where they approximated a function $\propto -\ln(x)$ and constructed a unitary operator that is a block-encoding of $S(\rho)$, while we approximate a function $\propto \sqrt{-\ln(x)}$ and prepare a density operator that is a block-encoding of $S(\rho)$.

Theorem 3.1. *Suppose*

1. U_{ρ} is an $(n + n_{\rho})$ -qubit unitary operator that prepares an n -qubit density operator ρ with $\text{rank}(\rho) \leq r$.
2. n_{ρ} is a polynomial in n ¹².

There is a quantum algorithm that computes the von Neumann entropy $S(\rho)$ within additive error ε using $\tilde{O}(\frac{n^2}{\varepsilon^2})$ queries to U_{ρ} and $\tilde{O}(\frac{r^2}{\varepsilon^2} \text{poly}(n))$ elementary quantum gates.

Before the proof of Theorem 3.1, we need the following method of approximating functions by polynomials based on Taylor series.

Lemma 3.2 (Corollary 66 of the full version of [GSLW19]). *Let $x_0 \in [-1, 1]$, $r \in (0, 2]$, $\delta \in (0, r]$ and $f : [x_0 - r - \delta, x_0 + r + \delta] \rightarrow \mathbb{C}$ such that $f(x_0 + x) = \sum_{k=0}^{\infty} a_k x^k$ for all $x \in [-r - \delta, r + \delta]$. Suppose $B > 0$ and $\sum_{k=0}^{\infty} |a_k| (r + \delta)^k \leq B$. Let $\varepsilon \in (0, \frac{1}{2B}]$, then there is an efficient computable polynomial $P \in \mathbb{C}[x]$ of degree $O(\frac{1}{\delta} \log(\frac{B}{\varepsilon}))$ such that*

$$\|f(x) - P(x)\|_{[x_0 - r, x_0 + r]} \leq \varepsilon,$$

$$\|P\|_{[-1, 1]} \leq \varepsilon + \|f\|_{[x_0 - r - \delta/2, x_0 + r + \delta/2]} \leq \varepsilon + B,$$

$$\|P\|_{[-1, 1] \setminus [x_0 - r - \delta/2, x_0 + r + \delta/2]} \leq \varepsilon.$$

¹²Theoretically, any n -qubit mixed quantum state has a purification with at most n ancilla qubits, so it is sufficient to assume that $n_{\rho} \leq n$. Here, we just assume that $n_{\rho} = \text{poly}(n)$ for convenience.

By Lemma 3.2, we are able to give an approximation of scaled $\sqrt{-\ln(x)}$ as follows.

Lemma 3.3. *For every $\delta', \varepsilon \in (0, \frac{1}{4}]$, there is an efficient computable polynomial $P \in \mathbb{R}[x]$ of degree $O(\frac{1}{\delta'} \log(\frac{1}{\delta'\varepsilon}))$ such that*

$$\left\| P(x) - \frac{\sqrt{-\ln(x)}}{2\sqrt{-\ln(\delta')}} \right\|_{[\delta', 1-\delta']} \leq \varepsilon, \\ \|P\|_{[-1,1]} \leq 1.$$

Proof. Let $f(x) = \frac{\sqrt{-\ln(x)}}{2\sqrt{-\ln(\delta')}}$ whose Taylor series expanded around $x_0 = \frac{1}{2}$ is $f(x_0 + x) = \sum_{k=0}^{\infty} a_k x^k$. We note that $f(x)$ is holomorphic in $\mathbb{C} \setminus (-\infty, 0] \setminus [1, \infty)$ if we choose the definitions of $\ln(\cdot)$ and $\sqrt{\cdot}$ to be their principle branches in complex analysis. Thus the radius of convergence of the Taylor series of $f(x)$ expanded around $x_0 = \frac{1}{2}$ is $R = \frac{1}{2}$. We have

$$\limsup_{k \rightarrow \infty} \sqrt[k]{|a_k|} = \frac{1}{R} = 2.$$

Therefore, there exists $k_0 \in \mathbb{N}$ such that for every $k > k_0$, it holds that $\sqrt[k]{|a_k|} < 2 + \delta'$. Now we set $r = \frac{1}{2} - \delta'$ and $\delta = \delta'/2$, and we have

$$\sum_{k=0}^{\infty} |a_k| (r + \delta)^k \leq \sum_{k=0}^{\infty} (2 + \delta')^k \left(\frac{1}{2} - \frac{\delta'}{2} \right)^k + O(1) \leq \sum_{k=0}^{\infty} \left(1 - \frac{\delta'}{2} \right)^k + O(1) = \frac{2}{\delta'} + O(1) =: B.$$

Now applying Lemma 3.2, there is an efficiently computable polynomial $P \in \mathbb{C}[x]$ of degree $O(\frac{1}{\delta} \log(\frac{B}{\varepsilon})) = O(\frac{1}{\delta'} \log(\frac{1}{\delta'\varepsilon}))$ such that

$$\|f(x) - P(x)\|_{[\delta', 1-\delta']} \leq \varepsilon, \\ \|P(x)\|_{[-1,1]} \leq \varepsilon + \|f\|_{[3\delta'/4, 1-3\delta'/4]}, \\ \|P\|_{[-1,1] \setminus [3\delta'/4, 1-3\delta'/4]} \leq \varepsilon.$$

Here, we note that

$$\|f\|_{[3\delta'/4, 1-3\delta'/4]} = f\left(\frac{3\delta'}{4}\right) \leq \frac{3}{4}$$

and we obtain $\|P\|_{[-1,1]} \leq 1$ combining the three cases above. Finally, since we are only interested in the real part of $P(x)$ and x is always a real number, just selecting the real part of the coefficients of $P(x)$ will obtain a desired polynomial with real coefficients. \square

Now we are ready to give the proof of Theorem 3.1.

Proof of Theorem 3.1. Let $\delta, \varepsilon_1 \in (0, \frac{1}{4})$ and

$$f(x) = \frac{\sqrt{-\ln(x)}}{2\sqrt{-\ln(\delta)}}.$$

By Lemma 3.3, there is an even polynomial $P(x)$ of degree $O\left(\frac{1}{\delta} \log\left(\frac{1}{\delta\varepsilon_1}\right)\right)$ such that $\|P\|_{[-1,1]} \leq 1$ and $\|P(x) - f(x)\|_{[\delta, 1-\delta]} \leq \varepsilon_1$. By Corollary 2.11, there is an even polynomial $R(x)$ of degree $O\left(\frac{1}{\delta} \log\left(\frac{1}{\varepsilon_1}\right)\right)$ such that $\|R\|_{[-1,1]} \leq 1$ and

$$R(x) \in \begin{cases} [1 - \varepsilon_1, 1] & x \in [-1 + 2\delta, 1 - 2\delta] \\ [0, \varepsilon_1] & x \in [-1, -1 + \delta] \cup [1 - \delta, 1] \end{cases}.$$

We note that $P(x)R(x)$ is an even polynomial of degree $d = O\left(\frac{1}{\delta} \log\left(\frac{1}{\delta\varepsilon_1}\right)\right)$. Let $\delta_1 \in (0, 1)$ and by Lemma 2.4, there is a quantum circuit \tilde{U} such that

1. \tilde{U} prepares an n -qubit subnormalized density operator A_1 , and A_1 is a $(1, 0, \delta_1)$ -block-encoding of $\rho(P(\rho)R(\rho))^2$.
2. \tilde{U} uses $O(d)$ queries to U_ρ and U_ρ^\dagger , 1 query to controlled- U and controlled- U_ρ^\dagger , and $O((n+a)d)$ elementary quantum gates.
3. A description of \tilde{U} can be computed by a (classical) Turing machine in $O(\text{poly}(d, \log(1/\delta_1)))$ time.

Now we are going to show that

$$\|x(P(x)R(x))^2 - x(f(x))^2\|_{[0,1]} \leq \Theta\left(\varepsilon_1 + \frac{\delta}{\ln\left(\frac{1}{\delta}\right)}\right),$$

which immediately yields

$$\|\rho(P(\rho)R(\rho))^2 - \rho(f(\rho))^2\| \leq \Theta\left(\varepsilon_1 + \frac{\delta}{\ln\left(\frac{1}{\delta}\right)}\right).$$

We consider four cases.

1. $x \in [0, \delta]$. In this case, $|x(P(x)R(x))^2 - x(f(x))^2| \leq |x(P(x)R(x))^2| + |x(f(x))^2| \leq \delta + \delta(f(\delta))^2 = \delta + \delta/4 = \Theta(\delta)$.
2. $x \in [\delta, 1 - 2\delta]$. In this case,

$$\begin{aligned} |x(P(x)R(x))^2 - x(f(x))^2| &\leq |x| (|(P(x))^2 - (f(x))^2| |(R(x))^2| + |(R(x))^2 - 1| |(f(x))^2|) \\ &\leq 2|P(x) - f(x)| + 2|R(x) - 1| \leq \varepsilon_1 + \varepsilon_1 = \Theta(\varepsilon_1). \end{aligned}$$

3. $x \in [1 - 2\delta, 1 - \delta]$. We note that $-x \ln(x) < 1 - x$ for every $x \in (0, 1)$. In this case,

$$\begin{aligned} |x(P(x)R(x))^2 - x(f(x))^2| &\leq |x(P(x)R(x))^2| + |x(f(x))^2| \leq |x(P(x))^2| + |x(f(x))^2| \\ &\leq 2|x(f(x))^2| + |x(P(x))^2 - x(f(x))^2| \\ &\leq 2\frac{-x \ln(x)}{-4 \ln(\delta)} + 2|P(x) - f(x)| \\ &\leq \frac{1 - x}{-2 \ln(\delta)} + 2\varepsilon_1 \leq \frac{2\delta}{-2 \ln(\delta)} + 2\varepsilon_1 = \Theta\left(\frac{\delta}{\ln\left(\frac{1}{\delta}\right)} + \varepsilon_1\right). \end{aligned}$$

4. $x \in [1 - \delta, 1]$. In this case,

$$\begin{aligned} |x(P(x)R(x))^2 - x(f(x))^2| &\leq |x(P(x)R(x))^2| + |x(f(x))^2| \leq |(R(x))^2| + |x(f(x))^2| \\ &\leq \Theta\left(\varepsilon_1 + \frac{\delta}{\ln\left(\frac{1}{\delta}\right)}\right). \end{aligned}$$

We note that $\text{tr}(\rho(f(\rho))^2) = \frac{S(\rho)}{4\ln(\frac{1}{\delta})}$. Based on this, we have

$$\left| 4\ln\left(\frac{1}{\delta}\right) \text{tr}(A_1) - S(\rho) \right| \leq \Theta\left(r\left((\varepsilon_1 + \delta_1)\ln\left(\frac{1}{\delta}\right) + \delta\right)\right).$$

On the other hand, $\text{tr}(A_1)$ has an upper bound that

$$\text{tr}(A_1) \leq \frac{S(\rho)}{4\ln(\frac{1}{\delta})} + O(1) \leq \frac{\ln(r)}{4\ln(\frac{1}{\delta})} + O(1) =: B.$$

Let $\varepsilon_2 \in (0, 1)$. By Lemma 2.15, we can compute \tilde{p} such that $|\text{tr}(A_1) - \tilde{p}| \leq \varepsilon_2$ with $O\left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)$ queries to \tilde{U} and \tilde{U}^\dagger .

Finally, we choose $4\ln(\frac{1}{\delta})\tilde{p}$ to be the approximation of $S(\rho)$. The error is bounded by

$$\left| 4\ln\left(\frac{1}{\delta}\right) \tilde{p} - S(\rho) \right| \leq \Theta\left(r\left((\varepsilon_1 + \delta_1)\ln\left(\frac{1}{\delta}\right) + \delta\right) + \varepsilon_2 \ln\left(\frac{1}{\delta}\right)\right). \quad (4)$$

Let the right hand side of Eq. (4) become $\leq \varepsilon$, then the number of queries to U_ρ is $\tilde{O}(r^2/\varepsilon^2)$. \square

3.2 Max Entropy and Rank of Quantum States

The Max (Hartley) entropy $S^{\max}(\rho) = \ln(\text{rank}(\rho))$ of a quantum state ρ is the logarithm of its rank. Low-rank quantum states turn out to be useful in quantum algorithms, e.g. [GLF⁺10, LMR14, RSML18, BKL⁺19, WZC⁺21]. Estimating the rank of quantum states is important in checking whether a quantum state fits in a certain low-rank condition of a quantum algorithm. Recently, [TV21] proposed a variational quantum algorithm to estimate the rank of quantum states. Here, we provide a quantum algorithm for rank estimation. For $\delta > 0$, the δ -rank of a matrix A is defined by

$$\text{rank}_\delta(A) = \min\{\text{rank}(B) : \|A - B\| \leq \delta\}.$$

In particular, $\text{rank}_0(A) = \text{rank}(A)$. We note that if A is Hermitian and has the spectrum decomposition $A = \sum_j \lambda_j |\psi_j\rangle\langle\psi_j|$, then $\text{rank}_\delta(A) = \text{tr}(\Pi_{\text{supp}_\delta(A)})$ is the number of eigenvalues λ_j such that $|\lambda_j| > \delta$.

Theorem 3.4 (Rank estimation). *Suppose*

1. U is an $(n + a)$ -qubit unitary operator that prepares an n -qubit density operator ρ .
2. $\delta \in (0, \frac{1}{10}]$.

For $\varepsilon, \varepsilon' > 0$, there is a quantum algorithm that outputs \tilde{r} such that

$$(1 - \varepsilon)\text{rank}_\delta(\rho) - \varepsilon' \leq \tilde{r} \leq (1 + \varepsilon)\text{rank}(\rho) + \varepsilon',$$

using $\tilde{O}(\frac{1}{\delta^2\varepsilon})$ queries to U and $\tilde{O}(\frac{1}{\delta^2\varepsilon} \text{poly}(n))$ elementary quantum gates.

Proof. Step 1. By Lemma 2.19, introducing parameters $\delta_1, \varepsilon_1 \in (0, \frac{1}{10}]$, there is a quantum circuit \tilde{U} such that

1. \tilde{U} prepares an n -qubit subnormalized density operator A , which is a $(1, 0, \delta_1)$ -block-encoding of $\tilde{\Pi}$ such that

$$\left(\frac{\delta}{8}(1 - 2\varepsilon_1) - \left(\frac{\delta}{2}\right)^{1/2} \varepsilon_1\right) \Pi_{\text{supp}_\delta(\rho)} \leq \tilde{\Pi} \leq \left(\frac{\delta}{8} + \varepsilon_1^2 + \left(\frac{\delta}{2}\right)^{1/2} \varepsilon_1\right) \Pi_{\text{supp}(\rho)}. \quad (5)$$

2. \tilde{U} uses $O(d)$ queries to U and U^\dagger , 1 query to controlled- U and $O((n+a)d)$ elementary quantum gates, where $d = O\left(\frac{1}{\delta} \log\left(\frac{1}{\varepsilon_1}\right)\right)$.
3. A description of \tilde{U} can be computed by a (classical) Turing machine in $\text{poly}(d, \log(1/\delta_1))$ time.

We note that $|\text{tr}(A) - \text{tr}(\tilde{\Pi})| \leq 2^n \delta_1$ and by Eq. (5) we have

$$(1 - 2\delta^{-1}\varepsilon_1) \text{rank}_\delta(\rho) \leq 8\delta^{-1} \text{tr}(\tilde{\Pi}) \leq (1 + 2\delta^{-1}\varepsilon_1) \text{rank}(\rho).$$

Step 2. Introducing a parameter ε_2 , by Lemma 2.15, we can compute \tilde{p} that estimates $\text{tr}(A)$ such that $|\tilde{p} - \text{tr}(A)| \leq \varepsilon_2$ with $O\left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)$ queries to \tilde{U} and \tilde{U}^\dagger , where B is an upper bound of $\text{tr}(A)$. Here, we just choose $B = 1$.

Step 3. Output $\tilde{r} = 8\delta^{-1}\tilde{p}$ as the estimation of the rank of ρ . Here, we see that

$$(1 - 2\delta^{-1}\varepsilon_1) \text{rank}_\delta(\rho) - 8\delta^{-1}(2^n \delta_1 + \varepsilon_2) \leq \tilde{r} \leq (1 + 2\delta^{-1}\varepsilon_1) \text{rank}(\rho) + 8\delta^{-1}(2^n \delta_1 + \varepsilon_2).$$

By letting $2\delta^{-1}\varepsilon_1 = \varepsilon$ and $8\delta^{-1}(2^n \delta_1 + \varepsilon_2) = \varepsilon'$, the number of queries to U is

$$O\left(\frac{1}{\delta} \log\left(\frac{1}{\varepsilon_1}\right) \cdot \left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)\right) = \tilde{O}\left(\frac{1}{\delta^2 \varepsilon}\right).$$

And similarly, the number of elementary quantum gates is $\tilde{O}\left(\frac{1}{\delta^2 \varepsilon} \text{poly}(n)\right)$. \square

Based on Theorem 3.4, we can obtain the exact rank of ρ if $\Pi/\kappa \leq \rho$ for some projector Π and $\kappa > 0$.

Corollary 3.5 (Exact rank). *Suppose*

1. U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit density operator ρ .
2. $\delta \in (0, \frac{1}{10}]$.

If $\Pi/\kappa \leq \rho$ for some projector Π and $\kappa > 0$, then there is a quantum algorithm that outputs $r = \text{rank}(\rho)$ using $\tilde{O}(\kappa^3)$ queries to U and $\tilde{O}(\kappa^3 \text{poly}(n))$ elementary quantum gates.

Proof. The claim holds immediately by letting $\delta = \varepsilon = \Theta(1/\kappa)$ in Theorem 3.4. \square

Now we furthermore define the δ -Max entropy by $S_\delta^{\max}(\rho) = \ln(\text{rank}_\delta(\rho))$. Based on Theorem 3.4, we are able to give an estimation of the Max entropy.

Theorem 3.6 (Max entropy estimation). *Suppose*

1. U is an $(n+a)$ -qubit unitary operator that prepares an n -qubit density operator ρ .
2. $\delta \in (0, \frac{1}{10}]$.

For $\varepsilon > 0$, there is a quantum algorithm that outputs \tilde{s} such that

$$S_\delta^{\max}(\rho) - \varepsilon \leq \tilde{s} \leq S^{\max}(\rho) + \varepsilon,$$

using $\tilde{O}(\frac{1}{\delta^2 \varepsilon})$ queries to U and $\tilde{O}(\frac{1}{\delta^2 \varepsilon} \text{poly}(n))$ elementary quantum gates.

Moreover, if $\Pi/\kappa \leq \rho$ for some projector Π and $\kappa > 0$, there is a quantum algorithm that computes the Max entropy $S^{\max}(\rho)$ within additive error ε using $\tilde{O}(\frac{\kappa^2}{\varepsilon})$ queries to U and $\tilde{O}(\frac{\kappa^2}{\varepsilon} \text{poly}(n))$ elementary quantum gates.

Proof. By Theorem 3.4, there is a quantum algorithm that outputs \tilde{r} such that

$$\left(1 - \frac{\varepsilon}{2}\right) \text{rank}_\delta(\rho) \leq \left(1 - \frac{\varepsilon}{4}\right) \text{rank}_\delta(\rho) - \frac{\varepsilon}{4} \leq \tilde{r} \leq \left(1 + \frac{\varepsilon}{4}\right) \text{rank}(\rho) + \frac{\varepsilon}{4} \leq \left(1 + \frac{\varepsilon}{2}\right) \text{rank}(\rho),$$

using $\tilde{O}(\frac{1}{\delta^2\varepsilon})$ queries to U and $\tilde{O}(\frac{1}{\delta^2\varepsilon} \text{poly}(n))$ elementary quantum gates. After taking logarithm of both sides, we have

$$\ln(\text{rank}_\delta(\rho)) + \ln\left(1 - \frac{\varepsilon}{2}\right) \leq \ln(\tilde{r}) \leq \ln(\text{rank}(\rho)) + \ln\left(1 + \frac{\varepsilon}{2}\right),$$

which is

$$S_\delta^{\max}(\rho) - \varepsilon \leq \ln(\tilde{r}) \leq S^{\max}(\rho) + \varepsilon.$$

We only need to output $\tilde{s} = \ln(\tilde{r})$ as an estimation of the Max entropy $S^{\max}(\rho)$.

Moreover, if $\Pi/\kappa \leq \rho$ for some projector Π and $\kappa > 0$, the claim is obtained by letting $\delta = \frac{1}{\kappa}$ (and then $S_\delta^{\max}(\rho) = S^{\max}(\rho)$). \square

3.3 Quantum Rényi Entropy and Quantum Tsallis Entropy

Now we are going to discuss how quantum algorithms can compute the quantum Rényi entropy $S_\alpha^R(\rho)$ and the quantum Tsallis entropy $S_\alpha^T(\rho)$. The key is to compute $\text{tr}(\rho^\alpha)$, which is given as follows.

Theorem 3.7 (Trace of positive powers). *Suppose*

1. U_ρ is an $(n + n_\rho)$ -qubit unitary operator that prepares an n -qubit density operator ρ with $\text{rank}(\rho) \leq r$.
2. n_ρ is a polynomial in n .

For $a \in (0, 1) \cup (1, +\infty)$, there is a quantum algorithm that computes $\text{tr}(\rho^\alpha)$ within additive error ε using Q queries to U_ρ and $Q \cdot \text{poly}(n)$ elementary quantum gates, where

$$Q = \begin{cases} \tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right), & 0 < \alpha < 1 \\ O(1/\varepsilon), & \alpha > 1 \wedge \alpha \equiv 1 \pmod{2} \\ \tilde{O}\left(r^{1/\{\frac{\alpha-1}{2}\}}/\varepsilon^{1+1/\{\frac{\alpha-1}{2}\}}\right), & \text{otherwise} \end{cases}$$

and $\{x\} = x - \lfloor x \rfloor$ is the decimal part of real number x .

Proof. We will discuss in three cases as stated in the statement of this theorem.

Case 1. $0 < \alpha < 1$. In this case, we have $\text{tr}(\rho^\alpha) \leq r^{1-\alpha}$. By Lemma 2.8 and introducing δ_1 and ε_1 , there is a quantum circuit \tilde{U} such that

1. \tilde{U} prepares an n -qubit subnormalized density operator A , and A is a $(4\delta_1^{\alpha-1}, 0, \Theta(\delta_1^\alpha + \varepsilon_1\delta_1^{\alpha-1}))$ -block-encoding of ρ^α .
2. \tilde{U} uses $O(d)$ queries to U_ρ and $O((n+n_\rho)d)$ elementary quantum gates, where $d = O\left(\frac{1}{\delta_1} \log\left(\frac{1}{\varepsilon_1}\right)\right)$.
3. The description of \tilde{U} can be computed by a classical Turing machine in $O(\text{poly}(d))$ time.

Note that A is a $(4\delta_1^{\alpha-1}, 0, \Theta(\delta_1^\alpha + \varepsilon_1\delta_1^{\alpha-1}))$ -block-encoding of ρ^α , i.e., $\|4\delta_1^{\alpha-1}A - \rho^\alpha\| \leq \Theta(\delta_1^\alpha + \varepsilon_1\delta_1^{\alpha-1})$, we have $|4\delta_1^{\alpha-1}\text{tr}(A) - \text{tr}(\rho^\alpha)| \leq \Theta(r(\delta_1^\alpha + \varepsilon_1\delta_1^{\alpha-1}))$. Therefore,

$$\text{tr}(A) \leq \frac{1}{4\delta_1^{\alpha-1}} (\text{tr}(\rho^\alpha) + \Theta(r(\delta_1^\alpha + \varepsilon_1\delta_1^{\alpha-1}))) \leq \Theta(r^{1-\alpha}\delta_1^{1-\alpha} + r\delta_1 + r\varepsilon_1) =: B.$$

By Lemma 2.15 and introducing ε_2 , we can obtain \tilde{x} as an approximation of $\text{tr}(A)$ with $Q = O\left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)$ queries to \tilde{U} such that $|\text{tr}(A) - \tilde{x}| \leq \varepsilon_2$. Then we output $4\delta_1^{\alpha-1}\tilde{x}$ as an approximation of $\text{tr}(\rho^\alpha)$ by noting that

$$|4\delta_1^{\alpha-1}\tilde{x} - \text{tr}(\rho^\alpha)| \leq \Theta(\delta_1^{\alpha-1}\varepsilon_2 + r(\delta_1^\alpha + \varepsilon_1\delta_1^{\alpha-1})).$$

The number of queries to U_ρ is

$$Qd = \tilde{O}\left(\frac{1}{\delta_1}\left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)\right) = \tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right)$$

by taking $\delta_1 = \tilde{\Theta}((\varepsilon/r)^{1/\alpha})$, $\varepsilon_1 = \tilde{\Theta}((\varepsilon/r)^{1/\alpha})$ and $\varepsilon_2 = \tilde{\Theta}(\varepsilon^{1/\alpha}/r^{1/\alpha-1})$.

Case 2. $\alpha > 1$ and α is an odd number. Let $\alpha = 2\beta + 1$. By Lemma 2.1, there is a unitary operator U_1 , which is a $(1, n + n_\rho, 0)$ -block-encoding of ρ with 1 query to U_ρ . By Lemma 2.12, there is a unitary operator U_β , which is a $(1, \Theta(\beta(n + n_\rho)), 0)$ -block-encoding of ρ^β with β queries to U_1 . By Lemma 2.2, there is a quantum circuit U that prepares $\rho^{2\beta+1} = \rho^\alpha$ with 1 query to U_ρ and 1 query to U_β . Note that $\text{tr}(\rho^\alpha) \leq 1$ and by Lemma 2.15, we can obtain \tilde{x} as an approximation of $\text{tr}(\rho^\alpha)$ with $O(1/\varepsilon)$ queries to U such that $|\tilde{x} - \text{tr}(\rho^\alpha)| \leq \varepsilon$. In total, the number of queries to U_ρ is $O(1/\varepsilon) \cdot \beta = O(1/\varepsilon)$.

Case 3. $\alpha > 1$ and α is not an odd number. Let $\beta = \lfloor \frac{\alpha-1}{2} \rfloor$ and $c = \{\frac{\alpha-1}{2}\}$. By Lemma 2.13 and introducing δ_1 and ε_1 , there is a unitary operator U_c that is a $(2, O(n + n_\rho), \Theta(\varepsilon_1 + \delta_1^c))$ -block-encoding of ρ^c with $Q_1 = O\left(\frac{1}{\delta_1} \log\left(\frac{1}{\varepsilon_1}\right)\right)$ queries to U_1 . By Lemma 2.12, there is a unitary operator $U_{\beta+c}$ that is a $(2, O(\beta(n + n_\rho)), \Theta(\varepsilon_1 + \delta_1^c))$ -block-encoding of $\rho^{\beta+c}$ with 1 query to U_β and 1 query to U_c . By Lemma 2.2, there is a unitary operator U that prepares a subnormalized density operator A with 1 query to U_ρ and 1 query to $U_{\beta+c}$, and A is a $(4, 0, \Theta(\varepsilon_1 + \delta_1^c))$ -block-encoding of $\rho^{2(\beta+c)+1} = \rho^\alpha$, i.e., $\|4A - \rho^\alpha\| \leq \Theta(\varepsilon_1 + \delta_1^c)$. Note that

$$\text{tr}(A) \leq \frac{1}{4} (\text{tr}(\rho^\alpha) + \Theta(r(\varepsilon_1 + \delta_1^c))) =: B.$$

By Lemma 2.15 and introducing ε_2 , we can obtain \tilde{x} as an approximation of $\text{tr}(A)$ with $Q_2 = O\left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)$ queries to U such that $|\tilde{x} - \text{tr}(A)| \leq \varepsilon_2$. Then we output $4\tilde{x}$ as an approximation of $\text{tr}(\rho^\alpha)$ by noting that

$$|4\tilde{x} - \text{tr}(\rho^\alpha)| \leq \Theta(\varepsilon_2 + r(\varepsilon_1 + \delta_1^c)).$$

The number of queries to U_ρ is

$$(\beta + Q_1)Q_2 = \tilde{O}\left(\left(\beta + \frac{1}{\delta_1}\right)\left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)\right) = \tilde{O}\left(\frac{r^{1/c}}{\varepsilon^{1+1/c}}\right)$$

by taking $\delta_1 = \tilde{\Theta}((\varepsilon/r)^{1/c})$, $\varepsilon_1 = \tilde{\Theta}(\varepsilon/r)$ and $\varepsilon_2 = \tilde{\Theta}(\varepsilon)$. \square

In the following, we are going to show how to estimate the quantum Rényi and Tsallis entropies based on Theorem 3.7.

Theorem 3.8 (Quantum Rényi entropy). *Suppose*

1. U_ρ is an $(n + n_\rho)$ -qubit unitary operator that prepares an n -qubit density operator ρ with $\text{rank}(\rho) \leq r$.
2. n_ρ is a polynomial in n .

For $a \in (0, 1) \cup (1, +\infty)$, there is a quantum algorithm that computes $S_\alpha^R(\rho)$ within additive error ε using Q queries to U_ρ and $Q \cdot \text{poly}(n)$ elementary quantum gates, where

$$Q = \begin{cases} \tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right), & 0 < \alpha < 1 \\ O\left(r^{\alpha-1}/\varepsilon\right), & \alpha > 1 \wedge \alpha \equiv 1 \pmod{2} \\ \tilde{O}\left(r^{\alpha-1+\alpha/\{\frac{\alpha-1}{2}\}}/\varepsilon^{1+1/\{\frac{\alpha-1}{2}\}}\right), & \text{otherwise} \end{cases}$$

and $\{x\} = x - \lfloor x \rfloor$ is the decimal part of real number x .

Proof. We will discuss in cases as stated in the statement of this theorem.

Case 1. $0 < \alpha < 1$. In this case, $1 \leq \text{tr}(\rho^\alpha) \leq r^{1-\alpha}$. By Theorem 3.7, there is a quantum algorithm that outputs $1 \leq x \leq r^{1-\alpha}$ such that $|x - \text{tr}(\rho^\alpha)| \leq \varepsilon'$. Then

$$\left| \frac{1}{1-\alpha} \ln(x) - S_\alpha^R(\rho) \right| \leq \Theta\left(\frac{\varepsilon'}{1-\alpha}\right).$$

Let $\varepsilon' = \Theta((1-\alpha)\varepsilon)$. The number of queries to U_ρ is

$$\tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon'^{\frac{3+\alpha}{2\alpha}}\right) = \tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right).$$

Case 2. $\alpha > 1$. In this case, $r^{1-\alpha} \leq \text{tr}(\rho^\alpha) \leq 1$. By Theorem 3.7, there is a quantum algorithm that outputs $r^{1-\alpha} \leq x \leq 1$ such that $|x - \text{tr}(\rho^\alpha)| \leq \varepsilon'$. Then

$$\left| \frac{1}{1-\alpha} \ln(x) - S_\alpha^R(\rho) \right| \leq \Theta\left(\frac{r^{\alpha-1}\varepsilon'}{\alpha-1}\right).$$

Let $\varepsilon' = \Theta((\alpha-1)r^{1-\alpha}\varepsilon)$.

Subcase 2.1. $\alpha > 1$ and α is an odd number. The number of queries to U_ρ is

$$O\left(\frac{\alpha}{\varepsilon'}\right) = O\left(\frac{r^{\alpha-1}}{\varepsilon}\right).$$

Subcase 2.2. $\alpha > 1$ and α is not an odd number. The number of queries to U_ρ is

$$\tilde{O}\left(\left(\alpha + (r/\varepsilon')^{1/\{\frac{\alpha-1}{2}\}}\right)/\varepsilon'\right) = \tilde{O}\left(r^{\alpha-1+\alpha/\{\frac{\alpha-1}{2}\}}/\varepsilon^{1+1/\{\frac{\alpha-1}{2}\}}\right).$$

□

Theorem 3.9 (Quantum Tsallis entropy). *Suppose*

1. U_ρ is an $(n + n_\rho)$ -qubit unitary operator that prepares an n -qubit density operator ρ with $\text{rank}(\rho) \leq r$.
2. n_ρ is a polynomial in n .

For $a \in (0, 1) \cup (1, +\infty)$, there is a quantum algorithm that computes $S_\alpha^T(\rho)$ within additive error ε using Q queries to U_ρ and $Q \cdot \text{poly}(n)$ elementary quantum gates, where

$$Q = \begin{cases} \tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right), & 0 < \alpha < 1 \\ O(1/\varepsilon), & \alpha > 1 \wedge \alpha \equiv 1 \pmod{2} \\ \tilde{O}\left(r^{1/\{\frac{\alpha-1}{2}\}}/\varepsilon^{1+1/\{\frac{\alpha-1}{2}\}}\right), & \text{otherwise} \end{cases}$$

and $\{x\} = x - \lfloor x \rfloor$ is the decimal part of real number x .

Proof. By Theorem 3.7, there is a quantum algorithm that outputs $1 \leq x \leq r^{1-\alpha}$ such that $|x - \text{tr}(\rho^\alpha)| \leq \varepsilon'$. Then

$$\left| \frac{1}{1-\alpha} \ln(x) - S_\alpha^T(\rho) \right| \leq \Theta\left(\frac{\varepsilon'}{|1-\alpha|}\right).$$

Let $\varepsilon' = \Theta(|1-\alpha|\varepsilon)$. We will discuss in three cases as stated in the statement of this theorem.

Case 1. $0 < \alpha < 1$. The number of queries to U_ρ is

$$\tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon'^{\frac{3+\alpha}{2\alpha}}\right) = \tilde{O}\left(r^{\frac{3-\alpha^2}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right).$$

Case 2. $\alpha > 1$ and α is an odd number. The number of queries to U_ρ is

$$O\left(\frac{\alpha}{\varepsilon'}\right) = O\left(\frac{1}{\varepsilon}\right).$$

Case 3. $\alpha > 1$ and α is not an odd number. The number of queries to U_ρ is

$$\tilde{O}\left(\left(\alpha + (r/\varepsilon')^{1/\{\frac{\alpha-1}{2}\}}\right)/\varepsilon'\right) = \tilde{O}\left(r^{1/\{\frac{\alpha-1}{2}\}}/\varepsilon^{1+1/\{\frac{\alpha-1}{2}\}}\right).$$

□

We note that when $\alpha > 1$ is an odd number, the query complexities of our quantum algorithms for $\text{tr}(\rho^\alpha)$ and $S_\alpha^T(\rho)$ do not depend on r . This result can be applied to computing the classical Tsallis entropy of a distribution $p : [N] \rightarrow [0, 1]$. Suppose a quantum oracle U is given as

$$U |0\rangle = \sum_{i \in [N]} \sqrt{p(i)} |i\rangle. \quad (6)$$

For convenience, we assume that $N = 2^n$. This kind of quantum oracle is called “classical distribution with pure state preparation access”. We start from the quantum state $|0\rangle_n |0\rangle_n$, and the algorithm for estimating the classical Tsallis entropy of p is as follows.

1. Apply U on the first part of the quantum state, then the state becomes

$$\sum_{i \in [N]} \sqrt{p(i)} |i\rangle_n |0\rangle_n.$$

2. Apply a CNOT gate with control qubit the j -th qubit of the first part and target qubit the j -th qubit of the second part for each $j \in [n]$, then the state becomes

$$\sum_{i \in [N]} \sqrt{p(i)} |i\rangle_n |i\rangle_n.$$

3. Note that if the second part of the quantum state after step 2 is traced out, it becomes a mixed quantum state (density operator)

$$\rho = \sum_{i \in [N]} p(i) |i\rangle \langle i|.$$

Apply the algorithm of Theorem 3.9, we are able to obtain an estimation of the quantum Tsallis entropy $S_\alpha^T(\rho)$ (i.e., the classical α -Tsallis entropy of p) within additive error ε with $O(1/\varepsilon)$ queries to U and $O(1/\varepsilon \cdot \text{poly}(n))$ elementary quantum gates.

Corollary 3.10. *For odd integer $\alpha > 1$, given the quantum oracle U to a probability distribution $p : [N] \rightarrow [0, 1]$ as in Eq. (6), there is a quantum algorithm that computes the Tsallis entropy $S_\alpha^T(p)$ of p within additive error ε , using $O(1/\varepsilon)$ queries to U and $O(1/\varepsilon \cdot \text{poly}(n))$ elementary quantum gates.*

For integer $\alpha \geq 2$, according to [EAO⁺02] (see also [KLL⁺17]), there is a simple SWAP test like quantum circuit that outputs 0 and 1 with probability $(1 \pm \text{tr}(\rho^\alpha))/2$, respectively, using α copies of ρ . With a straightforward statistical method, we can estimate $\text{tr}(\rho^\alpha)$ within additive error ε by $O(1/\varepsilon^2)$ repetitions of that quantum circuit. Directly applying this method also implies a quantum algorithm, which computes the Tsallis entropy (both quantum and classical) within additive error ε , using $O(1/\varepsilon^2)$ queries to quantum oracles. Compare to this simple algorithm, our quantum algorithm (of Theorem 3.9 and Corollary 3.10) yields a quadratic speedup for odd $\alpha > 1$.

3.4 Lower Bounds

We establish lower bounds for estimating quantum entropies in the low-rank case, which are derived from known lower bounds for estimating entropies of classical distributions [LW19, BKT20].

Theorem 3.11. *Suppose U_ρ be a quantum oracle that prepares the density operator ρ , and $r = \text{rank}(\rho)$. For $\alpha \geq 0$, Any quantum algorithm that computes $S_\alpha^R(\rho)$ within additive error $\varepsilon = \Omega(1)$, then the number of queries to U_ρ is $\Omega(Q(r))$, where*

$$Q(r) = \begin{cases} r^{1/3}, & \alpha = 0, \\ \max\{r^{1/7\alpha - o(1)}, r^{1/3}\}, & 0 < \alpha < 1, \\ \tilde{\Omega}(r^{1/2}), & \alpha = 1, \\ \max\{r^{\frac{1}{2} - \frac{1}{2\alpha}}, r^{1/3}\}, & r > 1. \end{cases}$$

Proof. We obtain lower bounds from those for classical distributions. The quantum query model for classical distributions we adopt is called the “classical distribution with quantum query access”. Suppose $p : [N] \rightarrow [0, 1]$ is a probability distribution on $[N]$. The quantum oracle U is given by

$$U |s, 0\rangle = |s, f(s)\rangle$$

for $s \in [S]$ and $S \in \mathbb{N}$ such that

$$p(i) = \frac{1}{S} |\{s \in [S] : f(s) = i\}|$$

for $i \in [N]$. It is pointed out in [GL20] that we can easily construct a “purified quantum query access” oracle by preparing a uniform superposition through the Hadamard gates, and then makes

a query to U . Therefore, all lower bounds in the “classical distribution with quantum query access” model also hold in the “purified quantum query access” model.

Let $B(N)$ be the lower bound for estimating the Rényi entropy. It is straightforward to see that if there is a quantum algorithm that computes the quantum Rényi entropy using $Q(r)$ queries to U_ρ , then with the same algorithm, we can compute the Rényi entropy of a probability distribution $p : [N] \rightarrow [0, 1]$ using $Q(N)$ queries to the “classical distribution with quantum query access” oracle. Therefore, we have $Q(r) \geq B(r)$. Our claim immediately holds by taking the lower bounds of $B(N)$ given in [LW19, BKT20]. \square

4 Quantum Distances

Distance measures of quantum states are quantum information quantities that indicate their closeness. Testing the closeness of quantum states is a basic problem in quantum property testing. Two of the most important distance measures of quantum states are the trace distance and fidelity.

In this section, we will provide quantum algorithms for computing them as well as their extensions. Section 4.1 presents quantum algorithms for computing the trace distance and its extension. Section 4.2 presents quantum algorithms for computing the fidelity and its extensions.

4.1 Trace Distance

The α -trace distance of two quantum states ρ and σ is defined by

$$T_\alpha(\rho, \sigma) = \text{tr} \left(\left| \frac{\rho - \sigma}{2} \right|^\alpha \right).$$

Here, $T_1(\rho, \sigma) = T(\rho, \sigma)$ is the trace distance. The trace distance of two pure quantum states (i.e., quantum states of rank 1) can be computed directly from their fidelity, which can be solved by the SWAP test [BCWdW01]. The closeness testing of the 1-, 2-, and 3-trace distances were studied in [GL20].

Our quantum algorithms for computing the α -trace distance are given as follows.

Theorem 4.1. *Suppose*

1. U_ρ is an $(n + n_\rho)$ -qubit unitary operator that prepares an n -qubit density operator ρ .
2. U_σ is an $(n + n_\sigma)$ -qubit unitary operator that prepares an n -qubit density operator σ .
3. n_ρ and n_σ are polynomials in n .
4. $r = \max\{\text{rank}(\rho), \text{rank}(\sigma)\}$.

For $\alpha > 0$, there is a quantum algorithm that computes $T_\alpha(\rho, \sigma)$ within additive error ε using Q queries to both U_ρ and U_σ , and $Q \cdot \text{poly}(n)$ elementary quantum gates, where

$$Q = \begin{cases} \tilde{O}(r^3/\varepsilon^4), & \alpha \equiv 0 \pmod{2} \\ \tilde{O}(r^{5/\alpha}/\varepsilon^{5/\alpha+1}), & 0 < \alpha < 1 \\ \tilde{O}(r^{3+1/\{\alpha/2\}}/\varepsilon^{4+1/\{\alpha/2\}}), & \text{otherwise} \end{cases}$$

and $\{\beta\} = \beta - \lfloor \beta \rfloor$.

Especially, taking $\alpha = 1$, we obtain a quantum algorithm for trace distance estimation using $\tilde{O}(r^5/\varepsilon^6)$ queries to U_ρ and U_σ .

The key observation of our quantum algorithm is that

$$T_\alpha(\rho, \sigma) = \text{tr} \left(\left| \frac{\rho - \sigma}{2} \right|^\alpha \right) = \text{tr} \left(\left| \frac{\rho - \sigma}{2} \right|^{\alpha/2} \Pi_{\text{supp}(\mu)} \left| \frac{\rho - \sigma}{2} \right|^{\alpha/2} \right),$$

where $\mu = (\rho + \sigma)/2$, $\text{supp}(\mu)$ is the support of μ and Π_S is the projector onto a subspace S . A straightforward idea is to first prepare a subnormalized density operator that is a block-encoding of $\Pi_{\text{supp}(\mu)}$, and then prepare another subnormalized density operator that is a block-encoding of $|\nu|^{\alpha/2} \Pi_{\text{supp}(\mu)} |\nu|^{\alpha/2}$ by the evolution of subnormalized density operators (Lemma 2.2), where $\nu = (\rho - \sigma)/2$. However, we are only able to prepare subnormalized density operator that is a block-encoding of a projector onto a truncated support by Lemma 2.19. In this way, we can prepare a subnormalized density operator $|\nu|^{\alpha/2} \Pi_{\text{supp}_\delta(\mu)} |\nu|^{\alpha/2}$ for some $\delta > 0$, instead of $|\nu|^{\alpha/2} \Pi_{\text{supp}(\mu)} |\nu|^{\alpha/2}$.

When δ is fixed, the inherent error of this approach is

Proposition 4.2.

$$\left| \text{tr} \left(|\nu|^{\alpha/2} \Pi_{\text{supp}(\mu)} |\nu|^{\alpha/2} \right) - \text{tr} \left(|\nu|^{\alpha/2} \Pi_{\text{supp}_\delta(\mu)} |\nu|^{\alpha/2} \right) \right| \leq 2r\delta^{\min\{\alpha, 1\}/2}.$$

Proof. Let $\mu = \sum_j \lambda_j |\psi_j\rangle \langle \psi_j|$, where $\lambda_j \in [0, 1]$ and $\sum_j \lambda_j = 1$. Then $\| |\nu| |\psi_j\rangle \| \leq \sqrt{\lambda_j}$. This is seen by the following.

$$\begin{aligned} \|\rho - \sigma\|^2 &= \langle \psi_j | (\rho - \sigma)^2 | \psi_j \rangle \\ &= \langle \psi_j | \rho^2 | \psi_j \rangle + \langle \psi_j | \sigma^2 | \psi_j \rangle - \langle \psi_j | (\rho\sigma + \sigma\rho) | \psi_j \rangle \\ &\leq \langle \psi_j | \rho^2 | \psi_j \rangle + \langle \psi_j | \sigma^2 | \psi_j \rangle + |\langle \psi_j | \rho\sigma | \psi_j \rangle| + |\langle \psi_j | \sigma\rho | \psi_j \rangle| \\ &\leq \langle \psi_j | \rho^2 | \psi_j \rangle + \langle \psi_j | \sigma^2 | \psi_j \rangle + 2\|\rho\|\|\sigma\| \\ &= \langle \psi_j | \rho^2 | \psi_j \rangle + \langle \psi_j | \sigma^2 | \psi_j \rangle + 2\sqrt{\langle \psi_j | \rho^2 | \psi_j \rangle \langle \psi_j | \sigma^2 | \psi_j \rangle} \\ &\leq 2(\langle \psi_j | \rho^2 | \psi_j \rangle + \langle \psi_j | \sigma^2 | \psi_j \rangle) \\ &\leq 2(\langle \psi_j | \rho | \psi_j \rangle + \langle \psi_j | \sigma | \psi_j \rangle) \\ &= 4\langle \psi_j | \mu | \psi_j \rangle \\ &\leq 4\|\mu\| \\ &= 4\lambda_j. \end{aligned}$$

Note that

$$\left| \text{tr} \left(|\nu|^{\alpha/2} \Pi_{\text{supp}(\mu)} |\nu|^{\alpha/2} \right) - \text{tr} \left(|\nu|^{\alpha/2} \Pi_{\text{supp}_\delta(\mu)} |\nu|^{\alpha/2} \right) \right| = \text{tr} \left((\Pi_{\text{supp}(\mu)} - \Pi_{\text{supp}_\delta(\mu)}) |\nu|^\alpha \right).$$

Then for $\alpha \geq 1$, we have

$$\begin{aligned} \text{tr} \left((\Pi_{\text{supp}(\mu)} - \Pi_{\text{supp}_\delta(\mu)}) |\nu|^\alpha \right) &= \sum_{0 < \lambda_j < \delta} \langle \psi_j | |\nu|^\alpha | \psi_j \rangle \\ &\leq \sum_{0 < \lambda_j < \delta} \langle \psi_j | |\nu| | \psi_j \rangle \\ &\leq \sum_{0 < \lambda_j < \delta} \| |\nu| |\psi_j\rangle \| \\ &\leq \sum_{0 < \lambda_j < \delta} \sqrt{\lambda_j} \\ &\leq \sqrt{\delta} \text{rank}(\mu) \\ &\leq 2r\sqrt{\delta}. \end{aligned}$$

Before deriving bounds for $0 < \alpha < 1$, we need the following lemma.

Lemma 4.3. *Suppose that A is an n -dimensional positive semidefinite operator, $|\psi\rangle$ is an n -dimensional vector, and $0 < \alpha < 1$. Then*

$$\|A^\alpha |\psi\rangle\| \leq \|A |\psi\rangle\|^\alpha \|\psi\|^{1-\alpha}.$$

Proof. Let

$$A = \sum_{j=1}^n \lambda_j |\psi_j\rangle \langle \psi_j|,$$

where $\{|\psi_j\rangle\}$ is an orthonormal basis, and $\lambda_j \geq 0$ for all $1 \leq j \leq n$. Let

$$|\psi\rangle = \sum_{j=1}^n \beta_j |\psi_j\rangle.$$

By Hölder's inequality, we have

$$\begin{aligned} \|A^\alpha |\psi\rangle\|^2 &= \sum_{j=1}^n |\lambda_j^\alpha \beta_j|^2 \\ &= \sum_{j=1}^n |\lambda_j^{2\alpha} \beta_j^{2\alpha}| \cdot |\beta_j^{2(1-\alpha)}| \\ &\leq \left(\sum_{j=1}^n |\lambda_j^{2\alpha} \beta_j^{2\alpha}|^{1/\alpha} \right)^\alpha \left(\sum_{j=1}^n |\beta_j^{2(1-\alpha)}|^{1/(1-\alpha)} \right)^{1-\alpha} \\ &= \left(\sum_{j=1}^n |\lambda_j \beta_j|^2 \right)^\alpha \left(\sum_{j=1}^n |\beta_j|^2 \right)^{1-\alpha} \\ &= \|A |\psi\rangle\|^{2\alpha} \|\psi\|^{2(1-\alpha)}. \end{aligned}$$

□

For $0 < \alpha < 1$, by Lemma 4.3, we have

$$\begin{aligned} \text{tr} \left((\Pi_{\text{supp}(\mu)} - \Pi_{\text{supp}_\delta(\mu)}) |\nu|^\alpha \right) &= \sum_{0 < \lambda_j < \delta} \langle \psi_j | |\nu|^\alpha | \psi_j \rangle \\ &\leq \sum_{0 < \lambda_j < \delta} \| |\nu|^\alpha | \psi_j \rangle \| \\ &\leq \sum_{0 < \lambda_j < \delta} \| |\nu| | \psi_j \rangle \|^\alpha \| | \psi_j \rangle \|^{1-\alpha} \\ &\leq \sum_{0 < \lambda_j < \delta} \lambda_j^{\alpha/2} \\ &\leq 2r\delta^{\alpha/2}. \end{aligned}$$

Therefore,

$$\left| \text{tr} \left(|\nu|^{\alpha/2} \Pi_{\text{supp}(\mu)} |\nu|^{\alpha/2} \right) - \text{tr} \left(|\nu|^{\alpha/2} \Pi_{\text{supp}_\delta(\mu)} |\nu|^{\alpha/2} \right) \right| \leq 2r\delta^{\min\{\alpha, 1\}/2}.$$

□

Hence, we could obtain a reasonable error by setting δ small enough.

Step 1. By Lemma 2.17 with the Hadamard gate

$$H|0\rangle = \sqrt{\frac{1}{2}}|0\rangle + \sqrt{\frac{1}{2}}|1\rangle,$$

we obtain an $O(n+n_\rho+n_\sigma)$ -qubit unitary operator U_μ that prepares density operator $\mu = (\rho+\sigma)/2$, using 1 query to U_ρ and U_σ , and $O(1)$ elementary quantum gates.

Introducing three parameters $\delta_1, \varepsilon_1, \delta_Q \in (0, \frac{1}{10}]$, by Lemma 2.19, there is a quantum circuit U_1 , which prepares a subnormalized density operator A_1 and A_1 is a $(1, 0, \delta_Q)$ -block-encoding of Π_1 , where

$$\left(\frac{\delta_1}{4}(1-2\varepsilon_1) - \delta_1^{1/2}\varepsilon_1\right) \Pi_{\text{supp}_{2\delta_1}(\mu)} \leq \Pi_1 \leq \left(\frac{\delta_1}{4} + \varepsilon_1^2 + \delta_1^{1/2}\varepsilon_1\right) \Pi_{\text{supp}(\mu)}.$$

Here, U_1 uses Q_1 queries to U_μ and $O(Q_1(n+n_\rho+n_\sigma))$ elementary quantum gates, where $Q_1 = O\left(\frac{1}{\delta_1} \log\left(\frac{1}{\varepsilon_1}\right)\right)$. Moreover, U_1 can be computed by a classical Turing machine in poly $\left(Q_1, \log\left(\frac{1}{\delta_Q}\right)\right)$ time.

Next, we are going to construct a unitary operator that is a block-encoding of $|\nu|^{\alpha/2}$. By Lemma 2.1, there are two unitary operators V_σ and V_ρ which are a $(1, n+n_\sigma, 0)$ -block-encoding of σ and a $(1, n+n_\rho, 0)$ -block-encoding of ρ , respectively. Here, V_σ uses 1 query to each of U_σ and U_σ^\dagger and n_σ elementary quantum gates, and V_ρ uses 1 query to each of U_ρ and U_ρ^\dagger and n_ρ elementary quantum gates. Let $n' = \max(n_\rho, n_\sigma)$, then $V_\rho \otimes I_{n'-n_\rho}$ and $V_\sigma \otimes I_{n'-n_\sigma}$ are $(1, n+n', 0)$ -block-encodings of ρ and σ , respectively. According to Definition 2.3, we note that (HX, H) is a $(2, 1, 0)$ -state-preparation-pair for $y = (1, -1)$, where H is the Hadamard gate and X is the Pauli matrix. By Theorem 2.18, there is a $(2n+n'+1)$ -qubit quantum circuit W which is a $(1, n+n'+1, 0)$ -block-encoding of $\nu = (\rho - \sigma)/2$, using 1 query to each of V_ρ and V_σ and $O(1)$ elementary quantum gates.

Now we analyze the error if we replace $\Pi_{\text{supp}(\mu)}$ by $4\delta_1^{-1}\Pi_1$ in the following.

Proposition 4.4.

$$\left| \text{tr} \left(|\nu|^{\alpha/2} (4\delta_1^{-1}\Pi_1) |\nu|^{\alpha/2} \right) - T_\alpha(\rho, \sigma) \right| \leq \begin{cases} \Theta \left(\varepsilon_1 \delta_1^{-1/2} + r \delta_1^{1/2} \right), & \alpha \geq 1, \\ \Theta \left(r^{1-\alpha} \varepsilon_1 \delta_1^{-1/2} + r \delta_1^{\alpha/2} \right), & 0 < \alpha < 1. \end{cases}$$

Proof. Note that $\Pi_L \leq 4\delta_1^{-1}\Pi_1 \leq \Pi_U$, where

$$\Pi_L = \left(1 - 2\varepsilon_1 - 4\varepsilon_1 \delta_1^{-1/2}\right) \Pi_{\text{supp}_{2\delta_1}(\mu)},$$

$$\Pi_U = \left(1 + 4\varepsilon_1^2 \delta_1^{-1} + 4\varepsilon_1 \delta_1^{-1/2}\right) \Pi_{\text{supp}(\mu)}.$$

This leads to

$$f(\Pi_L) \leq f(4\delta_1^{-1}\Pi_1) \leq f(\Pi_U),$$

where $f(\Pi) = \text{tr} \left(|\nu|^{\alpha/2} \Pi |\nu|^{\alpha/2} \right)$ for convenience. Therefore,

$$|f(4\delta_1^{-1}\Pi_1) - f(\Pi_{\text{supp}(\mu)})| \leq \max\{T_L, T_U\},$$

where

$$T_L = |f(\Pi_L) - f(\Pi_{\text{supp}(\mu)})|,$$

$$T_U = |f(\Pi_U) - f(\Pi_{\text{supp}(\mu)})|.$$

By Proposition 4.2, we have

$$\begin{aligned} T_L &\leq \left| f(\Pi_L) - f(\Pi_{\text{supp}_{2\delta_1}(\mu)}) \right| + \left| f(\Pi_{\text{supp}_{2\delta_1}(\mu)}) - f(\Pi_{\text{supp}(\mu)}) \right| \\ &\leq f\left(\left(2\varepsilon_1 + 4\varepsilon_1\delta_1^{-1/2}\right)\Pi_{\text{supp}_{2\delta_1}(\mu)}\right) + 2r(2\delta_1)^{\min\{\alpha, 1\}/2} \\ &\leq \Theta\left(\varepsilon_1\delta_1^{-1/2}T_\alpha(\rho, \sigma) + r\delta_1^{\min\{\alpha, 1\}/2}\right). \end{aligned}$$

Also we have

$$T_U \leq f\left(\left(4\varepsilon_1^2\delta_1^{-1} + 4\varepsilon_1\delta_1^{-1/2}\right)\Pi_{\text{supp}(\mu)}\right) \leq \Theta\left(\varepsilon_1\delta_1^{-1/2}T_\alpha(\rho, \sigma)\right).$$

Combining the both, we have

$$|f(4\delta_1^{-1}\Pi_1) - f(\Pi_{\text{supp}(\mu)})| \leq \Theta\left(\varepsilon_1\delta_1^{-1/2}T_\alpha(\rho, \sigma) + r\delta_1^{\min\{\alpha, 1\}/2}\right).$$

We note that $T_\alpha(\rho, \sigma) \leq 1$ if $\alpha \geq 1$, and $T_\alpha(\rho, \sigma) \leq (2r)^{1-\alpha}$ if $0 < \alpha < 1$. These yield the claim. \square

In the following, we separately consider different cases of α .

Case 1: α is an even integer

Step 2. By Lemma 2.12, there is a unitary operator $W_{\alpha/2}$, which is a $(1, O(\alpha(n+n')), 0)$ -block-encoding of $|\nu|^{\alpha/2}$, using $\alpha/2$ queries to W . By Lemma 2.2, using 1 query to each of $W_{\alpha/2}$ and U_1 , we obtain a quantum circuit \tilde{U} , which prepares a subnormalized density operator $|\nu|^{\alpha/2} A_1 |\nu|^{\alpha/2}$. We note that

$$\left\| |\nu|^{\alpha/2} A_1 |\nu|^{\alpha/2} - |\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2} \right\| \leq \|A_1 - \Pi_1\| \leq \delta_Q.$$

Step 3. Introducing a parameter ε_3 , by Lemma 2.15, we can compute \tilde{p} that estimates $\text{tr}(|\nu|^{\alpha/2} A_1 |\nu|^{\alpha/2})$ such that $|\tilde{p} - \text{tr}(|\nu|^{\alpha/2} A_1 |\nu|^{\alpha/2})| \leq \varepsilon_3$ with $O\left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)$ queries to \tilde{U} , where $B = \Theta\left(\delta_1 + \varepsilon_1^2 + \delta_1^{1/2}\varepsilon_1 + r\delta_Q\right)$ is an upper bound of $\text{tr}(|\nu|^{\alpha/2} A_1 |\nu|^{\alpha/2})$. Note that

$$\begin{aligned} \text{tr}(|\nu|^{\alpha/2} A_1 |\nu|^{\alpha/2}) &\leq \text{tr}\left(|\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2}\right) + \Theta(r\delta_Q) \\ &\leq \Theta\left(\delta_1 + \varepsilon_1^2 + \delta_1^{1/2}\varepsilon_1 + r\delta_Q\right). \end{aligned}$$

Step 4. Output $4\delta_1^{-1}\tilde{p} \approx T_\alpha(\rho, \sigma)$ as the estimation. The additive error is

$$\begin{aligned} |4\delta_1^{-1}\tilde{p} - T_\alpha(\rho, \sigma)| &\leq 4\delta_1^{-1} \left| \tilde{p} - \text{tr}(|\nu|^{\alpha/2} A_1 |\nu|^{\alpha/2}) \right| + 4\delta_1^{-1} \left| \text{tr}(|\nu|^{\alpha/2} A_1 |\nu|^{\alpha/2}) - \text{tr}(|\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2}) \right| \\ &\quad + \left| \text{tr}\left(|\nu|^{\alpha/2} (4\delta_1^{-1}\Pi_1) |\nu|^{\alpha/2}\right) - \text{tr}\left(|\nu|^{\alpha/2} \Pi_{\text{supp}(\mu)} |\nu|^{\alpha/2}\right) \right| \\ &\leq \Theta\left(r\delta_1^{1/2} + \varepsilon_1\delta_1^{-1/2} + \delta_1^{-1}(\varepsilon_3 + r\delta_Q)\right). \end{aligned}$$

In order to make $|4\delta_1^{-1}\tilde{p} - T_\alpha(\rho, \sigma)| \leq \varepsilon$, it is sufficient to let $\delta_1 = \Theta(\varepsilon^2/r^2)$, $\varepsilon_3 = \Theta(\varepsilon^3/r^2)$, and other parameters become small enough polynomials in r and $1/\varepsilon$. Under these conditions, the number of queries to U_ρ and U_σ is

$$Q = O\left(Q_1 \alpha \left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)\right) = \tilde{O}\left(\frac{r^3}{\varepsilon^4}\right),$$

and the number of elementary quantum gates is $O(Q \cdot \text{poly}(n))$.

Case 2: $\alpha \geq 1$ and α is not an even integer

Step 2. Now introducing two parameters $\delta_2, \varepsilon_2 \in (0, \frac{1}{4}]$, by Lemma 2.13, there is a quantum circuit $W_{\{\alpha/2\}}$ that is a $(1, O(n + n'), 0)$ -block-encoding of A_2 , and A_2 is a $(2, 0, \Theta(\varepsilon_2 + \delta_2^{\{\alpha/2\}}))$ -block-encoding of $|\nu|^{\{\alpha/2\}}$, using Q_2 queries to W and $O(Q_2(n + n'))$ elementary quantum gates, where $Q_2 = O\left(\frac{1}{\delta_2} \log\left(\frac{1}{\varepsilon_2}\right)\right)$. By Lemma 2.12, there is a unitary operator $W_{\lfloor \alpha/2 \rfloor}$, which is a $(1, O(\alpha(n + n')), 0)$ -block-encoding of $|\nu|^{\lfloor \alpha/2 \rfloor}$, using $\lfloor \alpha/2 \rfloor$ queries to W . Again by Lemma 2.12, there is a unitary operator $W_{\alpha/2}$, which is a $(2, O(\alpha(n + n')), \Theta(\varepsilon_2 + \delta_2^{\{\alpha/2\}}))$ -block-encoding of $|\nu|^{\alpha/2}$, using 1 query to $W_{\{\alpha/2\}}$ and 1 query to $W_{\lfloor \alpha/2 \rfloor}$. By Lemma 2.2, using 1 query to each of $W_{\alpha/2}$ and U_1 , we obtain a quantum circuit \tilde{U} , which prepares a subnormalized density operator $A_2 A_1 A_2^\dagger$. We note that

$$\begin{aligned} \left\| A_2 A_1 A_2^\dagger - \frac{1}{4} |\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2} \right\| &\leq \left\| A_2 A_1 A_2^\dagger - A_2 \Pi_1 A_2^\dagger \right\| + \left\| A_2 \Pi_1 A_2^\dagger - \frac{1}{4} |\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2} \right\| \\ &\leq \|A_1 - \Pi_1\| + \left\| A_2 - \frac{1}{2} |\nu|^{\alpha/2} \right\| \|\Pi_1\| \|A_2^\dagger\| \\ &\quad + \left\| A_2^\dagger - \frac{1}{2} |\nu|^{\alpha/2} \right\| \|\Pi_1\| \left\| \frac{1}{2} |\nu|^{\alpha/2} \right\| \\ &\leq \Theta\left(\delta_Q + (\delta_1 + \varepsilon_1^2 + \delta_1^{1/2} \varepsilon_1)(\varepsilon_2 + \delta_2^{\{\alpha/2\}})\right). \end{aligned}$$

Step 3. Introducing a parameter ε_3 , by Lemma 2.15, we can compute \tilde{p} that estimates $\text{tr}(A_2 A_1 A_2^\dagger)$ such that $\left| \tilde{p} - \text{tr}(A_2 A_1 A_2^\dagger) \right| \leq \varepsilon_3$ with $O\left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)$ queries to \tilde{U} , where $B = \Theta\left((\delta_1 + \varepsilon_1^2 + \delta_1^{1/2} \varepsilon_1)(1 + r(\varepsilon_2 + \delta_2^{\{\alpha/2\}})) + r\delta_Q\right)$ is an upper bound of $\text{tr}(A_2 A_1 A_2^\dagger)$. Note that

$$\begin{aligned} \text{tr}(A_2 A_1 A_2^\dagger) &\leq \text{tr}\left(\frac{1}{4} |\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2}\right) + \Theta\left(r\left(\delta_Q + (\delta_1 + \varepsilon_1^2 + \delta_1^{1/2} \varepsilon_1)(\varepsilon_2 + \delta_2^{\{\alpha/2\}})\right)\right) \\ &\leq \Theta\left((\delta_1 + \varepsilon_1^2 + \delta_1^{1/2} \varepsilon_1)(1 + r(\varepsilon_2 + \delta_2^{\{\alpha/2\}})) + r\delta_Q\right). \end{aligned}$$

Step 4. Output $4\delta_1^{-1} \tilde{p} \approx T_\alpha(\rho, \sigma)$ as the estimation. The additive error is

$$\begin{aligned} |4\delta_1^{-1} \tilde{p} - T_\alpha(\rho, \sigma)| &\leq 4\delta_1^{-1} \left| \tilde{p} - \text{tr}(A_2 A_1 A_2^\dagger) \right| + 4\delta_1^{-1} \left| \text{tr}(A_2 A_1 A_2^\dagger) - \text{tr}(|\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2}) \right| \\ &\quad + \left| \text{tr}(|\nu|^{\alpha/2} (4\delta_1^{-1} \Pi_1) |\nu|^{\alpha/2}) - \text{tr}(|\nu|^{\alpha/2} \Pi_{\text{supp}(\mu)} |\nu|^{\alpha/2}) \right| \\ &\leq \Theta\left(r\delta_1^{1/2} + \varepsilon_1 \delta_1^{-1/2} + r(\varepsilon_2 + \delta_2^{\{\alpha/2\}})(1 + \varepsilon_1 \delta_1^{-1/2}) + \delta_1^{-1}(\varepsilon_3 + r\delta_Q)\right). \end{aligned}$$

In order to make $|4\delta_1^{-1} \tilde{p} - T_\alpha(\rho, \sigma)| \leq \varepsilon$, it is sufficient to let $\delta_1 = \Theta(\varepsilon^2/r^2)$, $\delta_2 = \Theta((\varepsilon/r)^{1/\{\alpha/2\}})$, $\varepsilon_3 = \Theta(\varepsilon^3/r^2)$, and other parameters become small enough polynomials in r and $1/\varepsilon$. Under these conditions, the number of queries to U_ρ and U_σ is

$$Q = O\left(Q_1(Q_2 + \alpha) \left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)\right) = \tilde{O}\left(\frac{r^{3+1/\{\alpha/2\}}}{\varepsilon^{4+1/\{\alpha/2\}}}\right),$$

and the number of elementary quantum gates is $O(Q \cdot \text{poly}(n))$.

Case 3: $0 < \alpha < 1$

Step 2. Introducing two parameters $\delta_2, \varepsilon_2 \in (0, \frac{1}{4}]$, by Lemma 2.13, there is a quantum circuit $W_{\alpha/2}$ that is a $(1, O(n+n'), 0)$ -block-encoding of A_2 , and A_2 is a $(2, 0, \Theta(\varepsilon_2 + \delta_2^{\alpha/2}))$ -block-encoding of $|\nu|^{\alpha/2}$, using Q_2 queries to W and $O(Q_2(n+n'))$ elementary quantum gates, where $Q_2 = O\left(\frac{1}{\delta_2} \log\left(\frac{1}{\varepsilon_2}\right)\right)$. By Lemma 2.2, using 1 query to each of $W_{\alpha/2}$ and U_1 , we obtain a quantum circuit \tilde{U} , which prepares a subnormalized density operator $A_2 A_1 A_2^\dagger$. We note that

$$\begin{aligned} \left\| A_2 A_1 A_2^\dagger - \frac{1}{4} |\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2} \right\| &\leq \left\| A_2 A_1 A_2^\dagger - A_2 \Pi_1 A_2^\dagger \right\| + \left\| A_2 \Pi_1 A_2^\dagger - \frac{1}{4} |\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2} \right\| \\ &\leq \|A_1 - \Pi_1\| + \left\| A_2 - \frac{1}{2} |\nu|^{\alpha/2} \right\| \|\Pi_1\| \|A_2^\dagger\| \\ &\quad + \left\| A_2^\dagger - \frac{1}{2} |\nu|^{\alpha/2} \right\| \|\Pi_1\| \left\| \frac{1}{2} |\nu|^{\alpha/2} \right\| \\ &\leq \Theta\left(\delta_Q + (\delta_1 + \varepsilon_1^2 + \delta_1^{1/2} \varepsilon_1)(\varepsilon_2 + \delta_2^{\alpha/2})\right). \end{aligned}$$

Step 3. Introducing a parameter ε_3 , by Lemma 2.15, we can compute \tilde{p} that estimates $\text{tr}(A_2 A_1 A_2^\dagger)$ such that $|\tilde{p} - \text{tr}(A_2 A_1 A_2^\dagger)| \leq \varepsilon_3$ with $O\left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)$ queries to \tilde{U} , where $B = \Theta\left(r^{1-\alpha} \delta_1 + r(\delta_1 + \varepsilon_1^2 + \delta_1^{1/2} \varepsilon_1)(\varepsilon_2 + \delta_2^{\alpha/2}) + r\delta_Q\right)$ is an upper bound of $\text{tr}(A_2 A_1 A_2^\dagger)$. Note that

$$\begin{aligned} \text{tr}(A_2 A_1 A_2^\dagger) &\leq \text{tr}\left(\frac{1}{4} |\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2}\right) + \Theta\left(r\left(\delta_Q + (\delta_1 + \varepsilon_1^2 + \delta_1^{1/2} \varepsilon_1)(\varepsilon_2 + \delta_2^{\alpha/2})\right)\right) \\ &\leq \Theta\left(r^{1-\alpha} \delta_1 + r(\delta_1 + \varepsilon_1^2 + \delta_1^{1/2} \varepsilon_1)(\varepsilon_2 + \delta_2^{\alpha/2}) + r\delta_Q\right). \end{aligned}$$

Step 4. Output $4\delta_1^{-1} \tilde{p} \approx T_\alpha(\rho, \sigma)$ as the estimation. The additive error is

$$\begin{aligned} |4\delta_1^{-1} \tilde{p} - T_\alpha(\rho, \sigma)| &\leq 4\delta_1^{-1} |\tilde{p} - \text{tr}(A_2 A_1 A_2^\dagger)| + 4\delta_1^{-1} |\text{tr}(A_2 A_1 A_2^\dagger) - \text{tr}(|\nu|^{\alpha/2} \Pi_1 |\nu|^{\alpha/2})| \\ &\quad + \left| \text{tr}\left(|\nu|^{\alpha/2} (4\delta_1^{-1} \Pi_1) |\nu|^{\alpha/2}\right) - \text{tr}\left(|\nu|^{\alpha/2} \Pi_{\text{supp}(\mu)} |\nu|^{\alpha/2}\right) \right| \\ &\leq \Theta\left(r\delta_1^{\alpha/2} + r^{1-\alpha} \varepsilon_1 \delta_1^{-1/2} + r(\varepsilon_2 + \delta_2^{\alpha/2})(1 + \varepsilon_1 \delta_1^{-1/2}) + \delta_1^{-1}(\varepsilon_3 + r\delta_Q)\right). \end{aligned}$$

In order to make $|4\delta_1^{-1} \tilde{p} - T_\alpha(\rho, \sigma)| \leq \varepsilon$, it is sufficient to let $\delta_1 = \Theta((\varepsilon/r)^{2/\alpha})$, $\delta_2 = \Theta((\varepsilon/r)^{2/\alpha})$, $\varepsilon_3 = \Theta(\varepsilon^{2/\alpha+1}/r^{2/\alpha})$, and other parameters become small enough polynomials in r and $1/\varepsilon$. Under these conditions, the number of queries to U_ρ and U_σ is

$$Q = O\left(Q_1 Q_2 \left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)\right) = \tilde{O}\left(\frac{r^{5/\alpha+(1-\alpha)/2}}{\varepsilon^{5/\alpha+1}}\right),$$

and the number of elementary quantum gates is $O(Q \cdot \text{poly}(n))$.

4.2 Fidelity

Quantum fidelity estimation is a problem to compute the fidelity of two mixed quantum states given their purifications. The well-known SWAP test [BCWdW01] can solve this problem when one of

the quantum states is pure. Recently, [WZC⁺21] proposes a polynomial-time quantum algorithm for the case that one of the quantum states is low-rank. However, their algorithm has very large exponents of r (rank) and ε (additive error) in the complexity. Here, we are able to improve the complexity with much smaller exponents, compared to the $\tilde{O}(r^{21.5}/\varepsilon^{23.5})$ quantum algorithm for fidelity estimation proposed by [WZC⁺21].

In addition, the sandwiched quantum Rényi relative entropy $D_\alpha(\rho\|\sigma)$ [WWY14, MLDS⁺13] is a generalization of quantum state measures, defined by

$$F_\alpha(\rho, \sigma) = \exp((\alpha - 1)D_\alpha(\rho\|\sigma)) = \text{tr} \left(\left(\sigma^{\frac{1-\alpha}{2\alpha}} \rho \sigma^{\frac{1-\alpha}{2\alpha}} \right)^\alpha \right).$$

Here, $F_{1/2}(\rho, \sigma) = F(\rho, \sigma)$ is the quantum state fidelity. It is clear that $0 \leq F_\alpha(\rho, \sigma) \leq 1$ for $\alpha \in (0, 1)$ (see [MLDS⁺13]). Recently, the sandwiched quantum Rényi relative entropy is used in quantum machine learning [KMW21].

Our quantum algorithms for computing the α -fidelity are given as follows.

Theorem 4.5. *Suppose*

1. U_ρ is an $(n + n_\rho)$ -qubit unitary operator that prepares an n -qubit density operator ρ with $\text{rank}(\rho) = r$.
2. U_σ is an $(n + n_\sigma)$ -qubit unitary operator that prepares an n -qubit density operator σ .
3. n_ρ and n_σ are polynomials in n .

For $\alpha \in (0, 1)$, there is a quantum algorithm that computes $F_\alpha(\rho, \sigma)$ within additive error ε , using $\tilde{O}\left(r^{\frac{3-\alpha}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right)$ queries to U_ρ ¹³, Q queries to U_σ , and $Q \cdot \text{poly}(n)$ elementary quantum gates, where

$$Q = \begin{cases} \tilde{O}\left(r^{\frac{3-\alpha}{2\alpha}}/\varepsilon^{\frac{3+\alpha}{2\alpha}}\right), & \beta \in \mathbb{N}, \\ \tilde{O}\left(r^{\frac{3-\alpha}{2\alpha} + \frac{1}{\alpha\{\beta\}}}/\varepsilon^{\frac{3+\alpha}{2\alpha} + \frac{1}{\alpha\{\beta\}}}\right), & \beta \notin \mathbb{N}, \end{cases}$$

and $\beta = (1 - \alpha)/2\alpha$, $\{\beta\} = \beta - \lfloor \beta \rfloor$.

Especially, taking $\alpha = \frac{1}{2}$, we obtain a quantum algorithm for fidelity estimation using $\tilde{O}(r^{2.5}/\varepsilon^{3.5})$ queries to U_ρ and $\tilde{O}(r^{6.5}/\varepsilon^{7.5})$ queries to U_σ .

We put the detailed proofs into the following subsections. In fact, such techniques used in estimating the relative sandwiched Rényi entropy can also be used to compute the relative Rényi entropy.

Case 1: β is an integer

Step 1. By Lemma 2.1, there is a unitary operator U_1 , which is a $(1, n + n_\sigma, 0)$ -block-encoding of σ , using $O(1)$ queries to U_σ and $O(n_\sigma)$ elementary quantum gates. By Lemma 2.12, there is a unitary operator U_β , which is a $(1, O(\beta(n + n_\sigma)), 0)$ -block-encoding of σ^β , using β queries to U_1 . By Lemma 2.2, there is a unitary operator U_η , which prepares a subnormalized density operator $\eta = \sigma^\beta \rho \sigma^\beta$, using 1 query to U_β and 1 query to U_ρ .

¹³Since the quantum algorithm is complicated, we do not distinguish between the queries to a unitary operator and those to its controlled versions, and we ignore poly-logarithmic factors.

Now introducing two parameters δ_1 and ε_1 , by Lemma 2.8, there is a unitary operator \tilde{U} , which prepares a subnormalized density operator η' and η' is a $(4\delta_1^{\alpha-1}, 0, \Theta(\delta_1^\alpha + \varepsilon_1\delta_1^{\alpha-1}))$ -block-encoding of η^α , using $O(d_1)$ queries to U_η , where $d_1 = O(\frac{1}{\delta_1} \log \frac{1}{\varepsilon_1})$.

Step 2. Introducing a parameter ε_2 , by Lemma 2.15, we can compute \tilde{p} such that $|\tilde{p} - \text{tr}(\eta')| \leq \varepsilon_2$, using $O\left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)$ queries to \tilde{U} , where $B = \Theta(\delta_1^{1-\alpha} + r(\delta_1 + \varepsilon_1))$ is an upper bound of $\text{tr}(\eta')$. Note that

$$\text{tr}(\eta') \leq \frac{1}{4}\delta_1^{1-\alpha} \text{tr}(\eta^\alpha) + \Theta(r(\delta_1 + \varepsilon_1)) \leq \Theta(\delta_1^{1-\alpha} + r(\delta_1 + \varepsilon_1)).$$

Step 3. Output $4\delta_1^{\alpha-1}\tilde{p} \approx F_\alpha(\rho, \sigma)$ as the estimation. The additive error is

$$\begin{aligned} |4\delta_1^{\alpha-1}\tilde{p} - F_\alpha(\rho, \sigma)| &\leq 4\delta_1^{\alpha-1} |\tilde{p} - \text{tr}(\eta')| + |\text{tr}(4\delta_1^{\alpha-1}\eta') - \text{tr}(\eta^\alpha)| \\ &\leq \Theta(r(\delta_1^\alpha + \varepsilon_1\delta_1^{\alpha-1}) + \delta_1^{\alpha-1}\varepsilon_2). \end{aligned}$$

In order to make $|4\delta_1^{\alpha-1}\tilde{p} - F_\alpha(\rho, \sigma)| \leq \varepsilon$, it is sufficient to let $\delta_1 = \Theta((\varepsilon/r)^{1/\alpha})$, $\varepsilon_1 = \Theta((\varepsilon/r)^{1/\alpha})$, and $\varepsilon_2 = \Theta(\varepsilon^{1/\alpha}/r^{1/\alpha-1})$. Under these conditions, the number of queries to U_σ is

$$O\left(\beta d_1 \left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)\right) = \tilde{O}\left(\frac{r^{\frac{3-\alpha}{2\alpha}}}{\varepsilon^{\frac{3+\alpha}{2\alpha}}}\right),$$

and the number of queries to U_ρ is

$$O\left(d_1 \left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)\right) = \tilde{O}\left(\frac{r^{\frac{3-\alpha}{2\alpha}}}{\varepsilon^{\frac{3+\alpha}{2\alpha}}}\right),$$

and the number of elementary quantum gates is

$$O\left(\beta d_1 \left(\frac{\sqrt{B}}{\varepsilon_2} + \frac{1}{\sqrt{\varepsilon_2}}\right)\right) \cdot \text{poly}(n, n_\sigma, n_\rho) = \tilde{O}\left(\frac{r^{\frac{3-\alpha}{2\alpha}}}{\varepsilon^{\frac{3+\alpha}{2\alpha}}} \text{poly}(n)\right).$$

Case 2: β is not an integer

Let $\{\beta\} = \beta - \lfloor \beta \rfloor$ denote the decimal part of β .

Step 1. By Lemma 2.1, there is a unitary operator U_1 , which is a $(1, n + n_\sigma, 0)$ -block-encoding of σ , using $O(1)$ queries to U_σ and $O(n_\sigma)$ elementary quantum gates. By Lemma 2.13, introducing two parameters δ_1 and ε_1 , there is a unitary operator $U_{\{\beta\}}$, which is a $(1, O(n + n_\sigma), 0)$ -block-encoding of A_1 , using $O(Q_1)$ queries to U_1 and $O(Q_1(n + n_\sigma))$ elementary quantum gates, where $Q_1 = O\left(\frac{1}{\delta_1} \log \frac{1}{\varepsilon_1}\right)$ and A_1 is a $(2, 0, \Theta(\varepsilon_1 + \delta_1^{\{\beta\}}))$ -block-encoding of $\sigma^{\{\beta\}}$. By Lemma 2.12, there is a unitary operator $U_{\lfloor \beta \rfloor}$, which is a $(1, O(\beta(n + n_\sigma)), 0)$ -block-encoding of $\sigma^{\lfloor \beta \rfloor}$, using $\lfloor \beta \rfloor$ queries to U_1 . Again by Lemma 2.12, there is a unitary operator U_β , which is a $(2, O(\beta(n + n_\sigma)), 0)$ -block-encoding of $A_1\sigma^{\lfloor \beta \rfloor}$, using 1 query to $U_{\lfloor \beta \rfloor}$ and 1 query to $U_{\{\beta\}}$. By Lemma 2.2, there is a unitary operator \tilde{U} , which prepares a subnormalized density operator $A_1\sigma^{\lfloor \beta \rfloor}\rho\sigma^{\lfloor \beta \rfloor}A_1^\dagger$, using 1 query to \tilde{U} and 1 query to U_ρ . Note that

$$\begin{aligned} \left\| A_1\sigma^{\lfloor \beta \rfloor}\rho\sigma^{\lfloor \beta \rfloor}A_1^\dagger - \frac{1}{4}\sigma^\beta\rho\sigma^\beta \right\| &\leq \left\| A_1\sigma^{\lfloor \beta \rfloor} - \frac{1}{2}\sigma^\beta \right\| \|\rho\| \left\| \sigma^{\lfloor \beta \rfloor}A_1^\dagger \right\| + \left\| \sigma^{\lfloor \beta \rfloor}A_1^\dagger - \frac{1}{2}\sigma^\beta \right\| \|\rho\| \left\| \frac{1}{2}\sigma^\beta \right\| \\ &\leq \Theta\left(\varepsilon_1 + \delta_1^{\{\beta\}}\right). \end{aligned}$$

Step 2. By Lemma 2.8, introducing two parameters δ_2 and ε_2 , there is a unitary operator U_2 , which prepares a subnormalized density operator A_2 , using $O(Q_2)$ queries to \tilde{U} and $O(Q_2(n + n_\sigma + n_\rho))$ elementary quantum gates, where $Q_2 = O\left(\frac{1}{\delta_2} \log \frac{1}{\varepsilon_2}\right)$ and A_2 is a $(4\delta_2^{\alpha-1}, 0, \Theta(\delta_2^{\alpha-1}(\delta_2 + \varepsilon_2)))$ -block-encoding of $\left(A_1 \sigma^{[\beta]} \rho \sigma^{[\beta]} A_1^\dagger\right)^\alpha$.

In order to analysis the error, we need the following lemma.

Lemma 4.6. *Suppose that A and B are two positive semidefinite operators of rank $\leq r$, and $0 < \alpha < 1$. Then*

$$|\text{tr}(A^\alpha) - \text{tr}(B^\alpha)| \leq 5r \|A - B\|^\alpha.$$

Proof. Let $J = A - B$. Let the eigenvalues of A , B and J be

$$\begin{aligned} \mu_1 &\geq \mu_2 \geq \dots \geq \mu_N, \\ \nu_1 &\geq \nu_2 \geq \dots \geq \nu_N, \\ \xi_1 &\geq \xi_2 \geq \dots \geq \xi_N, \end{aligned}$$

respectively. Then we have $\mu_{r+1} = \dots = \mu_N = \nu_{r+1} = \dots = \nu_N = 0$. By Weyl's inequality [Wey12], we have

$$\nu_j - \|J\| \leq \nu_j + \xi_N \leq \mu_j \leq \nu_j + \xi_1 \leq \nu_j + \|J\|$$

for every $1 \leq j \leq N$. Furthermore, it holds that $|\mu_j^\alpha - \nu_j^\alpha| \leq 5\|J\|^\alpha$. This is seen by the following two cases.

1. $\nu_j \geq \left(1 + \alpha^{\frac{1}{1-\alpha}}\right) \|J\|$. In this case, $\nu_j^\alpha - \|J\|^\alpha \leq (\nu_j - \|J\|)^\alpha \leq \mu_j^\alpha \leq (\nu_j + \|J\|)^\alpha \leq \nu_j^\alpha + \|J\|^\alpha$.

Then we obtain that $|\mu_j^\alpha - \nu_j^\alpha| \leq \|J\|^\alpha$.

2. $\nu_j < \left(1 + \alpha^{\frac{1}{1-\alpha}}\right) \|J\| < 2\|J\|$. In this case, $|\mu_j^\alpha - \nu_j^\alpha| \leq |\mu_j|^\alpha + |\nu_j|^\alpha \leq |\nu_j + \|J\||^\alpha + |\nu_j|^\alpha < (3^\alpha + 2^\alpha) \|J\|^\alpha < 5\|J\|^\alpha$.

These yield that

$$|\text{tr}(A^\alpha) - \text{tr}(B^\alpha)| = \left| \sum_{j=1}^N \mu_j^\alpha - \sum_{j=1}^N \nu_j^\alpha \right| \leq \sum_{j=1}^r |\mu_j^\alpha - \nu_j^\alpha| \leq 5r \|J\|^\alpha.$$

□

By Lemma 4.6, we have

$$\begin{aligned} \left| \text{tr} \left(\left(A_1 \sigma^{[\beta]} \rho \sigma^{[\beta]} A_1^\dagger \right)^\alpha \right) - \text{tr} \left(\left(\frac{1}{4} \sigma^\beta \rho \sigma^\beta \right)^\alpha \right) \right| &\leq 5r \left\| A_1 \sigma^{[\beta]} \rho \sigma^{[\beta]} A_1^\dagger - \frac{1}{4} \sigma^\beta \rho \sigma^\beta \right\|^\alpha \\ &\leq \Theta \left(r \left(\varepsilon_1 + \delta_1^{\{\beta\}} \right)^\alpha \right). \end{aligned}$$

Step 3. Introducing a parameter ε_3 , by Lemma 2.15, we can compute \tilde{p} such that $|\tilde{p} - \text{tr}(A_2)| \leq \varepsilon_3$, using $O\left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)$ queries to U_2 , where $B = \Theta\left(\delta_2^{1-\alpha} + r\left(\varepsilon_1 + \delta_1^{\{\beta\}}\right)^\alpha + r(\delta_2 + \varepsilon_2)\right)$ is an upper bound of $\text{tr}(A_2)$. Note that

$$\begin{aligned} \text{tr}(A_2) &\leq \frac{1}{4} \delta_2^{1-\alpha} \text{tr} \left(\left(A_1 \sigma^{[\beta]} \rho \sigma^{[\beta]} A_1^\dagger \right)^\alpha \right) + \Theta(r(\delta_2 + \varepsilon_2)) \\ &\leq \frac{1}{4} \delta_2^{1-\alpha} \left(\text{tr} \left(\left(\frac{1}{4} \sigma^\beta \rho \sigma^\beta \right)^\alpha \right) + \Theta \left(r \left(\varepsilon_1 + \delta_1^{\{\beta\}} \right)^\alpha \right) \right) + \Theta(r(\delta_2 + \varepsilon_2)) \\ &\leq \Theta \left(\delta_2^{1-\alpha} + r \left(\varepsilon_1 + \delta_1^{\{\beta\}} \right)^\alpha + r(\delta_2 + \varepsilon_2) \right). \end{aligned}$$

Step 4. Output $4^{\alpha+1}\delta_2^{\alpha-1}\tilde{p} \approx F_\alpha(\rho, \sigma)$ as the estimation. The additive error is

$$\begin{aligned} |4^{\alpha+1}\delta_2^{\alpha-1}\tilde{p} - F_\alpha(\rho, \sigma)| &\leq 4^{\alpha+1}\delta_2^{\alpha-1}|\tilde{p} - \text{tr}(A_2)| + 4^\alpha \left| \text{tr}(4\delta_2^{\alpha-1}A_2) - \text{tr}\left(\left(A_1\sigma^{[\beta]} \rho \sigma^{[\beta]} A_1^\dagger\right)^\alpha\right) \right| \\ &\quad + 4^\alpha \left| \text{tr}\left(\left(A_1\sigma^{[\beta]} \rho \sigma^{[\beta]} A_1^\dagger\right)^\alpha\right) - \text{tr}\left(\left(\frac{1}{4}\sigma^\beta \rho \sigma^\beta\right)^\alpha\right) \right| \\ &\leq \Theta\left(r\left(\varepsilon_1 + \delta_1^{\{\beta\}}\right)^\alpha + r\delta_2^{\alpha-1}(\varepsilon_2 + \delta_2) + \delta_2^{\alpha-1}\varepsilon_3\right). \end{aligned}$$

In order to make $|4^{\alpha+1}\delta_2^{\alpha-1}\tilde{p} - F_\alpha(\rho, \sigma)| \leq \varepsilon$, it is sufficient to let $\delta_1 = \Theta((\varepsilon/r)^{1/\alpha\{\beta\}})$, $\varepsilon_1 = \Theta((\varepsilon/r)^{1/\alpha\{\beta\}})$, $\delta_2 = \Theta((\varepsilon/r)^{1/\alpha})$, $\varepsilon_2 = \Theta((\varepsilon/r)^{1/\alpha})$ and $\varepsilon_3 = \Theta(\varepsilon^{1/\alpha}/r^{1/\alpha-1})$. Under these conditions, the number of queries to U_σ is

$$O\left(Q_1 Q_2 \left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)\right) = \tilde{O}\left(\frac{r^{\frac{3-\alpha}{2\alpha} + \frac{1}{\alpha\{\beta\}}}}{\varepsilon^{\frac{3+\alpha}{2\alpha} + \frac{1}{\alpha\{\beta\}}}}\right),$$

and the number of queries to U_ρ is

$$O\left(Q_2 \left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)\right) = \tilde{O}\left(\frac{r^{\frac{3-\alpha}{2\alpha}}}{\varepsilon^{\frac{3+\alpha}{2\alpha}}}\right),$$

and the number of elementary quantum gates is

$$O\left(Q_1 Q_2 \left(\frac{\sqrt{B}}{\varepsilon_3} + \frac{1}{\sqrt{\varepsilon_3}}\right)\right) \cdot \text{poly}(n, n_\sigma, n_\rho) = \tilde{O}\left(\frac{r^{\frac{3-\alpha}{2\alpha} + \frac{1}{\alpha\{\beta\}}}}{\varepsilon^{\frac{3+\alpha}{2\alpha} + \frac{1}{\alpha\{\beta\}}}} \text{poly}(n)\right).$$

4.3 Lower Bounds and Hardness

Our quantum algorithms for both fidelity estimation and trace distance estimation requires time complexity polynomial in the rank r of quantum states. Here, we show that unless $\text{BQP} = \text{QSZK}$, there is no quantum algorithm for both fidelity estimation and trace distance estimation with time complexity polylogarithmic in r .

Theorem 4.7. *If there is a quantum algorithm that computes fidelity or trace distance of quantum states of rank $\leq r$ within additive error ε with time complexity $\text{poly}(\log r, 1/\varepsilon)$, then $\text{BQP} = \text{QSZK}$.*

Proof. Here, we recall a decision problem called (α, β) -Quantum State Distinguishability $((\alpha, \beta)$ -QSD). Given U_ρ and U_σ that prepares the purifications of density operators ρ and σ and a promise that either $T(\rho, \sigma) \leq \alpha$ or $T(\rho, \sigma) \geq \beta$, the problem is to determine which is the case. It was shown in [Wat02] that (α, β) -QSD is QSZK-complete if $0 \leq \alpha < \beta^2 \leq 1$.

If there is a quantum algorithm for computing trace distance with time complexity $\text{poly}(\log r, 1/\varepsilon)$, then we can distinguish the two cases with time complexity $\text{poly}(n)$ by letting $r = 2^n$ be the dimension of the two quantum states and $\varepsilon = (\beta - \alpha)/2 > 0$.

If there is a quantum algorithm for computing fidelity with time complexity $\text{poly}(\log r, 1/\varepsilon)$, then we can distinguish the two cases with time complexity $\text{poly}(n)$ by letting $r = 2^n$ be the dimension of the two quantum states and $\varepsilon = \left((1 - \alpha) - \sqrt{1 - \beta^2}\right)/2 > 0$. This is because $T(\rho, \sigma) \leq \alpha$ implies $F(\rho, \sigma) \geq 1 - \alpha$, and $T(\rho, \sigma) \geq \beta$ implies $F(\rho, \sigma) \leq \sqrt{1 - \beta^2}$. Then (α, β) -QSD is reduced to distinguish which is the case with promise that either $F(\rho, \sigma) \leq \sqrt{1 - \beta^2}$ and $F(\rho, \sigma) \geq 1 - \alpha$. \square

Our quantum algorithms for estimating the fidelity and trace distance achieve a significant speedup under the low-rank assumption. One might wonder whether our algorithms can be “de-quantized” through quantum-inspired low-rank techniques such as [Tan19, GLT18, CGL⁺20]. To this end, we point out the hardness of estimating fidelity and trace distance as follows.

Theorem 4.8. *Computing the fidelity and trace distance are DQC1-hard, even for pure quantum states.*

Proof. It was already proved in [CPCC20] that estimating the fidelity is DQC1-hard, even for pure quantum states. Here, we reduce the problem of estimating the fidelity to that of estimating the trace distance, and therefore show the DQC1-hardness of estimating the trace distance.

For any two pure quantum states $\psi = |\psi\rangle\langle\psi|$ and $\phi = |\phi\rangle\langle\phi|$, their trace distance is essentially

$$T(\psi, \phi) = \sqrt{1 - (F(\psi, \phi))^2}.$$

Therefore, any algorithm that computes the trace distance $T(\psi, \phi)$ will immediately yield the fidelity $F(\psi, \phi) = \sqrt{1 - (T(\psi, \phi))^2}$. As a result, estimating the trace distance is DQC1-hard even for pure quantum states. \square

It was shown in [FKM⁺18] that DQC1 is not (classically) weakly simulatable unless the polynomial hierarchy collapses to the second level, i.e., PH = AM. This, together with Theorem 4.8, means that there is unlikely an efficient classical algorithm that estimates the fidelity or trace distance.

Acknowledgements

We would like to thank Wang Fang, Kean Chen and Minbo Gao for helpful discussions.

References

- [AISW19] J. Acharya, I. Issa, N. V. Shende, and A. B. Wagne. Measuring quantum entropy. In *2019 IEEE International Symposium on Information Theory*, pages 3012–3016, 2019.
- [ALL21] A. Anshu, Z. Landau, and Y. Liu. Distributed quantum inner product estimation. ArXiv e-prints, 2021. arXiv:2111.03273.
- [Amb04] A. Ambainis. Quantum walk algorithm for element distinctness. In *Proceedings of the 45th IEEE Symposium on Foundations of Computer Science*, pages 22–31, 2004.
- [ARSW21] R. Agarwal, S. Rethinasamy, K. Sharma, and M. M. Wilde. Estimating distinguishability measures on quantum computers. ArXiv e-prints, 2021. arXiv:2108.08406.
- [Aud07] K. M. R. Audenaert. Subadditivity of q -entropies for $q > 1$. *Journal of Mathematical Physics*, 48(8):083507, 2007.
- [BCC⁺15] D. W. Berry, A. M. Childs, R. Cleve, R. Kothari, and R. D. Somma. Simulating Hamiltonian dynamics with a truncated Taylor series. *Physical Review Letters*, 114:090502, 2015.
- [BCK15] D. W. Berry, A. M. Childs, and R. Kothari. Hamiltonian simulation with nearly optimal dependence on all parameters. In *Proceedings of the 56th Annual IEEE Symposium on Foundations of Computer Science*, pages 792–809, 2015.

- [BCWdW01] H. Buhrman, R. Cleve, J. Watrous, and R. de Wolf. Quantum fingerprinting. *Physical Review Letters*, 87(16):167902, 2001.
- [BDKR05] T. Batu, S. Dasgupta, R. Kumar, and R. Rubinfeld. The complexity of approximating the entropy. *SIAM Journal on Computing*, 35(1):132–150, 2005.
- [BFF⁺01] T. Batu, E. Fischer, L. Fortnow, R. Kumar, R. Rubinfeld, and P. White. Testing random variables for independence and identity. In *Proceedings of the 42nd IEEE Symposium on Foundations of Computer Science*, pages 442–451, 2001.
- [BFR⁺00] T. Batu, L. Fortnow, R. Rubinfeld, W. D. Smith, and P. White. Testing that distributions are close. In *Proceedings of the 41st Annual Symposium on Foundations of Computer Science*, pages 259–269, 2000.
- [BFR⁺13] T. Batu, L. Fortnow, R. Rubinfeld, W. D. Smith, and P. White. Testing closeness of discrete distributions. *Journal of the ACM*, 60(1):1–25, 2013.
- [BGK15] C. Butucea, M. Guță, and T. Kypraios. Spectral thresholding quantum tomography for low rank states. *New Journal of Physics*, 17:113050, 2015.
- [BHH11] S. Bravyi, A. W. Harrow, and A. Hassidim. Quantum algorithms for testing properties of distributions. *IEEE Transactions on Information Theory*, 57(6):3971–3981, 2011.
- [BHMT02] G. Brassard, P. Høyer, M. Mosca, and A. Tapp. Quantum amplitude amplification and estimation. *Quantum Computation and Information*, 305:53–74, 2002.
- [BKL⁺19] F. G. S. L. Brandão, A. Kalev, T. Li, C. Y.-Y. Lin, K. M. Svore, and X. Wu. Quantum SDP solvers: Large speed-ups, optimality, and applications to quantum learning. In *Proceedings of the 46th International Colloquium on Automata, Languages and Programming*, pages 27:1–27:14, 2019.
- [BKR04] T. Batu, R. Kumar, and R. Rubinfeld. Sublinear algorithms for testing monotone and unimodal distributions. In *Proceedings of the 36th Annual ACM Symposium on Theory of Computing*, pages 381–390, 2004.
- [BKT20] M. Bun, R. Kothari, and J. Thaler. The polynomial method strikes back: Tight quantum query bounds via dual polynomials. *Theory of Computing*, 16(10):1–71, 2020.
- [BOW19] C. Bădescu, R. O’Donnell, and J. Wright. Quantum state certification. In *Proceedings of the 51st ACM Symposium on Theory of Computing*, pages 503–514, 2019.
- [CDVV14] S. Chan, I. Diakonikolas, P. Valiant, and G. Valiant. Optimal algorithms for testing closeness of discrete distributions. In *Proceedings of the 2014 Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 1193–1203, 2014.
- [CFMdW10] S. Chakraborty, E. Fischer, A. Matsliah, and R. de Wolf. New results on quantum property testing. In *Proceedings of the 30th International Conference on Foundations of Software Technology and Theoretical Computer Science*, volume 8, pages 145–156, 2010.

- [CGJ19] S. Chakraborty, A. Gilyén, and S. Jeffery. The power of block-encoded matrix powers: improved regression techniques via faster hamiltonian simulation. In *Proceedings of the 46th International Colloquium on Automata, Languages, and Programming*, pages 33:1–33:14, 2019.
- [CGL⁺20] N. Chia, A. Gilyén, T. Li, H. Lin, E. Tang, and C. Wang. Sampling-based sublinear low-rank matrix arithmetic framework for dequantizing quantum machine learning. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, pages 387–400, 2020.
- [CKS17] A. M. Childs, R. Kothari, and R. D. Somma. Quantum algorithm for systems of linear equations with exponentially improved dependence on precision. *SIAM Journal on Computing*, 46(6):1920–1950, 2017.
- [CPCC20] M. Cerezo, A. Poremba, L. Cincio, and P. J. Coles. Variational quantum fidelity estimation. *Quantum*, 4:248, 2020.
- [CSZW20] R. Chen, Z. Song, X. Zhao, and X. Wang. Variational quantum algorithms for trace distance and fidelity estimation. ArXiv e-prints, 2020. arXiv:2012.05768.
- [CW12] A. M. Childs and N. Wiebe. Hamiltonian simulation using linear combinations of unitary operations. *Quantum Information & Computation*, 12(11-12):901–924, 2012.
- [Dat09] N. Datta. Min- and max-relative entropies and a new entanglement monotone. *IEEE Transactions on Information Theory*, 55(6):2816–2826, 2009.
- [DK16] I. Diakonikolas and D. M. Kane. A new approach for testing properties of discrete distributions. In *Proceedings of the 57nd IEEE Symposium on Foundations of Computer Science*, pages 685–694, 2016.
- [EAO⁺02] A. K. Ekert, C. M. Alves, D. K. L. Oi, M. Horodecki, P. Horodecki, and L. C. Kwak. Direct estimations of linear and nonlinear functionals of a quantum state. *Physical Review Letters*, 88(21):217901, 2002.
- [EHC22] N. Ezzell, Z. Holmes, and P. J. Coles. The quantum low-rank approximation problem. ArXiv e-prints, 2022. arXiv:2203.00811.
- [FKM⁺18] K. Fujii, H. Kobayashi, T. Morimae, H. Nishimura, S. Tamate, and S. Tani. Impossibility of classically simulating one-clean-qubit model with multiplicative error. *Physical Review Letters*, 120:200502, 2018.
- [GHS21] T. Gur, M. Hsieh, and S. Subramanian. Sublinear quantum algorithms for estimating von Neumann entropy. ArXiv e-prints, 2021. arXiv:2111.11139.
- [Gil19] A. Gilyén. *Quantum Singular Value Transformation & Its Algorithmic Applications*. dissertation, University of Amsterdam, 2019.
- [GL20] A. Gilyén and T. Li. Distributional property testing in a quantum world. In *Proceedings of the 11th Innovations in Theoretical Computer Science Conference*, volume 151, pages 25:1–25:19, 2020.
- [GLF⁺10] D. Gross, Y. K. Liu, S. T. Flammia, S. Becker, and J. Eisert. Quantum state tomography via compressed sensing. *Physical Review Letters*, 105(15):150401, 2010.

- [GLM⁺20] A. Gilyén, S. Lloyd, I. Marvian, Y. Quek, and M. M. Wilde. Quantum algorithm for Petz recovery channels and pretty good measurement. ArXiv e-prints, 2020. arXiv:2006.16924.
- [GLT18] A. Gilyén, S. Lloyd, and E. Tang. Quantum-inspired low-rank stochastic regression with logarithmic dependence on the dimension. ArXiv e-prints, 2018. arXiv:1811.04909.
- [GP22] A. Gilyén and A. Poremba. Improved quantum algorithms for fidelity estimation. ArXiv e-prints, 2022. arXiv:2203.15993.
- [Gro96] L. K. Grover. A fast quantum mechanical algorithm for database search. In *Proceedings of the Twenty-eighth Annual ACM Symposium on Theory of Computing*, pages 212–219, 1996.
- [GSLW19] A. Gilyén, Y. Su, G. H. Low, and N. Wiebe. Quantum singular value transformation and beyond: exponential improvements for quantum matrix arithmetics. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing*, pages 193–204, 2019.
- [HHJ⁺17] J. Haah, A. W. Harrow, Z. Ji, X. Wu, and N. Yu. Sample-optimal tomography of quantum states. *IEEE Transactions on Information Theory*, 63(9):5628–5641, 2017.
- [HHL09] A. W. Harrow, A. Hassidim, and S. Lloyd. Quantum algorithm for linear systems of equations. *Physical Review Letters*, 103(15):150502, 2009.
- [HY06] X. Hu and Z. Ye. Generalized quantum entropy. *Journal of mathematical physics*, 47(2):023502, 2006.
- [Joz94] R. Jozsa. Fidelity for mixed quantum states. *Journal of Modern Optics*, 41(12):2315–2323, 1994.
- [JVHW15] J. Jiao, K. Venkat, Y. Han, and T. Weissman. Minimax estimation of functionals of discrete distributions. *IEEE Transactions on Information Theory*, 61(5):2835–2885, 2015.
- [KL51] S. Kullback and R. A. Leibler. On information and sufficiency. *Annals of Mathematical Statistics*, 22(1):79–86, 1951.
- [KLL⁺17] S. Kimmel, C. Y. Lin, G. H. Low, M. Ozols, and T. J. Yoder. Hamiltonian simulation with optimal sample complexity. *npj Quantum Information*, 3(1):1–7, 2017.
- [KMW21] M. Kieferová, C. O. Marrero, and N. Wiebe. Quantum generative training using Rényi divergences. ArXiv e-prints, 2021. arXiv:2106.09567.
- [Kot14] R. Kothari. *Efficient algorithms in quantum query complexity*. PhD thesis, University of Waterloo, 2014.
- [KRS09] R. König, R. Renner, and C. Schnaffer. The operational meaning of min- and max-entropy. *IEEE Transactions on Information Theory*, 55(9):4337–4347, 2009.
- [Kuz21] A. R. Kuzmak. Measuring distance between quantum states on a quantum computer. *Quantum Information Processing*, 20:269, 2021.

- [LBDP⁺20] S. Lloyd, S. Bosch, G. De Palma, B. Kiani, Z.-W. Liu, M. Marvian, P. Reberntrost, and D. M. Arvidsson-Shukur. Quantum polar decomposition algorithm. ArXiv e-prints, 2020. arXiv:2006.00841.
- [LC17] G. H. Low and I. L. Chuang. Optimal Hamiltonian simulation by quantum signal processing. *Physical Review Letters*, 118(1):010501, 2017.
- [LC19] G. H. Low and I. L. Chuang. Hamiltonian simulation by qubitization. *Quantum*, 3:163, 2019.
- [LKAS⁺21] S. Lloyd, B. T. Kiani, D. M. Arvidsson-Shukur, S. Bosch, G. De Palma, W. M. Kaminsky, Z.-W. Liu, and M. Marvian. Hamiltonian singular value transformation and inverse block encoding. ArXiv e-prints, 2021. arXiv:2104.01410.
- [LMR14] S. Lloyd, M. Mohseni, and P. Reberntrost. Quantum principal component analysis. *Nature Physics*, 10:631–633, 2014.
- [LMW13] N. Linden, M. Mosonyi, and A. Winter. The structure of Rényi entropic inequalities. *Proceedings of the Royal Society A Mathematical, Physical, and Engineering Science*, 469(2158):20120737, 2013.
- [LW19] T. Li and X. Wu. Quantum query complexity of entropy estimation. *IEEE Transactions on Information Theory*, 65(5):2899–2921, 2019.
- [MdW16] A. Montanaro and R. de Wolf. A survey of quantum property testing. *Theory of Computing Library, Graduate Surveys*, 7:1–81, 2016.
- [MLDS⁺13] M. Müller-Lennert, F. Dupuis, O. Szehr, S. Fehr, and M. Tomamichel. On quantum Rényi entropies: A new generalization and some properties. *Journal of Mathematical Physics*, 54(12):122203, 2013.
- [Mon15] A. Montanaro. Quantum speedup of Monte Carlo methods. *Proceedings of the Royal Society A*, 471(2181):20150301, 2015.
- [NC10] M. A. Nielsen and I. L. Chuang. *Quantum Computation and Quantum Information*. Cambridge University Press, 2010.
- [OP04] M. Ohya and D. Petz. *Quantum Entropy and Its Use*. Springer Science & Business Media, 2004.
- [OW15] R. O’Donnell and J. Wright. Quantum spectrum testing. In *Proceedings of the 47th ACM Symposium on Theory of Computing*, pages 529–538, 2015.
- [OW16] R. O’Donnell and J. Wright. Efficient quantum tomography. In *Proceedings of the 48th ACM Symposium on Theory of Computing*, pages 899–912, 2016.
- [OW17] R. O’Donnell and J. Wright. Efficient quantum tomography II. In *Proceedings of the 49th ACM Symposium on Theory of Computing*, pages 962–974, 2017.
- [Pan03] L. Paninski. Estimation of entropy and mutual information. *Neural Computation*, 15(6):1191–1253, 2003.
- [Pan04] L. Paninski. Estimating entropy on m bins given fewer than m samples. *IEEE Transactions on Information Theory*, 50(9):2200–2203, 2004.

- [Pan08] L. Paninski. A coincidence-based test for uniformity given very sparsely sampled discrete data. *IEEE Transactions on Information Theory*, 54(10):4750–4755, 2008.
- [PV15] D. Petz and D. Virosztek. Some inequalities for quantum tsallis entropy related to the strong subadditivity. *Mathematical Inequalities and Applications*, 18(2):555–568, 2015.
- [QR21] Y. Quek and P. Rebertost. Fast algorithm for quantum polar decomposition, pretty-good measurements, and the procrustes problem. ArXiv e-prints, 2021. arXiv:2106.07634.
- [Ras11] A. E. Rastegin. Some general properties of unified entropies. *Journal of Statistical Physics*, 143:1120–1135, 2011.
- [Rén61] A. Rényi. On measures of entropy and information. *University of California Press, Berkeley, California*, 1:547–561, 1961.
- [RSML18] P. Rebertost, A. Steffens, I. Marvian, and S. Lloyd. Quantum singular-value decomposition of nonsparse low-rank matrices. *Physical Review A*, 97(1):012327, 2018.
- [SH21] S. Subramanian and M. Hsieh. Quantum algorithm for estimating α -Rényi entropies of quantum states. *Physical Review A*, 104(2):022428, 2021.
- [Sha48] C. E. Shannon. A mathematical theory of communication. *Bell System Technical Journal*, 27:379–423, 1948.
- [SOG⁺02] R. D. Somma, G. Ortiz, J. E. Gubernatis, E. Knill, and R. Laflamme. Simulating physical phenomena by quantum networks. *Physical Review A*, 65:042323, 2002.
- [Sze04] M. Szegedy. Quantum speed-up of Markov chain based algorithms. In *Proceedings of the 45th IEEE Symposium on Foundations of Computer Science*, pages 32–41, 2004.
- [Tan19] E. Tang. A quantum-inspired classical algorithm for recommendation systems. In *Proceedings of the 51st Annual Symposium on Theory of Computing*, pages 219–228, 2019.
- [Tsa88] C. Tsalli. Possible generalization of Boltzmann-Gibbs statistics. *Journal of Statistical Physics*, 52(2):479–487, 1988.
- [TV21] K. C. Tan and T. Volkoff. Variational quantum algorithms to estimate rank, quantum entropies, fidelity, and fisher information via purity minimization. *Physical Review Research*, 3(3):033251, 2021.
- [vAG19] J. van Apeldoorn and A. Gilyén. Improvements in quantum SDP-solving with applications. In *Proceedings of the 46th International Colloquium on Automata, Languages, and Programming*, pages 99:1–99:15, 2019.
- [vDH02] W. van Dam and P. Hayden. Rényi-entropic bounds on quantum communication. ArXiv e-prints, 2002. arXiv:quant-ph/0204093.
- [vN32] J. von Neumann. *Mathematische Grundlagen der Quantenmechanik (Mathematical Foundations of Quantum Mechanics)*. Princeton University Press, 1932.

- [VV11a] G. Valiant and P. Valiant. Estimating the unseen: an $n/\log(n)$ -sample estimator for entropy and support size, shown optimal via new CLTs. In *Proceedings of the 43rd Annual ACM Symposium on Theory of Computing*, pages 685–694, 2011.
- [VV11b] G. Valiant and P. Valiant. The power of linear estimators. In *Proceedings of the 52nd Annual Symposium on Foundations of Computer Science*, pages 403–412, 2011.
- [Wat02] J. Watrous. Limits on the power of quantum statistical zero-knowledge. In *Proceedings of the 43rd Annual IEEE Symposium on Foundations of Computer Science*, pages 459–468, 2002.
- [Wey12] Hermann Weyl. Das asymptotische verteilungsgesetz der eigenwerte linearer partieller differentialgleichungen (mit einer anwendung auf die theorie der hohlraumstrahlung). *Mathematische Annalen*, 71(4):441–479, 1912.
- [WWY14] M. M. Wilde, A. Winter, and D. Yang. Strong converse for the classical capacity of entanglement-breaking and Hadamard channels via a sandwiched Rényi relative entropy. *Communications in Mathematical Physics*, 331(2):593–622, 2014.
- [WY16] Y. Wu and P. Yang. Minimax rates of entropy estimation on large alphabets via best polynomial approximation. *IEEE Transactions on Information Theory*, 62(6):3702–3720, 2016.
- [WZC⁺21] Q. S. Wang, Z. C. Zhang, K. A. Chen, J. Guan, W. Fang, and M. S. Ying. Quantum algorithm for fidelity estimation. ArXiv e-prints, 2021. arXiv:2103.09076.
- [WZW22] Y. Wang, B. Zhao, and X. Wang. Quantum algorithms for estimating quantum entropies. ArXiv e-prints, 2022. arXiv:2203.02386.
- [Yu21] N. K. Yu. Sample efficient identity testing and independence testing of quantum states. In *12th Innovations in Theoretical Computer Science Conference*, volume 185, pages 11:1–11:20, 2021.
- [ZLW⁺21] X. Zhang, M. Luo, Z. Wen, Q. Feng, S. Pang, W. Luo, and X. Zhou. Direct fidelity estimation of quantum states using machine learning. *Physical Review Letters*, 127(13):130503, 2021.