

# GitRank: A Framework to Rank GitHub Repositories

Niranjan Hasabnis

Intel Labs

Santa Clara, California, USA

niranjan.hasabnis@intel.com

## ABSTRACT

Open-source repositories provide wealth of information and are increasingly being used to build artificial intelligence (AI) based systems to solve problems in software engineering. Open-source repositories could be of varying quality levels, and bad-quality repositories could degrade performance of these systems. Evaluating quality of open-source repositories, which is not available directly on code hosting sites such as GitHub, is thus important. In this hackathon, we utilize known code quality measures and GrimoireLab toolkit to implement a framework, named GitRank, to rank open-source repositories on three different criteria. We discuss our findings and preliminary evaluation in this hackathon report.

### ACM Reference Format:

Niranjan Hasabnis. 2022. GitRank: A Framework to Rank GitHub Repositories. In *19th International Conference on Mining Software Repositories (MSR '22)*, May 23–24, 2022, Pittsburgh, PA, USA. ACM, New York, NY, USA, 3 pages. <https://doi.org/10.1145/3524842.3528519>

## 1 INTRODUCTION

Open-source code repositories, such as those hosted on popular hosting sites like GitHub, provide wealth of information about software projects such as team dynamics, project schedule and deliverables, among others [1, 2, 4, 22]. Such information is routinely used by researchers working on problems in the field of software engineering. More recently, researchers working at the intersection of machine learning (or AI) and software engineering are also using such information to build systems that automatically learn to solve problems from data [6, 11–13, 18, 27, 33, 34].

Unfortunately, deriving insights using open-source code repositories could be wrong or misleading because popular hosting sites such as GitHub typically do not indicate quality of code repositories. This could partly be because quality of a repository could be subjective. Nonetheless, measuring code quality a well-researched problem in the field of software engineering, and several, popular source code metrics such as Halstead volume [10], cyclomatic complexity [21], maintainability index [25], etc., exists [17, 19, 20].

Although, a number of frameworks and source code metrics to measure repository/code quality exist [5, 16, 17, 28–30], we could not find publicly-available, open-source implementation of a framework that ranks code repositories on quality. That is why we decided

Category	Description of the measure
Quality	Average Cyclomatic complexity of a repository
	Number of style errors per LoC
	Number of security errors of low severity per SLoC
	Number of security errors of medium severity per SLoC
Maintainability	Number of security errors of high severity per SLoC
	Average maintainability index of a repository
	Number of closed issues and pull requests over last 2 years
	Number of closed issues and pull requests over last 1 year
Popularity	Number of closed issues and pull requests over last 6 months
	Number of closed issues and pull requests over last 1 month
	Number of commits per day
	Number of subscribers per day
	Number of stargazers per day
	Number of forks per day

Table 1: Measures used in GitRank

to build such a framework, named GitRank<sup>1</sup>, in this hackathon. Additionally, GrimoireLab toolkit [3, 9] that is available as a part of this hackathon incentivized such an implementation as it makes retrieving some of the source code metrics easy. We, nonetheless, faced several challenges, which we discuss in this report.

## 2 GITRANK: DESIGN AND IMPLEMENTATION

We now describe our framework to rank open-source repositories based on quality, maintainability, and popularity. In addition to source code quality metrics, GitRank also considers popularity and maintainability metrics (similar to NPM registry [24]). GitRank currently supports ranking of repositories that use C/C++ as their primary language. Nonetheless, the design of our framework is easy to extend to other languages as well. GitRank is implemented in 700 lines of Python code and can be broken down into two phases.

### Phase 1: Obtaining values of metrics for every repository.

Given a set of open-source repositories to be ranked, in the first phase, we obtain values of quality, maintainability, and popularity metrics of every repository individually. Table 1 contains the set of measures that we consider. We use a subset of the typical code measures used in software engineering that are applicable to open-source repositories and are common across a set of languages.

**Cyclomatic complexity.** Cyclomatic complexity of a source code is a well-known metric of the structural code complexity [21]. We use Python APIs of lizard project [31] to obtain function-level cyclomatic complexity and then average it over a repository to obtain repository-level cyclomatic complexity<sup>2</sup>.

**Style errors.** We consider code formatting as a code quality metric and use cpplint project [15] to obtain the number of style errors (of the highest severity level)<sup>3</sup>. We divide the total number of errors

<sup>1</sup> Available at <https://github.com/nirhasabnis/gitrank>

<sup>2</sup> We ended up using lizard API directly as CoCom backend of Graal component in GrimoireLab [3] offered commit-specific code complexity instead of function-level or repository-level complexity.

<sup>3</sup> Graal's CoQua backend does not support obtaining this information for C/C++.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

MSR '22, May 23–24, 2022, Pittsburgh, PA, USA

© 2022 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-1-4503-9303-4/22/05...\$15.00

<https://doi.org/10.1145/3524842.3528519>

## Ranking of repositories

Click the table headers to sort the table accordingly:

repository_owner	repository_uri	overall_score	quality_score	maintainability_score
StarRocks_starrocks	https://github.com/StarRocks/starrocks	81.9	97.9	66.36
ApolloAuto_apollo	https://github.com/ApolloAuto/apollo	77.33	97.96	42.1
Qv2ray_Qv2ray	https://github.com/Qv2ray/Qv2ray	64.51	96.82	35.13
carla-simulator_carla	https://github.com/carla-simulator/carla	55.98	97.26	44.19
rethinkdb_rethinkdb	https://github.com/rethinkdb/rethinkdb	54.93	98.38	35.07
root-project_root	https://github.com/root-project/root	54.57	96.94	61.56
facebook_hhvm	https://github.com/facebook/hhvm	52.82	97.61	36.13

Figure 1: An HTML output of GitRank

by the lines of source code (SLoC) [23] to obtain the error density. Static analysis tools such as `cpplint` are known to suffer from false positives [26], and although, `GitRank` does not account for them right now, we believe that they could be accounted by adjusting the weight assigned to style errors in the overall quality score.

**Security errors.** We also consider security errors to determine code quality. Security issues, however, could be of varying severity levels. In our framework, we consider three severity levels: low, medium, and high. We used `FlawFinder` tool [7] to obtain the security errors in C/C++ programs<sup>4</sup> and divide the total number of errors reported for every level by the lines of source code (SLoC) to obtain the level-specific error density.

**Maintainability index.** Maintainability index is a well-known metric that incorporates a number of traditional source code metrics into a single number that indicates relative ease of maintaining source code [25]. We use the modified formula of MI [32] to obtain MI for individual modules from a repository<sup>5</sup>. MI for a repository is then obtained by averaging over MI for individual modules.

**Closed issues.** We use a combination of GitHub's REST APIs and GrimoireLab's Perceval [8] to obtain the number of closed issues over a period of time (last 2 years, last 1 year, last 6 months, and last 1 month, with increasing importance in that order) from the date of evaluation to determine maintenance activity of a repository. This is because we want to value current maintenance activity more.

**Stars, watches, and forks.** Existing approaches consider GitHub stars, subscriptions, and forks as popularity metrics [4]. We follow the same terminology. We use a combination of GitHub's REST APIs [14] and GrimoireLab's Perceval to obtain this information.

**Phase 2: Obtaining quality, popularity, and maintainability score of repositories.** In the second phase, we compare metrics across repositories to obtain overall score for every repository. Before we calculate scores for all the repositories, we first normalize values of all the measures to the range of 0% (lowest) to 100% (highest). This is performed by obtaining the lowest and the highest value of every measure and computing the position of a value within the range of the lowest and the highest value.

Normalized values of the measures are then used to compute the quality score and the popularity score as a weighted average, with equal weights for all the measures. For the maintainability score, we use different weights for the measures based on their significance<sup>6</sup>. We then compute overall score of a repository as a mean of all three scores. All of these scores are also normalized to the range of 0% (lowest) to 100% (highest).

## 3 EVALUATION

`GitRank` accepts a list of GitHub repositories (their URLs) as input and generates their ranked list as output (in CSV and HTML format). In our preliminary evaluation of `GitRank`, we ranked randomly-selected 500 GitHub repositories that use C++ as primary language. We dropped 12 repositories out of 500 as they had some peculiarities (such as unusual extensions of C++ files) because of which the tools used by `GitRank` could not obtain their metrics.

**Performance.** To support a large number of repositories, we have implemented phase 1 of `GitRank` to be highly-parallel (e.g., multiple machines and/or CPU cores). In our experiment, we divided the list of 500 repositories into 5 separate lists of 100 repositories each and processed them separately on 5 different machines. Phase 1 of `GitRank` took 1 hr and 25 KB of memory, while phase 2, implemented in a serial manner, took 0.1 sec and 1.5 KB of memory.

**Output.** Figure 1 shows the HTML-formatted ranked list of repositories in our experiment. The report also contains next level of details such as quality, maintainability, and popularity scores. Further levels of details (containing values of individual metrics) can be obtained with additional verbosity levels.

## 4 CONCLUSION

In this report, we described our efforts to build `GitRank`, a framework to rank open-source repositories using known source code metrics. So far, `GitRank` supports repositories using C/C++ as their primary languages and uses a combination of GrimoireLab toolkit and publicly-available tools for the implementation. As per our evaluation, `GitRank` is highly-parallel and performs reasonably well on commodity CPUs. We, however, did not explore applications of `GitRank` in this hackathon and consider this as a separate project that we plan to explore in the future.

<sup>4</sup>We used a standalone tool to obtain this information as we found that Graal's CoVuln backend did not support our specific case.

<sup>5</sup>We extend `lizard` project with a plugin to calculate Halstead volume in MI.

<sup>6</sup>We, however, envision that the weights could be adjusted by the `GitRank` user.

## REFERENCES

- [1] Rajiv D. Banker, Gordon B. Davis, and Sandra A. Slaughter. Software development practices, software complexity, and software maintenance performance: A field study. *Manage. Sci.*, apr 1998.
- [2] Christian Bird, Nachiappan Nagappan, Brendan Murphy, Harald Gall, and Premkumar Devanbu. Don't Touch My Code! Examining the Effects of Ownership on Software Quality. In *Proceedings of the 19th ACM SIGSOFT Symposium and the 13th European Conference on Foundations of Software Engineering*, ESEC/FSE '11, 2011.
- [3] Bitergia Inc. GrimoireLab: Free, Libre, Open Source Tools for Software Development Analytics. Available at <https://chaoss.github.io/grimoirelab/>.
- [4] Hudson Borges and Marco Tulio Valente. What's in a GitHub Star? Understanding Repository Starring Practices in a Social Coding Platform. *CoRR*, abs/1811.07643, 2018.
- [5] Kyriakos Chatzidimitriou, Michail Papamichail, Themistoklis Diamantopoulos, Michail Tsapanos, and Andreas Symeonidis. npm-Miner: An Infrastructure for Measuring the Quality of the npm Registry. In *2018 IEEE/ACM 15th International Conference on Mining Software Repositories (MSR)*, 2018.
- [6] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating Large Language Models Trained on Code. 2021.
- [7] David Wheeler. FlawFinder. Available at <https://dhwheeler.com/flawfinder>.
- [8] Santiago Dueñas, Valerio Cosentino, Gregorio Robles, and Jesus M Gonzalez-Barahona. Perceval: software project data at your will. In *Proceedings of the 40th International Conference on Software Engineering: Companion Proceedings*, pages 1–4. ACM, 2018.
- [9] Santiago Dueñas, Valerio Cosentino, Jesus M. Gonzalez-Barahona, Alvaro del Castillo San Felix, Daniel Izquierdo-Cortazar, Luis Cañas-Díaz, and Alberto Pérez García-Plaza. GrimoireLab: A toolset for software development analytics. 7(e601).
- [10] Maurice H. Halstead. *Elements of Software Science (Operating and Programming Systems Series)*. Elsevier Science Inc., USA, 1977.
- [11] Niranjana Hasabnis and Justin Gottschlich. ControlFlag: A Self-Supervised Idiosyncratic Pattern Detection System for Software Control Structures. In *Proceedings of the 5th ACM SIGPLAN International Symposium on Machine Programming*, MAPS 2021, 2021.
- [12] Niranjana Hasabnis and R Sekar. Extracting Instruction Semantics via Symbolic Execution of Code Generators. In *Proceedings of the 24th ACM SIGSOFT International Symposium on Foundations of Software Engineering*, FSE, 2016.
- [13] Niranjana Hasabnis and R. Sekar. Lifting Assembly to Intermediate Representation: A Novel Approach Leveraging Compilers. In *Proceedings of the Twenty-First International Conference on Architectural Support for Programming Languages and Operating Systems*, ASPLOS, 2016.
- [14] GitHub Inc. GitHub REST API. Available at <https://docs.github.com/en/rest>.
- [15] Google Inc. cpplint - static code checker for C++. Available at <https://github.com/cpplint/cpplint>.
- [16] ISO. ISO/IEC 25000:5000. Available at <https://www.iso.org/standard/35683.html>.
- [17] Oskar Jarczyk, Błażej Gruska, Szymon Jaroszewicz, Leszek Bukowski, and Adam Wierzbicki. *GitHub Projects. Quality Analysis of Open-Source Software*. Springer International Publishing, Cham, 2014.
- [18] Sifei Luan, Di Yang, Celeste Barnaby, Koushik Sen, and Satish Chandra. Aroma: Code Recommendation via Structural Code Search. *Proceedings of the ACM on Programming Languages*, 2019.
- [19] Jeremy Ludwig and Devin Cline. CBR Insight: Measure and Visualize Source Code Quality. In *2019 IEEE/ACM International Conference on Technical Debt (TechDebt)*. IEEE, 2019.
- [20] Jeremy Ludwig, Steven Xu, and Frederick Webber. Compiling Static Software Metrics for Reliability and Maintainability from GitHub Repositories. In *2017 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, 2017.
- [21] T.J. McCabe. A Complexity Measure. *IEEE Transactions on Software Engineering*, SE-2(4):308–320, 1976.
- [22] Nuthan Munaiah, Steven Kroh, Craig Cabrey, and Meiyappan Nagappan. Curating Github for Engineered Software Projects. *Empirical Software Engineering*, 2017.
- [23] Vu Nguyen, Sophia Deeds-rubin, Thomas Tan, and Barry Boehm. A SLOC Counting Standard. In *COCOMO II Forum*, 2007.
- [24] NPM, Inc. NPM. Available at <https://www.npmjs.com/>.
- [25] P. Oman and J. Hagemeyer. Metrics for Assessing a Software System's Maintainability. In *Proceedings Conference on Software Maintenance 1992*, 1992.
- [26] Sebastiano Panichella, Venera Arnaoudova, Massimiliano Di Penta, and Giuliano Antoniol. Would static analysis tools help developers with code reviews? In *2015 IEEE 22nd International Conference on Software Analysis, Evolution, and Reengineering (SANER)*, pages 161–170, 2015.
- [27] Baptiste Roziere, Marie-Anne Lachaux, Lowik Chanussot, and Guillaume Lample. Unsupervised Translation of Programming Languages. *Advances in Neural Information Processing Systems*, 2020.
- [28] Ioannis Samoladas, Georgios Gousios, Diomidis Spinellis, and Ioannis Stamelos. The SQO-OSS Quality Model: Measurement Based Open Source Software Evaluation. In Barbara Russo, Ernesto Damiani, Scott Hissam, Björn Lundell, and Giancarlo Succi, editors, *Open Source Development, Communities and Quality*, Boston, MA, 2008. Springer US.
- [29] Diomidis Spinellis, Georgios Gousios, Vassilios Karakoidas, Panagiotis Louridas, Paul Adams, Ioannis Samoladas, and Ioannis Stamelos. Evaluating the Quality of Open Source Software. *Electr. Notes Theor. Comput. Sci.*, 03 2009.
- [30] Ioannis Stamelos, Lefteris Angelis, Apostolos Oikonomou, and Georgios L. Bleris. Code Quality Analysis in Open Source Software Development. *Information Systems Journal*, 2002.
- [31] Terry Yin and other contributors. A Simple Code Complexity Analyser. Available at <https://github.com/terryyin/lizard>.
- [32] Kurt D. Welker, Paul W. Oman, and Gerald G. Atkinson. Development and Application of an Automated Source Code Maintainability Index. *Journal of Software Maintenance*, may 1997.
- [33] Michihiro Yasunaga and Percy Liang. Graph-based, Self-supervised Program Repair from Diagnostic Feedback. In *International Conference on Machine Learning (ICML)*, 2020.
- [34] Fangke Ye, Shengtian Zhou, Anand Venkat, Ryan Marucs, Nesime Tatbul, Jesmin Jahan Tithi, Niranjana Hasabnis, Paul Petersen, Timothy Mattson, Tim Kraska, Pradeep Dubey, Vivek Sarkar, and Justin Gottschlich. MISIM: An End-to-End Neural Code Similarity System. *arXiv preprint arXiv:2006.05265*, 2020.