COUNTERGEDI: A controllable approach to generate polite, detoxified and emotional counterspeech

Punyajoy Saha¹, Kanishk Singh¹, Adarsh Kumar¹, Binny Mathew¹ and Animesh Mukherjee ¹ Indian Institute of Technology, Kharagpur, India

{punyajoys,kanishksingh,adarshkumar712,binnymathew}@iitkgp.ac.in, animeshm@cse.iitkgp.ac.in

Abstract

Recently, many studies have tried to create generation models to assist counter speakers by providing counterspeech suggestions for combating the explosive proliferation of online hate. However, since these suggestions are from a vanilla generation model, they might not include the appropriate properties required to counter a particular hate speech instance. In this paper, we propose COUN-TERGEDI - an ensemble of generative discriminators (GEDI) to guide the generation of a DialoGPT model toward more polite, detoxified, and emotionally laden counterspeech. We generate counterspeech using three datasets and observe significant improvement across different attribute scores. The politeness and detoxification scores increased by around 15% and 6% respectively, while the emotion in the counterspeech increased by at least 10% across all the datasets. We also experiment with triple-attribute control and observe significant improvement over single attribute results when combining complementing attributes, e.g., politeness, joyfulness and detoxification. In all these experiments, the relevancy of the generated text does not deteriorate due to the application of these controls.

1 Introduction

One of the most effective strategies to combat the rising online hate speech is *counterspeech*. It is a direct response to hateful or harmful speech that seeks to undermine it. Several organisations like Facebook¹ have laid out guidelines for general public on how to counter hateful speech online. While these guidelines might be effective, writing a proper counterspeech is quite challenging [Fumagalli, 2020]. Recently, many non-profit organisations have taken up the task of countering online hate². This nichesourcing of counterspeech can be effective but might be a mentally taxing task for the NGO operators given the amount of hate generated each day [Vidgen *et al.*, 2019]. To assist these operators, the scientific community have come up with different human-in-the-loop methods to collect counterspeech data [Fanton *et al.*, 2021] as well as build models to generate counterspeech suggestions [Zhu and Bhat, 2021].

Such generation models aim to reduce the human intervention by helping the counter speakers with suggestions³, which they can further post-edit as per requirements. While these recent transformer based generation models can produce relevant outputs, they often fail to produce diverse output [Holtzman et al., 2020]. Further, we cannot control the generated output for any attribute from the vanilla generation model. However, as pointed out by different authors [Bartlett and Krasodomski-Jones, 2015], counterspeech can vary based on the hate speech instance, demography of the hate and counter speakers [Mathew et al., 2019] etc. Hence, the generation models without any control might produce suggestions that are not suitable for a particular instance. To counter effectively, the counter speakers should have the control over the generated content so that they can steer the counterspeech toward a desired property or a mixture of different properties. Such a generation model will allow the counter speaker to use different strategies to counter hate [Benesch et al., 2016]. In this paper, we propose six different GEDI⁴ models and use them in single and multiple attribute setting to guide the generation of a vanilla counterspeech generation model for English language. We observe that —

- The single attribute GEDI models improve the controlled attribute significantly for all the attributes. Specifically, there is 15% increase in politeness and 6% increase in detoxification.
- Among the GEDI with emotional attributes, *joy* has the highest attribute scores with an improvement of 15%, 17% and 88% in Gab [Qian *et al.*, 2019], Reddit [Qian *et al.*, 2019], and CONAN [Chung *et al.*, 2019] datasets respectively.
- While combining multiple attributes politeness, detoxification and joyfulness (one of the emotional attribute) for controlling the generation, we observe a further increase in scores compared to the single attribute setup.
- We are able to maintain the relevancy of the generated

¹https://counterspeech.fb.com/en/

²https://wecounterhate.com/

³We view the counterspeech generating task as delicate task which requires human supervision.

⁴Generative discirimintators.

- output measured using **BLEU-2** score while there is a slight drop in performance in terms of fluency which comes as a cost for the additional control.
- Finally, human judges also marked higher presence of the attributes in the attribute controlled setups compared to the baselines.

We show examples of emotion controlled counter speech corresponding to a hate speech in Table 1. Please refer to Appendix for more examples on single and multi attribute controlled counterspeech. The code is added here⁵.

Hate speech	Anyone who isn't a re***ded pickle has privilege, I sup-
	pose.
Counterspeech	The R word is highly offensive, Spread the word to end the
(no control)	word!
Counterspeech	in the words of my favorite friend this post sounds like such
(sad)	hate speech. it makes you sound uneducated. how sad. do
	not use internet powers to silence your anger with some-
	thing so simple or even reasonable!
Counterspeech	we all believe in open mindedness, whether your side of the
(joy)	fence is greater or lesser. we hope you have fun! mwahaha
	peace out and cool weather. keep hydrated npcs.

Table 1: This table presents an example hate speech and the counterspeech generated using different control attributes which is marked in the (bracket). Please refer to the Appendix for more examples on single and multi attribute controlled counterspeech.

2 Related works

With regard to countering hatred, we focus on two research aspects relevant to the present work (i) counterspeech datasets and models for counterspeech generation (ii) controlling methods for generation models particularly in NLP.

Counterspeech generation strategies: An effective strategy to mitigate hate speech is counterspeech as it does not violate freedom of expression [Benesch et al., 2016]. While the idea of countering some hateful messages is not new, the research community has recently started taking a massive interest in understanding counterspeech practices and its effectiveness while mitigating hate speech [Mathew et al., 2019]. Recently, Tekiroğlu et al. proposed novel techniques to generate counterspeech using a GPT-2 model with postfacto editing by experts or annotator groups. One of the recent generation methods uses a three stage pipeline - Generate, Prune and Select (GPS) to generate diverse and relevant counterspeech output [Zhu and Bhat, 2021]. The primary challenge in counterspeech generation research is understanding if the counterspeech produced is effective. One study[Bartlett and Krasodomski-Jones, 2015] found that effectiveness of the counterspeech further depends on the tone of the counterspeech. In specific, sentimental or casual tone received 83% more responses [Frenett and Dow, 2015]. In addition to that, Mathew et al. found that different communities find different types of counterspeech effective. In this work, we present a novel approach to guide the counterspeech toward one or more desired properties. This is done by building a controllable counterspeech generation pipeline based on GEDI.

Controllable text generation: Controllable text generation is the task of generating natural sentences whose attributes

can be controlled. The previous approaches rely on reinforcement learning or training conditional generative models [Prabhumoye *et al.*, 2020]. One of the earliest line of work focused on controlling a desired attribute by side constraints [Sennrich *et al.*,] and back propagating gradients [Dathathri *et al.*, 2019]. One of the variations - DEXPERTS [Liu *et al.*, 2021] uses language models for both positive and negative classes. While the other variation - GEDI [Krause *et al.*, 2020] uses class conditioned language models for positive and negative classes. The final output tokens in both these methods are generated based on an equation which utilises the contrast between the positive and the negative class.

We, in this work, use this GEDI model and apply it to the domain of counterspeech generation. We train different GEDI models to control attributes like *politeness*, *emotions* and *detoxification* of counterspeech.

3 Models

DialoGPT: We used a variant of the GPT model - DialoGPT [Zhang *et al.*, 2020] which was trained on a large corpus consisting of English Reddit dialogues. The corpus consist of 147 million instances of dialogues, collected over a period of 12 years. Unlike GPT-2, this model should generate better dialouge like responses to any given prompt. In this model, along with ground truth response $T = x_1, ..., x_n$ we also have a dialogue utterance history S. The model aims at maximising $p(T|S) = p(x_1|S) \prod_{i=2}^n p(x_i|S, ..., x_{i-1})$. For our experiment, we used DialoGPTm - a 24 layer, 345 million weight parameters transformer model⁶ and finetune over a particular dataset having hate and counterspeech pairs.

Generate Prune Select (GPS): One of the recent counterspeech generation model is Generate, Prune, Select (GPS) - a three stage pipelined approach [Zhu and Bhat, 2021]. At first, the generation part generates a large number of diverse response candidates using a generative model based on RNN based autoencoder. Second, the pruning part prunes the ungrammatical candidates from the candidate pool. This is done using a classifier trained on linguistic acceptability classifier. Finally, the response-selection part selects appropriate responses based on the hate speech instance. We use the similarity based method *USE-LARGE-SIM* [Zhu and Bhat, 2021]. GEDI: For controlling generated counterspeech, we use a recent method Generative Discriminators (GEDI) [Krause et al., 2020], where the authors present a decoding time algorithm to control the output from the generation model. GEDI assumes we have class conditioned language model (CC-LM) with a desired control code c and an undesired control code \bar{c} . For our case, we fix the control code c as 'true' and \bar{c} as 'false'. For each dataset, the attribute mentioned in the +vecolumn in Table 3 is considered as desired, while -ve column is used as undesired attribute.

The authors use the contrast between $P_{\theta}(x_{1:t}|c)$ and $P_{\theta}(x_{1:t}|\bar{c})$ to guide sampling from an LM that gives $P_{LM}(x_{1:T})$. The probability that the next token x_t belongs to desired class is calculated using this contrast.

⁵https://github.com/hate-alert/CounterGEDI

⁶https://huggingface.co/microsoft/DialoGPT-medium

For controlled generation, the authors propose a simple method to guide the model toward the target class which is represented using the heuristic equation 1 where ω is controllable parameter. In order to control multiple attributes, we extend the heuristic as represented in equation 2 where ω_i is a controllable parameter to bias the generation toward class c_i for GEDI trained on the i^{th} attribute.

$$P_{w}\left(x_{t} \mid x_{< t}, c\right) \propto P_{LM}\left(x_{t} \mid x_{< t}\right) P_{\theta}\left(c \mid x_{t}, x_{< t}\right)^{\omega} \tag{1}$$

$$P_{w}(x_{t} \mid x_{< t}, c_{1}, ... c_{n}) \propto P_{LM}(x_{t} \mid x_{< t}) \prod_{i=1,...,n} P_{\theta}(c_{i} \mid x_{t}, x_{< t})^{\omega_{i}}$$
(2)

4 Datasets

Counterspeech datasets: In order to evaluate our approach we use three public datasets which contain hate speech and its corresponding counterspeech. The details of these datasets are noted in Table 2. Reddit and Gab datasets contain 5, 257 and 14, 614 hate speech instances respectively [Qian et al., 2019]. We use the English part of the CONAN dataset [Chung et al., 2019] which contains 408 hate speech instances. The counterspeech in Gab and Reddit datasets were written by AMT workers, whereas for CONAN the counterspeech was written by expert NGO operators.

We further made hate speech and counterspeech pairs from these datasets such that each hate speech was associated with one counterspeech. Finally, we ended up with 3,864, 14,223, 41,580 datapoints for CONAN, Reddit and Gab respectively. We split each dataset randomly into train, validation, test set with 80% for training, 10% each for validation and testing.

Dataset	Source-H	Source-C	Hate instances	Total pairs
CONAN	synthetic	expert	408	3,864
Reddit	reddit	crowd	5,257	14,223
Gab	gab	crowd	14,614	41,580

Table 2: This table presents the source of hate speech (Source-H), source of counterspeech (Source-C), hate speech instances and the total pairs for each of the CONAN, Reddit and Gab dataset.

Attribute datasets: We control several attributes in the generated counterspeech. We selected these attributes following the recommended strategies for counterspeech [Benesch *et al.*, 2016] and properties of responses in human conversation [Clark *et al.*, 2019].

Politeness: One of the properties of counterspeech as suggested by [Benesch *et al.*, 2016] is empathy. As a first step in that direction we tried to make the generated counterspeech more polite. We used the dataset of 1.39 million posts released by [Madaan *et al.*, 2020] labelled into nine politeness classes (P1-P9). As recommended by the authors, we considered P9 as the polite part and others (P1-P8) as non-polite.

Detoxification: [Benesch et al., 2016] also noted several strategies which are discouraged while writing counterspeech. One of these discouraged strategies are hostile or aggressive behaviour. To detox any hostile counterspeech generated by the generation model, we use the a popular Kaggle

dataset⁷ which contains text samples having 'toxic' and 'nontoxic' labels. We stratified-split the released training dataset randomly into 90% training and 10% validation sets. The test set is already released separately with the dataset. We trained a GEDI model considering toxic as the positive label and nontoxic as the negative label. While generating using GEDI, we guide the generation toward the negative class (non-toxic). Emotion: Another important aspect of conversation is communicating different emotions. A study [Prendinger and Ishizuka, 2005] found that systems expressing emotions are more capable of providing user satisfaction. In case of counterspeech, emotions might enhance the effect of the generated counterspeech [Benesch et al., 2016]. For example, 'sadness' as an emotion can be added when the counter speakers affiliate themselves with the target group. Similarly, 'joy' can used to convey positivity in the counterspeech.

In order to control the emotion while generating a counterspeech, we used a large dataset [Saravia et al., 2018] of 416,809 datapoints comprising posts having seven emotions – 'sadness', 'joy', 'fear', 'anger', 'surprise', and 'love'. For this paper, we did not consider - 'love' and 'surprise' emotions as these had less than 10% posts in the dataset. We stratified-split each dataset randomly into training, validation, and test set with 80% for training, and 10% for both validation and testing. We consider each emotion as a separate attribute and trained a GEDI model for that emotion by considering it as positive label and other emotions as negative labels. For our experiments, we primarily focus on guiding the models toward the positive class.

A summary statistic of the attribute dataset for each of the task considered is noted in Table 3.

Dataset	+ve	-ve	T _r (%+ve)	V (%+ve)	T _e (%+ve)
Polite	p	n-p	1.12M (20%)	137k (20%)	137k (20%)
Toxic	t	n-t	143k (10%)	16k (10%)	153k (4%)
	j	0	333k (34%)	42k (34%)	42k (34%)
Emotion	f	0	333k (11%)	42k (11%)	42k (11%)
Emotion	s	О	333k (29%)	42k (29%)	42k (29%)
	a	o	333k (14%)	42k (14%)	42k (14%)

Table 3: This table shows the attribute datasets, positive and negative classes and data present in train, validation and test part for each. T_r : Train, V: Validation, T_e : Test, p: polite, n-p: non-polite, t: toxic, n-t: non-toxic, s: sadness, j: joy, a: anger, f: fear, o: others. The % associated with the T_r , V and T_e are the % of positive labels.

5 Experimental setup

Counterspeech generation models: The DialoGPTm model for each counterspeech model has six initial layers fixed due to resource constraints. The model were trained till 10 epochs with batch size as 8. We saved the final model at the epoch having the best language modelling loss for the validation dataset. We used a maximum length of 256 tokens for the DialoGPTm model⁸. The learning rate is fixed at $5e^{-6}$ for training the model.

GEDI models: We train the GPT-2 model as the GEDI models based on the training setting specified in the original paper [Krause *et al.*, 2020]. For each model we fix the batch

⁷https://www.kaggle.com/c/jigsaw-toxic-comment-classification-challenge/data

⁸1% datapoints have more than 256 tokens.




Figure 1: The figure shows how the overall setup of the pipeline. The counterspeech generation model is produces a probability distribution for the next possible token using hate speech+ counterspeech generated till now. The GEDI models individually take in the currently generated counter speech and produces a probability distribution for the next possible token based on the desired attributes. The output token selector selects the next output token. The unperturbed part in the counterspeech is created without any control, to provide the initial prompt to the GEDI model.

size at 8 and train the models for 5 epochs. The λ weight in the loss equation is fixed at 0.8 to maximise generation quality for the GEDI model. We used a maximum length of 128 tokens for the GPT-2 model. The learning rate is fixed at $2e^{-5}$ for training the model following the recommendations by [Krause *et al.*, 2020].

Final pipeline: Our final pipeline comprises three parts as shown in Figure 1. The part A represents the vanilla counterspeech generation model trained on one of the three counterspeech datasets. Similar to an auto-regressive setup, it takes in the hate speech with the currently generated counterspeech (empty at the initial step) and produces next token probablities for the production of the next token. The part B consists of the single or multiple GEDI models. Each GEDI model controls an attribute out of the total six. It takes as input the currently generated counterspeech and produces token probabilities based on the desired attribute. We initially allow the counterspeech generation models to generate 10 tokens without any control to provide the initial prompt to the GEDI model. Finally, part C selects the next token based on the token probabilities from different models, i.e., the counterspeech generation model and the GEDI models following equation 2. For each GEDI model, we primarily control the weight (ω) as mentioned in equation 1, while other parameters are kept same as the paper [Krause et al., 2020]. For single attribute, we fix the weight at 1 to give equal importance to the counterspeech generation as well as the control attributes. For two attribute control, we set weights at 0.5 for both the attributes. For three attributes control, which comprises detoxification, politeness and an emotion, we set 0.3 for politeness & detoxification each and 0.4 for the emotion. We also use nucleus sampling as a decoding strategy [Holtzman et al., 2020]. Please check Appendix for more details.

6 Evaluation

We consider several metrics to evaluate our whole pipeline of controlled counterspeech generation. The *generation metrics* measure the generation capability of the DialoGPTm and

GEDI models. The *classification metrics* are mainly to evaluate the GEDI model on the attribute datasets. Finally, we measure the amount of control in the generated counterspeech using external classifiers which we refer to as *controller metrics*. We generate 5 samples for every hate speech instance with DialoGPTm. The GPS framework automatically selects the best response based on the heuristic, hence we keep one sample for every hate speech instance.

Generation metrics: To measure the generation quality, we use different standard metrics. We use *BLEU-2*⁹ and *ME-TEOR* [Sai *et al.*, 2020] to measure how similar the generated counterspeech are to the ground truth counterspeech. We also measure if the generation model generates a diverse and novel counterspeech using metrics from previous research [Wang and Wan, 2018]. To measure fluency, we use a classifier of linguistic acceptability trained on the COLA dataset [Warstadt and Bowman, 2019]

GEDI metrics: For classification, we report *accuracy*, *macro F1-score*, and *AUROC* score for each GEDI model's performance on a test dataset of a particular attribute. We also report the generation performance using the perplexity [Zhang *et al.*, 2020].

Controller metrics: In order to evaluate the ability of the GEDI controller to control the attribute, we used third-party classifiers for each attribute. For politeness, we trained a bert-base-uncased model for politeness level detection on a scale of 0 to 7¹⁰. For measuring emotion in the generated text, we used the Ekman version of the GoEmotions models¹¹. For each post, it returns a confidence score between 0-1 for anger, disgust, fear, joy, sadness, surprise + neutral. We report the confidence score for a particular emotion as a measure of that emotion in a given post. Finally, to measure toxicity we used the HateXplain model [Mathew *et al.*, 2021] trained on two classes – toxic and non-toxic¹². We report the confidence between 0-1 for the non-toxic class.

7 Results

Generation results: We compare DialoGPTm model with the GPS in Table 4. We find BLEU-2 scores are better for the GPS model while the METEOR scores are better for DialoGPT model for all three datasets. DialoGPTm is also better in terms of novelty and diversity for all the three datasets. The fluency metric COLA is better for GPS for all the three datasets, since it straightforwardly prunes grammatically incorrect samples. Since DialoGPTm presents a competitive performance compared to the state-of-the-art model, we therefore use DialoGPTm for the rest of the experiments. GEDI metrics: As reported in Table 5, we find that F1-score and AUCROC scores for politeness and all the four emotions are above 0.9. This highlights that even with 0.2 as the weight for the discriminator we are able to get good scores on classification. The perplexity scores for all the test datasets are

⁹converted to a scale of 0-100 from 0-1

¹⁰https://github.com/AlafateABULIMITI/politeness-detection

¹¹https://huggingface.co/monologg/bert-base-cased-goemotions-ekman

¹²https://huggingface.co/Hate-speech-CNERG/bert-base-uncased-hatexplain-rationale-two

Model	B2 (†)	COLA (†)	M (†)	N (†)	D (†)		
	CONAN						
GPS	41.5	0.82	0.14	0.18	0.60		
DialoGPTm	12.7	0.78	0.18	0.84	0.80		
	Reddit						
GPS	14.1	0.82	0.11	0.30	0.47		
DialoGPTm	6.9	0.75	0.17	0.82	0.74		
Gab							
GPS	13.9	0.82	0.12	0.15	0.41		
DialoGPTm	7.7	0.80	0.17	0.80	0.72		

Table 4: Evaluation results for the three datasets. We report BLEU-2 (B2), COLA, METEOR (M), novelty (N) and diversity (D) to compare the two baselines: generate-prune-select (GPS) framework and DialoGPTm. For all metrics, higher is better and **bold** denotes the best scores.

also around 3.5^{13} . GEDI model for toxicity has lower scores than the other attribute tasks. The F1-score for toxicity detection is ~ 0.6 and AUCROC is ~ 0.83 . The perplexity is also higher at around 4.5 for the toxicity dataset. This highlights the difficulty of the task of detecting toxicity.

Dataset	Positive	F1 (↑)	Acc (†)	AUC(↑)	Perplexity (↓)
Toxicity	toxic	0.60	0.85	0.84	4.428
Politeness	polite	0.93	0.96	0.93	3.476
Emotion	joy	0.96	0.96	0.97	3.546
Emotion	sadness	0.98	0.98	0.99	3.543
Emotion	fear	0.94	0.97	0.98	3.774
Emotion	anger	0.96	0.98	0.99	3.560

Table 5: GEDI generation and classification performance on test set of attribute datasets. Generation is evaluated using the Perplexity whereas classification performance is measured using F1-score (F1), Accuracy (Acc) and AUCROC (AUC). For all the metrics except perplexity, higher is better.

Single-attribute control: In Table 6, we report the amount of different attributes present in the generated counterspeech for each dataset and for each model. When we compare GPS and DialoGPTm, we find that except anger emotion, all other scores are significantly higher for DialoGPTm. Second, using control for a particular attribute significantly improves the presence of that attribute (p-value <0.001). For instance, in Table 6, the politeness score increases from 3.91 to 4.54, from 5.24 to 6.05 and 5.14 to 6.11 for CONAN, Reddit and Gab respectively when the DialoGPTm model is controlled for politeness. This is true for all attributes barring the 'anger' emotion. Politeness and detoxification score increased by 15-18% and 6-8% respectively across all the datasets. For the emotion attributes, 'joy' has the highest scores among all for both controlled and uncontrolled attribute. We see an overall increase in 'joy' of around 17% for Gab, 14% for Reddit and 88% for CONAN. Counter responses in CONAN datasets are mostly devoid of any emotions hence bringing a change in them is much easier than the Reddit/Gab datasets which are higher in terms of the joy attribute. We reach closer to GPS baseline for anger emotion while controlling anger emotion and increase the score by 54%, 55% and 16% for Reddit, Gab and CO-NAN, respectively. While the increase for other emotions – 'sadness' and 'fear' increased significantly, the overall scores for them remain low.

Multi-attribute control: We also generate counterspeech with the DialoGPTm with mutli-attribute control. We keep

Model	D (†)	P (†)	J (†)	A (†)	S (†)	F (†)		
	CONAN							
GPS	0.68	2.01	0.16	0.12	0.03	0.01		
DialoGPTm	0.64	3.91	0.18	0.09	0.04	0.01		
DialoGPTm-c	0.68	4.54	0.34	0.11	0.08	0.05		
	Reddit							
GPS	0.82	1.62	0.23	0.32	0.04	0.01		
DialoGPTm	0.82	5.24	0.63	0.17	0.06	0.00		
DialoGPTm-c	0.87	6.05	0.72	0.27	0.10	0.02		
	Gab							
GPS	0.79	1.46	0.22	0.28	0.04	0.01		
DialoGPTm	0.81	5.14	0.66	0.17	0.05	0.00		
DialoGPTm-c	0.85	6.11	0.77	0.26	0.10	0.02		

Table 6: Performance of single attribute setups with the vanilla baseline generate-prune-select (GPS) and DialoGPTm models. Each column name represents the attribute being measured. The attributes measured are politeness (P), detoxification (D), sadness (S), joy (J), anger (A) and fear (F). Politeness (P) is measured in a scale of 0-7 whereas others are measured in the scale [0, 1]. For the last row - controlled DialoG-PTm (DialoGPTm-c) the column name also represents the attribute getting controlled. For all the metrics, higher is better and **bold** denotes the best scores.

Scores	Detox	Polite	Joy	Anger	Sadness	Fear	
			CONAN				
BLEU-2	13.8	12.1	12.2	11.6	12.0	12.8	
COLA	0.83	0.72	0.72	0.74	0.76	0.72	
	Reddit						
BLEU-2	8.1	7.8	7.7	7.8	7.5	7.3	
COLA	0.72	0.77	0.70	0.72	0.81	0.70	
Gab							
BLEU-2	8.7	8.3	8.5	8.3	8.2	8.3	
COLA	0.85	0.82	0.76	0.76	0.80	0.78	

Table 7: BLEU-2 and COLA performance for single attribute setups for DialoGPTmc model. Each column name represents the individual attribute model namely politeness (P), detoxification (D), sadness (S), joy (J), anger (A) and fear (F). **Bold** denotes the best scores across the row

politeness, detoxification and one of the emotion¹⁴ as control attributes. This gives us four variations for each dataset. We then measure the individual attribute scores for each of these three attribute and report the results in Table 8. For detoxification scores, the setup - joy+polite+detox outperforms other setups across all the experiment. This setup even outperforms the single-attribute detoxification setup by 8%, 2% and 2% for CONAN, Reddit and Gab, respectively. For politeness score, the best performance occurs for joy + polite + detoxsetup for CONAN and Reddit dataset, while the setup fear + polite + detox performs better in case of the Gab dataset. Compared to single attribute setup for politeness, the politeness scores drop across all the multi-attribute setups. Among the emotions, the attribute score for 'joy' in a multi-attribute setting outperforms the single attribute setting by 44%, 13% and 10% for CONAN, Reddit and Gab. For 'anger', the scores in multi-attribute setting decrease around 25-30% when compared to the single attribute setting. For other attributes like 'sadness' and 'fear', the multi-attribute results are below 0.1, similar to the single attribute results. Please also see Appendix for attribute ablation performances. Quality of controlled generation: In the previous section, we observed that we were able to control attributes in generated outputs in single and multi-attribute setups. While this is encouraging, it is important to understand if the controlled text are losing the central theme of remaining a counterspeech and are still fluent. For the former, we measure the BLEU-2

¹³For reference, perplexity for pretraining GPT-2 comes around 10 after 10K steps (https://tinyurl.com/3vwrvscd).

¹⁴One among 'joy', 'anger', 'fear' and 'sad'.

metric and for the latter we use the COLA metric.

According to Table 7, we find that relevance of the output (measured using BLEU-2) does not change much across different attributes for the single attribute setups. For some of the attributes like detoxification, the BLEU-2 scores even outperform the DialoGPTm model (without control) for all the datasets as noted in column B2 in Table 4. For Reddit and Gab, there is a further improvement of 1-2 points in the BLEU-2 metric for other attributes also as compared to the vanilla DialogGPTm model (in column B2 in Table 4). This shows that the controls do not affect the overall relevance of the generated counterspeech. In fact, the relevance improves in many cases. In terms of fluency, we see a slight drop which comes as a cost for controlling different attributes except few cases (comparing column COLA in Table 4 and Table 7). This might be due to the fact that GEDI model is not geared toward maintaining the fluency of the models. The observation holds for the multi attribute setup as well (comparing columns B2 and COLA in Table 4 and Table 8).

Overall, we observe that it is possible to control the attributes in the generated outputs using the single attributes. Our experiments with multi-attributes further reveals that there are certain complementing attributes for e.g joy + polite + detox which can be used to further increase the single-attributes setups. For other setups, the attribute scores drops below the single attribute setups. Another promising observation is that the control of attribute does not harm the relevance of the generated output as they still remain close to the ground truth. Since GEDI is not geared toward improving the fluency, we see a slight drop in the fluency of the generated outputs. An interesting research direction would be to look into improving attribute and fluency scores while using multi-attribute setups. We have added examples of single and multi-attribute setup in the Appendix.

Attributes	Detox(↑)	Polite(↑)	Emotion(↑)	B2 (↑)	COLA(†)		
	CONAN						
Joy(J)+P+D	0.74	4.13	0.49 (J)	13.4	0.79		
Anger(A)+P+D	0.67	3.06	0.08 (A)	12.6	0.68		
Sad(S)+P+D	0.70	3.56	0.07 (S)	13.2	0.74		
Fear(F)+P+D	0.70	4.00	0.06 (F)	13.6	0.75		
		Redd	it	•			
Joy+P+D	0.89	5.79	0.82 (J)	8.3	0.81		
Anger+P+D	0.85	4.24	0.19 (A)	8.3	0.72		
Sad+P+D	0.87	3.56	0.09 (S)	8.2	0.79		
Fear+P+D	0.87	4.00	0.01 (F)	7.8	0.79		
		Gab)				
Joy+P+D	0.87	5.68	0.85 (J)	8.8	0.85		
Anger+P+D	0.83	4.11	0.19 (A)	8.5	0.75		
Sad+P+D	0.85	4.70	0.09 (S)	8.8	0.84		
Fear+P+D	0.86	5.82	0.01 (F)	8.8	0.83		

Table 8: Results of controlling three attributes – politeness, detoxification and one of the emotions in a multi-attribute setting. The columns represent the amount of the attribute present for each setup. The column – *emotion* represents the score of the emotion shown in the parenthesis that is being controlled for that instance. BLEU(B2) and COLA were also reported for different setups. For all metrics, higher is better and **bold** denotes the best scores.

Human evaluation: In order to understand, if the improvement in the attribute scores across (while controlling different attributes) would be visible to the moderators, we perform a human evaluation on the generated counterspeech. In this experiment, an annotator is shown three sentences - one gen-

Model	Polite (†)	Joy (†)	Anger (†)	Sad (†)	Fear (†)		
CONAN							
GPS	0.50	1.30	2.50	1.00	0.00		
DGPTm	0.59	2.50	3.00	0.75	0.75		
DGPTm-c	2.00	1.00	4.00	1.00	2.00		
	Reddit						
GPS	1.83	0.93	1.50	0.33	0.36		
DGPTm	2.66	2.50	1.50	0.66	1.33		
DGPTm-c	3.50	3.33	2.00	2.00	1.25		
Gab							
GPS	1.56	1.28	0.81	0.4	0.17		
DGPTm	2.17	2.50	1.66	1.11	0.89		
DGPTm-c	3.21	2.92	1.90	2.03	1.00		

Table 9: Average human judgement scores (scale 0-5) for each of the models – GPS, DialoGPTm and controlled DialoGPTm (DGPTm). Each column represents the attribute that DialoGPTm-c (DGPTm-c) is controlled for. For all the metrics, higher is better and **bold** indicates best scores.

erated from the GPS pipeline, another generated using DialoGPTm model and finally, one generated using the DialoG-PTm model where some attribute x was getting controlled. We hide the type of model from which the post was generated and further shuffle the posts to remove any ordering bias. Next, the annotator was asked to mark the amount of the attribute x in the given three posts on a scale of 0-5 where 0 presents the absence of the attribute while 5 corresponds to the highest presence of that attribute. Five annotators participated in the annotation with each post getting marked by two annotators. The annotators annotated 20 randomly selected triplets per dataset for each attribute. We do not include the detoxification attribute for these experiments as there is very little difference in detoxification scores when comparing the baseline and the controlled setups. For more details about the annotations, please refer to the Appendix.

We observe an improvement in most of the attribute scores for the controlled model over the two baselines. Three cases where the improvement is not present is while controlling 'joy' and 'sad' for the CONAN dataset and controlling 'fear' for Reddit dataset. While controlling attribute 'sad', we only see an improvement relative to the base DialoGPTm model. The summary of this experiment is presented in the Table 9.

8 Conclusion and future work

Our research aims to add controllable parameters to counterspeech generation setup which can help the moderators to tune the counterspeech toward a particular strategy. Our controllable GEDI models for six different attribute shows significant improvement in the attribute scores over the baselines. We also try to control the generation using multi-attribute and find that the attribute scores can increase further if suitable attributes are mixed together.

In the future, we plan to add other attributes like 'hope' [Palakodety *et al.*, 2020] to the controllable generation pipeline. Finally, we would aim to build a counterspeech suggestion tool around this setup and allow counter speakers (NGO operators/moderators) to control the generation output as per their query attribute(s).

Ethical impact

Hate speech is a complex phenomenon. While the language generation methods are better than before, it is still very far from generating coherent and meaningful replies [Bender et al., 2021]. Hence, we advocate against deployment of fully automatic pipelines for countering hate speech [de los Riscos and D'Haro, 2021]. Based on the current progress, in this pipeline, an active participation of the counter speakers is required to generate relevant counterspeech. This automation, in turn, has the potential to reduce the mental toll of the counter speakers, at least partially.

References

- [Bartlett and Krasodomski-Jones, 2015] Jamie Bartlett and Alex Krasodomski-Jones. Counter-speech examining content that challenges extremism online. *DEMOS*, *October*, 2015.
- [Bender et al., 2021] Emily M. Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. On the dangers of stochastic parrots: Can language models be too big? In FAccT, 2021
- [Benesch et al., 2016] Susan Benesch, Derek Ruths, Kelly P Dillon, Haji Mohammad Saleem, and Lucas Wright. Considerations for successful counterspeech. A report for Public Safety Canada under the Kanishka Project. Accessed November, 25:2020, 2016.
- [Chung et al., 2019] Yi-Ling Chung, Elizaveta Kuzmenko, Serra Sinem Tekiroglu, and Marco Guerini. Conan-counter narratives through nichesourcing: a multilingual dataset of responses to fight online hate speech. In ACL, 2019.
- [Clark et al., 2019] Leigh Clark, Nadia Pantidi, Orla Cooney, Philip Doyle, Diego Garaialde, Justin Edwards, Brendan Spillane, Emer Gilmartin, Christine Murad, Cosmin Munteanu, Vincent Wade, and Benjamin R. Cowan. What Makes a Good Conversation? Challenges in Designing Truly Conversational Agents. ACM, 2019.
- [Dathathri *et al.*, 2019] Sumanth Dathathri, Andrea Madotto, Janice Lan, Jane Hung, Eric Frank, Piero Molino, Jason Yosinski, and Rosanne Liu. Plug and play language models: A simple approach to controlled text generation. In *ICLP*, 2019.
- [de los Riscos and D'Haro, 2021] Agustín Manuel de los Riscos and Luis Fernando D'Haro. *ToxicBot: A Conversational Agent to Fight Online Hate Speech*. 2021.
- [Fanton *et al.*, 2021] Margherita Fanton, Helena Bonaldi, Serra Sinem Tekiroğlu, and Marco Guerini. Human-in-the-loop for data collection: a multi-target counter narrative dataset to fight online hate speech. In *NAACL*, 2021.
- [Frenett and Dow, 2015] Ross Frenett and Moli Dow. One to one online interventions: A pilot eve methodology. *Institute for Strategic Dialogue*, 2015.
- [Fumagalli, 2020] Corrado Fumagalli. Counterspeech and ordinary citizens: How? when? *Political Theory*, page 0090591720984724, 2020.
- [Holtzman et al., 2020] Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. The curious case of neural text degeneration. In ICLP, 2020.
- [Krause et al., 2020] Ben Krause, Akhilesh Deepak Gotmare, Bryan McCann, Nitish Shirish Keskar, Shafiq Joty, Richard Socher, and Nazneen Fatema Rajani. Gedi: Generative discriminator guided sequence generation. arXiv preprint arXiv:2009.06367, 2020.
- [Liu et al., 2021] Alisa Liu, Maarten Sap, Ximing Lu, Swabha Swayamdipta, Chandra Bhagavatula, Noah A. Smith, and Yejin Choi. DExperts: Decoding-time controlled text generation with experts and anti-experts. In ACL-IJCNLP, 2021.

- [Madaan et al., 2020] Aman Madaan, Amrith Setlur, Tanmay Parekh, Barnabás Póczos, Graham Neubig, Yiming Yang, Ruslan Salakhutdinov, Alan W Black, and Shrimai Prabhumoye. Politeness transfer: A tag and generate approach. In ACL, 2020.
- [Mathew et al., 2019] Binny Mathew, Punyajoy Saha, Hardik Tharad, Subham Rajgaria, Prajwal Singhania, Suman Kalyan Maity, Pawan Goyal, and Animesh Mukherjee. Thou shalt not hate: Countering online hate speech. In ICWSM, 2019.
- [Mathew et al., 2021] Binny Mathew, Punyajoy Saha, Seid Muhie Yimam, Chris Biemann, Pawan Goyal, and Animesh Mukherjee. Hatexplain: A benchmark dataset for explainable hate speech detection. In AAAI, 2021.
- [Palakodety et al., 2020] Shriphani Palakodety, Ashiqur R Khud-aBukhsh, and Jaime G Carbonell. Hope speech detection: A computational analysis of the voice of peace. In ECAI 2020, pages 1881–1889. IOS Press, 2020.
- [Prabhumoye *et al.*, 2020] Shrimai Prabhumoye, Alan W Black, and Ruslan Salakhutdinov. Exploring controllable text generation techniques. *arXiv preprint arXiv:2005.01822*, 2020.
- [Prendinger and Ishizuka, 2005] Helmut Prendinger and Mitsuru Ishizuka. The empathic companion: A character-based interface that addresses users' affective states. *App. AI*, 2005.
- [Qian et al., 2019] Jing Qian, Anna Bethke, Yinyin Liu, Elizabeth Belding, and William Yang Wang. A benchmark dataset for learning to intervene in online hate speech. In EMNLP-IJCNLP, 2019
- [Sai et al., 2020] Ananya B Sai, Akash Kumar Mohankumar, and Mitesh M Khapra. A survey of evaluation metrics used for nlg systems. arXiv preprint arXiv:2008.12009, 2020.
- [Saravia et al., 2018] Elvis Saravia, Hsien-Chi Toby Liu, Yen-Hao Huang, Junlin Wu, and Yi-Shin Chen. Carer: Contextualized affect representations for emotion recognition. In EMNLP, 2018.
- [Sennrich *et al.*,] Rico Sennrich, Barry Haddow, and Alexandra Birch. Controlling politeness in neural machine translation via side constraints. In *NAACL 2016*.
- [Tekiroğlu *et al.*, 2020] Serra Sinem Tekiroğlu, Yi-Ling Chung, and Marco Guerini. Generating counter narratives against online hate speech: Data and strategies. In *ACL*, 2020.
- [Vidgen et al., 2019] Bertie Vidgen, Helen Margetts, and Alex Harris. How much online abuse is there. Alan Turing Institute, 2019.
- [Wang and Wan, 2018] Ke Wang and Xiaojun Wan. Sentigan: Generating sentimental texts via mixture adversarial networks. In *IJ-CAI*, 2018.
- [Warstadt and Bowman, 2019] Alex Warstadt and Samuel R Bowman. Linguistic analysis of pretrained sentence encoders with acceptability judgments. *arXiv preprint arXiv:1901.03438*, 2019.
- [Zhang et al., 2020] Yizhe Zhang, Siqi Sun, Michel Galley, Yen-Chun Chen, Chris Brockett, Xiang Gao, Jianfeng Gao, Jingjing Liu, and William B Dolan. Dialogpt: Large-scale generative pretraining for conversational response generation. In ACL: System Demonstrations, 2020.
- [Zhu and Bhat, 2021] Wanzheng Zhu and Suma Bhat. Generate, prune, select: A pipeline for counterspeech generation against online hate speech. *arXiv* preprint arXiv:2106.01625, 2021.

A Ablation study

In order to further understand the influence of each attribute, we perform an ablation study on the multi-attribute setups. For each setup,

we remove an attribute and generate the sentences for the other two attributes. Finally, we measure the score for that removed attribute itself. We report the summary of the results in Table 10 for CO-NAN, Table 11 for Reddit and Table 12 for Gab dataset. When the detox attribute is removed, we do not see much change in the detox-ification score (around 1-2% drop) across all datasets. On the other hand, removal of the politeness attribute decreases the scores massively. We observe an average of 12%, 15% and 14% drops across CONAN, Reddit and Gab datasets respectively.

Among the emotions, when the 'joy' attribute is removed we observe a huge reduction in the attribute score for the CONAN dataset (24%), while for other datasets the drop remains below 10%. Most significant change in the emotion score takes place when removing 'anger' and 'sadness' attributes where the average reduction remains around 40-60% across all the datasets. Finally, when removing 'fear' attribute, we only see a change for CONAN dataset (83%) but other scores remain almost the same.

Attributes	Detox	Polite	Emotion
Joy(J)+Polite	0.73	_	_
Joy+Detox	_	3.44	_
Polite+Detox	_	_	0.37 (J)
Anger(A)+Polite	0.68	_	_
Anger+Detox	_	2.79	_
Polite+Detox	_	_	0.05 (A)
Sad(S)+Polite	0.69	_	_
Sad+Detox	_	3.20	_
Polite+Detox	_	_	0.03 (S)
Fear(F)+Polite	0.70	_	_
Fear+Detox	_	3.30	_
Polite+Detox	_	_	0.01 (F)

Table 10: Results of the ablation study for $DialoGPT_{medium}$ model trained on CONAN dataset. In each of these setups, we remove one of the attribute and re-estimate that attribute's score. The last column – emotion represents the score of the emotion that is being controlled for that instance.

Attributes	Detox	Polite	Emotion
Joy(J)+Polite	0.87	_	_
Joy+Detox	_	5.12	_
Polite+Detox	_	_	0.76 (J)
Anger(A)+Polite	0.82	_	_
Anger+Detox	_	3.46	_
Polite+Detox	_	_	0.09 (A)
Sad(S)+Polite	0.84	_	_
Sad+Detox	_	3.96	_
Polite+Detox	_	_	0.05 (S)
Fear(F)+Polite	0.86	_	
Fear+Detox	_	3.34	_
Polite+Detox	_	_	0.01 (F)

Table 11: Results of the ablation study for $DialoGPT_{medium}$ model trained on Reddit dataset. In each of these setups, we remove one of the attribute and re-estimate that attribute's score. The last column – emotion represents the score of the emotion that is being controlled for that instance.

B Metrics

The diversity [Wang and Wan, 2018] of the given set of generated sentences s is defined in equation 3. ψ is the Jaccard similarity func-

Attributes	Detox	Polite	Emotion
Joy(J)+Polite	0.85	_	_
Joy+Detox	_	5.09	_
Polite+Detox	_	_	0.82 (J)
Anger(A)+Polite	0.80	_	_
Anger+Detox	_	3.41	_
Polite+Detox	_	_	0.08 (A)
Sad(S)+Polite	0.82	_	-
Sad+Detox	_	4.19	_
Polite+Detox	_	_	0.04 (S)
Fear(F)+Polite	0.85	_	-
Fear+Detox	_	4.69	_
Polite+Detox	_	_	0.00 (F)

Table 12: Results of the ablation study for $DialoGPT_{medium}$ model trained on Gab dataset. In each of these setups, we remove one of the attribute and re-estimate that attribute's score. The last column – emotion represents the score of the emotion that is being controlled for that instance.

tion

$$diversity(s) = (1/|s|) * \sum_{i} 1 - max((\psi(s_i, s_j))_{j=1}^{j=|s|, j! = i}$$
 (3)

Finally, we measure the novelty of the generated outputs to understand if the outputs are directly copied from the training dataset or not. We calculate the novelty [Wang and Wan, 2018] using equation 4 where c is the sentence set of training corpus and ψ is the Jaccard similarity function.

$$novelty(s) = (1/|s|) * \sum_{i} 1 - max((\psi(s_i, c_j))_{j=1}^{j=|c|})$$
 (4)

C Other hyperparameters

For the generation module, we fix the maximum generation length at 100 tokens due to resource constraints. No repeat ngram size was kept at 5, repetition penalty was set at 3.5 and temperature for generating output was 1.2. These steps were taken to further enhance the diversity of the samples generated. We also use nucleus sampling as a decoding strategy [Holtzman et al., 2020] with k=0.92 and p=100 to increase the diversity of the outputs.

D Limitations

We rely on the public datasets available for our work. Hence, the generated counterspeech is to some extent based on the properties of the dataset. For example, the CONAN dataset is primarily focused on countering Islamophobic speech. Second, this framework may not directly generalise to more complex type of counterspeech like contradiction or sarcasm.

E Examples of controlled generation

We present examples from controlled counterspeech generation corresponding to few hate speech. 13 and 14 show the generation based on single attribute control, while Tables 15 and 16 show the generated outputs for multi-attribute control.

F System and code requirements

For all the experiments in this paper, we used 48-core Xeon processor Linux based system with 126 GB RAM. For training the neural networks we used 2 NVIDIA P100 GPUs having 16 GB each with

Hate speech	Never break bread with a Quranimal.
	You risk catching HIV and/or Ebola
Counter speech (fear)	How can you expect us to live in peace- ful culture if we are afraid of everything that might come after? how can toler- antism do anything but bring fear? also it means focus on your chosen faith not get influenced by outsiders.
Counterspeech (sadness)	how is having people over spreading it such an issue, could you elaborate on this hatred of the quran for how these disgusting disease spread from us to their home countries. please do! its just so sad indeed. not everyone should tolerate hate like this.
Counterspeech (anger)	So not true. Islam can lead the way to salvation, but no one believes that. We should respect diversity! And you know, curing other peoples diseases? That seems very selfish we should eradicate disease!

Table 13: This table presents an example hate speech and the counterspeech generation using different control attributes which is marked in the (bracket).

Hate speech	wats wrong with being a commie jew? don't you want that high-iq baby inside your nazi womb?.
Counterspeech (politeness)	there is no need to degrade an entire re- ligion based on the actions of a few peo- ple here, please moderate your speech outside of this space and think about how using such language could be hurt- ful or even unfunny. thank you! happy new year!
Counter speech (joy)	its inappropriate to use this word when referring specifically to muslims and can be viewed as racist. please do not use these terms or consider them hurtful. thank you for using better language in the future.
Counterspeech (sad)	making fun of nationality, religion and sexual preference is not kosher in todays world. try rereading them both times just in case they are harmful for you or anyone! first time using words used here makes those hurt even more

Table 14: This table presents an example hate speech and the counter speech generation using different control attributes which is marked in the (bracket).

Hate speech	A black person robbed my friend so fuck you black pieces of shit. One day we will lynch all of you cuz you had it com- ing
Counterspeech (joy + polite)	to use hateful language only shows how intolerant and bigoted you are, in the hopes that you can be more accepting with your experiences. remember to use better language yourself in the future. thank you for your understanding.
Counter speech (anger + polite)	wow. what a hate filled hateful word that should not be used when discussing the color of peoples skin! several such things can contribute to productive discussion, and any further comments could easily be summarized using such words

Table 15: This table presents an example hate speech and the counter speech generation using multi-attributes control, which are marked in the (bracket).

II-4	D 1 41 4 1 1 4
Hate speech	Remember that time a bunch of peo-
	ple kidnapped a retard and tortured him
	live?.
Counter speech	it only happened once but in this in-
(joy + polite)	stance its not ok to use pejoratively
	based on medical conditions if you
	like supporting your opinions further so
	please feel free to vote out any language
	that suggests it may be used. thanks
Counter speech	wow, how racist these comments are. it
(anger + toxic)	actually incredibly disrespectful to gen-
	eralize people based on their race. we
	see plenty of genetic variation among
	people, not just racial variance. let us
	not thank anyone for missing details
Counter speech	i have no idea why you are even posting
(sadness + po-	this. reading through such posts hurt
lite)	deep down inside with fear by where
	your women will cry out from these
	comments when compared to actual vic-
	tims experiences across history s repul-
	sive has good won t it now would yield
	illiberal, whatever issues acusot or mo-
	ronic could look like. alsoplease refrain
	from using mental illness as an insult (
	over here) thanks for the heads up

Table 16: This table presents an example hate speech and the counterspeech generation using multi-attributes control, which are marked in the (bracket).

For the next three text	, On a scale of 0-5,	mark the amount of \${task1}
-------------------------	----------------------	------------------------------

\${text11}	
0-	
\${text12}	
0-	
\${text13}	
0	

For the next three texts, On a scale of 0-5, mark the amount of \${task2}

\${text21}	
\${text22}	
\${text23}	

Figure 2: The interface design for the Amazon Mechanical Turk platform.

CUDA version 10.1. We primarily based our system on Python libraries. Among the neural networks we used Huggingface's transformers library¹⁵ for GPT-2 based models with PyTorch as backend in general. All the libraries used in this research are pip installable. Further we also resort to the code which controls the generation using GEDI models and the code which trains the GEDI models from the authors' git repository¹⁶.

G Human judgement details

The annotators include 2 PhD and 3 BTech students. We consider the definitions and use several examples from the relevant attribute datasets to provide examples to the annotators to help them mark the presence of that attribute in the presented counterspeech. The final interface is shown in Figure 2. We use Amazon Mechanical Turk (AMT) sandbox¹⁷ environment, where the annotators login using their account and annotate the examples.

¹⁵ https://huggingface.co/

¹⁶https://github.com/salesforce/GeDi

¹⁷https://requestersandbox.mturk.com/create/projects