1

On the mechanics of droplet surface crater during impact on immiscible viscous liquid pool

Durbar Roy¹, Sophia M¹, and Saptarshi Basu¹[†]

¹Department of Mechanical Engineering, Indian Institute of Science, Bengaluru, 560012, India

(Received xx; revised xx; accepted xx)

We study drop impacts on immiscible viscous liquid pool and investigate the formation of droplet surface craters using experimental and theoretical analysis. We attribute the formation of air craters to the rapid deceleration of the droplet due to viscous drag force. The droplet response to the external impulsive decelerating force induces oscillatory modes on the surface exposed to the air forming capillary waves that superimpose to form air craters of various shapes and sizes. We introduce a non-dimensional parameter (Γ) , that is, the ratio of drag force to the capillary force acting on the droplet. We show that Γ is directly proportional to the capillary number. We show that droplets forming air craters of significant depths have $\Gamma > 1$. Further, we demonstrate that Legendre polynomials can locally approximate the central air crater jet profile. We also decipher that the air crater response time scale (T) varies as the square root of impact Weber number $(T \sim We^{1/2})$. Further, we generalize the local droplet response with a global response model for low-impact energies based on an eigenvalue problem. We represent the penetrating drop as a constrained Rayleigh drop problem with a dynamic contact line. The air-water interface dynamics is analyzed using an inviscid droplet deformation model for small deformation amplitudes. The local and global droplet response theory conforms with each other and depicts that the deformation profiles could be represented as a linear superposition of eigenmodes in Legendre polynomial basis. We unearth that the droplet response in an immiscible impact system differs from the miscible impact systems due to the presence of such a dynamic contact line.

Key words: Authors should not enter keywords on the manuscript, as these must be chosen by the author during the online submission process and will then be added during the typesetting process (see http://journals.cambridge.org/data/relatedlink/jfm-keywords.pdf for the full list)

1. Introduction

The study of drop impact physics began with the seminal works of Worthington in the late nineteenth century (Worthington 1877; Worthington & Cole 1897) and continues till date due to applications in various industries like manufacturing, printing, food-processing, bio-medical, and pharmaceuticals (Bolleddula *et al.* 2010; Pasandideh-Fard *et al.* 2002; Roy *et al.* 2019). The early pioneering work of Worthington led to the discovery of various spatio-temporal physics during drop impacts on solids and liquids.

Drop impacts on liquids generates aesthetically beautiful patterns like crowns, corona splash, and jets, to name a few (Gekle & Gordillo 2010; Gordillo & Gekle 2010) and are used in various artistic contexts and platforms. The mechanism underlying the beauty is multi-scale and multi-physics in origin and has attracted many scientists and engineers to study drop impacts on liquids theoretically, numerically, and experimentally (Rioboo *et al.* 2001; Sikalo *et al.* 2000; Tropea & Marengo 1999; Roisman & Tropea 2002; Thoraval *et al.* 2012; Renardy *et al.* 2003). With the advent of ultra-high-speed imaging and laser diagnostic techniques (Lauterborn & Vogel 1984; Adrian 1991; Thoroddsen *et al.* 2008; Versluis 2013) the spatio-temporal experimental resolution has increased by orders of magnitude from the early days of drop impact research (Worthington 1877; Worthington & Cole 1897).

A droplet impacting on a liquid media can result in a wide variety of phenomena like splashing, bouncing, coalescence, and formation of jets, corollas, and crowns depending on the impact parameter space characterized by various non-dimensional groups like impact Weber number, Reynolds number, Ohnesorge number, Bond number, Froude number to name a few (Thoroddsen et al. 2011; Yarin et al. 2017). The various nondimensional numbers represent the ratios of various competing effects governing the dynamics of drop impacts. Several phenomena like the formation of flower-like pattern in the liquid film, entrapment of air, generation and propagation of ejecta sheet widen the landscape of possibilities of drop impact physics on liquids (Thoroddsen 2002; Zhang et al. 2012; Marcotte et al. 2019). During the impinging process, just prior to impact, a thin lubricating air layer gets entrapped underneath the droplet (Thoroddsen et al. 2003; Bartolo et al. 2006). The entrapped air between the drop and the liquid must be displaced/drained out before proper contact between the drop and the pool. The pressure in the lubricating air layer is inversely proportional to the air layer thickness and hence increases monotonically till the entrapped air pressure reaches the capillary pressure of the droplet (Thoroddsen et al. 2003; Hicks & Purvis 2010, 2011; Roy et al. 2022). The excess pressure above the capillary pressure causes a dimple to form just beneath the impacting droplet. The air layer ruptures at a point leading to the first local contact of the drop and the formation of entrapped air bubbles. The formation of air bubbles in drop impact systems can be detrimental to specific technologies such as printing, coating, and several cooling applications (Aziz & Chandra 2000; Yarin et al. 2017; Aksoy et al. 2020). However, the entrapment of air bubbles is a boon to aquatic life forms since these entrapped air bubbles are medium of gaseous exchange between the atmosphere and the water bodies that sustain marine life forms (Woolf et al. 2007). For impact on similar liquids, after the initial entrapped air layer rupture phase, the droplet forms an air crater in the liquid layer/pool, collapsing to form Worthington jets. The singularity dynamics and curvature collapse leading to jet erruption on a fluid surface was studied in a seminal work by Zeff et al. (Zeff et al. 2000). Further, in the previous decade, Gekle and Gordillo studied the Worthington jet formed during the impact of a circular disc on water using detailed boundary-integral simulations and analytical modeling (Gekle & Gordillo 2010; Gordillo & Gekle 2010). They discovered that the flow structure inside the jet could be divided into three regions; the acceleration region, ballistic region, and tip region. Majority of the previous study on drop impact on liquids have focused on impacts on similar liquids (Shetabivash et al. 2014; Yarin et al. 2017; Castillo-Orozco et al. 2015; Castrejón-Pita et al. 2016; Hasegawa & Nara 2019). However, literature of drop impact on immiscible pools are relatively sparse (Yakhshi-Tafti et al. 2010; Dhuper et al. 2021; Che & Matar 2018; Minami & Hasegawa 2022). Drop impact on immiscible liquid pools is very important and is found in various industrial, engineering, and natural systems. Droplet interactions in immiscible systems are inherently different, as mentioned

in some of the literature available (Che & Matar 2018). In general, drop impact on liquids produces Worthington jets (Worthington & Cole 1897) on the liquid pool formed due to the collapse of an air crater in the liquid pool. However, we have found that the air craters formed in immiscible impact systems are significantly different from those reported in the literature for miscible liquids. Primarily, the air crater on the surface of the impacting droplet resembles central air craters found in drop impact on superhydrophobic substrates (Yamamoto et al. 2018) at low impact Weber number. Locally, the air craters on the drop surface can be understood based on the response dynamics of the droplet subjected to external forces, as was demonstrated by Harper et al. and Simpkins et al. (Harper et al. 1972; Simpkins & Bales 1972). The similarity between air craters/jets observed on droplet surface during impact on viscous immiscible liquid pools with jets/craters observed on droplet surface impacting a hydrophobic surface led us to map the immiscible liquid impact problem to the constrained Rayleigh drop eigenvalue problem (Strani & Sabetta 1984; Bostwick & Steen 2009, 2013a, b, 2014, 2015) as was done by Kern et al. for drop impact on solid surfaces (Kern et al. 2021). Recent studies have shown various topology of air crater/singular jet formation in immiscible impacts (Yang et al. 2020). However, the detailed mechanism of the jets produced on the surface of the droplets is not well understood and remains elusive.

A general three fluid immiscible system dealing with impact scenarios labelled as 1,2,3 is described by the following physical parameters: the densities (ρ_1, ρ_2, ρ_3) ; the viscosities (μ_1, μ_2, μ_3) ; the pair wise surface tensions $(\sigma_{12}, \sigma_{13}, \sigma_{23})$; the impact velocity V_0 ; acceleration due to gravity g; and radius of the droplet R_0 . Overall there are 12 dimensional parameters to fully characterize the general dynamics of the impacting system. Using the Buckingham-Pi theorem (Barenblatt et al. 1996) we can construct 9 non-dimensional parameters to reduce the parameter space. The non-dimensional parameters are $\rho_1/\rho_2, \rho_2/\rho_3, \mu_1/\mu_2, \mu_2/\mu_3, \sigma_{12}/\sigma_{13}, \sigma_{13}/\sigma_{23}, We, Ca, Fr$ where We, Caand Fr are the Weber, Capillary and Froude numbers respectively. We observe out of the 9 non-dimensional quantities only 3 quantities are related to dynamics and the remaining 6 quantities specifies the fluid properties and defines the particular fluids used. For a given set of fluids, the dynamics could be characterized based on the triplets (We, Ca, Fr). The Weber number based on the droplet diameter is defined as $We = \rho_w V_0^2 2R_0/\sigma_{aw}$, where ρ_w is the density of the impacting droplet, V_0 is the impact velocity and σ_{aw} is the air-water surface tension. The capillary number is defined as $Ca = \mu_s V_0 / \sigma_{aw}$, where μ_s is the viscosity of silicone oil pool. The Froude number is defined as $Fr = V_0/gR_0$. Note that the three triplets (We, Ca, Fr) are monotonically increasing function of the impact velocity V_0 . The Weber number depends on the impact velocity quadratically whereas the Capillary and Froude number varies linearly. The main experimental control parameter used in this work is the impact velocity and hence the Weber number has the largest variation in terms of numerical values. We use Weber number to characterize all the observations experimentally since an order of magnitude change is observed in We due to the variation in the range of V_0 . Note however for different values of Weber number, the Capillary number and the Froude number are uniquely defined and any impact event in the current experimental context of the work requires a triplet of (We, Ca, Fr) to uniquely define an impact event. In general, the force involved to cause droplet retardation is viscous drag. However, the observed response of the droplet is governed by inertia and surface tension. This is due to the fact that the impacting droplet is about 350 times less viscous than the silicone oil pool. The experimental response time scale of the droplet is within the capillary time scale $(t_c \sim \mathcal{O}(9 \times 10^{-3} s))$. The viscous effects inside the droplet are important at the scale of the viscous diffusion time scale $(\sim \mathcal{O}(4R_0^2/\nu_w) = 5.43s)$. We should realize that the droplet response occurs at a scale

of milliseconds which is three orders of magnitude smaller than the viscous diffusion time scale inside the droplet. Therefore, we can use Weber number to describe the crater observations in general. Further, the high viscosity of the pool ensures that the surface of the droplet below the dynamic contact line has negligible modal oscillations due to high dissipation. The time scale of the viscous dissipation in the liquid pool is of the order of the air crater response time scale $(\sim \mathcal{O}(4R_0^2/\nu_s) \sim 10^{-3}s \sim t_c)$. In this work, we study the role of impact Weber number ($We = \rho_w V_0^2 2R_0/\sigma_{aw}$) on the formation of air craters on the surface of an impacting water droplet on an immiscible highly viscous liquid pool of silicone oil with particular focus on the mechanism of air crater formation using experimental and theoretical analysis. The remaining text is organized as follows. In section 2, we provide the details of the experimental setup and data processing methods. Section 3 outlines the results and discussions with various subsections. Subsection 3.1 provides a global overview of the important results obtained. Subsection 3.2 discusses droplet penetration dynamics and the scales of the various forces acting on the droplet. Subsection 3.3 details ways of characterizing droplet deformation from the spherical shape. Subsection 3.4 provides a criterion for forming air craters of significant depth. Subsection 3.5 computes the center of mass velocity of the droplet. Section 3.6 outlines the details of droplet response/air crater and jet characteristics from a local analysis view point. Section 3.7 discusses the droplet response from a constrained Rayleigh drop model perspective using the Green function method to solve an eigen value problem. We conclude with the results and future scope in conclusion (section 4). The underlying theme of the current work was to identify the mechanisms and mechanics involved in the droplet surface crater formation of the air-water interface of the impacting droplet on an immiscible high viscous liquid pool. The detailed characterization for various experimental parameter range is outside the scope of the present work.

2. Materials and Methods

Fig. 1(a) shows a schematic representation of the experimental setup for the high speed imaging. The various components labelled in the schematic representation are a syringe pump (New Era Pump Systems, NE-1010); syringe and a hypodermic needle; stroboscopic light source; a diffuser plate; water droplet; acrylic container; siliconeoil pool; computer with image acquisition software and high-speed cameras (Photron Fastcam Mini UX100, Photron Fastcam SA5) with Tokina and Navitar zoom lens. The small red dotted rectangle represent the region of interest for all experimental imaging. The dotted straight line 1-0 and 2-0 represents the visual axis of the high speed camera for image acquisition. De-ionised water droplet of radius $(R_0 = 1.1 \pm 0.1 mm)$ was used as the impacting liquid droplet. Silicone oil was used as the liquid pool, and the pool depth was maintained constant at $H_p \sim 5mm$. The kinematic viscosity of the pool used was $\nu_s = 350 cSt$ and density was $\rho_s \sim 970 kg/m^3$. All experiments were conducted at room temperature of $T \sim 298 K$. The droplet impacts energy was varied by changing the impact velocity (0.3-2.2 m/s), and hence the triplet of non-dimensional numbers impact Weber number, Capillary number and Froude number (We, Ca, Fr) was varied by changing the free fall height of the droplet from the free surface of the liquid pool using a vertical linear stage. We explored the formation mechanism of air crater on the surface of the droplet in regime (We, Ca, Fr) = (4 - 145, 1.7 - 10.27, 3.48 - 20.97). The high-speed imaging was performed at 10kHz (10⁴ frames per second) with a spatial resolution of 1.5 micrometers per pixel (equivalent pixel density of ~ $666.667 \, pixels/mm$). Fig. 1(b) shows a highspeed time sequence images depicting the formation of surface craters on the impacting droplet at impact Weber number We = 65. The timestamps are in milliseconds and the



FIGURE 1. (a) Schematic of the experimental setup used for high-speed imaging (not to scale). The various components of the setup are labelled in the figure. The red dotted rectangle represents the region of interest. The dotted straight line 1 - 0 and 2 - 0 represents the visual axis (different sightline) of the camera used during high speed imaging experiments. (b) Time sequence images for impact Weber number We = 65 depicting the formation of air craters . Scale bar represents 1.56mm and timestamps are in milliseconds. (c) Schematic representing the air-water interface deformation process as a function of time leading to the formation of air craters. The arrows depict the direction of air-water interface propagation. The white line depicts the dynamic contact line that travels towards the north pole relative to the impacting droplet.

scale bar represents 1.56mm The acquired high speed images were processed through an image processing pipeline consisting of background subtraction, image segmentation through an adaptive thresholding operation, followed by binarization and edge detection. The geometrical and kinematic quantities like droplet size and velocity were computed through various imaging processing shape descriptors using Image processing software ImageJ (Schneider *et al.* 2012) and, various in-house image processing codes written in Python (Van Rossum & Drake 2009) utilizing image processing libraries like opency (Bradski & Kaehler 2008; Bradski 2000; OpenCV 2015) and scikit-image (Van der Walt *et al.* 2014). The geometrical parameters extracted from the images that were taken from an oblique visual axis of the camera (Fig. 1(a)) were corrected using appropriate trigonometric and affine transformations (Che & Matar 2018; Chityala & Pudipeddi 2020).

3. Results and Discussions

3.1. Global Overview

We discover that the mechanism behind air crater formation is (Fig. 1(c)) intricately related to the penetration dynamics of the impinging droplet through the liquid pool and depends on the impact Weber number. Fig. 1(c) depicts the schematic representation of the surface crater formation on the air-water interface of the impacting droplet. Fig. 2 shows the high-speed snapshots of a water droplet impacting a silicone liquid pool at various impact Weber numbers (We = 4, 16, 65, 145). The timestamps are in milliseconds, and the scale bars represent 1mm. The interaction between the silicone pool and water droplet occurs through the interplay of viscous, buoyancy, droplet weight, air-water, and water-oil surface tension forces. Beyond a critical impact Weber number $(We_c \sim 10)$, air craters of significant depths (crater depth comparable to droplet size) are formed. No significant air craters are observed during the penetration phase for impact Weber number smaller than the critical Weber number $(We < We_c)$. The penetration time scale is largely increased due to the lubrication effect of the entrapped air layer formed under the droplet. The air layer rupture occurs at a time scale of the order of $t_r \sim 2 \times 10^{-1} s$. The transient dynamics of the droplet (surface oscillation) occur early above the pool for $t < t_r$. For $t > t_r$, the droplet penetrates smoothly without any surface oscillation. The deceleration of the droplet is delayed due to the entrapped air and is non-impulsive. The retarding force during the penetration phase is of the order of $F \sim \mathcal{O}(4 \times 10^{-4})N$ for We = 4. The air craters formed for $We > We_c$ occur due to the rapid deceleration experienced by the impacting droplet over a short period (impulsive deceleration). For impact Weber number larger than the critical Weber number $(We > We_c)$, the air layer rupture time scale is of the order of $t_r \sim \mathcal{O}(5 \times 10^{-4})s$, about two orders of magnitude faster than for low Weber number ($We{\sim}1$). We have shown using scaling analysis that the force responsible for the sudden deceleration is the viscous drag. The viscous drag force is of the order of $F_v \sim \mathcal{O}(1.5 \times 10^{-3} N)$ for We = 16which is comparatively larger than the buoyancy/weight of the droplet ($\mathcal{O}(5 \times 10^{-5} N)$). Further, we deduce a criterion for significant air crater depths. We show that the ratio of stokes viscous drag pressure to capillary pressure $(\Gamma = \Delta p_s / \Delta p_c)$ is the parameter characterizing the formation and the size of air craters. $\Delta p_c \sim 1$ corresponds to low We ber number states (We = 4). The ratio Γ increases as we increase the impact We ber number. The shape of the air crater central jet depends on the response of the droplet subjected to impulsive retardation. We show that the shape of the central air jet can be approximated with a fourth-order Legendre polynomial. We observe that the air crater formation/response time scales for all Weber number greater than the critical lies within the capillary time scale of $t_c \sim \sqrt{m/\sigma} \sim \mathcal{O}(9 \times 10^{-3} s)$. However, a complete air crater retraction time scale (T) is a monotonic function of impact Weber number $(T \sim We^{1/2})$. We further demonstrate that the immiscible impact problem could be mapped to a constrained Rayleigh droplet model by incorporating a dynamic contact line relative to the impacting droplet. The crater retraction time scale increases with an increase in impact Weber number. When the air crater dynamics subsides, the droplet penetrates slowly under the influence of weight and buoyancy and attains an almost steady-state submerged configuration.

3.2. Droplet penetration dynamics (Scales of various forces acting on the droplet)

Fig. 3(a) depicts a schematic representation of an impacting droplet on a silicone oil pool. The oil pool is shown in light yellow. The schematic is drawn at a time instant t ($t > t_r$) greater than the air rupture time scale, and the droplet is at a partially



FIGURE 2. Regime diagram showing the effect of impact Weber number on the evolution of droplet and air crater dynamics. The timestamp mentioned are in milliseconds and the scale bar denotes 1mm.

submerged state. CM represents the centre of mass of the impinging droplet. The contact line of three different fluids (air, water, and oil) is marked as a white dotted line. The submerged portion/volume of the droplet immersed below the oil surface is quantitatively characterized and measured by the penetration depth h(t) and penetration width w(t)(Fig. 3(a)). We assume that the droplet deforms into an ellipsoid during the penetration process. The ellipsoid is characterized by the semi-major axis a(t) and the semi-minor axis b(t) respectively (Fig. 3(a)). The forces acting on the droplet are the weight F_{mg} downwards, buoyancy force F_b upwards, and the viscous drag force F_v upwards. The coordinate axis z is chosen to be positive downwards. From mass conservation of the impacting droplet we have

$$\rho_w \frac{4}{3}\pi R_0^3 = \rho_w \frac{4}{3}\pi a^2(t)b(t) = m \tag{3.1}$$

where ρ_w is the density of the impacting droplet (water here), R_0 is the initial radius of the droplet and m is the mass of the impacting droplet. For droplet radius of $R_0 = 1.1mm$, the mass of the impinging water droplet is $m \sim \mathcal{O}(5.58 \times 10^{-6} kg)$. Simplifying equation (3.1) we have

$$a^2(t)b(t) = R_0^3 \tag{3.2}$$

The dynamical equation (Newton's second law of motion) for the impinging liquid droplet is given by

$$F_{mg} - F_b(t) - F_v(t) = m \frac{dV_{CM}(t)}{dt} = m a_{CM}$$
(3.3)

with initial condition for V_{CM} as

$$V_{CM}(t=0) = V_0 \tag{3.4}$$



FIGURE 3. (a) Schematic representation depicting various geometrical scales and forces acting on the impacting droplet while it penetrates the silicone oil pool. (b) log-log plot depicting the strength of various forces in comparison to weight of the droplet as a function of time normalized with respect to capillary time scale $t_c = \sqrt{m/\sigma_{aw}}$, where *m* is the mass of the droplet and σ_{aw} is the air-water surface tension with impact Weber number as a parameter. (c) and (d) $f(t)/R_0^2$ as a function of time in millisecond. The function f(t) is a measure of a spherical drop shape.

where V_{CM} is the centre of mass velocity, V_0 is the impact velocity. The t = 0 defines the time instant just before the penetration of the droplet. $F_{mg} = mg$ is the weight of the impacting droplet where $g = 9.81 m/s^2$ is the acceleration due to gravity, F_b is the buoyant force on the droplet and F_v is the viscous drag force on the droplet due to the interaction with the silicone oil pool. For $R_0=1.1mm$, the weight of the droplet is of the order of $F_{mg} \sim \mathcal{O}(5.47 \times 10^{-5} N)$. The submerged droplet volume in the silicone oil pool can be approximated by an ellipsoidal cap approximation (refer to Fig. 3(a))

$$v(t) = \frac{\pi a^2(t)h^2(t)}{3b^2(t)}(3b(t) - h(t))$$
(3.5)

where h(t) is the depth of penetration of the droplet. The buoyancy force is the weight of the displaced silicone oil, and therefore $F_b(t)$ becomes

$$F_b(t) = v(t)\rho_s g = \frac{\pi a^2 h^2 \rho_s g}{3b^2} (3b - h)$$
(3.6)



FIGURE 4. (a) Snapshots depicting the penetration depth (h(t)) and width (w(t)) respectively for impact Weber number of 4, 16 and 145. (b) $\Gamma(t) = \Delta p_s / \Delta p_c$ as a function of time $(t_r < t < t_c)$ for impact Weber number of 4, 16 and 145 respectively.

Using equation (3.2) in (3.6) the buoyancy force becomes

$$F_b(t) = \frac{\rho_s g \pi R_0^3 h^2}{3b^3} (3b - h) \tag{3.7}$$

At h = b (i.e. when the droplet (ellipsoid) is half submerged) the buoyancy force becomes

$$F_b = \frac{2}{3} \rho_s \pi R_0^3 g \sim \mathcal{O}(2.65 \times 10^{-5} N)$$
(3.8)

Notice that the order of magnitude of buoyancy force is the same as the weight of the droplet, and the buoyancy force becomes important at long time scales to determine the maximum steady-state submerged depth of the droplet. During the early stage of impact $(t\sim 2ms)$ the semi-major axis is approximately equal to the semi-minor axis $(a\simeq b)$ and hence the order of magnitudes of a and b are $\mathcal{O}(R_0)$. Equation (3.6) can therefore be approximated for computing the buoyancy force at early impact time as

$$F_b(t) = v(t)\rho_s g \sim \frac{\pi h^2 \rho_s g}{3} (3R_0 - h)$$
(3.9)

The viscous force on the droplet F_v can be approximated by the Stoke's drag law (Moghisi & Squire 1981) as given by

$$F_v(t) \sim 3\pi \mu_s w(t) \frac{dh}{dt} \tag{3.10}$$

where μ_s is the viscosity of the silicone oil pool. Fig. 3(b) represents the scales of viscous force, buoyancy forces comapred to the weight of the droplet plotted in a logarithmic scale against logarithmic time normalized with respect to the capillary time scale t_c for impact Weber number of 4, 16 and 145. Stoke's approximation used in equation (3.10) becomes valid since the Reynolds number inside the silicone oil pool is very small (Re = $V_0R_0/\nu_s \sim 1$). The maximum viscous force for $We \sim 16$ scales as $F_v \sim \mathcal{O}(1.5 \times 10^{-3} N)$ in the initial phase of penetration. Note that the viscous drag initially is a hundred times larger than the buoyant force and weight of the droplet. Therefore the initial dynamics of droplet penetration and droplet response are governed by Stoke's viscous drag.

3.3. Characterizing droplet deformation from spherical shape

In general as the droplet penetrates the liquid pool, the droplet undergoes deformation and evolves as an ellipsoid (Fig. 3(a)). We have measured and characterized the amount of deviation from a spherical shape by calculating the function f(t) defined as

$$f(t) = h^{2}(t) + \frac{w^{2}(t)}{4} - 2R_{0}h(t)$$
(3.11)

f(t) = 0 represents a spherical undeformed droplet while the penetration occurs. Larger non zero values of f(t) depicts the deviation from spherical symmetry. f(t) has a dimension of square length and therefore can be represented in a dimensionless way by normalizing with respect to R_0^2 . Equation (3.11) therefore becomes

$$\frac{f(t)}{R_0^2} = \frac{h^2(t)}{R_0^2} + \frac{w^2(t)}{4R_0^2} - 2\frac{h(t)}{R_0}$$
(3.12)

Fig. 3(c) and 3(d) shows the evolution of $f(t)/R_0^2$ plotted as a function of time using equation (3.12) for various impact Weber number (We = 4, 16, 145). It can be inferred from the variation of f(t) that for low Weber numbers (We~4), the droplet shape while penetration is very close to spherical. However, increasing the impact Weber number $(We \sim 16, 145)$ the droplet deformation is substantial as can be observed by the non-zero values of $f(t)/R_0^2 > 1$. Regardless of the impact Weber number, beyond the capillary time t_c , the droplet penetrates, maintaining a spherical shape. It could be inferred that the deviation from the spherical shape due to penetration is a short time scale phenomenon $(t < t_c)$. The dominant force experienced by the droplet on penetration is the viscous force (refer to Fig. 3(b)). We observe the formation of significant air craters due to sudden viscous drag acting on the droplet beyond critical impact Weber number of 10. Fig. 4(a) depicts the geometrical characteristics of the deforming droplet/air craters formed during penetration for three different impact Weber numbers equal to 4, 16, and 145. We observe that significant air craters does not form for low Weber number ($We \sim 4$ shown here) due to delayed air layer rupture $(t_r \sim \mathcal{O}(2 \times 10^{-1} s))$. The impulsive nature of the drag force does not manifest during the penetration process due to delayed air layer rupture, and the viscous force becomes gradual for $We < We_c$. Air craters of significant shape and size are observed for larger Weber numbers ($We \sim 16$ and $We \sim 145$ shown here).

3.4. Air crater formation criterion

The air craters observed for $We > We_c$ (refer to Fig. 4(a)) occur due to impulsive viscous drag force acting on the droplet across the immersed surface/volume in the silicone oil bounded by the contact line (refer to the schematic shown in Fig. 3(a). We introduce a non-dimensional parameter $\Gamma(t)$ as the ratio of the stokes drag pressure to capillary pressure across the air water interface in the air crater formation time scale $(t_r < t < t_c)$. The parameter can be represented as

$$\Gamma(t) = \frac{\Delta p_s}{\Delta p_c} \sim \frac{\mu_s w(t) V_0 R_0}{\sigma_{aw} w^2(t)}$$
(3.13)

where $\Delta p_s \sim \mu_s w(t) V_0 / w^2(t)$ is the pressure force due to the stokes drag and $\Delta p_c \sim \sigma_{aw} / R_0$ is the capillary pressure across the air-water interface. $\Gamma(t) \sim 1$ signifies that the impulsive



FIGURE 5. (a) High speed snapshots depicting the evolution of air layer rupture forming a bubble during penetration through silicone oil for impact Weber number We = 4. The timestamps are in milliseconds and the scale bar represents $500\mu m$. (b) Temporal evolution of kinematic parameters like penetration width and depth. (c) Temporal evolution of the various forces acting on the impacting droplet. The resultant of the various forces is also shown in red. Refer to supplementary Movie 1 for We = 4 here.

drag is almost balanced out by the capillary force acting across the air-water interface of the droplet.

Detectable air craters during the penetration process can only be observed if the viscous force becomes comparable and overcomes the capillary force across the droplet interface, which corresponds to $\Gamma(t) > 1$. We also show that for $\Gamma(t) \leq 1$ for $t < t_c$, no significant air craters are observed, as is the case for low impact Weber number. Increasing Weber number increases $\Gamma(t)$ and hence the ratio of Stokes viscous force to capillary force across the air-water interface of the droplet. Equation (3.13) can be rewritten in terms of the capillary number $Ca = \mu_s V_0 / \sigma_{aw}$ as

$$\Gamma(t) = \frac{\Delta p_s}{\Delta p_c} \sim Ca \frac{R_0}{w(t)}$$
(3.14)

Figure 4(b) represents $\Gamma(t) = \Delta p_s / \Delta p_c$ as a function of time for $t_r < t < t_c$ for Weber numbers 4, 16 and 145. It can be inferred from Fig. 4(b) that significant air craters are formed for $\Gamma > 1$ where the impulsive viscous forces become larger than the capillary force across the air-water interface. For small Weber number, $We < We_c = 10$, $\Gamma \lesssim 1$ signifying that the viscous forces are smaller than the capillary force across the air-water interface due to surface tension.



FIGURE 6. (a) High speed snapshots depicting the evolution of air layer rupture forming a bubble during penetration through silicone oil for impact Weber number We = 16. The timestamps are in milliseconds and the scale bar represents $500\mu m$. (b) Temporal evolution of kinematic parameters like penetration width and depth. (c) Temporal evolution of the various forces acting on the impacting droplet. The resultant of the various forces is also shown in red. Refer to supplementary Movie 2 for We = 16 here.

3.5. Evaluating the centre of mass velocity (V_{CM})

We observe that the order of magnitude of air crater jet velocity is comparable to the centre of mass velocity of the droplet (V_{CM}) . Using equation (3.9) and (3.10) for the buoyancy and viscous terms respectively in equation (3.3), the centre of mass acceleration of the droplet can be expressed as

$$\frac{dV_{CM}(t)}{dt} = \frac{1}{m} \left(mg - \frac{\pi h^2 \rho_s g}{3} (3R_0 - h) - 3\pi \mu_s w(t) \frac{dh}{dt} \right)$$
(3.15)

Integrating equation (3.15) we have

$$\int_{V_0}^{V_{CM}(t)} \frac{dV_{CM}(t)}{dt} dt = \int_0^t \frac{1}{m} \left(mg - \frac{\pi h^2 \rho_s g}{3} (3R_0 - h) - 3\pi \mu_s w(t) \frac{dh}{dt} \right) dt \qquad (3.16)$$

Simplifying equation (3.16) we have

$$V_{CM}(t) = V_0 + gt - \frac{\pi\rho_s g}{3} \int_0^t h^2 (3R_0 - h)dt - 3\pi\mu_s \int_0^t w(t) \frac{dh}{dt} dt$$
(3.17)

Notice that the acceleration due to gravity term gt and the buoyancy term (third term on the right hand side) is negligible compared to the viscous term (last term on the right



FIGURE 7. (a) High speed snapshots depicting the evolution of air layer rupture forming a bubble during penetration through silicone oil for impact Weber number We = 145. The timestamps are in milliseconds and the scale bar represents $500\mu m$. (b) Temporal evolution of kinematic parameters like penetration width and depth. (c) Temporal evolution of the various forces acting on the impacting droplet. The resultant of the various forces is also shown in red. Refer to supplementary Movie 3 for We = 145 here.

hand side) for $t_r < t < t_c$. The last term representing the viscous forces is the most dominant for $t_r < t < t_c$.

Fig. 5, Fig. 6, and Fig. 7 show various kinematic and dynamic quantities for impact Weber numbers of 4, 16, and 145, respectively. Fig. 5(a) depicts the high-speed snapshots during the penetration process for an impact Weber number of 4. The penetration dynamics for low Weber numbers are drastically different as the droplet, and air layer interaction is significant. The air layer rupture and formation of a subsequent bubble can be observed in Fig. 5(a). Further, as the droplet penetrates through the silicone oil pool, the droplet shape is close to spherical (refer to Fig. 3(c) and Fig. 3(d)). Fig. 5(b) shows the temporal evolution of submerged droplet normalized width $(w(t)/R_0)$ and normalized depth $(h(t)/2R_0)$ respectively. Using the experimental value of w(t) and h(t), we have calculated the resultant force acting on the droplet. All the individual forces $(F_{mg}, F_b \text{ and } F_v)$ along with the resultant force (in red $F_{mg} + F_b + F_v$) is plotted in Fig. 5(c). Notice that during the early time of penetration for $t < t_c$, the dominant force is only the viscous drag. In general, we observe that the resultant force is almost entirely due to viscous drag with buoyancy and weight almost balancing each other as time increases. Using the resultant external forces acting on the droplet (Fig. 5(c)), the centre of mass velocity (V_{CM}) can be evaluated using equation (3.17). We evaluate centre of mass velocity (V_{CM}) for early penetration time $(t < t_c)$ as the approximation under

14



FIGURE 8. (a) Comparison of the resultant force $\Sigma F(t)$ in mN acting on the droplet during the penetration process as a function of time t in ms for impact Weber number (We) of 4, 16 and 145 evaluated using the right hand side of equation (3.15). (b) Comparison of the centre of mass velocity of the droplet (V_{CM}) in m/s plotted as a function of time t in ms for impact Weber number (We) of 4, 16 and 145. (c) A high speed snapshot depicting the crater depth h_c . (d) Crater depth (h_c) evolution as a function of time in ms.

which equation (3.17) is derived becomes increasingly accurate for small time duration. The effect of the impact Weber number can be understood by analyzing the scale of F_v as a function of the Weber number. It can be inferred from Fig. 3(b) that on increasing the impact Weber number, the viscous force F_v changes significantly. The resultant force on the droplet is approximately equal to that of the viscous force. Therefore on increasing the impact Weber number, the ratio of stokes viscous pressure to capillary pressure of the droplet Γ increases resulting in the formation of air crater/reversed jets of various shapes and sizes (refer to Fig. 4(a) and Fig. 4(b)). Fig. 6(a) shows a sequence of high-speed snapshots showing the evolution of the air crater for We = 16. Fig. 6(b) plots the evolution of normalized penetration depth and width of the impacting droplet for impact Weber number of 16. The individual and resultant forces acting on the droplet are shown in Fig. 6(c). Fig. 7(a) shows the air crater formation and evolution for impact Weber number of 145. The crater formed is significantly different compared to the low Weber number impact. For Weber number of 16, a single air jet is formed due to the



FIGURE 9. (a) Image depicting the profile of the reversed jet formed during air crater formation/collapse at impact Weber number of 16. (b) Comparison of the experimental profile of the central jet with 4-th degree Legendre polynomial. (c) Image depicting the profile of the reversed jet formed during air crater formation/collapse at impact Weber number of 145. (d) Comparison of the experimental profile of the central jet with 4-th degree Legendre polynomial. (e) Experimental and theoretical comparison of air crater time scale (T) as a function of impact Weber number (We) based on equation (3.22).

D. Roy, Sophia M, and S. Basu

capillary waves interfering. Whereas for Weber number of 145, a cascade of capillary waves is formed, forming a bigger intricate air crater. The air crater normalized depth $(h(t)/2R_0)$ and normalized width $(w(t)/R_0)$ is plotted as a function of time in Fig. 7(b). Using the experimental air crater geometrical parameters, the individual and the resultant force acting on the impacting droplet were calculated and are shown in Fig. 7(c). The resultant force $\Sigma F(t)$ acting on the impinging droplet during the penetration process is plotted as a function of time for various impact Weber number in Fig. 8(a) for comparison purposes (We = 4, 16, 145). The centre of mass velocity (V_{CM}), the solution for equation (3.17) is plotted in Fig. 8(b) for various impact Weber numbers. The centre of mass velocity decreases as the droplet experiences retarding forces as it penetrates the liquid silicone oil pool. We can further observe that the centre of mass velocity shows a damped oscillatory response for $t \sim t_c$. Fig. 8(c) shows a typical air crater geometry and its characteristics scale (air crater depth h_c) formed on the surface of an impacting droplet. The evolution of air crater depth h_c as a function of time t is plotted in Fig. 8(d) for impact Weber numbers of 16, 65 and 145. Note that the initial slope of h_c vs. t plot is ordered according to the centre of mass velocity for various Weber numbers, respectively. We = 145 has the highest initial slope followed by We = 65 and We = 16.

3.6. Transient Droplet Response (Local Analysis)

The air crater/jets are formed due to the transient response of the droplet to impulsive forces acting on the droplet. The sudden deceleration of the droplet induces droplet oscillation that causes air craters of various shapes and sizes to form. Further, relative to the droplet the external force acting could also be formulated based on the relative effect of the surrounding air field. The transient response of the droplet surface based on sudden retardation can be characterized by surface displacement $\eta = r(\mu, t)/R_0$; where $r(\mu, t)$ is the radial location of the droplet interface at any angular coordinate θ at time t (refer to Fig. 3(a)) and R_0 is the initial droplet radius. We closely follow this part of the analysis based on the work of Harper et al. and Simpkins et al. (Harper *et al.* 1972; Simpkins & Bales 1972). The perturbation result for the surface displacement based on a linear theory proposed by Harper et al. (Harper *et al.* 1972) is given as

$$\eta = 1 + \epsilon \sum_{n=0}^{\infty} \frac{n(2n+1)}{4\beta_n^2} C_n P_n(\mu) [\cos(\beta_n t) - 1]$$
(3.18)

where $\epsilon = \rho_a / \rho_w$ is the density ratio of air to water characterizing the amplitude of the perturbation, n is a positive integer and C_n are the weighting coefficients given by,

$$C_n = \int P_e^{(0)} P_n(\chi) d\chi \tag{3.19}$$

where $\chi = \cos\psi$. $P_n(\mu)$ represents the n-th order legendre polynomials where $\mu = \cos\theta$ and

$$\beta_n = \left(\frac{(n-1)n(n+2)}{We_{R_0}}\right)^{1/2} \tag{3.20}$$

where β_n denotes the frequency of n-th Legendre mode and We_{R_0} denotes the Weber number defined with respect to the initial radius R_0 ($We = 2We_{R_0}$). $P_e^{(0)}$ represents the leading term of the external pressure P_e in the perturbation expansion with ϵ as the perturbation parameter acting on the droplet during the penetration process.

$$\beta \sim W e^{-1/2} \tag{3.21}$$



FIGURE 10. Graphical representation depicting the geometrical nomenclature and the air-water inerfacial waves for the global deformation analysis. (a) for $\alpha = \pi/4$ (b) for $\alpha = \pi/2$. (c) An experimental snapshot depicting the observed crater characteristics for impact Weber number We = 16.

Refer to Fig. 3(a) for the definition of various angular coordinates like θ and ψ . Note that near the droplet top surface that corresponds to $\psi = 0$ and $\theta = \pi$, the droplet shape approximates that of a Legendre polynomial locally. Fig. 9(a) and 9(b) show the comparison of the air jet profile at the centre with the fourth-order Legendre polynomial for We = 16. Similar comparison is shown in Fig. 9(c) and 9(d) for We = 145. In principle, the combined air crater deformation can be thought of as the superposition of various Legendre modes. The period of half oscillation of the air jets scales as

$$T \sim \beta^{-1} \sim W e^{1/2} \tag{3.22}$$

Therefore, from equation (3.22), we observe that the period of air crater dynamics increases monotonically with the impact Weber number. As inferred from Fig. 9(e), we observe the corresponding monotonic behavior experimentally.

3.7. Transient vibrational response of the droplet based on constrained rayleigh drop model (Global Analysis)

In this section we generalize the local analysis performed in the previous section (3.6) with a global response model. When the entrapped air beneath the impacting droplet ruptures and forms a central air bubble, a three-fluid dynamic contact line is formed (refer to Fig. 1(c), 3(a), 10(a) and 10(b)). The contact line is a one dimensional boundary separating the three immiscible fluids (air, water and silicone oil) and is one of the important aspects controlling the response of the droplet. The dynamic contact line separates the droplet interface into two disjoint curved surface areas. The dynamic contact line is characterized using an inclination angle α measured from the -y axis. Fig. 10(a), 10(b) graphically represents the geometry of a penetrating droplet from constrained Rayleigh drop perspective. Fig. 10(a) represents the droplet penetration at any given instant for an acute value of $\alpha = \pi/4$. For $\alpha = \pi/2$, the schematic is shown in figure 10(b). The colored saffron region represents the silicone oil pool. $R = R_0$ represents the radius of the undeformed equilibrium shape of the droplet. The dynamic contact line is represented by the horizontal dotted blue line. The curved dotted blue line represents the bottom submerged portion of the droplet. The red dotted curved interface represents the equilibrium position of the air-water interface. The blue and green solid line depicts the oscillating air-water interface of the droplet that leads to the formation of air craters. $z(\theta)$ represents the amplitude of the air-water interface from the equilibrium position of the interface at a given polar angle θ and time t. In general the dynamic contact line imposes the constraint of zero amplitude along its perimeter. However, owing to large viscosity of the silicone pool, the entire curved surface of the droplet submerged in the silicone pool (water-oil interface) could be considered as an surface area of negligible (zero) amplitude. The amplitude response of the droplet from the mean equilibrium shape in general depends on the impact Weber number and increases monotonically with the same (refer Fig. 8(d)). For small impact Weber number the droplet interface amplitudes and the deviation from the average spherical equilibrium shape is relatively small (refer Fig. 3(d)). We therefore use the constrained rayleigh drop model for such low energy impacts. We follow the analysis of Strani, Bostwick-Steen closely in this section (Strani & Sabetta 1984; Bostwick & Steen 2009). In a recent work, Kern et al. showed that in drop impact systems on solids, contact angle hysteresis filters impact energy into modal interfacial vibrations.

The continuity equation for incompressible flow inside the impacting droplet is given as

$$\nabla \cdot \mathbf{V} = 0 \tag{3.23}$$

The velocity field **V** inside the droplet could be extracted from a velocity potential Φ provided that the flow inside the impacting droplet is inviscid. This could be done due to the fact that the impacting droplet is about 350 times less viscous than the silicone oil pool. The experimental response time scale of the droplet is within the capillary time scale $(t_c \sim \mathcal{O}(9 \times 10^{-3} s))$. The viscous effects inside the droplet are important at the scale of the viscous diffusion time scale $(\sim \mathcal{O}(4R_0^2/\nu_w) = 5.43s)$. We should realize that the droplet response occurs at a scale of milliseconds which is three orders of magnitude smaller than the viscous diffusion time scale inside the droplet. We therefore use a inviscid droplet model for computing the droplet response during the capillary time scale.

$$\mathbf{V} = \nabla \Phi \tag{3.24}$$

Substituting equation (3.24) in equation (3.23) we have

$$\nabla^2 \Phi = 0 \tag{3.25}$$

where ∇^2 is the laplacian operator. We use spherical polar coordinates (r, θ, Ψ) where r represents the radial coordinate from the centre of the droplet, θ is the zenith/polar angle and Ψ is the azimuthal angle. We assume an axisymmetric geometry due to a cylindrical symmetry about the y-axis (Fig. 10(a)) in our experimental configuration. Note the local analysis carried out in the previous section uses a different nomenclature for various angular coordinates θ and ψ (refer Fig. 3(c)). Equation (3.25) in spherical axisymmetric polar coordinates therefore becomes

$$\nabla^2 \Phi = \sin\theta (r^2 \phi_r)_r + (\sin\theta \Phi_\theta)_\theta = 0 \tag{3.26}$$

on

$$\mathscr{D}^{i} \equiv \{ (r,\theta) \mid 0 \leqslant r \leqslant R , \ 0 \leqslant \theta \leqslant \pi \}$$

$$(3.27)$$

$$\mathscr{D}^{e} \equiv \{ (r, \theta) \mid R \leqslant r \leqslant \infty, \ 0 \leqslant \theta \leqslant \pi \}$$

$$(3.28)$$

We use subscript r, θ in equation (3.26) to represent partial derivatives with respect to radial coordinate (r) and the zenith angle (θ) respectively. This convention is used throughout the analysis in this section. \mathscr{D} represents the 2D axisymmetric equilibrium domain of the problem. The superscripts i, e represents regions pertaining to the interior and exterior of the droplet equilibrium shape respectively. \mathscr{D}^i in equation (3.27) represents the 2D axisymmetric interior region of the equilibrium shape of the impacting droplet. Similarly the exterior of the droplet in equilibrium conditions is given by \mathscr{D}^e represented in equation (3.28). The pressure inside and outside the droplet could be computed from the unsteady Bernoulli equation Kundu *et al.* (2015)

$$p(r,\theta,t) = p_0 + \rho \Phi_t \tag{3.29}$$

where p_0 is a reference pressure (the atmospheric pressure), and ρ is the density of the fluid. The subscript t refers to partial derivative of Φ with respect to time. The droplet interface is represented by $\partial \mathscr{D}$. The superscript s will represent the submerged interface (water-silicone oil interface) and the superscript f represents the free surface of the droplet (air-water interface). On the submerged boundary portion of the droplet represented by

$$\partial \mathscr{D}^{s} \equiv \{ (r, \theta) \mid r = R, \ \pi - \alpha \leqslant \theta \leqslant \pi \}$$
(3.30)

the radial velocity Φ_r and the amplitude Z is zero. This approximation could be made due to the fact that the liquid pool is highly viscous and dissipates any interface oscillatory motion. The time scale of the viscous dissipation in the liquid pool is of the order of $\sim \mathcal{O}(4R_0^2/\nu_s) \sim 10 \times 10^{-3} s \sim t_c$

$$\Phi_r = 0 \; ; \; Z = 0 \tag{3.31}$$

On the free boundary portion of the droplet

$$\partial \mathscr{D}^{f} \equiv \{ (r, \theta) \mid r = R, \ 0 \leqslant \theta \leqslant \pi - \alpha \}$$
(3.32)

the boundary condition at the interface preserving the continuity of normal velocity is given by

$$\Phi_r = -Z_t \tag{3.33}$$

The dynamic balance of momentum along the droplet radius gives

$$p^{i} - p^{e} = \sigma \left[\frac{2}{R} - \frac{1}{R^{2}} \left(\frac{1}{\sin\theta} \left(\sin\theta Z_{\theta} \right)_{\theta} + 2Z \right) \right]$$
(3.34)

Recognize that the unknowns are the droplet deformation from equilibrium position given

D. Roy, Sophia M, and S. Basu

by $Z(\theta, t)$ and the velocity potential given by $\Phi(r, \theta, t)$

$$Z = Z(\theta, t) = ?; \ \Phi(r, \theta, t) = ?$$
(3.35)

Conservation of mass for the impacting drop gives us

$$\int_0^{\pi} Z \sin\theta d\theta = 0 \tag{3.36}$$

This is true if the droplet does not fragment into daughter droplets which is true at low impact energies as in the current experimental configuration. By considering periodic motion inside and of the free air-water interface, we can set

$$\Phi(r,\theta,t) = \phi(r,\theta)e^{i\omega t}$$
(3.37)

$$Z(\theta, t) = z(\theta)e^{i(\omega t + \pi/2)}$$
(3.38)

The phase difference of $\pi/2$ is consistent with the boundary condition given by equation (3.33). The partial derivative of Φ with respect to the radial coordinate r is given by

$$\Phi_r = \phi_r e^{i\omega t} \tag{3.39}$$

The partial derivative of Z with respect to time t is given by

$$Z_t = z(\theta)i\omega e^{i\omega t}e^{i\pi/2} = -\omega z(\theta)e^{i\omega t}$$
(3.40)

Using equation (3.39) and (3.40) in (3.33) we have

$$\phi_r e^{i\omega t} = \omega z(\theta) e^{i\omega t} \tag{3.41}$$

The pressure inside the droplet p^i using equation (3.29) is given by

$$p^i = p_0^i + \rho^i \Phi_t^i \tag{3.42}$$

where ρ^i is density of the water droplet. The pressure outside the droplet p^e using equation (3.29) is given by

$$p^e = p_0^e + \rho^e \Phi_t^e \tag{3.43}$$

where ρ^e is density of the surrounding air. The difference in pressure inside and outside of the droplet across the air-water interface is given by

$$p^{i} - p^{e} = (p_{0}^{i} - p_{0}^{e}) + \rho^{i} \Phi_{t}^{i} - \rho^{e} \Phi_{t}^{e}$$
(3.44)

The partial derivative of equation (3.37) with respect to time can be written as

$$\Phi_t = i\omega\phi(r,\theta)e^{i\omega t} \tag{3.45}$$

Using equation (3.45) in equation (3.44) for both internal and external fluids we have

$$p^{i} - p^{e} = (p_{0}^{i} - p_{0}^{e}) + i\omega e^{i\omega t} [\rho^{i}\phi^{i} - \rho^{e}\phi^{e}]$$
(3.46)

Equation (3.46) can be simplified using the Euler's identity $e^{i\omega t} = cos(\omega t) + isin(\omega t)$ where *i* is the complex number $(i = \sqrt{-1})$

$$p^{i} - p^{e} = (p_{0}^{i} - p_{0}^{e}) - \omega \sin\omega t [\rho^{i} \phi^{i} - \rho^{e} \phi^{e}] + i\omega \cos\omega t [\rho^{i} \phi^{i} - \rho^{e} \phi^{e}]$$
(3.47)

The partial derivative of equation (3.38) with respect to θ can be written as

$$Z_{\theta} = iz'(\theta)e^{i\omega t} \tag{3.48}$$

Using equation (3.48) the curvature term in the right hand side of equation (3.34) can be written as

$$\left[\frac{2}{R} - \frac{1}{R^2} \left(\frac{1}{\sin\theta} \left(\sin\theta Z_\theta\right)_\theta + 2Z\right)\right] = I + II \tag{3.49}$$

$$I = -\frac{1}{R^2} \left[\cot\theta z'(\theta) + z''(\theta) + 2z(\theta) \right] \sin\omega t$$
(3.50)

$$II = \frac{i}{R^2} \left[\cot\theta z'(\theta) + z''(\theta) + 2z(\theta) \right] \cos\omega t$$
(3.51)

Using equation (3.47), (3.50) and (3.51) in equation (3.34) and equating real parts we have

$$p_0^i - p_0^e = \frac{2\sigma}{R}$$
(3.52)

and from equating imaginary parts we have

$$-\omega[\rho^{i}\phi^{i} - \rho^{e}\phi^{e}] = \frac{\sigma}{R^{2}} \left[\cot\theta z^{'}(\theta) + z^{''}(\theta) + 2z(\theta) \right]$$
(3.53)

Equation (3.52) reresents the laplace equation for the unperturbed spherical droplet. On the 2D axisymmetric domain \mathscr{D} we have

$$\nabla^2 \phi = 0 \tag{3.54}$$

and from equation (3.41) we have

$$\phi_r = \omega z(\theta) \tag{3.55}$$

On the free air-water interface of the droplet $\partial \mathscr{D}^f$ we have from equation (3.53)

$$\omega[\rho^i \phi^i - \rho^e \phi^e] = -\frac{\sigma}{R^2} \left[\frac{1}{\sin\theta} \left(\sin\theta Z_\theta \right)_\theta + 2Z \right]$$
(3.56)

On the submerged water-oil interface of the droplet $\partial \mathscr{D}^s$ we have from equation (3.31), (3.33), (3.37) and (3.38)

$$\phi_r = 0 , \ z = 0 \tag{3.57}$$

Using equation (3.38) in equation (3.36) we have

$$\int_0^{\pi} z \sin\theta d\theta = 0 \tag{3.58}$$

Equation (3.54) - equation (3.58) defines an eigen value problem in a continuous functional space. The equation

$$\nabla^2 \phi = 0 \tag{3.59}$$

on ${\mathscr D}$ and the equation

$$\phi_r = \omega z \tag{3.60}$$

on $\partial \mathscr{D}$ defines an Neumann problem. Further due to stagnant nature of the ambient at far field $r \to \infty$ we have

$$\phi^e \to 0 \ as \ r \to \infty \tag{3.61}$$

Introducing the change of variable $\mu = \cos\theta$, the velocity potential solution for the interior and exterior of the droplet could be written as infinite series using the Legendre

Polynomials as the basis functions. The velocity potential therefore could be written as

$$\phi^{i}(r,\mu) = \omega R \left(\phi_{0} + \sum_{k=1}^{\infty} \frac{\phi_{k}}{k} \frac{r^{k}}{R^{k}} P_{k}(\mu) \right)$$
(3.62)

$$\phi^{e}(r,\mu) = -\omega R \sum_{k=1}^{\infty} \frac{\phi_{k}}{k+1} \frac{R^{k+1}}{r^{k+1}} P_{k}(\mu)$$
(3.63)

where

$$\phi_k = \frac{\langle z, P_k \rangle}{\langle P_k, P_k \rangle} \tag{3.64}$$

$$\langle f,g \rangle = \int_{-1}^{+1} fg d\mu$$
 (3.65)

$$\langle P_k, P_k \rangle = \frac{2}{2k+1}$$
 (3.66)

Here $P_k(\mu)$ denotes the k-th Legendre polynomial and $\langle f, g \rangle$ represents the inner product of f and g and is square integragble in the domain $(L^2(-1,1))$. Equation (3.56) using the definition of μ could be written as

$$[(1-\mu^2)z\mu]_{\mu} + 2z = -\frac{\rho^i \omega R^2}{\sigma} \left[\phi^i(R,\mu) - \frac{\rho^e}{\rho^i}\phi^e(R,\mu)\right] = f(\mu)$$
(3.67)

for $a \leq \mu \leq 1$. Here $a = -\cos(\alpha)$ (refer Fig. 10(a)).

If $f(\mu) = 0$, equation (3.67) has two independent solutions

$$P_1(\mu) = \mu , \ Q_1(\mu) = \frac{1}{2}\mu log\left(\frac{1+\mu}{1-\mu}\right) - 1$$
(3.68)

The solution of equation (3.67) may be expressed as

$$z(\mu) = \int_{a}^{1} G'(\mu, \tau) f(\tau) d\tau$$
 (3.69)

where the symmetric Green function is given by the following mapping

$$G'(\mu,\tau):[a,1]\times[a,1]\to R\tag{3.70}$$

$$G'(\mu,\tau) = \begin{cases} P_1(\tau) \left[\frac{Q_1(a)}{a} P_1(\mu) - \frac{P_1(a)}{a} Q_1(\mu) \right], \ a \leq \mu \leq \tau \leq 1 \\ P_1(\tau) \left[\frac{Q_1(a)}{a} P_1(\mu) - \frac{P_1(a)}{a} Q_1(\mu) \right], \ a \leq \mu \leq \tau \leq 1 \end{cases}$$
(3.71)

When $a \rightarrow 0$ or $a \rightarrow -1$, the green function diverges.

$$\lim_{\mu \to a^+} z(\mu) = 0 , \ -1 \le \mu \le a$$
(3.72)

Equation (3.57) gives $z(\mu) = 0$ on $\partial \mathscr{D}^s$. Therefore for the entire boundary of the droplet $\partial \mathscr{D} = \partial \mathscr{D}^f \cup \partial \mathscr{D}^s$ we have

$$z(\mu) = \int_{-1}^{+1} G(\mu, \tau) f(\tau) d\tau$$
(3.73)

where $G(\mu, \tau) : [-1, 1] \times [-1, 1] \rightarrow R$ is the extension of $G'(\mu, \tau)$ for $(\mu, \tau) \in [a, 1] \times [a, 1]$

$$G(\mu, \tau) = \begin{cases} G'(\mu, \tau), \ (\mu, \tau) \in [a, 1] \times [a, 1] \\ 0, \ otherwise \end{cases}$$
(3.74)

From equations (3.62) and (3.63), we may evaluate the function $f(\tau)$ appearing in equation (3.73) as

$$f(\mu) = -\frac{1}{\lambda} \left[\phi_0 + \int_{-1}^{+1} \Gamma(\mu, \tau) z(\tau) d\tau \right]$$
(3.75)

where

$$\lambda = \frac{\sigma}{\rho^i \omega^2 R^3} \tag{3.76}$$

23

and

$$\Gamma(\mu,\tau) = \sum_{k=1}^{\infty} \frac{2k+1}{2} \left[\frac{1}{k} + \frac{\rho^e}{\rho^i} \frac{1}{k+1} \right] P_k(\mu) P_k(\tau)$$
(3.77)

Equation (3.73) after substitution of equation (3.75) becomes

$$z(\mu) = -\frac{1}{\lambda} \left[\phi_0 \int_{-1}^{+1} G(\mu, \tau) d\tau + \int_{-1}^{+1} \int_{-1}^{+1} G(\mu, \tau) \Gamma(\tau, \sigma) z(\sigma) d\sigma d\tau \right]$$
(3.78)

The constant ϕ_0 can be determined from equation (3.58) by imposing the conservation of droplet mass/volume.

$$\phi_0 = -\frac{\int_{-1}^{+1} \int_{-1}^{+1} \int_{-1}^{+1} G(\nu, \tau) \Gamma(\tau, \sigma) d\nu d\sigma d\tau}{\int_{-1}^{+1} \int_{-1}^{+1} G(\nu, \tau) d\nu d\tau}$$
(3.79)

Using the value of ϕ_0 from equation (3.79) equation (3.78) becomes

$$\lambda z(\mu) = \int_{-1}^{+1} K(\mu, \sigma) z(\sigma) d\sigma = \mathscr{A} z \; ; \; (-1 \leqslant \mu \leqslant 1) \tag{3.80}$$

where

$$K(\mu,\sigma) = \frac{\int_{-1}^{+1} \int_{-1}^{+1} \int_{-1}^{+1} G(\mu,\epsilon) G(\nu,\tau) \Gamma(\tau,\sigma) d\tau d\nu d\epsilon}{\int_{-1}^{+1} \int_{-1}^{+1} G(\nu,\tau) d\tau d\nu} - \int_{-1}^{+1} G(\mu,\tau) \Gamma(\tau,\sigma) d\tau \quad (3.81)$$

The continuous functional eigenvalue problem represented by equation (3.80) could be reduced to an infinite set of algebraic equations by expanding $z(\mu)$ and $K(\mu, \sigma)$ in the Legendre Polynomial basis as

$$z(\mu) = \sum_{k=1}^{\infty} z_k P_k(\mu) , \ z_k = \frac{\langle z, P_k \rangle}{P_k, P_k}$$
(3.82)

$$K(\mu,\sigma) = \sum_{h,l=1}^{\infty} K_{hl} P_h(\mu) P_l(\sigma)$$
(3.83)

$$G(\mu,\tau) = \sum_{h,l=0}^{\infty} G_{hl} P_h(\mu) P_l(\sigma)$$
(3.84)



FIGURE 11. (a) Visual representation of matrix A depicting its elements. (b) Visual representation of the eigenvector matrix of A. (c) Bar plot depicting the strength (eigenvalues) of various eigenmodes of matrix A. (d) Experimental and theoretical comparison of the the air-water interface crater profile for impact Weber number We = 16.

Using equation (3.74) we have

$$G_{hl} = G_{lh} = \frac{\langle \langle G, P_h \rangle, P_l \rangle}{\langle P_h, P_h \rangle \langle P_l, P_l \rangle} = \frac{(2h+1)(2l+1)}{4} \int_a^1 \int_a^1 G^{'}(\mu, \sigma) P_h(\mu) P_l(\sigma) d\mu d\sigma$$
(3.85)

Substituting equation (3.84), (3.85) for $G(\mu, \tau)$ and equation (3.77) for $\Gamma(\tau, \sigma)$ in equation (3.81) we have

$$K_{hl} = \left(\frac{G_{0l}G_{h0}}{G_{00}} - G_{lh}\right) \left(\frac{1}{l} + \frac{\rho^e}{\rho^i} \frac{1}{l+1}\right)$$
(3.86)

using equation (3.82) and (3.83) in (3.80) we have

$$\lambda z_h = \sum_{l=1}^{\infty} \left[\frac{2}{2l+1} \left(\frac{G_{h0} G_{0l}}{G_{00}} - G_{hl} \right) \left(\frac{1}{l} + \frac{1}{l+1} \right) \right]$$
(3.87)

Using a linear coordinate transformation between x_h and z_h we have

$$x_{h} = \left(\frac{\frac{1}{h} + \frac{\rho^{e}}{\rho^{i}} \frac{1}{h+1}}{2h+1}\right)^{1/2} z_{h}$$
(3.88)

$$\sum_{l=1}^{\infty} A_{lh} x_l = \lambda x_h \tag{3.89}$$

Equation (3.89) describes an infinite dimensional matrix-vector eigenvalue problem where A_{lh} represents the matrix, x_l or x_h represents the eigenvector and λ represents the eigenvalue corresponding to the eigenvector x_h . The elements of the matrix A is given by

$$A_{lh} = A_{hl} = 2\left(\frac{G_{h0}G_{0l}}{G_{00}} - G_{hl}\right) \left[\left(\frac{\frac{1}{h} + \frac{\rho^e}{\rho^i} \frac{1}{h+1}}{2h+1}\right) \left(\frac{\frac{1}{l} + \frac{\rho^e}{\rho^i} \frac{1}{l+1}}{2l+1}\right) \right]$$
(3.90)

Equation (3.90) depicts that the matrix A is real and symmetric.

$$G_{ik} = \frac{(2i+1)(2k+1)}{4} \left\{ A_i B_k + C_{ik} \right\}$$
(3.91)

$$A_i = \int_a^1 P_1(\tau) P_i(\tau) d\tau \tag{3.92}$$

$$B_k = \int_a^1 \left(\frac{Q_1(a)}{a} P_1(\mu) - \frac{P_1(a)}{a} Q_1(\mu) \right) P_k(\mu) d\mu$$
(3.93)

$$C_{ik} = \frac{P_1(a)}{a} \int_a^1 [P_i(\tau)P_1(\tau) \int_{\tau}^1 Q_1(\mu)P_k(\mu)d\mu - Q_1(\tau)P_i(\tau) \int_{\tau}^1 P_1(\mu)P_k(\mu)d\mu]d\tau$$
(3.94)

Equation (3.94) could be simplified based on the identities (MacRobert 1967) for $k \neq 1$

$$\int_{x}^{1} P_{h}(\mu) P_{k}(\mu) d\mu = \frac{h P_{k}(x) P_{h-1}(x) - k P_{h}(x) P_{k-1}(x) - (h-k) x P_{h}(x) P_{x}(x)}{(h-k)(h+k+1)}$$
(3.95)

$$\int_{x}^{1} Q_{h}(\mu) P_{k}(\mu) d\mu = \frac{h P_{k}(x) Q_{h-1}(x) - k Q_{h}(x) Q_{k-1}(x) - (h-k) x Q_{h}(x) P_{k}(x)}{(h-k)(h+k+1)}$$
(3.96)
If $k \neq 1$

$$G_{ki} = G_{ik} = \frac{(2i+1)(2k+1)}{4} \left[\frac{P_k(a)I_{1i}(a) - P_1(a)I_{ik}(a)}{a[k(k+1)-2]} \right]$$
(3.97)

where

$$I_{ik}(a) = \int_{a}^{1} P_i(\tau) P_k(\tau) d\tau \qquad (3.98)$$

and

$$I_{1i}(a) = I_{ik}(a)|_{i=1,k=i}$$
(3.99)

For i = k = 1

$$G_{11} = \frac{1}{2}log(1+a) - \frac{1}{4a} + \frac{7 - 6log(2)}{12} - \frac{a^3}{12} - \frac{a}{4}$$
(3.100)

D. Roy, Sophia M, and S. Basu

The symmetric Green function G' represented by equation (3.71) diverges for a = -1and a = 0. The eigenvalue problem described by equation (3.54) to equation (3.58) cannot be solved in the function space $L^2(-1, 1)$. The function space used should be different (Benjamin & Scott 1981) such that $\lim_{a\to 0} A_{hk}$ exists and is finite. The singularity for a = 0 could be easily resolved by setting

$$\mathscr{A}_{a=0} = \lim_{a \to 0} \mathscr{A}_a \tag{3.101}$$

Further, the limiting value of the operator \mathscr{A} and its eigenvalues as $a \rightarrow 0$ and $a \rightarrow -1^+$ is shown below.

$$\lim_{a \to 0} A_{hk} = 2 \left(\frac{\frac{1}{h} + \frac{\rho^e}{\rho^i} \frac{1}{h+1}}{2h+1} \frac{\frac{1}{k} + \frac{\rho^e}{\rho^i} \frac{1}{k+1}}{2k+1} \right)^{1/2}$$
(3.102)

From equation (3.102) we observe that $\lim_{\alpha \to 0} A_{hk}$ exists and is finite.

$$\lim_{a \to 0} \left(\frac{G_{h0} G_{k0}}{G_{00}} - G_{hk} \right) = \lim_{a \to 0} \left[\frac{1}{a} \left(\frac{a G_{h0} a G_{k0}}{a G_{00}} - a G_{hk} \right) \right]$$
(3.103)

$$aG_{hk} = \frac{(2h+1)(2k+1)}{4} \left[\frac{P_k(0)I_{1n}(0)}{k(k+1)-2} + \frac{P_k(0)I_{1h}(0) - I_{hk}(0)}{k(k+1)-2}a + \mathcal{O}(a^2) \right]$$
(3.104)

For $k \neq 1$,

$$aG_{11} = \frac{9}{4} \left[-\frac{1}{9} + \frac{1}{27} (7 - 6\log 2)a + \mathcal{O}(a^2) \right]$$
(3.105)

$$\left(\frac{aG_{h0}aG_{k0}}{aG_{00}} - aG_{kk}\right)_{a=0} = 0 \; ; \; \forall h, K \tag{3.106}$$

The derivative of equation (3.106) at a = 0 is finite, thus showing the existence of a finite value of the limit depicted in equation (3.103).

$$\lim_{a \to 0} \left(\frac{G_{h0}G_{k0}}{G_{00}} - G_{hk} \right) = \frac{(2h+1)(2k+1)}{4[k(k+1)-2]} \left[P_k(0) \left(2I_{1h}(0) - \int_0^1 P_h(\tau) d\tau \right) - E \right]$$
(3.107)

$$E = 2I_{1h}(0) \int_0^1 P_k(\tau) d\tau + I_{hk}(0)$$
(3.108)

$$\lim_{a \to -1^+} G_{ik} = \frac{(2i+1)(2k+1)}{4} \frac{(-1)^k \frac{2\delta_{i1}}{3} + \frac{2\delta_{ik}}{2k+1}}{2-k(k+1)}$$
(3.109)

For $k \neq 1$ the matrix elements of A becomes

$$A_{1k} = A_{k1} \rightarrow \frac{(-1)^k}{k(k+1) - 2} \left[\left(1 + \frac{1}{2} \frac{\rho^e}{\rho^i} \right) \left(\frac{1}{k} + \frac{1}{k+1} \frac{\rho^e}{\rho^i} \right) \left(\frac{2k+1}{3} \right) \right]^{1/2}$$
(3.110)

$$A_{hk} \rightarrow 0; \ (h \neq k, h, k \neq 1) \tag{3.111}$$

The diagonal elements of A becomes

$$A_{hh} \to \left(\frac{1}{h} + \frac{\rho^e}{\rho^i} \frac{1}{h+1}\right) \frac{1}{h(h+1) - 2}; \ (h \neq 1)$$
(3.112)

Equations (3.110, (3.111) and (3.112) depicts that A is a symmetric real diagonal matrix with eigenvalues as the elements of the diagonal. The eigenvalues becomes

$$\lambda^1 \to +\infty, \ x_k^1 \to \delta_{1k}, \ z_k^1 \to \delta_{1k}$$

$$(3.113)$$

$$\lambda^{n} \rightarrow \frac{(n+1) + (\rho^{e}/\rho^{i})n}{n(n-1)(n+1)(n+2)}; \ x_{k}^{n} \rightarrow \delta_{nk}, \ z_{k}^{n} \rightarrow \delta_{nk}$$
(3.114)

From equations (3.113) and (3.114) we observe that the first eigenmode corresponds to zero frequency which corresponds to a rigid body motion, whereas the various other eigenmodes tend towards pure Rayleigh modes for the case of negligible pinning at and below the dynamic contact line. The infinite dimensional eigenvalue problem represented by equation (3.89) is solved numerically using in-house program written in python using a 10 dimensional Legendre function space approximation. The elements of the matrix A were represented using equation (3.90). Note that the matrix A is real and symmetric. Fig. 11(a) depicts a visual representation of the matrix A. Note that the matrix A is diagonal. Further A being real and symmetric has real eigenvalues and the eigenvalues are the ordered diagonal elements. Matrix A represent a self-adjoint operator in an orthonormal basis of Legendre polynomials forming a real inner product space. Fig. 10(b) depicts the eigenvector matrix for A. The columns of the matrix represents each eigenvector while the eigenvector matrix being diagonal represent the orthogonal nature of the eigenvectors in the function space. Fig. 11(c) represent the eigenvalues of the matrix. The eigenvalues correspond to the various modes of the Legendre polynomials used in the approximate function space for calculating the amplitude $z(\theta)$, ω , and $\phi(r, \theta)$. Fig. 11(a) and Fig. 11(c) depicts mode 3, 4 are the most dominant ones and can approximate the amplitude, frequency and velocity potential functions. Fig. 11(d) shows the comparison of the theoretical curve obtained from the global analysis with the experimental data at the maximum penetration width for impact Weber number of 16. The experimental and theoretical curves conforms within the experimental error bounds. Further it agrees with the local analysis outlined in the previous section (3.6). For larger impact Weber number, extreme air-crater deformations occur (Fig. 7) and the above analysis needs to be generalized for high amplitudes $z(\theta)$. Further, in a general scenario the effects of viscosity has to be incorporated in the shape model and the pinned boundary conditions needs to be applied on the dynamic 1D contact line.

4. Conclusion

In conclusion, we unearthed the mechanics of air crater formation on the air-water interface during impact on an immiscible viscous liquid pool using high speed imaging and theoretical analysis. We found that the penetration process was smooth without the formation air craters/jets for low impact energies. The smooth penetration was due to the delayed air layer rupture time scale $(t_r \sim \mathcal{O}(2 \times 10^{-1}s))$. For higher impact energies, the air layer rupture time scale is reduced by three orders of magnitude $(t_r \sim \mathcal{O}(5 \times 10^{-4}s))$. The droplet experiences an impulsive force that results in the formation of capillary waves, causing the formation of air craters. The major cause of the air crater formation is the sudden deceleration of the impinging droplet. The retardation of the droplet is primarily due to viscous forces and is a monotonically increasing function of impact Weber number. We discovered that significant depth air craters during penetration are formed when the ratio of viscous force and capillary force exceeds unity ($\Gamma = \Delta p_s / \Delta p_c > 1$). Further, the air crater response time scale is also a monotonically increasing function of Weber number $(T \sim We^{1/2})$. Further, in general we found that the air crater/jet profiles could be described by the superposition of dominant eigenmodes in Legendre polynomial basis. The air crater/jet profiles were computed using a local and global analysis based on the eigenvalue problem of a inviscid constrained Rayleigh drop model with a dynamic contact line. Due to high viscosity, the entire drop surface below and including the dynamic contact line had negligible amplitude and hence assumed to be pinned. The air craters observed in the experiment were caused due to the interfacial deformation of the droplet surface area above the dynamic contact line. In future, we will generalize the idea of droplet surface response during imapct on immiscible liquids by considering the viscous Rayleigh drop model and allowing zero amplitude (pinned contact) only on the 1D dynamic contact line rather than on a 2D surface.

Supplementary movie captions

Movie 1: Supplementary movie for impact Weber number (We = 4). Recorded at 10000 FPS, playback speed 100FPS.

Movie 2: Supplementary movie for impact Weber number (We = 16). Recorded at 10000 FPS, playback speed 10FPS.

Movie 3: Supplementary movie for impact Weber number (We = 145). Recorded at 10000 FPS, playback speed 10FPS.

Acknowledgement

The authors are thankful for the funding received from the Defence Research and Development Organization (DRDO) Chair Professorship.

Declaration of Interests

The authors declare no conflict of interest.

REFERENCES

- ADRIAN, RONALD J 1991 Particle-imaging techniques for experimental fluid mechanics. Annual review of fluid mechanics 23 (1), 261–304.
- AKSOY, YUNUS TANSU, ZHU, YANSHEN, ENEREN, PINAR, KOOS, ERIN & VETRANO, MARIA ROSARIA 2020 The impact of nanofluids on droplet/spray cooling of a heated surface: a critical review. *Energies* 14 (1), 80.
- AZIZ, SHIRAZ D & CHANDRA, SANJEEV 2000 Impact, recoil and splashing of molten metal droplets. International journal of heat and mass transfer 43 (16), 2841–2857.
- BARENBLATT, GRIGORY ISAAKOVICH, BARENBLATT, GRIGORII ISAAKOVIC & ISAAKOVICH, BARENBLATT GRIGORY 1996 Scaling, self-similarity, and intermediate asymptotics: dimensional analysis and intermediate asymptotics. Cambridge University Press.
- BARTOLO, DENIS, JOSSERAND, CHRISTOPHE & BONN, DANIEL 2006 Singular jets and bubbles in drop impact. *Physical review letters* **96** (12), 124501.
- BENJAMIN, TB & SCOTT, JC 1981 Trends in applications of pure mathematics to mechanics, vol. iii.
- BOLLEDDULA, DA, BERCHIELLI, A & ALISEDA, A 2010 Impact of a heterogeneous liquid droplet on a dry surface: Application to the pharmaceutical industry. Advances in colloid and interface science 159 (2), 144–159.
- BOSTWICK, JB & STEEN, PH 2009 Capillary oscillations of a constrained liquid drop. *Physics* of Fluids **21** (3), 032108.
- BOSTWICK, JB & STEEN, PH 2013a Coupled oscillations of deformable spherical-cap droplets. part 1. inviscid motions. *Journal of Fluid Mechanics* **714**, 312–335.
- BOSTWICK, JB & STEEN, PH 2013b Coupled oscillations of deformable spherical-cap droplets. part 2. viscous motions. *Journal of Fluid Mechanics* **714**, 336–360.
- BOSTWICK, JB & STEEN, PH 2014 Dynamics of sessile drops. part 1. inviscid theory. *Journal* of fluid mechanics **760**, 5–38.
- BOSTWICK, JB & STEEN, PH 2015 Stability of constrained capillary surfaces. Annu. Rev. Fluid Mech 47 (1), 539–568.
- BRADSKI, G. 2000 The OpenCV Library. Dr. Dobb's Journal of Software Tools.
- BRADSKI, GARY & KAEHLER, ADRIAN 2008 Learning OpenCV: Computer vision with the OpenCV library." O'Reilly Media, Inc.".
- CASTILLO-OROZCO, EDUARDO, DAVANLOU, ASHKAN, CHOUDHURY, PRETAM K & KUMAR, RANGANATHAN 2015 Droplet impact on deep liquid pools: Rayleigh jet to formation of secondary droplets. *Physical Review E* **92** (5), 053022.
- CASTREJÓN-PITA, J RAFAEL, MUÑOZ-SÁNCHEZ, BEATRIZ N, HUTCHINGS, IAN M & CASTREJÓN-PITA, AA 2016 Droplet impact onto moving liquids. Journal of Fluid Mechanics 809, 716–725.
- CHE, ZHIZHAO & MATAR, OMAR K 2018 Impact of droplets on immiscible liquid films. Soft Matter 14 (9), 1540–1551.
- CHITYALA, RAVISHANKAR & PUDIPEDDI, SRIDEVI 2020 Image processing and acquisition using Python. Chapman and Hall/CRC.
- DHUPER, KARAN, GULERIA, SHAREY DEEP & KUMAR, PARMOD 2021 Interface dynamics at the impact of a drop onto a deep pool of immiscible liquid. *Chemical Engineering Science* **237**, 116541.
- GEKLE, STEPHAN & GORDILLO, JOSÉ MANUEL 2010 Generation and breakup of worthington jets after cavity collapse. part 1. jet formation. *Journal of fluid mechanics* 663, 293–330.
- GORDILLO, JOSÉ MANUEL & GEKLE, STEPHAN 2010 Generation and breakup of worthington jets after cavity collapse. part 2. tip breakup of stretched jets. *Journal of fluid mechanics* 663, 331–346.
- HARPER, EY, GRUBE, GW & CHANG, I-DEE 1972 On the breakup of accelerating liquid drops. Journal of Fluid Mechanics 52 (3), 565–591.
- HASEGAWA, K & NARA, T 2019 Energy conservation during single droplet impact on deep liquid pool and jet formation. *Aip Advances* **9** (8), 085218.
- HICKS, PETER D & PURVIS, RICHARD 2010 Air cushioning and bubble entrapment in threedimensional droplet impacts. Journal of Fluid Mechanics 649, 135–163.
- HICKS, PETER D & PURVIS, RICHARD 2011 Air cushioning in droplet impacts with liquid layers and other droplets. *Physics of fluids* **23** (6), 062104.

- KERN, VANESSA R, BOSTWICK, JOSHUA B & STEEN, PAUL H 2021 Drop impact on solids: contact-angle hysteresis filters impact energy into modal vibrations. *Journal of Fluid Mechanics* 923.
- KUNDU, PIJUSH K, COHEN, IRA M & DOWLING, DAVID R 2015 *Fluid mechanics*. Academic press.
- LAUTERBORN, WERNER & VOGEL, ALFRED 1984 Modern optical techniques in fluid mechanics. Annual Review of Fluid Mechanics 16 (1), 223–244.
- MACROBERT, THOMAS MURRAY 1967 Spherical harmonics: An elementary treatise on harmonic functions, with applications, vol. 98. Dover publications.
- MARCOTTE, FLORENCE, MICHON, GUY-JEAN, SÉON, THOMAS & JOSSERAND, CHRISTOPHE 2019 Ejecta, corolla, and splashes from drop impacts on viscous fluids. *Physical review letters* **122** (1), 014501.
- MINAMI, F & HASEGAWA, K 2022 Cavity and jet formation after immiscible droplet impact into deep water pool. *Physics of Fluids* **34** (3), 033315.
- MOGHISI, M & SQUIRE, PT 1981 An experimental investigation of the initial force of impact on a sphere striking a liquid surface. *Journal of Fluid Mechanics* **108**, 133–146.
- OPENCV 2015 Open source computer vision library.
- PASANDIDEH-FARD, M, CHANDRA, S & MOSTAGHIMI, J 2002 A three-dimensional model of droplet impact and solidification. International Journal of Heat and Mass Transfer 45 (11), 2229–2242.
- RENARDY, YURIKO, POPINET, STÉPHANE, DUCHEMIN, LAURENT, RENARDY, MICHAEL, ZALESKI, STÉPHANE, JOSSERAND, CHRISTOPHE, DRUMRIGHT-CLARKE, MA, RICHARD, D, CLANET, CHRISTOPHE & QUÉRÉ, DAVID 2003 Pyramidal and toroidal water drops after impact on a solid surface. *Journal of Fluid Mechanics* 484, 69–83.
- RIOBOO, ROMAIN, TROPEA, CAMERON & MARENGO, MARCO 2001 Outcomes from a drop impact on solid surfaces. *Atomization and sprays* **11** (2).
- ROISMAN, ILIA V & TROPEA, CAMERON 2002 Impact of a drop onto a wetted wall: description of crown formation and propagation. *Journal of Fluid Mechanics* **472**, 373–397.
- ROY, DURBAR, M, SOPHIA, RAO, SRINIVAS S. & BASU, SAPTARSHI 2022 Droplet impact on immiscible liquid pool: Multi-scale dynamics of entrapped air cushion at short timescales. *Physics of Fluids* 34 (5), 052004, arXiv: https://doi.org/10.1063/5.0091584.
- ROY, DURBAR, PANDEY, KHUSHBOO, BANIK, MENEKA, MUKHERJEE, RABIBRATA & BASU, SAPTARSHI 2019 Dynamics of droplet impingement on bioinspired surface: insights into spreading, anomalous stickiness and break-up. *Proceedings of the Royal Society A* 475 (2229), 20190260.
- SCHNEIDER, CAROLINE A, RASBAND, WAYNE S & ELICEIRI, KEVIN W 2012 Nih image to imagej: 25 years of image analysis. *Nature methods* **9** (7), 671–675.
- SHETABIVASH, H, OMMI, F & HEIDARINEJAD, G 2014 Numerical analysis of droplet impact onto liquid film. *Physics of Fluids* **26** (1), 012102.
- SIKALO, S, MARENGO, MARCO, TROPEA, CAMERON & GANIC, EN 2000 Analysis of impact of droplets on horizontal surfaces. In *Thermal Sciences 2000. Proceedings of the International Thermal Science Seminar. Volume 1.* Begel House Inc.
- SIMPKINS, PG & BALES, EL 1972 Water-drop response to sudden accelerations. *Journal of Fluid Mechanics* 55 (4), 629–639.
- STRANI, M & SABETTA, F 1984 Free vibrations of a drop in partial contact with a solid support. Journal of Fluid Mechanics 141, 233–247.
- THORAVAL, MARIE-JEAN, TAKEHARA, KOHSEI, ETOH, TAKEHARU GOJI, POPINET, STÉPHANE, RAY, PASCAL, JOSSERAND, CHRISTOPHE, ZALESKI, STÉPHANE & THORODDSEN, SIGURDUR T 2012 von kármán vortex street within an impacting drop. *Physical review letters* **108** (26), 264506.
- THORODDSEN, ST 2002 The ejecta sheet generated by the impact of a drop. Journal of Fluid Mechanics **451**, 373–381.
- THORODDSEN, ST, ETOH, TG & TAKEHARA, K 2003 Air entrapment under an impacting drop. Journal of Fluid Mechanics 478, 125–134.
- THORODDSEN, SIGURDUR T, ETOH, TAKEHARU GOJI & TAKEHARA, KOHSEI 2008 High-speed imaging of drops and bubbles. Annu. Rev. Fluid Mech. 40, 257–285.

- THORODDSEN, SIGURDUR T, THORAVAL, M-J, TAKEHARA, K & ETOH, TG 2011 Droplet splashing by a slingshot mechanism. *Physical review letters* **106** (3), 034501.
- TROPEA, CAMERON & MARENGO, MARCO 1999 The impact of drops on walls and films. Multiphase Science and Technology 11 (1).
- VAN ROSSUM, G & DRAKE, FL 2009 Python 3 reference manual createspace. Scotts Valley, CA .
- VERSLUIS, MICHEL 2013 High-speed imaging in fluids. Experiments in fluids 54 (2), 1–35.
- VAN DER WALT, STEFAN, SCHÖNBERGER, JOHANNES L, NUNEZ-IGLESIAS, JUAN, BOULOGNE, FRANÇOIS, WARNER, JOSHUA D, YAGER, NEIL, GOUILLART, EMMANUELLE & YU, TONY 2014 scikit-image: image processing in python. *PeerJ* 2, e453.
- WOOLF, DK, LEIFER, IS, NIGHTINGALE, PD, RHEE, TS, BOWYER, P, CAULLIEZ, GUILLEMETTE, DE LEEUW, G, LARSEN, SØREN EJLING, LIDDICOAT, M, BAKER, J & OTHERS 2007 Modelling of bubble-mediated gas transfer: Fundamental principles and a laboratory test. *Journal of Marine Systems* **66** (1-4), 71–91.
- WORTHINGTON, ARTHUR MASON 1877 Xxviii. on the forms assumed by drops of liquids falling vertically on a horizontal plate. *Proceedings of the royal society of London* **25** (171-178), 261–272.
- WORTHINGTON, ARTHUR MASON & COLE, REGINALD SORRÈ 1897 V. impact with a liquid surface, studied by the aid of instantaneous photography. *Philosophical Transactions of* the Royal Society of London. Series A, Containing Papers of a Mathematical or Physical Character (189), 137–148.
- YAKHSHI-TAFTI, EHSAN, CHO, HYOUNG J & KUMAR, RANGANATHAN 2010 Impact of drops on the surface of immiscible liquids. *Journal of colloid and interface science* **350** (1), 373–376.
- YAMAMOTO, KEN, MOTOSUKE, MASAHIRO & OGATA, SATOSHI 2018 Initiation of the worthington jet on the droplet impact. Applied Physics Letters **112** (9), 093701.
- YANG, ZI QIANG, TIAN, YUAN SI & THORODDSEN, SIGURDUR T 2020 Multitude of dimple shapes can produce singular jets during the collapse of immiscible drop-impact craters. *Journal of Fluid Mechanics* **904**.
- YARIN, ALEXANDER L, ROISMAN, ILIA V & TROPEA, CAMERON 2017 Collision phenomena in liquids and solids. Cambridge University Press.
- ZEFF, BENJAMIN W, KLEBER, BENJAMIN, FINEBERG, JAY & LATHROP, DANIEL P 2000 Singularity dynamics in curvature collapse and jet eruption on a fluid surface. *Nature* 403 (6768), 401–404.
- ZHANG, LV, TOOLE, J, FEZZAA, K & DEEGAN, RD 2012 Evolution of the ejecta sheet from the impact of a drop with a deep pool. *Journal of Fluid Mechanics* **690**, 5–15.