

---

# THE BUDGE PROGRAMMING LANGUAGE

---

A PREPRINT

**Boro Sitnikovski**  
 Skopje, North Macedonia  
 buritomath@gmail.com

May 25, 2022

## ABSTRACT

We present a simple, esoteric programming language based on Gödel numbering and prime factorization, enhanced with explicit, scoped loops, allowing for easy program composition. We will show the syntax and semantics and then provide a few example programs and their evaluation.

**Keywords** Programming language, computational model, Gödel numbering

## 1 Introduction

Budge (bʌʤ, b'dzh) is an esoteric programming language. It uses Gödel numbering[1] to represent registers and their values by relying on the Fundamental Theorem of Arithmetic[2]. For example, to represent the values 1, 2, and 3 in memory, we would calculate  $2^1 \cdot 3^2 \cdot 5^3$  (the first three primes 2, 3, 5 to the power of the number of the value at the corresponding register), arriving at the state  $i = 2250$ . We can extract 1, 2, and 3 from 2250 using prime factorization.

Budge uses similar constructs as FRACTRAN[3]. However, Budge provides a more convenient way to construct loops and uses integers rather than fractions to denote instructions. A negative integer will decrease a register's value, while a positive integer will increase a register's value. In addition, it provides an easy way to code loops by using nested parenthesis<sup>1</sup>. Finally, it abstracts prime numbers in the code from the programmer.

## 2 Syntax and semantics

Where data is represented as  $i \in \mathbb{N}^+$  (product of primes), the syntax of the code in Backus-Naur form[4] is:

```
<posn> ::= "1" | "2" | ...           <negn> ::= "-1" | "-2" | ...
<stmt> ::= <posn> | <negn> | ("<posn>", "<stmts>")
<stmts> ::= <stmt> | "<stmts>" | <stmt>   <code> ::= ("<stmts>")
```

Let  $p(n)$  be the  $n$ -th prime number. Let  $\text{sign}(n) = 1$  if  $n > 0$  and  $-1$  otherwise; this will determine whether we need to multiply or divide. With  $\forall x, n_x \in \mathbb{Z} \wedge n'_x \in \mathbb{Z}$ , let  $E(i, s)$  represent the evaluation of a sequence  $s$  (`<code>`) for input  $i$  be defined by:

$$E(i, s) = \begin{cases} E(i \cdot p(|n_0|)^{\text{sign}(n_0)}, (n_1, \dots, n_k)) & s = (n_0, n_1, \dots, n_k) \wedge i \cdot p(|n_0|)^{\text{sign}(n_0)} \in \mathbb{N}, \\ E(i, (n_1, \dots, n_k)) & s = (n_0, n_1, \dots, n_k) \wedge i \cdot p(|n_0|)^{\text{sign}(n_0)} \notin \mathbb{N}, \\ E(E(i, (n'_0, \dots, n'_k)), s) & s = ((P, n'_0, \dots, n'_k), n_0, \dots, n_j) \wedge i \cdot p(|P|)^{-1} \in \mathbb{N}, \\ E(i, (n_0, \dots, n_j)) & s = ((P, n'_0, \dots, n'_k), n_0, \dots, n_j) \wedge i \cdot p(|P|)^{-1} \notin \mathbb{N}, \\ i & \text{otherwise, that is, } s = () \end{cases}$$

Semantically, the first case handles increasing/decreasing a value in a register  $n_0$ . The second case is for skipping an instruction. The third and fourth cases represent the start and end of a loop (nested parenthesis).

---

<sup>1</sup>One disadvantage of the syntax for loops is that programs can't be as easily represented in memory.

### 3 Example programs in Budge

#### 3.1 Addition of numbers (evaluation explanation)

To compute  $E(2^3 \cdot 3^3, ((2, -2, 1)))$  we iterate the sequence  $(-2, 1)$  until  $\frac{i}{p(2)}$  is no longer an integer, that is,  $\frac{i}{3}$ :

1. Initially,  $i = 2^3 \cdot 3^3 = 216$ , and since  $\frac{216}{3} = 72 \in \mathbb{N}$ , proceed with evaluation.
2. Calculate  $p(|n|)^{\text{sign}(n)}$  for  $n = -2$ :  $i' = p(2)^{-1} = 3^{-1}$ . Since  $i \cdot i' \in \mathbb{N}$ , set  $i$  to  $i \cdot i' = 216 \cdot i' = 72$ .
3. Calculate  $p(|n|)^{\text{sign}(n)}$  for  $n = 1$ :  $i' = p(1)^1 = 2$ . Since  $i \cdot i' \in \mathbb{N}$ , set  $i$  to  $i \cdot i' = 72 \cdot i' = 144$ .
4. At this point, we go back and check the condition if  $\frac{144}{3} \in \mathbb{N}$  - proceed with the evaluation.
5. Calculate  $p(|n|)^{\text{sign}(n)}$  for  $n = -2$ :  $i' = p(2)^{-1} = 3^{-1}$ . Since  $i \cdot i' \in \mathbb{N}$ , set  $i$  to  $i \cdot i' = 144 \cdot i' = 48$ .
6. Calculate  $p(|n|)^{\text{sign}(n)}$  for  $n = 1$ :  $i' = p(1)^1 = 2$ . Since  $i \cdot i' \in \mathbb{N}$ , set  $i$  to  $i \cdot i' = 48 \cdot i' = 96$ .
7. At this point, we go back and check the condition if  $\frac{96}{3} \in \mathbb{N}$  - proceed with the evaluation.
8. Calculate  $p(|n|)^{\text{sign}(n)}$  for  $n = -2$ :  $i' = p(2)^{-1} = 3^{-1}$ . Since  $i \cdot i' \in \mathbb{N}$ , set  $i$  to  $i \cdot i' = 96 \cdot i' = 32$ .
9. Calculate  $p(|n|)^{\text{sign}(n)}$  for  $n = 1$ :  $i' = p(1)^1 = 2$ . Since  $i \cdot i' \in \mathbb{N}$ , set  $i$  to  $i \cdot i' = 32 \cdot i' = 64$ .
10. Now we have that  $\frac{64}{3} \notin \mathbb{N}$ , so the evaluation halts.

Thus,  $i$  is now equal to  $64 = 2^6$ . That is, the value from the first register  $p(1)$  and the value from the second register  $p(2)$  were added, and then stored in the first register,  $p(1)$ . In general,  $E(2^a \cdot 3^b, ((2, -2, 1))) = 2^n$ , with  $n = a + b$ .

#### 3.2 Other arithmetic operations

*Subtraction:*  $E(2^x \cdot 3^y, s_s) = 2^n \cdot 3^k$  where  $n = |x - y|$  and  $k = 1$  if  $y > x$ , and  $k = 0$  otherwise.

$$s_s = ((1, -1, 3, 5), (2, -2, 4, 6), (3, -3, -4), (6, -5, -6), (4, -4, 1, 3), (3, (3, -3), 2), (5, -5, 1))$$

*Multiplication:*  $E(2^x \cdot 3^y, s_m) = 2^n$  where  $n = x \cdot y$ .

$$s_m = ((1, -1, (2, -2, 3, 4), (4, -4, 2)), (2, -2), (3, -3, 1))$$

*Division:*  $E(2^a \cdot 3^d, s_d) = 2^q \cdot 3^r$  where  $a = qd + r$  and  $0 \leq r < d$ .

$$s_d = ((2, -2, 7), (1, (7, -7, 2, 8), (8, -8, 7))) \# s_s \# (9, (2, -2, (1, -1, -7), (7, -7, 8), -9)), (7, -7), (9, -9, 1), (8, -8, 2))$$

### 4 Composing and interpreting programs

As we saw with  $s_d$ , sequences can be composed by concatenating them:  $\forall s_1, \forall s_2, E(E(i, s_1), s_2) = E(i, s_1 \# s_2)$ . For example, the sequence  $(1, 2, 2, (2, -2, 1))$  is consisted of concatenating  $(1, 2, 2)$  and  $((2, -2, 1))$ ; increase the first and the second register by 1 and 2 respectively, and then add the registers together, storing the result in the first register.

We show the pseudo-code representation of this sequence by following its semantical interpretation:

```
r1 += 1; r2 += 2; // sequence 1
while (r2 > 0) { r2 -= 1; r1 += 1; } // sequence 2
// r1 += r2; r2 = 0; // sequence 2 optimized
```

### References

- [1] Douglas Hofstadter *Godel, Escher, Bach: an Eternal Golden Braid* Basic Books, Inc., 1979.
- [2] Artur Korniłowicz, Piotr Rudnicki *Fundamental Theorem of Arithmetic* Formalized Mathematics 12.2, 2004.
- [3] John H. Conway *Fractran: A simple universal programming language for arithmetic* Open problems in Communication and Computation, 1986.
- [4] Daniel D. McCracken, Edwin D. Reilly *Backus-Naur Form (BNF)* Encyclopedia of Computer Science, 2003.