Towards Size-Independent Generalization Bounds for Deep Operator Nets *

Pulkit Gopalani †[1], Sayar Karmakar[2], Dibyakanti Kumar[3], and Anirbit Mukherjee[4]

[1]Department of Computer Science & Engineering, University of Michigan, US

[2]Department of Statistics, University of Florida, US

[3]Barclays, Pune, India

[4]Department of Computer Science, The University of Manchester, UK

January 23, 2024

arXiv:2205.11359v2 [cs.LG] 22 Jan 2024

Abstract

In recent times machine learning methods have made significant advances in becoming a useful tool for analyzing physical systems. A particularly active area in this theme has been "physics-informed machine learning" which focuses on using neural nets for numerically solving differential equations. In this work, we aim to advance the theory of measuring out-of-sample error while training DeepONets – which is among the most versatile ways to solve PDE systems in one-shot.

Firstly, for a class of DeepONets, we prove a bound on their Rademacher complexity which does not explicitly scale with the width of the nets involved. Secondly, we use this to show how the Huber loss can be chosen so that for these DeepONet classes generalization error bounds can be obtained that have no explicit dependence on the size of the nets. We note that our theoretical results apply to any PDE being targeted to be solved by DeepONets.

Keywords: Rademacher complexity, DeepONets, Physics-Inspired ML, Operator Learning

*The statement of Theorem 9 has appeared previously in DeepMath 2022.

†This work was done when the author was at the Department of Electrical Engineering, Indian Institute of Technology Kanpur (IIT Kanpur), India.

1 Introduction

In the recent past, deep learning has emerged as a competitive way to solve P.D.Es numerically. We note that the idea of using nets to solve P.D.Es dates back many decades [LLF98] [BL88]. In recent times this idea has gained significant momentum and "AI for Science" [KGK21] has emerged as a distinctive direction of research. Some of the methods at play for solving P.D.Es neurally [EHJ21] are the Physics Informed Neural Networks (PINNs) paradigm [RPK19] [LYLI22], "Deep Ritz Method" (DRM, [Y+18]), "Deep Galerkin Method" (DGM), [SS18] and many further variations that have been developed of these ideas, [KKB21, EMM19, WWK21, LLSK+22, SLG22].

These different data-driven methods of solving the P.D.Es can broadly be classified into two kinds, **(1)** ones which train a single neural net to solve a specific P.D.E and **(2)** operator methods – which train multiple nets in tandem to be able to solve in "one shot" a family of differential equations, with a fixed differential operator and different "source / forcing" functions. The operator net was initiated in [CC95] and its most popular deep neural version, the DeepONet, was introduced in [LJP+21]. An unsupervised form of this idea was introduced in [WWP21a]. We note that the operator methods are particularly useful in the supervised setup when the underlying physics is not known – as is the setup in this work – and state-of-the-art approaches of this type, can be seen in works like [RMR+23].

As an explicit example of using DeepONet in the unsupervised setup, consider solving a pendulum O.D.E., $\mathbb{R}^2 \ni \frac{\mathrm{d}(y,v)}{\mathrm{d}t} = (v, -k \cdot \sin(y) + f(t)) \in \mathbb{R}^2$ for different forcing functions $f(t)$. Then using sample measurements of valid (f, y) tuples, a DeepONet setup can be trained only once, and then repeatedly be used for inference on new forcing functions f to estimate their corresponding solutions y. This approach is fundamentally unlike traditional numerical methods where one needs to rerun the optimization algorithm afresh for every new source function. In a recent study [LMC+22], the authors showed how the DeepONet setup – that we focus on in this work – has significant advantages over other competing neural operators, like the FNO [LKA+20], in solving various differential equations of popular industrial use.

As a testament to the foundational nature of the idea, we note that over the last couple of years, several variants of DeepONets have been introduced, like, [TC23, GKSK22, ZZL22, Had22, PKH+23, dSARCJ23, TC22, XLW23, LMZ23]. Different implementations of the idea of neural operator have been demonstrated to be performing well for various scientific applications, like for predicting crack shapes in brittle materials [GYYK22], for fluid flow in porous materials [CCW+23], for simulating plasmas [GS20], for seismic wave propagation [LGBC23], for weather modeling [KSH+23] etc.

In light of this burgeoning number of applications, we posit that it becomes critical that the out-of-sample performance of neural operators be mathematically understood. In this work, we take some of the first steps towards that goal by focusing on measuring the generalization error of one of the most versatile forms of operator learning, that of DeepONets – via the lens of Rademcher complexity.

Motivations for Understanding Rademacher Complexity We recall that in machine learning there is a vast lack of information about the distribution of the obtained models in any training situation. For any practically relevant stochastic training algorithm, say ALG, which is using a $m-$ sized dataset $\mathcal{S}_m$ to search over a class of predictors $\mathcal{H}$, there is only scarce mathematical control possible over the distribution of its output random variable – the random predictor thus obtained, say $\mathrm{ALG}(\mathcal{S}_m, \mathcal{H})$. Hence there is an almost insurmountable challenge in being able to control the quantity that we are really after, the out-of-sample risk of the obtained predictor i.e $R\left(\ell \circ \mathrm{ALG}(\mathcal{S}_m, \mathcal{H})\right)$ - where R denotes the expectation with respect to the true data distribution, say $\mathcal{D}$, of a loss ℓ evaluated on the predictor $\mathrm{ALG}(\mathcal{S}_m, \mathcal{H})$.

The fundamental idea that takes us beyond this conundrum is to relax our goals from aiming to control the above to aiming to control only the data averaged worst (over all possible predictors) "generalization gap" between the population and the empirical risk i.e, $\mathbb{E}_{\mathcal{S}_m \sim \mathcal{D}^m}\left[\sup_{h \in \mathcal{H}}\left(\hat{R}_m(\ell \circ h) - R(\ell \circ h)\right)\right]$ – where corresponding to a choice of loss ℓ, $\hat{R}_m(\ell \circ h)$ is the empirical estimate over the data sample $\mathcal{S}_m$ of the risk of h and $R(\ell \circ h)$ is the population risk of h over the data distribution $\mathcal{D}$. The importance of the statistical quantity, Rademacher complexity [BM03] of the function class $\ell \circ \mathcal{H}$ i.e $\mathbb{E}_{\mathbf{z}_1, \ldots, \mathbf{z}_m \sim \mathcal{D}^m}\left(\mathbb{E}_\epsilon\left[\sup_{h \in \mathcal{H}} \frac{1}{m} \sum_{i=1}^m \epsilon_i \ell \circ h(\mathbf{z}_i)\right]\right)$ (where $\epsilon_i \sim \pm 1$ are Bernoulli random variables) stems from the fact that it is what bounds this afore stated measure of the generalization gap.

It is to be noted that trying to control the above frees us from the specifics of any particular M.L. training algorithm being used (of which there is a myriad of heuristically good options) to find $\mathrm{arginf}_{h \in \mathcal{H}} R(\ell \circ h)$. But on the other hand, by analyzing the Rademacher complexity we gain insight into how the choice of the hypothesis class $\mathcal{H}$, the choice of the loss ℓ, and the data distribution $\mathcal{D}$ interact to determine the ability to find $\mathrm{arginf}_{h \in \mathcal{H}} R(\ell \circ h)$ via empirical estimates. This trade-off becomes immensely helpful when $\mathcal{H}$ is very complicated, as is the focus here, that of $\mathcal{H}$ being made of DeepOperatorNets. In Appendix D, we review some of the recent advances in the Rademacher analysis of neural networks.

We crucially note that any condition on $m, \ell, \mathcal{H}$ and $\mathcal{D}$ that makes Rademacher complexity small is a sufficient condition for the empirical and the population risk to be close for any predictor in the class $\mathcal{H}$.

In this work, we will compute the Rademacher complexity of appropriate classes of DeepONets and use it to give the first-of-its-kind bounds on their generalization error which do not explicitly scale with the number of parameters. Generalization bounds that do not scale with the size of the nets can be seen as a necessary first step towards explaining the success of overparameterized architectures for that learning task. Further, our experiments will demonstrate that the complexity measures of DeepONets as found by our Rademacher analysis indeed correlate to the true generalization gap, over varying sizes of the training data.

1.1 Overview of Training DeepONets & Our Main Results

Following [LJP+21], we refer to the schematic in Fig.1 below for the DeepONet architecture,




Figure 1: A Sketch of the DeepONet ("DON") Architecture

In the above diagram the Branch Network and the Trunk Network are neural nets with a common output dimension. $\mathbf{x}_B(f) \in \mathbb{R}^{d_1}$, the input to the branch net is an "encoded" version of a function f i.e a discretization of f onto a d_1-sized grid of "sensor points" in its input domain. $\mathbf{x}_T \in \mathbb{R}^{d_2}$ is the trunk input. If the activation is σ at all layers and the branch net and the trunk net's layers are named $\mathbf{B}_k, k = 1, 2, \ldots, q_B$ and $\mathbf{T}_k, k = 1, 2, \ldots, q_T$ respectively, then the above architecture implements the map,

$$\mathbb{R}^{d_1} \times \mathbb{R}^{d_2} \ni (\mathbf{x}_B(f), \mathbf{x}_T) \mapsto \text{DeepONet}(\mathbf{x}_B(f), \mathbf{x}_T) \coloneqq \left(\mathbf{B}_{q_B}(\sigma(\mathbf{B}_{q_B-1}(\ldots\sigma(\mathbf{B}_1(\mathbf{x}_B(f)))\ldots)))\right)^{\top}\left(\mathbf{T}_{q_T}(\sigma(\mathbf{T}_{q_T-1}(\ldots\sigma(\mathbf{T}_1(\mathbf{x}_T))\ldots)))\right) \tag{1}$$

For a concrete example of using the above architecture, consider the task of solving the pendulum O.D.E from the previous section, $\mathbb{R}^2 \ni \frac{\mathrm{d}(y,v)}{\mathrm{d}t} = (v, -k \cdot \sin(y) + f(t)) \in \mathbb{R}^2$. For a fixed initial condition, here the training/test data sets would be 3−tuples of the form, $(\mathbf{x}_B(f), x_T, y)$ where $y \in \mathbb{R}$ is the angular position of the pendulum at time $t = x_T$ for the forcing function f. Typically y is a standard O.D.E. solver's approximate solution. Given m such training data samples, the ℓ_2 empirical loss would be,

$$\hat{\mathcal{L}}_{\text{DON}} \coloneqq \frac{1}{2m}\sum_{i=1}^{m}\left(y_i - \text{DeepONet}(\mathbf{x}_B(f_i), x_{T,i})\right)^2. \tag{2}$$

The rationale for this loss function above originates from the universal approximation property of DeepONets which we have reviewed as Theorem C.3.

Theorem 1 (Informal Statement of Theorem 9) *Consider a class of DeepONets, with absolute value activation, whose branch and trunk networks are both of depth n (i.e $q_B = q_T = n$ in equation 1) and suppose that the squared norms of the inputs to them are bounded in expectation by $M_{x,B}$ and $M_{x,T}$ respectively. Then the average Rademacher complexity, for training with samples of size m, is bounded by,*

$$\mathcal{O}\left(\frac{2^{n-1}\mathcal{C}_{n,n-1}}{\sqrt{m}}\left(\prod_{j=2}^{n-1}\mathcal{C}_{-j,-j}\right)M_{x,B}M_{x,T}\right) \tag{3}$$

where the constants $\mathcal{C}_{n,n-1}$ and $\mathcal{C}_{-k,-k}$, $k = 2, 3, \ldots, n-1$ are defined so that the weight matrices of the Branch Network and the Trunk Network of all the DeepONets in the class satisfy the following bounds,

$$\sum_{k_1=1}^{b_{-1}} \sum_{k_2=1}^{t_{-1}} \left| \left[\sum_{j=1}^{p} (\mathbf{B}_{n,j} \mathbf{T}_{n,j}^{\top}) \right]_{k_1,k_2} \right| \cdot \left\| \mathbf{B}_{n-1,k_1} \right\| \cdot \left\| \mathbf{T}_{n-1,k_2} \right\| = \mathcal{C}_{n,n-1},$$

$$\sup_{(\mathbf{v},\mathbf{w})} \sum_{j_1=1}^{b_{-k}} \sum_{j_2=1}^{t_{-k}} \left| (\mathbf{v}\mathbf{w}^{\top})_{j_1,j_2} \right| \cdot \left\| \mathbf{B}_{n-k,j_1} \right\| \left\| \mathbf{T}_{n-k,j_2} \right\| = \mathcal{C}_{-k,-k} \qquad \forall k = 2, \ldots, n-1, \tag{4}$$

where in each sum, above $\mathbf{v}, \mathbf{w}$ are on the unit spheres of the same dimensionality as the number of rows in $\mathbf{B}_{n-k}$ and $\mathbf{T}_{n-k}$ respectively. (For any branch weight matrix say $\mathbf{B}_p$, in above we have denoted its j-th row as $\mathbf{B}_{p,j}$ and similarly for the trunk.)

Towards making the above measures computationally more tractable, in Appendix K we have shown that $\forall k = 2, \ldots, n-1$ one can choose an upperbound on $\mathcal{C}_{-k,-k}$ i.e

$$\tilde{\mathcal{C}}_{-k,-k} = \|\mathbf{X}\| \text{ where } \mathbf{X} \in \mathbb{R}^{b_{-k} \times t_{-k}} \text{ with } \mathbf{X}_{j_1,j_2} \coloneqq \left\| \mathbf{B}_{n-k,j_1} \right\| \cdot \left\| \mathbf{T}_{n-k,j_2} \right\| \tag{5}$$

In Section 2.3, we undertake an empirical study on a particular component of the generalization bound, represented as $\frac{\mathcal{C}_{n,n-1}}{\sqrt{m}}, \left(\prod_{j=2}^{n-1} \tilde{\mathcal{C}}_{-j,-j} \right)$, in relation to the generalization gap to assess the correlation between these factors.

Having proven the key theorem above, the following generalization bound with a modified loss function for DeepONets follows via standard arguments about Rademacher complexity,

Theorem 2 (Informal Statement of Theorem 10) *Considering the same class of DeepONets as in Theorem 1 and using the Huber loss $\ell_{H,\delta}(x) \coloneqq \begin{cases} \frac{1}{2}x^2 & \text{for } |x| \le \delta \\ \delta \cdot (|x| - \frac{1}{2}\delta) & \text{for } |x| > \delta \end{cases}$ with $\delta = \left(\frac{1}{2}\right)^{n-1}$ as the loss function. The expectation over data of the supremum of the generalization error over the above class of DeepONets can then be bounded by, $\mathcal{O}\left(\frac{\mathcal{C}_{n,n-1}}{\sqrt{m}} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j} \right) M_{x,B} M_{x,T} \right)$ where $\mathcal{C}_{n,n-1}$ and $\mathcal{C}_{-j,-j}$ are the constants defined in Theorem 1.*

To the best of our knowledge, the above theorem is a first-of-ts-kind demonstration of a generalization error bound for DeepONets which does not have any explicit dependency on the number of training parameters. Interestingly, in [PMR+23], the authors had recently demonstrated empirically the effectiveness of using Huber loss for training neural networks to solve P.D.Es. Albeit for a different setup, that of solving PDE systems, in this work, we provide a theoretical justification for why Huber losses could be well suited for such tasks, and in here we are also able to derive a good value of δ while this hyperparameter choice in [PMR+23] was not grounded in any theory. In Appendix B we give an experimental study of how lowering the value of δ indeed helps lower generalization error.

In light of the above, we note the following *practical applicability* and *qualitative significance* of our bounds on the Rademacher complexity and generalization error of DeepONets.

Choosing the Loss Function Theorem 10 suggests that training on the Huber loss function could lead to better generalization. We give a performance demonstration in Appendix A for Huber loss function at $\delta = \frac{1}{2^{n-1}}$ for DeepONets using tanh activation (although our above theorem does not capture this choice of activation) and we note that it gives 2 orders of magnitude lower test error than for the same experiment using ℓ_2 loss.

Additionally, note that, DeepONets without biases and with positively homogeneous activation, are invariant to scaling the branch net's layers $\mathbf{B}_k$ and trunk net's layers $\mathbf{T}_k$ by any μ_k & $\lambda_k > 0$ respectively $\forall k$ s.t $\prod_k (\mu_k \cdot \lambda_k) = 1$ *This is a larger symmetry than for usual nets but our complexity measure mentioned above is invariant under this combined scaling.* This can be seen as being strongly suggestive of our result being a step in the right direction.

Explaining Overparameterization Since our generalization error bound has no explicit dependence on the width or the depth (or the number of parameters), it constitutes a step towards explaining the benefits of overparameterization in this new setup.

1.1.1 Comparison to [LMK22]

Firstly, we note that none of the theorems presented here depend on the results in [LMK22]. The proof strategies are entirely independent. *Secondly,* to the best of our knowledge, Theorem 5.3 in [LMK22] is the only existing result on generalization error bounds for DeepONets. However, their bound has an explicit dependence on the total number of parameters (the parameter d_θ there) in the DeepONet. Such a bound is not expected to explain the benefits of overparameterization, which is one of the key features of modern deep learning [DMB21, YYY+20].

We note that for usual implementations for DeepONets, where depths are typically small and the layers are wide, for a class of DeepONets at any fixed value of our complexity measure i.e $\mathcal{C}_{n,n-1}\left(\prod_{j=2}^{n-1}\mathcal{C}_{-j,-j}\right)$, a generalization error bound based on our Rademacher complexity bound in Theorem 9 will be smaller than the one in [LMK22] that scales with the total number of parameters.

Further, as pointed out in our second main result, Theorem 10, our Rademacher bound lends itself to an entirely size-independent generalization bound when the loss is chosen as a certain Huber loss.

Notation Given any $U \subset \mathbb{R}^n$, denote as $L^2(U)$ the set of all functions $f : U \to \mathbb{R}$ s.t $\int_U f^2(\mathbf{x})\,\mathrm{d}\mu\,(\mathbf{x}) < \infty$ where μ is the standard Lebesgue measure on $\mathbb{R}^n$. And we denote as $C(U)$, the set of all real valued continuous functions on U. The unit sphere in $\mathbb{R}^k$ is denoted by $S^{k-1} \coloneqq \left\{\mathbf{x} \in \mathbb{R}^k \mid \|x\|_2 = 1\right\}$. For any matrix $\mathbf{A}$, $\|\mathbf{A}\| = \sup_{\mathbf{v}\neq 0}\frac{\|\mathbf{A}\mathbf{v}\|_2}{\|\mathbf{v}\|_2}$ denotes its spectral norm.

1.2 The Mathematical Setup

Firstly we define the general DeepONet architecture which will be our focus in this work.

Definition 3 (A DeepONet (Version 2)) *Let p be the common output dimension of the "branch net" and the "trunk net". Let q_B be the depth of the branch network and q_T be the depth of trunk net. Let $\mathbf{B}_i$, $i = 1,\ldots,B$ be a set of the branch net's weight matrices s.t the product $\mathbf{B}_{q_B}\cdot\ldots\cdot\mathbf{B}_1$ is well-defined and $\mathbf{B}_{q_B}$ has p rows. Let $\mathbf{T}_j$, $j = 1,\ldots,T$ be a valid set of trunk net's weight matrices s.t the product $\mathbf{T}_{q_T}\cdot\ldots\cdot\mathbf{T}_1$ is well-defined and $\mathbf{T}_{q_T}$ has p rows. Further, let σ_1 and σ_2 be two $\mathbb{R}\to\mathbb{R}$ functions (applied pointwise on vector inputs), d_1 be the domain dimension of $\mathbf{B}_1$ and d_2 be the domain dimension of $\mathbf{T}_1$. Then we define the corresponding DeepONet as the map,*

$$\mathbb{R}^{d_1}\times\mathbb{R}^{d_2}\ni(\mathbf{x}_B,\mathbf{x}_T)\mapsto \mathrm{DeepONet}(\mathbf{x}_B,\mathbf{x}_T) = \langle f_B(\mathbf{x}_B), f_T(\mathbf{x}_T)\rangle \in \mathbb{R},$$

where,

$$f_B(\mathbf{x}_B) \coloneqq \mathbf{B}_{q_B}(\sigma_1(\mathbf{B}_{q_B-1}(\ldots\sigma_1(\mathbf{B}_1(\mathbf{x}_B))\ldots))),$$
$$f_T(\mathbf{x}_T) \coloneqq \mathbf{T}_{q_T}(\sigma_2(\mathbf{T}_{q_T-1}(\ldots\sigma_2(\mathbf{T}_1(\mathbf{x}_T))\ldots))).$$

When required to emphasize some constraint on the weights of a DeepONet, we will denote $\mathrm{DeepONet}(\mathbf{x}_B,\mathbf{x}_T)$ *by* $\mathrm{DeepONet}_{\mathbf{w}}(\mathbf{x}_B,\mathbf{x}_T)$, *where* $\mathbf{w}$ *collectively stands for all the weight matrices in branch and trunk networks.*

Corresponding to the DeepONets defined above we define the following width parameters for the different weight matrices.

Definition 4 (Width Parameters for DeepONets)

- *For $k = 1,\ldots,q_B-1$ and $\ell = 1,\ldots,q_T-1$, define b_{-k} & $t_{-\ell}$ to be the number of rows in the weight matrices $\mathbf{B}_{q_B-k}$ and $\mathbf{T}_{q_T-\ell}$ respectively.*
- *In the setup of Definition 3, we define the functions $\mathbf{f}'_B$ and $\mathbf{f}'_T$ s.t given any m inputs to a* DeepONet *as, $\{(\mathbf{x}_{B,i},\mathbf{x}_{T,i}) \mid i = 1,\ldots,m\}$ we have the following equalities,*

$$f_B(\mathbf{x}_{B,i}) = \mathbf{B}_{q_B}\sigma_1\left(\mathbf{B}_{q_B-1}\mathbf{f}'_B(\mathbf{x}_{B,i})\right),\ f_T(\mathbf{x}_{T,i}) = \mathbf{T}_{q_T}\sigma_2\left(\mathbf{T}_{q_T-1}\mathbf{f}'_T(\mathbf{x}_{T,i})\right). \tag{6}$$

Next, we define a certain smoothness condition that we need for the activation functions used.

Assumption 5 *Let $\phi_P,\phi_Q : \mathbb{R}\to\mathbb{R}$ be the activation functions for the branch net and the trunk net such that $\exists L > 0$ s.t for any two sets of functions valued in $\mathbb{R}$, say $\mathcal{P}$ and $\mathcal{Q}$, $\forall(p,q),(p',q') \in \mathcal{P}\times\mathcal{Q}$ and $\forall(\mathbf{x},\mathbf{y}) \in \mathrm{Domain}(\mathcal{P})\times\mathrm{Domain}(\mathcal{Q})$, the following inequality holds,*

$$|\phi_P(p(\mathbf{x}))\phi_Q(q(\mathbf{y})) - \phi_P(p'(\mathbf{x}))\phi_Q(q'(\mathbf{y}))| \le L|p(\mathbf{x})q(\mathbf{y}) - p'(\mathbf{x})q'(\mathbf{y})|. \tag{7}$$

Our main results work under the above assumption and hence in particular, our results apply to the absolute value map, $\mathbb{R}\ni x\mapsto|x|\in\mathbb{R}$, being the activation function in both the branch and the trunk net. In Appendix J we will indicate why this is sufficient to also capture DeepONets with ReLU activations and facing bounded data.

Towards formalizing the setup of the loss functions and the training data for training DeepONets we recall the definition of the Huber loss.

Definition 6 (Huber Loss) *For some $\delta \ge 0$ the Huber loss is defined as*

$$\ell_{H,\delta}(x) \coloneqq \begin{cases}\frac{1}{2}x^2 & \text{for } |x|\le\delta\\ \delta\cdot(|x|-\frac{1}{2}\delta) & \text{for } |x|>\delta\end{cases}$$

Corresponding to a choice of any univariate loss function (ℓ), like Huber loss as above, we define the DeepONet training loss as follows.

Definition 7 (A Loss Function for DeepONets) *We continue in the same setup as Definition C.1 and define a function class of allowed forcing functions $\mathcal{F} \subset C(D)$. Further, we consider* DeepONet *maps as given in Definition 3, mapping as* DeepONet $: \mathbb{R}^{d_1} \times \mathbb{R}^{d_2} \to \mathbb{R}$ *and consider an instance of the training data given as,*

$$\{(f_i, \mathbf{x}_{T,i}) \in \mathcal{F} \times \mathbb{R}^{d_2} \mid i = 1, \ldots, \mathcal{S}\}.$$

Then the corresponding DeepONet loss function is given by,

$$\hat{\mathcal{L}}_{\text{DON}} = \frac{1}{m} \sum_{i=1}^{m} \ell(\mathcal{G}(f_i)(\mathbf{x}_{T,i}) - \text{DeepONet}(\mathbf{x}_{B,i}, \mathbf{x}_{T,i})). \tag{8}$$

where ℓ is some loss function. Here we assume a fixed grid of size d_1 on which the function f_i gets discretized, to get $\mathbf{x}_{B,i} \in \mathbb{R}^{d_1}$.

As the DeepONet function varies, corresponding to it a class of loss functions gets defined via the above equation. This class of DeepONets can be seen as being parameterized by the different choices of weights on the chosen architecture.

Also, it can also be seen that the loss function in the experiment described in Section 1.1 was a special case of the loss in equation 8 for $\ell(x) = \frac{x^2}{2}$, the squared loss – and if we assume that the numerical solver exactly solved the forced pendulum O.D.E.

Next we define the key statistical quantity, that of Rademacher complexity, which we focus on as our chosen way to measure generalization error for DeepONets.

Definition 8 (Empirical and Average Rademacher complexity) *For a function class $\mathcal{K}$, suppose being given a $m-$sized data-set of points $\{\mathbf{x}_i \mid i = 1, \ldots, m\}$ in the domain of the elements in $\mathcal{K}$. For $\epsilon_i \sim \pm 1$ with equal probability, the corresponding empirical Rademacher complexity is given by $\hat{\mathcal{R}}_m(\mathcal{K}) = \mathbb{E}_\epsilon \left[\sup_{k \in \mathcal{K}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i k(\mathbf{x}_i)\right]$. If the elements of this data-set above are sampled from a distribution P, then the average Rademacher complexity is given by,*

$$\mathcal{R}_m(\mathcal{K}) = \mathop{\mathbb{E}}_{\mathbf{x}_1, \ldots, \mathbf{x}_m \sim P} \left(\mathop{\mathbb{E}}_{\epsilon} \left[\sup_{k \in \mathcal{K}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i k(\mathbf{x}_i) \right] \right) \tag{9}$$

The crux of our mathematical analysis will be to uncover a recursive structure between the Rademacher complexity of DeepONets and certain DeepONets of one depth lower in the branch and the trunk network, and which would always have one-dimensional outputs for the branch and the trunk and which share weights with the original DeepONet in the corresponding layers.

2 Results

Our central result about Rademacher complexity of DeepONets will be stated in Theorem 9 of Section 2.1 and consequent to that our result about bounding the generalization error of DeepONets will be stated in Theorem 10 of Section 2.2. In Section 2.3, we present an empirical study of our bound on Rademacher complexity for a DeepONet trained to solve the Burgers' P.D.E.

2.1 First Main Result : Rademacher Complexity of DeepONets

In the result below we will see how for a certain class of activations, we can get a bound on the Rademacher complexity of DeepONets which does not scale with the width of the nets for the branch and the trunk nets being of arbitrary equal depths.

Theorem 9 (Rademacher Complexity of Special Symmetric DeepONets) *We consider a special case of DeepONets as given in Definition 3, with (a) $q_B = q_T = n$, and (b) σ_1, σ_2 satisfies Assumption 5 for some constant $L > 0$, and they are positively homogeneous. Further, let b_{-i} and t_{-i} be the number of rows of the weight matrices $\mathbf{B}_{n-i}$ and $\mathbf{T}_{n-i}$ respectively, as in Definition 4, for $i \geq 1$ and recall from Definition 3 that p is the number of rows of $\mathbf{B}_n$ and $\mathbf{T}_n$. Then given a class of*

DeepONet maps as above, we define the following $n-1$ constants, $\mathcal{C}_{n,n-1} > 0$ and $\mathcal{C}_{-k,-k} > 0$, $k = 2, \ldots, n-1$, such that for $\mathcal{S}_k \coloneqq S^{b_{-k}-1} \times S^{t_{-k}-1}$, all the DeepONet maps in the class satisfy the following bounds,

$$\sum_{k_1=1}^{b_{-1}} \sum_{k_2=1}^{t_{-1}} \left\|\mathbf{B}_{n-1,k_1}\right\| \cdot \left\|\mathbf{T}_{n-1,k_2}\right\| \cdot \left|\left[\sum_{j=1}^{p} (\mathbf{B}_{n,j}\mathbf{T}_{n,j}^{\top})\right]_{k_1,k_2}\right| \leq \mathcal{C}_{n,n-1},$$

$$\sup_{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_k} \sum_{j_1=1}^{b_{-k}} \sum_{j_2=1}^{t_{-k}} \left|(\mathbf{v}\mathbf{w}^{\top})_{j_1,j_2}\right| \left\|\mathbf{B}_{n-k,j_1}\right\| \left\|\mathbf{T}_{n-k,j_2}\right\| \leq \mathcal{C}_{-k,-k}, \ \forall k = 2, \ldots, n-1.$$

Then given training data as in Definition 7, the empirical Rademacher complexity of this class is bounded as,

$$\hat{\mathcal{R}}_m \leq \frac{(2L)^{n-1}\mathcal{C}_{n,n-1}}{m} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j}\right) \sqrt{\sum_{i=1}^{m} \left\|\mathbf{x}_{B,i}\right\|_2^2 \left\|\mathbf{x}_{T,i}\right\|_2^2}.$$

Further assuming that the input distribution over $\mathcal{F} \times \mathbb{R}^{d_2}$ induces marginals distributions s.t $\mathbb{E}\left[\left\|\mathbf{x}_B\right\|_2^2\right] \leq M_{x,B}^2, \mathbb{E}\left[\left\|\mathbf{x}_T\right\|_2^2\right] \leq M_{x,T}^2$, we have the average Rademacher complexity of the same class bounded as,

$$\mathcal{R}_m \leq \frac{(2L)^{n-1}\mathcal{C}_{n,n-1}}{\sqrt{m}} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j}\right) M_{x,B} M_{x,T}.$$

The proof for the above is outlined in Section 4. For $\sigma_1(x) = \sigma_2(x) = |x|$ i.e for DeepONets with absolute value activations, we have $L = 1$ and hence the subsequent simplification also happens in the result in Theorem 9.

2.2 Second Main Result : Size-Independent Generalization Error Bound for DeepONets Trained via a Huber Loss on Unbounded Data

Theorem 10 (Generalization Error Bound for DeepONet) *We continue with the setup of the DeepONets as in Theorem 9 but with $\sigma_1(x) = \sigma_2(x) = |x|$. For an operator $\mathcal{G} : C(D) \to H^s(U)$ where $H^s(U)$ is the L^2-based Sobolev space for some $s > 0$, a class of forcing functions $\mathcal{F} \subset C(D)$ and $\mathcal{W}$ a set of possible weights $\mathbf{w}$ for DeepONets (denoted as $\text{DeepONet}_{\mathbf{w}}$), we define the function class $\mathcal{H}$ as,*

$$\mathcal{H} \coloneqq \{\mathcal{F} \times \mathbb{R}^{d_2} \ni (f, \mathbf{x}_T) \mapsto \mathcal{G}(f)(\mathbf{x}_T) - \text{DeepONet}_{\mathbf{w}}(\mathbf{x}_B(f), \mathbf{x}_T) \in \mathbb{R} \mid \mathbf{w} \in \mathcal{W}\}$$

Then for Huber loss $\ell_{H,\delta}(\cdot)$ as in Definition 6 with $\delta = \left(\frac{1}{2}\right)^{n-1}$ where n is the depth of the branch and the trunk nets we have the following generalization bound,

$$\begin{aligned} &\mathbb{E}_{\{(f_i,\mathbf{x}_{T,i})^{iid}_{\sim}\mathcal{D} \ | i=1\ldots m\}} \left[\sup_{\mathbf{w}\in\mathcal{W}} \left[\frac{1}{m}\sum_{i=1}^{m} \ell_{H,\delta}(h(f_i,\mathbf{x}_{T,i})) - \mathbb{E}_{(f,\mathbf{x}_T)\sim\mathcal{D}}\left[\ell_{H,\delta}(h(f,\mathbf{x}_T))\right]\right]\right] \\ &\leq \frac{2\mathcal{C}_{n,n-1}}{\sqrt{m}} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j}\right) M_{x,B} M_{x,T} \end{aligned} \tag{10}$$

where $\mathcal{C}_{n,n-1}$ and $\mathcal{C}_{-j,-j}$ are the constants as defined in Theorem 9, and $\mathcal{D}$ is a distribution over $\mathcal{F} \times \mathbb{R}_{d_2}$.

The proof for the above theorem is given in Section 4.

2.3 An Experimental Exploration of the Proven Rademacher Complexity Bound for DeepONets

For our experiments, we consider the following specification of the Burgers' P.D.E with periodic boundary conditions,

$$\frac{\partial s}{\partial t} + s\frac{\partial s}{\partial x} = \kappa \frac{\partial^2 s}{\partial x^2}, \quad (x,t) \in [-\pi, \pi] \times [0, \mathrm{T}]$$
$$s(x-\pi, t) = s(x+\pi, t), s(x, 0) = u(x)$$

where, $\kappa > 0$ denotes the fluid viscosity, $u(x)$ is a 2π-periodic initial condition with zero mean i.e. $\int_{-\pi}^{\pi} u(x)dx = 0$ and $\rho, \mathrm{T} \in \mathbb{R}$.

Hence it follows that the solution operator of Definition C.1 corresponding to the above maps the initial condition u to the solution to the Burgers' P.D.E, s. Hence, we will approximate the implicit solution operator ($\mathcal{G}$) with a DeepONet ($\tilde{\mathcal{G}}$) - which for this case would be a map as follows,

$$\mathbb{R}^m \times \mathbb{R}^2 \to \mathbb{R},\ (\mathbf{v}, \mathbf{y}) \mapsto \tilde{\mathcal{G}}(\mathbf{v}, \mathbf{y}) := \sum_{k=1}^{q} \mathcal{N}_{\mathrm{B,k}}(\mathbf{v}) \cdot \mathcal{N}_{\mathrm{T,k}}(\mathbf{y})$$

where $\mathcal{N}_\mathrm{B}$ and $\mathcal{N}_\mathrm{T}$ are any two neural nets mapping $\mathbb{R}^m \to \mathbb{R}^q$ and $\mathbb{R}^2 \to \mathbb{R}^q$ respectively - the Branch net and the Trunk net. In above, q, the common output dimension of the branch and the trunk net is a hyperparameter for the experiment.

The data required to set up the training for the above map $\tilde{G}$ can be summarized as a 3−tuple of tensors, $(u_{\text{training}},\ y_{\text{training}},\ s_{\text{training}})$ of dimensions and descriptions as given below.

- $u_{\text{training}} \in \mathbb{R}^{N_{\text{training}} \times m}$ = evaluations of the N_{training} number of input functions at the m sensors. We denote the i^{th} row of the above as, $[u_i(x_1), u_i(x_2), \ldots, u_i(x_\mathrm{m})]\ \forall i \in \{1, \ldots, N_{\text{training}}\}$
- $y_{\text{training}} \in \mathbb{R}^{N_{\text{training}} \times P_{\text{training}} \times 2}$ = P_{training} number of uniformly sampled collocation points in $\mathbb{R}^2$ corresponding to each of the N_{training} number of input functions. And $\forall \mathrm{i} \in \{1, \ldots, N_{\text{training}}\}$, we denote the sampled points as $\{(x_{\mathrm{i,j}}, t_{\mathrm{i,j}}) \mid j = 1, \ldots, P_{\text{training}}\} \overset{\text{uniform}}{\sim} ([-\pi, \pi] \times [0, T])^{P_{\text{training}}}$
- $s_{\text{training}} \in \mathbb{R}^{N_{\text{training}} \times\ P_{\text{training}}}$ = the value of the numerical solution of the P.D.E at the respective collocation points. And the $(i, j)^{\text{th}}$−entry of this would be denoted as $s_\mathrm{i}(x_{\mathrm{i,j}}, t_{\mathrm{i,j}})$.

In terms of the above training data, the corresponding training loss (Definition 7) is,

$$\mathcal{L}_{\text{Training}}(\theta) = \frac{1}{N_{\text{training}} P_{\text{training}}} \sum_{i=1}^{N_{\text{training}}} \sum_{j=1}^{P_{\text{training}}} \ell\left(s_i(x_{\mathrm{i,j}}, t_{\mathrm{i,j}}) - \sum_{k=1}^{q} \mathcal{N}_{\mathrm{B,k}}(u_i(x_1), u_i(x_2), \ldots, u_i(x_m)) \cdot \mathcal{N}_{\mathrm{T,k}}(x_{\mathrm{i,j}}, t_{\mathrm{i,j}}) \right) \quad (11)$$

whereby in our experiments ℓ is either chosen as the ℓ_2 loss or the Huber loss and θ denotes the vector of all trainable parameters over both the nets. Similarly as above the test loss $\mathcal{L}_{\text{Test}}$ would be defined corresponding to a random sampling of N_{test} input functions and P_{test} points in the domain of the P.D.E where the true solution is known corresponding to each of these test input functions.

Further, for our experiments, we sampled the input functions u_i by sampling functions of the form, $u_i(x) = \sum_{n=1}^{N} c_n \sin((n+1)x)$, where the coefficients were sampled as, $c_n \sim \mathcal{N}(0, A^2)$, with A and N being arbitrarily chosen constants. This way of sampling ensures that the functions chosen are all 2π-periodic and will have zero mean in the interval $[-\pi, \pi]$ - as required in our setup.

In this section, we demonstrate our Rademacher complexity bound by training DeepONets on the above loss function and measuring the generalization gap of the trained DeepONet obtained and computing for this trained DeepONet an upperbound on the essential part of our Rademacher bound (i.e $\frac{C_{n,n-1}}{\sqrt{m}} \left(\prod_{j=2}^{n-1} \tilde{C}_{-j,-j} \right)$ where $\tilde{C}_{-k,k}$ is as defined in equation 5). Then we vary the number of training data (i.e $N_{\text{training}} \times P_{\text{training}}$) and show that the two numbers computed above are significantly correlated as this training hyperparameter is varied. We use branch and trunk nets each of which are of depth 3 and width 100.


The correlation plots shown in Figures 2a and 2b, correspond to training on the Huber loss function, with two different values of δ - and the left plot corresponding to the special value of $\delta = \frac{1}{4}$ where the size independent generalization bound in Theorem 10 clicks for this setup.

In Figure 3 we repeat the same experiments but for the ℓ_2 loss function and show that the required correlation persists even with this loss which is outside the scope of Theorem 10.


3 Discussion

The most immediate research direction that is being suggested by our generalization error bound is to explore if the advantages shown here for Huber loss can make DeepONets competitive with CNO [RMR+23].

Further, in [WWP21b], an unsupervised variation of the loss function of a DeepONet was shown to give better performance. In [GYYK22], authors employ a variational framework for solving differential equations using DeepONets, through a novel loss function. Understanding precisely when these variations in the loss function used give



(a) δ=0.25, correlation = 0.857



(b) δ=0.4, correlation = 0.791

Figure 2: The above plot shows the behaviour of the measured generalization error with respect to $\frac{\mathcal{C}_{3,2}\,\tilde{\mathcal{C}}_{-2,-2}}{\sqrt{m}}$ for training DeepONets with empirical loss as given in equation 11, specialized to the Huber loss (Definition 6) for the stated values of δ and for the branch and the trunk nets being of depth 3. Each point is labelled by the number of training data used in that experiment.

advantages over the basic DeepONet loss is yet another interesting direction for future research - and the path towards such goals could be to explore if the methods demonstrated here for computation of generalization bounds can be used for these novel setups too.

Also, it would be fruitful to understand how the generalization bounds obtained in this work can be modified to cater to the variations of the DeepONet architecture [KGKS23], [BKH+23] [LMC+22] that are getting deployed.

In the context of understanding the generalization error of Siamese networks, the authors in [DAS+21] dealt with a certain product of neural outputs structure (where the nets share weights). In their analysis, the authors bound the Rademacher complexity via covering numbers. Since we try to directly bound the Rademacher complexity for DeepONets, it would be interesting to investigate if our methods can be adapted to improve such results about Siamese nets.

Lastly, we note that the existing bounds on the Rademacher complexity of nets have typically been proven by making ingenious use of the algebraic identities satisfied by Rademacher complexity (Theorem 12 in [BM03]). But to the best of our knowledge, we are not aware of any general result on how Rademacher complexity of a product of function spaces can be written in terms of individual Rademacher complexities. We posit that such a mathematical development, if achieved in generality, can be a significant advance affecting various fields.




Figure 3: The above plot shows the behaviour of the measured generalization error with respect to $\frac{\mathcal{C}_{3,2}\,\tilde{\mathcal{C}}_{-2,-2}}{\sqrt{m}}$ for training DeepONets with empirical loss as given in equation 11, specialized to the ℓ_2 loss and for the branch and the trunk nets being of depth 3. Each point is labelled by the number of training data used in that experiment.

4 Methods

In this section, we will outline the proofs of the main results, Theorems 9 and 10. We would like to emphasize that the subsequent propositions 13 and 14 hold in more generality than Theorem 9, because they do not need the branch and the trunk nets to be of equal depth.

Outline of the Proof Techniques Derivation of the first main result, Theorem 9, involves 3 key steps: **(a)** formulating a variation of the standard Talagrand contraction (Lemma 11) **(b)** using this to bound the Rademacher complexity of a class of DeepONets with certain activations (e.g. absolute value) by the Rademacher complexity for a class of DeepONets having one less depth and 1−dimensional outputs, for both the branch and the trunk (Lemma 13) and lastly **(c)** uncovering a recursive structure for the Rademacher complexity across depths between special DeepONet classes having 1−dimensional outputs for both the branch and the trunk. (Lemma 14).

Lemma 13 removes the last 4 matrices from the DeepONet (2 each from the branch and the trunk) leading to one-dimensional output branch and trunk nets. Lemma 14 removes 2 matrices (1 each from branch and trunk) – by an entirely different argument than needed in the former. Lemma 13 is invoked only once at the beginning, while Lemma 14 is repeatedly used for each remaining layer of the DeepONet.

We note that both our "peeling" lemmas above are structurally very different from the one in [GRS18] - where the last layer of a standard net gets peeled in every step.

Deriving the second main result, Theorem 10, involves the following key steps: **(a)** establishing a relationship between the Rademacher complexity of the loss class and that of the DeepONet when the loss function is Lipschitz (Proposition H.7) and **(b)** using this to upper bound the expectation over data of the supremum of generalization error in terms of the Rademacher complexity of the DeepONet.

Towards proving Theorem 9, we need the following lemma which can be seen as a variation of the standard Talagrand contraction lemma,

Lemma 11 *Let $\phi_P, \phi_Q : \mathbb{R} \to \mathbb{R}$ be two functions such that Assumption 5 holds and let $\mathcal{P}$ and $\mathcal{Q}$ be any two sets of real-valued functions. Then given any two sets of points $\{\mathbf{x}_i \mid i = 1, \ldots, m\}$ and $\{\mathbf{y}_i \mid i = 1, \ldots, m\}$ in the domains of the functions in $\mathcal{P}$ and $\mathcal{Q}$ respectively, we have the following inequality of Rademacher complexities - where both the sides are being evaluated on this same set of points,*

$$\mathcal{R}_m(\phi_P \circ \mathcal{P} \cdot \phi_Q \circ \mathcal{Q}) \leq L\mathcal{R}_m(\mathcal{P} \cdot \mathcal{Q}).$$

The above lemma has been proven in Appendix I.1.

Towards stating Propositions 13 and 14, we will need to define a class of sub-DeepONets s.t these sub-DeepONets would be one depth lower in the branch and trunk network, and would always have one dimensional outputs for both the branch and trunk nets and would share weights below that with the corresponding layers in the original DeepONet.

Definition 12 (Classes of sub-DeepONets)

- *Let $\mathcal{W}_{\text{rest}}$ be a set of allowed matrices for nets f'_B and f'_T as in Definition 4.*
- *Further, given a constant $\mathcal{C}_{q_B,q_T,q_B-1,q_T-1} > 0$ we define the following set of 4−tuples of outermost layer of matrices in the* DeepONet *as,*

$$\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}) \coloneqq \Bigg\{ (\mathbf{B}_{q_B}, \mathbf{B}_{q_B-1}, \mathbf{T}_{q_T}, \mathbf{T}_{q_T-1}) \;\Bigg|\; \sum_{k_1=1}^{b_{-1}} \sum_{k_2=1}^{t_{-1}} \left\| \mathbf{B}_{q_B-1,k_1} \right\| \cdot \left\| \mathbf{T}_{q_T-1,k_2} \right\| \cdot \left| \Big[\sum_{j=1}^{p} (\mathbf{B}_{q_B,j} \mathbf{T}_{q_T,j}^{\top}) \Big]_{k_1,k_2} \right| \leq \mathcal{C}_{q_B,q_T,q_B-1,q_T-1} \Bigg\}. \tag{12}$$

- *Corresponding to the above we define the following class of* DeepONets*,*

$$\text{DeepONet}(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}), \mathcal{W}_{\text{rest}}) \coloneqq \Big\{ \text{DeepONet}_{\mathbf{w}} \text{ (as in Definition 3)} \;\Big|\; \mathbf{w} \in (\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}), \mathcal{W}_{\text{rest}}) \Big\}. \tag{13}$$

- *Lastly, we define the following class of DeepONets,*

$$\text{DeepONet}(\mathcal{W}_{\text{rest}}) \coloneqq \Bigg\{ (\mathbf{x}_B, \mathbf{x}_T) \mapsto \mathbf{v}^\top \mathbf{f}'_B(\mathbf{x}_B) \cdot \mathbf{w}^\top \mathbf{f}'_T(\mathbf{x}_T) \in \mathbb{R} \tag{14}$$

$$\Bigg| \text{ the set of allowed matrices for nets } f'_B \text{ \& } f'_T \text{ are in } \mathcal{W}_{\text{rest}} \text{ ; } (\mathbf{v}, \mathbf{w}) \in S^{b_{-2}-1} \times S^{t_{-2}-1} \Bigg\}.$$

Proposition 13 (Removal of the Last 4 Matrices of a DeepONet) *We continue to be in the setup of Definition 4 and assuming that σ_1, σ_2 satisfies Assumption 5 for some $L > 0$, and are positively homogeneous. Then given the definitions of* $\text{DeepONet}(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}), \mathcal{W}_{\text{rest}})$ *and* $\text{DeepONet}(\mathcal{W}_{\text{rest}})$ *in Definition 12, we have the following upperbound on empirical Rademacher complexity of a DeepONet, (here $\mathcal{S}_k \coloneqq S^{b_{-k}-1} \times S^{t_{-k}-1}$)*

$$\begin{aligned}
&\hat{\mathcal{R}}_m\Big(\text{DeepONet}(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}), \mathcal{W}_{\text{rest}})\Big) \\
&\leq 2L \cdot \mathcal{C}_{q_B,q_T,q_B-1,q_T-1} \cdot \mathbb{E}_\epsilon \Bigg[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2 \\ \mathcal{W}_{\text{rest}}}} \left(\sum_{i=1}^m \epsilon_i \mathbf{v}^\top \mathbf{f}'_B(\mathbf{x}_{B,i}) \cdot \mathbf{w}^\top \mathbf{f}'_T(\mathbf{x}_{T,i}) \right) \Bigg] \\
&\leq 2L \cdot \mathcal{C}_{q_B,q_T,q_B-1,q_T-1} \cdot \hat{\mathcal{R}}_m\Big(\text{DeepONet}(\mathcal{W}_{\text{rest}})\Big).
\end{aligned}$$

Note that both sides of the above are computed for the same data $\{(\mathbf{x}_{B,i}, \mathbf{x}_{T,i}) \in \mathbb{R}^{d_1} \times \mathbb{R}^{d_2} \mid i = 1, \ldots, m\}$. The proof of the above proposition is given in Appendix F.

Referring to the definitions of the DeepONet classes on the L.H.S. and the R.H.S. of the above, as given in equations 13 and 14 respectively, we see that the above lemma upperbounds the Rademacher complexity of a DeepONet class (whose individual nets can have multi-dimensional outputs) by the Rademacher complexity of a simpler DeepONet class. The DeepONet class in the R.H.S. is simpler because the last layer of each of the individual nets therein is constrained to be a unit vector of appropriate dimensions (and thus the individual nets here are always of 1 dimensional output) – and whose both branch and the trunk are shorter in depth by 1 activation and 1 linear transform than in the L.H.S.

Proposition 14 (Peeling for DeepONets) *We continue in the setup of Proposition 13 and define the functions $\mathbf{f}''_B$ and $\mathbf{f}''_T$ s.t we have the following equalities, $\mathbf{f}'_B = \sigma_1\left(\mathbf{B}_{q_B-2}\mathbf{f}''_B\right)$ &$\mathbf{f}'_T = \sigma_2\left(\mathbf{T}_{q_T-2}\mathbf{f}''_T\right)$ Further, given a constant $\mathcal{C}_{-2,-2} > 0$, we define $\mathcal{W}'_{rest}$ as the union of (a) the set of weights that are allowed in the $\mathcal{W}_{rest}$ set for the matrices $\mathbf{B}_{q_B-3}, \mathbf{B}_{q_B-4}, \ldots, \mathbf{B}_1$ and $\mathbf{T}_{q_T-3}, \mathbf{T}_{q_T-4}, \ldots, \mathbf{T}_1$ and (b) the subset of the weights for $\mathbf{B}_{q_B-2}$ & $\mathbf{T}_{q_T-2}$ that are allowed by $\mathcal{W}_{rest}$ which also additionally satisfy the constraint, (here $\mathcal{S}_k \coloneqq S^{b_{-k}-1} \times S^{t_{-k}-1}$)*

$$\sup_{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2} \sum_{j_1=1}^{b_{-2}} \sum_{j_2=1}^{t_{-2}} \left|(\mathbf{v}\mathbf{w}^\top)_{j_1,j_2}\right| \left\|\mathbf{B}_{q_B-2,j_1}\right\| \left\|\mathbf{T}_{q_T-2,j_2}\right\| \leq \mathcal{C}_{-2,-2}. \tag{15}$$

Then we get the following inequality between Rademacher complexities,

$$\begin{aligned}
&\mathbb{E}_\epsilon \Bigg[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2 \\ \mathcal{W}_{\text{rest}}}} \left(\sum_{i=1}^m \epsilon_i \mathbf{v}^\top \mathbf{f}'_B(\mathbf{x}_{B,i}) \cdot \mathbf{w}^\top \mathbf{f}'_T(\mathbf{x}_{T,i}) \right) \Bigg] \\
&\leq 2LC_{-2,-2}\mathbb{E}_\epsilon \Bigg[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_3 \\ \mathcal{W}'_{rest}}} \left(\sum_{i=1}^m \epsilon_i (\mathbf{v}^\top \mathbf{f}''_B(\mathbf{x}_{B,i}))(\mathbf{w}^\top \mathbf{f}''_T(\mathbf{x}_{T,i})) \right) \Bigg],
\end{aligned}$$

where b_{-k}, t_{-k} are as in Definition 4.

Proof of the above proposition is given in Appendix G. And now we have stated all the intermediate results needed to prove our bounds on the Rademacher complexity of a certain DeepONet class.

Proof of Theorem 9

Proof For each $k = 2, 3, \ldots, n-1$, we define a product of unit-spheres, $\mathcal{S}_k \coloneqq S^{b_{-k}-1} \times S^{t_{-k}-1}$ and let $\mathcal{S}_n \coloneqq S^{d_1-1} \times S^{d_2-1}$. Now we define,

$$\mathcal{W}^1_{\text{rest}} \coloneqq \Bigg\{ (\mathbf{B}_n, \mathbf{B}_{n-1}, \mathbf{T}_n, \mathbf{T}_{n-1}) \;\Bigg|\; \sum_{k_1=1}^{b_{-1}} \sum_{k_2=1}^{t_{-1}} \left\|\mathbf{B}_{n-1,k_1}\right\| \cdot \left\|\mathbf{T}_{n-1,k_2}\right\| \cdot \left[\sum_{j=1}^{p} (\mathbf{B}_{n,j}\mathbf{T}^\top_{n,j}) \right]_{k_1,k_2} \leq \mathcal{C}_{n,n-1} \Bigg\}.$$

Next, for each $i = 2, 3, \ldots, n-1$, we define

$$\mathcal{W}^i_{\text{rest}} \coloneqq \bigcup_{k=1}^{n-i} \left\{ (\mathbf{B}_k, \mathbf{T}_k) \;\middle|\; \sup_{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_k} \sum_{j_1=1}^{b_{-k}} \sum_{j_2=1}^{t_{-k}} \left|(\mathbf{v}\mathbf{w}^\top)_{j_1,j_2}\right| \cdot \left\|\mathbf{B}_{n-k,j_1}\right\| \cdot \left\|\mathbf{T}_{n-k,j_2}\right\| \leq \mathcal{C}_{-k,-k} \right\}.$$

Thus we have,

$$m\hat{\mathcal{R}}_m = \mathbb{E}_\epsilon \left[\sup_{(\mathcal{W}^1_{\text{rest}}, \mathcal{W}^2_{\text{rest}})} \left(\sum_{i=1}^m \epsilon_i \left\langle \mathbf{B}_n \sigma_1 \left(\mathbf{B}_{n-1} \mathbf{f}'_B(\mathbf{x}_{B,i}) \right), \mathbf{T}_n \sigma_2 \left(\mathbf{T}_{n-1} \mathbf{f}'_T(\mathbf{x}_{T,i}) \right) \right\rangle \right) \right].$$

Then we can invoke Lemma 13 on the above to get,

$$\begin{aligned} m\hat{\mathcal{R}}_m &= \mathbb{E}_\epsilon \left[\sup_{(\mathcal{W}^1_{\text{rest}}, \mathcal{W}^2_{\text{rest}})} \left(\sum_{i=1}^m \epsilon_i \left\langle \mathbf{B}_n \sigma_1 \left(\mathbf{B}_{n-1} \mathbf{f}'_B(\mathbf{x}_{B,i}) \right), \mathbf{T}_n \sigma_2 \left(\mathbf{T}_{n-1} \mathbf{f}'_T(\mathbf{x}_{T,i}) \right) \right\rangle \right) \right] \\ &\leq 2LC_{n,n-1} \mathbb{E}_\epsilon \left[\sup_{\substack{\mathcal{W}^2_{\text{rest}} \\ \mathbf{v}_1, \mathbf{v}_2 \in \mathcal{S}_2}} \left(\sum_{i=1}^m \epsilon_i \mathbf{v}_1^\top \mathbf{f}'_B(\mathbf{x}_{B,i}) \, \mathbf{v}_2^\top \mathbf{f}'_T(\mathbf{x}_{T,i}) \right) \right]. \end{aligned}$$

Now, using Lemma 14 repeatedly on the R.H.S above, and defining in a natural fashion the subsequent branch and trunk sub-networks as $\mathbf{f}^{(i)}(\cdot)$ we have,

$$\begin{aligned} m\hat{\mathcal{R}}_m &\leq (2L)^2 \mathcal{C}_{n,n-1} \mathcal{C}_{-2,-2} \mathbb{E}_\epsilon \left(\sup_{\substack{\mathcal{W}^3_{rest} \\ (\mathbf{v}_1, \mathbf{v}_2) \in \mathcal{S}_3}} \sum_{i=1}^m \epsilon_i (\mathbf{v}_1^\top \mathbf{f}''_B(\mathbf{x}_{B,i}))(\mathbf{v}_2^\top \mathbf{f}''_T(\mathbf{x}_{T,i})) \right) \\ &\vdots \\ &\leq (2L)^i \mathcal{C}_{n,n-1} \left(\prod_{j=2}^i \mathcal{C}_{-j,-j} \right) \mathbb{E}_\epsilon \left(\sup_{\substack{\mathcal{W}^{i+1}_{\text{rest}} \\ (\mathbf{v}_1, \mathbf{v}_2) \in \mathcal{S}_{i+1}}} \sum_{i=1}^m \epsilon_i (\mathbf{v}_1^\top \mathbf{f}_B^{(i)}(\mathbf{x}_{B,i}))(\mathbf{v}_2^\top \mathbf{f}_T^{(i)}(\mathbf{x}_{T,i})) \right) \\ &\vdots \\ &\leq (2L)^{n-1} \mathcal{C}_{n,n-1} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j} \right) \mathbb{E}_\epsilon \left(\sup_{(\mathbf{v}_1, \mathbf{v}_2) \in \mathcal{S}_n} \sum_{i=1}^m \epsilon_i (\mathbf{v}_1^\top \mathbf{x}_{B,i})(\mathbf{v}_2^\top \mathbf{x}_{T,i}) \right). \end{aligned}$$

Using Lemma 15, the final bound on the empirical Rademacher complexity becomes,

$$\hat{\mathcal{R}}_m \leq \frac{(2L)^{n-1} \mathcal{C}_{n,n-1}}{m} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j} \right) \sqrt{\sum_{i=1}^m \|\tilde{\mathbf{x}}_i\|_2^2}.$$

Invoking the assumption that the input is bounded s.t $\mathbb{E}\left[\|\tilde{\mathbf{x}}_B\|_2^2\right] \leq M^2_{x,B}$ and $\mathbb{E}\left[\|\tilde{\mathbf{x}}_T\|_2^2\right] \leq M^2_{x,T}$, the average Rademacher complexity can be bounded as

$$\mathcal{R}_m \leq \frac{(2L)^{n-1} \mathcal{C}_{n,n-1}}{\sqrt{m}} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j} \right) M_{x,B} M_{x,T}.$$

■

Lemma 15

$$\mathbb{E}_\epsilon \left(\sup_{(\mathbf{v}_1, \mathbf{v}_2) \in \mathcal{S}_n} \sum_{i=1}^m \epsilon_i (\mathbf{v}_1^\top \mathbf{x}_{B,i})(\mathbf{v}_2^\top \mathbf{x}_{T,i}) \right) \leq \sqrt{\sum_{i=1}^m \|\tilde{\mathbf{x}}_i\|_2^2}.$$

where $\tilde{\mathbf{x}}_i = \mathbf{x}_{B,i} \mathbf{x}_{T,i}^\top$ *and* $\mathcal{S}_n = S^{d_1 - 1} \times S^{d_2 - 1}$ *and each* $\epsilon_i \sim \pm 1$ *uniformly.*

Proof of the above lemma is given in Appendix E. In Appendix H we have setup a general framework for using Rademacher bounds as proven in the above theorem to prove generalization error bounds for DeepONets. And we will now invoke the result there to prove our main theorem about generalization error of DeepONets.

Proof of Theorem 10

Proof We recall from Theorem 9 the following bound on Rademacher complexity for the given DeepONet class,

$$\mathcal{R}_m \leq \frac{(2L)^{n-1}\mathcal{C}_{n,n-1}}{\sqrt{m}} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j} \right) M_{x,B} M_{x,T}$$

Combining the above with Proposition H.7 we have,

$$\begin{aligned}
&\mathbb{E}_{\{(f_i,\mathbf{x}_{T,i}) \overset{iid}{\sim} \mathcal{D} \; | i=1\ldots m\}} \left[\sup_{h \in \mathcal{H}} \left[\frac{1}{m} \sum_{i=1}^{m} \ell(h(f_i, \mathbf{x}_{T,i})) - \mathbb{E}_{(f,\mathbf{x}_T)\sim\mathcal{D}} \left[\ell(h(f, \mathbf{x}_T)) \right] \right] \right] \\
&\leq 2R \cdot \frac{(2L)^{n-1}\mathcal{C}_{n,n-1}}{\sqrt{m}} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j} \right) M_{x,B} M_{x,T}
\end{aligned}$$

Note that Huber-loss $\ell_{H,\delta}$ is δ-Lipshitz and further setting $\delta = \left(\frac{1}{2}\right)^{n-1}$ and rewriting the supremum over all $h \in \mathcal{H}$ as supremum over all $\mathbf{w} \in \mathcal{W}$ we can write the above inequality as

$$\begin{aligned}
&\mathbb{E}_{\{(f_i,\mathbf{x}_{T,i}) \overset{iid}{\sim} \mathcal{D} \; | i=1\ldots m\}} \left[\sup_{\mathbf{w} \in \mathcal{W}} \left[\frac{1}{m} \sum_{i=1}^{m} \ell_{H,\delta}(h(f_i, \mathbf{x}_{T,i})) - \mathbb{E}_{(f,\mathbf{x}_T)\sim\mathcal{D}} \left[\ell_{H,\delta}(h(f, \mathbf{x}_T)) \right] \right] \right] \\
&\leq \frac{(2L)^{n-1}\mathcal{C}_{n,n-1}}{2^{(n-2)}\sqrt{m}} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j} \right) M_{x,B} M_{x,T}
\end{aligned}$$

Lastly, considering that the activation functions are $\sigma_1(x) = \sigma_2(x) = |x|$ which makes $L = 1$ in Lemma 11 we obtained the claimed bound,

$$\begin{aligned}
&\mathbb{E}_{\{(f_i,\mathbf{x}_{T,i}) \overset{iid}{\sim} \mathcal{D} \; | i=1\ldots m\}} \left[\sup_{\mathbf{w} \in \mathcal{W}} \left[\frac{1}{m} \sum_{i=1}^{m} \ell_{H,\delta}(h(f_i, \mathbf{x}_{T,i})) - \mathbb{E}_{(f,\mathbf{x}_T)\sim\mathcal{D}} \left[\ell_{H,\delta}(h(f, \mathbf{x}_T)) \right] \right] \right] \\
&\leq \frac{2\mathcal{C}_{n,n-1}}{\sqrt{m}} \left(\prod_{j=2}^{n-1} \mathcal{C}_{-j,-j} \right) M_{x,B} M_{x,T}
\end{aligned}$$

■

References

[ABMS21] Raman Arora, Peter Bartlett, Poorya Mianjy, and Nathan Srebro. Dropout: Explicit forms and capacity control. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 351–361. PMLR, 2021.

[AGNZ18] Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. In Jennifer G. Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 254–263. PMLR, 2018.

[BFT17] Peter L. Bartlett, Dylan J. Foster, and Matus Telgarsky. Spectrally-normalized margin bounds for neural networks. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 6240–6249, 2017.

[BKH+23] Boris Bonev, Thorsten Kurth, Christian Hundt, Jaideep Pathak, Maximilian Baust, Karthik Kashinath, and Anima Anandkumar. Spherical fourier neural operators: Learning stable dynamics on the sphere. 2023.

[BL88] David Broomhead and David Lowe. Radial basis functions, multi-variable functional interpolation and adaptive networks. *ROYAL SIGNALS AND RADAR ESTABLISHMENT MALVERN (UNITED KINGDOM)*, RSRE-MEMO-4148, 03 1988.

[BM03] Peter L. Bartlett and Shahar Mendelson. Rademacher and gaussian complexities: Risk bounds and structural results. *J. Mach. Learn. Res.*, 3(null):463–482, mar 2003.

[CC95] Tianping Chen and Hong Chen. Universal approximation to nonlinear operators by neural networks with arbitrary activation functions and its application to dynamical systems. *IEEE Transactions on Neural Networks*, 6(4):911–917, 1995.

[CCW+23] Abouzar Choubineh, Jie Chen, David A Wood, Frans Coenen, and Fei Ma. Fourier neural operator for fluid flow in small-shape 2d simulated porous media dataset. *Algorithms*, 16(1):24, 2023.

[DAS+21] Kunal Dahiya, Ananye Agarwal, Deepak Saini, Gururaj K, Jian Jiao, Amit Singh, Sumeet Agarwal, Purushottam Kar, and Manik Varma. Siamesexml: Siamese networks meet extreme classifiers with 100m labels. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 2330–2340. PMLR, 18–24 Jul 2021.

[DMB21] Yehuda Dar, Vidya Muthukumar, and Richard G. Baraniuk. A farewell to the bias-variance tradeoff? an overview of the theory of overparameterized machine learning. *CoRR*, abs/2109.02355, 2021.

[DR17] Gintare Karolina Dziugaite and Daniel M. Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. In Gal Elidan, Kristian Kersting, and Alexander T. Ihler, editors, *Proceedings of the Thirty-Third Conference on Uncertainty in Artificial Intelligence, UAI 2017, Sydney, Australia, August 11-15, 2017*. AUAI Press, 2017.

[dSARCJ23] Joao Lucas de Sousa Almeida, Pedro Rocha, Allan Carvalho, and Alberto Costa Nogueira Junior. A coupled variational encoder-decoder-deeponet surrogate model for the rayleigh-bénard convection problem. In *AAAI Conference on Artificial Intelligence*, 2023.

[DSL+22] Beichuan Deng, Yeonjong Shin, Lu Lu, Zhongqiang Zhang, and George Em Karniadakis. Approximation rates of deeponets for learning operators arising from advection–diffusion equations. *Neural Networks*, 153:411–426, 2022.

[EHJ21] Weinan E, Jiequn Han, and Arnulf Jentzen. Algorithms for solving high dimensional PDEs: from nonlinear monte carlo to machine learning. *Nonlinearity*, 35(1):278–310, dec 2021.

[EMM19] N. Benjamin Erichson, Michael Muehlebach, and Michael W. Mahoney. Physics-informed autoencoders for lyapunov-stable fluid flow prediction, 2019.

[GKSK22] Somdatta Goswami, Katiana Kontolati, Michael D Shields, and George Em Karniadakis. Deep transfer operator learning for partial differential equations under conditional shift. *Nature Machine Intelligence*, 4(12):1155–1164, 2022.

[GRS18] Noah Golowich, Alexander Rakhlin, and Ohad Shamir. Size-independent sample complexity of neural networks. In *Conference On Learning Theory*, pages 297–299. PMLR, 2018.

[GS20] Vignesh Gopakumar and D Samaddar. Image mapping the temporal evolution of edge characteristics in tokamaks using neural networks. *Machine Learning: Science and Technology*, 1(1):015006, 2020.

[GYYK22] Somdatta Goswami, Minglang Yin, Yue Yu, and George Em Karniadakis. A physics-informed variational DeepONet for predicting crack path in quasi-brittle materials. *Computer Methods in Applied Mechanics and Engineering*, 391:114587, mar 2022.

[Had22] Patrik Simon Hadorn. Shift-deeponet: Extending deep operator networks for discontinuous output functions. ETH Zurich, Seminar for Applied Mathematics, 2022.

[KGK21] Karniadakis, G.E., and Kevrekidis. Physics-informed machine learning, 2021.

[KGKS23] Katiana Kontolati, Somdatta Goswami, George Em Karniadakis, and Michael D Shields. Learning in latent spaces improves the predictive accuracy of deep neural operators. *arXiv preprint arXiv:2304.07599*, 2023.

[KKB21] Eurika Kaiser, J. Nathan Kutz, and Steven L. Brunton. Data-driven discovery of koopman eigenfunctions for control, 2021.

[KSH+23] Thorsten Kurth, Shashank Subramanian, Peter Harrington, Jaideep Pathak, Morteza Mardani, David Hall, Andrea Miele, Karthik Kashinath, and Anima Anandkumar. Fourcastnet: Accelerating global high-resolution weather forecasting using adaptive fourier neural operators. In *Proceedings of the Platform for Advanced Scientific Computing Conference*, pages 1–11, 2023.

[LGBC23] Fanny Lehmann, Filippo Gatti, Michaël Bertin, and Didier Clouteau. Fourier neural operator surrogate model to predict 3d seismic waves propagation. *arXiv preprint arXiv:2304.10242*, 2023.

[LJP+21] Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning nonlinear operators via DeepONet based on the universal approximation theorem of operators. *Nature Machine Intelligence*, 3(3):218–229, mar 2021.

[LKA+20] Zongyi Li, Nikola Borislavov Kovachki, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew Stuart, Anima Anandkumar, et al. Fourier neural operator for parametric partial differential equations. In *International Conference on Learning Representations*, 2020.

[LLF98] I.E. Lagaris, A. Likas, and D.I. Fotiadis. Artificial neural networks for solving ordinary and partial differential equations. *IEEE Transactions on Neural Networks*, 9(5):987–1000, 1998.

[LLSK+22] Zongyi Li, Miguel Liu-Schiaffini, Nikola Kovachki, Burigede Liu, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Learning dissipative dynamics in chaotic systems, 2022.

[LMC+22] Lu Lu, Xuhui Meng, Shengze Cai, Zhiping Mao, Somdatta Goswami, Zhongqiang Zhang, and George Em Karniadakis. A comprehensive and fair comparison of two neural operators (with practical extensions) based on fair data. *Computer Methods in Applied Mechanics and Engineering*, 393:114778, 2022.

[LMK22] Samuel Lanthaler, Siddhartha Mishra, and George E Karniadakis. Error estimates for DeepONets: a deep learning framework in infinite dimensions. *Transactions of Mathematics and Its Applications*, 6(1), 03 2022. tnac001.

[LMZ23] Guang Lin, Christian Moya, and Zecheng Zhang. B-deeponet: An enhanced bayesian deeponet for solving noisy parametric pdes using accelerated replica exchange sgld. *Journal of Computational Physics*, 473:111713, 2023.

[LYLI22] Zaharaddeen Lawal, Hayati Yassin, Daphne Teck Ching Lai, and Azam Idris. Physics-informed neural network (pinn) evolution and beyond: A systematic literature review and bibliometric analysis. *Big Data and Cognitive Computing*, 11 2022.

[Ma21] Tengyu Ma. *STATS214 / CS229M: Machine Learning Theory*, 2021.

[MR23] Anirbit Mukherjee and Amartya Roy. Size lowerbounds for deep operator networks. *arXiv preprint arXiv:2308.06338*, 2023.

[Muk21] Anirbit Mukherjee. A study of the mathematics of deep learning. *CoRR*, abs/2104.14033, 2021.

[Nag21] Vaishnavh Nagarajan. Explaining generalization in deep learning: progress and fundamental limits. *CoRR*, abs/2110.08922, 2021.

[NBS18] Behnam Neyshabur, Srinadh Bhojanapalli, and Nathan Srebro. A pac-bayesian approach to spectrally-normalized margin bounds for neural networks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

[NLB+19] Behnam Neyshabur, Zhiyuan Li, Srinadh Bhojanapalli, Yann LeCun, and Nathan Srebro. The role of over-parametrization in generalization of neural networks. In *International Conference on Learning Representations*, 2019.

[NTS15] Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. Norm-based capacity control in neural networks. In Peter Grünwald, Elad Hazan, and Satyen Kale, editors, *Proceedings of The 28th Conference on Learning Theory, COLT 2015, Paris, France, July 3-6, 2015*, volume 40 of *JMLR Workshop and Conference Proceedings*, pages 1376–1401. JMLR.org, 2015.

[PKH+23] Jaewan Park, Shashank Kushwaha, Junyan He, Seid Koric, Diab Abueidda, and Iwona Jasiuk. Sequential deep learning operator network (s-deeponet) for time-dependent loads. *arXiv preprint arXiv:2306.08218*, 2023.

[PMR+23] Raphaël Pestourie, Youssef Mroueh, Chris Rackauckas, Payel Das, and Steven Johnson. Physics-enhanced deep surrogates for partial differential equations. *Nature Machine Intelligence*, 5, 12 2023.

[RMR+23] Bogdan Raonić, Roberto Molinaro, Tobias Rohner, Siddhartha Mishra, and Emmanuel de Bezenac. Convolutional neural operators. *arXiv preprint arXiv:2302.01178*, 2023.

[RPK19] Maziar Raissi, Paris Perdikaris, and George E Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational physics*, 378:686–707, 2019.

[Sel23] Mark Sellke. On size-independent sample complexity of relu networks. *arXiv preprint arXiv:2306.01992*, 2023.

[SLG22] Cristopher Salvi, Maud Lemercier, and Andris Gerasimovics. Neural stochastic pdes: Resolution-invariant learning of continuous spatiotemporal dynamics, 2022.

[SS18] Justin Sirignano and Konstantinos Spiliopoulos. Dgm: A deep learning algorithm for solving partial differential equations. *Journal of computational physics*, 375:1339–1364, 2018.

[TC22] Lesley Tan and Liang Chen. Enhanced deeponet for modeling partial differential operators considering multiple input functions. *arXiv preprint arXiv:2202.08942*, 2022.

[TC23] Tapas Tripura and Souvik Chakraborty. Wavelet neural operator for solving parametric partial differential equations in computational mechanics problems. *Computer Methods in Applied Mechanics and Engineering*, 404:115783, 2023.

[WWK21] Nils Wandel, Michael Weinmann, and Reinhard Klein. Teaching the incompressible navier–stokes equations to fast neural surrogate models in three dimensions. *Physics of Fluids*, 33(4):047117, apr 2021.

[WWP21a] Sifan Wang, Hanwen Wang, and Paris Perdikaris. Learning the solution operator of parametric partial differential equations with physics-informed deeponets. *Science Advances*, 7(40):eabi8605, 2021.

[WWP21b] Sifan Wang, Hanwen Wang, and Paris Perdikaris. Learning the solution operator of parametric partial differential equations with physics-informed DeepONets. *Science Advances*, 7(40):eabi8605, 2021.

[XLW23] Wuzhe Xu, Yulong Lu, and Li Wang. Transfer learning enhanced deeponet for long-time prediction of evolution equations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 10629–10636, 2023.

[Y+18] Bing Yu et al. The deep ritz method: a deep learning-based numerical algorithm for solving variational problems. *Communications in Mathematics and Statistics*, 6(1):1–12, 2018.

[YYY+20] Zitong Yang, Yaodong Yu, Chong You, Jacob Steinhardt, and Yi Ma. Rethinking bias-variance trade-off for generalization of neural networks. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 10767–10777. PMLR, 2020.

[ZZL22] Jiahao Zhang, Shiqi Zhang, and Guang Lin. Multiauto-deeponet: A multi-resolution autoencoder deeponet for nonlinear dimension reduction, uncertainty quantification and operator learning of forward and inverse stochastic problems. *arXiv preprint arXiv:2204.03193*, 2022.

Appendix

A Evidence for Training DeepONets with tanh Activation and Huber Loss

Similar to the experiments in Section 2.3, in this section too we use DeepONets whose both branch and trunk networks are of depth of 3 and have a width of 100. However, unlike Section 2.3, the activation function used in the experiments displayed in Figure 4 is tanh. The chosen training loss is the same as in equation 11, where ℓ is set to the Huber loss with $\delta = \frac{1}{2^{3-1}} = 0.25$, the value as would be inspired by Theorem 10.




Figure 4: This plot demonstrates the ability of Huber loss trained DeepONets to predict the solution to a Burgers' P.D.E on an arbitrarily chosen inhomogeneous term u, which is different from the u's used for training the net.

The plots above motivate future studies exploring the possibility of Huber loss being good for training DeepONets.

B Empirical Study on the Behaviour of Generalization Error for Huber Loss at Different δ

Similar to the experiments in Section 2.3, in this section too we use DeepONets whose both branch and trunk networks are of depth of 3 and have a width of 100. The selected training loss is identical to the one in Equation 11, with ℓ set to the Huber loss. The generalization error is plotted for various values of delta at $P_{\text{training}} = 200$ and 1500, while maintaining $N_{\text{training}} = 400$. In this setup, in Figure 5 we plot the generalization error for $\delta = \frac{1}{(\sqrt{2})^k}$ for $k = 4, 5, \cdots, 18$ to show how this difference between test error and train error drops as δ gets smaller.

C Related Work on DeepONet Theory

We follow the setup in [LMK22] for a brief review of its key theorem that motivates DeepONets.

Definition C.1 (Solution Operator) *Given $U \subset \mathbb{R}^n$ and $D \subset \mathbb{R}^d$, compact sets with boundaries, suppose we have a differential operator $\mathcal{L} : H^s(U) \to C(D)$, where $H^s(U)$ is the L^2-based Sobolev space for some $s > 0$. Denote the functions in the*




Figure 5: This plot demonstrates the behaviour of generalization error for Huber loss trained DeepONets to predict the solution to a Burgers' P.D.E at varying values of δ for 2 different dataset sizes.

range of $\mathcal{L}$ to be "forcing" / "input" functions and those in the domain of $\mathcal{L}$ to be the "output" functions. Let ∂U denote the boundary of U. Then given $g \in L^2(\partial U)$ and $f \in C(D)$ a solution to the differential system $(g, f, \mathcal{L})$ is a function $u^* \in H^s(U)$ s.t.

$$\mathcal{L}u^* = f \text{ s.t } u^* = g \text{ on } \partial U.$$

At a fixed "boundary condition" g for such a differential system, we assume that the solutions for the above system for different forcing functions f are given via an operator/map, $\mathcal{G}$ s.t.

$$\mathcal{G} : C(D) \to H^s(U) \;\; s.t \;\; \mathcal{L} \circ \mathcal{G}(f) = f \;\; and \;\; \mathcal{G}(f) = g \;\; on \;\; \partial U.$$

Further, assume that μ is a probability measure on $C(D)$ s.t $\mathcal{G} \in L^2(\mu)$ i.e $\int_{C(D)} \|\mathcal{G}(f)\|^2_{H^s(U)} \, \mathrm{d}\mu(f) < \infty$.

Multiple examples of $\mathcal{G}$ have been discussed in [LMK22], and bounds on these operators evaluated – for instance, in Lemma 4.1 therein one can see the bounds on the $\mathcal{G}$ that corresponds to the the case of a forced pendulum that we used as a demonstrative example in Section 1.1

Definition C.2 (DeepONet (Version 1)) *Suppose $\forall f \in C(D), \mathbf{x}_B(f)$ is a discretization of f. Further suppose $\mathcal{A}$ is a branch net mapping to $\mathbb{R}^p$ and $\tau : \mathbb{R}^n \mapsto \mathbb{R}^{p+1}$ is a trunk net. Then a "DeepONet" $(\mathcal{N} : C(D) \mapsto L^2(U))$ is defined as,*

$$\forall \mathbf{x}_T \in U \subset \mathbb{R}^n, \quad \mathcal{N}(f)(\mathbf{x}_T) \coloneqq \tau_0(\mathbf{x}_T) + \sum_{k=1}^{p} \mathcal{A}_k(\mathbf{x}_B(f))\tau_k(\mathbf{x}_T).$$

Theorem C.3 (Restatement of a Key Result from [LMK22]) *Let μ be as in Definition C.1. Let $\mathcal{G} : C(D) \to L^2(U)$ be a Borel measurable mapping, with $\mathcal{G} \in L^2(\mu)$, then for every $\epsilon > 0$, there exists an operator network $\mathcal{N} : C(D) \to L^2(U)$, such that*

$$\|\mathcal{G} - \mathcal{N}\|_{L^2(\mu)} = \left(\int_{C(D)} \|\mathcal{G}(f) - \mathcal{N}(f)\|^2_{L^2(U)} d\mu(f) \right)^{1/2} < \epsilon.$$

Remark 4 *Henceforth $\mathbf{x}_B \coloneqq \mathbf{x}_B(f)$ for any function f, and similarly $\mathbf{x}_{B,i}$ for a function f_i.*

The above approximation guarantee between DeepONets ($\mathcal{N}$) and solution operators of differential equations ($\mathcal{G}$) clearly motivates the use of DeepONets for solving differential equations. In [DSL+22], the authors present specific scenarios wherein particularly small DeepONets satisfy Theorem C.3. And as a counterpoint, in [MR23], scenarios are demonstrated where small DeepONets would not be able to reduce the empirical training error below a certain threshold in the presence of noise in the data.

D Related Work on Rademacher Theory for Neural Nets

Over the past few years, many novel generalization bounds for standard neural nets have been established. Many of these works have computed bounds on Rademacher complexity for various classes of nets, to show how different norm combinations of the involved weight matrices affect generalization performance, [Sel23], [GRS18], [BFT17], [NTS15]. For shallow neural nets such methods have also been useful in explaining the benefits of dropout [ABMS21] and overparameterization [NLB+19]. However, for state-of-the-art neural nets, other approaches [DR17], [AGNZ18], [NBS18], [Muk21] have sometimes given tighter bounds while using bounding expressions that are computationally very expensive. A thorough discussion of the reach and limitations of these various bounds can be found in [Nag21].

E Proof of Lemma 15

Proof Denote by $\mathcal{S}_n = S^{d_1-1} \times S^{d_2-1}$. Define $\tilde{\mathbf{W}} = (\mathbf{v}_1\mathbf{v}_2^\top)$ and $\tilde{\mathbf{x}}_i = (\mathbf{x}_{B,i}(\mathbf{x}_{T,i})^\top)$. Then

$$
\begin{aligned}
&= \mathbb{E}_\epsilon \left(\sup_{(\mathbf{v}_1,\mathbf{v}_2)\,\in\,\mathcal{S}_n} \sum_{i=1}^{m} \epsilon_i \left(\sum_{k_1=1}^{d_1} v_{1,k_1} x_{B,i,k_1} \right) \left(\sum_{k_2=1}^{d_2} v_{2,k_2} x_{T,i,k_2} \right) \right) \\
&= \mathbb{E}_\epsilon \left(\sup_{(\mathbf{v}_1,\mathbf{v}_2)\,\in\,\mathcal{S}_n} \sum_{i=1}^{m} \sum_{k_1=1}^{d_1} \sum_{k_2=1}^{d_2} \epsilon_i \left(v_{1,k_1} x_{B,i,k_1} \right) \left(v_{2,k_2} x_{T,i,k_2} \right) \right) \\
&= \mathbb{E}_\epsilon \left(\sup_{(\mathbf{v}_1,\mathbf{v}_2)\,\in\,\mathcal{S}_n} \sum_{k_1=1}^{d_1} \sum_{k_2=1}^{d_2} v_{1,k_1} v_{2,k_2} \left(\sum_{i=1}^{m} \epsilon_i \left(x_{B,i,k_1} \right) \left(x_{T,i,k_2} \right) \right) \right)
\end{aligned}
$$

Note that, $(\mathbf{v}_1, \mathbf{v}_2) \in \mathcal{S}_n \implies \left\|\tilde{\mathbf{W}}\right\|_2 = \sqrt{\sum_{k_1=1}^{d_1} \sum_{k_2=1}^{d_2} v_{1,k_1}^2 v_{2,k_2}^2} = \|\mathbf{v}_1\|_2 \|\mathbf{v}_2\|_2 = 1.$

Hence, we can enlarge the domain to get,

$$
\leq \mathbb{E}_\epsilon \left(\sup_{\left\|\tilde{\mathbf{W}}\right\|_2 \leq 1} \sum_{k_1=1}^{d_1} \sum_{k_2=1}^{d_2} \tilde{W}_{(k_1,k_2)} \left(\sum_{i=1}^{m} \epsilon_i \, \tilde{x}_{i,k_1,k_2} \right) \right).
$$

The above sum can be viewed as an inner product of 2 vectors in $\mathbb{R}^{d_1 \times d_2}$. We have,

$$
= \mathbb{E}_\epsilon \left(\sup_{\left\|\tilde{\mathbf{W}}\right\|_2 \leq 1} \left\langle \tilde{\mathbf{W}}, \sum_{i=1}^{m} \epsilon_i \, \tilde{\mathbf{x}}_i \right\rangle \right) \leq \sqrt{\sum_{i=1}^{m} \|\tilde{\mathbf{x}}_i\|_2^2} \leq \sqrt{\sum_{i=1}^{m} \left\|\mathbf{x}_{B,i}\right\|_2^2 \left\|\mathbf{x}_{T,i}\right\|_2^2},
$$

where the inequality follows from Theorem 5.5 in [Ma21].

F Proof of Proposition 13

Proof We recall from the setup of Definition 4 that b_{-1} and t_{-1} are the number of rows of the matrices $\mathbf{B}_{q_B-1}$ and $\mathbf{T}_{q_T-1}$ - and b_{-2} and t_{-2} are the output dimensions of the nets $\mathbf{f}'_B$ and $\mathbf{f}'_T$. From Definition 12 we further recall the definitions of the 2 sets of matrices $\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1})$ and $\mathcal{W}_{\text{rest}}$ and we simplify the required empirical Rademacher complexity as,

$$
\begin{aligned}
m\hat{\mathcal{R}}_m &= \mathop{\mathbb{E}}_{\epsilon} \left[\sup_{\left(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}}\right)} \sum_{i=1}^{m} \epsilon_i \left\langle \mathbf{f}_B(\mathbf{x}_{B,i}), \mathbf{f}_T(\mathbf{x}_{T,i}) \right\rangle \right] \\
&= \mathbb{E}_\epsilon \left[\sup_{\left(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}}\right)} \left(\sum_{i=1}^{m} \epsilon_i \left\langle \mathbf{B}_{q_B} \sigma_1 \left(\mathbf{B}_{q_B-1} \mathbf{f}'_B(\mathbf{x}_{B,i}) \right), \mathbf{T}_{q_T} \sigma_2 \left(\mathbf{T}_{q_T-1} \mathbf{f}'_T(\mathbf{x}_{T,i}) \right) \right\rangle \right) \right]. \qquad (16)
\end{aligned}
$$

Here, we have substituted the definitions of the functions $\mathbf{f}'_B$ and the $\mathbf{f}'_T$ as given in the statement of Lemma 13. To ease notation now we define the following vectors,

$$
\mathbf{b}_i \coloneqq \sigma_1 \left(\mathbf{B}_{q_B-1} \mathbf{f}'_B(\mathbf{x}_{B,i}) \right), \; \mathbf{t}_i \coloneqq \sigma_2 \left(\mathbf{T}_{q_T-1} \mathbf{f}'_T(\mathbf{x}_{T,i}) \right).
$$

Then we can rewrite the above as,

$$
\begin{aligned}
m\hat{\mathcal{R}}_m &= \mathbb{E}_\epsilon\left[\sup_{(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}})}\left(\sum_{i=1}^{m}\epsilon_i\left\langle \mathbf{B}_{q_B}\mathbf{b}_i, \mathbf{T}_{q_T}\mathbf{t}_i\right\rangle\right)\right] \\
&= \mathbb{E}_\epsilon\left[\sup_{(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}})}\left(\sum_{i=1}^{m}\epsilon_i\sum_{j=1}^{p}\mathbf{B}_{q_B,j}^\top\mathbf{b}_i\cdot\mathbf{T}_{q_T,j}^\top\mathbf{t}_i\right)\right] \\
&= \mathbb{E}_\epsilon\left[\sup_{(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}})}\left(\sum_{i=1}^{m}\epsilon_i\sum_{j=1}^{p}\left(\sum_{k_1=1}^{b_{-1}}B_{q_B,j,k_1}b_{i,k_1}\right)\cdot\left(\sum_{k_2=1}^{t_{-1}}T_{q_T,j,k_2}t_{i,k_2}\right)\right)\right] \\
&= \mathbb{E}_\epsilon\left[\sup_{(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}})}\left(\sum_{j=1}^{p}\sum_{k_1=1}^{b_{-1}}\sum_{k_2=1}^{t_{-1}}B_{q_B,j,k_1}T_{q_T,j,k_2}\sum_{i=1}^{m}\epsilon_i b_{i,k_1}\cdot t_{i,k_2}\right)\right] \\
&= \mathbb{E}_\epsilon\left[\sup_{(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}})}\left(\sum_{j=1}^{p}\sum_{k_1=1}^{b_{-1}}\sum_{k_2=1}^{t_{-1}}B_{q_B,j,k_1}T_{q_T,j,k_2}\sum_{i=1}^{m}\epsilon_i b_{i,k_1}\cdot t_{i,k_2}\right)\right] \\
&= \mathbb{E}_\epsilon\left[\sup_{\substack{\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1})\\ \mathcal{W}_{\text{rest}}}}\left(\sum_{j=1}^{p}\sum_{k_1=1}^{b_{-1}}\sum_{k_2=1}^{t_{-1}}(\mathbf{B}_{q_B,j}\mathbf{T}_{q_T,j}^\top)_{k_1,k_2}\right.\right. \\
&\qquad\left.\left.\cdot\sum_{i=1}^{m}\epsilon_i\sigma_1\left(\mathbf{B}_{q_B-1}\mathbf{f}_B'(\mathbf{x}_{B,i})\right)_{k_1}\cdot\sigma_2\left(\mathbf{T}_{q_T-1}\mathbf{f}_T'(\mathbf{x}_{T,i})\right)_{k_2}\right)\right] \\
&= \mathbb{E}_\epsilon\left[\sup_{\substack{\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1})\\ \mathcal{W}_{\text{rest}}}}\left(\sum_{j=1}^{p}\sum_{k_1=1}^{b_{-1}}\sum_{k_2=1}^{t_{-1}}(\mathbf{B}_{q_B,j}\mathbf{T}_{q_T,j}^\top)_{k_1,k_2}\cdot\left\|\mathbf{B}_{q_B-1,k_1}\right\|\cdot\left\|\mathbf{T}_{q_T-1,k_2}\right\|\right.\right. \\
&\qquad\left.\left.\cdot\sum_{i=1}^{m}\epsilon_i\sigma_1\left(\hat{\mathbf{B}}_{q_B-1,k_1}^\top\mathbf{f}_B'(\mathbf{x}_{B,i})\right)\cdot\sigma_2\left(\hat{\mathbf{T}}_{q_T-1,k_2}^\top\mathbf{f}_T'(\mathbf{x}_{T,i})\right)\right)\right].
\end{aligned}
$$

In the last line above we have invoked the positive homogeneity of σ_1 and σ_2.

Now assume 2 vectors $\mathbf{v}$ and $\mathbf{w}$ of dimensions $b_{-1}-1\times t_{-1}-1$ s.t they are indexed by the tuple (k_1,k_2) for $k_1\in\{1,\ldots,-1+b_{-1}\}$ and $k_2\in\{1,\ldots,-1+t_{-1}\}$ as follows,

$$
\begin{aligned}
v_{(k_1,k_2)} &\coloneqq \left\|\mathbf{B}_{q_B-1,k_1}\right\|\cdot\left\|\mathbf{T}_{q_T-1,k_2}\right\|\cdot\sum_{j=1}^{p}(\mathbf{B}_{q_B,j}\mathbf{T}_{q_T,j}^\top)_{k_1,k_2}, \\
w_{(k_1,k_2)} &\coloneqq \sum_{i=1}^{m}\epsilon_i\sigma_1\left(\hat{\mathbf{B}}_{q_B-1,k_1}^\top\mathbf{f}_B'(\mathbf{x}_{B,i})\right)\cdot\sigma_2\left(\hat{\mathbf{T}}_{q_T-1,k_2}^\top\mathbf{f}_T'(\mathbf{x}_{T,i})\right).
\end{aligned}
$$

Then we have,

$$
m\hat{\mathcal{R}}_m = \mathbb{E}_\epsilon\left[\sup_{(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}})}\left(\sum_{k_1=1}^{b_{-1}}\sum_{k_2=1}^{t_{-1}}v_{(k_1,k_2)}\cdot w_{(k_1,k_2)}\right)\right].
$$

Note that for any $\alpha,\beta\in\mathbb{R}^k$ we have, $\langle\alpha,\beta\rangle\le\left(\max_{p\in 1,\ldots,k}|\beta_p|\right)\cdot\sum_{j=1}^{k}|\alpha_j|$

$$
\le \mathbb{E}_\epsilon\left[\sup_{(\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}),\mathcal{W}_{\text{rest}})}\left(\sum_{k_1=1}^{b_{-1}}\sum_{k_2=1}^{t_{-1}}|v_{(k_1,k_2)}|\cdot\max_{\substack{k_1=1,\ldots,b_{-1}-1\\ k_2=1,\ldots,t_{-1}-1}}|w_{(k_1,k_2)}|\right)\right].
$$

Now we define a set of weights $\mathcal{W}_{\text{except-outer}}$ which is an union of all possible weight matrices that are allowed in $\mathcal{W}_{\text{rest}}$ and all possible choices of $(\mathbf{B}_{q_B-1},\mathbf{T}_{q_T-1})$ that are allowed in the set $\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1})$.

Then we recall the definition of $\mathcal{W}(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1})$, to get,

$$
m\hat{\mathcal{R}}_m \le \mathbb{E}_\epsilon\left[\sup_{\mathcal{W}_{\text{except-outer}}}\left(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}\cdot\max_{\substack{k_1=1,\ldots,b_{-1}-1\\ k_2=1,\ldots,t_{-1}-1}}\left|\sum_{i=1}^{m}\epsilon_i\sigma_1\left(\hat{\mathbf{B}}_{q_B-1,k_1}^\top\mathbf{f}_B'(\mathbf{x}_{B,i})\right)\cdot\sigma_2\left(\hat{\mathbf{T}}_{q_T-1,k_2}^\top\mathbf{f}_T'(\mathbf{x}_{T,i})\right)\right|\right)\right].
$$

where

$$\mathcal{C}_{q_B,q_T,q_B-1,q_T-1} = \sum_{k_1=1}^{b_{-1}} \sum_{k_2=1}^{t_{-1}} \left|v_{(k_1,k_2)}\right| = \sum_{k_1=1}^{b_{-1}} \sum_{k_2=1}^{t_{-1}} \left\|\mathbf{B}_{q_B-1,k_1}\right\| \cdot \left\|\mathbf{T}_{q_T-1,k_2}\right\| \left| \left[\sum_{j=1}^{p} \mathbf{B}_{q_B,j} \mathbf{T}_{q_T,j}^\top \right]_{k_1,k_2} \right|$$

Note that any pair of row directions in the pair of matrices $(\mathbf{B}_{q_B-1}, \mathbf{T}_{q_T-1})$ is in $\in S^{b_{-2}-1} \times S^{t_{-2}-1}$. So a sup over the set of $\mathbf{B}_{q_B-1}$ & $\mathbf{T}_{q_T-1}$ that is allowed by the constraint of $\mathcal{C}_{q_B,q_T,q_B-1,q_T-1}$ and a subsequent max over the pairs of row directions can be upperbounded by a single sup over $S^{b_{-2}-1} \times S^{t_{-2}-1}$. Thus we have,

$$m\hat{\mathcal{R}}_m \leq \mathbb{E}_\epsilon \left[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in S^{b_{-2}-1} \times S^{t_{-2}-1} \\ \mathcal{W}_{\text{rest}}}} \left(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1} \cdot \left| \sum_{i=1}^{m} \epsilon_i \sigma_1 \left(\mathbf{v}^\top \mathbf{f}_B'(\mathbf{x}_{B,i}) \right) \cdot \sigma_2 \left(\mathbf{w}^\top \mathbf{f}_T'(\mathbf{x}_{T,i}) \right) \right| \right) \right].$$

Invoking Lemma I.1, we have

$$m\hat{\mathcal{R}}_m \leq \mathbb{E}_\epsilon \left[2 \times \sup_{\substack{(\mathbf{v},\mathbf{w}) \in S^{b_{-2}-1} \times S^{t_{-2}-1} \\ \mathcal{W}_{\text{rest}}}} \left(\mathcal{C}_{q_B,q_T,q_B-1,q_T-1} \cdot \sum_{i=1}^{m} \epsilon_i \sigma_1 \left(\mathbf{v}^\top \mathbf{f}_B'(\mathbf{x}_{B,i}) \right) \cdot \sigma_2 \left(\mathbf{w}^\top \mathbf{f}_T'(\mathbf{x}_{T,i}) \right) \right) \right].$$

Now we invoke Lemma 11, assuming that Assumption 5 holds for σ_1 and σ_2 for some $L > 0$, to get,

$$m\hat{\mathcal{R}}_m \leq 2L \cdot \mathcal{C}_{q_B,q_T,q_B-1,q_T-1} \cdot \mathbb{E}_\epsilon \left[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in S^{b_{-2}-1} \times S^{t_{-2}-1} \\ \mathcal{W}_{\text{rest}}}} \left(\sum_{i=1}^{m} \epsilon_i \mathbf{v}^\top \mathbf{f}_B'(\mathbf{x}_{B,i}) \cdot \mathbf{w}^\top \mathbf{f}_T'(\mathbf{x}_{T,i}) \right) \right].$$

The above inequality is exactly what we set out to prove.

G Proof of Proposition 14

Proof We start with the expression in the R.H.S. of the Proposition 13 and simplify it similarly as was done in its proof in the previous appendix. Denote $\mathcal{S}_2 = S^{b_{-2}-1} \times S^{t_{-2}-1}$.

$$\begin{aligned}
&\mathbb{E}_\epsilon \left[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2 \\ \mathcal{W}_{\text{rest}}}} \left(\sum_{i=1}^{m} \epsilon_i \mathbf{v}^\top \mathbf{f}_B'(\mathbf{x}_{B,i}) \cdot \mathbf{w}^\top \mathbf{f}_T'(\mathbf{x}_{T,i}) \right) \right] \\
=&\mathbb{E}_\epsilon \left[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2 \\ \mathcal{W}_{\text{rest}}}} \left(\sum_{i=1}^{m} \epsilon_i \mathbf{v}^\top \sigma_1(\mathbf{B}_{q_B-2} \mathbf{f}_B''(\mathbf{x}_{B,i})) \cdot \mathbf{w}^\top \sigma_2(\mathbf{T}_{q_T-2} \mathbf{f}_T''(\mathbf{x}_{T,i})) \right) \right] \\
=&\mathbb{E}_\epsilon \left[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2 \\ \mathcal{W}_{\text{rest}}}} \sum_{j_1=1}^{b_{-2}} \sum_{j_2=1}^{t_{-2}} (\mathbf{v}\mathbf{w}^\top)_{j_1,j_2} \left\|\mathbf{B}_{q_B-2,j_1}\right\| \left\|\mathbf{T}_{q_T-2,j_2}\right\| \cdot \sum_{i=1}^{m} \epsilon_i \sigma_1(\hat{\mathbf{B}}_{q_B-2,j_1}^\top \mathbf{f}_B''(\mathbf{x}_{B,i})) \sigma_2(\hat{\mathbf{T}}_{q_T-2,j_2}^\top \mathbf{f}_T''(\mathbf{x}_{T,i})) \right].
\end{aligned}$$

Define

$$\begin{aligned}
\tilde{v}_{j_1,j_2} &\coloneqq (\mathbf{v}\mathbf{w}^\top)_{j_1,j_2} \left\|\mathbf{B}_{q_B-2,j_1}\right\| \left\|\mathbf{T}_{q_T-2,j_2}\right\| \\
\tilde{w}_{j_1,j_2} &\coloneqq \sum_{i=1}^{m} \epsilon_i \sigma_1(\hat{\mathbf{B}}_{q_B-2,j_1}^\top \mathbf{f}_B''(\mathbf{x}_{B,i})) \sigma_2(\hat{\mathbf{T}}_{q_T-2,j_2}^\top \mathbf{f}_T''(\mathbf{x}_{T,i})).
\end{aligned}$$

Thus we get,

$$\begin{aligned}
\mathbb{E}_\epsilon \left[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2 \\ \mathcal{W}_{\text{rest}}}} \left(\sum_{i=1}^{m} \epsilon_i \mathbf{v}^\top \mathbf{f}_B'(\mathbf{x}_{B,i}) \cdot \mathbf{w}^\top \mathbf{f}_T'(\mathbf{x}_{T,i}) \right) \right] &= \mathbb{E}_\epsilon \left[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2 \\ \mathcal{W}_{\text{rest}}}} \sum_{j_1=1}^{b_{-2}} \sum_{j_2=1}^{t_{-2}} \tilde{v}_{j_1,j_2} \tilde{w}_{j_1,j_2} \right] \\
&\leq \mathbb{E}_\epsilon \left[\sup_{\substack{(\mathbf{v},\mathbf{w}) \in \mathcal{S}_2 \\ \mathcal{W}_{\text{rest}}}} \left(\sum_{j_1=1}^{b_{-2}} \sum_{j_2=1}^{t_{-2}} \left|\tilde{v}_{j_1,j_2}\right| \cdot \max_{j_1,j_2} \left|\tilde{w}_{j_1,j_2}\right| \right) \right].
\end{aligned}$$

For ease of notation we define the set $\mathcal{W}_{-2,-2}$ as the set of matrices allowed in $\mathcal{W}_{rest}$ but with those with indices q_B-2 and q_T-2 additionally satisfying the constraint in equation 15 in the statement of the lemma.

$$\mathbb{E}_\epsilon\left[\sup_{\substack{(\mathbf{v},\mathbf{w})\in\mathcal{S}_2\\ \mathcal{W}_{\text{rest}}}}\left(\sum_{i=1}^m \epsilon_i \mathbf{v}^\top \mathbf{f}_B'(\mathbf{x}_{B,i})\cdot \mathbf{w}^\top \mathbf{f}_T'(\mathbf{x}_{T,i})\right)\right]$$

$$\leq \mathcal{C}_{-2,-2}\mathbb{E}_\epsilon\left[\sup_{\mathcal{W}_{-2,-2}}\left(\max_{\substack{j_1=1,\ldots q_B-2\\ j_2=1,\ldots,q_T-2}}\left|\tilde{w}_{j_1,j_2}\right|\right)\right]$$

$$\leq \mathcal{C}_{-2,-2}\mathbb{E}_\epsilon\left(\sup_{\mathcal{W}_{-2,-2}}\left(\max_{\substack{j_1=1,\ldots q_B-2\\ j_2=1,\ldots,q_T-2}}\left|\sum_{i=1}^m \epsilon_i \sigma_1(\hat{\mathbf{B}}_{q_B-2,j_1}^\top \mathbf{f}_B''(\mathbf{x}_{B,i}))\sigma_2(\hat{\mathbf{T}}_{q_T-2,j_2}^\top \mathbf{f}_T''(\mathbf{x}_{T,i}))\right|\right)\right).$$

We note that any pair of row directions in the pair of matrices $(\mathbf{B}_{q_B-2}, \mathbf{T}_{q_T-2})$ is $\in S^{b_{-3}-1}\times S^{t_{-3}-1}$. So a sup over the set of $\mathbf{B}_{q_B-2}$ & $\mathbf{T}_{q_T-2}$ that is allowed by the constraint of $\mathcal{C}_{-2,-2}$ and a subsequent max over the pairs of row directions can be upper-bounded by a single sup over $S^{b_{-3}-1}\times S^{t_{-3}-1}$.

We recall the definition of $\mathcal{W}'_{rest}$ given in the lemma to conclude, ($\mathcal{S}_3 = S^{b_{-3}-1}\times S^{t_{-3}-1}$)

$$\mathbb{E}_\epsilon\left[\sup_{\substack{(\mathbf{v},\mathbf{w})\in\mathcal{S}_2\\ \mathcal{W}_{\text{rest}}}}\left(\sum_{i=1}^m \epsilon_i \mathbf{v}^\top \mathbf{f}_B'(\mathbf{x}_{B,i})\cdot \mathbf{w}^\top \mathbf{f}_T'(\mathbf{x}_{T,i})\right)\right]$$

$$\leq \mathcal{C}_{-2,-2}\mathbb{E}_\epsilon\left(\sup_{\substack{(\mathbf{v},\mathbf{w})\in\mathcal{S}_3\\ \mathcal{W}'_{rest}}}\left|\sum_{i=1}^m \epsilon_i \sigma_1(\mathbf{v}^\top \mathbf{f}_B''(\mathbf{x}_{B,i}))\sigma_2(\mathbf{w}^\top \mathbf{f}_T''(\mathbf{x}_{T,i}))\right|\right).$$

Invoking Lemma I.1,

$$\leq 2\mathcal{C}_{-2,-2}\mathbb{E}_\epsilon\left(\sup_{\substack{(\mathbf{v},\mathbf{w})\in\mathcal{S}_3\\ \mathcal{W}'_{rest}}}\sum_{i=1}^m \epsilon_i \sigma_1(\mathbf{v}^\top \mathbf{f}_B''(\mathbf{x}_{B,i}))\sigma_2(\mathbf{w}^\top \mathbf{f}_T''(\mathbf{x}_{T,i}))\right)$$

$$\leq 2L\mathcal{C}_{-2,-2}\mathbb{E}_\epsilon\left(\sup_{\substack{(\mathbf{v},\mathbf{w})\in\mathcal{S}_3\\ \mathcal{W}'_{rest}}}\sum_{i=1}^m \epsilon_i (\mathbf{v}^\top \mathbf{f}_B''(\mathbf{x}_{B,i}))(\mathbf{w}^\top \mathbf{f}_T''(\mathbf{x}_{T,i}))\right).$$

In the last step above we have invoked Lemma 11 using the fact that Assumption 5 is true about σ_1 and σ_2.

H Generalization Bound For DeepONets For Unbounded Data

Definition H.1 ($\phi_{\mathcal{H}}$ Loss Function Class) *Given $\mathcal{H}$ as defined in Theorem 10, we define the class $\phi_{\mathcal{H}}$ associated with $\mathcal{H}$ as,*

$$\phi_{\mathcal{H}} \coloneqq \{\mathcal{F}\times\mathbb{R}^{d_2} \ni (f,\mathbf{x}_T)\mapsto \ell(h(f,\mathbf{x}_T))\in[0,\infty) \mid h\in\mathcal{H}\}$$

where ℓ is some non-negative univariate (loss) function

Applying Theorem 4.13 of [Ma21] to the above loss class we get the following theorem

Theorem H.2 *Given $\phi_{\mathcal{H}}$ as in Definition H.1 we have,*

$$\mathbb{E}_{\{(f_i,\mathbf{x}_{T,i})\overset{iid}{\sim}\mathcal{D}|i=1\ldots m\}}\left[\sup_{h\in\mathcal{H}}\left[\frac{1}{m}\sum_{i=1}^m \ell(h(f_i,\mathbf{x}_{T,i})) - \mathbb{E}_{(f,\mathbf{x}_T)\sim\mathcal{D}}\left[\ell(h(f,\mathbf{x}_T))\right]\right]\right] \leq 2\mathcal{R}_m(\phi_{\mathcal{H}})$$

where m is the number of samples used in the empirical risk, $\mathcal{D}$ is a distribution over $\mathcal{F}\times\mathbb{R}^{d_2}$, and $\mathcal{R}_m$ is Rademacher complexity as defined in Equation 9.

Lemma H.3 (Lipschitz Composition in Rademacher Complexity) *Assume that $\phi : \mathbb{R} \mapsto \mathbb{R}$ is a L_ϕ-Lipschitz continuous function, such that $|\phi(t) - \phi(s)| \leq L_\phi |t - s|$. Suppose $\mathcal{V} \subset \mathbb{R}^m$. Then,*

$$\mathbb{E}_\epsilon \left[\sup_{f \in \mathcal{V}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \phi(f_i) \right] \leq L_\phi \, \mathbb{E}_\epsilon \left[\sup_{f \in \mathcal{V}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i f_i \right].$$

Lemma H.4 ($\mathcal{R}(\ell(\mathcal{H}))$ in terms of $\mathcal{R}(\mathcal{H})$) *Given $\mathcal{H}$ as defined in Theorem 10, if $\ell(\cdot)$ is $R-$Lipschitz,*

$$\mathbb{E}_\epsilon \left[\sup_{h \in \mathcal{H}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, \ell(h(f_i, \mathbf{x}_{T,i})) \right] = \mathcal{R}(\ell(\mathcal{H})) \leq R \cdot \mathcal{R}(\mathcal{H}) = R \cdot \mathbb{E}_\epsilon \left[\sup_{h \in \mathcal{H}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, h(f_i, \mathbf{x}_{T,i}) \right].$$

Proof Any function $h \in \mathcal{H}$ maps from $\mathcal{F} \times \mathbb{R}^{d_2} \mapsto \mathbb{R}$. Hence, training data of size m for the DeepONet is of the form $\{(f_i, \mathbf{x}_{T,i}) \in \mathcal{F} \times \mathbb{R}^{d_2}, \, i = 1, 2, \ldots, m\}$.

Consider the set $\mathcal{K} = \{(h(f_1, \mathbf{x}_1), \ldots, h(f_m, \mathbf{x}_m)) \mid h \in \mathcal{H}\} \subset \mathbb{R}^m$. Then we can re-write,

$$\mathcal{R}(\ell(\mathcal{H})) = \mathbb{E}_\epsilon \left[\sup_{k \in \mathcal{K}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, \ell(k_i) \right].$$

Invoking that the Lipschitz constant for $\ell(\cdot)$ is R, and Lemma H.3 we have,

$$\mathcal{R}(\ell(\mathcal{H})) \leq R \, \mathbb{E}_\epsilon \left[\sup_{k \in \mathcal{K}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, k_i \right],$$

which we recognize as the inequality we set out to prove,

$$\mathcal{R}(\ell(\mathcal{H})) \leq R \cdot \mathcal{R}(\mathcal{H}).$$

Lemma H.5 ($\mathcal{R}(\mathcal{H})$ in terms of $\mathcal{R}(\text{DeepONet})$) *Recall that $\mathcal{W}$ is the set of allowed weights in the function class $\mathcal{H}$ (as defined in Theorem 10). Corrresponding to it define the class* DeepONet *s.t* $\text{DeepONet}_{\mathbf{w}} \in \text{DeepONet}$ *denotes a DeepONet with weight $\mathbf{w} \in \mathcal{W}$. Then the following holds,*

$$\mathcal{R}(\text{DeepONet}) \coloneqq \mathbb{E}_\epsilon \left[\sup_{\mathbf{w} \in \mathcal{W}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, \text{DeepONet}_{\mathbf{w}}(f_i, \mathbf{x}_{T,i}) \right] = \mathcal{R}(\mathcal{H}).$$

Proof Realizing that taking a sup over $h \in \mathcal{H}$ and $\mathbf{w} \in \mathcal{W}$ are equivalent, we get,

$$\mathbb{E}_\epsilon \left[\sup_{h \in \mathcal{H}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, h(f_i, \mathbf{x}_{T,i}) \right] = \mathbb{E}_\epsilon \left[\sup_{\mathbf{w} \in \mathcal{W}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, \left(\mathcal{G}(f_i, \mathbf{x}_{T,i}) - \text{DeepONet}_{\mathbf{w}}(f_i, \mathbf{x}_{T,i}) \right) \right],$$

where we have used $h(f_i, \mathbf{x}_{T,i}) = \mathcal{G}(f_i, \mathbf{x}_{T,i}) - \text{DeepONet}_{\mathbf{w}}(f_i, \mathbf{x}_{T,i})$. We can write $\mathcal{R}(\mathcal{H})$ as

$$\begin{aligned}
\mathcal{R}(\mathcal{H}) &= \mathbb{E}_\epsilon \left[\sup_{\mathbf{w} \in \mathcal{W}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \left(\mathcal{G}(f_i, \mathbf{x}_{T,i}) - \text{DeepONet}_{\mathbf{w}}(f_i, \mathbf{x}_{T,i}) \right) \right] \\
&= \mathbb{E}_\epsilon \left[\sup_{\mathbf{w} \in \mathcal{W}} \left\{ \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, \mathcal{G}(f_i, \mathbf{x}_{T,i}) - \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, \text{DeepONet}_{\mathbf{w}}(f_i, \mathbf{x}_{T,i}) \right\} \right] \\
&= \mathbb{E}_\epsilon \left[\frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, \mathcal{G}(f_i, \mathbf{x}_{T,i}) + \sup_{\mathbf{w} \in \mathcal{W}} \frac{1}{m} \sum_{i=1}^{m} (-\epsilon_i) \, \text{DeepONet}_{\mathbf{w}}(f_i, \mathbf{x}_{T,i}) \right] \\
&= 0 + \mathbb{E}_\epsilon \left[\sup_{\mathbf{w} \in \mathcal{W}} \frac{1}{m} \sum_{i=1}^{m} \epsilon_i \, \text{DeepONet}_{\mathbf{w}}(f_i, \mathbf{x}_{T,i}) \right] \\
&= \mathcal{R}(\text{DeepONet}).
\end{aligned}$$

since, $\epsilon = -\epsilon$ in distribution.

Hence combining the above two lemmas we get,

Lemma H.6 ($\mathcal{R}(\ell(\mathcal{H}))$ in terms of $\mathcal{R}(\text{DeepONet})$) *Let $\ell(\cdot)$ be $R-$Lipschitz. Then,*

$$\mathcal{R}(\ell(\mathcal{H})) \leq R \cdot \mathcal{R}(\text{DeepONet}).$$

Proposition H.7 (Generalization Error Bound for DeepONet) *Given $\phi_{\mathcal{H}}$ as in Definition H.1 and let $\ell(\cdot)$ be $R-$Lipschitz. Then we have the following generalization bound,*

$$\mathbb{E}_{\{(f_i,\mathbf{x}_{T,i})\overset{iid}{\sim}\mathcal{D}\ |i=1\ldots m\}}\left[\sup_{h\in\mathcal{H}}\left[\frac{1}{m}\sum_{i=1}^{m}\ell(h(f_i,\mathbf{x}_{T,i}))-\mathbb{E}_{(f,\mathbf{x}_T)\sim\mathcal{D}}\left[\ell(h(f,\mathbf{x}_T))\right]\right]\right]\leq 2R\cdot\mathcal{R}_m$$

where $\mathcal{R}_m$ is as in Theorem 9, and $\mathcal{D}$ is a distribution over $\mathcal{F}\times\mathbb{R}_{d_2}$

Proof We recall from Theorem H.2 that,

$$\mathbb{E}_{\{(f_i,\mathbf{x}_{T,i})\overset{iid}{\sim}\mathcal{D}|i=1\ldots m\}}\left[\sup_{h\in\mathcal{H}}\left[\frac{1}{m}\sum_{i=1}^{m}\ell(h(f_i,\mathbf{x}_{T,i}))-\mathbb{E}_{(f,\mathbf{x}_T)\sim\mathcal{D}}\left[\ell(h(f,\mathbf{x}_T))\right]\right]\right]\leq 2\mathcal{R}_m(\phi_{\mathcal{H}})$$

Now, invoking Lemma H.6 and using the fact that $\ell(\cdot)$ is $R-$Lipschitz we get the claimed inequality.

I Contraction Lemmas

Lemma I.1 *(From [Ma21]) Let $\epsilon\sim\text{Uniform}(\{1,-1\}^m)$ and suppose we have functions $\mathbf{f}_\theta$ and f'_θ parameterized by θ s.t, $(\mathbb{R}^k)^m\ni\mathbf{x}\mapsto\mathbf{f}_\theta(\mathbf{x})=\left(f'_\theta(x_1),\ldots,f'_\theta(x_m)\right)\in\mathbb{R}^m$. Suppose that for any $\epsilon\in\{\pm1\}^m$, $\sup_\theta\langle\epsilon,\mathbf{f}_\theta(x)\rangle\geq 0$. Then,*

$$\mathbb{E}_\epsilon\left[\sup_\theta|\langle\epsilon,\mathbf{f}_\theta(\mathbf{x})\rangle|\right]\leq 2\mathbb{E}_\epsilon\left[\sup_\theta\langle\epsilon,\mathbf{f}_\theta(\mathbf{x})\rangle\right].$$

Proof Letting ϕ be the ReLU function, the lemma's assumption implies that $\sup_\theta\phi\left(\langle\epsilon,f_\theta(x)\rangle\right)=\sup_\theta\langle\epsilon,f_\theta(x)\rangle$ for any $\epsilon\in\{\pm1\}^n$. Observing that $|z|=\phi(z)+\phi(-z)$,

$$\begin{aligned}\sup_\theta|\langle\epsilon,\mathbf{f}_\theta(x)\rangle|&=\sup_\theta\left[\phi\left(\langle\epsilon,\mathbf{f}_\theta(x)\rangle\right)+\phi\left(\langle-\epsilon,\mathbf{f}_\theta(x)\rangle\right)\right]\\&\leq\sup_\theta\phi\left(\langle\epsilon,\mathbf{f}_\theta(x)\rangle\right)+\sup_\theta\phi\left(\langle-\epsilon,\mathbf{f}_\theta(x)\rangle\right)\\&=\sup_\theta\langle\epsilon,\mathbf{f}_\theta(x)\rangle+\sup_\theta\langle-\epsilon,\mathbf{f}_\theta(x)\rangle.\end{aligned}$$

Taking the expectation over ϵ (and noting that ϵ and $-\epsilon$ have the same distribution) we get the desired conclusion.

I.1 Proof of Lemma 11

Proof

$$\mathcal{R}_{\text{m}}(\phi_P\circ\mathcal{P}\cdot\phi_Q\circ\mathcal{Q})=\frac{1}{m}\mathbb{E}_{\epsilon\sim U(\{-1,1\}^m)}\left[\sup_{(p,q)\in\mathcal{P}\times\mathcal{Q}}\sum_{i=1}^{m}\epsilon_i\cdot\phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i))\right].$$

We explicitly open up the expectation on ϵ_1 to get,

$$\begin{aligned}&=\frac{1}{2m}\cdot\mathbb{E}_{(\epsilon_2,\ldots,\epsilon_m)\sim U(\{-1,1\}^{m-1})}\left[\sup_{f,q\in\mathcal{P}\times\mathcal{Q}}\left(\phi_P(p(\mathbf{x}_1))\phi_Q(q(\mathbf{y}_1))+\sum_{i=2}^{m}\epsilon_i\cdot\phi_P(p(\mathbf{x}_i)\phi_Q(q(\mathbf{y}_i)))\right)+\right.\\&\qquad\left.\sup_{f',q'\in\mathcal{P}\times\mathcal{Q}}\left(-\phi_P(p'(\mathbf{x}_1))\phi_Q(q'(\mathbf{y}_1))+\sum_{i=2}^{m}\epsilon_i\cdot\phi_P(p'(\mathbf{x}_i))\phi_Q(q'(\mathbf{y}_i))\right)\right]\\&\leq\frac{1}{2m}\cdot\mathbb{E}_{(\epsilon_2,\ldots,\epsilon_m)}\left[\sup_{((p,q),(p',q'))\in(\mathcal{P}\times\mathcal{Q})^2}\left(L\cdot\left|\phi_P(p(\mathbf{x}_1))\phi_Q(q(\mathbf{y}_1))-\phi_P(p'(\mathbf{x}_1))\phi_Q(q'(\mathbf{y}_1))\right|\right.\right.\\&\qquad\left.\left.+\sum_{i=2}^{m}\epsilon_i\left(\phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i))+\phi_P(p'(\mathbf{x}_i))\phi_Q(q'(\mathbf{y}_i))\right)\right)\right]\end{aligned}$$

By invoking the the assumption 5 we get,

$$\leq \frac{1}{2m} \cdot \mathbb{E}_{(\epsilon_2,\ldots,\epsilon_m)}\Bigg[\sup_{((p,q),(p',q'))\in(\mathcal{P}\times\mathcal{Q})^2} \Bigg(L \cdot \left| p(\mathbf{x}_1)q(\mathbf{y}_1) - p'(\mathbf{x}_1)q'(\mathbf{y}_1) \right| + \sum_{i=2}^{m} \epsilon_i \left(\phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i)) + \phi_P(p'(\mathbf{x}_i))\phi_Q(q'(\mathbf{y}_i)) \right) \Bigg) \Bigg]$$

Now we invoke the fact that inside a supremum, an absolute value function is redundant, since anyway the higher combination will get picked. Thus we can rearrange the above to get,

$$\leq \frac{1}{2m} \cdot \mathbb{E}_{(\epsilon_2,\ldots,\epsilon_m)}\Bigg[\sup_{(p,q)\in\mathcal{P}\times\mathcal{Q}} \left(L \cdot p(\mathbf{x}_1)q(\mathbf{y}_1)) + \sum_{i=2}^{m} \epsilon_i \cdot \phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i)) \right) + \sup_{(p',q')\in\mathcal{P}\times\mathcal{Q}} \left(-L \cdot p'(\mathbf{x}_1)q'(\mathbf{y}_1) + \sum_{i=2}^{m} \epsilon_i \cdot \phi_P(p'(\mathbf{x}_i))\phi_Q(q'(\mathbf{y}_i)) \right) \Bigg]$$

$$\leq \frac{1}{m} \cdot \mathbb{E}_{\epsilon}\Bigg[\sup_{(p,q)\in\mathcal{P}\times\mathcal{Q}} \left(\epsilon_1 \cdot L \cdot p(\mathbf{x}_1)q(\mathbf{y}_1) + \sum_{i=2}^{m} \epsilon_i \cdot \phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i)) \right) \Bigg]$$

Re-iterating the above argument for $i = 2, 3, , \ldots, m$ we get,

$$= \frac{1}{m}\mathbb{E}_{\epsilon\sim U(\{-1,1\}^m)} \sup_{(p,q)\in\mathcal{P}\times\mathcal{Q}} \left[\sum_{i=1}^{m} \epsilon_i L \cdot p(\mathbf{x}_i)q(\mathbf{y}_i) \right]$$
$$= L\mathcal{R}_{\mathrm{m}}(\mathcal{P}\cdot\mathcal{Q}).$$

I.2 A Contraction Lemma with Biased Absolute Functions

Lemma I.2 *Let $\mathcal{P}$ and $\mathcal{G}$ be set of functions valued in $\mathbb{R}$ closed under negation. Given points $\{\mathbf{x}_i \mid i = 1, \ldots, m\}$, $\{\mathbf{y}_i \mid i = 1, \ldots, m\}$ in the domain of the functions in we have the following inequality of Rademacher complexities - where both the sides are being evaluated on this same set of points,*

$$\mathcal{R}_{\mathrm{m}}(|\mathcal{P} + B_1| \cdot |\mathcal{G} + B_2|) \leq \mathcal{R}_{\mathrm{m}}(\mathcal{P}\cdot\mathcal{G}) + |B_2|\mathcal{R}_{\mathrm{m}}(\mathcal{P}) + |B_1|\mathcal{R}_{\mathrm{m}}(\mathcal{G})$$

Proof Denote the uniform distribution over $\{-1, 1\}^m$ by $U(\{-1, 1\}^m)$. Then,

$$\mathcal{R}_{\mathrm{m}}(|\mathcal{P} + B_1| \cdot |\mathcal{Q} + B_2|) \leq \frac{1}{m}\mathbb{E}_{\epsilon\sim U(\{-1,1\}^m)} \sup_{p,q\in\mathcal{P}\times\mathcal{Q}} \left[\sum_{i=1}^{m} \epsilon_i \cdot |p(\mathbf{x}_i) + B_1||q(\mathbf{y}_i) + B_2| \right].$$

We explicitly open up the expectation on ϵ_1 to get,

$$
\begin{aligned}
&= \frac{1}{2m}\cdot \mathbb{E}_{(\epsilon_2,\ldots,\epsilon_m)\sim U(\{-1,1\}^{m-1})}\Bigg[\sup_{p,q\in\mathcal{P}\times\mathcal{Q}}\left(|p(\mathbf{x}_1)+B_1||q(\mathbf{y}_1)+B_2|+\sum_{i=2}^{m}\epsilon_i\cdot\phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i))\right)+\\
&\qquad\qquad \sup_{p',q'\in\mathcal{P}\times\mathcal{Q}}\left(-|p'(\mathbf{x}_1)+B_1||q'(\mathbf{y}_1)+B_2|+\sum_{i=2}^{m}\epsilon_i\cdot\phi_P(p'(\mathbf{x}_i))\phi_Q(q'(\mathbf{y}_i))\right)\Bigg]\\
&\leq \frac{1}{2m}\cdot \mathbb{E}_{(\epsilon_2,\ldots,\epsilon_m)}\Bigg[\sup_{p,p',q,q'\in\mathcal{P}\times\mathcal{P}\times\mathcal{Q}\times\mathcal{Q}}\Big(|p(\mathbf{x}_1)q(\mathbf{y}_1)-p'(\mathbf{x}_1)q'(\mathbf{y}_1)|+|B_2||p(\mathbf{x}_1)-p'(\mathbf{x}_1)|+|B_1||q(\mathbf{y}_1)-q'(\mathbf{y}_1)|\\
&\qquad\qquad +\sum_{i=2}^{m}\epsilon_i\left(\phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i))+\phi_P(p'(\mathbf{x}_i))\phi_Q(q'(\mathbf{y}_i))\right)\Big)\Bigg]\\
&= \frac{1}{2m}\cdot \mathbb{E}_{(\epsilon_2,\ldots,\epsilon_m)}\Bigg[\sup_{p,q\in\mathcal{P}\times\mathcal{Q}}\left(p(\mathbf{x}_1)q(\mathbf{y}_1)+|B_2|p(\mathbf{x}_1)+|B_1|q(\mathbf{y}_1)+\sum_{i=2}^{m}\epsilon_i\cdot\phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i))\right)\\
&\qquad\qquad +\sup_{p',q'\in\mathcal{P}\times\mathcal{Q}}\left(-p'(\mathbf{x}_1)q'(\mathbf{y}_1)-|B_2|p'(\mathbf{x}_1)-|B_1|q'(\mathbf{y}_1)+\sum_{i=2}^{m}\epsilon_i\cdot\phi_P(p'(\mathbf{x}_i))\phi_Q(q'(\mathbf{y}_i))\right)\Bigg]\\
&\leq \frac{1}{m}\cdot \mathbb{E}_{\epsilon}\left[\sup_{f,g\in\mathcal{P}\times\mathcal{Q}}\left(\epsilon_1\cdot\big(p(\mathbf{x}_1)q(\mathbf{y}_1)+|B_2|p(\mathbf{x}_1)+|B_1|q(\mathbf{y}_1)\big)+\sum_{i=2}^{m}\epsilon_i\cdot\phi_P(p(\mathbf{x}_i))\phi_Q(q(\mathbf{y}_i))\right)\right]
\end{aligned}
$$

Iterating this, we get

$$
\begin{aligned}
&\leq \frac{1}{m}\mathbb{E}_{\epsilon\sim U(\{-1,1\}^m)}\sup_{p,q\in\mathcal{P}\times\mathcal{Q}}\left[\sum_{i=1}^{m}\epsilon_i\cdot\big(p(\mathbf{x}_i)q(\mathbf{y}_i)+|B_2|p(\mathbf{x}_i)+|B_1|q(\mathbf{y}_i)\right]\\
&\leq \mathcal{R}_m(\mathcal{P}\cdot\mathcal{Q})+|B_2|\mathcal{R}_m(\mathcal{P})+|B_1|\mathcal{R}_m(\mathcal{Q}).
\end{aligned}
$$

In the second inequality we have used

$$
\Big||p(\mathbf{x}_1)+B_1|\cdot|q(\mathbf{y}_1)+B_2|-|p'(\mathbf{x}_1)+B_1|\cdot|q'(\mathbf{y}_1)+B_2|\Big|\leq\Big|(p(\mathbf{x}_1)+B_1)(q(\mathbf{y}_1)+B_2)-(p'(\mathbf{x}_1)+B_1)(q'(\mathbf{y}_1)+B_2)\Big|.
$$

In the next line we could open up the $|\cdot|$ since the supremum would be positive and $\mathcal{P}$ and $\mathcal{Q}$ are closed under multiplication by -1.

J Converting ReLU –DeepONets to abs–DeepONets

Firstly, we recall that the map $\mathbb{R}^q \ni \mathbf{x}\mapsto \mathbf{x}\in\mathbb{R}^q$ is an exact depth 2 ReLU net – one which passes every coordinate of the input through the ReLU net $\mathbb{R}\ni z\mapsto \max\{0,z\}-\max\{0,-z\}\in\mathbb{R}$. Using this, given any ReLU DeepONet, we can symmetrize the depths between the branch and the trunk by attaching the required number of identity computing layers at the input to the shorter side.

Secondly, for typical DeepONet experiments, one can assume that the the set of all possible input data is bounded. Combining this with the assumption of boundedness of the allowed matrices, we conclude that $\exists\ \mathcal{B}>0$ s.t the input to any ReLU gate in any DeepONet in the given class is bounded by $\mathcal{B}$. Now we observe that $\forall |z|\leq\mathcal{B}$, we can rewrite the map $z\mapsto\max\{0,z\}$ as, $z\mapsto\frac{1}{2}|z|+\frac{1}{4}|z+\mathcal{B}|-\frac{1}{4}|z-\mathcal{B}|$.

Hence, doing the above replacement at every gate we can rewrite any ReLU DeepONet (without biases) as a DeepONet using only absolute value activations but with biases – and computing the same function on the same bounded domain, at the cost of increasing the size of the branch and the trunk net by a factor of 3. Thirdly, a similar result as in Lemma 11 continues to hold for this setup as given in Lemma I.2. Note that, Lemma I.2 bounds the Rademacher complexity of a DeepONet class with the branch and trunk depths (k,k) by a linear sum of that of $(k-1,k-1)$ and sum of a $(k,0)$ and a $(0,k)$ DeepONet. While the first term can be recursed on again (using identical techniques as used to prove Theorem 9), for the last two one can invoke Theorem 1 of [GRS18].

Thus, we observe that following the same arguments as in the proof for Theorem 9 we can derive an analogous bound for arbitrary ReLU DeepONet classes - but with twice the depth of the DeepONet number of extra terms in the R.H.S. These extra terms would come in pairs – each pair consisting of a Rademacher complexity bound on a standard net, one from the branch side and one from the trunk side and of decreasing depths.

K Choosing $\tilde{\mathcal{C}}_{-k,-k}$

Defining $\left[X_{j_1,j_2}\right]_{\substack{j_1=1,\ldots,b_{-k}\\k_1=1,\ldots,t_{-k}}} \coloneqq \mathbf{X} \in \mathbb{R}^{b_{-k}\times t_{-k}}$ s.t $X_{j_1,j_2} \coloneqq \left\|\mathbf{B}_{n-k,j_1}\right\| \cdot \left\|\mathbf{T}_{n-k,j_2}\right\|$, we can simplify as follows the expression defining $\mathcal{C}_{-k,-k}$ in equation 4,

$$\begin{aligned}
&\sup_{(\mathbf{v},\mathbf{w})\in S^{-1+b_{-k}}\times S^{-1+t_{-k}}} \sum_{j_1=1}^{b_{-k}}\sum_{j_2=1}^{t_{-k}} \left|(\mathbf{v}\mathbf{w}^\top)_{j_1,j_2}\right| \left\|\mathbf{B}_{n-k,j_1}\right\| \left\|\mathbf{T}_{n-k,j_2}\right\| \\
&= \sup_{(\mathbf{v},\mathbf{w})\in S^{-1+b_{-k}}\times S^{-1+t_{-k}}} \sum_{j_1=1}^{b_{-k}}\sum_{j_2=1}^{t_{-k}} \left|v_{j_1}\right| \left\|\mathbf{B}_{n-k,j_1}\right\| \left\|\mathbf{T}_{n-k,j_2}\right\| \left|w_{j_2}\right| \\
&= \sup_{(\mathbf{v},\mathbf{w})\in S^{-1+b_{-k}}\times S^{-1+t_{-k}}} \sum_{j_1=1}^{b_{-k}}\sum_{j_2=1}^{t_{-k}} \left|v_{j_1}\right| \cdot \mathbf{X}_{j_1,j_2} \cdot \left|w_{j_2}\right| \\
&= \sup_{(\mathbf{v},\mathbf{w})\in S^{-1+b_{-k}}\times S^{-1+t_{-k}}} \tilde{\mathbf{v}}^\top \mathbf{X} \tilde{\mathbf{w}}
\end{aligned}$$

In the last line above we defined vectors $\tilde{\mathbf{v}}$ and $\tilde{\mathbf{w}}$ of appropriate dimensions s.t $\tilde{v}_i = |v_i|$ and $\tilde{w}_i = |w_i|$. Then note that, $\tilde{\mathbf{v}}^\top \mathbf{X} \tilde{\mathbf{w}} \leq \|\tilde{\mathbf{v}}\|_2 \|\mathbf{X}\tilde{\mathbf{w}}\|_2 \leq \|\tilde{\mathbf{v}}\|_2 \|\mathbf{X}\| \|\tilde{\mathbf{w}}\|_2$

In above $\|\mathbf{X}\|$ is the spectral norm of $\mathbf{X}$. Therefore we have the following upperbound,

$$\sup_{\mathbf{v},\mathbf{w}} \|\tilde{\mathbf{v}}\|_2 \|\mathbf{X}\| \|\tilde{\mathbf{w}}\|_2 \leq \sup_{\mathbf{v}} \|\tilde{\mathbf{v}}\|_2 \cdot \sup_{\mathbf{w}} \|\tilde{\mathbf{w}}\|_2 \cdot \|\mathbf{X}\|$$

Since $\|\tilde{\mathbf{v}}\| = \|\mathbf{v}\| \leq 1$ and $\|\tilde{\mathbf{w}}\| = \|\mathbf{w}\| \leq 1$ we have,

$$\sup_{(\mathbf{v},\mathbf{w})\in S^{-1+b_{-k}}\times S^{-1+t_{-k}}} \tilde{\mathbf{v}}^\top \mathbf{X} \tilde{\mathbf{w}} \leq \left\| \left[\left\|\mathbf{B}_{n-k,j_1}\right\| \cdot \left\|\mathbf{T}_{n-k,j_2}\right\| \right]_{\substack{j_1=1,\ldots,b_{-k}\\k_1=1,\ldots,t_{-k}}} \right\|$$

Thus it follows that the RHS of the above inequality gives an intuitive candidate for the quantity $\tilde{\mathcal{C}}_{-k,-k}$.

L Links to code

In this link we have given the code to generate the plot in Appendix A. The reader can change the activation from tanh to abs to recreate plots in Section 2.3.