FLEURS: Few-shot Learning Evaluation of Universal Representations of Speech

Alexis Conneau^{†‡1}, Min Ma^{†2}, Simran Khanuja^{†2}, Yu Zhang², Vera Axelrod², Siddharth Dalmia³, Jason Riesa², Clara Rivera², Ankur Bapna^{‡2}

¹Meta AI Research, ²Google Research, ³Carnegie Mellon University

aconneau@fb.com, {minm, simrankh, ngyuzh, vaxelrod, ankurbpn}@google.com, sdalmia@cs.cmu.edu

Abstract

We introduce FLEURS, the Few-shot Learning Evaluation of Universal Representations of Speech benchmark. FLEURS is an n-way parallel speech dataset in 102 languages built on top of the machine translation FLoRes-101 benchmark, with approximately 12 hours of speech supervision per language. FLEURS can be used for a variety of speech tasks, including Automatic Speech Recognition (ASR), Speech Language Identification (Speech LangID), Translation and Retrieval. In this paper, we provide baselines for the tasks based on multilingual pre-trained models like mSLAM. The goal of FLEURS is to enable speech technology in more languages and catalyze research in low-resource speech understanding.

1. Introduction

Speech technology has seen rapid development in the past few years, from the use of self-attention models [1, 2] to pre-training approaches [3, 4]. Methods like wav2vec 2.0 have demonstrated strong performance on LibriSpeech [5], in particular in the few-shot learning scenario with only 10 minutes of labeled data [6]. The recent scaled-up multilingual wav2vec 2.0 model, dubbed XLS-R [7], has expanded similar few-shot capabilities to many more languages, including low-resource ones. By leveraging large-scale pretraining datasets like Multilingual LibriSpeech [8] and VoxPopuli [9], XLS-R also provides representations that can be used across tasks, with significant gains over previous baselines on speech recognition, translation and classification. More recently, mSLAM [10], a joint speech and text multilingual pretrained model, outperformed XLS-R on speech translation and ASR and improved over speech-only baselines on Speech-LangID.

This progress was made possible by the release of both large-scale pretraining and evaluation datasets like Multilingual LibriSpeech [8], VoxPopuli [9], CoVoST-2 [11], CommonVoice [12] and the re-use of existing datasets like BA-BEL [13]. These datasets provide evaluations for speech recognition and speech translation in between 8 and 60 languages each. VoxLingua107 [14] also provides a Speech LangID classification dataset in 107 languages.

In machine translation, the release of new benchmarks like FLoRes-101 [20] has enabled advances in publicly available massively multilingual machine translation systems [21]. With FLEURS, we hope to provide a resource that could catalyze research towards building massively multilingual speech and

text representations and their evaluation on a variety of tasks. While there are a few other datasets containing n-way parallel speech and text, including Europarl-ST [16], MuST-C [17], mT-EDx [18] and the CVSS corpus [19], to the best of our knowledge, FLEURS is the only dataset spanning over 100 languages enabling research on a diverse set of languages. There are a few key properties of FLEURS that are important to note:

- FLEURS contains n-way parallel speech and text in 102 languages, see Table 9 for a full list;
- FLEURS provides natural human speech and high quality transcripts for each language with strong quality control;
- FLEURS uses a bottom up approach of collecting spoken utterances for aligned segments, while most other datasets are aligned at a document level with automatic segmentation and alignment for segments;

FLEURS is well-suited for several downstream tasks including ASR, Speech-to-Text and Speech-to-Speech Translation, Speech LangID, and Multilingual Speech-to-Speech and Speech-to-Text Retrieval. We compare FLEURS to existing common public multilingual corpora in Table 1.

In addition to the describing the dataset, we provide baselines for Speech-LangID, ASR and Speech-Text retrieval (both Speech-to-Text and Text-to-Speech retrieval) by fine-tuning the mSLAM [10] and multilingual w2v-BERT [22, 10] baselines on these tasks.

2. Dataset

2.1. Speech Data Collection

Our data collection process is simple. We start with the FLoRes-101 dataset.² FLoRes-101 contains 3001 sentences extracted from English Wikipedia and these sentences have been translated in 101 languages by human translators. Because the test set of FLoRes-101 is not publicly available, we only use the dev and devtest sets, which contain 2009 sentences in total. We split those sentences into new train, dev and test splits, with 1509, 150 and 350 sentences respectively. For each sentence in the 102 languages (101 counted in FLoRes plus English, see Table 9), we collected three recordings by three different native speakers, imposing a balance in terms of sex ratio of at least 30/70%, when possible.

After this first recording step, each recording is evaluated by additional workers to assesses whether the recording corresponds to the input sentence. Invalid recordings are discarded,

¹The dataset is publicly available via TFDS at https://tensorflow.org/datasets/catalog/xtreme_s and Huggingface at https://hf.co/datasets/google/xtreme_s.

[†] Equal Contributions.

[‡] Equal Advising Contributions. Work done while Alexis and Siddharth were at Google.

²Note: For clarity we have renamed FLoRes "Chinese (Simp)" to "Mandarin Chinese" (code "cmn") and "Chinese (Trad)" to "Cantonese Chinese" (code "yue").

Table 1: Compare FLEURS to common public multilingual speech benchmarks.

Dataset	#Languages	Total Duration	Domains	Speech Type	Transcripts	Parallel text	Parallel speech
BABEL [13]	17	1k hours	Conversational	Spontaneous	Yes	No	No
CommonVoice [12]	93	15k hours	Open domain	Read	Yes	No	No
CMU Wilderness [15]	700	14k hours	Religion	Read	Yes	Yes	Yes
MLS [8]	8	50.5k hours	Audiobook	Read	Yes	No	No
CoVoST-2 [11]	22	2.9k hours	Open domain	Read	Yes	Yes	No
Voxlingua-107 [14]	107	6.6k hours	YouTube	Spontaneous	No	No	No
Europarl-ST [16]	6	500 hours	Parliament	Spontaneous	Yes	Yes	No
MuST-C [17]	9	385 hours	TED talks	Spontaneous	Yes	Yes	No
mTEDx [18]	9	1k hours	TED talks	Spontaneous	Yes	Yes	No
VoxPopuli [9]	24	400k hours	Parliament	Spontaneous	Partial	Partial	Partial
CVSS [19]	22	1.1k hours	Open domain	Read/Synthetic	Yes	Yes	Yes
FLEURS (this work)	102	1.4k hours	Wikipedia	Read	Yes	Yes	Yes

Table 2: A comparison of commonly used datasets for multilingual speech representation learning, ASR, Speech Translation and Speech-LangID. CommonVoice statistics as on 24th May 2022.

leaving us between zero and three recordings per sentence in the final dataset. In the first version of the dataset, about 21.5% of the sentences are missing because none of the three recordings were validated. We plan to fill these gaps in the future versions of the dataset. All recordings are kept as they-are, either from quiet or noisy environment, without any data augmentations (e.g. SpecAugment [23], speed perturbation [24], simulated reverberation [25], etc.). The speech sampling rate is 16kHz.

We then split the collected data into train, development (dev) and test sets with disjoint speakers between train/dev and test, with a target ratio of 7:1:2. All the segments are within 30 seconds.

2.2. Textual Data

For source transcripts, we reuse the transcripts produced by human translators from [20]. We maintain the English translated transcripts, which are useful for tasks such as multi-modal speech translation evaluations.

Among the various possible modeling units (e.g. character or sentence-pieces) for massively multilingual ASR, a universal vocabulary of characters requires the least resources to build, and better matches a common evaluation metric (i.e. character level error rate). We adopt it as our modeling and evaluation unit.

The variety of orthographic symbols of languages complicates the tokenization process. For example, Chinese text in both traditional and simplified scripts does not have space between tokens. Depending on the transcribers, Japanese and Korean may or may not contain space irregularly. To ease the pain for other researchers and facilitate apple-to-apple comparisons and reproducibility, we provide the tokenized versions of the sentences. We apply NFC and then FST normalization to each sentence, lower-case, normalize and remove punctuations. We also split words into characters, and define the token | as word boundaries. For each sentence, three versions are provided: the original raw transcript (SRC_RAW), the preprocessed version (SRC_NORM) and its character-based version (SRC_CHAR), which should be used for ASR.

2.3. Taxonomy and Statistics

There are multiple ways to categorize languages. The languages of FLEURS cover 17 language families (distribution shown in Figure 1), and 27 unique writing systems (distribution shown in Figure 2). By construction, FLoRes sentences also cover a




Figure 1: Distributions of language families in FLEURS (y-axis is the count).

diversity in domains, including nature, politics, science, travel, sports etc. Each sentence also has an associated integer "index" between 1 and 2009, which can be used to recover the n-way parallelism from one language to another (i.e. sentence i in language A is the translation of sentence i in language B). We grouped languages along with their geographical areas: Western European (WE), Eastern Europe (EE), Central-Asia/Middle-East/North-Africa (CMN), Sub-Saharan Africa (SSA), South Asia (SA), South-East Asia (SEA) and Chinese, Japanese, and Korean (CJK) languages. In Table 3, we present the basic statistics of FLEURS data per geographical groups; see Table 9 for a full list of languages.

Table 3: Statistics for speech and transcript data in FLEURS.

Data Statistics	WE	EE	CMN	SSA	SA	SEA	CJK	All
train speech hours	231h	134h	116h	237h	124h	112h	32h	987h
dev speech hours	29h	18h	14h	24h	16h	14h	4h	120h
test speech hours	68h	43h	33h	58h	37h	35h	9h	283h
train transcript tokens	1475k	772k	630k	1072k	699k	525k	405k	5578k
dev transcript tokens	184k	107k	75k	116k	93k	65k	51k	692k
test transcript tokens	443k	260k	181k	272k	210k	158k	116k	1640k




Figure 2: Distributions of writing systems in FLEURS (y-axis is the count).

3. Task Baselines

3.1. Experimental Setup

FLEURS enables evaluations for several core speech tasks. In this paper, we focus on speech recognition, speech language identification and speech-text retrieval. Training a giant model from scratch on the FLEURS dataset will easily overfit. Finetuning on limited supervised data from a model pre-trained on a vast amount of (unsupervised) data has achieved state-of-theart performances in recent studies [26, 22]. Consequently, we adopt the pre-training and fine-tuning methodology to build our massively multilingual baselines.

Multilingual Pre-trained Multilingual pre-trained models have achieved significant gains in a range of NLP and ASR tasks. We initialize fine-tuning from a 600M parameter wav2vec-BERT [22] model, which has been pre-trained on 429k hours unlabeled speech data in 51 languages pooling from VoxPopuli [9], MLS [8], CommonVoice [12] and BABEL [13]. Pre-training for this baseline (dubbed w2v-bert-51 (0.6B)) is *speech-only*.

Multilingual Multimodal Pre-trained In addition to pre-training on multilingual speech, pre-training on speech and text data simultaneously allows for transfer learning across the two modalities. We explore fine-tuning from a multilingual model which has been pre-trained with the same speech data, and with more than 10TiB of unlabeled text from 101 languages [27]. The pre-trained model capacity is also of 600M parameters (dubbed as mSLAM (0.6B)).

More information about the baselines, including fine-tuning details can be found in [10].

3.2. Seen Languages and Unseen Languages

The languages for which speech data was presented to pretraining are referred to as *seen* languages. There are 54 seen languages:

- WE: Catalan (ca), Croatian (hr), Danish (da), Dutch (nl), American English (en), Finnish (fi), French (fr), German (de), Greek (el), Hungarian (hu), Irish (ga), Italian (it), Latin American Spanish (es), Maltese (mt), Portuguese (pt), Swedish (sv), Welsh (cy)
- EE: Bulgarian (bg), Czech (cs), Estonian (et), Georgian (ka), Latvian (lv), Lithuanian (lt), Polish (pl), Romanian (ro), Russian (ru), Slovak (sk), Slovenian (sl), Ukrainian (uk)

- CMN: Arabic (ar), Kazakh (kk), Kyrgyz (ky), Mongolian (mn), Pashto (ps), Persian (fa), Tajik (tg), Turkish (tr)
- SSA: Ganda (lg), Swahili (sw), Zulu (zu)
- SA: Assamese (as), Bengali (bn), Hindi (hi), Oriya (or), Punjabi (pa), Tamil (ta), Telugu (te)
- SEA: Cebuano (ceb), Indonesian (id), Lao (lo), Thai (th), Vietnamese (vi)
- CJK: Cantonese (yue), Japanese (ja), Mandarin (cmn)

Languages which do not have any speech data presented to pre-training are referred to as *unseen* languages. There are 48 unseen languages:

- WE: Asturian (ast), Bosnian (bs), Galician (gl), Icelandic (is), Kabuverdianu (kea), Luxembourgish (lb), Norwegian (nb), Occitan (oc)
- EE: Armenian (hy), Belarusian (be), Macedonian (mk), Serbian (sr)
- CMN: Azerbaijani (az), Hebrew (he), Sorani-Kurdish (ckb), Uzbek (uz)
- SSA: Afrikaans(af), Amharic (am), Fula (ff), Hausa (ha), Igbo (ig), Kamba (kam), Lingala (ln), Luo (luo), Northern-Sotho (nso), Nyanja (ny), Oromo (om), Shona (sn), Somali (so), Umbundu (umb), Wolof (wo), Xhosa (xh), Yoruba (yo)
- SA: Gujarati (gu), Kannada (kn), Malayalam (ml), Marathi (mr), Nepali (ne), Sindhi (sd), Urdu (ur)
- SEA: Filipino (fil), Javanese (jv), Khmer (km), Malay (ms), Maori (mi), Burmese (my)
- CJK: Korean (ko)

Text in pre-training includes most of the above, except: as, ast, bg, bs, ff, he, hr, kam, kea, lb, lg, ln, lo, luo, nb, nso, oc, om, or, umb and wo

4. Downstream Tasks

4.1. Speech Recognition

We add two LSTM[28] layer to fine-tune our pre-trained models for ASR, using a CTC [29] loss. The baselines use a 6100character vocabulary built from SRC_NORM. We do not include meta information of language identification labels in modeling, and there is no language model used for hypothesis scoring. We fine-tune on all 102 locales, and report results for multilingual fine-tuning from both speech-only pre-trained and speech-text pre-trained models. Our finetuning parameters follow [10]. We evaluate fine-tuned ASR models for all locales in terms of % character error rate (CER). Experiments show that fine-tuning from multimodal pre-training is slightly worse than fine-tuning from speech-only pre-training (similar to the patterns observed in [10]), particularly lagging behind for the unseen languages. Most gains of multimodal pre-training are observed in WE, EE and CMN groups, suggesting that multimodal pre-training can be promising for certain languages, especially those where relatively large amounts of unlabeled speech, text and paired data were available during pre-training.

4.1.1. Correlation with Language Groups

We observe in Table 4 that results are much better on the Western European group (with 10.7 and 10.6 average CER) than on

other groups like Sub-Saharan African (15.6 and 16.4 average CER) or South Asian (17.4 and 19.2), which can be explained in part due to the larger amounts of unlabeled data in WE languages from MLS and VoxPopuli. Reducing the gaps across geographical groups is an important research direction for future work.

As presented in Table 4, fine-tuning from a speech-text pretrained model leads to 0.5% regression in CER as compared to fine-tuning from a speech-only pre-trained model. We observed most degradation in SA, SSA and CJK, three geographical groups known for mixing textual systems. For the model initialized from speech-only pre-training, EE and WE are the groups with the lowest average CERs, CMN, SSA, SA and SEA observe moderate CERs, while CJK gets the highest group CER. Further breaking down the distributions of error types, substitution errors are dominating across all the groups, which is a common error pattern in multilingual ASR [30], especially when no explicit language id information was incorporated. CJK languages are known for the vast number of homophones in speech, which adds difficulties in selecting the correct character without aid from language models. For SA, the group seeing the second highest substitution error rate, most substitutions come from Urdu. This is due to being essentially acoustically similar to Hindi, many Urdu utterances have been transliterated into Devanagari script. In other geographical groups, misrecognized characters from another writing system are observed less frequently. A potential solution is to include the language specific information and utilize language model fusion.

Table 4: *Speech recognition - Fleurs massively multilingual ASR baselines, reporting % CER* (\downarrow) *, by geographical group.*

Model	WE	EE	CMN	SSA	SA	SEA	CJK Avg.				
Speech recognition CER for all languages											
# languages	25	16	12	20	14	11	4 102				
w2v-bert-51 (0.6B) mSLAM (0.6B)	10.7 10.6	9.9 10.0	14.5 14.8	15.6 16.4	17.4 19.2	14.7 14.9	24.6 14.1 25.0 14.6				

4.1.2. Generalizability

Languages Seen by Pre-training A majority of the languages which have been seen in pre-training observed a test CER lower than average. While most of the languages with high CERs suffer from relatively high substitution error rates, ga and lo are also undermined by high insertion and deletion error rates.

Languages Unseen by Pre-training For languages which were not seen in pre-training, a large fraction observed a test CER worse than global average due to fine-tuning on very limited amount of supervised data. These observations align with previous findings in [7].

For the unseen languages which achieved a lower CER than average, 15 use Latin script based writing systems, while 3 use Cyrillic. Languages with Latin-scripts have a higher average CER than those using Cyrillic. Interestingly, unseen languages which use scripts other than Latin or Cyrillic can obtain good CER: ml_in (Malayalam), kn_in (Kannada), gu_in (Gujarati), ne_np (Devanagari), my_mm (Burmese), ckb_iq (Arabic). The success in recognizing unseen Malayalam, Kannada, Gujarati, Nepali can potentially be attributed to the Indian languages seen during pre-training (bn_in, te_in, pa_in, as_in, ta_in) from pre-

training.

4.2. Speech Language Identification

We fine-tune our models on Speech LangID classification following [10]. As shown in Table 5, fine-tuning from mSLAM obtains 73.3% macro-average accuracy on FLEURS LangID, while fine-tuning from w2v-bert-51 (0.6B) obtains 71.4% respectively. The group average accuracy decreases in the order of: CJK > WE > EE > CMN > SEA > SSA > SA. This could be due to the following reasons: (1) there are only four languages in the CJK group, which are relatively easy to distinguish from each other and from languages in the other groups; (2) Most of the data seen during pre-training is from Western European and Eastern European languages; (3) CMN, SEA, SSA and SA are geographical regions which are known for language diversity, but with limited amounts of publicly available pre-training data.

We note that on FLEURS-LangID, speakers are different among the train and dev/test sets. Avoiding over-fitting on speaker ID for the LangID task is essential for obtaining good performance.

Table 5: *Speech identification - FLEURS langID baselines, reporting % accuracy* (†), by geographical group.

Model	WE	EE	CMN	SSA	SA	SEA	CJK Avg.				
Speech identification accuracy for all languages											
# languages	25	16	12	20	14	11	4 102				
w2v-bert-51 (0.6B) mSLAM (0.6B)	85.3 84.6	78.4 81.3	72.9 75.9	59.1 62.2	52.0 51.7	65.7 73.4	89.7 71.4 87.8 73.3				

4.3. Cross-modal Speech-Text Retrieval

As user interactions with machines moves beyond typing textual queries, multi-modal retrieval of documents across the web is of growing interest [31, 32, 33]. The ability to build fixed-sized vector representations for queries be it speech, text or images, allows for building such content retrieval models [34, 35]. FLEURS is a rich multi-lingual, multi-modal, n-way parallel dataset which we hope will act as a benchmark to accelerate research in this field. FLEURS can act as a test-bench for various kinds of speech-text retrieval scenarios like speech-to-speech, text-to-text, speech-to-text, and text-to-speech retrieval along with testing cross-lingual and zero-shot capabilities.

As part of our multilingual baseline, we study the efficacy of pre-trained models towards learning fixed sized representations for both speech-to-text and text-to-speech retrieval. Given the multi-modal nature of the task, we only fine-tune our multilingual multi-modal pretrained model, i.e., mSLAM (0.6B), on the training set from all languages in FLEURS. Following [36, 37], cross-modal embeddings are trained using the additive margin softmax loss with in-batch negative sampling. We add bi-directional loss for retrieving speech given a text query and vice-versa [36]. We obtain embeddings for the normalized text (SRC_NORM) for all languages.

For evaluating the speech-to-text retrieval task, we report the % Precision at 1 (P@1) retrieval score of retrieving the correct text segment given a speech query from a database of indomain textual keys collected from the FLEURS test set. Similarly, for text-to-speech retrieval task, we report the P@1 retrieval score of retrieving any of the speakers who speaks the correct textual query. We report results for both retrieving text segments from speech queries and speech segments from textual queries. The summary tables for each geographical group can be found in Table 6 for both speech-to-text and text-to-speech retrieval. The detailed retrieval score for each language can be found in Table 8.

We observe an average P@1 of 76.9% for speech-to-text retrieval and a P@1 of 74.4% for text-to-speech retrieval. We observe that P@1 for seen languages in almost all geographical groups (except SA and SEA) is higher than their unseen counterparts, as is the case with speech recognition and language identification. In particular, we notice a steep degradation in the retrieval performance on CJK languages. We anticipate this to be the result of tokenization mismatch between the fine-tuning and the pre-training regime.

From Table 8, we can observe some interesting language specific peculiarities in the retrieval performance. For example, while Odia (or) is seen in speech, it is unseen in text since it is not present in the mc4 corpus [27] on which the mSLAM model was trained. This is exacerbated by Odia's unique script [38], which leads to the language being unrepresented in the tokenizer. On the other hand, Urdu (ur) is seen in the text pretraining but unseen in speech. This is interesting because Urdu performs considerably worse in Text-to-Speech retrieval compared to Speech-to-Text. We believe this is because Urdu is phonetically close to other SA languages like Hindi, consistent with our observations in Section 4.1.1, making it hard for the model to disambiguate speech without pre-training data in the speech modality.

Table 6: *Cross-modal Speech-Text Retrieval* - *FLEURS massively multilingual Speech-to-Text and Text-to-Speech retrieval baselines, reporting* % P@1 (\uparrow) *score, by geographical group.*

Task	WE	EE	CMN	SSA	SA	SEA	CJK Avg.		
P@1 for all languages									
# languages	25	16	12	20	14	11	4 102		
Speech-to-Text Retrieval Text-to-Speech Retrieval	87.6 83.7	91.1 88.3	79.4 77.1	83.9 83.5	67.7 61.4	54.8 55.4	4.7 76.9 4.7 74.4		

5. Conclusion

In this paper, we introduced FLEURS a new dataset for Few-shot Learning Evaluation of Universal Representations of Speech, in 102 languages. FLEURS is an n-way parallel speech dataset that can be used to evaluate speech recognition, translation, classification and retrieval methods. By building up baseline ASR, language identification and retrieval systems on it, we show that it is especially suited to evaluate data-efficient multilingual pre-trained representations of speech (and text). We hope this dataset will catalyze research in few-shot understanding in many languages, enabling progress towards building speech technologies for everyone.

6. References

- A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention is all you need," in *Proc. of NIPS*, 2017.
- [2] A. Gulati, J. Qin, C.-C. Chiu, N. Parmar, Y. Zhang, J. Yu, W. Han, S. Wang, Z. Zhang, Y. Wu, and R. Pang, "Con-

- former: Convolution-augmented transformer for speech recognition," Proc. of Interspeech, 2020.
- [3] A. Baevski, Y. Zhou, A. Mohamed, and M. Auli, "wav2vec 2.0: A framework for self-supervised learning of speech representations," in *Proc. of NeurIPS*, 2020.
- [4] A. Conneau, A. Baevski, R. Collobert, A. Mohamed, and M. Auli, "Unsupervised cross-lingual representation learning for speech recognition," in *Proc. of Interspeech*, 2021.
- [5] V. Panayotov, G. Chen, D. Povey, and S. Khudanpur, "Librispeech: an asr corpus based on public domain audio books," in *Proc. of ICASSP*. IEEE, 2015, pp. 5206–5210.
- [6] Q. Xu, A. Baevski, T. Likhomanenko, P. Tomasello, A. Conneau, R. Collobert, G. Synnaeve, and M. Auli, "Self-training and pretraining are complementary for speech recognition," in *Proc. of ICASSP*, 2020.
- [7] A. Babu, C. Wang, A. Tjandra, K. Lakhotia, Q. Xu, N. Goyal, K. Singh, P. von Platen, Y. Saraf, J. Pino, A. Baevski, A. Conneau, and M. Auli, "XLS-R: Self-supervised cross-lingual speech representation learning at scale," arXiv preprint arXiv:2111.09296, 2021.
- [8] V. Pratap, Q. Xu, A. Sriram, G. Synnaeve, and R. Collobert, "MLS: A large-scale multilingual dataset for speech research," in *Proc. of Interspeech*, 2020.
- [9] C. Wang, M. Riviere, A. Lee, A. Wu, C. Talnikar, D. Haziza, M. Williamson, J. Pino, and E. Dupoux, "VoxPopuli: A large-scale multilingual speech corpus for representation learning, semi-supervised learning and interpretation," in *Proc. of ACL*, 2021.
- [10] A. Bapna, C. Cherry, Y. Zhang, Y. Jia, M. Johnson, Y. Cheng, S. Khanuja, J. Riesa, and A. Conneau, "mSLAM: Massively multilingual joint pre-training for speech and text," *CoRR*, vol. abs/2202.01374, 2022. [Online]. Available: https://arxiv.org/abs/2202.01374
- [11] C. Wang, A. Wu, and J. Pino, "CoVoST 2 and massively multilingual speech-to-text translation," arXiv, 2020.
- [12] R. Ardila, M. Branson, K. Davis, M. Henretty, M. Kohler, J. Meyer, R. Morais, L. Saunders, F. M. Tyers, and G. Weber, "Common Voice: A massively-multilingual speech corpus," *Proc.* of *LREC*, 2020
- [13] M. J. F. Gales, K. M. Knill, A. Ragni, and S. P. Rath, "Speech recognition and keyword spotting for low-resource languages: Babel project research at cued," in n Spoken Language Technologies for Under-Resourced Languages, 2014.
- [14] J. Valk and T. Alumäe, "VoxLingua107: a dataset for spoken language recognition," in *Proc. of SLT*, 2020.
- [15] A. W. Black, "CMU wilderness multilingual speech dataset," in ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2019, pp. 5971– 5975.
- [16] J. Iranzo-Sánchez, J. A. Silvestre-Cerda, J. Jorge, N. Roselló, A. Giménez, A. Sanchis, J. Civera, and A. Juan, "Europarl-ST: A multilingual corpus for speech translation of parliamentary debates," in *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2020, pp. 8229–8233.
- [17] R. Cattoni, M. A. Di Gangi, L. Bentivogli, M. Negri, and M. Turchi, "Must-c: A multilingual corpus for end-to-end speech translation," *Computer Speech & Language*, vol. 66, p. 101155, 2021
- [18] E. Salesky, M. Wiesner, J. Bremerman, R. Cattoni, M. Negri, M. Turchi, D. W. Oard, and M. Post, "The multilingual TEDx corpus for speech recognition and translation," arXiv preprint arXiv:2102.01757, 2021.
- [19] Y. Jia, M. T. Ramanovich, Q. Wang, and H. Zen, "CVSS corpus and massively multilingual speech-to-speech translation," arXiv preprint arXiv:2201.03713, 2022.

- [20] N. Goyal, C. Gao, V. Chaudhary, P.-J. Chen, G. Wenzek, D. Ju, S. Krishnan, M. Ranzato, F. Guzman, and A. Fan, "The FLORES-101 evaluation benchmark for low-resource and multilingual machine translation," arXiv preprint arXiv:2106.03193, 2021.
- [21] A. Fan, S. Bhosale, H. Schwenk, Z. Ma, A. El-Kishky, S. Goyal, M. Baines, O. Celebi, G. Wenzek, V. Chaudhary et al., "Beyond english-centric multilingual machine translation," *Journal of Machine Learning Research*, vol. 22, no. 107, pp. 1–48, 2021.
- [22] Y.-A. Chung, Y. Zhang, W. Han, C.-C. Chiu, J. Qin, R. Pang, and Y. Wu, "W2v-BERT: Combining contrastive learning and masked language modeling for self-supervised speech pre-training," 2021.
- [23] D. S. Park, W. Chan, Y. Zhang, C.-C. Chiu, B. Zoph, E. D. Cubuk, and Q. V. Le, "SpecAugment: A simple data augmentation method for automatic speech recognition," *Proc. Interspeech* 2019, pp. 2613–2617, 2019.
- [24] T. Ko, V. Peddinti, D. Povey, and S. Khudanpur, "Audio augmentation for speech recognition." in *INTERSPEECH*. ISCA, 2015, pp. 3586–3589. [Online]. Available: http://dblp. uni-trier.de/db/conf/interspeech/interspeech2015.html#KoPPK15
- [25] T. Ko, V. Peddinti, D. Povey, M. L. Seltzer, and S. Khudanpur, "A study on data augmentation of reverberant speech for robust speech recognition," in 2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2017, pp. 5220–5224.
- [26] Y. Zhang, D. S. Park, W. Han, J. Qin, A. Gulati, J. Shor, A. Jansen, Y. Xu, Y. Huang, S. Wang, Z. Zhou, B. Li, M. Ma, W. Chan, J. Yu, Y. Wang, L. Cao, K. C. Sim, B. Ramabhadran, T. N. Sainath, F. Beaufays, Z. Chen, Q. V. Le, C.-C. Chiu, R. Pang, and Y. Wu, "BigSSL: Exploring the frontier of large-scale semi-supervised learning for automatic speech recognition," arXiv, 2021.
- [27] L. Xue, N. Constant, A. Roberts, M. Kale, R. Al-Rfou, A. Sid-dhant, A. Barua, and C. Raffel, "mT5: A massively multilingual pre-trained text-to-text transformer," arXiv preprint arXiv:2010.11934, 2020.
- [28] S. Hochreiter and J. Schmidhuber, "Long short-term memory," Neural Computation, vol. 9, no. 8, pp. 1735–1780, 1997.
- [29] A. Graves, S. Fernández, F. Gomez, and J. Schmidhuber, "Connectionist temporal classification: labelling unsegmented sequence data with recurrent neural networks," in *Proceedings of the 23rd international conference on Machine learning*, 2006, pp. 369–376.
- [30] X. Li, S. Dalmia, J. Li, M. Lee, P. Littell, J. Yao, A. Anastasopoulos, D. R. Mortensen, G. Neubig, A. W. Black et al., "Universal phone recognition with a multilingual allophone system," in ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2020, pp. 8249–8253.
- [31] M. Witbrock and A. G. Hauptmann, "Speech recognition and information retrieval: Experiments in retrieving spoken documents," in *Proceedings of the DARPA speech recognition work*shop, vol. 97, 1997.
- [32] S.-y. Ishikawa, T. Ikeda, K. Miki, F. Adachi, R. Isotani, K.-I. Iso, and A. Okumura, "Speech-activated text retrieval system for multimodal cellular phones," in 2004 IEEE International Conference on Acoustics, Speech, and Signal Processing, vol. 1. IEEE, 2004, pp. I–453.
- [33] L.-s. Lee, J. Glass, H.-y. Lee, and C.-a. Chan, "Spoken content retrieval—beyond cascading speech recognition with text retrieval," *IEEE/ACM Transactions on Audio, Speech, and Language Pro*cessing, vol. 23, no. 9, pp. 1389–1420, 2015.
- [34] A. Jain, M. Guo, K. Srinivasan, T. Chen, S. Kudugunta, C. Jia, Y. Yang, and J. Baldridge, "MURAL: Multimodal, multitask representations across languages," in *Findings of the Association for Computational Linguistics: EMNLP 2021*. Punta Cana, Dominican Republic: Association for Computational Linguistics, Nov. 2021, pp. 3449–3463. [Online]. Available: https://aclanthology.org/2021.findings-emnlp.293

- [35] P.-A. Duquenne, H. Gong, and H. Schwenk, "Multimodal and multilingual embeddings for large-scale speech mining," Advances in Neural Information Processing Systems, vol. 34, 2021.
- [36] Y. Yang, G. H. Ábrego, S. Yuan, M. Guo, Q. Shen, D. Cer, Y.-H. Sung, B. Strope, and R. Kurzweil, "Improving multilingual sentence embedding using bi-directional dual encoder with additive margin softmax," in *IJCAI*, 2019.
- [37] F. Feng, Y. Yang, D. Cer, N. Arivazhagan, and W. Wang, "Language-agnostic BERT sentence embedding," in *Proceedings* of ACL. Dublin, Ireland: Association for Computational Linguistics, May 2022, pp. 878–891. [Online]. Available: https://aclanthology.org/2022.acl-long.62
- [38] R. K. Mohapatra, T. K. Mishra, S. Panda, and B. Majhi, "Ohcs: A database for handwritten atomic odia character recognition," in 2015 Fifth National Conference on Computer Vision, Pattern Recognition, Image Processing and Graphics (NCVPRIPG). IEEE, 2015, pp. 1–4.
- [39] D. van Esch, T. Lucassen, S. Ruder, I. Caswell, and C. E. Rivera, "Writing system and speaker metadata for 2,800+ language varieties," in *Proceedings of LREC*, 2022.

Table 7: FLEURS full ASR results, reporting % CER (\downarrow), for all 102 languages.

								West	ern Eur	opean							
Language		ast	bs	ca	hr	da	nl	en	fi	fr	gl	de		el	hu	is	ga
w2v-bert-51 (0.6B mSLAM (0.6B))	8.7	5.8 5.1		9.3 8.5	11.3 14.0	6.0 6.8	17.2 16.3	3.0 3.4	9.6 9.7	8.6 8.7	8.0 5.7	11 12			11.9 12.8	39.5 40.5
					We	estern E	uropean	(WE)						Easte	ern Euro	pean	
Language		it	kea	a lt	o mt	nb	oc	pt	es	sv	С	y	hy	be	bg	cs	et
w2v-bert-51 (0.6B mSLAM (0.6B)	3)	2.6					11.7 12.7	4.2 4.4	3.7 3.3	7.6 7.8	11. 12.		7.2	9.1 7.5	4.8 5.2	10.3 9.2	3.1 3.5
	ī					Eastern	Europea	an (EE)							Central-	Asia an	d
Language	1	ka	lv	lt	mk	pl	ro	ru	sr	sk	sl		uk	ar	az	he	k
w2v-bert-51 (0.6B) mSLAM (0.6B)		30.7 31.0	4.4 4.5	12.8 11.6	11.8 9.8	5.0 6.3	8.0 8.4	5.6 6.6	11.6 12.2	4.9 4.8	7.9 10.3	21 21		10.5 11.0	12.7 15.9	37.2 42.5	6. 5.
			Mi	ddle-Eas	t and No	th-Afric	a (CMN	()					Sub-S	aharan	Africa		
anguage	ŀ	су	mn	ps	fa	ckb	tg	tr	uz	af	an	1	ff	lg	ha	ig	; k
/2v-bert-51 (0.6B) nSLAM (0.6B)			15.2 16.1	20.4 21.1	15.7 10.0	15.1 15.0	7.1 7.6	8.5 9.7	16.8 15.5	9.5 11.9	17.2 17.8		7.8 7.5	12.4 12.9	9.8 10.5	18.1 18.7	
1						5	Sub-Saha	aran Afr	ica (SSA	A)						So	uth-A
anguage	į	ln	luo	nso	ny	om	sn	so	sw	umb	W	/O	xh	yo) zı	1 8	as
2v-bert-51 (0.6B) SLAM (0.6B)	6		7.0 7.4	11.7 11.9		21.7 22.6	16.6 17.6	21.3 23.4	19.4 20.2	13.1 14.0	17 18		23.9 25.1	23.3 23.2			
							South-A	sia (SA)						S	outh-Ea	st Asi
Language	- 1	gu	hi	kn	ml	mr	ne	or	pa	sd		ta	te	u	r m	y ce	b
v2v-bert-51 (0.6B) nSLAM (0.6B)).3).6	12.4 15.2	7.0 9.6	8.6 12.2	14.8 18.9	13.0 14.8	19.2 20.7	13.6 15.2	16.0 20.8	11 13		12.0 12.3	82.9 83.			
					South-Ea	ıst Asia	(SEA)			-		C	JK				
Language		id	jv	v km	ı lo	ms	mi	th	ı v	i y	ue	cmn	j	ja	ko	All	
w2v-bert-51 (0.6E mSLAM (0.6B)	3)	5.2				8.6 7.2	10.3 11.2	18.6 20.1			7.0 9.8	22.2 23.1	37. 39.			14.1 14.6	

Table 8: FLEURS Speech-to-Text and Text-to-Speech retrieval results, reporting % P@1 (\uparrow), for all 102 languages.

							Wes	stern Eu	ropean						
Language	ast	bs	ca	hr	da	nl	en	fi	fr	gl	d	e e	l hu	is	ga
Speech-to-Text Retrieval Text-to-Speech Retrieval	90.1 83.5	95.5 95.1	93.2 87.0	98.0 95.3	94.1 90.1	95.3 87.1	96.0 94.4	93.0 90.6	90.7 80.6	90.9 81.0	91. 81.			71.7 67.4	55.1 56.7
				W	estern Eu	ropean (WE)					Е	astern Euro	pean	
Language	it	kea	lb	mt	nb	oc	pt	es	sv	cy	h	y b	e bg	cs	et
Speech-to-Text Retrieval Text-to-Speech Retrieval	93.5 86.0	95.4 95.6	80.5 78.8	92.7 89.0	91.9 85.7	77.4 85.2	91.9 88.9	69.6 61.5	94.2 90.4	82.3 79.6	50. 52.			98.1 96.3	95.6 94.1
					Easter	n Europe	an (EE)						Central-	Asia and	i
Language	ka	lv	lt	mk	pl	ro	ru	sr	sk	sl	u	k a	r az	he	kk
Speech-to-Text Retrieval Text-to-Speech Retrieval	70.5 66.9	97.4 95.7	96.8 94.0	96.1 92.7	95.8 92.0	92.0 86.4	93.2 89.2	97.7 95.6	97.6 95.6	97.4 94.8	93. 88.			64.0 71.3	88.7 89.7
		l	Middle-E	ast and I	North-Afr	rica (CM	N)		1		St	ıb-Sahara	ın Africa		
Language	ky	mn	ps	fa	ckb	tg	tr	uz	af	am	1	f 1	g ha	ig	kam
Speech-to-Text Retrieval Text-to-Speech Retrieval	84.3 78.6	70.7 70.4	84.8 78.7	85.4 85.5	80.8 76.9	76.3 70.7	84.5 81.0	67.6 63.5	90.1 86.7	34.1 40.3	81. 65.			85.8 90.2	89.7 90.7
		Sub-Saharan Africa (SSA)												Sout	h-Asia
Language	ln	luo	nso	ny	om	sn	so	sw	umb	wo	х	h y	o zu	as	bn
Speech-to-Text Retrieval Text-to-Speech Retrieval	91.2 95.2	91.0 88.3	80.8 83.4	85.5 84.9	92.7 90.2	84.1 79.1	68.7 69.0	91.2 91.2	77.3 83.6	90.6 90.8	90. 88.			81.5 78.8	83.5 77.6
						South-	Asia (SA	<u>(</u>)					Sou	th-East	Asia
Language	gu	hi	kn	ml	mr	ne	or	pa	ı sd	ta	ı	te i	ır my	ceb	fil
Speech-to-Text Retrieval Text-to-Speech Retrieval	77.0	78.0 66.0	69.0 67.1	62.3 57.1	69.8 70.0	66.1 62.4	15.7 18.6	70.6 70.2						79.8 75.6	73.1 69.5
				Sout	h-East A	sia (SEA	.)				CJk				
Language		id	jv	km	lo	ms	mi	th	vi	yue	cmn	ja	ko All	l	
Speech-to-Text Retr Text-to-Speech Retr		79.6 75.3	78.0 72.5	42.1 49.3	37.0 47.7	77.7 73.7	64.7 74.8	3.2 3.8	64.5 64.4	2.4 2.7	5.4 5.1		5.2 76.9 2.9 74.4		_

Table 9: Characteristics of the 102 languages in FLEURS, with their ISO codes, language families, estimated number of speakers in millions (#S) from [39]. Languages are grouped geographically in Western Europe (WE), Eastern Europe (EE), Central-Asia/Middle-East/North-Africa (CMN), Sub-Saharan Africa (SSA), South Asia (SA), South-East Asia (SEA) and CJK languages. Note that we make some minor changes compared to FLoRes, renaming "Chinese (Simp)" to "Mandarin Chinese" with code "cmn" (not "zho") and renaming "Chinese (Trad)" to "Cantonese Chinese" with code "yue" (not "zho").

Idx	Language	ISO 639-3	ISO 639-1	Family	Group	#S
1	Afrikaans	afr	af	Indo-European	SSA	17
2	Amharic	amh	am	Afro-Asiatic	SSA	22
3	Arabic	ara	ar	Afro-Asiatic	CMN	180
4	Armenian	hye	hy	Indo-European	EE	6
5	Assamese	asm	as	Indo-European	SA	13
6	Asturian	ast	-	Indo-European	WE	0.6
7	Azerbaijani	azj	az	Turkic	CMN	18
8	Belarusian	bel	be	Indo-European	EE	3
9	Bengali	ben	bn	Indo-European	SA	260
10	Bosnian	bos	bs	Indo-European	WE	9
11	Bulgarian	bul	bg	Indo-European	EE	7
12	Burmese	mya	my	Sino-Tibetan	SEA	33
13	Cantonese Chinese	yue	-	Sino-Tibetan	CJK	920
14	Catalan	cat	ca	Indo-European	WE	4
15	Cebuano	ceb	_	Austronesian	SEA	16
16	Croatian	hrv	hr	Indo-European	WE	4
17	Czech	ces	cs	Indo-European	EE	10
18	Danish	dan	da	Indo-European	WE	5
19	Dutch	nld	nl	Indo-European	WE	21
20	English	eng	en	Indo-European	WE	550
21	Estonian	est	et	Uralic	EE	1
22	Filipino (Tagalog)	tgl	tg	Austronesian	SEA	22
23	Finnish	fin	fi	Uralic	WE	5
24	French	fra	fr	Indo-European	WE	280
25	Fula	ful	ff	Atlantic-Congo	SSA	12
26	Galician	glg	gl	Indo-European	WE	2
27	Ganda	lug	lg	Atlantic-Congo	SSA	4
28	Georgian	kat	ka	Kartvelian	EE	4
29	German	deu	de	Indo-European	WE	83
30	Greek	ell	el	Indo-European	WE	13
31	Gujarati	guj	gu	Indo-European	SA	56
32	Hausa	hau	ha	Afro-Asiatic	SSA	70
33	Hebrew	heb	he	Afro-Asiatic	CMN	4
34	Hindi	hin	hi	Indo-European	SA	320
35	Hungarian	hun	hu	Uralic	WE	13
36	Icelandic	isl	is	Indo-European	WE	0.3
37	Igbo	ibo	ig	Atlantic-Congo	SSA	18
38	Indonesian	ind	id	Austronesian	SEA	200
39	Irish	gle	ga	Indo-European	WE	0.2
40	Italian	ita	it	Indo-European	WE	61
41	Japanese		ja	Japonic	CJK	130
42	Javanese	jpn jav	jv	Austronesian	SEA	85
43	Kabuverdianu	kea	J* -	Indo-European	WE	0.9
44	Kamba	kam	_	Atlantic-Congo	SSA	4
45	Kannada	kan	kn	Dravidian	SA	43
46	Kazakh	kaz	kk	Turkic	CMN	11
47	Khmer	khm	km	Austro-Asiatic	SEA	16
48	Korean	kor	ko	Koreanic	CJK	52
49	Kyrgyz	kir	ky	Turkic	CMN	8
50	Lao	lao	lo	Kra-Dai	SEA	20
51	Latvian	lav	lv	Indo-European	EE	20
51	Latvian	iav	1 V	muo-European		4

Idx	Language	ISO 639-3	ISO 639-1	Family	Group	#S
52	Lingala	lin	ln	Atlantic-Congo	SSA	15
53	Lithuanian	lit	lt	Indo-European	EE	2
54	Luo	luo	-	Nilo-Saharan	SSA	4
55	Luxembourgish	ltz	lb	Indo-European	WE	0.4
56	Macedonian	mkd	mk	Indo-European	EE	1
57	Malay	msa	ms	Austronesian	SEA	80
58	Malayalam	mal	ml	Dravidian	SA	77
59	Maltese	mlt	mt	Afro-Asiatic	WE	0.5
60	Mandarin Chinese	cmn	-	Sino-Tibetan	CJK	80
61	Maori	mri	mi	Austronesian	SEA	0.2
62	Marathi	mar	mr	Indo-European	SA	83
63	Mongolian	mon	mn	Mongolic	CMN	5
64	Nepali	npi	ne	Indo-European	SA	16
65	Northern Sotho	nso	-	Atlantic-Congo	SSA	14
66	Norwegian	nob	nb	Indo-European	WE	5
67	Nyanja	nya	ny	Atlantic-Congo	SSA	12
68	Occitan	oci	oc	Indo-European	WE	0.5
69	Oriya	ory	or	Indo-European	SA	35
70	Oromo	orm	om	Afro-Asiatic	SSA	24
71	Pashto	pus	ps	Indo-European	CMN	13
72	Persian	fas	fa	Indo-European	CMN	40
73	Polish	pol	pl	Indo-European	EE	38
74	Portuguese (Brazil)	por	pt	Indo-European	WE	220
75	Punjabi	pan	pa	Indo-European	SA	113
76	Romanian	ron	ro	Indo-European	EE	19
77	Russian	rus	ru	Indo-European	EE	150
78	Serbian	srp	sr	Indo-European	EE	6
79	Shona	sna	sn	Atlantic-Congo	SSA	9
80	Sindhi	snd	sd	Indo-European	SA	68
81	Slovak	slk	sk	Indo-European	EE	4
82	Slovenian	slv	sl	Indo-European	EE	2
83	Somali	som	so	Afro-Asiatic	SSA	24
84	Sorani Kurdish	ckb	-	Indo-European	CMN	7
85	Spanish	spa	es	Indo-European	WE	490
86	Swahili	swh	sw	Atlantic-Congo	SSA	24
87	Swedish	swe	sv	Indo-European	WE	8
88	Tajik	tgk	tg	Indo-European	CMN	8
89	Tamil	tam	ta	Dravidian	SA	76
90	Telugu	tel	te	Dravidian	SA	82
91	Thai	tha	th	Kra-Dai	SEA	20
92	Turkish	tur	tr	Turkic	CMN	82
93	Ukrainian	ukr	uk	Indo-European	EE	32
94	Umbundu	umb	-	Atlantic-Congo	SSA	6
95	Urdu	urd	ur	Indo-European	SA	120
96	Uzbek	uzb	uz	Turkic	CMN	57
97	Vietnamese	vie	vi	Austro-Asiatic	SEA	96
98	Welsh	cym	cy	Indo-European	WE	0.7
99	Wolof	wol	wo	Atlantic-Congo	SSA	4
100	Xhosa	xho	xh	Atlantic-Congo	SSA	19
101	Yoruba	yor	yo	Atlantic-Congo	SSA	21
102	Zulu	zul	zu	Atlantic-Congo	SSA	11