# Position Labels for Self-Supervised Vision Transformer

Zhemin Zhang<sup>1</sup>, Xun Gong<sup>1</sup>, Jinyi Wu<sup>1</sup>

<sup>1</sup>Southwest Jiaotong University, China zheminzhang@my.swjtu.edu.cn

#### Abstract

Position encoding is important for vision transformer (ViT) to capture the spatial structure of the input image. General efficacy has been proven in ViT. In our work we propose to train ViT to recognize the 2D position encoding of patches of the input image, this apparently simple task actually yields a meaningful self-supervisory task. Based on previous work on ViT position encoding, we propose two position labels dedicated to 2D images including absolute position and relative position. Our position labels can be easily plugged into transformer, combined with the various current ViT variants. It can work in two ways: 1.As an auxiliary training target for vanilla ViT (e.g., ViT-B [Dosovitskiy et al., 2020] and Swin-B [Liu et al., 2021)) to improve model performance. 2. Combine the self-supervised ViT (e.g., MAE [He et al., 2021) to provide a more powerful self-supervised signal for semantic feature learning. Experiments demonstrate that solely due to the proposed selfsupervised methods. Swin-B and ViT-B obtained improvements of 1.9% (top-1 Acc) and 5.6% (top-1 Acc) on Mini-ImageNet, respectively.

### 1 Introduction

Vision transformers (ViT) [Dosovitskiy *et al.*, 2020; Zhao *et al.*, 2020] have recently emerged as an alternative to convolutional neural networks (CNNs) for computer vision. The design of ViT is inspired by the transformer of natural language processing (NLP), split an image into patches and provide the sequence of linear embeddings of these patches as an input to a Transformer [Touvron *et al.*, 2021]. Image patches are treated the same way as tokens (words) in NLP. The core of transformer is self-attention [Vaswani *et al.*, 2017], which is able to model long-range dependencies in the data. However, Self-attention is fully symmetric, it cannot capture the ordering of input tokens, which is undesirable for modeling structured data. Therefore, incorporating position encoding is especially important for ViT.

There are mainly two classes of methods to add position information to the ViT's encoded patches. One is absolute and the other is relative. Absolute position encoding [Gehring



Figure 1: Our absolute position labels combined with ViT-B. We split an image into fixed-size patches, each corresponding to an absolute position, and feed the sequence of image patches to a standard ViT encoder. The full set of encoded patches output by the ViT is processed by a lightweight MLP block that outputs the 2D absolute position corresponding to each image patch. After training, the MLP block is discarded.

et al., 2017; Li et al., 2018]: each absolute position of the input token sequence from 1 to maximum sequence length has a separate encoding vector. The encoding vector is then combined with the input tokens, usually element-wise add, to incorporate positional information into the ViT's input tokens. On the other hand, relative position encoding [Dai et al., 2019; Shaw et al., 2018] calculates the relative position between tokens based on the absolute position of each input token, and establishes a look-up table. Each relative position corresponds to a learnable parameter of the table to learn the pairwise relations of tokens. The parameters in the table interact with the self-attention weights. Relative position encoding has been verified to be effective in ViT [Wu et al., 2021]. Different from the previous explicit incorporation of position information, we use the position information as a supervision signal for ViT self-supervised training, making each encoded patch implicitly contains its position information, as shown in Figure 1.

In this paper, we seek to expand the applicability of position information to serve as a supervised signal for selfsupervised training of ViT. Based on the position information, we propose a new ViT self-supervised loss function, namely position loss, which allows each token to implicitly contain its position information. Specifically, we split an image into fixed-size patches and feed the sequence of image patches to a standard ViT. The full set of encoded patches output by the ViT is processed by a lightweight MLP block that outputs the position label corresponding to each image patch. Based on previous research on ViT position encoding, we propose two position labels for ViT: absolute position labels and relative position labels. In Section 3, we illustrate in detail how to apply these two position labels to ViT and the differences between them.

Our position loss can work in two ways: 1. Combined with vanilla ViT (e.g., ViT-B [Dosovitskiy et al., 2020] and swin transformer [Liu et al., 2021]), as an auxiliary training task for the model. The ViT is trained under the joint supervision of the softmax loss and position loss, with a hyper parameter to balance the two supervision signals. We find that with joint supervision, the classification performance of ViT is significantly improved. 2. Combine the self-supervised ViT, e.g., MAE [He et al., 2021]. MAE masks random patches from the input image and reconstructs the missing patches in the pixel space. Our position loss can be combined with MAE, allowing the model to not only reconstructs the pixels of the missing patches, but also outputs the position information of the missing patches, providing a more powerful self-supervised signal for semantic feature learning. Our contributions can be summarized as:

- We propose two position labels for ViT self-supervised learning, absolute position labels and relative position labels. The position labels are simple and can be easily plugged into self-attention layers.
- We introduce efficient implementations for each of the two position labels, considering both efficiency and generalizability, enabling ViT to effectively utilize position supervision signals.
- Our position labels can be combined with vanilla ViT and self-supervised ViT. Experiments show that, without adjusting any hyperparameters and settings, Swin-B and ViT-B obtained improvements of 1.9% (top-1 Acc) and 5.6% (top-1 Acc) on Mini-ImageNet, respectively.

# 2 Related Work

# 2.1 Self-Supervised ViT

In pioneering works [Chen *et al.*, 2020; He *et al.*, 2021], training self-supervised Transformers for vision problems in general follows the masked auto-encoding paradigm in NLP [Devlin *et al.*, 2018; Wang *et al.*, 2019]. iGPT [Chen *et al.*, 2020] masks and reconstructs pixels. MAE [He *et al.*, 2021] masks a high proportion of the input image patches and reconstruct the missing patches. DINO [Caron *et al.*, 2021] studies the importance of momentum encoder [He *et al.*, 2020], multicrop training [Caron *et al.*, 2020], and the use of small patches with ViTs, to design a simple self-supervised approach that can be interpreted as a form of knowledge distillation with no labels. [Chen *et al.*, 2021] focuses on training Transformers in the contrastive/Siamese paradigm, in which the loss is not defined for reconstructing the inputs. In this work, we propose a novel self-supervised learning signal for ViT, named position labels.

### 2.2 Position Encoding

**Absolute Position Encoding.** Since transformer contains no recurrence and no convolution, in order for the model to make use of the order of the sequence, we need to inject some information about the position of the tokens. The original self-attention considers the absolute position, and add the absolute positional encodings to the input token embedding by element-wise addition [Vaswani *et al.*, 2017]. There are several choices of absolute positional encodings, such as Sinusoidal position [Vaswani *et al.*, 2017] fixed encoding using sine and cosine functions sampling at different frequencies and [Gehring *et al.*, 2017] the learnable encoding via training parameters.

Relative Position Encoding. Relative position encoding is proposed firstly by [Shaw et al., 2018], extending the selfattention mechanism to efficiently consider representations of the relative positions, where relative position encodings are added into the self-attention weight calculation. [Dai et al., 2019] proposed a novel positional encoding scheme with the prior of the sinusoid matrix and more learnable parameters, which not only enables capturing longer-term dependency, but also resolves the context fragmentation problem. [Wu et al., 2021] proposes new relative position encoding methods dedicated to 2D images, called image RPE (iRPE). iRPE considers directional relative distance modeling as well as the interactions between queries and relative position embeddings in self-attention mechanism. [Ramachandran et al., 2019] proposed 2D relative position encoding that computes and concatenates separate encodings of each dimension. [Srinivas et al., 2021] proposes to incorporate the position information in the convolutional feature map into ViT by concatenating the convolutional feature map with a set of feature maps produced via the self-attentive mechanism.

Unlike the previous explicit combination of position information, we use the position information as a supervised signal for ViT self-supervised training, such that each encoded patch implicitly contains its position information.

# 3 Method

#### 3.1 Absolute position label

Here we take ViT-B [Dosovitskiy *et al.*, 2020] as an example, other ViT variants (e.g., Swin-B [Liu *et al.*, 2021]) are calculated in the same way. An overview of the absolute position as an auxiliary training task for classification is depicted in Figure 1.

We split an image  $x \in \mathbb{R}^{H \times W \times C}$  into fixed-size patches  $x_m \in \mathbb{R}^{N \times (m^2 \cdot C)}$ , where (H, W) is the resolution of the original image, *C* is the number of channels, (m, m) is the resolution of each image patch, and  $N = HW/m^2$  is the number of generated patches.  $x_{class}$  is the classification token, whose state at the output of the ViT serves as the image representation  $z_{class}$  (Eq.2). In ViT-B, as an alternative to raw image patches, the input sequence can be formed from feature



Figure 2: Our relative position labels combined with ViT-B. For the breViTy of the image, here we take the relative position label of the central image patch of the input image as an example, and the rest of the image patches are calculated in the same way. We combine the center encoded patch with other encoded patches pairwise, input a lightweight MLP block, and output the 2D relative position between the center image patch and other image patches.

maps of a CNN [He *et al.*, 2016], the patch embedding projection  $\mathsf{E} \in \mathbb{R}^{(m^2 \cdot C) \times D}$  is applied to patches extracted from a CNN feature map. The linear projection  $\mathsf{E}$  maps x to D dimensions. We refer to the output y of this projection as the patch embeddings:

$$[\mathsf{y}_{class};\mathsf{y}_1;\mathsf{y}_2;\cdots;\mathsf{y}_N] = \left[\mathsf{x}_{class};\mathsf{x}_m^1\mathsf{E};\mathsf{x}_m^2\mathsf{E};\cdots;\mathsf{x}_m^N\mathsf{E}\right] (1)$$

Feed the sequence of patch embeddings to a standard ViT encoder:

$$[\mathsf{z}_{class};\mathsf{z}_1;\mathsf{z}_2;\cdots;\mathsf{z}_N] = \bigvee_{\theta}^{\mathsf{iT}} ([\mathsf{y}_{class};\mathsf{y}_1;\mathsf{y}_2;\cdots;\mathsf{y}_N]) \quad (2)$$

where  $z_{class}$  is the image representation, which is input to the classifier to calculate the classification loss.  $\theta$  denotes the trainable parameters of ViT.  $z_i = (z_1, \dots, z_N)$  is the representation of the image patch  $x_m^i = (x_m^1, \dots, x_m^N)$ . We use a trainable lightweight MLP block (shown in Figure 1) to project  $z_i = (z_1, \dots, z_N)$  as a 2D vector:

$$\begin{bmatrix} \stackrel{\wedge}{\mathbf{p}}_1; \stackrel{\wedge}{\mathbf{p}}_2; \cdots; \stackrel{\wedge}{\mathbf{p}}_N \end{bmatrix} = \mathsf{MLP}\left( [\mathsf{z}_1; \mathsf{z}_2; \cdots \mathsf{z}_N] \right)$$
(3)

The optimization goal for absolute position label is:

$$L_p = \underset{\theta}{\operatorname{arg\,min}} \left( \frac{1}{N} \sum_{i=1}^{N} \mathsf{MSE}(\stackrel{\wedge}{\mathsf{p}}_i, \mathsf{p}_i) \right) \tag{4}$$

each  $x_m^i$  corresponds to a 2D absolute position label  $p_i = (p_1, \dots, p_N)$ , as shown in Figure 1  $(p_1 = (0, 0), \dots, p_9 = (2, 2))$ . MSE denotes mean squared error.

#### **3.2 Relative position label**

Besides the absolute position of each input image patch, we also consider the relative positional relationship between patches. Relative position methods encode the relative distance between input patches and learn the pairwise relationships of patches. We encode the relative position between the input image patches  $x_m^i$  and  $x_m^j$  into a vector  $\mathbf{p}_{ij}^r$ . To establish the pairwise positional relationship between the output image patch embeddings, we intercept half of  $z_i$ , named  $\frac{1}{2}z_i$ , and combine them in pairs, as shown in Figure 2:

$$\mathbf{z}_{ij} = concat\left(\frac{1}{2}\mathbf{z}_i, \frac{1}{2}\mathbf{z}_j\right) \tag{5}$$

where the *concat* operation concatenates the two embeddings. Same as absolute position labels, feed  $z_{ij}$  to a lightweight MLP block:

$$\hat{\mathsf{P}}_{ij}^r = \mathsf{MLP}\left(\mathsf{z}_{ij}\right) \tag{6}$$

where  $P_{ij}^{n}$  denotes the 2D relative position label between  $x_m^i$  and  $x_m^j$  output by the model. The optimization goal of the relative position label is:

$$L_p^r = \operatorname*{arg\,min}_{\theta} \left( \frac{1}{N^2} \sum_{i=1}^N \sum_{j=1}^N \mathsf{MSE}(\stackrel{\wedge}{\mathsf{P}}_{ij}^r, \mathsf{p}_{ij}^r) \right)$$
(7)

### 3.3 Position label joint MAE

The above two position labels can not only be used as auxiliary supervision signals for classification tasks, but also can be used for self-supervised training of ViT, which can be combined with various current ViT self-supervised methods to obtain more powerful self-supervised signals. In this section, we illustrate our position labels combined with MAE, as shown in Figure 3. The output of the decoder is not only used for MAE to reconstruct the image, but also input to the encoder to output the absolute position corresponding to each reconstructed image patch. The two encoders in Figure 3 share parameters. The MAE decoder and our position supervision signal are only used during pre-training.

#### **4** Experiments

In this section, we first describe our experiment dataset and experiment settings, then conduct an ablation experiment to



Figure 3: Our absolute position labels combined with MAE. The output of the decoder is not only used for MAE to reconstruct the image, but also input to the encoder to output the absolute position corresponding to each reconstructed image patch. The two encoders in the figure share parameters. This illustration was inspired by MAE.

demonstrate the position encoding can be used in joint with the proposed position label. Finally, we combine our approach with some of the current most popular ViTs to demonstrate the effectiveness of position labels.

Table 1: Top-1 and Top-5 accuracies (%) for ViT-B model, on Mini-ImageNet datasets. **PE**: position encoding term of ViT; **APL**: the proposed absolute position label; **RPL**: the proposed relative position label.

Method	Top-1 acc.	Top-5 acc.
ViT-B + PE (Baseline)	58.28	79.57
ViT-B	56.89	76.32
ViT-B + APL	63.27	80.86
ViT-B + RPL	63.16	80.33
ViT-B + PE + RPL	63.97	83.06
ViT-B + PE + APL	64.43	83.73

### 4.1 Experiment Settings

**Dataset.** We evaluate the performance of our method using the top-1 and top-5 accuracy of the Mini-ImageNet [Krizhevsky *et al.*, 2012]. Mini-ImageNet contains a total of 60,000 images from 100 classes.

**Implementation details**. We use the PyTorch toolbox [Paszke *et al.*, 2019] to implement all our experiments. During training, we used the standard SGD optimizer with a momentum of 0.9 to train all the models. The weight decay is set to 4E-5 always. The cosine learning schedule [He *et al.*, 2019] with an initial learning rate of 0.1 is adopted. The images are cropped to  $224 \times 224$  as the input. Random horizontal flipping and random cropping are used for data augmentation.

#### 4.2 Ablation Studies

Incorporating explicit representations of position information is known to be especially important for Transformers, since the model is otherwise entirely invariant to sequence ordering, which is undesirable for modeling structured data. We

Table 2: Top-1 and Top-5 accuracies (%) for Swin-B model, on Mini-ImageNet datasets.

Method	Top-1 acc.	Top-5 acc.
Swin-B + PE (Baseline)	67.39	86.88
Swin-B	66.18	86.02
Swin-B + APL	67.95	87.19
Swin-B + RPL	68.46	87.45
Swin-B + PE + APL	68.73	87.83
Swin-B + PE + RPL	69.11	88.02

Table 3: Top-1 and Top-5 accuracies (%) of various ViT variants, on Mini-ImageNet datasets. Each ViT variant follows the approach of adding position encoding in its paper.

Method	Top-1 acc.	Top-5 acc.
ViT-B [Dosovitskiy et al., 2020]	58.28	79.57
DeiT-B [Touvron et al., 2021]	63.67	83.92
Swin-B [Liu et al., 2021]	67.39	86.88
MaxViT-B [Tu et al., 2022]	67.20	86.31
NesT-B [Zhang et al., 2022]	67.43	86.75
ViT-B + APL	64.43	83.73
DeiT-B + APL	66.49	85.34
Swin-B + APL	68.91	87.83
MaxViT-B + APL	68.60	87.56
NesT-B + APL	68.73	87.95
ViT-B + RPL	63.97	83.06
DeiT-B + RPL	66.85	85.21
Swin-B + RPL	69.11	88.02
MaxViT-B + RPL	68.93	88.58
NesT-B + RPL	69.56	88.67

are surprised to find that the proposed position labels can be used in combination with traditional position encoding, the model does not learn the identities and can achieve the best performance gains. We experiment on ViT-B and Swin-B respectively, as shown in Table 1 and Table 2.

### 4.3 Combination with various ViT variants

We combine absolute and relative position labels with various ViT variants, each ViT variant follows the approach of adding position encoding in its paper. The experimental results show that the proposed position label can significantly improve the performance of ViT, for full-attention transformer (eg: ViT-B) absolute position label works better, for local-attention transformer (eg: Swin-B) relative position label works better, as shown in Table 3.

# 5 Conclusions

In this paper, we review existing position encoding methods, and propose two position labels for self-supervised training of ViT. The abundant experiments show that our method can be combined with various ViT variants, bringing significant improvements on classification tasks. Our methods could be easily plugged into existing ViTs. In addition, our position labels can also be used for ViT fully self-supervised training to provide a more powerful self-supervised signal.

# References

- [Caron et al., 2020] Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin, editors, Advances in Neural Information Processing Systems, volume 33, pages 9912–9924. Curran Associates, Inc., 2020.
- [Caron et al., 2021] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pages 9650–9660, October 2021.
- [Chen et al., 2020] Mark Chen, Alec Radford, Rewon Child, Jeffrey Wu, Heewoo Jun, David Luan, and Ilya Sutskever. Generative pretraining from pixels. In Hal Daumé III and Aarti Singh, editors, Proceedings of the 37th International Conference on Machine Learning, volume 119 of Proceedings of Machine Learning Research, pages 1691– 1703. PMLR, 13–18 Jul 2020.
- [Chen *et al.*, 2021] Xinlei Chen, Saining Xie, and Kaiming He. An empirical study of training self-supervised vision transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 9640–9649, October 2021.
- [Dai *et al.*, 2019] Zihang Dai, Zhilin Yang, Yiming Yang, Jaime G. Carbonell, Quoc V. Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. *CoRR*, abs/1901.02860, 2019.
- [Devlin et al., 2018] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. CoRR, abs/1810.04805, 2018.
- [Dosovitskiy *et al.*, 2020] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *CoRR*, abs/2010.11929, 2020.
- [Gehring et al., 2017] Jonas Gehring, Michael Auli, David Grangier, Denis Yarats, and Yann N. Dauphin. Convolutional sequence to sequence learning. In Doina Precup and Yee Whye Teh, editors, Proceedings of the 34th International Conference on Machine Learning, volume 70 of Proceedings of Machine Learning Research, pages 1243– 1252. PMLR, 06–11 Aug 2017.
- [He et al., 2016] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), June 2016.
- [He et al., 2019] Tong He, Zhi Zhang, Hang Zhang, Zhongyue Zhang, Junyuan Xie, and Mu Li. Bag of tricks for image classification with convolutional neural

networks. In *Proceedings of the IEEE/CVF Conference* on Computer Vision and Pattern Recognition, pages 558–567, 2019.

- [He *et al.*, 2020] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings* of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), June 2020.
- [He *et al.*, 2021] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross B. Girshick. Masked autoencoders are scalable vision learners. *CoRR*, abs/2111.06377, 2021.
- [Krizhevsky *et al.*, 2012] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25:1097–1105, 2012.
- [Li *et al.*, 2018] Chen Li, Zhen Zhang, Wee Sun Lee, and Gim Hee Lee. Convolutional sequence to sequence model for human dynamics. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition* (*CVPR*), June 2018.
- [Liu et al., 2021] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pages 10012–10022, October 2021.
- [Paszke et al., 2019] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, highperformance deep learning library. Advances in neural information processing systems, 32:8026–8037, 2019.
- [Ramachandran et al., 2019] Prajit Ramachandran, Niki Parmar, Ashish Vaswani, Irwan Bello, Anselm Levskaya, and Jon Shlens. Stand-alone self-attention in vision models. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.
- [Shaw *et al.*, 2018] Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani. Self-attention with relative position representations. *CoRR*, abs/1803.02155, 2018.
- [Srinivas et al., 2021] Aravind Srinivas, Tsung-Yi Lin, Niki Parmar, Jonathon Shlens, Pieter Abbeel, and Ashish Vaswani. Bottleneck transformers for visual recognition. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 16519– 16529, June 2021.
- [Touvron et al., 2021] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Herve Jegou. Training data-efficient image transformers-amp; distillation through attention. In Marina Meila and Tong Zhang, editors, Proceedings of the

38th International Conference on Machine Learning, volume 139 of Proceedings of Machine Learning Research, pages 10347–10357. PMLR, 18–24 Jul 2021.

- [Tu et al., 2022] Zhengzhong Tu, Hossein Talebi, Han Zhang, Feng Yang, Peyman Milanfar, Alan Bovik, and Yinxiao Li. Maxvit: Multi-axis vision transformer. In https://arxiv.org/abs/2204.01697, 04 2022.
- [Vaswani et al., 2017] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.
- [Wang et al., 2019] Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. Superglue: A stickier benchmark for general-purpose language understanding systems. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, Advances in Neural Information Processing Systems, volume 32. Curran Associates, Inc., 2019.
- [Wu et al., 2021] Kan Wu, Houwen Peng, Minghao Chen, Jianlong Fu, and Hongyang Chao. Rethinking and improving relative position encoding for vision transformer. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pages 10033–10041, October 2021.
- [Zhang et al., 2022] Zizhao Zhang, Han Zhang, Long Zhao, Ting Chen, Sercan O Arik, and Tomas Pfister. Nested hierarchical transformer: Towards accurate, data-efficient and interpretable visual understanding. In AAAI Conference on Artificial Intelligence (AAAI), volume 2022, 2022.
- [Zhao et al., 2020] Hengshuang Zhao, Jiaya Jia, and Vladlen Koltun. Exploring self-attention for image recognition. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), June 2020.