

C-Pack of IPAs: A C90 Program Benchmark of Introductory Programming Assignments

Pedro Orvalho
pmorvalho@tecnico.ulisboa.pt
INESC-ID/IST - U. Lisboa
Lisboa, Portugal

Mikoláš Janota
mikolas.janota@cvut.cz
Czech Technical University in Prague
Prague, Czech Republic

Vasco Manquinho
vasco.manquinho@tecnico.ulisboa.pt
INESC-ID/IST - U. Lisboa
Lisboa, Portugal

ABSTRACT

Due to the vast number of students enrolled in Massive Open Online Courses (MOOCs), there has been an increasing number of automated program repair techniques focused on introductory programming assignments (IPAs). Such techniques take advantage of previous correct student implementations in order to provide automated, comprehensive, and personalized feedback to students.

This paper presents C-PACK-IPAs, a publicly available benchmark of students' programs submitted for 25 different IPAs. C-PACK-IPAs contains semantically correct, semantically incorrect, and syntactically incorrect programs plus a test suite for each IPA. Hence, C-PACK-IPAs can be used to help evaluate the development of novel semantic, as well as syntactic, automated program repair frameworks focused on providing feedback to novice programmers.

CCS CONCEPTS

• **Applied computing** → *Computer-assisted instruction*; • **Theory of computation** → **Program semantics**; **Program analysis**; **Program reasoning**; • **Computing methodologies** → *Machine learning*.

KEYWORDS

dataset, benchmark, Introductory Programming Assignments, Programming Exercises, Automated Program Repair, Semantic Program Repair, Syntactic Program Repair, Program Clustering, Program Analysis, Programming Education, Computer-Aided Education, MOOCs, C, C90, IPAs

1 INTRODUCTION

Nowadays, thousands of students enroll every year in programming-oriented Massive Open Online Courses (MOOCs) [3]. On top of that, due to the current pandemic situation, even small programming courses are being taught online. Providing feedback to novice students in introductory programming assignments (IPAs) in these courses requires substantial effort and time by the faculty. Hence, there is an increasing need for systems that provide automated, comprehensive, and personalized feedback to students in incorrect programming assignments. Therefore, automated program repair has become crucial to provide automatic personalized feedback to each novice programmer [15].

Typically, a programming assignment in Computer Science courses follows a pattern: the lecturer defines a computational problem; students program a solution; each solution is submitted and checked for correctness using pre-defined tests. If the student's tentative solution does not pass a given test, it is deemed incorrect without helpful feedback that would help the student. If a student program does not pass a portion of the pre-defined tests, she usually asks the

Table 1: High-level Description of C-PACK-IPAs Benchmark.

Labs	#IPAs	#Correct Submissions	#Semantically Incorrect Submissions	#Syntactically Incorrect Submissions
Lab02	10	316	161	50
Lab03	7	145	255	29
Lab04	8	192	97	19
Total	25	653	513	98

lecturer for feedback on why her code does not have the expected behavior. If her program does not pass at least one pre-defined test, that means her implementation is semantically incorrect. Unfortunately, it is not feasible to have personalized feedback from a lecturer in many cases due to the growing number of student enrolments. Therefore, automated semantic program repair frameworks [2, 3, 5, 6, 9–12, 14, 16] are ideal for providing hints on how students should repair their incorrect programming assignments.

This paper presents C-PACK-IPAs, a C90 Program benchmark of introductory programming assignments (IPAs). C-PACK-IPAs is a collection of students' programs submitted for 25 different IPAs and the test suite used for each IPA. The set of IPAs is described in Section 3. For each IPA, C-PACK-IPAs has a set of semantically correct and incorrect implementations evaluated with the IPA's test suite. C-PACK-IPAs also contains a set of syntactically faulty programs submitted for each IPA. This paper aims to introduce C-PACK-IPAs that contains semantically and syntactically incorrect students' implementations. Thus, C-PACK-IPAs can help evaluate novel semantic, as well as syntactic, automated program repair frameworks whose goal is to assist novice programmers.

2 C-PACK-IPAS

C-PACK-IPAs is a pack of student programs developed during an introductory programming course in the C programming language. These programs were collected over three distinct practical classes at Instituto Superior Técnico for 25 different IPAs. The set of submissions was split into three groups: semantically correct, semantically incorrect, and syntactically incorrect submissions. The students' submissions that satisfied the set of input-output test cases for each IPA were considered semantically correct. The submissions that failed at least one input-output test but successfully compiled were considered semantically incorrect implementations. Lastly, the students' submissions that did not successfully compile were considered syntactically incorrect implementations.

Table 1 presents the number of submissions gathered. For 25 different programming exercises, this dataset contains 653 different correct programs, 513 semantically incorrect submissions, and 98

Table 2: The number of semantically correct student submissions received for 25 different programming assignments over three lab classes for two different years.

		E1	E2	E3	E4	E5	E6	E7	E8	E9	E10	Total
Year 1	Lab02	25	25	25	23	25	23	22	23	24	23	238
	Lab03	20	17	16	7	16	17	20	-	-	-	113
	Lab04	22	22	19	22	18	19	17	13	-	-	152
		E1	E2	E3	E4	E5	E6	E7	E8	E9	E10	Total
Year 2	Lab02	13	8	8	7	8	8	7	6	7	6	78
	Lab03	6	5	3	1	4	7	6	-	-	-	32
	Lab04	6	7	6	6	4	4	4	3	-	-	40

syntactically incorrect implementations. C-PACK-IPAs is publicly available at GitHub: <https://github.com/pmorvalho/C-Pack-IPAs>.

Table 2 presents the number of correct submissions for each one of the 25 different programming exercises over three lab classes for two different years. In addition, Table 3 presents the number of semantically incorrect submissions, and Table 4 shows the distribution of syntactically incorrect submissions for each IPA.

Furthermore, C-PACK-IPAs only contains students’ submissions that gave their permission to use their programs for academic purposes. Each student’s identification was anonymized for privacy reasons, and all the comments were removed from their programs. A unique identifier was assigned to each student. These identifiers are consistent among different IPAs and different years of the programming course. For example, if the identifier `stu_3` appears in more than one programming exercise, it corresponds to the same student. If some students take the course more than once, they are always assigned to the same anonymized identifier.

3 IPAS DESCRIPTION

The set of IPAs corresponds to three different lab classes of the introductory programming course to the C programming language at Instituto Superior Técnico. Each lab class focuses on a different topic of the C programming language. In Lab02, the students learn how to program with integers, floats, IO operations (mainly `printf` and `scanf`), conditionals (if-statements), and simple loops (for and while-loops). In Lab03, the students learn how to program with loops, nested loops, auxiliary functions, and chars. Finally, in Lab04, the students learn how to program with integer arrays and strings. The textual description of each programming assignment can be found in the public GitHub repository, and the input/output tests used to evaluate semantically the set of students’ submissions. Moreover, there is also a reference implementation for each IPA in the public git repository that can be used by program repair frameworks that only accept a single reference implementation to repair incorrect programs.

4 RELATED WORK

Over the last few years, several program repair tools [3–5, 14] have exploited diverse correct implementations from previously enrolled students for each IPA to repair new incorrect student submissions. On the one hand, some syntactic program repair tools [4, 15] have been developed to help students with compilation errors. On the other hand, semantic program repair has also been used to

help repair students’ programs semantically [2, 3, 5, 8, 14]. However, the number of publicly available benchmarks to help develop and evaluate new program repair tools is significantly small. The ITSP dataset [16] has been used by other automated software repair tools [1, 16] that use only one reference implementation. This dataset is also a collection of C programs although it is well balanced, i.e., the number of correct submissions is closer to the number of incorrect submissions in this dataset. The IntroClass dataset [7] is a collection of C programs submitted to six different IPAs and has the information about the number of defects in each program and the total number of unique defects for each IPA. Codeflaws [13] is a dataset of programs submitted for programming competitions on the Codeforces website. More program benchmarks are available for other languages than the C programming language. For example, the dataset of Python programs used to evaluate Refactory [5] is also publicly available. More datasets for automated program repair applied to industry software are also available ¹.

5 CONCLUSION

C-PACK-IPAs, a C90 Program benchmark of introductory programming assignments (IPAs), is a publicly available benchmark of students’ submissions for 25 different programming assignments. C-PACK-IPAs has a set of semantically correct and incorrect implementations as well as syntactically faulty programs submitted for each IPA. To the best of our knowledge, C-PACK-IPAs is one of the few, if not the only, benchmark of IPAs written in the C programming language that contains both semantically and syntactically incorrect students’ implementations and diverse correct implementations for the same IPA. Thus, C-PACK-IPAs can help evaluate novel semantic, as well as syntactic, automated program repair frameworks whose goal is to assist novice programmers in introductory programming courses.

ACKNOWLEDGMENTS

We would like to thank all the students who gave permission to use their programs for our research. Secondly, we would like to thank Instituto Superior Técnico. This research was supported by Fundação para a Ciência e Tecnologia (FCT) through grant SFRH/BD/07724/2020 and projects UIDB/50021/2020 and PTDC/CCI-COM/32378/2017. Any opinions, findings, conclusions, or recommendations expressed in this material are those of the author and do not necessarily reflect the views of FCT.

¹<https://program-repair.org/benchmarks.html>

Table 3: The number of semantically incorrect student submissions received for 25 different programming assignments over three lab classes for two different years.

		E1	E2	E3	E4	E5	E6	E7	E8	E9	E10	Total
Year 1	Lab02	31	10	7	12	3	5	6	9	21	3	107
	Lab03	32	35	20	67	16	17	8	-	-	-	195
	Lab04	5	11	5	3	10	5	18	10	-	-	67
		E1	E2	E3	E4	E5	E6	E7	E8	E9	E10	Total
Year 2	Lab02	28	2	1	7	2	4	7	2	3	4	60
	Lab03	14	10	11	16	9	6	4	-	-	-	70
	Lab04	6	1	1	2	9	1	4	6	-	-	30

Table 4: The number of syntactically incorrect student submissions received for 25 different programming assignments over three lab classes for two different years.

		E1	E2	E3	E4	E5	E6	E7	E8	E9	E10	Total
Year 1	Lab02	6	0	1	5	4	4	4	2	1	2	29
	Lab03	6	4	1	7	2	1	2	-	-	-	23
	Lab04	2	1	1	0	5	0	1	2	-	-	12
		E1	E2	E3	E4	E5	E6	E7	E8	E9	E10	Total
Year 2	Lab02	6	3	0	5	1	6	0	0	0	0	21
	Lab03	1	0	0	1	1	1	2	-	-	-	6
	Lab04	0	0	0	1	1	1	4	0	-	-	7

REFERENCES

- [1] Umair Z. Ahmed, Zhiyu Fan, Jooyong Yi, Omar I. Al-Bataineh, and Abhik Roychoudhury. Verifix: Verified repair of programming assignments. *CoRR*, abs/2106.16199, 2021.
- [2] Umair Z. Ahmed, Zhiyu Fan, Jooyong Yi, Omar I. Al-Bataineh, and Abhik Roychoudhury. Verifix: Verified repair of programming assignments. *ACM Trans. Softw. Eng. Methodol.*, jan 2022.
- [3] Sumit Gulwani, Ivan Radicek, and Florian Zuleger. Automated clustering and program repair for introductory programming assignments. In *PLDI 2018*, pages 465–480. ACM, 2018.
- [4] Rahul Gupta, Soham Pal, Aditya Kanade, and Shirish K. Shevade. Deepfix: Fixing common C language errors by deep learning. In Satinder P. Singh and Shaul Markovitch, editors, *AAAI 2017*, pages 1345–1351. AAAI Press, 2017.
- [5] Yang Hu, Umair Z. Ahmed, Sergey Mehtaev, Ben Leong, and Abhik Roychoudhury. Re-factoring based program repair applied to programming assignments. In *34th IEEE/ACM International Conference on Automated Software Engineering, ASE 2019, San Diego, CA, USA, November 11-15, 2019*, pages 388–398. IEEE, 2019.
- [6] Yalin Ke, Kathryn T. Stolee, Claire Le Goues, and Yuriy Brun. Repairing programs with semantic code search (T). In Myra B. Cohen, Lars Grunske, and Michael Whalen, editors, *30th IEEE/ACM International Conference on Automated Software Engineering, ASE 2015*, pages 295–306. IEEE Computer Society, 2015.
- [7] Claire Le Goues, Neal Holtschulte, Edward K Smith, Yuriy Brun, Premkumar Devanbu, Stephanie Forrest, and Westley Weimer. The manybugs and introclass benchmarks for automated repair of c programs. *IEEE Transactions on Software Engineering*, 41(12):1236–1256, 2015.
- [8] Xiao Liu, Shuai Wang, Pei Wang, and Dinghao Wu. Automatic grading of programming assignments: an approach based on formal semantics. In Sarah Beecham and Daniela E. Damian, editors, *Proceedings of the 41st International Conference on Software Engineering: Software Engineering Education and Training, ICSE (SEET) 2019*, pages 126–137. IEEE / ACM, 2019.
- [9] Sergey Mehtaev, Jooyong Yi, and Abhik Roychoudhury. Directfix: Looking for simple program repairs. In Antonia Bertolino, Gerardo Canfora, and Sebastian G. Elbaum, editors, *37th IEEE/ACM International Conference on Software Engineering, ICSE 2015*, pages 448–458. IEEE Computer Society, 2015.
- [10] Sergey Mehtaev, Jooyong Yi, and Abhik Roychoudhury. Angelix: scalable multiline program patch synthesis via symbolic analysis. In Laura K. Dillon, Willem Visser, and Laurie A. Williams, editors, *ICSE 2016*, pages 691–701. ACM, 2016.
- [11] Hoang Duong Thien Nguyen, Dawei Qi, Abhik Roychoudhury, and Satish Chandra. Semfix: program repair via semantic analysis. In David Notkin, Betty H. C. Cheng, and Klaus Pohl, editors, *35th International Conference on Software Engineering, ICSE '13*, pages 772–781. IEEE Computer Society, 2013.
- [12] Reudismam Rolim, Gustavo Soares, Loris D’Antoni, Oleksandr Polozov, Sumit Gulwani, Rohit Gheyi, Ryo Suzuki, and Björn Hartmann. Learning syntactic program transformations from examples. In Sebastián Uchitel, Alessandro Orso, and Martin P. Robillard, editors, *ICSE 2017*, pages 404–415. IEEE / ACM, 2017.
- [13] Shin Hwei Tan, Jooyong Yi, Yulis, Sergey Mehtaev, and Abhik Roychoudhury. Codeflaws: a programming competition benchmark for evaluating automated program repair tools. In Sebastián Uchitel, Alessandro Orso, and Martin P. Robillard, editors, *Proceedings of the 39th International Conference on Software Engineering, ICSE 2017, Buenos Aires, Argentina, May 20-28, 2017 - Companion Volume*, pages 180–182. IEEE Computer Society, 2017.
- [14] Ke Wang, Rishabh Singh, and Zhendong Su. Search, align, and repair: data-driven feedback generation for introductory programming exercises. In *PLDI 2018*, pages 481–495. ACM, 2018.
- [15] Michihiro Yasunaga and Percy Liang. Graph-based, self-supervised program repair from diagnostic feedback. In *ICML 2020*, volume 119 of *Proceedings of Machine Learning Research*, pages 10799–10808. PMLR, 2020.
- [16] Jooyong Yi, Umair Z. Ahmed, Amey Karkare, Shin Hwei Tan, and Abhik Roychoudhury. A feasibility study of using automated program repair for introductory programming assignments. In Eric Bodden, Wilhelm Schäfer, Arie van Deursen, and Andrea Zisman, editors, *ESEC/FSE 2017*, pages 740–751. ACM, 2017.