

Lower bounds for adiabatic quantum algorithms by quantum speed limit

Jyong-Hao Chen^{1,*}

¹*Instituut-Lorentz, Universiteit Leiden, P.O. Box 9506, 2300 RA Leiden, The Netherlands*

(Dated: August 24, 2022)

We introduce a simple framework for estimating lower bounds on the runtime of a broad class of adiabatic quantum algorithms. The central formula consists of calculating the variance of the final Hamiltonian with respect to the initial state. After examining adiabatic versions of certain keystone circuit-based quantum algorithms, this technique is applied to adiabatic quantum algorithms with undetermined speedup. In particular, we analytically obtain lower bounds on adiabatic algorithms for finding k -clique in random graphs. Additionally, for a particular class of Hamiltonian, it is straightforward to prove the equivalence between our framework and the conventional approach based on spectral gap analysis.

Introduction.— Adiabatic approximation in quantum mechanics has found applications in many fields since it was initially developed in the 1920s [1, 2]. Nonetheless, the idea that adiabatic approximation may serve as a basis for quantum computing did not arise until the last two decades [3, 4]. Although adiabatic quantum computation is proven [5, 6] to be equivalent to the standard circuit-based quantum computation [7, 8], there is no general way to translate between circuit-based quantum algorithms and adiabatic quantum algorithms.

An adiabatic quantum algorithm (AQA) consists of three components [9, 10]: (i) a *problem* (or *final*) *Hamiltonian* H_1 whose ground state encodes solutions to the problem; (ii) a *driver* (or *initial*) *Hamiltonian* H_0 who does not commute with the final Hamiltonian H_1 and whose ground state is known; and (iii) a timing *schedule* $\lambda(t) \in [0, 1]$, a time-dependent strictly increasing function that interpolates between the initial Hamiltonian and the final Hamiltonian. The full time-dependent Hamiltonian $H_{\lambda(t)}$ of an AQA is then defined as

$$H_{\lambda(t)} := (1 - \lambda(t))H_0 + \lambda(t)H_1 \quad (1)$$

with boundary conditions $\lambda(0) = 0$ and $\lambda(T) = 1$, where T is the runtime of the algorithm.

An AQA is executed by preparing a quantum system at the ground state of the initial Hamiltonian H_0 and then letting it evolve. The adiabatic theorem [1, 2, 11, 12] guarantees that the final state of time evolution remains close to the instantaneous ground state of the problem Hamiltonian H_1 , provided that the system evolves slowly enough, or, equivalently, the runtime must be long enough. A typical sufficient condition for the runtime T is that it must scale polynomially with an inverse of the minimum spectral gap (the difference between the two smallest energy eigenvalues) of the full Hamiltonian H_λ [10, 12, 13]. Nevertheless, analytical calculation of spectral gap is possible only for relatively simple Hamiltonians, whereas performing numerical calculations is limited to small system size.

This work proposes a more elementary, alternative method to the conventional spectral gap analysis. We

derive a formula for estimating *necessary* runtime using the quantum uncertainty of the final Hamiltonian with respect to the initial state. We shall clarify the condition for which the obtained necessary runtime can be interpreted as a *lower bound* (in the sense of computational complexity) on the runtime of AQAs. After examining our formula with adiabatic versions [4, 14–17] of certain keystone quantum algorithms [18–22], our technique is applied to analytically obtain lower bounds for the algorithm of Childs et al. [23] and its variant for finding k -clique in random graphs.

Formalism.— Consider a quantum system characterized by a time-dependent Hamiltonian H_λ with $\lambda = \lambda(t)$ being a function of time t . For each λ , the instantaneous ground state $|\Phi_\lambda\rangle$ is the solution to the eigenvalue problem, $H_\lambda|\Phi_\lambda\rangle = E_{\text{GS},\lambda}|\Phi_\lambda\rangle$, where $E_{\text{GS},\lambda}$ is the ground state energy. On the other hand, the actual dynamics of the quantum system is described by the physical (or time-evolved) state $|\Psi_\lambda\rangle$, which is the solution to the scaled time-dependent Schrödinger equation, $i\Gamma\partial_\lambda|\Psi_\lambda\rangle = H_\lambda|\Psi_\lambda\rangle$ with initial condition $|\Psi_0\rangle = |\Phi_0\rangle$, where $\Gamma := \partial_t\lambda(t)$ is the driving rate. Mathematically, adiabaticity can be quantified by the fidelity between the physical state $|\Psi_\lambda\rangle$ and the instantaneous ground state $|\Phi_\lambda\rangle$, namely, the *adiabatic fidelity* $\mathcal{F}(\lambda) := |\langle\Phi_\lambda|\Psi_\lambda\rangle|^2$. In essence, the quantum adiabatic theorem [1, 2, 11, 12] ensures the following condition,

$$1 - \mathcal{F}(\lambda) \leq \epsilon, \quad (2)$$

provided that the driving rate Γ is small enough for any given allowance $\epsilon \in [0, 1]$.

Building upon the seminal work of Ref. [24], one of the main results of Ref. [25] is the following inequality that ties the adiabatic fidelity, $\mathcal{F}(\lambda)$, the overlap of instantaneous ground states, $\mathcal{C}(\lambda) := |\langle\Phi_\lambda|\Phi_0\rangle|^2$, and the Bures angle for physical states, $\theta(\lambda) := \arccos(|\langle\Psi_\lambda|\Psi_0\rangle|)$, through

$$|\mathcal{F}(\lambda) - \mathcal{C}(\lambda)| \leq \sin\theta(\lambda) \leq \sin\tilde{\mathcal{R}}(\lambda), \quad (3)$$

where $\tilde{\mathcal{R}}(\lambda) := \min(\mathcal{R}(\lambda), \frac{\pi}{2})$ with

$$\mathcal{R}(\lambda) := \int_0^\lambda \frac{d\lambda'}{|\Gamma(\lambda')|} \delta E_0(\lambda'), \quad (4a)$$

$$\text{where } \delta E_0(\lambda) := \sqrt{\langle H_\lambda^2 \rangle_0 - \langle H_\lambda \rangle_0^2}. \quad (4b)$$

Here, $\langle \dots \rangle_0 := \langle \Psi_0 | \dots | \Psi_0 \rangle$. The second inequality in Eq. (3), i.e., $\theta(\lambda) \leq \tilde{\mathcal{R}}(\lambda)$, sets an upper bound on the Bures angle of physical states is dubbed as *quantum speed limit* [26–32]. This name is suggested by the fact that since the Bures angle $\theta(\lambda) \in [0, \pi/2]$ is a measure of distance, the quantum uncertainty $\delta E_0(\lambda)$ signifies speed.

In this work, we explore a union of the adiabatic condition (2) and the inequality of adiabatic fidelity (3) at the end of the time evolution of AQAs, $t = T$ [i.e., when $\lambda(t = T) = 1$]. Combining Eqs. (2) with (3) leads to the following inequality that must be satisfied by the runtime T [33, Sec. 1],

$$T \geq \frac{\arcsin(\max(1 - \epsilon - \mathcal{C}(\lambda(T)), 0))}{\mathcal{R}(\lambda(T))/T}. \quad (5)$$

This inequality may be interpreted as a *necessary condition* obeyed by the runtime T of adiabatic quantum evolution.

When applied to AQAs with a full Hamiltonian $H_{\lambda(t)}$ defined as in Eq. (1), the function $\mathcal{R}(\lambda(t))$ of Eq. (4) reads $\mathcal{R}(\lambda(t)) = t\lambda(t)\delta V_n$, where

$$\delta V_n := \sqrt{\langle H_1^2 \rangle_0 - \langle H_1 \rangle_0^2} \quad (6)$$

is the quantum uncertainty of the final Hamiltonian H_1 with respect to the initial ground state $|\Phi_0\rangle$, and $\lambda(t) := t^{-1} \int_0^t dt' \lambda(t')$ is the time average of the schedule function $\lambda(t)$. The subscript n emphasizes that the quantum uncertainty δV_n often varies with the problem size (or number of qubits), n . Consequently, applying the Hamiltonian of AQAs (1) to the inequality (5) yields

$$T \geq \frac{\arcsin(\max(1 - \epsilon - \mathcal{C}(1), 0))}{\lambda(T)\delta V_n}. \quad (7)$$

Now, since the numerator, $\arcsin(\max(1 - \epsilon - \mathcal{C}(1), 0))$, is $\mathcal{O}(1)$, [34] and because $0 < \lambda(T) \leq 1$ (as a consequence of $\lambda(t) \in [0, 1]$ by definition), we shall just concentrate on the asymptotic behavior of δV_n (6) for the purpose of performing asymptotic analysis using Eq. (7),

$$T \geq T_{\text{inf}}, \quad \text{where } T_{\text{inf}} := \mathcal{O}(1/\delta V_n). \quad (8)$$

Observe that estimating a necessary runtime T_{inf} using Eq. (8) requires only two ingredients, i.e., the initial state $|\Phi_0\rangle$ and the final Hamiltonian H_1 . Although the schedule function $\lambda(t)$ is one of the three ingredients for specifying an AQA, our formula (8) for determining a necessary runtime does not depend on any particular form of

$\lambda(t)$. This is unlike the conventional approach of spectral gap analysis [13] where an explicit form of $\lambda(t)$ must be specified; given an initial Hamiltonian and a final Hamiltonian, different forms of $\lambda(t)$ could result in different estimations of asymptotic forms of runtime. However, it is not possible for those runtime estimates using spectral gap analysis to be smaller than the necessary runtime determined by Eq. (8). In other words, for an AQA specified by an initial state and a final Hamiltonian, one can use Eq. (8) to obtain a necessary runtime. This necessary runtime might be saturated by choosing particular schedule function or different initial Hamiltonian.

Although the inequality (8) is established as a universal necessary condition for the runtime of any AQA, interpreting the necessary runtime T_{inf} (8) as a *lower bound* on time complexity only applies to those AQAs whose inverse of the quantum uncertainty δV_n is different from zero when n goes to infinity, namely, if

$$\lim_{n \rightarrow \infty} 1/\delta V_n \neq 0. \quad (9)$$

Otherwise, one would incorrectly deduce that the required runtime decreases as the input size n increases. The asymptotic property (9) can be fulfilled by a wide class of final Hamiltonians H_1 that meets the following condition (up to a redefinition of H_1 [35]),

$$\langle H_1^2 \rangle_0 \stackrel{!}{=} \langle H_1 \rangle_0. \quad (10)$$

To see this, imposing the *moments condition* (10) on the definition of quantum uncertainty δV_n (6) yields $\delta V_n = \sqrt{\langle H_1 \rangle_0(1 - \langle H_1 \rangle_0)}$. This quantum uncertainty satisfies the desired asymptotic property (9) since the expectation value $\langle H_1 \rangle_0$ is bounded, $0 \leq \langle H_1 \rangle_0 \leq 1$, which is a consequence of the moments condition (10) together with the Cauchy-Schwarz inequality. If the moments condition (10) holds, the corresponding lower bound on runtime (8) reads

$$T_{\text{inf}} = \mathcal{O}(1/\delta V_n), \quad \delta V_n = \sqrt{\langle H_1 \rangle_0(1 - \langle H_1 \rangle_0)}. \quad (11)$$

A stronger condition than the moments condition (10) is when the final Hamiltonian is a projector, namely, if $H_1^2 \stackrel{!}{=} H_1$. As we shall see shortly, the adiabatic version of Deutsch-Jozsa algorithm [14, 15], Bernstein-Vazirani algorithm [16], and Grover search [4, 17], all can be implemented using a projector final Hamiltonian. A representative final Hamiltonian that does not satisfy the asymptotic property (9) is the one containing Ising terms, whose quantum uncertainty scales as $\delta V_n \propto \sqrt{n}$ [33, Sec. 2].

In what follows, we shall focus on AQAs that satisfy the moments condition (10), and apply formula (11) to obtain a lower bound on runtime. For this purpose, we need to specify what kind of initial state $|\Phi_0\rangle$ and final Hamiltonian H_1 we wish to use. For an AQA consisting of n qubits, the initial state $|\Phi_0\rangle$ can often be chosen as

the uniform superposition of all basis states of the 2^n -dimensional Hilbert space in the computational basis,

$$|\Phi_0\rangle = \frac{1}{\sqrt{2^n}} \sum_{z \in \{0,1\}^n} |z\rangle =: |+\rangle^{\otimes n}. \quad (12)$$

Here, $|z\rangle = |z_0\rangle \otimes |z_1\rangle \otimes \cdots \otimes |z_{n-1}\rangle$ with each $z_i \in \{0,1\}$, $\{0,1\}^n$ is the set of 2^n possible n -bit binary strings, and $|\pm\rangle = (|0\rangle \pm |1\rangle)/\sqrt{2}$. As for the final Hamiltonian H_1 , the following two types of final Hamiltonian satisfying Eq. (10) will be discussed in detail:

- I. Final Hamiltonian with orthogonal projection.
- II. A special class of optimization problems.

Final Hamiltonian of type-I.— Let Π_{Φ_1} be an projector that projects onto the eigenspace of the final state $|\Phi_1\rangle$. In certain AQAs, their final Hamiltonian H_1 can be implemented by an complementary projector of Π_{Φ_1} ,

$$H_1 = \mathbb{I} - \Pi_{\Phi_1}, \quad (13)$$

where \mathbb{I} is an identity operator. Adiabatic Deutsch-Jozsa algorithm [14, 15] and adiabatic Bernstein-Vazirani algorithm [16] are two examples of AQAs whose final Hamiltonian has the form shown in Eq. (13). We shall discuss the first example in the main text, while the second example is presented in Supplemental Material [33, Sec. 3]

Example: Adiabatic Deutsch-Jozsa algorithm. Recall that in the problem of Deutsch-Jozsa [18], we are given a Boolean function $f: \{0,1\}^n \rightarrow \{0,1\}$. The task is to determine whether f is constant or balanced (i.e., equal number of output of 0's and 1's). In the AQA proposed by Ref. [14], the final state is chosen as (here, $N \equiv 2^n$)

$$|\Phi_1\rangle = \mu_f |0\rangle + \frac{1 - \mu_f}{\sqrt{N}} \sum_{i=1}^{N-1} |i\rangle, \quad (14)$$

where $\mu_f := N^{-1} \left| \sum_{z \in \{0,1\}^n} (-1)^{f(z)} \right|$. If f is constant (resp., balanced), then $\mu_f = 1$ (resp., $\mu_f = 0$). The corresponding final Hamiltonian can be constructed as a projector shown in Eq. (13) with $\Pi_{\Phi_1} = |\Phi_1\rangle\langle\Phi_1|$. The initial state is chosen as an equal weight superposition of all basis states (12). In Ref. [14], using conventional spectral gap analysis yields the scaling of runtime $T \sim \mathcal{O}(N)$ for $\lambda(t) = \frac{t}{T}$ and $T \sim \mathcal{O}(\sqrt{N})$ for a local adiabatic evolution. These results do not reach the well-known [18] optimal runtime, i.e., $\mathcal{O}(1)$. Nevertheless, we shall demonstrate that using the formula (11) enables us to obtain the lowest runtime found in Ref. [14]. We compute the overlap $|\langle\Phi_1|\Phi_0\rangle|^2$ using Eqs. (12) and (14),

$$|\langle\Phi_1|\Phi_0\rangle|^2 = \frac{1}{N} \left(\mu_f + (1 - \mu_f)\sqrt{N-1} \right)^2, \quad (15)$$

and apply it to Eq. (11) to obtain $T_{\text{inf}} = \mathcal{O}(\sqrt{N})$, which is consistent with the result obtained by Ref. [14] as mentioned above.

From the general expression of T_{inf} (11), it is clear that in order to reproduce the correct optimal runtime of the Deutsch-Jozsa algorithm, the overlap $|\langle\Phi_1|\Phi_0\rangle|^2$ should be independent of N . In light of this, the final state (14) should be modified. Exactly this modification has been carried out in Ref. [15] by replacing the final state of Eq. (14) with the one which is more symmetric in amplitudes,

$$|\Phi_1\rangle = \frac{\mu_f}{\sqrt{N/2}} \sum_{i=0}^{N/2-1} |2i\rangle + \frac{1 - \mu_f}{\sqrt{N/2}} \sum_{i=0}^{N/2-1} |2i+1\rangle. \quad (16)$$

Upon using Eqs. (12) and (16), the overlap $|\langle\Phi_1|\Phi_0\rangle|^2$ reads

$$|\langle\Phi_1|\Phi_0\rangle|^2 = \frac{1}{N} \frac{1}{N/2} \left(\mu_f \frac{N}{2} + (1 - \mu_f) \frac{N}{2} \right)^2 = \frac{1}{2}. \quad (17)$$

Bring Eq. (17) to Eq. (11) yields $T_{\text{inf}} = \mathcal{O}(1)$. Therefore, the optimal runtime for the Deutsch-Jozsa problem is attained. In contrast to the usual approach of estimating runtime via spectral gap as done in Refs. [14, 15], our formalism clearly illustrates why the algorithm of Ref. [15] is superior to that of Ref. [14].

Final Hamiltonian of type-II.— For optimization problems with a cost function $h: \{0,1\}^n \rightarrow \mathbb{R}$, we seek a minimum of h . In the framework of adiabatic quantum computation [3, 4], a final Hamiltonian can be defined to be diagonal in the computational basis, with cost function h being the diagonal element

$$H_1 = \sum_{z \in \{0,1\}^n} h(z) |z\rangle\langle z|. \quad (18)$$

If the uniform superposition of all basis states (12) is chosen as the initial state, the quantum uncertainty (6) reads $\delta V_n = (\bar{h}^2 - \overline{h^2})^{1/2}$, with the arithmetic average $\bar{h} := 2^{-n} \sum_z h(z)$ and $\overline{h^2} := 2^{-n} \sum_z h^2(z)$. Furthermore, if we impose the moments condition (10), which amounts to requiring

$$\overline{h^2} \stackrel{!}{=} \bar{h}, \quad (19)$$

then the lower bound T_{inf} (11),

$$T_{\text{inf}} = \mathcal{O}(1/\delta V_n) \quad \text{with} \quad \delta V_n = \sqrt{\bar{h}(1 - \bar{h})}, \quad (20)$$

is completely determined by the arithmetic average of the cost function, i.e., \bar{h} . Note that $0 \leq \bar{h} \leq 1$ as a result of Cauchy-Schwarz together with the moments condition (19).

Example: Adiabatic Grover search. Taking the unstructured search problem of Grover [21, 22] as an example, it can be formulated as a combinatorial optimization problem with the following cost function [4, 36]: $h(z) = 0$ for M marked items and $h(z) = 1$ otherwise. For this case, one immediately finds $\overline{h^2} = \bar{h} =$

$1 - M/N$ (here, $N \equiv 2^n$). It then follows from Eq. (20) that a lower bound $T_{\text{inf}} = \mathcal{O}(\sqrt{N/M})$, as expected [17, 37, 38]. We note that the final Hamiltonian of adiabatic Grover search can be equivalently written as $H_1 = \mathbb{I} - \sum_{z \in \mathcal{M}} |z\rangle\langle z|$, where \mathcal{M} is the space of solution (of size M). Hence, this final Hamiltonian also belongs to the type-I final Hamiltonian [see Eq. (13)]. It is with this expression of projector final Hamiltonian that Ref. [39] used a formula similar to Eq. (7) to obtain the optimal runtime for adiabatic Grover search. For completeness, we present a similar calculation using our formula in [33, Sec. 4].

Thus far, three adiabatic versions of keystone quantum algorithms have been examined. We shall now apply our technique to the adiabatic algorithm proposed by Childs et al. [23] for finding k -clique in random graphs.

Adiabatic algorithm for finding k -clique.— Consider a random graph G where every pair of vertices is connected or disconnected with a probability of $1/2$. A *clique* is a subgraph of G in which every pair of vertices is connected by an edge. The problem of finding cliques of k vertices (called *k -clique*) in a random graph of n vertices is an NP-complete problem if both n and k are treated as inputs [40, 41].

In the algorithm proposed by Ref. [23], each vertex is associated with a qubit. Hence, there are n qubits for a graph of n vertices. As before, each qubit state is represented by $|z_i\rangle$ with $z_i \in \{0, 1\}$ for $i \in \{0, \dots, n-1\}$. A vertex i is included into a subgraph of k vertices only if $z_i = 1$.

Although the full Hilbert space is 2^n -dimensional, we can focus only on the subspace spanned by quantum states with Hamming weight k since we are only interested in those quantum states that represent cliques of k vertices. For notational convenience, we denote the set of n -bit binary strings of Hamming weight k as $\mathcal{S}_k := \{z \in \{0, 1\}^n : |z| = k\}$, where $|z| = \sum_{i=0}^{n-1} z_i$ is the Hamming weight of the n -bit binary string z . The size of \mathcal{S}_k is $\binom{n}{k} \equiv C(n, k)$. In the subspace generated by binary strings from \mathcal{S}_k , the initial state can be chosen as a Dicke state [42–44],

$$|\Phi_0\rangle := \frac{1}{\sqrt{C(n, k)}} \sum_{z \in \mathcal{S}_k} |z\rangle. \quad (21)$$

In Ref. [23], the final Hamiltonian is of the form shown in Eq. (18) with the cost function

$$h_{\text{C}}(z) := \sum_{i, j=0: i > j}^{n-1} (1 - G_{ij}) z_i z_j, \quad (22)$$

where G_{ij} with $i, j \in \{0, \dots, n-1\}$ is the matrix element of the adjacency matrix for a graph G . As usual, $G_{ij} = 1$ if the vertices i and j are connected by an edge; otherwise, $G_{ij} = 0$. Observe that the cost function $h_{\text{C}}(z)$

takes values in $\{0, 1, \dots, L_k\}$, where $L_k := C(k, 2)$ is the total number of edges for a graph of k vertices.

We proceed to obtain a lower bound on runtime using Eq. (8) for the algorithm defined above. Since each $G_{ij} \in \{0, 1\}$ is a random variable, an exact computation for the arithmetic average, $\overline{h_{\text{C}}}$ and $\overline{h_{\text{C}}^2}$, is not possible without knowing an explicit instance of G_{ij} . We attempt to consider a “mean-field” (or “randomized”) approach by replacing G_{ij} with its (classical) expectation value $\mathbb{E}[G_{ij}] = 1/2$, and obtain [33, Sec. 4] $\mathbb{E}[\overline{h_{\text{C}}}] = L_k/2$ and $\mathbb{E}[\overline{h_{\text{C}}^2}] = (L_k + 1)L_k/4$. It follows from Eq. (8) that a lower bound on runtime $T_{\text{rand,inf}}$ reads $T_{\text{rand,inf}} = \mathcal{O}(\sqrt{1/L_k})$, which is independent of n . It is very likely that this n -independent lower bound is considerably lower than the sufficient runtime obtained using the spectral gap analysis (though it is not available). We also notice that the moments condition (19) is not met for the cost function defined in Eq. (22). Nevertheless, we note that the k dependence in $T_{\text{rand,inf}}$ seems consistent with the numerical data found in Ref. [23], saying that the median runtime for finding cliques of $k = 5$ is longer than that for finding cliques of $k = 6$. Specifically, $T_{\text{med}}(k = 5)/T_{\text{med}}(k = 6) = 30.87/18.56 \approx 1.66$ found in Ref. [23], whereas our result indicates $T_{\text{rand,inf}}(k = 5)/T_{\text{rand,inf}}(k = 6) = \sqrt{15/10} \approx 1.22$.

To make better use of our formula (20), we propose the following deformed cost function

$$h(z) := \frac{1}{2} (1 + h_{\text{C}}(z) - |1 - h_{\text{C}}(z)|). \quad (23)$$

This amounts to $h(z) = \min(h_{\text{C}}(z), 1)$, where $h_{\text{C}}(z)$ is defined in Eq. (22). In other words, those $h_{\text{C}}(z) > 1$ are mapped to $h(z) = 1$. Therefore, the deformed cost function is Boolean-valued, $h(z) \in \{0, 1\}$. This deformed cost function is similar to that of adiabatic Grover search discussed previously. One finds that the cost function defined in Eq. (23) along with the initial state defined in Eq. (21) satisfies the moments condition (19). Explicitly, $\overline{h} = \overline{h^2} = (1 - M/C(n, k))$, which renders a lower bound from Eq. (20)

$$T_{\text{inf}} = \mathcal{O}\left(\sqrt{C(n, k)/M}\right), \quad (24)$$

where M is the number of cliques of k vertices. The result (24) is consistent with that of a circuit-based algorithm of Ref. [45] in which the time complexity is related to the number of Grover iterations. For the special case of $n \gg k$, Eq. (24) simplifies: $T_{\text{inf}} = \mathcal{O}(n^{k/2})$ for $n \gg k$. A well-studied case is $k = 3$, i.e., the so-called *3-clique problem* (or *triangle-finding problem*); the resulting lower bound is $T_{\text{inf}} = \mathcal{O}(n^{3/2})$. The exponent, $3/2$, agrees with that found in a quantum algorithm [46] for the triangle-finding problem using a plain Grover search.

Connection to spectral gap analysis.— We shall now compare our approach with conventional spectral

gap analysis. An equivalence between the two approaches can be directly shown for a particular class of Hamiltonians where both the initial and final Hamiltonians are of the projector form, $H_0 = \mathbb{I} - |\Phi_0\rangle\langle\Phi_0|$ and $H_1 = \mathbb{I} - |\Phi_1\rangle\langle\Phi_1|$. It was then proved in Ref. [47] that the spectral gap of the full Hamiltonian H_λ (1), denoted as $g(H_\lambda)$, is bounded from below: $g(H_\lambda) \geq |\langle\Phi_1|\Phi_0\rangle| \equiv g_{\min}$, where $g_{\min} = \min_{\lambda \in [0,1]} g(H_\lambda)$ is the minimal spectral gap. If the schedule function $\lambda(t)$ is chosen simply as $\lambda(t) = t/T$, spectral gap analysis [13, 17] yields the scaling of runtime $T_{\text{gap}} \sim \mathcal{O}(1/g_{\min}^2)$. Furthermore, it is possible to improve [13, 17] the error dependence on the minimal gap by adopting a non-linear schedule function; if so, one obtains $T'_{\text{gap}} \sim \mathcal{O}(1/g_{\min})$. On the other hand, using our formalism, we directly obtain $\langle H_1 \rangle_0 = \langle H_1^2 \rangle_0 = 1 - |\langle\Phi_1|\Phi_0\rangle|^2 = 1 - g_{\min}^2$. Consequently, a lower bound on runtime follows from Eq. (11), $T_{\text{inf}} = \mathcal{O}(1/g_{\min})$.

If the minimal gap $g_{\min} = |\langle\Phi_1|\Phi_0\rangle|$ is independent of n , then the two estimates, T_{gap} and T_{inf} , are equal: $T_{\text{gap}} = T_{\text{inf}} = \mathcal{O}(1)$. This is the case for the adiabatic Deutsch-Jozsa algorithm and the adiabatic Bernstein-Vazirani algorithm discussed previously. For the case of adiabatic Grover search, the optimal runtime obtained from the spectral gap analysis along with a non-linear schedule function yields [17] $T'_{\text{gap}} = \mathcal{O}(1/g_{\min})$, which again agrees with our lower bound $T_{\text{inf}} = \mathcal{O}(1/g_{\min})$.

Comparison with prior works.— (i) A new class of quantum speed limits is presented in Refs. [48, 49] and applied to adiabatic searches. A lower bound on runtime is defined there as the minimum time it takes for the physical state to be orthogonal to the initial state. This definition is, however, too restrictive [50]. (ii) While the main result of Ref. [39] is an inequality similar to Eq. (7), the present work makes several crucial advances. First, we provide a more systematic and rigorous method for estimating lower bounds. Second, we carefully address the applicability of Eq. (7). Specifically, we explicitly emphasize the importance of the asymptotic property (9) and the irrelevance of schedule function $\lambda(t)$ in asymptotic analysis. Finally, more examples of adiabatic quantum algorithms are explored, as compared to only the adiabatic Grover algorithm is examined in Ref. [39]. (iii) It is also worth noting that quantum speed limits and the formalism of shortcuts to adiabaticity [51–58] are combined in Ref. [59] to investigate the performance of adiabatic quantum computation.

Concluding remarks.— We have shown that for a wide class of adiabatic quantum algorithms, in which Eq. (9) holds, nontrivial lower bounds on the runtime of adiabatic algorithms can be estimated by calculating the quantum uncertainty of the final Hamiltonian with respect to the initial state [see Eq. (8)]. A runtime estimation obtained by conventional spectral gap analysis will not be smaller than the necessary runtime derived with our method. The reason is that our formula is a *necessary* condition obeyed by the runtime of adiabatic

quantum evolution. Our approach may shed new light on the design of new adiabatic quantum algorithms.

ACKNOWLEDGMENTS

This work was funded by the Dutch Research Council (NWO) through the project Adiabatic Protocols in Extended Quantum Systems (Project No. 680-91-130).

* jhchen@lorentz.leidenuniv.nl

- [1] M. Born, *Zeitschrift fur Physik* **40**, 167 (1927).
- [2] M. Born and V. Fock, *Zeitschrift fur Physik* **51**, 165 (1928).
- [3] E. Farhi, J. Goldstone, S. Gutmann, and M. Sipser, arXiv e-prints, quant-ph/0001106 (2000), [arXiv:quant-ph/0001106](https://arxiv.org/abs/quant-ph/0001106) [quant-ph].
- [4] E. Farhi, J. Goldstone, S. Gutmann, J. Lapan, A. Lundgren, and D. Preda, *Science* **292**, 472 (2001), [arXiv:quant-ph/0104129](https://arxiv.org/abs/quant-ph/0104129) [quant-ph].
- [5] D. Aharonov, W. van Dam, J. Kempe, Z. Landau, S. Lloyd, and O. Regev, *SIAM Journal on Computing* **37**, 166 (2007).
- [6] A. Mizel, D. A. Lidar, and M. Mitchell, *Phys. Rev. Lett.* **99**, 070502 (2007).
- [7] R. P. Feynman, *Optics news* **11**, 11 (1985).
- [8] M. Nielsen and I. Chuang, *Quantum Computation and Quantum Information: 10th Anniversary Edition* (Cambridge University Press, 2010).
- [9] V. Choi, arXiv e-prints, arXiv:1004.2226 (2010), [arXiv:1004.2226](https://arxiv.org/abs/1004.2226) [quant-ph].
- [10] T. Albash and D. A. Lidar, *Rev. Mod. Phys.* **90**, 015002 (2018).
- [11] T. Kato, *J. Phys. Soc. Japan* **5**, 435 (1950).
- [12] A. Messiah, *Quantum Mechanics*, Dover Books on Physics (Dover Publications, 2014).
- [13] S. Jansen, M.-B. Ruskai, and R. Seiler, *Journal of Mathematical Physics* **48**, 102111 (2007).
- [14] S. Das, R. Kobes, and G. Kunstatter, *Phys. Rev. A* **65**, 062310 (2002).
- [15] Z. Wei and M. Ying, *Physics Letters A* **354**, 271 (2006).
- [16] I. Hen, *EPL (Europhysics Letters)* **105**, 50005 (2014).
- [17] J. Roland and N. J. Cerf, *Phys. Rev. A* **65**, 042308 (2002).
- [18] D. Deutsch and R. Jozsa, *Proceedings of the Royal Society of London. Series A: Mathematical and Physical Sciences* **439**, 553 (1992).
- [19] E. Bernstein and U. Vazirani, in *Proceedings of the Twenty-Fifth Annual ACM Symposium on Theory of Computing*, STOC '93 (Association for Computing Machinery, New York, NY, USA, 1993) p. 11–20.
- [20] E. Bernstein and U. Vazirani, *SIAM Journal on Computing* **26**, 1411 (1997).
- [21] L. K. Grover, in *Proceedings of the twenty-eighth annual ACM symposium on Theory of computing* (1996) pp. 212–219.
- [22] L. K. Grover, *Phys. Rev. Lett.* **79**, 325 (1997).
- [23] A. M. Childs, E. Farhi, J. Goldstone, and S. Gutmann, *Quantum Inf. Comput.* **2**, 181 (2002).

- [24] O. Lychkovskiy, O. Gamayun, and V. Cheianov, *Phys. Rev. Lett.* **119**, 200401 (2017).
- [25] J.-H. Chen and V. Cheianov, arXiv e-prints, arXiv:2112.06900 (2021), arXiv:2112.06900 [quant-ph].
- [26] L. Mandelstam and I. Tamm, *J. Phys. USSR* **9**, 249 (1945).
- [27] Y. Aharonov and L. Vaidman, *Phys. Rev. A* **41**, 11 (1990).
- [28] J. Anandan and Y. Aharonov, *Phys. Rev. Lett.* **65**, 1697 (1990).
- [29] L. Vaidman, *American Journal of Physics* **60**, 182 (1992).
- [30] A. Uhlmann, *Physics Letters A* **161**, 329 (1992).
- [31] P. Pfeifer, *Phys. Rev. Lett.* **70**, 3365 (1993).
- [32] S. Deffner and S. Campbell, *Journal of Physics A: Mathematical and Theoretical* **50**, 453001 (2017).
- [33] For further details, refer to Supplemental Material.
- [34] Throughout this paper, we use $\mathcal{O}(\cdot)$ to indicate “order of.”
- [35] For instance, if $H_1^2 = -H_1$, one can define a new Hamiltonian $H_1' = \mathbb{I} + H_1$ such that $H_1'^2 = H_1'$ holds.
- [36] W. van Dam, M. Mosca, and U. Vazirani, in *Proceedings 42nd IEEE symposium on foundations of computer science* (IEEE, 2001) pp. 279–287.
- [37] C. H. Bennett, E. Bernstein, G. Brassard, and U. Vazirani, *SIAM Journal on Computing* **26**, 1510 (1997).
- [38] E. Farhi and S. Gutmann, *Phys. Rev. A* **57**, 2403 (1998).
- [39] O. Lychkovskiy, *J. Russ. Laser Res.* **39**, 552 (2018).
- [40] R. M. Karp, in *Complexity of computer computations* (Springer, 1972) pp. 85–103.
- [41] C. Moore and S. Mertens, *The Nature of Computation* (OUP Oxford, 2011).
- [42] R. H. Dicke, *Phys. Rev.* **93**, 99 (1954).
- [43] G. Tóth, *J. Opt. Soc. Am. B* **24**, 275 (2007).
- [44] A. Bäertschi and S. Eidenbenz, in *International Symposium on Fundamentals of Computation Theory* (Springer, 2019) pp. 126–139.
- [45] S. A. Metwalli, F. Le Gall, and R. Van Meter, *IEEE Transactions on Quantum Engineering* **1**, 1 (2020).
- [46] H. Buhrman, C. Dürr, M. Heiligman, P. Høyer, F. Magniez, M. Santha, and R. de Wolf, *SIAM Journal on Computing* **34**, 1324 (2005).
- [47] D. Aharonov and A. Ta-Shma, *SIAM Journal on Computing* **37**, 47 (2007).
- [48] T. D. Kieu, *Proc. R. Soc., Ser. A* **475**, 20190148 (2019).
- [49] T. D. Kieu, *Quantum Information Processing* **18**, 1 (2019).
- [50] The final state of most adiabatic quantum algorithms is never orthogonal to the initial state, even though the overlap between the two is typically very small.
- [51] M. Demirplak and S. A. Rice, *The Journal of Physical Chemistry A* **107**, 9937 (2003).
- [52] M. Demirplak and S. A. Rice, *The Journal of Physical Chemistry B* **109**, 6838 (2005).
- [53] M. V. Berry, *Journal of Physics A: Mathematical and Theoretical* **42**, 365303 (2009).
- [54] X. Chen, A. Ruschhaupt, S. Schmidt, A. del Campo, D. Guéry-Odelin, and J. G. Muga, *Phys. Rev. Lett.* **104**, 063002 (2010).
- [55] E. Torrontegui, S. Ibáñez, S. Martínez-Garaot, M. Modugno, A. del Campo, D. Guéry-Odelin, A. Ruschhaupt, X. Chen, and J. G. Muga, in *Advances in Atomic, Molecular, and Optical Physics*, Advances In Atomic, Molecular, and Optical Physics, Vol. 62, edited by E. Arimondo, P. R. Berman, and C. C. Lin (Academic Press, 2013) pp. 117–169.
- [56] A. del Campo, *Phys. Rev. Lett.* **111**, 100502 (2013).
- [57] C. Jarzynski, *Phys. Rev. A* **88**, 040101 (2013).
- [58] D. Guéry-Odelin, A. Ruschhaupt, A. Kiely, E. Torrontegui, S. Martínez-Garaot, and J. G. Muga, *Rev. Mod. Phys.* **91**, 045001 (2019).
- [59] K. Suzuki and K. Takahashi, *Phys. Rev. Research* **2**, 032016 (2020).

Supplemental Material for “Lower bounds for adiabatic quantum algorithms by quantum speed limit”

Jyong-Hao Chen¹

¹*Instituut-Lorentz, Universiteit Leiden, P.O. Box 9506, 2300 RA Leiden, The Netherlands*

S1. PROOF OF EQ. (5)

We want to prove the following inequality (5)

$$T \geq \frac{\arcsin(\max(1 - \epsilon - \mathcal{C}(1), 0))}{\mathcal{R}(1)/T}. \quad (\text{S1})$$

Proof. We begin with rewriting the inequality (3) into the following form

$$\mathcal{C}(\lambda) - \sin \tilde{\mathcal{R}}(\lambda) \leq \mathcal{F}(\lambda) \leq \mathcal{C}(\lambda) + \sin \tilde{\mathcal{R}}(\lambda). \quad (\text{S2})$$

This together with Eq. (2) yields $1 - \epsilon \leq \mathcal{F}(\lambda) \leq \mathcal{C}(\lambda) + \sin \tilde{\mathcal{R}}(\lambda)$, which can be expressed as

$$\max(1 - \epsilon - \mathcal{C}(\lambda), 0) \leq \sin \tilde{\mathcal{R}}(\lambda) \quad (\text{S3})$$

since $\sin \tilde{\mathcal{R}}(\lambda) \geq 0$ by definition. Now, since $\sin x$ is a monotonically increasing function for $x \in [0, \pi/2]$, the inequality above can be inverted to obtain

$$\arcsin(\max(1 - \epsilon - \mathcal{C}(\lambda), 0)) \leq \tilde{\mathcal{R}}(\lambda) \leq \mathcal{R}(\lambda), \quad (\text{S4})$$

where we have used $\tilde{\mathcal{R}}(\lambda) \leq \mathcal{R}(\lambda)$ to obtain the last inequality. Upon taking $\lambda(t = T) = 1$, the proof of Eq. (S1) is therefore complete. \square

S2. QUANTUM UNCERTAINTY OF ISING TERMS

Consider a final Hamiltonian H_1 that consists of Ising terms $H_1 = -\sum_{i=0}^{n-1} Z_i Z_{i+1}$, where Z_i is the third Pauli matrix acting on the i -th qubit. Recall that $Z|+\rangle = |-\rangle$ and $Z|-\rangle = |+\rangle$. Choosing the initial state $|\Phi_0\rangle$ as the uniform superposition state (12). We first compute

$$|\tilde{\Phi}\rangle := H_1|\Phi_0\rangle = -\sum_{i=0}^{n-1} Z_i Z_{i+1} |+\rangle^{\otimes n} = -\sum_{i=0}^{n-1} (|-\rangle_i \otimes |-\rangle_{i+1} \otimes |+\rangle^{\otimes n-2}). \quad (\text{S5})$$

We then find

$$\begin{aligned} \langle \Phi_0 | H_1 | \Phi_0 \rangle &= \langle \Phi_0 | \tilde{\Phi} \rangle = \langle + |^{\otimes n} \left(-\sum_{i=0}^{n-1} (|-\rangle_i \otimes |-\rangle_{i+1} \otimes |+\rangle^{\otimes n-2}) \right) = 0, \\ \langle \Phi_0 | H_1^2 | \Phi_0 \rangle &= \langle \tilde{\Phi} | \tilde{\Phi} \rangle = \sum_{i,j=0}^{n-1} (\langle - |_i \otimes \langle - |_{i+1} \otimes |+\rangle^{\otimes n-2}) (|-\rangle_j \otimes |-\rangle_{j+1} \otimes |+\rangle^{\otimes n-2}) = \sum_{i,j=0}^{n-1} \delta_{ij} = n. \end{aligned} \quad (\text{S6})$$

It then follows from Eq. (6) that the quantum uncertainty reads $\delta V_n = \sqrt{n}$.

S3. EXAMPLE: ADIABATIC BERNSTEIN-VAZIRANI ALGORITHM

As the second example for the final Hamiltonian of Type-I (13), we consider an adiabatic algorithm solving the Bernstein-Vazirani problem. Recall that in the Bernstein-Vazirani problem [19, 20], one is given an oracle that evaluates the function $f_\lambda : \{0, 1\}^n \mapsto \{0, 1\}$ with $f_\lambda(z) = \sum_{i=0}^{n-1} z_i s_i \pmod{2}$. The task is to find the unknown n -bit

binary string $s \in \{0, 1\}^n$ using as few queries of the function f_λ as possible. The adiabatic algorithm proposed by Ref. [16] is the following. First, notice that the oracle function f_λ can be encoded in a projector final Hamiltonian as shown in Eq. (13) and acting on two subsystems, A and B, comprising n -qubits and 1-qubit, respectively,

$$H_1 = \mathbb{I}_A \otimes \mathbb{I}_B - \Pi_{\Phi_1}, \quad \Pi_{\Phi_1} = \sum_{z \in \{0,1\}^n} |z\rangle_A \langle z| \otimes |f_\lambda(z)\rangle_B \langle f_\lambda(z)|. \quad (\text{S7})$$

The ground state of H_1 is $|\Phi_1\rangle = \frac{1}{\sqrt{2^n}} \sum_{z \in \{0,1\}^n} |z\rangle_A \otimes |f_\lambda(z)\rangle_B$ with eigenvalue 0. The initial state is again the uniform superposition state (12), $|\Phi_0\rangle = |+\rangle_A^{\otimes n} \otimes |+\rangle_B$. We refer to Refs. [10, 16] for further details on the mechanism behind this adiabatic algorithm. For our purpose, we proceed to use the formula (11) to obtain a lower bound on the runtime. We first note that H_1 defined in Eq. (S7) is apparently a projector, $H_1^2 = H_1$. The remaining task is to compute $\langle \Phi_0 | H_1 | \Phi_0 \rangle$,

$$\begin{aligned} \langle \Phi_0 | H_1 | \Phi_0 \rangle &= 1 - \frac{1}{2^n} \sum_{x,y,z \in \{0,1\}^n} \langle x|z\rangle \langle z|y\rangle \langle +|f_\lambda(z)\rangle \langle f_\lambda(z)|+ \rangle \\ &= 1 - \frac{1}{2^n} \sum_{z \in \{0,1\}^n} |\langle +|f_\lambda(z)\rangle|^2 \stackrel{(*)}{=} 1 - \frac{1}{2^n} \sum_{z \in \{0,1\}^n} \left(\frac{1}{\sqrt{2}} \right)^2 = \frac{1}{2}, \end{aligned} \quad (\text{S8})$$

where in (*) we have used the following identity, $|f_\lambda(z)\rangle_B = \frac{1}{\sqrt{2}} (|+\rangle_B + (-1)^{f_\lambda(z)} |-\rangle_B)$. Finally, it follows from Eq. (11) that $T_{\text{inf}} = \mathcal{O}(1)$ as expected.

S4. DETAIL CALCULATION FOR ADIABATIC GROVER SEARCH

Consider a set of N items among which $M < N$ items are marked, the goal being to find marked items in minimum time. We use n qubits to encode the N items. Hence, the Hilbert space is of dimension $N = 2^n$. In this space, the basis states can be written as $|i\rangle$ with $i \in \{0, \dots, N-1\}$. The desired final state is $|\Phi_1\rangle = \frac{1}{\sqrt{M}} \sum_{m \in \mathcal{M}} |m\rangle$, and the corresponding final Hamiltonian can be chosen as a projector, $H_1 = \mathbb{I} - \sum_{m \in \mathcal{M}} |m\rangle \langle m|$, where \mathcal{M} is the space of solution (of size M). One can easily see that the ground state of H_1 is $|\Phi_1\rangle$ with eigenenergy zero.

The remaining task is to calculate the quantum uncertainty δV_n (6) with $|\Phi_0\rangle$ given by the uniform superposition state (12). First, we calculate the overlap $|\langle \Phi_1 | \Phi_0 \rangle|^2$,

$$|\langle \Phi_1 | \Phi_0 \rangle|^2 = \left| \left(\frac{1}{\sqrt{M}} \sum_{m \in \mathcal{M}} \langle m| \right) \left(\frac{1}{\sqrt{N}} \sum_{i=0}^{N-1} |i\rangle \right) \right|^2 = \frac{1}{MN} \left| \sum_{m \in \mathcal{M}} \sum_{i=0}^{N-1} \langle m|i\rangle \right|^2 = \frac{M}{N}. \quad (\text{S9})$$

We then obtain $\langle \Phi_0 | H_1 | \Phi_0 \rangle = 1 - |\langle \Phi_1 | \Phi_0 \rangle|^2 = 1 - \frac{M}{N}$. Bring this result to Eq. (11) yields $T_{\text{inf}} = \mathcal{O}(\sqrt{N/M})$.

S5. DETAIL CALCULATION FOR ADIABATIC ALGORITHM OF FINDING K-CLIQUE IN RANDOM GRAPHS

We want to calculate $\langle \Phi_0 | H_1 | \Phi_0 \rangle =: \overline{h_C}$ and $\langle \Phi_0 | H_1^2 | \Phi_0 \rangle =: \overline{h_C^2}$, where

$$\overline{h_C} = \frac{1}{C(n,k)} \sum_{z \in \{0,1\}^n: |z|=k} h_C(z) \quad \text{and} \quad \overline{h_C^2} = \frac{1}{C(n,k)} \sum_{z \in \{0,1\}^n: |z|=k} h_C^2(z), \quad (\text{S10})$$

with the cost function $h_C(z) = \sum_{i>j} (1 - G_{ij}) z_i z_j$ as defined in Eq. (22). To conduct the calculation, one encounters terms like $\sum_{i>j} G_{ij}$, which cannot be done generically without knowing the explicit form of G_{ij} . We attempt a ‘‘mean-field’’ approach by considering the ‘‘average property’’ of G_{ij} since each pair of vertices has probability p to be connected and probability $(1-p)$ otherwise. Note that p is 1/2 in the main text.

A. Mean-field approach

We shall approximate G_{ij} by its expected value, $\mathbb{E}[G_{ij}]$. Specifically, since each $G_{ij} = 1$ with probability p and $G_{ij} = 0$ with probability $1 - p$, we obtain

$$\mathbb{E}[G_{ij}] = p. \quad (\text{S11})$$

We now compute $\overline{h_C}$ (S10),

$$\begin{aligned} \overline{h_C} &= \frac{1}{C(n, k)} \sum_{z \in \{0,1\}^n: |z|=k} \sum_{i>j} (1 - G_{ij}) z_i z_j \\ &\approx \mathbb{E}[\overline{h_C}] \\ &= \frac{1}{C(n, k)} \sum_{z \in \{0,1\}^n: |z|=k} \sum_{i>j} (1 - \mathbb{E}[G_{ij}]) z_i z_j \\ &= \frac{1}{C(n, k)} \left(\sum_{z \in \{0,1\}^n: |z|=k} \sum_{i>j} z_i z_j - \sum_{z \in \{0,1\}^n: |z|=k} \sum_{i>j} \mathbb{E}[G_{ij}] z_i z_j \right). \end{aligned} \quad (\text{S12})$$

There are $C(n, k)$ states $|z\rangle$ satisfy $|z| = k$ that we have to consider. For each such state, there are k 's z_i for which $z_i = 1$. Therefore, the first term in the parenthesis of Eq. (S12) is simply

$$\sum_{z \in \{0,1\}^n: |z|=k} \sum_{i>j} z_i z_j = \sum_{z \in \{0,1\}^n: |z|=k} C(k, 2) = C(n, k) C(k, 2) = C(n, k) L_k. \quad (\text{S13})$$

Here, for notational convenience, we define $L_k \equiv C(k, 2)$. The second term in the parenthesis of Eq. (S12) can be calculated with the help of Eq. (S11)

$$\sum_{z \in \{0,1\}^n: |z|=k} \sum_{i>j} \mathbb{E}[G_{ij}] z_i z_j = p C(n, k) L_k. \quad (\text{S14})$$

Bring Eqs. (S13) and (S14) back to Eq. (S12) yields

$$\mathbb{E}[\overline{h_C}] = (1 - p) L_k. \quad (\text{S15})$$

Next, we compute $\overline{h_C^2}$ (S10),

$$\begin{aligned} \overline{h_C^2} &= \frac{1}{C(n, k)} \sum_{z \in \{0,1\}^n: |z|=k} \sum_{i'>j'} \sum_{i>j} (1 - 2G_{ij} + G_{i'j'} G_{ij}) z_{i'} z_{j'} z_i z_j \\ &\approx \mathbb{E}[\overline{h_C^2}] \\ &= \frac{1}{C(n, k)} \sum_{z \in \{0,1\}^n: |z|=k} \sum_{i'>j'} \sum_{i>j} \left(1 - 2\mathbb{E}[G_{ij}] + \mathbb{E}[G_{i'j'} G_{ij}] \right) z_{i'} z_{j'} z_i z_j. \end{aligned} \quad (\text{S16})$$

There are three terms in the parenthesis of Eq. (S16). The first term is deterministic,

$$\sum_{z \in \{0,1\}^n: |z|=k} \sum_{i'>j'} \sum_{i>j} z_{i'} z_{j'} z_i z_j = \sum_{z \in \{0,1\}^n: |z|=k} \left(\sum_{i'>j'} z_{i'} z_{j'} \right) \left(\sum_{i>j} z_i z_j \right) = \sum_{z \in \{0,1\}^n: |z|=k} L_k L_k = C(n, k) L_k^2. \quad (\text{S17})$$

The second term in the parenthesis of Eq. (S16) reads

$$\begin{aligned} \sum_{z \in \{0,1\}^n: |z|=k} \sum_{i'>j'} \sum_{i>j} (-2\mathbb{E}[G_{ij}]) z_{i'} z_{j'} z_i z_j &= -2 \sum_{z \in \{0,1\}^n: |z|=k} \left(\sum_{i'>j'} z_{i'} z_{j'} \right) \left(\sum_{i>j} \mathbb{E}[G_{ij}] z_i z_j \right) \\ &\stackrel{(\text{S11})}{=} -2 \sum_{z \in \{0,1\}^n: |z|=k} \left(\sum_{i'>j'} z_{i'} z_{j'} \right) \left(\sum_{i>j} p z_i z_j \right) = -2p C(n, k) L_k^2. \end{aligned} \quad (\text{S18})$$

Before proceed to calculate the third term in the parenthesis of Eq. (S16), we notice the following decomposition property

$$\begin{aligned}
\sum_{i'>j'} \sum_{i>j} \mathbb{E} [G_{i'j'} G_{ij}] &= \sum_{i>j} \mathbb{E} [G_{ij} G_{ij}] + \sum_{i'>j', i>j: i \neq i', j \neq j'} \mathbb{E} [G_{i'j'} G_{ij}] \\
&= \sum_{i>j} \mathbb{E} [G_{ij}^2] + \sum_{i'>j', i>j: i \neq i', j \neq j'} \mathbb{E} [G_{i'j'}] \mathbb{E} [G_{ij}] \\
&= \sum_{i>j} p + \sum_{i'>j', i>j: i \neq i', j \neq j'} p^2 = L_k p + (L_k^2 - L_k) p^2.
\end{aligned} \tag{S19}$$

Finally, the third term in the parenthesis of Eq. (S16) is

$$\sum_{z \in \{0,1\}^n: |z|=k} \left(\sum_{i'>j'} \sum_{i>j} \mathbb{E} [G_{i'j'} G_{ij}] z_{i'} z_{j'} z_i z_j \right) \stackrel{(S19)}{=} p C(n, k) L_k^2 \left(p + \frac{(1-p)}{L_k} \right). \tag{S20}$$

Upon using the above results, Eq. (S16) reads

$$\mathbb{E}[\overline{h_C^2}] = \left(1 - 2p + p \left(p + \frac{1-p}{L_k} \right) \right) L_k^2 = (1-p)^2 L_k^2 + p(1-p) L_k. \tag{S21}$$

Hence, the quantum uncertainty reads $\delta V_n = \sqrt{p(1-p)L_k}$. It then follows from Eq. (8) a lower bound on runtime

$$T_{\text{inf}} = \mathcal{O} \left(\sqrt{1/L_k} \right), \tag{S22}$$

which is independent of n . Note that if the cost function $h_C(z)$ is rescaled as $h_C(z) \rightarrow h_C(z)/L_k$, one should find $T_{\text{inf}} = \mathcal{O}(\sqrt{L_k})$.

B. Combinatorial approach

In this section, we use an explicit combinatorial method to reproduce the same result as we found in Eq. (S22). The following observation is crucial:

- If a binary string z of Hamming weight k represents a graph that is a k -clique after adding α connected edges, then $h_C(z) = \alpha$, where $\alpha \in \{0, 1, \dots, C(k, 2)\}$.

For notational convenience, we define $L_k \equiv C(k, 2)$. Now the question is what is the multiplicity, m_α , for each possible value of cost function $h_C(z) = \alpha$. Since each of the L_k edges has probability p to be present if random graphs are generated uniformly, we expect

$$m_\alpha = p^{L_k - \alpha} (1-p)^\alpha C(L_k, \alpha) C(n, k), \quad \text{for } \alpha \in \{0, 1, \dots, L_k\}. \tag{S23}$$

One verifies that the sum of all multiplicity equals $C(n, k)$, i.e., the number of binary strings of Hamming weight k ,

$$\sum_{\alpha=0}^{L_k} m_\alpha = C(n, k) \underbrace{\sum_{\alpha=0}^{L_k} p^{L_k - \alpha} (1-p)^\alpha C(L_k, \alpha)}_{=(p+1-p)^{L_k}} = C(n, k). \tag{S24}$$

We proceed to compute $\mathbb{E}[\overline{h_C}]$,

$$\mathbb{E}[\overline{h_C}] = \frac{1}{C(n, k)} \sum_{\alpha=0}^{L_k} m_\alpha \alpha = \sum_{\alpha=0}^{L_k} p^{L_k - \alpha} (1-p)^\alpha C(L_k, \alpha) \alpha = (1-p) L_k, \tag{S25}$$

which is the same as Eq. (S15). We then compute $\mathbb{E}[\overline{h_C^2}]$,

$$\mathbb{E}[\overline{h_C^2}] = \frac{1}{C(n, k)} \sum_{\alpha=0}^{L_k} m_\alpha \alpha^2 = \sum_{\alpha=0}^{L_k} p^{L_k - \alpha} (1-p)^\alpha C(L_k, \alpha) \alpha^2 = (1-p)^2 L_k^2 + p(1-p) L_k, \tag{S26}$$

which is identical to Eq. (S21).