Lattice Linear Predicate Algorithms for the Constrained Stable Marriage Problem with Ties*

Vijay K. Garg The University of Texas at Austin Austin, Texas, USA garg@ece.utexas.edu

ABSTRACT

We apply Lattice-Linear Predicate Detection Technique to derive parallel and distributed algorithms for various variants of the stable matching problem. These problems are: (a) the constrained stable marriage problem (b) the super stable marriage problem in presence of ties, and (c) the strongly stable marriage in presence of ties. All these problems are solved using the Lattice-Linear Predicate (LLP) algorithm showing its generality. The constrained stable marriage problem is a version of finding the stable marriage in presence of lattice-linear constraints such as "Peter's regret is less than that of Paul." For the constrained stable marriage problem, we present a distributed algorithm that takes $O(n^2)$ messages each of size $O(\log n)$ where *n* is the number of men in the problem. Our algorithm is completely asynchronous. Our algorithms for the stable marriage problem with ties are also parallel with no synchronization.

ACM Reference Format:

Vijay K. Garg. 2023. Lattice Linear Predicate Algorithms for the Constrained Stable Marriage Problem with Ties. In *Proceedings of ICDCN'2023 (ICDCN'23)*. ACM, New York, NY, USA, 10 pages. https://doi.org/10.1145/nnnnnnnnnnnnn

1 INTRODUCTION

The Lattice-Linear Predicate (LLP) algorithm [12] is a general technique for designing parallel algorithms for combinatorial optimization problems. In [12], it is shown that the stable marriage problem, the shortest path problem in a graph, and the assignment problem can all be solved using the LLP algorithm. In [14], many dynamic programming problems, in [13], the housing problem, and in [1], it is shown that the minimum spanning tree problem can be solved using the LLP algorithm. In [17], Gupta and Kulkarni extend LLP algorithms for deriving self-stabilizing algorithms. In this paper, we show that many generalizations of the stable matching problem can also be solved using the LLP algorithm. A forthcoming book on parallel algorithms [15] gives a uniform description of these and other problems that can be solved using the LLP algorithm.

The Stable Matching Problem (SMP) [9] has wide applications in economics, distributed computing, resource allocation and many

ICDCN'23, January 2023, Kharagpur, India

© 2023 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-x/YY/MM...\$15.00

https://doi.org/10.1145/nnnnnnnnnnn

other fields [21, 25]. In the standard SMP, there are *n* men and *n* women each with their totally ordered preference list. The goal is to find a matching between men and women such that there is no instability, i.e., there is no pair of a woman and a man such that they are not married to each other but prefer each other over their partners. In this paper, we show that LLP algorithm can be used to derive solutions to a more general problem than SMP, called constrained SMP. In our formulation, in addition to men's preferences and women's preferences, there may be a set of *lattice-linear* constraints on the set of marriages consistent with men's preferences. For example, we may state that Peter's regret [18] should be less than that of Paul, where the regret of a man in a matching is the choice number he is assigned. As another example, we may require the matching must contain some pairs called forced pairs, or must not contain some pairs called forbidden pairs [7]. We call such constraints external constraints. Any algorithm to solve constrained SMP can solve standard SMP by setting (external) constraints to the empty set.

In this paper, we also present a distributed algorithm to solve the constrained SMP in an asynchronous system. One of the goals is to show how a parallel LLP algorithm can be converted into a distributed asynchronous algorithm. Our distributed algorithm uses a diffusing computation whose termination is detected using a standard algorithm such as the Dijkstra-Scholten algorithm. The algorithm uses $O(n^2)$ messages each of size $O(\log n)$. Kipnis and Patt-Shamir [23] have given a distributed algorithm for stable matching in a synchronous system. There are many differences with their work. First, they do not consider external constraints and their work is not easily extensible for incorporating external constraints. Second, for termination detection, they require each rejected node to broadcast the fact that the protocol has not terminated on a shortest-path tree. This step requires the assumption of synchrony for termination detection and incurs additional message overhead. Our algorithm avoids such broadcasts and works for asynchronous systems. Their paper suggests use of α synchronizer [2] for simulating in asynchronous systems. However, each round adds $O(n^2)$ messages for using α synchronizer. Thus, our algorithm not only solves a more general problem, it is also more efficient for running the traditional SMP in an asynchronous system.

We also consider the generalizations of the stable matching problem to the case when the preference lists may have ties. The problem of stable marriage with ties is clearly more general than the standard stable matching problem and has also been extensively studied [6, 18, 20]. We consider three versions of matching with ties. In the first version, called *weakly stable* matching M, there is no blocking pair of man and woman (m, w) who are not married in Mbut strictly prefer each other to their partners in M. In the second

^{*}partially supported by NSF CNS-1812349, and the Cullen Trust for Higher Education Endowed Professorship

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

version, called *superstable* matching M, we require that there is no blocking pair of man and woman (m, w) who are not married in M but either (1) both of them prefer each other to their partners in M, or (2) one of them prefers the other over his/her partner in M and the other one is indifferent, or (3) both of them are indifferent to their spouses. The third version, called *strongly stable matching*, we require that if there is no blocking pair (m, w) such that they are not married in M but either (1) both of them prefer each other to their partners in M, or (2) one of them prefers the other over his/her partner in M and the other one is indifferent. Algorithms for these problems are well-known; our goal is to present LLP algorithms for these problems.

2 BACKGROUND: LATTICE-LINEAR PREDICATE DETECTION ALGORITHM

In this section, we give a self-contained description of the Lattice-Linear Predicate detection algorithm. The reader should consult [12] for more details. Let *L* be the lattice of all *n*-dimensional vectors of reals greater than or equal to zero vector and less than or equal to a given vector *T* where the order on the vectors is defined by the component-wise natural \leq . The lattice is used to model the search space of the combinatorial optimization problem. The combinatorial optimization problem is modeled as finding the minimum element in *L* that satisfies a boolean *predicate B*, where *B* models *feasible* (or acceptable solutions). We are interested in parallel algorithms to solve the combinatorial optimization problem with *n* processes. We will assume that the systems maintains as its state the current candidate vector $G \in L$ in the search lattice, where G[i]is maintained at process *i*. We call *G*, the global state, and G[i], the state of process *i*.

Fig. 1 shows a finite poset corresponding to *n* processes (*n* equals two in the figure), and the corresponding lattice of all eleven global states.




Figure 1: A poset and its corresponding distributive lattice L

Finding an element in lattice that satisfies the given predicate B, is called the *predicate detection* problem. Finding the *minimum* element that satisfies B (whenever it exists) is the combinatorial optimization problem. A key concept in deriving an efficient predicate detection algorithm is that of a *forbidden* state. Given a predicate B, and a vector $G \in L$, a state G[j] is *forbidden* (or equivalently, the index j is forbidden) if for any vector $H \in L$, where $G \leq H$, if H[j] equals G[j], then B is false for H. Formally,

Definition 2.1 (Forbidden State [4]). Given any distributive lattice *L* of *n*-dimensional vectors of $\mathbb{R}_{\geq 0}$, and a predicate *B*, we define forbidden(*G*, *j*, *B*) $\equiv \forall H \in L : G \leq H : (G[j] = H[j]) \Rightarrow \neg B(H)$.

We define a predicate B to be *lattice-linear* with respect to a lattice L if for any global state G, B is false in G implies that G contains a *forbidden state*. Formally,

Definition 2.2 (lattice-linear Predicate [4]). A boolean predicate *B* is *lattice-linear* with respect to a lattice *L* iff $\forall G \in L : \neg B(G) \Rightarrow (\exists j : \text{forbidden}(G, j, B)).$

Once we determine j such that forbidden(G, j, B), we also need to determine how to advance along index j. To that end, we extend the definition of forbidden as follows.

Definition 2.3 (α -forbidden). Let *B* be any boolean predicate on the lattice *L* of all assignment vectors. For any *G*, *j* and positive real $\alpha > G[j]$, we define forbidden(*G*, *j*, *B*, α) iff

$$\forall H \in L : H \ge G : (H[j] < \alpha) \Longrightarrow \neg B(H).$$

Given any lattice-linear predicate *B*, suppose $\neg B(G)$. This means that *G* must be advanced on all indices *j* such that forbidden(*G*, *j*, *B*). We use a function $\alpha(G, j, B)$ such that forbidden(*G*, *j*, *B*, $\alpha(G, j, B)$) holds whenever forbidden(*G*, *j*, *B*) is true. With the notion of $\alpha(G, j, B)$, we have the Algorithm *LLP*. The algorithm *LLP* has two inputs the predicate *B* and the top element of the lattice *T*. It returns the least vector *G* which is less than or equal to *T* and satisfies *B* (if it exists). Whenever *B* is not true in the current vector *G*, the algorithm advances on all forbidden indices *j* in parallel. This simple parallel algorithm can be used to solve a large variety of combinatorial optimization problems by instantiating different forbidden(*G*, *j*, *B*) and $\alpha(G, j, B)$.

ALGORITHM LLP: Find the minimum vector at most <i>T</i> that satisfies
В
vector function getLeastFeasible(<i>T</i> : vector, <i>B</i> : predicate)
var <i>G</i> : vector of reals initially $\forall i : G[i] = 0$;
while $\exists j$: forbidden(G, j, B) do
for all j such that forbidden (G, j, B) in parallel:
if $(\alpha(G, j, B) > T[j])$ then return null;
else $G[j] := \alpha(G, j, B);$
endwhile;
return <i>G</i> ; // the optimal solution

The following Lemma is useful in proving lattice-linearity of predicates.

LEMMA 2.4. [4, 12] Let B be any boolean predicate defined on a lattice L of vectors.

(a) Let $f : L \to \mathbb{R}_{\geq 0}$ be any monotone function defined on the lattice L of vectors of $\mathbb{R}_{\geq 0}$. Consider the predicate $B \equiv G[i] \geq f(G)$ for some fixed *i*. Then, B is lattice-linear.

(b) If B_1 and B_2 are lattice-linear then $B_1 \wedge B_2$ is also lattice-linear.

We now give an example of lattice-linear predicates for scheduling of *n* jobs. Each job *j* requires time t_j for completion and has a set of prerequisite jobs, denoted by pre(j), such that it can be started only after all its prerequisite jobs have been completed. Our goal is to find the minimum completion time for each job. We let our lattice *L* be the set of all possible completion times. A completion vector $G \in L$ is feasible iff $B_{jobs}(G)$ holds where $B_{jobs}(G) \equiv \forall j : (G[j] \ge t_j) \land (\forall i \in pre(j) : G[j] \ge G[i] + t_j)$. B_{jobs} is lattice-linear because if it is false, then there exists *j* such that either $G[j] < t_j$ or $\exists i \in pre(j) : G[j] < G[i] + t_j$. We claim that forbidden(G, j, B_{jobs}). Indeed, any vector $H \ge G$ cannot be feasible with G[j] equal to H[j]. The minimum of all vectors that satisfy feasibility corresponds to the minimum completion time.

As an example of a predicate that is not lattice-linear, consider the predicate $B \equiv \sum_j G[j] \ge 1$ defined on the space of two dimensional vectors. Consider the vector *G* equal to (0, 0). The vector *G* does not satisfy *B*. For *B* to be lattice-linear either the first index or the second index should be forbidden. However, none of the indices are forbidden in (0, 0). The index 0 is not forbidden because the vector H = (0, 1) is greater than *G*, has H[0] equal to G[0] but it still satisfies *B*. The index 1 is also not forbidden because H = (1, 0) is greater than *G*, has H[1] equal to G[1] but it satisfies *B*.

We now go over the notation used in description of our parallel algorithms. Fig. 2 shows a parallel algorithm for the job-scheduling problems.

The **var** section gives the variables of the problem. We have a single variable G in the example shown in Fig. 2. G is an array of objects such that G[j] is the state of thread j for a parallel program.

The **input** section gives all the inputs to the problem. These inputs are constant in the program and do not change during execution.

The **init** section is used to initialize the state of the program. All the parts of the program are applicable to all values of j. For example, the *init* section of the job scheduling program in Fig. 2 specifies that G[j] is initially t[j]. Every thread j would initialize G[j].

The **always** section defines additional variables which are derived from *G*. The actual implementation of these variables are left to the system. They can be viewed as macros. We will show its use later.

The LLP algorithm gives the desirable predicate either by using the **forbidden** predicate or **ensure** predicate. The *forbidden* predicate has an associated *advance* clause that specifies how G[j]must be advanced whenever the forbidden predicate is true. For many problems, it is more convenient to use the complement of the forbidden predicate. The *ensure* section specifies the desirable predicates of the form $(G[j] \ge expr)$ or $(G[j] \le expr)$. The statement *ensure* $G[j] \ge expr$ simply means that whenever thread j finds G[j] to be less than expr; it can advance G[j] to expr. Since expr may refer to G, just by setting G[j] equal to expr, there is no guarantee that G[j] continues to be equal to expr — the value of expr may change because of changes in other components. We use *ensure* statement whenever expr is a monotonic function of G and therefore the predicate is lattice-linear.

3 A PARALLEL ALGORITHM FOR THE CONSTRAINED STABLE MATCHING PROBLEM

We now derive the algorithm for the stable matching problem using Lattice-Linear Predicates [11]. We let G[i] be the choice number that man *i* has proposed to. Initially, G[i] is 1 for all men.

Definition 3.1. An assignment *G* is feasible for the stable marriage problem if (1) it corresponds to a perfect matching (all men are paired with different women) and (2) it has no blocking pairs.




Figure 2: LLP Parallel Program for (a) job scheduling problem using forbidden predicate (b) job scheduling problem using ensure clause and (c) the shortest path problem

The predicate "*G* is a stable marriage" is a lattice-linear predicate [12] which immediately gives us LLP-ManOptimalStableMarriage. The **always** section defines variables which are derived from *G*. These variables can be viewed as macros. For example, for any thread z = mpref[j][G[j]]. This means that whenever G[j] changes, so does *z*. If man *j* is forbidden, it is clear that any vector in which man *j* is matched with *z* and the other man *i* is matched with his current or a worse choice can never be a stable marriage. Thus, it is safe for man *j* to advance to the next choice.

ALGORITHM LLP-ManOptimalStableMarriage: A Parallel Algo-
rithm for Stable Matching
P_j : Code for thread j
input : <i>mpref</i> [<i>i</i> , <i>k</i>]: int for all <i>i</i> , <i>k</i> ; <i>wrank</i> [<i>k</i>][<i>i</i>]: int for all <i>k</i> , <i>i</i> ;
init : $G[j] := 1;$
always : $z = mpref[j][G[j]];$
forbidden:
$\exists i : \exists k \leq G[i] : (z = mpref[i][k]) \land (wrank[z][i] < $
wrank[z][j])
advance : $G[j] := G[j] + 1;$

We now generalize LLP-ManOptimalStableMarriage algorithm to solve the constrained stable marriage problem. In the standard stable matching problem, there are no constraints on the order of proposals made by different men. Let *E* be the set of proposals made by men to women. We also call these proposals *events* which are executed by *n* processes corresponding to *n* men denoted by $\{P_1 \dots P_n\}$. Each of the events can be characterized by a tuple (i, j)that corresponds to the proposal made by man *i* to woman *j*. We impose a partial order \rightarrow_p on this set of events to model the order in which these proposals can be made. In the standard SMP, every man P_i has its preference list mpref[i] such that mpref[i][k] gives the k^{th} most preferred woman for P_i . We model mpref using \rightarrow_p ; if P_i prefers woman *j* to woman *k*, then there is an edge from the event (i, j) to the event (i, k). As in SMP, we assume that every man gives a total order on all women. Each process makes proposals to women in the decreasing order of preferences (similar to Gale-Shapley algorithm).

In the standard stable matching problem, there are no constraints on the order of proposals made by different men, and \rightarrow_p can be visualized as a partial order (E, \rightarrow_p) with *n* disjoint chains. We generalize the SMP problem to include external constraints on the set of proposals. In the constrained SMP, \rightarrow_p can relate proposals made by different men and therefore \rightarrow_p forms a general poset (E, \rightarrow_p) . For example, the constraint that Peter's regret is less than or equal to John can be modeled by adding \rightarrow_p edges as follows. For any regret *r*, we add an \rightarrow_p edge from the proposal by John with regret *r* to the proposal by Peter with regret *r*. We draw \rightarrow_p edges in solid edges as shown in Fig. 5.

Let $G \subseteq E$ denote the global state of the system. A global state G is simply the subset of events executed in the computation such that it preserves the order of events within each P_i . Since all events executed by a process P_i are totally ordered, it is sufficient to record the number of events executed by each process in a global state. Let G[i] be the number of proposal made by P_i . Initially, G[i] is 1 for all men. If P_i has made G[i] > 0 proposals, then mpref[i][G[i]] gives the identity of the woman last proposed by P_i . We let event(i, G[i]) denote the event in which P_i makes a proposal to mpref[i][G[i]]. We also use succ(event(i, G[i])) to denote the next proposal made by P_i , if any.

For the constrained SMP, we have \rightarrow_p edges that relate proposals of different processes. The graph in Fig. 5 shows an example of using \rightarrow_p edges in the constrained SMP. For this problem, we work with *consistent global states* (or order ideals [5, 10]). A global state $G \subseteq E$ is *consistent* if $\forall e, f \in E : (e \rightarrow_p f) \land (f \in G) \Rightarrow (e \in G)$. In the context of constrained SMP, it is easy to verify that *G* is consistent iff or all *j*, there does not exist *i* such that

$$succ(event(j, G[j])) \rightarrow_{p} event(i, G[i]).$$

It is well known that the set of all consistent global states of a finite poset forms a finite distributive lattice [5, 10]. We use the lattice of all consistent global states as L for the predicate detection.

In the standard SMP, women's preferences are specified by preference lists *wpref* such that *wpref*[*i*][*k*] gives the k^{th} most preferred man for woman *i*. It is also convenient to define *wrank* such that *wrank*[*i*][*j*] gives the choice number *k* for which *wpref*[*i*][*k*] equals *j*, i.e., *wpref*[*i*][*k*] = *j* iff *wrank*[*i*][*j*] = *k*. We model these preferences using edges on the computation graph as follows. If an event *e* corresponds to a proposal by P_i to woman *q* and she prefers P_j , then we add a dashed edge from *e* to the event *f* that corresponds to P_j proposing to woman *q*. The set *E* along with the dashed edges also forms a partial order (E, \rightarrow_w) where $e \rightarrow_w f$ iff both proposals are to the same woman and that woman prefers the proposal *f* to *e*. With $((E, \rightarrow_p), \rightarrow_w)$ we can model any SMP specified using *mpref* and *wpref*.

Figure 4 gives an example of a standard SMP problem in Fig. 3 in our model. To avoid cluttering the figure, we have shown preferences of all men but preferences of only two of the women. Fig 5 gives an example of a constrained SMP. Since both \rightarrow_p and \rightarrow_w are transitive relations, we draw only the transitively reduced diagrams.

The above discussion motivates the following definition.

Vijay K. Garg

mpref					wpref				
P1	w4	w1	w2 w1 w4	w3	w1	P4	P1	P3	P2
P2	w2	w3	w1	w4	w2	P1	P4	P2	P3
P3	w3	w1	w4	w2	w3	P1	P2	P4	P3
P4	w2	w4	w3	w1	w4	P3	P1	P4	P2

Figure 3: Stable Matching Problem specified using men preference list (mpref) and women preference list (wpref).




Figure 4: Men preferences are shown in blue solid edges. Preferences of women 1 and 2 are shown in dashed green edges. In the standard SMP graph, there are no blue edges from any event in P_i to any event in P_j for distinct *i* and *j*.

Definition 3.2 (Constrained SMP Graph). Let $E = \{(i, j) | i \in [1..n] \text{ and } j \in [1..n]\}$. A Constrained SMP Graph $((E, \rightarrow_p), \rightarrow_w)$ is a directed graph on E with two sets of edges \rightarrow_p and \rightarrow_w with the following properties: (1) (E, \rightarrow_p) is a poset such that the set $P_i = \{(i, j) | j \in [1..n]\}$ is a chain for all i, and (2) (E, \rightarrow_w) is a poset such that the set $Q_j = \{(i, j) | i \in [1..n]\}$ is a chain for all j and there is no \rightarrow_w edge between proposals to different women, i.e., for all $i, j, k, l : (i, j) \rightarrow_w (k, l) \Rightarrow (j = l)$.

Given a global state *G*, we define the *frontier* of *G* as the set of maximal events executed by any process. The frontier includes only the last event executed by P_i (if any). Formally, frontier(*G*) = { $e \in G \mid \forall f \in G$ such that $f \neq e$, *f* and *e* are executed by P_i implies $f \rightarrow_p e$ }. We call the events in *G* that are not in frontier(*G*) as pre-frontier events.

We now define the feasible predicate on global states as follows.

Definition 3.3 (feasibility for marriage). A global state *G* is feasible for marriage iff (1) *G* is a consistent global state, and (2) there is no dashed edge (\rightarrow_w) from a frontier event to any event of *G* (frontier or pre-frontier). Formally, $B_{marriage}(G) \equiv$

 $consistent(G) \land (\forall e \in frontier(G), \forall g \in G : \neg(e \rightarrow_w g).$




Figure 5: Constrained SMP Graph corresponding to constraint that the *regret* for P_2 is less than or equal to that of P_1 . It also shows the preference of w_3 of P_4 over P_3 .

It is easy to verify that the problem of finding a stable matching is the same as finding a global state that satisfies the predicate $B_{marriage}$ which is defined purely in graph-theoretic terms on the constrained SMP graph. The next task is to show that $B_{marriage}$ is lattice-linear.

THEOREM 3.4. For any global state G that is not a constrained stable matching, there exists i such that $forbidden(G, i, B_{marriage})$.

PROOF. First suppose that *G* is not consistent, i.e., there exists $f \in G$ such that there exists $e \notin G$ and $e \rightarrow_p f$. Suppose that *e* is on P_i . Then, forbidden(*G*, *i*, *B*) holds because any global state *H* that is greater than *G* cannot be consistent unless *e* is included.

Next, suppose that *G* is a consistent global state but the assignment for *G* is not a matching. This means that for some distinct *i* and *j*, both *G*[*i*] and *G*[*j*] refer to the same woman, say *w*. Suppose that *w* prefers *j* to *i*, then we claim forbidden(*G*, *i*, *B*). Consider any *H* such that H[i] = G[i] and $H[j] \ge G[j]$. First consider the case H[j] = G[j]. In this case, the same woman *w* is still assigned to two men and hence *H* is not a stable matching. Now consider the case H[j] > G[j]. In this case, the woman *w* prefers man *j* to *i*, and the man *j* prefers *w* to the woman assigned in H[j] violating stability.

Now suppose that the assignment for *G* is a constrained matching but not stable. Suppose that (j, w) is a blocking pair in *G*. Let *i* be assigned to *w* in *G* (i.e., the woman corresponding to *G*[*i*] prefers man *j* to *i*, and the man *j* also prefers her to his assignment). We claim that forbidden(*G*, *i*, *B*). Consider any *H* such that H[i] =G[i] and $H[j] \ge G[j]$. In this case, (j, w) continues to be blocking in *H*. The woman *w* prefers man *j* to *i*, and the man *j* prefers *w* to the woman assigned in H[j]. We now apply the detection of lattice-linear global predicates for the constrained stable matching.

ALGORITHM LLP-ConstrainedStableMarriage: A Parallel Algo-
rithm for the Constrained Stable Matching
P_j : Code for thread j
input : <i>mpref</i> [<i>i</i> , <i>k</i>]: int for all <i>i</i> , <i>k</i> ; <i>wrank</i> [<i>k</i>][<i>i</i>]: int for all <i>k</i> , <i>i</i> ;
init : $G[j] := 1;$
always : $z = mpref[j][G[j]];$
forbidden:
$\exists i : \exists k \leq G[i] : (z = mpref[i][k]) \land (wrank[z][i] <$
$wrank[z][j]) \lor (\exists i : succ(event(j, G[j])) \rightarrow_p event(i, G[i]))$
advance : if $(G[j] < n)$ then $G[j] := G[j] + 1$;
else print("no constrained stable marriage")

The algorithm to find the man-optimal constrained stable marriage is shown in Fig. LLP-ConstrainedStableMarriage. From the proof of Theorem 3.4, we get the following implementation of forbidden(G, j, $B_{marriage}$) in Fig. LLP-ConstrainedStableMarriage. The first disjunct holds when the woman z assigned to man j is such that there exists a man i who is either (1) currently assigned to z and woman z prefers man i, or (2) currently assigned to another woman but he prefers z to the current assignment. The first case holds when k = G[i] and the second case holds when k < G[i]. The first case is equivalent to checking if a dashed edge exists from (j, z) to a frontier event. The second case is equivalent to checking if a dashed edge exists to a pre-frontier event. The second disjunct checks that the assignment for G satisfies all external constraints with respect to j.

Our algorithm generalizes the Gale-Shapley algorithm in that it allows specification of external constraints.

We now show an execution of the algorithm on the CSMP in Fig. 5. Since every P_i must make at least one proposal, we start with the first proposal for every P_i . The corresponding assignment is $[w_4, w_2, w_3, w_2]$, i.e., P_1 is assigned w_4 , P_2 is assigned w_2 and so on. In this global state G, the second component is forbidden. This is because w_2 prefers P_4 over P_2 . We advance on P_2 to get the global state $[w_4, w_3, w_3, w_2]$. Now, because w_3 prefers P_2 over P_3, P_3 must advance. We get the global state $[w_4, w_3, w_1, w_2]$. This is a stable matching. However, it does not satisfy the constraint that the regret of P_2 is less than or equal to that of P_1 . Here, P_1 is forbidden and P_1 must advance. We now get the global state $[w_1, w_3, w_1, w_2]$ which is not a matching. Since w_1 prefers P_1 over P_3, P_3 must advance. We reach the global state $[w_1, w_3, w_4, w_2]$ which satisfies the constrained stable matching.

We have discussed man-oriented constrained stable marriage problem. One can also get an LLP algorithm the for woman-oriented constrained stable marriage problem. The paper [16] gives an algorithm β that does the downward traversal in the proposal lattice in search of a stable marriage. When men and women are equal then such a traversal can be accomplished by switching the roles of men and women. However, in [16] is is assumed that the number of men n_m may be much smaller than the number of women n_w . It has the time complexity of $O(n_m^2 + n_w)$. Switching the roles of men and women is not feasible without increasing the complexity of the algorithm.

4 A DISTRIBUTED ALGORITHM FOR THE CONSTRAINED STABLE MATCHING PROBLEM

Although the standard SMP has been studied in a distributed system setting (e.g., [3, 22]), we study the constrained SMP in a distributed system setting. Our goal is to show how a parallel LLP algorithm can be converted to a distributed program. We assume an asynchronous system in which all channels are FIFO and reliable and that processes do not crash.

We assume that each man and woman knows only his or her preference lists. P_i corresponds to the computation at man i and Q_i corresponds to the computation at woman i. Each process P_i is responsible for updating its own component in G[i]. For the LLP algorithm, we will assume that the only variable at P_i is G and all other variables such as *mpref* are constants. In addition, each man is given a list of prerequisite proposals for each of the women that he can propose to. In terms of the constrained-SMP graph, this corresponds to every man knowing the incoming solid edges for the chain that corresponds to that man in the graph. From *mpref*, one can also derive *mrank*, the rank P_i assigns to each woman.

The process Q_i has *wpref*, preferences of woman *i*. However, it is more convenient to keep *wrank*, the rank Q_i assigns to each man. This information is input to Q_i . The only variable a woman Q_i maintains is the *partner*. Note that given *G*, the partner for each woman can be derived. However, in a distributed system setting it is more efficient to maintain the partner at each woman.

Whenever G[i] is updated by P_i , we will assume that P_i sends a message to other relevant processes informing them about the update. Each process keeps enough information to be able to evaluate its forbidden predicate. Since the message transfer takes time, the data structures are not necessarily up to date at each process. In particular P_j may have an old value of G[i] maintained at P_i . We show that the LLP algorithm has the advantage that it works correctly despite the fact that processes use old values of G. Each process evaluates its forbidden predicate and advances its state whenever the forbidden predicate is true. The algorithm terminates when no process is forbidden. In a distributed system setting, we need some process to determine that the system has reached such a state. A possible solution for running LLP algorithms in a distributed environment is to run it as a diffusing computation[8] and use a termination detection algorithm along with the LLP algorithm.

We now present a diffusing computation for solving the constrained SMP. We adopt the standard rules of a diffusing computation. A *passive* process can become *active* only on receiving messages, and only an active process can send a message. We assume the existence of a process called environment that starts the algorithm by sending *initiate* messages to all men. In our algorithm shown in Fig. 6,

There are four types of messages used in this algorithm. There are exactly *n* initiate messages sent by the environment to all men. Each man can send two types of messages. He sends *propose* messages to women one at a time in the order given by *mpref*. These messages are sent whenever the current state of the man is forbidden and he needs to advance to the next woman. A man may sometimes skip proposing some women as explained later. A man also sends

advance messages to other men which may force other men to skip certain proposals to satisfy external constraints.

A woman acts only when she receives a *propose* message from a man *j*. On receiving a *propose* message, if she is currently not engaged, she gets engaged to man *j*. If she is engaged to a man and the new proposal is preferable to her current partner then she sends a *reject* message to the current partner. If the new proposal is less preferable, then she sends a *reject* message to the proposer. The variable *partner* indicates her partner at any point. If the value of *partner* is zero, then that woman is free; otherwise, she is engaged. Note that a woman never sends any *accept* message. The algorithm is based on the assumption that if a woman has received a proposal and not rejected it, then she has accepted the message (the algorithm assumes that no messages are lost).

We now explain the behavior of men for each message type he receives as shown in Fig. 6. On receiving an initiate message from the environment, we know that any assignment must have at least one proposal from that man. To satisfy external constraints, all proposals that are prerequisite must also be made. Hence, the man sends an *advance* message to all men with prerequisite proposals. He then sends a proposal to his top choice. On receiving a reject message, he first checks if the reject message is from his current partner. Since a man may have advanced to a different proposal, there is no need for any action if the reject message is from an earlier proposal. If the *reject* message is for the current proposal, then the man knows that he must make another proposal. If he is out of proposals, then he announces that there is no stable marriage with external constraints. Otherwise, he moves on to the next best proposal after sending out advance messages to all men with prerequisite proposals. On receiving an advance message with woman w, the man must ensure that he has made a proposal to woman w. If he has already made a proposal to w, then there is nothing to be done; otherwise, he skips all proposals till he gets to his choice which corresponds to w. Next, he makes a proposal to w thereby satisfying external constraints.

Observe that when a man P_i advances, he does not inform his existing partner, if any. Since the number of men and women are same, his partner will eventually get a proposal from someone who she prefers to P_i if there exists a constrained stable matching. His partner q can never be matched with P_j such that q prefers P_i over P_j . Otherwise, we have a blocking pair: both q and P_i prefer each other over their partners.

If there are no external constraints, then there are no *advance* messages, and the algorithm is a distributed version of the Gale-Shapley algorithm. Even in the presence of external constraints, the algorithm shares the following properties with the Gale-Shapley algorithm. As the algorithms progress, the partner for a man can only get worse and the partner for a woman can only get better. Both these properties are direct results of the way men send their proposals and the way women respond to proposals.

There are also some crucial differences from the Gale-Shapley algorithm. In the Gale-Shapley algorithm, once a woman is engaged she continues to be engaged. For any woman w, the predicate that there exists a man such that he is assigned to w is a stable predicate. As a result, the termination of Gale-Shapley (sequential or distributed version) is easy to detect. When all women have been proposed to, the system has reached a stable matching. However,

Lattice Linear Predicate Algorithms for the Constrained Stable Marriage Problem with Ties

```
\begin{array}{l} P_{i::: // Process \text{ for Man } i \\ \textbf{input} \\ mpref: \operatorname{array}[1..n] \text{ of } 1..n; // \operatorname{men's preferences} \\ mrank: \operatorname{array}[1..n] \text{ of } 1..n; // \operatorname{rank } of each of the women by man} \\ // mrank can be derived from mpref \\ prerequisite: \operatorname{array}[1..n] \text{ of list of proposals;} \\ // \operatorname{list of proposals that must be executed before mpref[i]} \\ \textbf{var} \\ G_i: 1..n \text{ initially } 1; // \operatorname{proposal number by } P_i \\ \\ \text{Upon receiving a message "initiate" from environment;} \\ \text{ for each } (m, w) \in \operatorname{prerequisite}[G_i] \\ & \operatorname{send} ("advance", w) \operatorname{to} P_m; \\ & \operatorname{send} ("proposal", i) \operatorname{to woman mpref}[G_i]; \\ \end{array}
```

```
Upon receiving a message ("reject", j):

if (mpref[G_i] = j) then // rejected by current partner

if (G_i = n) then

Announce "no constrained stable marriage possible";

else

G_i := G_i + 1;

for each (m, w) \in prerequisite[G_i]

send ("advance", w) to P_m;
```

send ("*proposal*", *i*) to woman $mpref[G_i]$;

```
Upon receiving a message ("advance", q):

while (mrank[q] > G_i)

G_i := G_i + 1

for each (m, w) \in prerequisite[G_i]
```

```
send ("advance", w) to P<sub>m</sub>;
endwhile;
send ("proposal", i) to woman mpref[G<sub>i</sub>];
```

```
Q_i:: // Process for Woman i
```

input

wrank: array[1..n] of 1..n; // rank of each man by the woman ${\bf var}$

partner: 0..n; initially 0 // current partner

```
Upon receiving a message ("proposal", j):
if (partner = 0) then
    partner := j;
else if (wrank[j] < wrank[partner]) then
    send ("reject", i) to P<sub>partner</sub>;
    partner := j;
```

Environment::

Process that (1) initiates the diffusing computation and (2) detects Termination

send "initiate" message to all P_i

Upon Detecting Termination of Diffusing Computation Announce the current assignment as a stable marriage satisfying external constraints. Halt

Figure 6: A diffusing distributed computation algorithm for constrained SMP for men P_i and women Q_i

due to external constraints, it is not true in CSMP that once a woman is engaged she continues to stay engaged. The man who she was engaged to, may be required to advance on receiving an *advance* message and then that woman is no longer logically assigned to that man. For the constrained SMP algorithm, we need additional messages to detect termination. It is the environment process that initiates the computation and detects termination of the computation. We assume that a termination detection algorithm such as that of Dijkstra and Scholten [8] is running in conjunction with the CSMP algorithm. Termination in a diffusing computation corresponds to the condition that all processes are passive and there are no messages in-transit.

We now show that the algorithm in Fig. 6 correctly finds the least assignment (or man-optimal) constrained stable matching whenever it exists. The correctness follows from the following invariants.

LEMMA 4.1. Any assignment M in which $M[i] < G_i$ for any P_i cannot be a constrained stable marriage.

PROOF. Initially, the invariant is true because G_i is initialized to 1 and M[i] < 1 implies that P_i has not proposed to any one. There are only two reasons the G_i variable is incremented. Either the woman corresponding to the current proposal has sent a *reject* or a man has sent a message to *advance* beyond the current woman. We first consider the case when the current proposal was rejected by the woman q. It is sufficient to show that any assignment in which this man is assigned q cannot be a stable marriage. Suppose q rejected P_i in favor of P_j . If P_j is also assigned to q in G, then it is not a matching. If P_j is assigned to a woman that he proposes to later, then we have that q assigned to P_i prefers P_j and P_j prefers q to the woman he is assigned. If G_i is advanced because of an *advance* message from P_j , then any assignment in which $M[i] < G_i$ does not satisfy prerequisite constraints due to \rightarrow_p .

To show that the algorithm gives a stable matching on termination, if it exists, we show that the number of successful proposals is equal to n on termination. A proposal is defined to be successful if it is not rejected by a woman and not advanced over by a man and thereby rejected by the man. We start the algorithm by each process sending out a proposal. Thus, there are n proposals to start with. Any proposal that is rejected by a woman leads to another proposal if the reject message is not in transit. Any proposal that is skipped due to prerequisite constraints also leads to another proposal. So either a man runs out of proposals, or the computation has not terminated until every man has made a successful proposal. This assertion gives us

LEMMA 4.2. If the algorithm announces that the current assignment denotes stable marriage, then the assignment given by G is a stable matching satisfying external constraints, i.e., if P_i is paired with mpref[i][G_i], then the assignment satisfies constrained stable matching.

PROOF. Since there are no *reject* messages, *advance* messages, or *propose* messages in transit, we know that there are *n* successful proposals. Each successful proposal has the property that the value of current for P_i equals *j* iff the value of partner for Q_j equals *i*. Since any proposal that violates stability is rejected and any proposal that

violates external constraints is advanced we get that the assignment on termination is a stable matching satisfying external constraints. $\hfill\square$

We now analyze the message complexity of the algorithm. Suppose that there are *e* external constraints, *n* men, *n* women and *m* unsuccessful proposals. There are *n* initiate messages. For every unsuccessful proposal, the algorithm uses at most one *reject* message. There are exactly *n* final successful proposals resulting in one message per proposal in the diffusing computation. If there are *e* external constraints (solid edges) across processes), then there are at most *e* advance messages. Thus, the messages in the diffusing computation are at most *n initiate messages, m* unsuccessful *propose* messages, and *e advance* messages. Thus, the total number of messages in the diffusing computation is at most 2m + 2n + e.

Termination detection algorithms such as Dijkstra and Scholten's requires as many messages as the application messages in the worst case giving us the overall message complexity of 4m + 4n + 2e messages. We note here that this message complexity can be reduced by various optimizations such as combining the *signal/ack* messages of Dijkstra and Scholten's algorithm with application messages. For example, a *reject* message can also serve as an *ack* message for a *propose* message. For simplicity, we do not consider these optimizations in the paper. Since both *m* and *e* are $O(n^2)$, we get $O(n^2)$ overall message complexity. Although the number of unsuccessful proposals can be $O(n^2)$ in the worst case, they are $O(n \log n)$ on an average for the standard SMP [24]. Note that each message carries only $O(\log n)$ bits.

5 SUPERSTABLE MATCHING

In many applications, agents (men and women for the stable marriage problem) may not totally order all their choices. Instead, they may be indifferent to some choices [20, 26]. We generalize mpref[i][k] to a set of women instead of a single woman. Therefore, mrank function is not 1-1 anymore. Multiple women may have the same rank. Similarly, wrank function is not 1-1 anymore. Multiple men may have the same rank. We now define the notion of blocking pairs for a matching M with ties [20]. We let M(m)denote the woman matched with the man m and M(w) denote the man matched with the woman w. In the version, called *weakly stable* matching M, there is no blocking pair of man and woman (m, w) who are not married in M but strictly prefer each other to their partners in M. Formally, a pair of man and woman (m, w) is *blocking for a weakly stable matching* M if they are not matched in M and

 $(mrank[m][w] < mrank[m][M(m)]) \land$

(wrank[w][m] < wrank[w][M(w)].

For the weakly stable matching, ties can be broken arbitrarily and any matching that is stable in the resulting instance is also weakly stable for the original problem. Therefore, Gale-Shapley algorithm is applicable for the weakly stable matching [20]. We focus on other forms of stable matching — superstable and strongly stable matchings.

A matching M of men and women is *superstable* if there is no blocking pair (m, w) such that they are not married in M but they either prefer each other to their partners in M or are indifferent

with their partners in M. Formally, a pair of man and woman (m, w) is *blocking for a super stable matching* M if they are not matched in M and

 $(mrank[m][w] \leq mrank[m][M(m)]) \land$

 $(wrank[w][m] \leq wrank[w][M(w)].$

The algorithms for superstable marriage have been proposed in [20, 26]. Our goal is to show that LLP algorithm is applicable to this problem as well. As before, we will use G[i] to denote the *mrank* that the man *i* is currently considering. Initially, G[i] is 1 for all *i*, i.e., each man proposes to all his top choices. We say that *G* has a superstable matching if there exist *n* women w_1, w_2, \ldots, w_n such that $\forall i : w_i \in mpref[i][G[i]]]$ and the set (m_i, w_i) is a superstable matching.

We define a bipartite graph Y(G) on the set of men and women with respect to any *G* as follows. If a woman does not get any proposal in *G*, then she is unmatched. If she receives multiple proposals then there is an edge from that woman to all men in the most preferred rank. We say that Y(G) is a perfect matching if every man and woman has exactly one adjacent edge in Y(G),

We claim

LEMMA 5.1. If Y(G) is not a perfect matching, then there is no superstable matching with G as the proposal vector.

PROOF. If there is a man with no adjacent edge in Y(G) then it is clear that G cannot have a superstable matching. Now consider the case when a man has at least two adjacent edges. If all the adjacent women for this man have degree one, then exactly one of them can be matched with this man and other women will remain unmatched. Therefore, there is at least one woman w who is also adjacent to another man m'. If w is matched with m, then (m', w) is a blocking pair. If w is matched with m', then (m, w) is a blocking pair.

We now claim that the predicate $B(G) \equiv Y(G)$ is a perfect matching is a lattice-linear predicate.

LEMMA 5.2. If Y(G) is not a perfect matching, then at least one index in G is forbidden.

PROOF. Consider any man *i* such that there is no edge adjacent to *i* in Y(G). This happens when all women that man *i* has proposed in state *G* have rejected him. Consider any *H* such that H[i] equals G[i]. All the women had rejected man *i* in *G*. As *H* is greater than *G*, these women can only have more choices and will reject man *i* in *H* as well.

Now suppose that every man has at least one adjacent edge. Let Z(G) be the set of women with degree exactly one. If every woman is in Z(G), then we have that Y(G) is a perfect matching because every man has at least one adjacent edge. If not, consider any man i who is not matched to a woman in Z(G). This means that all the women he is adjacent to have degrees strictly greater than one. In H all these women would have either better ranked proposals or equally ranked proposals. In either case, man i would not be matched with any of these women. Hence, i is forbidden.

We are now ready to present LLP-ManOptimalSuperStableMarriage. In LLP-ManOptimalSuperStableMarriage, we start with the proposal vector G with all components G[j] as 1. Whenever a woman receives multiple proposals, she rejects proposals by men who are ranked lower than anyone who has proposed to her. We say that a man j is forbidden in G, if every woman z that man j proposes in G is either engaged to or proposed by someone who she prefers to j or is indifferent with respect to j. LLP-ManOptimalSuperStableMarriage is a parallel algorithm because all processes j such that forbidden(j) is true can advance in parallel.

ALGORITHM LLP-ManOptimalSuperStableMarriage: A Parallel Algorithm for Man-Optimal Super Stable Matching

 $\begin{array}{l} P_{j}: \text{Code for thread } j \\ \textbf{input: } mpref[i,k]: \text{ set of int for all } i,k; wrank[k][i]: \text{ int for all } k,i; \\ \textbf{init: } G[j]:=1; \\ \textbf{always: } Y(j) = mpref[j][G[j]]; \\ \textbf{forbidden}(j): \\ \forall z \in Y(j): \exists i \neq j: \exists k \leq G[i]: (z \in mpref[i][k]) \land (wrank[z][i] \leq wrank[z][j])) \\ // \text{ all women } z \text{ in the current proposals from } j \text{ have been proposed by someone who either they prefer or are indifferent over } j. \\ \textbf{advance: } G[j]:=G[j]+1; \end{array}$

Let us verify that this algorithm indeed generalizes the standard stable marriage algorithm. For the standard stable marriage problem, *mpref*[*i*, *k*] is singleton for all *i* and *k*. Hence, *Y*(*j*) is also singleton. Using *z* for the singleton value in *Y*(*j*), we get the expression $\exists i \neq j : \exists k \leq G[i] : (z = mpref[i][k]) \land (wrank[z][i] < wrank[z][j]))$ which is identical to the stable marriage problem once we substitute < for \leq for comparing the *wrank* of man *i* and man *j*.

When the preference list has a singleton element for each rank as in the classical stable marriage problem, we know that there always exists at least one stable marriage. However, in presence of ties there is no guarantee of existence of a superstable marriage. Consider the case with two men and women where each one of them does not have any strict preference. Clearly, for this case there is no superstable marriage.

By symmetry of the problem, one can also get woman-optimal superstable marriage by switching the roles of men and women. Let mpref[i].length() denote the number of equivalence classes of women for man *i*. When all women are tied for the man *i*, the number of equivalence classes is equal to 1, and when there are no ties then it is equal to *n*. Consider the distributive lattice *L* defined as the cross product of mpref[i] for each *i*. We now have the following result.

THEOREM 5.3. The set of superstable marriages, $L_{superstable}$, is a sublattice of the lattice L.

PROOF. From Lemma 5.2, the set of superstable marriages is closed under meet. By symmetry of men and women, the set is also closed under join.

It is already known that the set of superstable marriages forms a distributive lattice [28]. The set of join-irreducible elements of the lattice $L_{superstable}$ forms a partial order (analogous to the rotation poset [18]) that can be used to generate all superstable marriages. Various posets to generate all superstable marriages are discussed in [19, 27]

We note that the algorithm LLP-ManOptimalSuperStableMarriage can also be used to find the constrained superstable marriage. In particular, the following predicates are lattice-linear:

- (1) Regret of man *i* is at most regret of man *j*.
- (2) The proposal vector is at least *I*.

6 STRONGLY STABLE MATCHING

A matching M of men and women is *strongly stable* if there is no blocking pair (m, w) such that they are not married in M but either (1) both of them prefer each other to their partners in M, or (2) one of them prefers the other to his/her partner in M and the other one is indifferent. Formally, a pair of man and woman (m, w) is *block-ing for a strongly stable matching* M if they are not matched in M and

 $((mrank[m][w] \le mrank[m][M(m)]) \land (wrank[w][m] < wrank[w][M(w)])) \lor ((mrank[m][w] < mrank[m][M(m)]) \land (wrank[m][m] \le wrank[w][M(w)])).$

As in superstable matching algorithm, we let mpref[i][k] denote the set of women ranked k by man i. As before, we will use G[i] to denote the *mrank* that the man i is currently considering. Initially, G[i] is 1 for all i, i.e., each man proposes to all his top choices. We define a bipartite graph Y(G) on the set of men and women with respect to any G as follows. If a woman does not get any proposal in G, then she is unmatched. If she receives multiple proposals then there is an edge from that woman to all men in the most preferred rank. For superstable matching, we required Y(G) to be a perfect matching. For strongly stable matching, we only require Y(G) to contain a perfect matching.

We first note that a strongly stable matching may not exist. The following example is taken from [20].

m1: w1, w2

 $m2: {\rm both\ choices\ are\ ties\ }$

w1: m2, m1

w2: m2, m1

The matching $\{(m1, w1), (m2, w2)\}$ is blocked by the pair (m2, w1): w1 strictly prefers m2 and m2 is indifferent between w1 and w2. The only other matching is $\{(m1, w2), (m2, w1)\}$. This matching is blocked by (m2, w2): w2 strictly prefers m2 and m2 is indifferent between w1 and w2.

Consider any bipartite graph with an equal number of men and women. If there is no perfect matching in the graph, then by Hall's theorem there exists a set of men of size r who collectively are adjacent to fewer than r women. We define *deficiency* of a subset Z of men as |Z| - N(Z) where N(Z) is the *neighborhood* of Z (the set of vertices that are adjacent to at least one vertex in Z). The deficiency $\delta(G)$ is the maximum deficiency taken over all subsets of men. We call a subset of men Z *critical* if it is maximally deficient and does not contain any maximally deficient proper subset. Our algorithm to find a strongly stable matching is simple. We start with G as the global state vector with top choices for all men. If Y(G) has a perfect matching, we are done. The perfect matching in Y(G) is a strongly stable matching. Otherwise, there must be a critical subset of men with maximum deficiency. These set of men must then advance on their proposal number, if possible. If these men cannot advance, then there does not exist a strongly stable marriage and the algorithm terminates.

ALGORITHM LLP-ManOptimalStronglyStableMarriage: A Par-

allel Algorithm for Man-Optimal Strongly Stable Matching

 P_i : Code for thread *j*

input: *mpref*[*i*, *k*]: set of int for all *i*, *k*; *wrank*[*k*][*i*]: int for all *k*, *i*; **init**: *G*[*j*] := 1;

always: Y(j) = mpref[j][G[j]];

forbidden(j):

j is a member of the critical subset of men in the graph Y(G)**advance**: G[j] := G[j] + 1;

LLP-ManOptimalStronglyStableMarriage is the LLP version of the algorithm proposed by Irving and the interested reader is referred to [20] for the details and the proof of correctness. Similar to superstable marriages, we also get the following result.

THEOREM 6.1. The set of strongly stable marriages, $L_{stronglystable}$, is a sublattice of the lattice L.

Observe that each element in $L_{stronglystable}$ is not a single marriage but a set of marriages. This is in contrast to $L_{superstable}$, where each element corresponds to a single marriage.

7 CONCLUSIONS AND FUTURE WORK

We have shown that the Lattice-Linear Parallel Algorithm can solve many problems in the stable marriage literature. We have shown that the LLP Algorithm can also be converted into an asynchronous distributed algorithm.

In the constrained SMP formulation, we have assumed that (E, \rightarrow_p) is a poset for simplicity. Our algorithms are applicable when (E, \rightarrow_p) may have cycles. For the general graph (E, \rightarrow_p) we can consider the graph on strongly connected components which is guaranteed to be acyclic. By viewing each strongly connected component as a super-proposal in which multiple proposals are made simultaneously, the same analysis and algorithms can be applied.

We have also derived parallel LLP algorithms for stable matching problems with ties. Our technique gives an easy derivation of algorithms to find the man-optimal matchings as well as the sublattice representation of superstable and strongly stable matchings.

REFERENCES

- David R. Alves and Vijay K. Garg. 2022. Parallel Minimum Spanning Tree Algorithms via Lattice Linear Predicate Detection. In Proc. Parallel and Distributed Combinatorics and Optimization (PDCO), June 2022. Lyon, France.
- [2] B. Awerbuch. 1985. Complexity of Network Synchronization. J. ACM 32, 4 (Oct. 1985), 804–823.
- [3] Ismel Brito and Pedro Meseguer. 2005. Distributed stable matching problems. Principles and Practice of Constraint Programming-CP 2005 (2005), 152–166.
- [4] Craig M Chase and Vijay K Garg. 1998. Detection of global predicates: Techniques and their limitations. Distributed Computing 11, 4 (1998), 191–201.
- [5] B. A. Davey and H. A. Priestley. 1990. Introduction to Lattices and Order. Cambridge University Press, Cambridge, UK.
- [6] Manlove David. 2013. Algorithmics of matching under preferences. Vol. 2. World Scientific.
- [7] Vânia M.F. Dias, Guilherme D. da Fonseca, Celina M.H. de Figueiredo, and Jayme L. Szwarcfiter. 2003. The stable marriage problem with restricted pairs. *Theoretical Computer Science* 306, 1 (2003), 391 – 405.
- [8] Edsger W Dijkstra and Carel S. Scholten. 1980. Termination detection for diffusing computations. Inform. Process. Lett. 11, 1 (1980), 1–4.

- [9] David Gale and Lloyd S Shapley. 1962. College admissions and the stability of marriage. The American Mathematical Monthly 69, 1 (1962), 9–15.
- [10] Vijay K Garg. 2015. Lattice Theory with Computer Science Applications. Wiley, New York, NY.
- [11] Vijay K. Garg. 2017. Brief Announcement: Applying Predicate Detection to the Stable Marriage Problem. In 31st International Symposium on Distributed Computing, DISC 2017, October 16-20, 2017, Vienna, Austria (LIPIcs, Vol. 91), Andréa W. Richa (Ed.). Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 52:1–52:3. https://doi.org/10.4230/LIPIcs.DISC.2017.52
- [12] Vijay K. Garg. 2020. Predicate Detection to Solve Combinatorial Optimization Problems. In SPAA '20: 32nd ACM Symposium on Parallelism in Algorithms and Architectures, Virtual Event, USA, July 15-17, 2020, Christian Scheideler and Michael Spear (Eds.). ACM, 235–245. https://doi.org/10.1145/3350755.3400235
- [13] Vijay K. Garg. 2021. A Lattice Linear Predicate Parallel Algorithm for the Housing Market Problem. In Stabilization, Safety, and Security of Distributed Systems - 23rd International Symposium, SSS 2021, Virtual Event, November 17-20, 2021, Proceedings (Lecture Notes in Computer Science, Vol. 13046), Colette Johnen, Elad Michael Schiller, and Stefan Schmid (Eds.). Springer, 108–122. https://doi.org/10.1007/978-3-030-91081-5_8
- [14] Vijay K. Garg. 2022. A Lattice Linear Predicate Parallel Algorithm for the Dynamic Programming Problems. In Proc. of the Int'l Conf. on Distributed Computing and Networking (ICDCN). Springer-Verlag, Delhi, India.
- [15] Vijay K. Garg. 2023. A Systematic Approach to Parallel Algorithms. http://users.ece.utexas.edu/ garg/algo.html.
- [16] Vijay Kumar Garg and Changyong Hu. 2020. Improved Paths to Stability for the Stable Marriage Problem. https://doi.org/10.48550/ARXIV.2007.07121
- [17] Arya Tanmay Gupta and Sandeep S. Kulkarni. 2021. Extending Lattice Linearity for Self-stabilizing Algorithms. In Stabilization, Safety, and Security of Distributed Systems - 23rd International Symposium, SSS 2021, Virtual Event, November 17-20, 2021, Proceedings (Lecture Notes in Computer Science, Vol. 13046), Colette Johnen, Elad Michael Schiller, and Stefan Schmid (Eds.). Springer, 365–379. https: //doi.org/10.1007/978-3-030-91081-5_24
- [18] Dan Gusfield and Robert W Irving. 1989. The stable marriage problem: structure and algorithms. MIT press.
- [19] Changyong Hu and Vijay K. Garg. 2021. Characterization of Super-Stable Matchings. In Algorithms and Data Structures - 17th International Symposium, WADS 2021, Virtual Event, August 9-11, 2021, Proceedings (Lecture Notes in Computer Science, Vol. 12808), Anna Lubiw and Mohammad R. Salavatipour (Eds.). Springer, 485-498. https://doi.org/10.1007/978-3-030-85508-8_35
- [20] Robert W. Irving. 1994. Stable marriage and indifference. Discrete Applied Mathematics 48, 3 (1994), 261–272. https://doi.org/10.1016/0166-218X(92)00179-P
- [21] Kazuo Iwama and Shuichi Miyazaki. 2008. A survey of the stable marriage problem and its variants. In Informatics Education and Research for Knowledge-Circulating Society, 2008. ICKS 2008. International Conference on. IEEE, 131–136.
- [22] Alex Kipnis and Boaz Patt-Shamir. 2009. A note on distributed stable matching. In Distributed Computing Systems, 2009. ICDCS'09. 29th IEEE International Conference on. IEEE, 466–473.
- [23] Alexander Kipnis and Boaz Patt-Shamir. 2010. On the complexity of distributed stable matching with small messages. *Distributed Computing* 23, 3 (2010), 151– 161.
- [24] Donald Ervin Knuth. 1997. Stable marriage and its relation to other combinatorial problems: An introduction to the mathematical analysis of algorithms. Vol. 10. American Mathematical Soc.
- [25] Bruce M Maggs and Ramesh K Sitaraman. 2015. Algorithmic nuggets in content delivery. ACM SIGCOMM Computer Communication Review 45, 3 (2015), 52–66.
- [26] David F Manlove. 2002. The structure of stable marriage with indifference. Discrete Applied Mathematics 122, 1-3 (2002), 167–181.
- [27] Sandy Scott. 2005. A study of stable marriage problems with ties. University of Glasgow (United Kingdom).
- [28] Boris Spieker. 1995. The set of super-stable marriages forms a distributive lattice. Discrete applied mathematics 58, 1 (1995), 79-84.