Maximum Minimal Feedback Vertex Set: A Parameterized Perspective

Ajinkya Gaikwad¹, Hitendra Kumar¹, Soumen Maity¹, Saket Saurabh^{2,3}, and Shuvam Kant Tripathi¹

¹ Indian Institute of Science Education and Research, Pune, India
² The Institute of Mathematical Sciences, Chennai, India
³ University of Bergen, Bergen, Norway
ajinkya.gaikwad@students.iiserpune.ac.in; soumen@iiserpune.ac.in;

ajinkya.gaikwad@students.llserpune.ac.in; soumen@llserpune.ac.in; saket@imsc.res.in

Abstract. In this paper we study a maximization version of the classical FEEDBACK VERTEX SET (FVS) problem, namely, the MAX MIN FVS problem, in the realm of parameterized complexity. In this problem, given an undirected graph G, a positive integer k, the question is to check whether G has a minimal feedback vertex set of size at least k. We obtain following results for MAX MIN FVS.

- 1. We first design a fixed parameter tractable (FPT) algorithm for MAX MIN FVS running in time $10^k n^{\mathcal{O}(1)}$.
- 2. Next, we consider the problem parameterized by the vertex cover number of the input graph (denoted by vc(G)), and design an algorithm with running time $2^{\mathcal{O}(vc(G) \log vc(G))}n^{\mathcal{O}(1)}$. We complement this result by showing that the problem parameterized by vc(G) does not admit a polynomial compression unless coNP \subseteq NP/poly.
- 3. Finally, we give an FPT-approximation scheme (fpt-AS) parameterized by vc(G). That is, we design an algorithm that for every $\epsilon > 0$, runs in time $2^{\mathcal{O}\left(\frac{vc(G)}{\epsilon}\right)}n^{\mathcal{O}(1)}$ and returns a minimal feedback vertex set of size at least $(1 - \epsilon)$ opt.

Keywords: Parameterized Complexity · FPT · vertex cover

1 Introduction

FEEDBACK VERTEX SET (FVS) together with VERTEX COVER are arguably the two most well studied problems in parameterized complexity. In FVS, we are given an undirected graph G, a positive integer k, and the question is to check whether G has a vertex set S of size at most k such that G - S is a forest (an acyclic graph). The set S is called *feedback vertex set* or *fvs* in short. Downey and Fellows [5], and Bodlaender [2] proposed the first two fixed parameter tractable (FPT) algorithms with the running time $\mathcal{O}^*(2^{\mathcal{O}(k \log k)})^4$. After a long series of improvements, the current champion algorithms are as follows. The fastest

⁴ The notation \mathcal{O}^* hides the polynomial factor in the running time.

known randomized algorithm is given by Li and Nederlof [11] and runs in time $\mathcal{O}^*(2.7^k)$, and the fastest known deterministic algorithm, given by Iwata and Kobayashi [10], runs in time $\mathcal{O}^*(3.460^k)$. Several minimization variants of FVS have been studied in the literature such as finding a set S such that G - S is acyclic and G[S] is connected or G[S] is an independent set. In this paper we consider a (not so well studied) maximization version of FVS, namely MAX MIN FVS. A set S is called a *minimal fvs*, if S is an fvs and for every $v \in S$, $S \setminus \{v\}$ is not an fvs. That is, no proper subset of S is an fvs. It is not hard to see that if S is a minimal FVS, then every $u \in S$ has a *private cycle*, that is, there exists a cycle in $G[(V(G) \setminus S) \cup \{u\}]$, which goes through u. Now we are ready to define the problem formally.

MAX MIN FVS **Input:** An undirected graph G = (V, E) and an integer $k \in \mathbb{N}$. **Question:** Does G admit a minimal FVS of size greater than or equal to k?

The graph parameter we discuss in this paper is vertex cover number.

Definition 1. A set $C \subseteq V$ is a vertex cover of G = (V, E) if each edge $e \in E$ has at least one endpoint in C. The minimum size of a vertex cover in G is the vertex cover number of G, denoted by vc(G).

Lately, finding a large size minimal solution has attracted a lot of attention from the perspective of the Approximation Algorithms and Parameterized Complexity. Boria et al. [3] proved that for any constant $\epsilon > 0$, the optimization version of MAX MIN VERTEX COVER is inapproximable within ratios $\mathcal{O}(n^{0.5-\epsilon})$, unless P=NP. They complement this result by proving that MAX MIN VERTEX COVER is approximable within ratio $\mathcal{O}(n^{0.5})$ in polynomial time. This is in sharp contrast to the approximability of the classical VERTEX COVER problem, for which an easy factor 2-approximation exists. This becomes even more interesting when we consider the optimization version of MAX MIN FVS. The MAX MIN FVS problem was first considered by Mishra and Sikdar [12], who showed that the problem does not admit an $n^{0.5-\epsilon}$ approximation (unless P=NP), and that it remains APX-hard even when the input graph is of degree at most 9. Dublois et al. [7] improved upon this by showing the first non-trivial polynomial time approximation for MAX MIN FVS with a ratio of $\mathcal{O}(n^{\frac{2}{3}})$, as well as a matching hardness of approximation bound of $n^{\frac{2}{3}-\epsilon}$. Apart from these two problems, there are many other classical optimization problems that have recently been studied in the MAXMIN or MINMAX framework, such as MAX MIN SEPARATOR [9] and MAX MIN CUT [8].

In the realm of parameterized complexity, Zehavi [13] studied MAX MIN VERTEX COVER – find a minimal vertex cover of size at least k, if exists – and designed an algorithm with running time $\mathcal{O}^{\star}(2^{\operatorname{vc}(G)})$, which is "almost optimal" unless Strong Exponential Time Hypothesis fails. For MAX MIN FVS, Dublois et al. [7] obtained a polynomial kernel of size $\mathcal{O}(k^3)$. That is, they design a polynomial time algorithm that given an instance (G, k) returns an equivalent instance (G', k') such that $k' \leq k$ and $|V(G') + E(G')| \leq O(k^3)$. This result is the starting point of our work. There are results about kernelization of MAX MIN VERTEX COVER and MAX MIN FVS in [1]. In particular, they proved that MAX MIN VC parameterized by vertex cover number does not admit a polynomial kernel. This result is related to the kernelization of MAX MIN FVS parameterized by vertex cover of our work.

1.1 Preliminaries

We only consider finite undirected graphs without loops or multiple edges, and we denote an edge between two vertices u and v by (u, v). A subgraph H of a graph G is *induced* if H can be obtained from G by deleting a set of vertices $D = V(G) \setminus S$, and we denote H = G[S]. For a graph G and a set $S \subseteq V(G)$, we use the notation $G - S = G[V(G) \setminus S]$, and for a vertex $v \in V(G)$, we abbreviate $G \setminus \{v\}$ as G - v. The *(open) neighbourhood* $N_G(v)$ of a vertex $v \in V(G)$ is the set $\{u \mid (u, v) \in E(G)\}$. The closed neighbourhood $N_G[v]$ of a vertex $v \in V(G)$ is the set $\{v\} \cup N_G(v)$. The degree of $v \in V(G)$ is $|N_G(v)|$ and denoted by $d_G(v)$. We use $d_S(v)$ to denote the degree of vertex v in G[S]. For an integer $n \ge 1$, we let [n] be the set containing all integers i with $1 \le i \le n$. In a graph G, contraction of an edge e = (u, v) is the replacement of u and v with a single vertex such that edges incident to the new vertex are the edges other than e that were incident with u or v. The resulting graph, denoted G/e, has one less edge than G. We refer to Appendix A and [4,6] for details on parameterized complexity.

1.2 Our results and methods

Using, the polynomial kernel, of size $\mathcal{O}(k^3)$, of Dublois et al. [7], we can design an FPT algorithm for MAX MIN FVS running in time $\mathcal{O}^{\star}(2^{\mathcal{O}(k^3)})$ as follows. For every vertex subset S of size at least k' of V(G') test whether S is a minimal fvs or not. If we succeed for any S, we have that (G, k) is a yes instance, else, it is a no instance. As our first result we improve upon this result and obtain the following result.

Theorem 1. MAX MIN FVS can be solved in time $\mathcal{O}^{\star}(10^k)$.




Fig. 1. Graph G with fvs(G) = 1 and opt(G) = 4

Proof of Theorem 1 follows the strategy used for designing an iterative compression based FPT algorithm for FVS. Let $\mathsf{fvs}(G)$ denote the minimum size of a feedback vertex set of G, and let $\mathsf{opt}(G)$ denote the maximum size of a minimal feedback vertex set of G. Clearly, $\mathsf{fvs}(G) \leq \mathsf{opt}(G)$. The gap between these quantities can be arbitrary large – as shown in Figure 1. Here, $\mathsf{fvs}(G) = 1$, while $\mathsf{opt}(G) = |V(G)| - 2$. Further, observe that the same example also shows that the gap between $\mathsf{vc}(G)$ and $\mathsf{opt}(G)$ can be arbitrary large. Here, $\mathsf{vc}(G) = 2$, while $\mathsf{opt}(G) = |V(G)| - 2$. The discussion above implies that for MAX MIN FVS both $\mathsf{fvs}(G)$ and $\mathsf{vc}(G)$ are interesting parameters to consider. For our second result, we consider MAX MIN FVS parameterized by $\mathsf{vc}(G)$ and obtain the following result.

Theorem 2. MAX MIN FVS can be solved in time $\mathcal{O}^{\star}(2^{\mathcal{O}(\mathsf{vc}(G) \log \mathsf{vc}(G))})$.

The starting point of the algorithm is based on the natural partitioning ideas. However, to complete the algorithm we need to design an algorithm for INDUCED FOREST ISOMORPHISM parameterized by vc(G), which could be of independent interest. This algorithm is the bottleneck in designing an algorithm for MAX MIN FVS running in time $\mathcal{O}^*(2^{\mathcal{O}(vc(G) \log vc(G))})$. We complement this result by showing that MAX MIN FVS parameterized by vc(G) does not admit a polynomial compression unless coNP \subseteq NP/poly. Note that vc(G) can be much larger than opt(G), for example in a cycle, and so Theorem 1 is not implied by Theorem 2. Finally, we show that if we allow a "small loss" then we can improve upon Theorem 2. That is, we design an FPT-approximation algorithm for MAX MIN FVS parameterized by vc(G).

Theorem 3. Let $\epsilon > 0$ be a fixed constant. Then, there exists an algorithm for MAX MIN FVS, that runs in time $2^{\mathcal{O}(\frac{\operatorname{ve}(G)}{\epsilon})}n^{\mathcal{O}(1)}$ and returns a minimal feedback vertex set of size at least $(1 - \epsilon)\operatorname{opt}(G)$.

2 FPT algorithm parameterized by solution size

In this section we design an FPT algorithm for MAX MIN FVS. First we give an algorithm for EXTENSION MAX MIN FVS. We start by defining EXTENSION MAX MIN FVS. In this problem, as input instance $I = (G, W_1, W_2, k)$, we are given an undirected graph G, an integer k and a minimal feedback vertex set $W = W_1 \cup W_2$ in G. We are also given a partition (W_1, W_2) of the vertices of W. The objective is to decide if G has a minimal feedback vertex set S such that $W_1 \subseteq S$, $W_2 \cap S = \emptyset$ and $|S \setminus W_1| \ge k$, or correctly conclude that no such minimal feedback vertex set exists. We give an algorithm for EXTENSION MAX MIN FVS running in time $3^{k+\gamma(I)}n^{\mathcal{O}(1)}$, where $\gamma(I)$ is the number of connected components of $G[W_2]$. Maximum Minimal Feedback Vertex Set: A Parameterized Perspective

2.1 An algorithm for Extension Max Min FVS

Let $I = (G, W_1, W_2, k)$ be an instance of EXTENSION MAX MIN FVS and let H = G - W where $W = W_1 \cup W_2$ and $W_1 \cap W_2 = \emptyset$. We first give some reduction rules to simplify the input instance.

Reduction EMMFVS 1 If $G - W_1$ has a vertex v of degree at most 1, remove it from the graph.

Reduction EMM-FVS 1 is safe, because for a given instance (G, W_1, W_2, k) of EXTENSION MAX MIN FVS, if the graph $G - W_1$ has a vertex of degree at most one, then this vertex is not part of any cycle in $G - W_1$. Thus, its removal does not change the solution.

Reduction EMMFVS 2 If there is a vertex v in H such that $G[W_2 \cup \{v\}]$ contains a cycle, then include v in W_1 , and decrease the parameter by 1. That is, the new instance is $(G, W_1 \cup \{v\}, W_2, k-1)$.

Reduction MMFVS 2 is safe. Suppose $G[W_2 \cup \{v\}]$ contains a cycle C. As the solution here has to be disjoint from W_2 , the only way to destroy C is to include v in the solution.

Reduction EMMFVS 3 If $(u, v) \in E(G)$ such that $N(u) \cap N(v) = \emptyset$, d(v) = d(u) = 2 and $u, v \notin W$, then contract (u, v). That is, the new instance is $(G/(u, v), W_1, W_2, k)$.

Reduction Rule EMMFVS 3 is safe as any minimal feedback vertex set contains at most one of u and v. This reduction rule is inspired from [7] and a formal proof of this rule is given in [7]. Furthermore, all reductions can be applied in polynomial time.

Lemma 1. EXTENSION MAX MIN FVS can be solved in time $3^{k+\gamma(I)}n^{\mathcal{O}(1)}$.

Proof. Let (G, W_1, W_2, k) be the input instance. If $G[W_2]$ is not a forest then we return that (G, W_1, W_2, k) is a no-instance. So from now onward we assume that $G[W_2]$ is a forest. We follow a branching technique with a measure function μ . For instance $I = (G, W_1, W_2, k)$, we define its measure

$$\mu(I) = k + \gamma(I)$$

where $\gamma(I)$ is the number of connected components of $G[W_2]$. The algorithm first applies Reduction EMMFVS 1, EMMFVS 2, and EMMFVS 3 exhaustively. For clarity we denote the reduced instance by (G, W_1, W_2, k) . Since W is a feedback vertex set, H = G - W is a forest. Thus H has a vertex of degree at most 1. In each tree of the forest H, arbitrarily pick one of its vertices as the root. Now we focus on a deepest leaf v of any tree in H. Clearly v has at least one neighbour in W_2 , otherwise Reduction EMMFVS 1 would have been applied. We distinguish two cases based on the number of neighbours of v in W_2 .

Case 1. Assume that v has at least two neighbours in W_2 . Since Reduction EMMFVS 2 cannot be applied, we have that no two neighbours of v belong to the same connected component of $G[W_2]$. So, we can assume that all neighbours of v belong to different connected components of $G[W_2]$. See Figure 2(a). Now we branch by including v in the solution in one branch and excluding it in the other branch. That is, we call the algorithm on instances $(G, W_1 \cup \{v\}, W_2, k-1)$ and $(G, W_1, W_2 \cup \{v\}, k)$. We check minimality of the partial solution in every branch. If one of these branches returns a solution, then we conclude that (G, W_1, W_2, k) is a yes-instance, otherwise (G, W_1, W_2, k) is a no-instance.

Case 2. Assume that v has exactly one neighbour in W_2 . Let $\pi(v)$ be the parent of v in H. We now have a number of subcases and subsubcases to consider. Clearly, the degree of $\pi(v)$ cannot be one in $G - W_1$, otherwise Reduction EMM-FVS 1 would have been applied.

Subcase 2.1. Assume that the degree of $\pi(v)$ in $G-W_1$ is two. Then both v and $\pi(v)$ are of degree two, and hence must have a common neighbour in W_2 , otherwise Reduction EMMFVS 3 would have been applied. See Figure 2(b). Clearly, every solution of the EXTENSION MAX MIN FVS instance (G, W_1, W_2, k) contains either v or $\pi(v)$. Note that, without loss of generality we can add v inside the solution and keep $\pi(v)$ outside the solution. Therefore, we get reduced EXTENSION MAX MIN FVS instance $(G, W_1 \cup \{v\}, W_2 \cup \{\pi(v)\}, k-1)$. We check minimality of this partial solution.

Subcase 2.2. Assume that the degree of $\pi(v)$ in $G - W_1$ is at least 3. We split this subcase into two subsubcases.

Subsubcase 2.2.1. Assume that $\pi(v)$ has no neighbours in W_2 . As the degree of $\pi(v)$ in $G - W_1$ is at least three and it has no neighbours in W_2 , it has at least two children. Without loss of generality, suppose $\pi(v)$ has two children v and v'. Observe that v' is a leaf node, otherwise v is not a deepest leaf in H. The degree of v' cannot be one in $G - W_1$, otherwise Reduction EMMFVS 1 would have been applied. Also the degree of v' cannot be more than one in W_2 as otherwise Case 1 will be applicable. Therefore v' has exactly one neighbour in W_2 . Similarly, we can argue that v has exactly one neighbour in W_2 . See Figure 2(c). In this case we make three branches by including one of v and v' in the solution and excluding $\{v, v', \pi(v)\}$ in the other branch. That is, we get instances $(G, W_1 \cup \{v\}, W_2, k-1), (G, W_1 \cup \{v'\}, W_2, k-1) \text{ and } (G, W_1, W_2 \cup \{v, v', \pi(v)\}, k).$ We check minimality of the partial solution in every branch. Notice that we have not considered a branch where $\pi(v)$ is inside the solution. For the sake of contradiction, assume that $\pi(v)$ is inside the solution S. We will prove that starting from S, we can construct another solution S' such that $|S'| \ge |S|$ but $\pi(v) \notin S'$. First we observe that if $\pi(v)$ is in S, none of its children are in S. This is because each child of $\pi(v)$ has degree two in $G - W_1$ and one of its neighbours is $\pi(v)$. That means every cycle that contains a child of $\pi(v)$ also contains $\pi(v)$. Next




Fig. 2. Illustration of different cases in the proof of Theorem 1.

assuming that $\pi(v)$ is inside the solution S, there must exist a private cycle C of $\pi(v)$. Note that C must contain at least one child of $\pi(v)$ as it does not have a neighbour in W_2 . Without loss of generality, let that child be v. In this case we will replace $\pi(v)$ by v, that is, $S' = (S \setminus {\pi(v)}) \cup {v}$. We observe that the solution will satisfy minimality condition because every cycle that is hit by v is also hit by $\pi(v)$.

Subsubcase 2.2.2. Assume that $\pi(v)$ has at least one neighbour in W_2 . Note that $\pi(v)$ has at least one child. See Figure 2(d). In this case we get three branches by including one of v and $\pi(v)$ in the solution and excluding $\{v, \pi(v)\}$ in the other branch. That is, we get instances $(G, W_1 \cup \{v\}, W_2, k-1), (G, W_1 \cup \{\pi(v)\}, W_2, k-1)$ and $(G, W_1, W_2 \cup \{v, \pi(v)\}, k)$. We check minimality of the partial solution in every branch.

The algorithm stops when k = 0 or $H = \emptyset$. If k = 0 at some leaf node in the search tree, then we conclude that the given instance of EXTENSION MAX MIN FVS is a yes-instance. Otherwise, it is a no-instance. Note that at each branch of Case 1, Subcase 2.1, Subsubcase 2.2.1 and 2.2.2, we check the minimality of the partial solution, that is, we check if for every vertex $w \in W_1$ whether there exists a cycle containing w in $G - \{W_1 \setminus w\}$. If the partial solution of a branch is not minimal, the we discard that branch. To estimate the running time of the algorithm for instance $I = (G, W_1, W_2, k)$, we use the measure $\mu(I)$ as defined at the beginning of the proof. Observe that Reductions EMMFVS 1, EMMFVS 2, and EMMFVS 3 do not increase the measure. Now we see how $\mu(I)$ changes

when we branch. In Case 1, when v goes to the solution, k decreases by 1 and $\gamma(I)$ remains the same. Thus $\mu(I)$ decreases by 1. In the other branch, v goes into W_2 , then k remains the same and $\gamma(I)$ decreases at least by 1. Thus $\mu(I)$ decreases at least by 1. Thus we have a branching vector $(1, \geq 1)$ for branching in Case 1. In Subcase 2.1, when v or $\pi(v)$ goes to the solution, k decreases by 1 and $\gamma(I)$ remains the same. Thus $\mu(I)$ decreases by 1. In Subsubcase 2.2.1, clearly $\mu(I)$ decreases by 1 in the first and second branch as k value decreases by 1. In the third branch, when we include $\{v, \pi(v), v'\}$ in W_2 , $\gamma(I)$ drops at least by 1 and k remains the same, therefore $\mu(I)$ decreases at least by 1. Thus, we have a branching vector $(1, 1, \geq 1)$. Similarly, we have a branching vector $(1, 1, \geq 1)$ for Subsubcase 2.2.2. As the maximum number of branches is 3, the running time of our algorithm is $3^{\mu(I)}n^{\mathcal{O}(1)}$.

2.2 An algorithm for MAX MIN FVS

Given an input instance (G, k), greedily find a minimal feedback vertex set W of G. If $|W| \geq k$, then (G, k) is a yes-instance. Otherwise, we have a minimal feedback vertex set W of size at most k - 1, that is, $\gamma(I) \leq k - 1$ and the goal is to decide whether G has a minimal feedback vertex set S of size at least k. We do the following. We guess the intersection of S with W, that is, we guess the set $W_1 = S \cap W$, and reduce parameter k by $|W_1|$. For each guess of W_1 , we set $W_2 = W \setminus W_1$ and solve EXTENSION MAX MIN FVS on the instance $(G, W_1, W_2, k - |W_1|)$. If for some guess, G has a minimal feedback vertex set S such that $W_1 \subseteq S, W_2 \cap S = \emptyset$ and $|S \setminus W_1| \geq k - |W_1|$, then we conclude that the given instance of MAX MIN FVS is a yes-instance. Otherwise, we conclude that the given instance of MAX MIN FVS is a no-instance. The number of all guesses is bounded by $\sum_{i=0}^{k-1} {k-1 \choose i}$. We have an algorithm solving EXTENSION MAX MIN FVS in time $3^{k+\gamma(I)}n^{\mathcal{O}(1)} = 9^k n^{\mathcal{O}(1)}$ as $k + \gamma(I) \leq 2k - 1$. Therefore we have an algorithm solving MAX MIN FVS in time

$$\sum_{i=0}^{k-1} \binom{k-1}{i} 9^{k-i} n^{O(1)} = 10^k n^{O(1)}.$$

Thus we obtain Theorem 1.

3 FPT algorithm parameterized by vertex cover number

In this section we prove that MAX MIN FVS is FPT when parameterized by vertex cover number vc(G).

Proof (The Proof of Theorem 2). If G = (V, E) has a vertex v of degree at most 1, remove it from the graph. We find a vertex cover C of size at most vc(G)

8

of the reduced graph G. For our purpose, a standard branching algorithm with $O(2^{\operatorname{vc}(G)}n)$ running time is sufficient (see e.g. [4]). We denote by I the independent set $V \setminus C$. We next guess $C_{in} = S \cap C$, where S is a largest minimal FVS. There are at most $2^{\operatorname{vc}(G)}$ candidates for C_{in} as each member of C has two options: either in $C_{in} = S \cap C$ or $C_{out} = \overline{S} \cap C$. Clearly, $C_{out} = \overline{S} \cap C$ contains the vertices of C which are outside the solution. If $G[C_{out}]$ is not a forest then return that C_{in} is a wrong guess and reject it. So from now onwards we assume that $G[C_{out}]$ is indeed a forest. Next we check minimality of C_{in} , that is, for each v in C_{in} , whether $G[V \setminus C_{in} \cup \{v\}]$ has a cycle containing v. If the minimality of C_{in} is not satisfied then return that C_{in} is a wrong guess

Outline of the algorithm: Given a guess C_{in} , our goal is to find a largest minimal FVS containing C_{in} . We look for a set $Z \subseteq I$ of vertices which can be added to C_{out} so that $G[C_{out} \cup Z]$ remains a forest and every vertex $v \in I \setminus Z$ has at least two neighbours in some component of $G[C_{out} \cup Z]$. This is why every vertex in $I \setminus Z$ must be included in the solution. Finally the algorithm outputs $C_{in} \cup (I \setminus Z)$.

Algorithm to find Z: If $G - C_{in}$ has a vertex v of degree at most 1, remove it from the graph. If there is a vertex v in I such that $G[C_{out} \cup \{v\}]$ contains a cycle, then include v in the solution. Suppose S' is a minimal FVS such that $C_{in} \subseteq S'$. We know G - S' is a forest \mathcal{F} . Suppose \mathcal{F} has exactly q trees T_1, T_2, \ldots, T_q . Note that the number of trees in \mathcal{F} is at most vc(G), that is, $q \leq vc(G)$. We guess a partition $\mathcal{P} = \{P_1, P_2, \ldots, P_q\}$ of C_{out} . We say the partition $\mathcal{P} = \{P_1, P_2, \ldots, P_q\}$ corresponds to trees of \mathcal{F} , if $P_i = C_{out} \cap V(T_i)$. For each part P_i there must exist a set $Z_i \subseteq I$ of vertices such that $G[P_i \cup Z_i] = T_i$. Otherwise \mathcal{P} is a wrong guess. Note that $Z = \bigcup_{i=1}^q Z_i$. There are at most $vc(G)^{vc(G)}$ candidates for \mathcal{P} and we try out all guesses.

Algorithm to find Z_i : Consider ith part P_i of \mathcal{P} . Note that $G[P_i]$ is a collection trees. Given P_i , we want to have a set $Z_i \subseteq I$ of vertices such that $G[P_i \cup Z_i]$ is a tree. This can happen in different ways. For example, it may be the case that only one vertex z of I connects all trees of $G[P_i]$ to form a single tree. It may be the case that we need $s_i > 1$ vertices of I to connect all trees of $G[P_i]$ to form a single tree. We further guess a partition $\mathcal{P}_i = \{P_{i1}, P_{i2}, \dots, P_{is_i}\}$ of P_i into s_i parts. For each P_i there are at most $vc(G)^{|P_i|}$ possible partitions. Given a partition $\mathcal{P}_i = \{P_{i1}, P_{i2}, \dots, P_{is_i}\}$ of P_i we want to have a set $Z_i = \{z_{i1}, z_{i2}, \dots, z_{is_i}\}$ of vertices such that $z_{ij} \in I$ is adjacent to exactly one vertex of every tree in P_{ij} . Thus $G[z_{ij} \cup P_{ij}]$ forms a tree. Next we guess how these s_i trees are joined to form a single tree. We need $s_i - 1$ cross edges of the form (z_{ij}, v_{ik}) where $v_{ik} \in P_{ik}, j \neq k$ to join s_i trees. See Figure 3. There are $s_i(s_i - 1)$ cross edges of the form (z_{ij}, v_{ik}) where $v_{ik} \in P_{ik}, j \neq k$. Thus $s_i - 1$ edges can be selected in at most $(s_i^2)^{s_i}$ many ways. So the total number of selections of cross edges for all P_i 's together is at most $\prod_{i=1}^q (s_i^2)^{s_i} \leq \mathsf{vc}(G)^{2\mathsf{vc}(G)}$. Thus there are total $\mathsf{vc}(G)^{4\mathsf{vc}(G)}$ guesses for the structure of trees involving vertices $V(P_i) \cup Z_i$ and cross edges for all i combined. A selection of $s_i - 1$ cross edges is a valid selec-




Fig. 3. An illustration for partition of P_i into four parts $P_{i1}, P_{i2}, P_{i3}, P_{i4}$; cross edges $(z_{i1}, v_{i2}), (z_{i1}, v_{i4}), (z_{i4}, v_{i3})$ are shown in orange. For simplicity trees in each part are singleton.

tion if the chosen cross edges can join s_i trees to form one tree. For example, three cross edges (orange) in Figure 3 can join four trees to produce one tree; so these three orange edges form a valid selection. Note that the vertices in Z_i are abstract; now we look for candidates of $z_{ij} \in Z_i$ for all j, in the input graph. For a given guess, a vertex $x \in I$ is a *candidate* for z_{ij} if and only if x is only adjacent to exactly one vertex from each tree in P_{ij} and also it is adjacent to a vertex in P_{ik} when (z_{ij}, v_{ik}) is a cross edge in the given guess. For a particular guess there could be several candidates for z_{ij} . We claim that only one of the candidates of z_{ij} can go to Z_i and the rest go to the solution. Suppose there are two candidates x_1 and x_2 for z_{ij} . Without loss of generality assume that x_1 goes to Z_i , that is, x_1 does not go to the solution. Then we prove that x_2 must go to the solution. We consider two cases:

Case 1: Assume that P_{ij} contains at least two trees. Then there is a cycle C containing x_2 where the remaining vertices of C are outside the solution; see Figure 4 (a). Therefore x_2 must go to the solution in order to destroy C.




Fig. 4. Illustration of Case 1 and Case 2.

Case 2: Assume that P_{ij} contains exactly one tree. Recall that if $G - C_{in}$ has a vertex v of degree at most 1, then we remove it from the graph. Therefore x_1 and x_2 have degree at least two. Since $d(x_1), d(x_2) \ge 2$, both of them must

have a neighbour in some P_{ik} where $j \neq k$, and (z_{ij}, v_{ik}) is a cross edge in the given guess. Therefore, the graph $G[V(P_{ij}) \cup V(P_{ik}) \cup \{x_1, x_2, x_3\}]$ has a cycle C containing x_2 where x_3 is a candidate vertex for z_{ik} and x_3 is outside the solution. See Figure 4 (b). Note that C contains x_2 where the remaining vertices are outside the solution. So x_2 must be inside the solution in order to destroy C; this proves the claim.

So while choosing a candidate for z_{ij} , we only make sure that the remaining candidates which are going to the solution do not disturb the minimality of C_{in} . If there is no such candidate then we return that it is a wrong guess. Clearly, it takes polynomial time to check if Z_i exists for all *i*. For a given guess C_{in} , if $Z = \bigcup_{i=1}^{q} Z_i$ exists in *I* then we see that $C_{in} \cup (I \setminus Z)$ forms a minimal feedback vertex set containing C_{in} .

Given C_{in} , in order to compute Z we consider at most $\mathsf{vc}(G)^{4\mathsf{vc}(G)}$ guesses. Thus given C_{in} we can compute Z in time $\mathsf{vc}(G)^{4\mathsf{vc}(G)}n^{O(1)}$. Given C_{in} the above algorithm returns either a minimal FVS containing C_{in} or returns C_{in} is a wrong guess. Finally we consider the maximum size solution obtained over all guesses. As there are $2^{\mathsf{vc}(G)}$ candidates for C_{in} , we can solve the problem in $\mathsf{vc}(G)^{5\mathsf{vc}(G)}n^{O(1)}$ time.

4 No polynomial kernel parameterized by vc(G)

We proved that MAX MIN FVS is FPT when parameterized by vertex cover number vc(G), and in this section we show kernelization hardness of the problem.

Theorem 4. MAX MIN FVS parameterized by vc(G) does not admit a polynomial compression unless $coNP \subseteq NP/poly$.

Proof. We give a polynomial parameter transformation (PPT) from the MAX MIN VC problem. Given an instance (G, k) of MAX MIN VC, we construct in polynomial time an instance (G', k') of MAX MIN FVS as follows. We start with the graph G. We add a new vertex x and make it adjacent to every vertex of G. We add a set $V_x = \{x_1, x_2, \ldots, x_{n+3}\}$ of new vertices and make x adjacent to every vertex of V_x . Furthermore, we add a new vertex y and make y adjacent to every vertex of V_x . This completes the construction of G'. It is easy to see that $\mathsf{vc}(G') \leq \mathsf{vc}(G) + 2$. Finally we set k' = k + n + 2. We claim that G contains a minimal vertex cover of size at least k if and only if G' contains a minimal feedback vertex set of size at least k'.

Suppose C is a minimal vertex cover in G such that $|C| \ge k$. We observe that the set $C \cup (V_x \setminus \{x_1\})$ forms a minimal feedback vertex set of size at least k' in G'. Conversely, suppose that G' has a minimal feedback vertex set S of size at least k'. First we see that $x \notin S$. This is true because if $x \in S$ then $(V_x \cup \{y\}) \cap S = \emptyset$ as the vertices in $V_x \cup \{y\}$ are not part of any cycle in G' - x. This implies that $|S| \le n + 1$ which is a contradiction. Similarly, we can argue that $y \notin S$. As we know that $\{x, y\} \cap S = \emptyset$, we must have $|S \cap V_x| = n + 2$. This

implies that $|S \cap V(G)| \ge k$. Now, we show that $C = S \cap V(G)$ is a minimal vertex cover of G. It is easy to see that $C = S \cap V(G)$ is a vertex cover of G otherwise S will not be a feedback vertex set of G'. For the sake of contradiction assume that $C \setminus \{x\}$ is also a vertex cover of G. In this case, we observe that x is not part of any cycle in $G' - (S \setminus \{x\})$ which is a contradiction. Therefore C is a minimal vertex cover of size at least k in G.

5 An fpt-AS for MAX MIN FVS parameterized by vc(G)

An *fpt-approximation scheme (fpt-AS)* with parameterization κ is an algorithm whose input is an instance $x \in I$ and an $\epsilon > 0$, and it produces a $(1 - \epsilon)$ -approximate solution in time $f(\epsilon, \kappa(x)) \cdot |x|^{O(1)}$ for some computable function f. In this section we prove Theorem 3.

Proof (The Proof of Theorem 3). We present an $f(\epsilon, \mathsf{vc}(G)) \cdot n^{O(1)}$ time algorithm that produces a $(1 - \epsilon)$ -approximate solution for the problem, where n is the number of vertices in the input graph G. We assume that we have a minimum vertex cover C of size $\mathsf{vc}(G)$ of the input graph G = (V, E). We denote by I the independent set $V \setminus C$. Our goal here is to find a largest minimal FVS S with $C_{in} = S \cap C$, where $C_{in} \subseteq C$ is given. That is, we guess the intersection of S with vertex cover C. There are $2^{\mathsf{vc}(G)}$ possible guesses. Clearly, $C_{out} = \overline{S} \cap C$ contains the vertices of C which are outside the solution. If $G[C_{out}]$ is not a forest then return that C_{in} is a wrong guess and reject it. So from now onwards we assume that $G[C_{out}]$ is indeed a forest. We give some reduction rules to simplify the input instance.

Reduction EMMFVS 4 If there is a vertex $u \in I$ with at most one neighbour in C_{out} , delete u.

Reduction EMMFVS 5 If there is a vertex $u \in I$ such that $G[C_{out} \cup \{u\}]$ contains a cycle, then include u in the solution and delete u.




Fig. 5. Here $Q(a) = \{C_1, C_2, C_3\}, Q(b) = \{C_1, C_2, C_4\}, Q(c) = \{C_1, C_3\}, Q(d) = \{C_2, C_3, C_4\}.$ Note that $S_a = \{b, c, d\}.$

The algorithm first applies Reductions EMMFVS 1, EMMFVS 4 and EMM-FVS 5 exhaustively. Every vertex $u \in I$ has at least two neighbours in C_{out} , otherwise Reduction EMMFVS 4 would have been applied. Since Reduction EMMFVS 5 cannot be applied, we have that no two neighbours of $u \in I$ belong to the same connected component of $G[C_{out}]$. On the reduced instance, we run the following greedy algorithm. Suppose that C_{out} has connected components C_1, C_2, \dots We say connected component C_i is a neighbour of $u \in I$, that is $C_i \in Q(u)$, if G contains an edge (u, v) for some $v \in C_i$. We pick an arbitrary vertex $u \in I$ and define $S_u = \left\{ x_i \in I : |Q(u) \cap Q(x_i)| \ge 2 \right\}$. See Figure 5. Note that if u is not included in S then all the vertices of S_u must be included in S. The intention is that if $|S_u| \ge 2$, then we prefer not to include u in S, and hence include all the vertices of S_u in S as it is a maximization problem. But while including the vertices of S_u in the solution, we need to be careful about whether the inclusion of S_u in the solution, disturbs the minimality property of C_{in} . This can be verified by checking if each vertex in C_{in} still has a private cycle after the inclusion of S_u in the solution. Based on the above observations, we propose the following algorithm. We pick an arbitrary vertex $u \in I$, compute S_u and check the minimality of C_{in} assuming S_u is included in the solution. If the minimality of C_{in} is preserved then we set $S = S \cup S_u$, $I = I \setminus (S_u \cup \{u\})$, and $C_{out} = C_{out} \cup \{u\}$, that is, we include S_u in the solution and move u to C_{out} . As u has neighbours in at least two connected components of $G[C_{out}]$, when we move u to C_{out} , the number of components in $G[C_{out}]$ drops by at least 1. The algorithm again applies Reductions EMMFVS 4 and EMMFVS 5 exhaustively as C_{out} has been modified. On the other hand, if the minimality of C_{in} is not preserved then we set $S = S \cup \{u\}$ and $I = I \setminus \{u\}$. We repeat the above until I becomes empty.

There are $2^{\mathsf{vc}(G)}$ candidates for C_{in} ; for each guess the above algorithm returns a minimal FVS and finally we consider the maximum size solution obtained over all guesses. Suppose the algorithm outputs S. Let S_{opt} be an optimum solution. We claim that $|S| \geq |S_{opt}| - \mathsf{vc}(G)$. Let $C_{in} = C \cap S_{opt}$. Clearly, we have $|S_{opt}| \leq |C_{in}| + |I|$. Recall that the greedy algorithm adds all vertices from I to the solution except the ones that are moved to C_{out} . We claim that there are at most $\mathsf{vc}(G)$ vertices from I that are moved to C_{out} and therefore not added to the solution. Every time a vertex is moved to C_{out} , the number of connected components in $G[C_{out}]$ drops by at least one. After moving $\mathsf{vc}(G) - 1$ vertices, the number of connected components in $G[C_{out}]$ becomes one. Therefore, we have moved at most $\mathsf{vc}(G)$ vertices to C_{out} . This proves that $|S| \geq |C_{in}| + I - \mathsf{vc}(G) \geq |S_{opt}| - \mathsf{vc}(G)$.

Next, we propose an FPT approximation scheme. Given an input graph G, we first ask whether G has a minimal FVS of size at least $\frac{\operatorname{vc}(G)}{\epsilon}$. Note that this can be answered in time $10^{\frac{\operatorname{vc}(G)}{\epsilon}} n^{O(1)}$ using the FPT algorithm proposed in Section 2. If this is a no-instance then we can find $\operatorname{opt}(G)$ in the same time by repetitively using the FPT algorithm. If this is a yes-instance, then obviously

 $\operatorname{opt}(G) \geq \frac{\operatorname{vc}(G)}{\epsilon}$. Hence the value of the constructed solution S is at least

$$\frac{\mathsf{opt}(G) - \mathsf{vc}(G)}{\mathsf{opt}(G)} \ge 1 - \frac{\mathsf{vc}(G)}{\mathsf{opt}(G)} \ge 1 - \epsilon$$

times the optimum. That is, the constructed solution S is a $(1 - \epsilon)$ -approximate solution.

6 Conclusion and Open Problems

In this paper, we have studied MAX MIN FVS parameterized by the solution size and the vertex cover number of the input graph. We gave a single exponential time algorithm for MAX MIN FVS parameterized by solution size and a $\mathcal{O}^{\star}(2^{\mathcal{O}(\mathsf{vc}(G)\log\mathsf{vc}(G))})$ time algorithm parameterized by $\mathsf{vc}(G)$. Finally we proposed an FPT-AS parameterized by $\mathsf{vc}(G)$ with better running time $2^{\mathcal{O}\left(\frac{\mathsf{vc}(G)}{\epsilon}\right)}n^{\mathcal{O}(1)}$. We list some nice problems that emerge from the results here: can our algorithm parameterized by $\mathsf{vc}(G)$ be made $c^{\mathcal{O}(\mathsf{vc}(G))}$ time algorithm, for a fixed constant c? A $2^{\mathcal{O}(\omega^{\mathcal{O}(1)})}n^{\mathcal{O}(1)}$ time algorithm seems possible where ω is the treewidth of the input graph. Therefore, it would be interesting to see if the idea in Theorem 2 can be extended to study MAX MIN FVS parameterized by $\mathsf{fvs}(G)$.

References

- J. Araújo, M. Bougeret, V. Campos, and I. Sau. A new framework for kernelization lower bounds: The case of maximum minimal vertex cover. In *IPEC 2021-16th International Symposium on Parameterized and Exact Computation*, volume 214, pages 4–1, 2021.
- H. L. Bodlaender. On disjoint cycles. International Journal of Foundations of Computer Science, 5(1):59–68, 1994.
- N. Boria, F. D. Croce, and V. T. Paschos. On the max min vertex cover problem. Discret. Appl. Math., 196:62–71, 2015.
- M. Cygan, F. V. Fomin, L. Kowalik, D. Lokshtanov, D. Marx, M. Pilipczuk, M. Pilipczuk, and S. Saurabh. *Parameterized Algorithms*. Springer, 2015.
- R. G. Downey and M. R. Fellows. Fixed-parameter tractability and completeness i: Basic results. SIAM J. Comput., 24:873–921, 1995.
- 6. R. G. Downey and M. R. Fellows. Parameterized Complexity. Springer, 2012.
- L. Dublois, T. Hanaka, M. K. Ghadikolaei, M. Lampis, and N. Melissinos. (in)approximability of maximum minimal FVS. J. Comput. Syst. Sci., 124:26–40, 2022.
- 8. H. Eto, T. Hanaka, Y. Kobayashi, and Y. Kobayashi. Parameterized algorithms for maximum cut with connectivity constraints. In *IPEC*, 2019.
- 9. T. Hanaka, H. L. Bodlaender, T. C. van der Zanden, and H. Ono. On the maximum weight minimal separator. *Theoretical Computer Science*, 796:294–308, 2019.
- Y. Iwata and Y. Kobayashi. Improved analysis of highest-degree branching for feedback vertex set. In 14th International Symposium on Parameterized and Exact Computation, IPEC 2019, September 11-13, 2019, Munich, Germany, volume 148 of LIPIcs, pages 22:1–22:11, 2019.

15

- 11. J. Li and J. Nederlof. Detecting feedback vertex sets of size k in $O^*(2.7^k)$ time. In Proceedings of the Thirty First Annual ACM-SIAM Symposium on Discrete Algorithms, SODA, pages 971–981, 2020.
- S. Mishra and K. Sikdar. On the hardness of approximating some NP-optimization problems related to minimum linear ordering problem. *RAIRO - Theoretical Informatics and Applications - Informatique Théorique et Applications*, 35(3):287–309, 2001.
- M. Zehavi. Maximum minimal vertex cover parameterized by vertex cover. SIAM J. Discret. Math., 31(4):2440–2456, 2017.