

OrderedCuts: A new approach for computing Gomory-Hu tree

Vladimir Kolmogorov
 Institute of Science and Technology Austria (ISTA)
 vnk@ist.ac.at

Abstract

The Gomory-Hu tree, or a cut tree, is a classic data structure that stores minimum s - t cuts of an undirected weighted graph for all pairs of nodes (s, t) . We propose a new approach for computing the cut tree based on a reduction to the problem that we call **OrderedCuts**. Given a sequence of nodes s, v_1, \dots, v_ℓ , its goal is to compute minimum $\{s, v_1, \dots, v_{i-1}\}$ - v_i cuts for all $i \in [\ell]$. We show that the cut tree can be computed by $\tilde{O}(1)$ calls to **OrderedCuts**. We also establish new results for **OrderedCuts** that may be of independent interest. First, we prove that all ℓ cuts can be stored compactly with $O(n)$ space in a data structure that we call an **OC tree**. We define a weaker version of this structure that we call *depth-1 OC tree*, and show that it is sufficient for constructing the cut tree. Second, we prove results that allow divide-and-conquer algorithms for computing OC tree. We argue that the existence of divide-and-conquer algorithms makes our new approach a good candidate for a practical implementation.

We study the problem of computing the *Gomory-Hu (GH) tree* [11] (aka *cut tree*) in an undirected weighted graph $G = (V, E, w)$ with non-negative weights. This is a weighted spanning tree \mathcal{T} on nodes V with the property that for any distinct $s, t \in V$, a minimum s - t cut $S \subseteq V$ in \mathcal{T} is also a minimum s - t cut in G . It has numerous applications in various domains (see e.g. Section 1.4 in [4]).

More than half a century ago Gomory and Hu [11] showed that such tree exists and can be computed using $n - 1$ maximum flow computations and graph contractions. This bound has been improved upon only very recently: in a breakthrough result Abboud et al. showed in [1] that the GH tree can be computed w.h.p. in time $\tilde{O}(n^2)$. This very exciting development still leaves some open questions:

- Is further improvement possible, e.g. is there an $O(m^{1+o(1)})$ algorithm? (This is Open Question 1.4 in [3]).
- Is there a Las-Vegas algorithm that computes a GH tree with probability one (rather than w.h.p.) faster than $O(n)$ maxflows?
- What is the most efficient algorithm in practice?

We argue that a Las-Vegas algorithm may be preferable in practice to a Monte-Carlo algorithm even if one is satisfied with an answer that holds with high probability (and so the last two questions are connected). Indeed, in a Monte-Carlo algorithm one may need to set parameters such as the number of iterations to their worst-case bounds since one cannot observe directly whether an iteration succeeded or not. This is not the case for a Las Vegas algorithm, and so for practical instances the latter may perform much faster than the worst-case bound.

In an attempt to address these questions we investigate a new approach for constructing a GH tree based on the reduction to the problem that we call **OrderedCuts**. The latter is formulated below; we use notation $f(U, v)$ to denote the cost of a minimum U - v cut in $G = (V, E, w)$.

Algorithm 1: **OrderedCuts** $(s, v_1, \dots, v_\ell; G)$ /* s, v_1, \dots, v_ℓ are distinct nodes in G */

- 1 for each $i \in [\ell]$ compute s - v_i cut S_i with $v_i \in S_i$ s.t. $\mathbf{cost}(S_i) \leq f(\{s, v_1, \dots, v_{i-1}\}, v_i)$
 - 2 for each $v \in V$ compute $\lambda(v) = \min_{i \in [\ell]: v \in S_i} \mathbf{cost}(S_i)$, return λ
-

One possibility is to choose S_i as a minimum $\{s, v_1, \dots, v_{i-1}\}-v_i$ cut for each $i \in [\ell]$; we will refer to such version as *strong OrderedCuts* (and accordingly to the general version as *weak OrderedCuts*). Another option is to choose S_i as a minimum $s-v_i$ cut; then the procedure would return vector λ with $\lambda(v_i) = f(s, v_i)$. Thus, $\text{OrderedCuts}(s, v_1, \dots, v_\ell; G)$ can be trivially implemented (in time $O(n + m)$) if we have an access to the Gomory-Hu tree for G . Our first result is the opposite direction given by the theorem below.

Theorem 1. *There exists a randomized (Las-Vegas) algorithm for computing GH tree for graph G with expected complexity $\tilde{O}(1) \cdot (t_{\text{OC}}(n, m) + t_{\text{MC}}(n, m))$, where $t_{\text{OC}}(n, m)$ and $t_{\text{MC}}(n, m)$ are the complexities of $\text{OrderedCuts}(\cdot)$ and minimum s - t cut computations respectively on a sequence of graphs H_1, \dots, H_k that have $O(n)$ nodes and $O(m)$ edges in total.*^{1 2}

We then focus on the strong version of OrderedCuts , and prove several new results for it (which we believe may be of independent interest).

First, we show that all cuts S_1, \dots, S_ℓ can be stored compactly with $O(n)$ space using a data structure that we call an OC tree . We also define the notion of a *depth-1 OC tree* (or OC_1 tree), and prove that Theorem 1 still holds if the OC tree oracle is replaced with an OC_1 tree oracle (at the expense of extra logarithmic factors). Note that the OC_1 tree can be trivially computed from the OC tree by repeatedly removing leaves at depth two or larger, but could potentially be computed faster.

Second, we present two lemmas that allow the use of divide-and-conquer strategies for computing OC tree . On the high level, these strategies have the same form as the computations performed by the classical Gomory-Hu algorithm: given a problem on the current graph G , run maxflow algorithm to obtain a certain cut (S, T) and then recurse on the problems defined by S and by T (contracting the other set to a single vertex). If cuts (S, T) were balanced (meaning $\min\{|S|, |T|\} = \Omega(|V_G|)$) then the maximum depth of the recursion would be logarithmic in n and the approaches would take $\tilde{O}(1)$ calls to the maxflow algorithm on graphs of size $(O(n), O(m))$. Unfortunately, we cannot show the balancedness of cuts in either of the approaches. We were only able to prove that the OC tree can be computed faster than a naive approach in the case when the order of nodes in the sequence (v_1, \dots, v_ℓ) is a random permutation (see Theorem 22 in Section 3).

There is, however, one important distinction between the Gomory-Hu algorithm and the algorithm for computing OC tree : cuts computed in the former approach are minimum s - t in the original graph for some terminals s, t , whereas cuts in the latter approaches are minimum S - T cuts in the original graph where the sizes of S, T may grow at deeper levels of the recursion, and furthermore the size of T can be controlled to a certain degree. Thus, one may expect to obtain more balanced cut in the latter approach.

To test this intuition, we have implemented a version of the algorithm based on the OrderedCuts procedure, and compared it experimentally with the classical Gomory-Hu algorithm. On all of our test instances (except for one family of graphs, name cycle graphs) the total size of graphs on which the maxflow algorithm is run was significantly smaller in the OrderedCuts approach compared to the GH approach. For the majority of test instances this translated to smaller runtimes (and outperformed previous implementations of [10] and [6]). Details of this study are reported in [13].

We thus believe that besides theoretical contributions described above our work has a significant practical value, as it provides a basis for a practical implementation that appears to be the current state-of-the art.

¹In the case of minimum s - t cut computations it suffices to take $k = 1$, since such computations in graphs H_1, \dots, H_k are equivalent to a minimum s - t cut computation in the union of H_1, \dots, H_k . The same holds for the two special cases of OrderedCuts discussed before Theorem 1 (the sources need to be merged). However, in the most general case of OrderedCuts such reduction may not work.

²Throughout the paper we assume that $t_{\text{MF}}(n, m) = \Omega(n + m)$ and $t_{\text{OC}}(n, m) = \Omega(n + m)$, and so we do not explicitly include the time spent outside these subroutines in complexity bounds.

Related work GH tree construction algorithms have been extensively studied in the literature. A significant progress has been made for unweighted simple graphs [7, 4, 3, 17, 5] and for the approximate version of the problem [2, 16, 14]. Several authors also explored fine-grained reductions from the GH construction problem to some other problems. Our work also follows this direction, so we describe existing results in more detail.

Abboud, Krauthgamer and Trabelsi considered in [2] the “single source min cut problem” whose goal is to compute minimum s - v cuts C_{sv} for a fixed source node s and all other nodes v . More precisely, Abboud et al. considered two variants; one of them asks for the set of edges of C_{sv} , and the other one asks only for the cost of C_{sv} which we denote as $f(s, v) = \text{cost}(C_{sv})$. These problems can be formulated as the follows.

Algorithm 2: SingleSourceMinCut($s; G$).

```

1 for each  $v \in V - \{s\}$  compute minimum  $s$ - $v$  cut  $C_{sv}$ 
2 build data structure  $\mathcal{D}$  that supports operation  $\text{Query}(v)$  for given  $v \in V - \{s\}$ , return  $\mathcal{D}$ 
  /*  $\text{Query}(v)$  should return  $\delta C_{sv}$  in time  $\tilde{O}(|\delta C_{sv}|)$ , where  $\delta C_{sv}$  is the set of
     edges of the cut  $(C_{sv}, V - C_{sv})$  */
```

Algorithm 3: SingleSourceMaxFlow($s; G$).

```

1 for each  $v \in V - \{s\}$  compute  $\lambda(v) = f(s, v)$ , return  $\lambda$ 
```

It was shown in [2] that the GH tree can be constructed by $\tilde{O}(1)$ calls to `SingleSourceMinCut(\cdot)` on graphs with $O(n)$ nodes and $O(m)$ edges plus $\tilde{O}(m)$ additional work. For the second procedure [2] was able to show a weaker result, namely how to construct a *flow-equivalent tree* for G by $\tilde{O}(1)$ calls to `SingleSourceMaxFlow(\cdot)` on graphs with $O(n)$ nodes and $O(m)$ edges plus $\tilde{O}(n)$ additional work.³ Li, Panigrahi and Saranurak observed in [17] that instead of computing values $f(s, v)$ it suffices to verify whether $f(s, v)$ equals a given upper bound $\mu(v)$. More precisely, they considered the following problem; value γ in the precondition is a positive constant.

Algorithm 4: SingleSourceMaxflowVerification($s, X, \mu; G$).

```

/* preconditions:  $X \subseteq V - \{s\}$ ,  $\max_{v \in X} f(s, v) \leq (1 + \gamma) \min_{v \in X} f(s, v)$ ,  $\mu(v) \geq f(s, v)$  for all  $v \in X$  */
```

```

1 compute  $Y = \{v \in X : \mu(v) = f(s, v)\}$ , return  $Y$ 
```

It was shown in [17] that the GH tree can be constructed via $\tilde{O}(1)$ calls to `SingleSourceMaxflowVerification` and to the maxflow algorithm on graphs of size (n, m) ; if $\gamma = +\infty$ then the answer is correct with probability 1, otherwise it is correct w.h.p.. Abboud et al. designed in [1] a Monte-Carlo algorithm for `SingleSourceMaxflowVerification` with $\gamma = 0.1$ whose complexity is $\tilde{O}(n^2)$, and thus obtained the improvement over $O(n)$ maxflow computations mentioned earlier.

Note that `SingleSourceMaxflow` can be viewed as a special case of `OrderedCuts` and of `SingleSourceMaxflowVerification` (via trivial reductions). The latter two problems appear incomparable.

Connection to the Hao-Orlin algorithm The strong version of `OrderedCuts` is reminiscent of the Hao-Orlin algorithm [12] for computing a minimum cut in a graph. The latter also computes minimum $\{s, v_1, \dots, v_{i-1}\}$ - v_i cut for each $i \in [\ell]$, for some sequence of nodes s, v_1, \dots, v_ℓ . It has the same complexity $O(nm \log(n^2/m))$ as a single call to a push-relabel maxflow algorithm. The crucial difference is that the Hao-Orlin algorithm selects the order of nodes v_1, \dots, v_ℓ itself; it cannot be used for a given ordering of nodes. Note that the Hao-Orlin algorithm works for directed graphs, whereas our results for `OrderedCuts` are restricted to undirected weighted graphs.

The rest of the paper is organized as follows. Section 1 gives background on GH tree construc-

³A flow-equivalent tree for G is a spanning tree \mathcal{T} on V such that for any $s, t \in V$, the costs of the minimum cut s - t in G and in \mathcal{T} coincide. Every GH tree is also flow-equivalent tree, but the reverse is not true.

tion algorithms. Section 2 presents a new algorithm based on the reduction to the **OrderedCuts** problem, and proves Theorem 1. Section 3 defines the notion of **OC** trees and studies their properties. Finally, Section 4 introduces depth-1 **OC** trees and shows how they can be used for constructing **GH** trees.

1 Background and notation

Consider an undirected weighted graph $G = (V_G, E_G, w_G)$. A *cut* of G is a set U with $\emptyset \subsetneq U \subsetneq V_G$. It is an S - T *cut* for disjoint subsets S, T of V_G if $T \subseteq U \subseteq V_G - S$. The cost of U is defined as $\text{cost}_G(U) = \sum_{uv \in E_G: \{u,v\} \cap U = 1} w_G(uv)$. The cost of a minimum S - T cut in G is denoted as $f_G(S, T)$. If one of the sets S, T is singleton, e.g. $T = \{t\}$, then we say “ S - t cut” and write $f_G(S, t)$ for brevity.

When graph G is clear from the context we omit subscript G and write $V, E, \text{cost}(U), f(S, T)$.

Gomory-Hu algorithm Below we review the classical Gomory-Hu algorithm [11] for computing the cut tree. It works with a *partition tree* for G which is a spanning tree $\mathcal{T} = (V_{\mathcal{T}}, E_{\mathcal{T}})$ such that $V_{\mathcal{T}}$ is a partition of V . An element $X \in V_{\mathcal{T}}$ is called a *supernode* of \mathcal{T} . Each edge $XY \in E_{\mathcal{T}}$ defines a cut in G in a natural way; it will be denoted as C_{XY} where we assume that $Y \subseteq C_{XY}$. We view \mathcal{T} as a **weighted** tree where the weight of XY (equivalently, $f_{\mathcal{T}}(X, Y)$) equals $\text{cost}_G(C_{XY})$. Tree \mathcal{T} is *complete* if all supernodes are singleton subsets of the form $\{v\}$; such \mathcal{T} can be identified with a spanning tree on V in a natural way.

We use the following notation for a graph G , partition tree \mathcal{T} on V and supernode $X \in V_{\mathcal{T}}$:

- $H = G[\mathcal{T}, X]$ is the auxiliary graph obtained from G as follows: (i) initialize $H := G$, let \mathcal{F} be the forest on $V_{\mathcal{T}} - \{X\}$ obtained from tree \mathcal{T} by removing node X ; (ii) for each edge $XY \in E_{\mathcal{T}}$ find the connected component \mathcal{C}_Y of \mathcal{F} containing Y , and then modify H by contracting nodes in $\bigcup_{C \in \mathcal{C}_Y} C$ to a single node called v_Y . Note that $V_H = X \cup \{v_Y : XY \in E_{\mathcal{T}}\}$.

Algorithm 5: Gomory-Hu algorithm for graph G .

```

1 set  $\mathcal{T} = (\{V\}, \emptyset)$ 
2 while exists  $X \in V_{\mathcal{T}}$  with  $|X| \geq 2$  do
3   pick supernode  $X \in V_{\mathcal{T}}$  with  $|X| \geq 2$  and distinct  $s, t \in X$ 
4   form auxiliary graph  $H = G[\mathcal{T}, X]$ 
5   compute minimum  $s$ - $t$  cut  $S$  in  $H$ 
6   define  $(A, B) = (X - S, X \cap S)$ , update  $V_{\mathcal{T}} := (V_{\mathcal{T}} - \{X\}) \cup \{A, B\}$  and  $E_{\mathcal{T}} := E_{\mathcal{T}} \cup \{AB\}$ 
7   for each  $XY \in E_{\mathcal{T}}$  update  $E_{\mathcal{T}} := (E_{\mathcal{T}} - \{XY\}) \cup \{CY\}$  where  $C = \begin{cases} A & \text{if } v_Y \notin S \\ B & \text{if } v_Y \in S \end{cases}$ 

```

Note that at every step Algorithm 5 splits some supernode X into two smaller supernodes, A and B . We will use a generalized version proposed by Abboud et al. [2] in which one iteration

that may split X into more than two supernodes.

Algorithm 6: Generalized Gomory-Hu algorithm for graph G .

```

1 set  $\mathcal{T} = (\{V\}, \emptyset)$ 
2 while exists  $X \in V_{\mathcal{T}}$  with  $|X| \geq 2$  do
3   pick supernode  $X \in V_{\mathcal{T}}$  with  $|X| \geq 2$ , form auxiliary graph  $H = G[\mathcal{T}, X]$ 
4   find node  $s \in X$  and non-empty laminar family  $\Pi$  of subsets of  $V_H - \{s\}$  such that
     each  $S \in \Pi$  is a minimum  $s$ - $t$  cut in  $H$  for some  $t \in X$ 
5   while  $\Pi \neq \emptyset$  do
6     pick minimal set  $S \in \Pi$ 
7     update  $\mathcal{T}$  as in lines 6-7 of Alg. 5 for given  $S$  (with  $(A, B) = (X - S, X \cap S)$ )
8     update  $X := A$ , update  $H$  accordingly to restore  $H = G[\mathcal{T}, X]$  /* now  $v_B \in V_H$  */
9     remove  $S$  from  $\Pi$ , for each  $S' \in \Pi$  with  $S \subseteq S'$  replace  $S'$  with  $(S' - S) \cup v_B$  in  $\Pi$ 

```

Note that graph H at line 8 is updated by contracting set S to a single vertex named v_B . Clearly, such transformation and the update at line 9 preserve the property of set Π : it is still a laminar family of subsets of $V_H - \{s\}$ such that each $S \in \Pi$ is a minimum s - t cut in H for some $t \in X$. This means Algorithm 6 updates tree \mathcal{T} in the same way as Algorithm 5 (with certain choices of triplets (X, s, t)). This fact implies the correctness of Algorithm 6.

To conclude this section, we state two more results that we will need later. The first one deals with procedure `IsolatingCuts`, which appeared in [15] (and independently in [4]). It can be formulated as follows.

Algorithm 7: `IsolatingCuts`($s, Y; G$).

```

1 for each  $v \in Y$  compute minimum  $(Y \cup \{s\} - \{v\})$ - $v$  cut  $S_v$ , return these cuts

```

Importantly, Algorithm 7 can be efficiently implemented.

Theorem 2 ([15]). *There exists an implementation of `IsolatingCuts`($s, \{v_1, \dots, v_\ell\}; G$) that runs in time $O(\log \ell) \cdot t_{\text{MC}}(n, m)$ and outputs a set of disjoint cuts $\{S_{v_i} : i \in [\ell]\}$.⁴*

The second result appeared in [10] in the context of the Hao-Orlin algorithm. Using our notation, it can be stated as follows.

Lemma 3 ([10]). *Consider distinct nodes v_0, v_1, \dots, v_k in an undirected graph G with $k \geq 1$. If $f(\{v_0, \dots, v_{k-1}\}, v_k) \leq \min_{i \in [k]} f(\{v_0, \dots, v_{i-1}\}, v_i)$ then $f(\{v_0, \dots, v_{k-1}\}, v_k) = f(v_0, v_k)$.*

Proof. Denote $\lambda_i = f(\{v_0, \dots, v_{i-1}\}, v_i)$. Suppose the claim is false, then there exists s - v_k cut S with $v_k \in S$ and $\text{cost}(S) < \lambda_k$. Let i be the largest index in $[k]$ such that $\{s, v_1, \dots, v_{i-1}\} \subseteq V - S$, then $v_i \in S$ and so $\text{cost}(S) \geq \lambda_i$, contradicting condition $\lambda_k \leq \min_{i \in [k]} \lambda_i$. \square

Throughout the paper we will use notation C_{uv} to denote the minimal minimum u - v cut in a given graph. (The graph will always be clear from the context). Note that $v \in C_{uv}$. Set C_{uv} is also known as the *latest* u - v cut [8]. We also denote $\langle \Pi \rangle = \bigcup_{S \in \Pi} S$ for a set of subsets Π .

2 Computing Gomory-Hu tree via OrderedCuts

As mentioned earlier, we will use Algorithm 6. Its key computational step is line 4; we need to efficiently compute minimum s - t cuts for fixed node s and many nodes $t \in V_H - \{s\}$. One

⁴Ignoring base cases, the algorithm can be described as follows (see the description in [4]):

- (1) compute minimum $\{s, v_1, \dots, v_k\}$ - $\{v_{k+1}, \dots, v_\ell\}$ cut (S, T) in G where $k = \lfloor \ell/2 \rfloor$;
- (2) make recursive calls `IsolatingCuts`($s'', \{v_1, \dots, v_k\}; G''$) and `IsolatingCuts`($s', \{v_{k+1}, \dots, v_\ell\}; G'$) where G' and G'' are the graphs obtained from G by contracting respectively sets S and T to a single nodes s' and s'' ;
- (3) combine the results.

potentially useful subroutine for this is procedure `IsolatingCuts(s, Y)`. It does compute many cuts S_v at once, and some of them are guaranteed to be minimum s - v cuts. In particular, this holds if $Y \cap C_{sv} = \{v\}$. Unfortunately, it does not seem possible to distinguish “true” minimum s - v cuts in the output of `IsolatingCuts(·)` from “false” ones. In the next section we describe procedure `CertifiedOrderedCuts` that also produces many minimum s - v cuts, and importantly certifies some of these cuts as “true” cuts.

2.1 Procedure `CertifiedOrderedCuts`

Consider undirected weighted graph $G = (V, E, w)$ and a sequence of distinct nodes s, v_1, \dots, v_ℓ in V . Let us define the following algorithm.

Algorithm 8: `CertifiedOrderedCuts(s, v1, …, vℓ; G)`.

- 1 call $\lambda \leftarrow \text{OrderedCuts}(s, v_1, \dots, v_\ell; G)$
 - 2 compute $Y^* = \{v_k : \lambda(v_k) \leq \min_{i \in [k-1]} \lambda(v_i), k \in [\ell]\}$
 - 3 call `IsolatingCuts(s, Y*; G)` to get cut $S_v \subseteq V - \{s\}$ for each $v \in Y^*$
 - 4 define $\mathcal{C}^* = \{S_v : v \in Y^*, \text{cost}(S_v) = \lambda(v)\}$
 - 5 return (λ, \mathcal{C}^*)
-

Lemma 4. *Let (λ, \mathcal{C}^*) be the output of `CertifiedOrderedCuts(s, v1, …, vℓ; G)`, and denote $Y = \{v_1, \dots, v_\ell\}$. Pair (λ, \mathcal{C}^*) has the following properties.*

- (a) *Subsets in \mathcal{C}^* are disjoint, and each $S \in \mathcal{C}^*$ is a minimum s - v cut for some $v \in Y$.*
- (b) *If $Y \cap C_{sv_k} = \{v_k\}$ and $f(s, v_k) \leq \min_{i \in [k]} f(s, v_i)$ then \mathcal{C}^* contains a minimum s - v_k cut.*
- (c) *There exists a family of cuts $\mathcal{C} \subseteq \{S : \emptyset \neq S \subseteq V - \{s\}\}$ such that*
 - (i) $\lambda(v) = \min_{S \in \mathcal{C}: v \in S} \text{cost}(S)$ for each $v \in V - \{s\}$ (and hence $\lambda(v) \geq f(s, v)$);
 - (ii) *if $\{v_1, \dots, v_k\} \cap C_{sv_k} = \{v_k\}$ then \mathcal{C} contains a minimum s - v_k cut (and hence $\lambda(v_k) = f(s, v_k)$) and $\lambda(v) \leq f(s, v_k)$ for all $v \in C_{sv_k}$.*

Proof. We take $\mathcal{C} = \{S_k : k \in [\ell]\}$ to be the set of cuts considered inside the call to `OrderedCuts(·)`, then the condition in (c.i) holds by the definition of `OrderedCuts`. We claim that for each $v_k \in Y^*$ we have $\lambda(v_k) = f(s, v_k)$. Indeed, let S be a minimum s - v_k cut and i be the largest index in $[k]$ such that $\{s, v_1, \dots, v_{i-1}\} \subseteq V - S$, then $v_i \in S$ and so $f(s, v_k) = \text{cost}(S) \geq f(\{s, v_1, \dots, v_{i-1}\}, s_i) \geq \lambda(v_i) \geq \lambda(v_k)$, implying the claim. (The middle inequality holds by the definition of `OrderedCuts` and the last inequality holds since $v_k \in Y^*$). We are now ready to prove the lemma.

Part (a) Sets S_v at line 3 (and thus sets in \mathcal{C}^*) are disjoint by the definition of `IsolatingCuts`. Set S_v is added to \mathcal{C}^* only if $v \in Y^*$ and $\text{cost}(S_v) = \lambda(v) = f(s, v)$, and so the claim holds.

Parts (b) and (c.ii) Consider $k \in [\ell]$ with $\{v_1, \dots, v_k\} \cap C_{sv_k} = \{v_k\}$. The condition implies that C_{sv_k} is a minimum $\{s, v_1, \dots, v_{k-1}\}$ - v_k cut and hence $f(\{s, v_1, \dots, v_{k-1}\}, v_k) = f(s, v_k)$. Therefore, set $S_k \in \mathcal{C}$ must satisfy $\text{cost}(S_k) \leq f(s, v_k)$, i.e. S_k is a minimum s - v_k cut. This proves part (c.ii). Now suppose that $Y \cap C_{sv_k} = \{v_k\}$ and $f(s, v_i) \geq f(s, v_k)$ for each $i \in [k]$. We have $\lambda(v_k) = f(s, v_k)$ and $\lambda(v_i) \geq f(s, v_i)$ for $i \in [k]$, therefore node v_k will be added to Y^* . We also have $Y^* \cap C_{sv_k} = \{v_k\}$, and so set C_{sv_k} returned by `IsolatingCuts(s, Y*; G)` is a minimum s - v_k cut. This set satisfies $\text{cost}(C_{sv_k}) = \lambda(v_k) = f(s, v_k)$, and so S_{v_k} will be added to \mathcal{C}^* . \square

Remark 1. *We will use only properties of `CertifiedOrderedCuts(·)` given in Lemma 4. Any other implementation of `CertifiedOrderedCuts(·)` would work, as long as Lemma 4 holds. If, for example, a strong version of `OrderedCuts` is used that explicitly constructs OC tree then set \mathcal{C}^* can be constructed from this tree without calling `IsolatingCuts`, see Section 3. Furthermore, in that section we discuss a weaker criterion for adding cuts to \mathcal{C}^* that in general can certify a larger set of cuts stored in an OC tree.*

2.2 Computing cuts for a fixed source

We now come back to the main computational problem at line 4 of Algorithm 6: computing node $s \in X$ and a set of disjoint subsets Π such that each $S \in \Pi$ is an s - t cut in H for some $t \in X$. In this section we describe our main subroutine that solves this problem for a fixed source node s . Then in Section 2.3 we discuss how to select s , and analyze the complexity of the resulting algorithm.

Let us fix graph H , subset $X \subseteq V_H$, node $s \in V_H$ and number $L \geq 1$. It will be convenient to assume that $s \notin X$. For brevity of notation we let $V = V_H$ to be the set of nodes of H . Let us also denote

$$\begin{aligned}\widehat{\Pi}_s^{(L)} &= \{S \subseteq V - \{s\} : S \text{ is a minimum } s\text{-}t \text{ cut for some } t \in X, |S \cap X| \leq L\} \\ \Pi_s^{(L)} &= \{S = C_{st} : t \in X, |S \cap X| \leq L\} \subseteq \widehat{\Pi}_s^{(L)}\end{aligned}$$

It is well-known that family $\Pi_s^{(L)}$ is laminar (this can be easily deduced from the submodularity inequality for cuts).

We say that the output of `CertifiedOrderedCuts`(\cdot) is *minimal* if under the condition (b) of Lemma 4 family \mathcal{C}^* contains the minimal minimum s - v_k cut C_{sv_k} , rather than an arbitrary minimum s - v_k cut. The main result of this section is given by the following theorem.

Theorem 5. *There exists an algorithm that outputs a laminar family of subsets $\Pi \subseteq \widehat{\Pi}_s^{(L)}$. It makes $O(\log^3 |X|)$ calls to procedure `CertifiedOrderedCuts` for graph H and performs $O(|X| \log^4 |X|)$ additional work. Furthermore, it satisfies $\langle \Pi \rangle = \langle \Pi_s^{(L)} \rangle$ with probability at least $1 - 1/\text{poly}(|X|)$ (for an arbitrary fixed polynomial) assuming that all outputs of `CertifiedOrderedCuts` are minimal.*

Our algorithm is given below. Its parameter is a sequence of probabilities $\alpha_1, \dots, \alpha_{2N}$ that will be specified later. `RandomSubset`($U; \alpha$) in line 3 is a random subset of U in which each element $v \in U$ is included independently with prob. α .

Algorithm 9: `FixedSourcePartition`($s, X, L; H$).

```

1 set  $\Pi = \emptyset$  and  $\mu(v) = \text{cost}(\{v\})$  for all  $v \in V - \{s\}$ 
2 for  $i = 1, \dots, 2N$  do
3   sample  $Y \leftarrow \text{RandomSubset}(X - \langle \Pi \rangle; \alpha_i)$ 
4   sort nodes in  $Y$  as  $v_1, \dots, v_\ell$  so that  $\mu(v_1) \geq \dots \geq \mu(v_\ell)$ ,  $\ell = |Y|$ 
5   call  $(\lambda, \mathcal{C}^*) \leftarrow \text{CertifiedOrderedCuts}(s, v_1, \dots, v_\ell; H)$ 
6   update  $\mu(v) := \min\{\mu(v), \lambda(v)\}$  for  $v \in Y$ 
7   update  $\Pi := \Pi \cup \{S \in \mathcal{C}^* : |S \cap X| \leq L\}$ 
8   if  $\Pi$  becomes non-laminar then terminate and return  $\emptyset$ 
9 return  $\Pi$ 

```

By Lemma 4(a), set Π in Algorithm 9 always satisfies $\Pi \subseteq \widehat{\Pi}_s^{(L)}$. For the rest of analysis we assume that all outputs of `CertifiedOrderedCuts` are minimal, and thus $\Pi \subseteq \Pi_s^{(L)}$. We will show next that there exists sequence $\alpha_1, \dots, \alpha_{2N}$ with $N = \Theta(\log^3 |X|)$ for which $\langle \Pi \rangle = \langle \Pi_s^{(L)} \rangle$ w.h.p..

We will need some notation. We write $u \sim v$ for nodes $u, v \in X$ if $C_{su} = C_{sv}$. Clearly, \sim is an equivalence relation on X . Let Φ be the set of equivalence classes of this relation with $\langle \Phi \rangle = X$, and for $v \in X$ let $\llbracket v \rrbracket \in \Phi$ be the class to which v belongs. We write $\llbracket u \rrbracket \preceq \llbracket v \rrbracket$ if $C_{su} \subseteq C_{sv}$. Clearly, \preceq is a partial order on Φ . Furthermore, laminarity of cuts C_{sv} implies that \preceq can be represented by a rooted forest \mathcal{F} on nodes Φ so that $A \preceq B$ for $A, B \in \Phi$ iff A belongs to the subtree of \mathcal{F} rooted at B . For node $A \in \Phi$ we denote $A^\downarrow = \{B \in \Phi : B \preceq A\}$; equivalently, A^\downarrow is the set of nodes of the subtree of \mathcal{F} rooted at A . It can be seen that $C_{sv} \cap X = \langle \llbracket v \rrbracket^\downarrow \rangle$ for $v \in X$.

Consider $R \in \Phi$. We say that subset $\Psi \subseteq \Phi$ is *R -rooted* if it can be represented as $\Psi = R^\downarrow - \bigcup_{A \in \tilde{\Psi}} A^\downarrow$ for some subset $\tilde{\Psi} \subseteq R^\downarrow$. The minimal set $\tilde{\Psi}$ in this representation will be denoted as Ψ^- ; clearly, such minimal $\tilde{\Psi}$ exists, and equals the set of maximal elements of $R^\downarrow - \Psi$ w.r.t.

\preceq . One exception is the set $\Psi = \emptyset$: for such Ψ we define $\Psi^- = \{R\}$ (set R will always be clear from the context). It can be seen that if Ψ is R -rooted and A, B are distinct nodes in Ψ^- then sets $A^\downarrow, B^\downarrow$ are disjoint.

Now consider subsets $Y \subseteq X$, $\Psi \subseteq \Phi$ and node $v \in \langle \Psi \rangle$. Borrowing terminology from [16], we say that Y *hits* v in Ψ if $C_{sv} \cap \langle \Psi \rangle \cap Y = \{v\}$. We denote

$$\Psi[Y] = \Psi - \bigcup_{v : Y \text{ hits } v \text{ in } \Psi} \llbracket v \rrbracket^\downarrow$$

For subsets Y_1, \dots, Y_k we also denote $\Phi[Y_1, \dots, Y_k] = \Phi[Y_1] \dots [Y_k]$. Clearly, if Φ is R -rooted then so is $\Phi[Y_1, \dots, Y_k]$. With this notation in place, we proceed with the analysis of Algorithm 9.

We can assume that subset Y in line 3 is generated by first sampling $\hat{Y} \leftarrow \text{RandomSubset}(X; \alpha_i)$ and then taking $Y = \hat{Y} - \langle \Pi \rangle$. Let $\Pi_i, \lambda_i, \mathcal{C}_i^*, \mu_i, \hat{Y}_i, Y_i$ for $i \in [2N]$ be the variables at the end of the i -th iteration, and Π_0, μ_0 be as initialized at line 1. We refer to iterations $i = 1, \dots, N$ as the *first stage*, and to iterations $i = N + 1, \dots, 2N$ as the *second stage*. The lemma below analyzes the first stage.

Lemma 6. *Suppose that $R^\downarrow[\hat{Y}_1, \dots, \hat{Y}_N] = \emptyset$ for $R \in \Phi$. Then $\mu_N(v) = f(s, v)$ for all $v \in R - \langle \Pi_N \rangle$.*

Proof. Denote $\Psi_i = R^\downarrow[\hat{Y}_1, \dots, \hat{Y}_i]$, then $R^\downarrow = \Psi_0 \supseteq \Psi_1 \supseteq \dots \supseteq \Psi_N = \emptyset$. Let us define function $f : \Phi \rightarrow \mathbb{R}$ via $f(\llbracket v \rrbracket) = \text{cost}(C_{sv}) = f(s, v)$ for $v \in X$. We make the following claim:

(*) For each $i \in [0, N]$ and $A \in \Psi_i^-$ there holds $\mu_i(v) \leq f(A)$ for $v \in \langle A^\downarrow \rangle - \langle \Pi_i \rangle$.

To prove this, we use induction on i . If $i = 0$ then $\Psi_i^- = \emptyset$ and the claim is vacuous. Suppose it holds for $i - 1$; let us prove for $i \in [N]$. Note that $\Psi_i = \Psi_{i-1}[\hat{Y}_i]$. Consider $A \in \Psi_i^-$. If $A \in \Psi_{i-1}^-$ then for each $v \in \langle A^\downarrow \rangle - \langle \Pi_i \rangle \subseteq \langle A^\downarrow \rangle - \langle \Pi_{i-1} \rangle$ we have $\mu_i(v) \leq \mu_{i-1}(v) \leq f(A)$ where the last inequality is by the induction hypothesis. We thus suppose that $A \notin \Psi_{i-1}^-$. Condition $A \in \Psi_i^- = (\Psi_{i-1}[\hat{Y}_i])^-$ then implies that there exists $a \in A$ such that \hat{Y}_i hits a in Ψ_{i-1} , i.e. $C_{sa} \cap \langle \Psi_{i-1} \rangle \cap \hat{Y}_i = \{a\}$. We then have $A = \llbracket a \rrbracket \in \Psi_{i-1}$.

First, suppose that $a \notin Y_i$. Then $a \in \langle \Pi_i \rangle$ (since $a \in \hat{Y}_i$ and $Y_i = \hat{Y}_i - \langle \Pi_i \rangle$) and hence $A \subseteq \langle \Pi_i \rangle$ and $\langle A^\downarrow \rangle \subseteq \langle \Pi_i \rangle$, so (*) vacuously holds. Next, suppose that $\mu_{i-1}(a) = f(s, a) = f(A)$. If $C_{sa} = \langle A^\downarrow \rangle = \{a\}$ then (*) clearly holds. Otherwise $\mu_0(a) < f(s, a)$ and hence $\lambda_j(a) = f(s, a)$ for some $j \in [i - 1]$. This means that set \mathcal{C}_j computed in the j -th call to `CertifiedOrderedCuts` contained set S which is a minimum s - a cut. We have $C_{sa} \subseteq S$, and hence $\mu_{i-1}(v) \leq \lambda_j(v) \leq \text{cost}(S) = f(s, a)$ for all $v \in C_{sa} \cap X = \langle A^\downarrow \rangle$, i.e. (*) holds.

It remains to consider the case when $a \in Y_i$ and $\mu_{i-1}(a) > f(s, a) = f(A)$. We claim that all $v \in (C_{sa} \cap Y_i) - \{a\}$ satisfy $\mu_{i-1}(v) \leq f(A)$. Indeed, we have $C_{sa} \cap \langle \Psi_{i-1} \rangle \cap \hat{Y}_i = \{a\}$, and so $v \notin \langle \Psi_{i-1} \rangle$. Furthermore, $v \in C_{sa} \cap X = \langle A^\downarrow \rangle$ and $A \in \Psi_{i-1}$. These conditions imply that there exists $B \in \Psi_{i-1}^-$ with $B \preceq A$ (implying $f(B) \leq f(A)$) and $v \in \langle B^\downarrow \rangle$. By the choice of Y_i at line 3 we have $Y_i \cap \langle \Pi_{i-1} \rangle = \emptyset$, and so $v \notin \langle \Pi_{i-1} \rangle$ and $v \in \langle B^\downarrow \rangle - \langle \Pi_{i-1} \rangle$. By the induction hypothesis, $\mu_{i-1}(v) \leq f(B)$, which gives the claim.

Now consider the i -th step of Algorithm 9. As we just showed, we have $\mu_{i-1}(v) \leq f(A) < \mu_{i-1}(a)$ for all $v \in (C_{sa} \cap Y_i) - \{a\}$. Thus, nodes in Y_i will be sorted as $v_1, \dots, v_{k-1}, a, \dots$ where $\{v_1, \dots, v_{k-1}\} \cap C_{sa} = \emptyset$. Lemma 4(c) now gives that $\mu_i(v) \leq \lambda_i(v) \leq \text{cost}(C_{sa}) = f(A)$ for all $v \in C_{sa} \cap X = \langle A^\downarrow \rangle$.

We have proved claim (*). Let us use it for $i = N$. We have $\Psi_N = \emptyset$, so $\Psi_N^- = \{R\}$ and thus $\mu_N(v) \leq f(R)$ for all $v \in R - \langle \Pi_N \rangle$. We also have $\mu_N(v) \geq f(R)$ for such v , which gives the lemma. \square

We say that the first stage is *successful* if the precondition of Lemma 6 holds for every $R \in \Phi$. By the lemma, if the first stage is successful then $\mu_N(v) = f(s, v)$ for all $v \in X - \langle \Pi_N \rangle$.

Lemma 7. *Suppose that the first stage is successful and $R^\downarrow[\hat{Y}_{N+1}, \dots, \hat{Y}_{2N}] = \emptyset$ for $R \in \Phi$ with $|\langle R^\downarrow \rangle| \leq L$. Then $\langle R^\downarrow \rangle \subseteq \langle \Pi_{2N} \rangle$.*

Proof. For $i \in [N, 2N]$ denote $\Psi_i = R^\downarrow[\hat{Y}_{N+1}, \dots, \hat{Y}_i]$, then $R^\downarrow = \Psi_N \supseteq \Psi_{N+1} \supseteq \dots \supseteq \Psi_{2N} = \emptyset$. We make the following claim:

(*) For each $i \in [N, 2N]$ and $A \in \Psi_i^-$ there holds $\langle A^\downarrow \rangle \subseteq \langle \Pi_i \rangle$.

To prove this, we use induction on i . If $i = N$ then $\Psi_i^- = \emptyset$ and the claim is vacuous. Suppose it holds for $i - 1$; let us prove for $i \in [N + 1, 2N]$. Note that $\Psi_i = \Psi_{i-1}[\hat{Y}_i]$. Consider $A \in \Psi_i^-$. If $A \in \Psi_{i-1}^-$ then $\langle A^\downarrow \rangle \subseteq \langle \Pi_{i-1} \rangle \subseteq \langle \Pi_i \rangle$ where the first inclusion is by the induction hypothesis. We thus suppose that $A \notin \Psi_{i-1}^-$. Condition $A \in \Psi_i^- = (\Psi_{i-1}[\hat{Y}_i])^-$ then implies that there exists $a \in A$ such that \hat{Y}_i hits a in Ψ_{i-1} , i.e. $C_{sa} \cap \langle \Psi_{i-1} \rangle \cap \hat{Y}_i = \{a\}$. We then have $A = \llbracket a \rrbracket \in \Psi_{i-1}$.

First, suppose that $a \notin Y_i$. Then $a \in \langle \Pi_i \rangle$ (since $a \in \hat{Y}_i$ and $Y_i = \hat{Y}_i - \langle \Pi_i \rangle$) and hence $A \subseteq \langle \Pi_i \rangle$ and $\langle A^\downarrow \rangle \subseteq \langle \Pi_i \rangle$, i.e. (*) holds. We thus assume from now on that $a \in Y_i$. We claim that $C_{sa} \cap Y_i = \{a\}$. Indeed, suppose there exists $v \in (C_{sa} \cap Y_i) - \{a\}$. We have $C_{sa} \cap \langle \Psi_{i-1} \rangle \cap \hat{Y}_i = \{a\}$ and thus $v \notin \langle \Psi_{i-1} \rangle$. Furthermore, $v \in C_{sa} \cap X = \langle A^\downarrow \rangle$ and $A \in \Psi_{i-1}$. These conditions imply that there exists $B \in \Psi_{i-1}^-$ with $B \preceq A$ and $v \in \langle B^\downarrow \rangle$. By the induction hypothesis, $\langle B^\downarrow \rangle \subseteq \langle \Pi_{i-1} \rangle$ and so $v \in \langle \Pi_{i-1} \rangle$. By the choice of Y_i at line 3 we thus have $v \notin Y_i$, which is a contradiction.

Now consider the i -th step of Algorithm 9. Let $v_1, \dots, v_{k-1}, a, \dots$ be the sorting of Y_i . Since the first stage is successful and nodes in Y_i are sorted according to $\mu_{i-1}(\cdot)$, we have $f(s, v_1) \geq \dots \geq f(s, v_{k-1}) \geq f(s, a)$. Thus, the precondition of Lemma 4(b) holds for node $v_k = a$, and hence set \mathcal{C}_i^* contains C_{sa} . We have $C_{sa} \cap X = \langle A^\downarrow \rangle \subseteq \langle R^\downarrow \rangle$ and hence $|C_{sa} \cap X| \leq L$, therefore C_{sa} will be added to Π_i at line 7 and hence (*) holds.

We have proved claim (*). Let us use it for $i = 2N$. We have $\Psi_{2N} = \emptyset$, so $\Psi_{2N}^- = \{R\}$ and thus $\langle R^\downarrow \rangle \subseteq \langle \Pi_{2N} \rangle$, as claimed. \square

Our next goal is to construct sequence $\alpha_1, \dots, \alpha_{2N}$ such that the preconditions of Lemmas 6 and 7 hold w.h.p.. For that we will use the argument from [16]. First, we show the following.

Lemma 8. *Let Ψ be an R -rooted set for some $R \in \Phi$, and let Z_0, \dots, Z_d be a sequence of independent subsets generated via $Z_i \leftarrow \text{RandomSubset}(X, 2^{-i})$ where $d = \lfloor \log_2 |X| \rfloor$. Then $\mathbb{E}|\langle \Psi[Z_0, \dots, Z_d] \rangle| \leq \left(1 - \frac{\Theta(1)}{1+d}\right) |\langle \Psi \rangle| = \left(1 - \frac{\Theta(1)}{\log |X|}\right) |\langle \Psi \rangle|$.*

Proof. Define directed multigraph $(\langle \Psi \rangle, P)$ as follows: for every $i \in [0, d]$ and every $v \in \langle \Psi \rangle$ such that Z_i hits v in Ψ add edges $\{(v, u) : u \in C_{sv} \cap \langle \Psi \rangle\}$ to P . (We say that these edges are at level i). We will show the following:

- (a) The expected out-degree of each $v \in \langle \Psi \rangle$ is $\Omega(1)$.
- (b) The in-degree of each $u \in \langle \Psi \rangle$ is at most $d + 1$.
- (c) If $(v, u) \in P$ then $u \notin \Psi[Z_0, \dots, Z_d]$.

Part (a) will imply that P has $\Omega(\langle \Psi \rangle)$ edges in expectation; combined with (b), this will mean that the expected number of nodes $u \in \langle \Psi \rangle$ with at least one incoming edge is $\Omega(|\langle \Psi \rangle|/(d + 1))$. Part (c) will then give the claim of the lemma. We now focus on proving (a)-(c).

Part (a) Denote $n_v = |C_{sv} \cap \langle \Psi \rangle|$. There must exist $i \in [0, d]$ such that $n_v \in [2^i, 2^{i+1}]$. The probability that Z_i hits v in Ψ equals $2^{-i} \cdot (1 - 2^{-i})^{n_v-1} = \Theta(2^{-i})$. If this event happens then n_v edges of the form $(v, u), u \in C_{sv} \cap \langle \Psi \rangle$ are added to P . Thus, the expected number of outgoing edges from v at level i is at least $\Theta(2^{-i}) \cdot n_v = \Theta(1)$.

Part (b) Suppose that P contains edges $(v, u), (v', u)$ with $v \neq v'$ at the same level i . Z_i hits both v and v' in Ψ , so $u \in C_{sv} \cap C_{sv'}$ and thus by laminarity either $C_{sv} \subsetneq C_{sv'}$ or $C_{sv'} \subsetneq C_{sv}$. Assume w.l.o.g. that $C_{sv'} \subsetneq C_{sv}$. Then $C_{sv} \cap \langle \Psi \rangle \cap Z_i$ contains at least two nodes (v and v'), which is a contradiction.

Part (c) Denote $\Psi_i = \Psi[Z_1, \dots, Z_i]$ for $i \in [0, d]$, and consider edge $(v, u) \in P$ at level i . Let $A = \llbracket v \rrbracket \in R^\downarrow$. We claim that $A \notin \Psi_i$ (implying that $A \notin \Psi_d$ and thus $u \notin \langle \Psi_d \rangle$ since $u \in \langle A^\downarrow \rangle = C_{sv} \cap X$). Indeed, assume that $A \in \Psi_i \subseteq \Psi_{i-1}$. Since Z_i hits v in Ψ we have $C_{sv} \cap \langle \Psi \rangle \cap Z_i = \{v\}$. This means that $C_{sv} \cap \langle \Psi_{i-1} \rangle \cap Z_i = \{v\}$, i.e. Z_i hits v in Ψ_{i-1} . This in turn implies that $A \notin \Psi_{i-1}[Z_i] = \Psi_i$, which is a contradiction. \square

Corollary 9. *Denote $n = |X|$. For every fixed polynomial $p(n)$ there exists a sequence $\alpha_1, \dots, \alpha_{2N}$ with $N = \Theta(\log^3 n)$ such that the preconditions of Lemmas 6 and 7 hold with probability at least $1 - \frac{1}{p(n)}$.*

Proof. Let $\alpha_1, \dots, \alpha_{2N}$ be the sequence obtained by repeating the sequence used in Lemma 8 (i.e. $2^{-0}, 2^{-1}, \dots, 2^{-d}$) $2K$ times, so that $N = K(d+1)$. If $K = \Theta(\log n)$ (with an appropriate constant) then for any fixed $R \in \Phi$ we will have $\mathbb{E}[|\langle R^\downarrow[Z_1, \dots, Z_N] \rangle|] \leq \frac{1}{2np(n)}$, and thus $R^\downarrow[Z_1, \dots, Z_N] = \emptyset$ with probability at least $1 - \frac{1}{2np(n)}$. (Here Z_i is a subset generated via $Z_i \leftarrow \text{RandomSubset}(X, \alpha_i)$). The preconditions of Lemmas 6 and 7 have at most $2n$ events of the form above, so by the union bound they will all hold with probability at least $1 - \frac{1}{p(n)}$. \square

This concludes the proof of Theorem 5.

2.3 Overall algorithm

First, we need to make sure that the outputs of `CertifiedOrderedCuts` are minimal. One possibility is to use procedure `IsolatingCuts`($s, Y; H$) that produces minimal minimum $(Y \cup \{s\} - \{v\})$ - v cuts S_v . If `IsolatingCuts`($s, Y; H$) uses maximum flow computations then this can easily be achieved for free without increasing the complexity. Otherwise we can use a standard technique of adding a small random perturbation to the edge weights. The correctness of this technique follows from the Isolation Lemma of [18] (see e.g. [2, Proposition 3.14]).

Proposition 10. *One can add random polynomially-bounded values to the edge weights in H such that any GH tree in the new graph H' is also a valid GH tree for H , and furthermore with high probability H' has a unique GH tree.*

We now come back to the problem discussed in the beginning of Section 2, i.e. how to implement line 4 of Algorithm 6. We select source s uniformly at random (as in [2]), and then call the procedure developed in the previous section.

Algorithm 10: Line 4 of Algorithm 6.

```

1 while true do
2   sample  $s \in X$  uniformly at random
3   apply random permutation to  $H$  as in Proposition 10 to get graph  $H'$ 
4   call  $\Pi \leftarrow \text{FixedSourcePartition}(s, X - \{s\}, L; H')$  where  $L \stackrel{\text{def}}{=} |X|/2$ 
5   remove non-maximal subsets from  $\Pi$  /* this is to simplify the analysis */
6   if  $|(V - \langle \Pi \rangle) \cap X| \leq L$  then terminate and return  $(s, \Pi)$ 

```

In order to analyze Algorithm 10, let us introduce a total order \preceq on cuts $S \subseteq V$ as follows: (i) if $\text{cost}(S) < \text{cost}(S')$ then $S \prec S'$; (ii) if $\text{cost}(S) = \text{cost}(S')$ and $|S \cap X| < |S' \cap X|$ then $S \prec S'$; (iii) otherwise use an arbitrary rule. We write $u \sqsubset v$ for distinct nodes $u, v \in X$ if $C_{vu} \prec C_{uv}$. Equivalently, $u \sqsubset v$ if $u \in S$ where S is the minimum subset w.r.t. \preceq that separates u and v . We write $u \sqsubseteq v$ if either $u \sqsubset v$ or $u = v$.

Lemma 11. *Relation \sqsubseteq is a total order on X .*

Proof. It suffices to show that for any distinct $a, b, c \in X$ relation \sqsubseteq is not cyclic on a, b, c . We can assume w.l.o.g. that C_{ab} is the smallest subset w.r.t. \preceq among C_{xy} for distinct $x, y \in \{a, b, c\}$. Note that $b \sqsubset a$. If $c \in C_{ab}$ then C_{ab} is an a - c cut with $C_{ab} \preceq C_{ac}$, implying $C_{ac} = C_{ab}$ and $c \sqsubset a$. If $c \notin C_{ab}$ then C_{ab} is an c - b cut with $C_{ab} \preceq C_{cb}$, implying $C_{cb} = C_{ab}$ and $b \sqsubset c$. In both cases \sqsubseteq is not cyclic on a, b, c . \square

Lemma 12. *Each iteration of Algorithm 10 succeeds with probability $\Omega(1)$ (and thus the expected number of iterations is $O(1)$).*

Proof. Let a be the L -th smallest node in X w.r.t. \sqsubseteq . With probability $\Omega(1)$ the following events will hold jointly: (i) $a \sqsubset s$; (ii) H' has the unique GH tree (and thus the outputs of `CertifiedOrderedCuts` will be minimal); (iii) `FixedSourcePartition`($s, X, L; H'$) returns Π with $\langle \Pi \rangle = \langle \Pi_s^{(L)} \rangle$. In that case for any $v \in U \stackrel{\text{def}}{=} \{v \in X : v \sqsubseteq a\}$ we have $v \sqsubset s$, or equivalently $C_{sv} \prec C_{vs}$. This implies that $|C_{sv} \cap X| \leq |C_{vs} \cap X| \leq |(V - C_{sv}) \cap X|$, and so $|C_{sv} \cap X| \leq L$, $C_{sv} \in \Pi_s^{(L)}$ and hence $v \in C_{sv} \subseteq \langle \Pi_s^{(L)} \rangle = \langle \Pi \rangle$. We have $U \subseteq \langle \Pi \rangle$ and $|U| = L$, and so $|(V - \langle \Pi \rangle) \cap X| \leq |(V - U) \cap X| \leq L$. \square

Next, we analyze the overall complexity of Algorithm 6. Each supernode X that appears during the execution of can be assigned a depth using natural rules: (i) the initial supernode V is at depth 0; (ii) if supernode X at depth d is split into supernodes X_0, \dots, X_k then the latter supernodes are assigned depth $d + 1$. By construction, in the latter case we have $|X_i| \leq |X|/2$ for $i \in [0, k]$. Therefore, supernode X at depth d satisfies $|X| \leq n \cdot 2^{-d}$, and so the maximum depth is $O(\log n)$. We will need the following result from [2].

Lemma 13 ([2, Lemma 3.12]). *Let $X_1, \dots, X_{k(d)}$ be the supernodes at depth d , and let $H_1, \dots, H_{k(d)}$ be the corresponding auxiliary graphs. Then the total number of edges in $H_1, \dots, H_{k(d)}$ is $O(m)$.*

An analogous result also holds for the number of nodes.

Lemma 14. *Let $X_1, \dots, X_{k(d)}$ be the supernodes at depth d , and let $H_1, \dots, H_{k(d)}$ be the corresponding auxiliary graphs. Then the total number of nodes in $H_1, \dots, H_{k(d)}$ is $O(n)$.*

Proof. Consider graph $H = H_i$ corresponding to supernode $X = X_i$. Recall that $V_H = X \cup \{v_Y : XY \in \mathcal{T}\}$ where \mathcal{T} is the partition tree at the moment when X is processed. Clearly, sets $X_1, \dots, X_{k(d)}$ are disjoint, so we need to bound the total number of nodes of H due to edges $XY \in \mathcal{T}$ (let us call them “contracted nodes”). After X is processed, each XY is transformed to an edge $X'Y$ for some supernode $X' \subset X$, other edges of \mathcal{T} are kept intact (or “transformed to themselves”), and some new edges are added to \mathcal{T} . Let us track how edge XY transforms during the algorithm; eventually, it becomes an edge xy of the final GH tree, with $x \in X$ and $y \in Y$. Let us charge node v_Y in graph H to node x . Clearly, no other node in graphs $H_1, \dots, H_{k(d)}$ is charged to x . The number of edges in the final GH tree is $n - 1$, and thus the total of contracted nodes in $H_1, \dots, H_{k(d)}$ is at most $2(n - 1)$. \square

By putting all results together, we obtain

Corollary 15. *The expected complexity of Algorithm 6 with line 4 implemented as in Algorithm 10 is $O((t_{\text{OC}}(n, m) + t_{\text{MC}}(n, m) + n \log n) \cdot \log^4 n)$.*

When combined with Theorem 2, this yields Theorem 1.

3 Properties of strong OrderedCuts

Consider undirected weighted graph $G = (V, E, w)$. We will use letters $\varphi, \alpha, \beta, \dots$ to denote sequences of distinct nodes in V . For a sequence φ and a set $X \subseteq V$ we denote $\varphi \cap X$ to be the subsequence of φ containing only nodes in X . With some abuse of notation we will often view sequence $\varphi = v_0 \dots v_\ell$ as a set $\{v_0, \dots, v_\ell\}$; such places should always be clear from the context. Sequence φ imposes a total order on nodes in φ ; we will denote this order as \sqsubseteq (so that $v_0 \sqsubseteq v_1 \sqsubseteq \dots \sqsubseteq v_\ell$), when φ is clear from the context.

Definition 16. Consider sequence $\varphi = s \dots$. An OC tree for φ is a pair (Ω, \mathcal{E}) where

- (φ, \mathcal{E}) is a rooted tree with the root s and edges oriented towards the root such that for any $uv \in \mathcal{E}$ we have $v \sqsubseteq u$. We write $u \preceq v$ for nodes $u, v \in \varphi$ if this tree has a directed path from u to v .
- Ω is a partition of some set V with $|\Omega| = |\varphi|$ such that $|A \cap \varphi| = 1$ for all $A \in \Omega$. For node $v \in V$ we denote $[v]$ to be the unique component in Ω containing v (then $[u] \neq [v]$ for distinct $u, v \in \varphi$). We also denote $[v]^\downarrow = \bigcup_{u \in \varphi: u \preceq v} [u]$ for $v \in \varphi$.

We say that (Ω, \mathcal{E}) is an OC tree for (φ, G) (or is valid for G , when φ is clear) if the following holds: if $\varphi = \alpha v \dots$ with $|\alpha| \geq 1$ then $[v]^\downarrow$ is a minimum α - v cut in G .

Note that operation $[\cdot]$ depends on Ω . Below we will need to work with multiple OC trees. Unless noted otherwise, we will use the following convention: different OC trees will be denoted with an additional symbol, e.g. (Ω, \mathcal{E}) , (Ω', \mathcal{E}') , ..., and the corresponding operations will be denoted accordingly as $[\cdot]$, $[\cdot]'$, Operations \preceq and $(\cdot)^\downarrow$ also depend on the OC tree, but we will always use the same notation for them; the corresponding OC tree should always be clear from the context (or these operations would be the same for all considered OC trees).

Consider OC tree (Ω, \mathcal{E}) for sequence φ and a leaf node $u \in \varphi$. Let v be the parent of u in (φ, \mathcal{E}) (i.e. $uv \in \mathcal{E}$). We define φ^{-u} to be the sequence obtained from φ by removing node u , and $(\Omega^{-u}, \mathcal{E}^{-u})$ to be the OC tree for φ^{-u} obtained from (Ω, \mathcal{E}) by removing edge uv and merging components $[u]$ and $[v]$ of Ω into a single component $[v]^{-u} = [v] \cup [u]$. Equivalently, $(\Omega^{-u}, \mathcal{E}^{-u})$ can be defined as the unique OC tree for φ^{-u} with the property that $[w]^{-u\downarrow} = [w]^\downarrow$ for all $w \in \varphi^{-u}$.

It will be convenient to introduce the following notation for graph $G = (V, E, w)$, subset $X \subseteq V$ and node $s \in X$: $G[X; s]$ is the graph obtained from G by contracting set $(V - X) \cup \{s\}$ to s . Note that the set of nodes of $G[X; s]$ equals X . We will often use an s - t cut in $G[X; s]$ where $s, t \in X$; clearly, this the same as an s - t cut U in G satisfying $U \subseteq X$.

Lemma 17. Suppose that (Ω, \mathcal{E}) is an OC tree for φu and $v \in \varphi$ is the parent of u in $(\varphi u, \mathcal{E})$. Suppose further that $(\Omega^{-u}, \mathcal{E}^{-u})$ is an OC tree for (φ, G) . Then (Ω, \mathcal{E}) is valid for G if and only if set $[u]$ is a minimum v - u cut in $G[[v]^{-u}; v]$.

Lemma 17 gives a constructive proof of the existence of OC tree for a given (φ, G) .

Corollary 18. For every undirected graph G and non-empty sequence φ of nodes in G there exists OC tree (Ω, \mathcal{E}) for (φ, G) .

Proof. It suffices to show that if there exists OC tree (Ω, \mathcal{E}) for (φ, G) and u is a node in $V - \varphi$ then there also exists OC tree $(\tilde{\Omega}, \tilde{\mathcal{E}})$ for $(\varphi u, G)$; the claim will then follow by induction. Let $v \in \varphi$ be the unique node in φ with $u \in [v]$. Let T be a minimum v - u cut in $G[[v]; v]$. Define $\tilde{\Omega} = (\Omega - [v]) \cup \{[v] - T, T\}$ and $\tilde{\mathcal{E}} = \mathcal{E} \cup \{uv\}$. Note that $(\Omega, \mathcal{E}) = (\tilde{\Omega}^{-u}, \tilde{\mathcal{E}}^{-u})$. By Lemma 17, $(\tilde{\Omega}, \tilde{\mathcal{E}})$ is an OC tree for $(\varphi u, G)$. \square

Extracting minimum s - t cuts from an OC tree Let (Ω, \mathcal{E}) be an OC tree for (φ, G) with $\varphi = s \dots u \dots$, and let v be the parent of u in (φ, \mathcal{E}) . Define $\pi(u)$ as the maximal node $w \in \varphi$ w.r.t. \sqsubseteq satisfying the following conditions: (i) $w \sqsubset u$; (ii) $w \in \{v\} \cup \{w : vw \in \mathcal{E}\}$. Clearly, by following pointers $\pi(\cdot)$ we will eventually arrive at the root node s (visiting v on the way). Let $\pi^*(u) = s \dots v \dots$ be the reversed sequence of nodes traversed during this process. We will prove the following result.

Lemma 19. (a) *Set $[u]^\downarrow$ is a minimum $\pi^*(u)$ - u cut.*
(b) *If $\text{cost}([w]^\downarrow) \geq \text{cost}([u]^\downarrow)$ for all $w \in \pi^*(u) - \{s\}$ then $[u]^\downarrow$ is a minimum s - u cut.*

The lemma means that cuts extracted from OC tree can be used to implement procedure `CertifiedOrderedCuts` without the need to call `IsolatingCuts`, as mentioned in Remark 1.

Divide-and-conquer algorithms Next, we give two results that can be used to design a divide-and-conquer algorithm for constructing OC tree.

Lemma 20. *Consider sequence $\varphi = \alpha \dots$ in graph G with $|\alpha| \geq 1$. Suppose that $(\Omega^\circ, \mathcal{E}^\circ)$ is an OC tree for (α, G) , and for each $v \in \alpha$ pair $(\Omega^v, \mathcal{E}^v)$ is an OC tree for $(\varphi \cap [v]^\circ, G[[v]^\circ; v])$. Then (Ω, \mathcal{E}) is an OC tree for (φ, G) where $\Omega = \bigcup_{v \in \alpha} \Omega^v$ and $\mathcal{E} = \mathcal{E}^\circ \cup \bigcup_{v \in \alpha} \mathcal{E}^v$.*

Lemma 21. *Consider sequence $\varphi = s\alpha \dots$ in graph G with $|\alpha| \geq 1$. Let (S, T) be a minimum s - α cut in G , and let $T_s = T \cup \{s\}$. Suppose that (Ω', \mathcal{E}') is an OC tree for $(\varphi \cap S, G[S; s])$ and $(\Omega'', \mathcal{E}'')$ is an OC tree for $(\varphi \cap T_s, G[T_s; s])$. Then (Ω, \mathcal{E}) is an OC tree for (φ, G) where $\Omega = \{[s]' \cup [s]''\} \cup (\Omega' - \{[s]'\}) \cup (\Omega'' - \{[s]''\})$ and $\mathcal{E} = \mathcal{E}' \cup \mathcal{E}''$.*

To illustrate the use of these results, we show how we can compute an OC tree more efficiently than a naive algorithm for random permutations. Let us consider the following algorithm.

Algorithm 11: `OrderedCuts`($\varphi; G$): divide-and-conquer algorithm.

- 1 if $|\varphi| \leq 2$ then compute OC tree (Ω, \mathcal{E}) for (φ, G) non-recursively and return (Ω, \mathcal{E})
 - 2 split $\varphi = \alpha\beta$ where $|\alpha| = \lceil \frac{1}{2}(|\varphi| + 1) \rceil$
 - 3 call $(\Omega^\circ, \mathcal{E}^\circ) \leftarrow \text{OrderedCuts}(\alpha; G)$, set $(\Omega, \mathcal{E}) = (\emptyset, \mathcal{E}^\circ)$
 - 4 **for** $v \in \alpha$ **do**
 - 5 compute minimum v - $(\beta \cap [v]^\circ)$ cut (S, T) in $G[[v]^\circ; v]$ such that T is minimal
 - 6 let $(\Omega^v, \mathcal{E}^v) \leftarrow \text{OrderedCuts}(v(\beta \cap T), G[T \cup \{v\}; v])$
 - 7 update $\Omega := \Omega \cup \{S \cup [v]^v\} \cup (\Omega^v - [v]^v)$ and $\mathcal{E} := \mathcal{E} \cup \mathcal{E}^v$
 - 8 **return** (Ω, \mathcal{E})
-

The correctness follows by an induction argument and by the previous lemmas: at line 7 $(\{S \cup [v]^v\} \cup (\Omega^v - [v]^v), \mathcal{E}^v)$ is an OC tree for $G[[v]^\circ; v]$ by Lemma 21, and the output at line 8 is an OC tree for (φ, G) by Lemma 20.

Theorem 22. *Algorithm 11 for sequence φ has complexity of maximum flow computations on $O(n)$ graphs of size (n, m) each. If $\varphi = (s, v_1, \dots, v_\ell)$ and the order of v_1, \dots, v_ℓ is a uniformly random permutation then the expected total number of nodes and edges in these graphs is $(O(n^{1+\gamma}), O(n^\gamma m))$ where $\gamma = \log_2 1.5 = 0.584\dots$*

3.1 Proof of Lemma 17

We will need the following well-known fact about minimum cuts. It follows, for example, from the properties of the parametric maxflow problem [9].

Lemma 23. *Consider graph G and pairs of disjoint subsets (S, T) and (S', T') with $S \subseteq S'$ and $T \supseteq T'$. If U is a minimum S - T cut then there exists a minimum S' - T' cut U' with $U' \subseteq U$.*

We proceed with the proof of Lemma 17.

Lemma 17 (restated). *Suppose that (Ω, \mathcal{E}) is an OC tree for φu and $v \in \varphi$ is the parent of u in $(\varphi u, \mathcal{E})$. Suppose further that $(\Omega^{-u}, \mathcal{E}^{-u})$ is an OC tree for (φ, G) . Then (Ω, \mathcal{E}) is valid for G if and only if set $[u]$ is a minimum v - u cut in $G[[v]^{-u}; v]$.*

Proof. Clearly, we have $[w]^\downarrow = [w]^{-u\downarrow}$ for all $w \in \varphi$ and $[w]^\downarrow = [u]$ for $w = u$. Therefore, (Ω, \mathcal{E}) is valid for G if and only if $[u]$ is a minimum φ - u cut in G . Let T be the minimal minimum φ - u cut in G ; since $\varphi \cap [v]^{-u} = \{v\}$, it suffices to show that $T \subseteq [v]^{-u}$.

Let us write $\varphi = \alpha v \dots$. We claim that $T \subseteq [v]^\downarrow = [v]^{-u\downarrow}$. Indeed, assume that $|\alpha| \geq 1$ (otherwise $[v]^\downarrow = V$ and the claim is trivial). Since $[v]^\downarrow$ is a minimum α - v cut and $u \in [v]^\downarrow$, set $[v]^\downarrow$ is also a minimum α - $\{v, u\}$ cut. Applying Lemma 23 gives that $T \subseteq [v]^\downarrow$, as desired.

Now consider node $w \in \varphi$ with $w \prec v$. Let us write $\varphi = \alpha v \beta w \dots$. Let U be a minimum $\alpha v \beta w$ - u cut. We know that $[w]^\downarrow = [w]^{-u\downarrow}$ is a minimum $\alpha v \beta w$ - u cut. Define $A = [w]^\downarrow - U$ and $B = U - [w]^\downarrow$. By symmetry of cuts and submodularity, we have

$$\begin{aligned} \text{cost}([w]^\downarrow) + \text{cost}(U) &= \text{cost}([w]^\downarrow) + \text{cost}(V - U) \\ &\geq \text{cost}([w]^\downarrow \cap (V - U)) + \text{cost}([w]^\downarrow \cup (V - U)) \\ &= \text{cost}(A) + \text{cost}(V - B) = \text{cost}(A) + \text{cost}(B) \end{aligned}$$

Clearly, we have $\alpha v \beta \cap A = \alpha v \beta w \cap B = \emptyset$, $w \in A$ and $u \in B$. Set A is an $\alpha v \beta w$ - u cut, and thus $\text{cost}(A) \geq \text{cost}([w]^\downarrow)$. This implies that $\text{cost}(B) \leq \text{cost}(U)$, and thus B is a minimum $\alpha v \beta w$ - u cut. Lemma Lemma 23 gives that $T \subseteq B$. We have $B \cap [w]^\downarrow = \emptyset$ and thus $T \cap [w]^\downarrow = \emptyset$. Since this holds for all $w \in \varphi$ with $w \prec v$ (and since $T \subseteq [v]^\downarrow$), we conclude that $T \subseteq [v]^{-u}$, as desired. \square

3.2 Proof of Lemma 19

Part (b) follows directly from part (a) and Lemma 3, so we focus on proving part (a). Consider OC tree (Ω, \mathcal{E}) for sequence φ with $|\varphi| \geq 2$, and let $t \in \varphi$ be a leaf node in (φ, \mathcal{E}) . We say that t is a *free leaf* in (φ, \mathcal{E}) if the following holds: if $\varphi = \dots t \dots u \dots$ then t and u have different parents. In particular, the last node of φ is a free leaf if $|\varphi| \geq 2$. We will show the following result.

Lemma 24. *Suppose that (Ω, \mathcal{E}) is an OC tree for (φ, G) and $t \in \varphi$ is a free leaf in (φ, \mathcal{E}) . Then $(\Omega^{-t}, \mathcal{E}^{-t})$ is an OC tree for (φ^{-t}, G) .*

Proof. We use induction on $|\varphi|$. If $|\varphi| = 2$ then the claim is trivial; suppose that $|\varphi| > 2$. Clearly, for any $w \in \varphi^{-t}$ we have $[w]^{-t\downarrow} = [w]^\downarrow$.

Let u be the last node of φ . It can be seen that $(\Omega^{-u}, \mathcal{E}^{-u})$ is an OC tree for φ^{-u} (if $\varphi^{-u} = \alpha w \dots$ then set $[w]^{-u\downarrow} = [w]^\downarrow$ is indeed a minimum α - w cut). Thus, if $t = u$ then the claim holds. Suppose that $\varphi = \dots t \dots u$. Note that t, u are leaf nodes with distinct parents. Denote $\varphi^{-tu} = (\varphi^{-u})^{-t} = (\varphi^{-t})^{-u}$ and $(\Omega^{-tu}, \mathcal{E}^{-tu}) = ((\Omega^{-u})^{-t}, (\mathcal{E}^{-u})^{-t}) = ((\Omega^{-t})^{-u}, (\mathcal{E}^{-t})^{-u})$. Clearly, t is a free leaf in $(\varphi^{-u}, \mathcal{E}^{-u})$, and thus $(\Omega^{-tu}, \mathcal{E}^{-tu})$ is an OC tree for (φ^{-tu}, G) by the induction hypothesis. Let v be the parent of u in (φ, \mathcal{E}) . We have $[u] = [u]^{-t}$ and $[v]^{-u} = [v]^{-tu}$ since t is a leaf node which is not a child of v .

$(\Omega^{-u}, \mathcal{E}^{-u})$ is an OC tree for (φ^{-u}, G) and (Ω, \mathcal{E}) is an OC tree for (φ, G) . By Lemma 17, $[u]$ is a minimum v - u cut in $G[[v]^{-u}; v]$.

$(\Omega^{-tu}, \mathcal{E}^{-tu})$ is an OC tree for (φ^{-tu}, G) and $[u]^{-t}$ is a minimum v - u cut $G[[v]^{-tu}; v]$. By Lemma 17, $(\Omega^{-t}, \mathcal{E}^{-t})$ is an OC tree for (φ^{-t}, G) . \square

We are now ready to prove Lemma 19. Let (Ω, \mathcal{E}) be an OC tree for (φ, G) , and consider non-root node $u \in \varphi$. Let us repeatedly modify $(\varphi, \Omega, \mathcal{E})$ using the following algorithm: while (φ, \mathcal{E}) has a free leaf t with $t \notin \pi^*(u) \cup \{u\}$, pick arbitrary such t and update $(\varphi, \Omega, \mathcal{E}) \leftarrow (\varphi^{-t}, \Omega^{-t}, \mathcal{E}^{-t})$.

By construction, u is always in φ . We claim that the sequence $\pi^*(u)$ never changes. Indeed, it suffices to show that each step preserves $\pi(u)$; applying this fact to $\pi(\pi(u)), \pi(\pi(\pi(u))), \dots$ will then yield the claim. It suffices to consider the case when u comes after t , i.e. $\varphi = s \dots t \dots u \dots$. Let v be the parent of u . We say that node $w \in \varphi$ is *u-admissible* in (φ, \mathcal{E}) if it satisfies the following conditions: (i) $w \sqsubset u$; (ii) $w \in \{v\} \cup \{w : vw \in \mathcal{E}\}$. Recall that $\pi(u)$ is the maximal *u-admissible* node w in (φ, \mathcal{E}) w.r.t. \sqsubseteq . We cannot have $w = t$, since t is a free leaf. It can be checked that a node $w \neq t$ is *u-admissible* in (φ, \mathcal{E}) if and only if it is *u-admissible* in $(\varphi^{-t}, \mathcal{E}^{-t})$; this implies the claim.

Denote $\psi = \pi^*(u)u$. We will show next that upon termination we have $\varphi = \psi$; clearly, this will imply Lemma 19(a). Suppose the claim is false, then $\varphi = s \dots t\alpha$ where $t \notin \psi$ and $\alpha \subseteq \psi$. If node t has a child w then $w \in \psi$ and thus $t \in \pi^*(w) \subseteq \psi$ - a contradiction. Thus, t is a leaf in (φ, \mathcal{E}) . It is not a free leaf since the algorithm has terminated, thus there exists $w \in \alpha$ such that t and w have the same parent. But then $t \in \pi^*(w) \subseteq \psi$ - a contradiction.

3.3 Proof of Lemma 20

Lemma 20 (restated). *Consider sequence $\varphi = \alpha \dots$ in graph G with $|\alpha| \geq 1$. Suppose that $(\Omega^\circ, \mathcal{E}^\circ)$ is an OC tree for (α, G) , and for each $v \in \alpha$ pair $(\Omega^v, \mathcal{E}^v)$ is an OC tree for $(\varphi \cap [v]^\circ, G[[v]^\circ; v])$. Then (Ω, \mathcal{E}) is an OC tree for (φ, G) where $\Omega = \bigcup_{v \in \alpha} \Omega^v$ and $\mathcal{E} = \mathcal{E}^\circ \cup \bigcup_{v \in \alpha} \mathcal{E}^v$.*

We use induction on $|\varphi|$. If $\varphi = \alpha$ then the claim is trivial. Suppose that $\varphi = \alpha\beta u$. Let $v \in \alpha$ be the unique node with $u \in [v]^\circ$, and denote $\gamma = \beta \cap [v]^\circ$. We will work with pairs $(\Omega^{-u}, \mathcal{E}^{-u})$ and $((\Omega^v)^{-u}, (\mathcal{E}^v)^{-u})$, which are OC trees for sequences $\alpha\beta$ and $v\gamma$ respectively. Clearly, we have $[w] = [w]^v$ for $w \in \gamma u$ and $[w]^{-u} = ([w]^v)^{-u}$ for $w \in \gamma$ (where $([w]^v)^{-u}$ is the component of $(\Omega^v)^{-u}$ to which w belongs). Let $p \in v\gamma$ be the parent of u in (φ, \mathcal{E}) (equivalently, in $(v\gamma u, \mathcal{E}^v)$). Denote $H = G[[v]^\circ; v]$. By Lemma 24, $((\Omega^v)^{-u}, (\mathcal{E}^v)^{-u})$ is an OC tree for $(v\gamma, H)$. Thus, the induction hypothesis gives that $(\Omega^{-u}, \mathcal{E}^{-u})$ is an OC tree for $(\alpha\beta, G)$. By Lemma 17, $[u]^v = [u]$ is a minimum p - u cut in $H(([p]^v)^{-u}; p) = G[[p]^{-u}; p]$. By Lemma 17, (Ω, \mathcal{E}) is an OC tree for (φ, G) .

3.4 Proof of Lemma 21

Lemma 21 (restated). *Consider sequence $\varphi = s\alpha \dots$ in graph G with $|\alpha| \geq 1$. Let (S, T) be a minimum s - α cut in G , and let $T_s = T \cup \{s\}$. Suppose that (Ω', \mathcal{E}') is an OC tree for $(\varphi \cap S, G[S; s])$ and $(\Omega'', \mathcal{E}'')$ is an OC tree for $(\varphi \cap T_s, G[T_s; s])$. Then (Ω, \mathcal{E}) is an OC tree for (φ, G) where $\Omega = \{[s]' \cup [s]''\} \cup (\Omega' - \{[s]'\}) \cup (\Omega'' - \{[s]''\})$ and $\mathcal{E} = \mathcal{E}' \cup \mathcal{E}''$.*

First, let us consider node $u \in \varphi \cap S$ with $u \neq s$. We can write $\varphi = s\alpha\beta u \dots$, since $\alpha \cap S = \emptyset$. We need to show that $[u]^\downarrow$ is a minimum $s\alpha\beta$ - u cut. If $|\alpha| = 1$ then the claim follows from Lemma 20 (since $(\Omega^\circ, \mathcal{E}^\circ) = (\{S, T\}, \{\alpha s\})$ is an OC tree for $(s\alpha, G)$). The general case can be reduced to the case above by contracting nodes in α to a single node. Such transformation preserves set S in a minimum s - α cut (S, T) ; thus, OC tree (Ω', \mathcal{E}') for $(\varphi \cap S, G[S; s])$ is not affected, and therefore set $[u]^\downarrow$ is also not affected.

Now consider node $u \in \varphi \cap T$. Let us write $\varphi = \beta u \dots$, and denote $\beta \cap S = A$ and $\beta \cap T = B$. For brevity, we denote $X_1 \dots X_k = X_1 \cup \dots \cup X_k$ for disjoint subsets X_1, \dots, X_k ; if $X_i = \{x_i\}$ then we write x_i instead of X_i . We make two claims:

- There exists a minimum AB - u cut (S', T') with $S \subseteq S'$. Indeed, (S, T) is a minimum s - $(\alpha \cup \{u\})$ cut (since $u \in T$). The claim now holds by Lemma 23.
- $[u]^\downarrow$ is a minimum SB - u cut in G . Indeed, $(\Omega'', \mathcal{E}'')$ is an OC tree for $(\varphi \cap T_s, G[T_s; s])$, thus set $[u]^\downarrow = [u]''^\downarrow$ is a minimum sB - u cut in $G[T_s; s]$. This is equivalent to the claim above.

These claims imply that $[u]^\downarrow$ is a minimum AB - u cut, or equivalently a minimum β - u cut.

3.5 Proof of Theorem 22: analysis of Algorithm 11

Computations performed by the algorithm can be represented by a rooted tree whose nodes have the form $\sigma = (\varphi; G)$. For such node we denote $\varphi_\sigma = \varphi$, and define $H_\sigma = (V_\sigma, E_\sigma)$ to be the graph obtained from G by removing node s and incident edges, where s is the first node of sequence φ . The leaves σ of this tree satisfy $|\varphi_\sigma| \leq 2$. Each non-leaf node σ has a child τ corresponding to the recursive call at line 3 (we call the *left child*), and children $\{\tau^v : v \in \alpha\}$ corresponding to recursive calls at line 6 (we call them *right children*). Let us assign label $\lambda(\sigma) = (\lambda_1(\sigma), \dots, \lambda_d(\sigma)) \in \{0, 1\}^*$ according to the following rules: (i) the label of the root node is the empty string; (ii) if σ is a non-leaf node then its left child is assigned label $(\lambda(\sigma), 0)$ and its right children are assigned label $(\lambda(\sigma), 1)$. Let d_σ be the depth of node σ , then $d_\sigma = |\lambda(\sigma)|$. The set of labels that appears during the algorithm will be denoted as $\Lambda \subseteq \{0, 1\}^*$, and for a label $\mu \in \Lambda$ let Σ_μ be the set of nodes σ with $\lambda(\sigma) = \mu$.

Lemma 25. *The execution of $\text{OrderedCuts}(\varphi; G)$ satisfies the following properties.*

- (a) *The maximum depth satisfies $d_{\max} \leq \log_2 |\varphi| + O(1)$, and $|\Lambda| \leq O(|\varphi|)$.*
- (b) *Consider non-leaf node σ , and let τ be its left child and τ_1, \dots, τ_k be its right children. Then $(V_\tau, E_\tau) = (V_\sigma, E_\sigma)$, $V_{\tau_1}, \dots, V_{\tau_k}$ are disjoint subsets of V_σ , and $E_{\tau_1}, \dots, E_{\tau_k}$ are disjoint subsets of E_σ .*
- (c) *For each $\mu \in \Lambda$ sets in $\{V_\sigma : \sigma \in \Sigma_\mu\}$ and in $\{E_\sigma : \sigma \in \Sigma_\mu\}$ are disjoint.*

Proof. By construction, if τ is a child of σ then $|\varphi_\tau| \leq |\varphi_\sigma|/2 + 1$ if $|\varphi_\sigma|$ is even, and $|\varphi_\tau| \leq (|\varphi_\sigma| + 1)/2$ if $|\varphi_\sigma|$ is odd. Let d_{\max} be the maximum depth. For each non-leaf node σ we have $|\varphi_\sigma| \geq 2^{d_{\max} - d - 1} + 2$, therefore $d_{\max} \leq \log_2 |\varphi| + O(1)$ where φ is the input string. This implies that $|\Lambda| \leq 1 + 2^1 + \dots + 2^{d_{\max}} \leq O(|\varphi|)$, and proves part (a).

Part (b) follows from the algorithm's construction. Part (c) follows from part (b) combined with a straightforward induction argument. \square

Lemma 25 gives the first part of Theorem 22, i.e. that the complexity of Algorithm 11 is $O(|\varphi| \cdot t_{\text{MC}}(n, m))$. We now focus on the second part. Let us define a *generalized sequence* φ as a set of nodes together with a partial order \sqsubseteq on this set. With some abuse of terminology the set of nodes in φ will be denoted simply as φ . We say that φ is a *0-sequence* if \sqsubseteq does not impose any relations on φ , and φ is a *1-sequence* if there exists $s \in \varphi$ such that $s \sqsubseteq v$ for all $v \in \varphi - \{s\}$ and \sqsubseteq does not impose any relations on $\varphi - \{s\}$. If φ is a 1-sequence then we will write $\varphi = s\varphi'$ where φ' is a 0-sequence.

Let us define a randomized algorithm $\text{OrderedCuts}'(\varphi; G)$ that takes as an input 1-sequence $\varphi = s\varphi'$, graph G and returns triplet $(\Omega, \mathcal{E}, \sqsubseteq)$ where \sqsubseteq is a partial order on φ' . This algorithm has the same structure as $\text{OrderedCuts}(\varphi; G)$ but with the following modifications:

- At line 2 the split $\varphi = \alpha\beta$ is replaced by the following operation: sample a random subset $A \subseteq \varphi'$ of size $|A| = \lceil \frac{1}{2}(|\varphi| + 1) \rceil - 1$, let α be the 1-sequence with $\alpha = sA$, and let β be a 0-sequence with $\beta = \varphi - \alpha$.
- Replace lines 3 and 6 with “ $(\Omega^\circ, \mathcal{E}^\circ, \sqsubseteq^\circ) \leftarrow \dots$ ” and “ $(\Omega^v, \mathcal{E}^v, \sqsubseteq^v) \leftarrow \dots$ ” respectively.
- At line 1 replace output (Ω, \mathcal{E}) with $(\Omega, \mathcal{E}, \sqsubseteq)$ where \sqsubseteq is the given total order on φ .
- At line 8 return $(\Omega, \mathcal{E}, \sqsubseteq)$ where \sqsubseteq copies all relations from \sqsubseteq° (that impose a partial order on $\alpha - \{s\}$), copies all relations from \sqsubseteq^v for $v \in \alpha$ (that impose a partial order on $v(\beta \cap T)$), and imposes additionally relations $a \sqsubseteq b$ for all $a \in \alpha - \{s\}$, $b \in \beta$.

Suppose that $\text{OrderedCuts}'(s\varphi'; G)$ returns $(\Omega, \mathcal{E}, \sqsubseteq)$. The following claims can be easily verified by a straightforward induction:

- (i) $\text{OrderedCuts}(s, v_1, \dots, v_\ell; G)$ returns (Ω, \mathcal{E}) for any permutation v_1, \dots, v_ℓ of φ' consistent with \sqsubseteq .
- (ii) If v_1, \dots, v_ℓ is sampled as a uniformly random permutation of φ' consistent with \sqsubseteq then v_1, \dots, v_ℓ is a uniformly random permutation of φ' .

To prove the second part of Theorem 22, it thus suffices to show that the expected complexity of $\text{OrderedCuts}'(\varphi; G)$ for a given 1-sequence φ is $O(t_{\text{MC}}(n, m) \cdot \log |\varphi|)$. We use the same notation and terminology for analyzing $\text{OrderedCuts}'(\varphi; G)$ that we defined in the beginning of this section for $\text{OrderedCuts}(\varphi; G)$. We make the following claim about the execution of $\text{OrderedCuts}'(\varphi; G)$.

Lemma 26. (a) Consider non-leaf node σ , and let τ_1, \dots, τ_k be its right children. Then $\mathbb{E}[\sum_{i \in [k]} |V_{\tau_i}|] \leq \frac{1}{2}|V_\sigma|$ and $\mathbb{E}[\sum_{i \in [k]} |E_{\tau_i}|] \leq \frac{1}{2}|E_\sigma|$.
 (b) For each $\mu \in \Lambda$ we have $\mathbb{E}[|V_\mu|] \leq n \cdot (\frac{1}{2})^{|\mu|}$ and $\mathbb{E}[|E_\mu|] \leq m \cdot (\frac{1}{2})^{|\mu|}$ where $V_\mu = \bigcup_{\sigma: \lambda(\sigma)=\mu} V_\sigma$, $E_\mu = \bigcup_{\sigma: \lambda(\sigma)=\mu} E_\sigma$, $n = |V_G|$, $m = |E_G|$, and $|\mu|$ is the number of 1's in μ .

Proof. Part (b) is a straightforward consequence of part (a) (and Lemma 25(b)), so we focus on proving part (a). Consider the call $\text{OrderedCuts}'(s\varphi'; G)$ with graph $G = (V, E, w)$ corresponding to node σ . Define $\ell = |\varphi'|$, $p = \lceil \frac{1}{2}(|\varphi| + 1) \rceil - 1$ and $q = \ell - p$, then $p \geq q$. Define sets $A = \alpha - \{s\}$ and $B = \beta$. Recall that A is a random subset of φ' of size p , and $B = \varphi' - A$.

Let A' be a random subset of A of size q , and let T^* be the minimal minimum A' - B cut in G . We claim that $\mathbb{E}[|V_{G[T^*]}|] \leq \frac{1}{2}|V|$ and $\mathbb{E}[|E_{G[T^*]}|] \leq \frac{1}{2}|E|$. Indeed, for disjoint subsets $X, Y \subseteq \varphi'$ of size q let $T_{X,Y}^*$ be the minimal minimum X - Y cut in G . Clearly, sets $T_{X,Y}^*$ and $T_{Y,X}^*$ are disjoint. Conditioned on the event $\{A', B\} = \{X, Y\}$, we have $(A', B) = (X, Y)$ with prob. $\frac{1}{2}$ and $(A', B) = (Y, X)$ with prob. $\frac{1}{2}$. Therefore,

$$\mathbb{E}[|V_{G[T^*]}| \mid \{A', B\} = \{X, Y\}] = \frac{1}{2}|V_{G[T_{X,Y}^*]}| + \frac{1}{2}|V_{G[T_{Y,X}^*]}| \leq \frac{1}{2}|V|$$

Summing this over pairs (X, Y) with appropriate probabilities gives the desired bound on $\mathbb{E}[|V_{G[T^*]}|]$. The bound on $\mathbb{E}[|E_{G[T^*]}|]$ can be obtained in a similar way.

Now consider node $v \in \alpha$, and let (S, T) be the cut computed at line 5 for node v . (S, T) can be equivalently defined as the minimum A_v - B_v cut in G with minimal T where $A_v = (V - [v]^\circ) \cup \{v\}$ and $B_v = B \cap [v]^\circ$. We have $A' \subseteq A_v$ and $B_v \subseteq B$, so by Lemma 23 we have $T \subseteq T^*$. This implies H_{τ_v} is a subgraph of $G[T^*]$ where τ_v is the right child of σ corresponding to node v , and thus proves the claim. □

Using Lemma 26(b), we can bound the expected total number of nodes in edges as follows:

$$\sum_{\mu \in \Lambda} \mathbb{E}[|V_\mu|] \leq n \cdot \sum_{\mu \in \Lambda} (\frac{1}{2})^{|\mu|} \quad \sum_{\mu \in \Lambda} \mathbb{E}[|E_\mu|] \leq m \cdot \sum_{\mu \in \Lambda} (\frac{1}{2})^{|\mu|}$$

Theorem 22 now follows from the following calculation:

$$\begin{aligned} \sum_{\mu \in \Lambda} (\frac{1}{2})^{|\mu|} &\leq \sum_{d=0}^{d_{\max}} \sum_{\mu \in \{0,1\}^d} (\frac{1}{2})^{|\mu|} = \sum_{d=0}^{d_{\max}} \sum_{k=0}^d \binom{d}{k} (\frac{1}{2})^k = \sum_{d=0}^{d_{\max}} (1 + \frac{1}{2})^d \\ &= 2((\frac{3}{2})^{d_{\max}+1} - 1) \leq (\frac{3}{2})^{\log_2 n + O(1)} = O(n^{\log_2(3/2)}) \end{aligned}$$

4 Depth-1 OC trees

In this section we introduce the notion of a *depth-1 OC tree*, or OC_1 tree.

Definition 27. Consider sequence $s\varphi$ in graph G . A OC_1 tree for (φ, G) is a pair (Ω, \mathcal{E}) such that there exists subsequence $\psi = s\dots$ of $\varphi = s\dots$ with the following properties.

- (ψ, \mathcal{E}) is a star graph with the root s , i.e. $\mathcal{E} = \{vs : v \in \psi - \{s\}\}$.
- (ψ, \mathcal{E}) is an OC tree for (ψ, G) .
- For every $v \in \varphi - \{s\}$ there exists $u \in \psi - \{s\}$ such that $u \sqsubseteq v$ and $v \in [u]$.

The following result shows the existence of an OC_1 tree.

Lemma 28. Let (Ω, \mathcal{E}) be an OC tree for (φ, G) . Define $\psi = \varphi$, and let us modify tuple $(\psi, \Omega, \mathcal{E})$ using the following algorithm: while (ψ, \mathcal{E}) has a leaf node of depth two or larger, pick the rightmost such node $u \in \psi$ and replace $(\psi, \Omega, \mathcal{E})$ with $(\psi^{-u}, \Omega^{-u}, \mathcal{E}^{-u})$. Then the resulting pair (Ω, \mathcal{E}) is an OC_1 tree for (φ, G) .

Proof. We will use Lemma 24. In the light of this lemma, it suffices to show the following: if (Ω, \mathcal{E}) is an OC tree for sequence φ and t is the rightmost leaf of (φ, \mathcal{E}) that has depth two or larger then t is a free leaf in (φ, \mathcal{E}) . Suppose not, then $\varphi = \dots t\dots u\dots$ where t, u have the same parent. Thus, u has depth two or larger. Let v be a leaf of the subtree of (φ, \mathcal{E}) rooted at u , then v also has depth two or larger. Furthermore, either $v = u$ or $\varphi = \dots t\dots u\dots v\dots$. This contradicts the choice of t . \square

The lemma means that an OC_1 tree for (φ, G) can be trivially constructed if we have OC for (φ, G) . However, an OC_1 tree can potentially be constructed faster than an OC tree, since we do not need to recurse on subproblems corresponding to depths larger than 1.

Let $\text{OrderedCuts}_1(\varphi, G)$ be a procedure that outputs an OC_1 tree for (φ, G) . In this section we prove the following.

Theorem 29. There exists a randomized (Las-Vegas) algorithm for computing GH tree for graph G with expected complexity $\tilde{O}(1) \cdot (t_{\text{OC}_1}(n, m))$, where $t_{\text{OC}_1}(n, m)$ is the complexity of $\text{OrderedCuts}_1(\cdot)$ on a graph with $O(n)$ nodes and $O(m)$ edges.

It will be convenient to define a *named partition of set V* as a pair (\mathcal{S}, Π) where $\mathcal{S} \subseteq V$ and Π is a set of disjoint subsets of V such that (i) $\mathcal{S} \subseteq \langle \Pi \rangle$ and (ii) for each $v \in \mathcal{S}$ there exists unique $U \in \Pi$ with $v \in U$. With some abuse of terminology we will denote a named partition with a single letter \mathcal{S} (treating it as a subset of V when needed), and will denote set $U \in \Pi$ containing v as \mathcal{S}_v . We denote $\langle \mathcal{S} \rangle = \bigcup_{v \in \mathcal{S}} \mathcal{S}_v$.

Note that an OC_1 tree (Ω, \mathcal{E}) can be uniquely represented by a named partition \mathcal{S} with $\mathcal{S} = \{v : vs \in \mathcal{E}\}$ and $\mathcal{S}_v \in \Omega$ for $v \in \mathcal{S}$. We can thus assume that procedure $\text{OrderedCuts}_1(\varphi, G)$ for sequence $\varphi = s\dots$ returns named partition \mathcal{S} of $V_G - \{s\}$, with $\mathcal{S} \subseteq \varphi - \{s\}$. In the new notation Definition 27 can be reformulated as follows.

Definition 30. Named partition \mathcal{S} of $V_G - \{s\}$ is an OC_1 tree for sequence $\varphi = sv_1\dots v_\ell$ and graph G if

- For every $v_k \in \mathcal{S}$ set \mathcal{S}_{v_k} is a minimum $s((v_1\dots v_{k-1}) \cap \mathcal{S})$ - v_k cut in G .
- For every $k \in [\ell]$ there exists $v_i \in \{v_1, \dots, v_k\} \cap \mathcal{S}$ with $v_k \in \mathcal{S}_{v_i}$.

Remark 2. In the algorithm below instead of condition (ii) we will only need a slightly weaker property: condition (ii) needs to hold only for $k \in [\ell]$ such that $\{v_1, \dots, v_{k-1}\} \cap C_{sv_k} = \emptyset$ where C_{sv_k} is a minimum s - v_k cut.

4.1 Computing cuts for a fixed source

Let us consider graph $G = (V, E, w)$, node $s \in V$ and subset $X \subseteq V - \{s\}$. First, we show how we can use procedure `OrderedCuts1` to compute minimum s - v cuts for many nodes $v \in X$ under the following condition.

Assumption 1. *For every $v \in X$ the minimum s - v cut in G is unique.*

In particular, we will present an algorithm with the following properties.

Theorem 31. *There exists randomized algorithm `FixedSourcePartition1`(s, X, G) that outputs a named partition \mathcal{S} of $V_G - \{s\}$ with $\mathcal{S} \subseteq X$ satisfying the following:*

- (a) \mathcal{S}_v is a minimum s - v cut in G for every $v \in \mathcal{S}$.
- (b) If Assumption 1 holds then $X \subseteq \langle \mathcal{S} \rangle$ with probability at least $1 - 1/\text{poly}(|X|)$ (for an arbitrary fixed polynomial).

It makes $O(\log^3 |X|)$ calls to procedure `OrderedCuts1`(\cdot) for graph G and performs $O(|X| \log^4 |X|)$ additional work.

The algorithm is given below. Its parameter is a sequence of probabilities $\alpha_1, \dots, \alpha_N$ that will be specified later.

Algorithm 12: `FixedSourcePartition1`(s, X, G).

```

1 set  $\lambda(v) = \text{cost}(\{v\})$  for all  $v \in X$ 
2 for  $i = 1, \dots, N + 1$  do
3   sample  $Y \leftarrow \text{RandomSubset}(X; \alpha_i)$  /* use  $\alpha_{N+1} = 1$  */
4   sort nodes in  $Y$  as  $v_1, \dots, v_\ell$  so that  $\lambda(v_1) \geq \dots \geq \lambda(v_\ell)$ ,  $\ell = |Y|$ 
5   call  $\mathcal{S} \leftarrow \text{OrderedCuts}_1(sv_1, \dots, v_\ell, G)$  /*  $\mathcal{S} \subseteq Y \subseteq X$  */
6   if  $i \leq N$  then
7     for each  $v \in \mathcal{S}$  update  $X := X - (\mathcal{S}_v - \{v\})$ 
8     for each  $v \in \mathcal{S}$  and  $u \in \mathcal{S}_v$  update  $\lambda(u) := \min\{\lambda(u), \text{cost}(\mathcal{S}_v)\}$ 
9   else
10    let  $\mathcal{S}^* = \{v_k \in \mathcal{S} : \text{cost}(\mathcal{S}_{v_k}) \leq \text{cost}(\mathcal{S}_v) \ \forall v \in \{v_1, \dots, v_k\} \cap \mathcal{S}\}$ 
11    return named partition  $\mathcal{S}^*$  where  $\mathcal{S}_v^* = \mathcal{S}_v$  for  $v \in \mathcal{S}^*$ 

```

Note that each update at line 7 preserves the property $\mathcal{S} \subseteq X$, since the sets in $\{\mathcal{S}_v : v \in \mathcal{S}\}$ are disjoint. This means, in particular, that the update $X := X - (\mathcal{S}_v - \{v\})$ is equivalent to the update $X := (X - \mathcal{S}_v) \cup \{v\}$.

It can be seen that the output of Algorithm 12 satisfies property (a) of Theorem 31; this follows from the definition of `OrderedCuts1` and from Lemma 3. We will show next that there exist sequence $\alpha_1, \dots, \alpha_N$ with $N = \Theta(\log^3 |X|)$ so that property (b) of Theorem 31 holds.

We let λ_i, X_i, Y_i for $i \in [N + 1]$ to be the variables at the end of the i -th iteration, and λ_0, X_0 be the variables after initialization at line 1. Note that $Y_i = \text{RandomSubset}(X_{i-1}; \alpha_i)$ for $i \in [N + 1]$. We always use letter X to denote the original set $X = X_0$.

In the remainder of the analysis we assume that Assumption 1 holds. We use the same notation as in Section 2.2; let us recap it briefly. For $v \in X$ let C_{sv} be the minimum s - v cut in G (which is now unique). We write $u \sim v$ for nodes $u, v \in X$ if $C_{su} = C_{sv}$. Let Φ be the set of equivalence classes of equivalence relation \sim , and for $v \in X$ let $\llbracket v \rrbracket \in \Phi$ be the class to which v belongs. We write $\llbracket u \rrbracket \preceq \llbracket v \rrbracket$ if $C_{su} \subseteq C_{sv}$, then \preceq is a partial order on Φ that can be represented by a rooted forest \mathcal{F} on nodes Φ so that $A \preceq B$ for $A, B \in \Phi$ iff A belongs to the subtree of \mathcal{F} rooted at B . We denote $\text{Roots}(\mathcal{F})$ to be the set of roots of this forest. For node $A \in \Phi$ we denote $A^\downarrow = \{B \in \Phi : B \preceq A\}$. We define function $f : \Phi \rightarrow \mathbb{R}$ via $f(\llbracket v \rrbracket) = \text{cost}(C_{sv}) = f(s, v)$ for $v \in X$. Assumption 1 implies that $f(B) < f(A)$ for $B \prec A$.

Lemma 32. For each $R \in \text{Roots}(\mathcal{F})$ and $i \in [N]$ there holds $R \cap X_i \neq \emptyset$.

Proof. We use induction on i (for a fixed $R \in \text{Roots}(\mathcal{F})$). Consider the i -th iteration, and let \mathcal{S} be the OC_1 tree computed at line 5. We make the following claim:

- If $v \in \mathcal{S}$ and $v \notin R$ then $\mathcal{S}_v \cap R = \emptyset$. Indeed, conditions $v \notin R$ and $R \in \text{Roots}(\mathcal{F})$ imply that $C_{sv} \cap R = \emptyset$. By the definition of OC_1 tree, set \mathcal{S}_v is a minimum sa - v cut for some sequence α . Lemma 23 gives that $\mathcal{S}_v \subseteq C_{sv}$, implying the claim.

The claim of Lemma 32 now easily follows (recalling that the update $X := X - (\mathcal{S}_v - \{v\})$ at line 7 is equivalent to the update $X := (X - \mathcal{S}_v) \cup \{v\}$). \square

Consider root $R \in \text{Roots}(\mathcal{F})$. As in Section 2.2, subset $\Psi \subseteq \Phi$ is said to be R -rooted if it can be represented as $\Psi = R^\downarrow - \bigcup_{A \in \tilde{\Phi}} A^\downarrow$ for some subset $\tilde{\Psi} \subseteq R^\downarrow$. The minimal set $\tilde{\Psi}$ in this representation will be denoted as Ψ^- . One exception is the set $\Psi = \emptyset$: for such Ψ we define $\Psi^- = \{R\}$ (set R will always be clear from the context).

Consider subsets $Y \subseteq X$, $\Psi \subseteq \Phi$ and node $v \in X$. As before, we say that Y hits v in Ψ if $C_{sv} \cap \langle \Psi \rangle \cap Y = \{v\}$. We denote

$$\Psi[Y] = \Psi - \bigcup_{v : Y \text{ hits } v \text{ in } \Psi} [v]^\downarrow$$

For subsets Y_1, \dots, Y_k we also denote $\Psi[Y_1, \dots, Y_k] = \Psi[Y_1] \dots [Y_k]$.

Lemma 33. Consider root $R \in \text{Roots}(\mathcal{F})$, and for $i \in [N]$ denote $\Psi_i = R^\downarrow[Y_1, \dots, Y_i]$, so that $R^\downarrow = \Psi_0 \supseteq \Psi_1 \supseteq \dots \supseteq \Psi_N$. Then the following holds for every $A \in \Psi_i^-$, $i \in [N]$:

- $|\langle A^\downarrow \rangle \cap X_i| \leq 1$. If $\langle A^\downarrow \rangle \cap X_i = \{v\}$ then $v \in A$ and $\lambda_i(v) = f(A)$.

Proof. We use induction on i . If $i = 0$ then $\Psi_i^- = \emptyset$ and the claim is vacuous. Suppose it holds for $i - 1$; let us prove for $i \in [N]$. Note that $\Psi_i = \Psi_{i-1}[Y_i]$. Consider $A \in \Psi_i^-$. If $A \in \Psi_{i-1}^-$ then the claim holds by the induction hypothesis and the facts that $X_i \subseteq X_{i-1}$ and $\mu_i(v) \leq \mu_{i-1}(v)$ for all v . Suppose that $A \notin \Psi_{i-1}^-$. Condition $A \in \Psi_i^- = (\Psi_{i-1}[Y_i])^-$ then implies that there exists $v \in A$ such that Y_i hits v in Ψ_{i-1} , i.e. $C_{sv} \cap \langle \Psi_{i-1} \rangle \cap Y_i = \{v\}$. We then have $A = [v] \in \Psi_{i-1}$.

Let $\varphi = sav \dots$ be the ordering of nodes in $\{s\} \cup Y_i$ used in the algorithm. We claim that $\alpha \cap C_{sv} = \emptyset$. Indeed, suppose that there exists $u \in \alpha \cap C_{sv} \subseteq Y_i \cap C_{sv}$, then we must have $u \notin \langle \Psi_{i-1} \rangle$ and hence $[u] \notin \Psi_{i-1}$. Condition $u \in C_{sv}$ implies that $[u] \preceq [v] = A$. Conditions $A \in \Psi_{i-1}$, $[u] \preceq A$, $[u] \notin \Psi_{i-1}$ imply that there exists $B \in \Psi_{i-1}$ with $[u] \preceq B \prec A$. We have $u \in \langle B^\downarrow \rangle$ and $u \in Y_i \subseteq X_{i-1}$. The induction hypothesis gives that $\langle B^\downarrow \rangle \cap X_{i-1} = \{u\}$, $u \in B$ and $\lambda_{i-1}(u) = f(B)$. We obtain that $\lambda_{i-1}(u) = f(B) < f(A) \leq \lambda_{i-1}(v)$ and so u should come after v in φ - a contradiction.

Let $\mathcal{S} = \text{OrderedCuts}_1(\varphi, G)$ be the OC_1 tree computed at iteration i . By the definition OC_1 tree, there exists $u \in (\alpha v) \cap \mathcal{S}$ such that \mathcal{S}_u is a minimum sa' - u cut for some $\alpha' \subseteq \alpha - \{u\}$, and $v \in \mathcal{S}_u$. As shown above, we have $\alpha' \cap C_{sv} = \emptyset$. By construction, we have $X_i \subseteq X_{i-1} - (\mathcal{S}_u - \{u\})$. Recall that $C_{sv} \cap X = \langle A^\downarrow \rangle$ and so $\langle A^\downarrow \rangle \cap X_i \subseteq C_{sv} \cap X_i$. We now consider two possible cases.

- $u = v$. The conditions above imply that $\mathcal{S}_v = C_{sv}$, and so $\langle A^\downarrow \rangle \cap X_i \subseteq C_{sv} \cap X_i \subseteq \{v\}$. Furthermore, if $v \in X_i$ then we will have $\lambda_i(v) \leq \text{cost}(\mathcal{S}_v) = f(A)$.
- $u \neq v$. Since $\alpha' \cap C_{sv} = \emptyset$, set C_{sv} is also (the unique) minimum sa' - v cut. Recall that \mathcal{S}_u is a minimum sa' - u cut and $v \in \mathcal{S}_u$, and so \mathcal{S}_u is a minimum sa' - uv cut. Lemma 23 gives that $C_{sv} \subseteq \mathcal{S}_u$. Condition $\alpha \cap C_{sv} = \emptyset$ implies that $u \notin C_{sv}$ and so $C_{sv} \subseteq \mathcal{S}_u - \{u\}$. Thus, we will have $\langle A^\downarrow \rangle \cap X_i \subseteq C_{sv} \cap X_i = \emptyset$.

In both cases the claim of Lemma 33 holds. □

Lemma 34. *Suppose that $R^\downarrow[Y_1, \dots, Y_N] = \emptyset$ for all $R \in \text{Roots}(\mathcal{F})$. Then the output of Algorithm 12 satisfies $X \subseteq \langle \mathcal{S}^* \rangle$.*

Proof. Condition $R^\downarrow[Y_1, \dots, Y_N] = \emptyset$ implies that $(R^\downarrow[Y_1, \dots, Y_N])^- = \{R\}$. Lemma 33 gives that $|\langle R^\downarrow \rangle \cap X_N| \leq 1$. By Lemma 32 we conclude that $\langle R^\downarrow \rangle \cap X_N = \{v\}$ for some $v \in R$. Furthermore, $\lambda_N(v) = f(R)$ by Lemma 33.

To summarize, we showed that $X_N \subseteq \langle \text{Roots}(\mathcal{F}) \rangle$, and for each $R \in \text{Roots}(\mathcal{F})$ there exists unique $v \in R \cap X_N$; this v satisfies $\lambda_N(v) = f(R)$. Let $\varphi = sv_1 \dots v_\ell$ be the ordering of nodes in $Y_N = X_N$ used in the algorithm, and let $\mathcal{S} = \text{OrderedCuts}_1(\varphi, G)$ be the computed OC_1 tree for (φ, G) . By the definition of OC_1 tree, for each $v \in \mathcal{S}$ set \mathcal{S}_v is a minimum $s\alpha$ - v cut for some $\alpha \subseteq X_N - \{v\}$. We have $\alpha \cap C_{sv} = \emptyset$, and thus $\mathcal{S}_v = C_{sv}$. We must also have $\mathcal{S} = X_N$ (if there exists $v \in X_N - \mathcal{S}$ then $v \in \mathcal{S}_u = C_{su}$ for some $u \in \mathcal{S}$, $u \neq v$ - a contradiction). Since $\lambda(v_1) \geq \dots \geq \lambda(v_\ell)$, we will have $\text{cost}(\mathcal{S}_{v_1}) \geq \dots \geq \text{cost}(\mathcal{S}_{v_\ell})$ and so line 9 outputs set $\mathcal{S}^* = \mathcal{S}$. The claim follows. □

It remains to construct sequence $\alpha_1, \dots, \alpha_N$ such that the precondition of Lemma 34 holds w.h.p.. For that we use the same technique as in Section 2.2, which is based on Lemma 8. Applying the same argument as in Corollary 9 gives the following result, and concludes the proof of Theorem 31.

Corollary 35. *Denote $n = |X|$. For every fixed polynomial $p(n)$ there exists a sequence $\alpha_1, \dots, \alpha_N$ with $N = \Theta(\log^3 n)$ such that the precondition of Lemma 34 holds with probability at least $1 - \frac{1}{p(n)}$.*

4.2 Overall algorithm

We finally show how to implement line 4 of Algorithm 6 using procedure `FixedSourcePartition1`. Note that we this procedure does not allow to specify constraints on the sizes of computing minimum s - v cuts, so the technique used earlier in Section 2.3 (sampling s at random) will not work. We will instead use a different approach. It relies on the total order \preceq on cuts $S \subseteq V$ introduced in Section 2.3. This order satisfies, in particular, the following: if $|S \cap X| < |(V - S) \cap X|$ then $S \prec V - S$. The algorithm is given below; the sequence of probabilities β, \dots, β_M will be specified later.

Algorithm 13: Line 4 of Algorithm 6.

```

1 while true do
2   pick arbitrary  $s \in X$ 
3   apply random permutation to  $H$  as in Proposition 10 to get graph  $H'$ 
4   for  $i = 1, \dots, M$  do
5     sample  $Y \leftarrow \text{RandomSubset}(X - \{s\}; \beta_i)$ 
6     call  $\mathcal{S} \leftarrow \text{FixedSourcePartition}_1(s, Y, H')$ 
7     if exists  $v \in \mathcal{S}$  with  $V - \mathcal{S}_v \prec \mathcal{S}_v$  then pick arbitrary such  $v$  and update  $s := v$ 
8     else if  $X - \{s\} \subseteq \langle \mathcal{S} \rangle$  then terminate and return  $(s, \{\mathcal{S}_v : v \in \mathcal{S}\})$ 

```

We will show the following.

Lemma 36. *Suppose that $(\beta, \dots, \beta_M) = (\underbrace{2^{-d}, \dots, 2^{-d}}_{K \text{ times}}, \dots, \underbrace{2^{-2}, \dots, 2^{-2}}_{K \text{ times}}, \underbrace{2^{-1}, \dots, 2^{-1}}_{K \text{ times}}, 1)$ where $d = \lfloor \log_2 |X| \rfloor$ and $K = \Theta(\log \log n)$ (with an appropriate constant). Then each run of Algorithm 13 (i.e. lines 2-7) terminates with probability $\Omega(1)$.*

Proof. We can assume that the modification of H at line 3 produces graph H' with a unique GH tree (this happens with probability $\Omega(1)$), and so Assumption 1 always holds. We have, in particular, $C_{uv} = V - C_{vu}$ for any $u, v \in X$.

Let \sqsubseteq be the total order on X induced by \preceq (see Lemma 11). Denote $n = |X|$, and for $s \in X$ let $\mathbf{rank}(s) \in [n]$ be the rank of s according to the reverse of \sqsubseteq (so that the largest node s w.r.t. \sqsubseteq satisfies $\mathbf{rank}(s) = 1$). Clearly, if node s is updated at line 7 then we must have $s \sqsubset v$, i.e. every such update strictly decreases the rank of s .

For $p \in [d]$ let “ p -stage” be the sequence of iterations i that use $\beta_i = 2^{-p}$. We say the p -stage is successful if at the end of this stage node s satisfies $\mathbf{rank}(s) \leq 2^{p-1}$ (or if the algorithm has terminated earlier). We claim that the p -stage is successful with probability at least $1 - \frac{1}{2d}$ assuming that either $p = d$ or $p \in [d - 1]$ and $(p + 1)$ -stage is successful. Indeed, consider a single iteration (lines 5-8) with $\beta_i = 2^{-p}$. If $\mathbf{rank}(s) \leq 2^{p-1}$ then the claim holds; we can thus assume that $\mathbf{rank}(s) \in (2^{p-1}, 2^p]$. Let $Y \subseteq X - \{s\}$ be the set sampled at this iteration. The following events will hold jointly with probability at least $1 - \gamma$ for some constant $\gamma > 0$: $Y \cap \{v \in X : \mathbf{rank}(v) \leq 2^{p-1}\} \neq \emptyset$ and $Y \cap \{v \in X : 2^{p-1} < \mathbf{rank}(v) \leq 2^p\} = \emptyset$. The first event implies that this iteration will update s , and the second event implies that the new s will satisfy $\mathbf{rank}(s) \leq 2^{p-1}$. The p -stage has K iterations, and thus it will be successful with probability at least $1 - \gamma^K = 1 - \gamma^{\Theta(\log \log n)} \geq 1 - \frac{1}{2d}$ with an appropriate constant in the $\Theta(\cdot)$ notation.

There are d such stages in total, so all of them will be successful with probability at least $\frac{1}{2}$. If this happens, s becomes the largest node in X w.r.t. \sqsubseteq , and so the last iteration (with $\beta_M = 1$) will produce named partition \mathcal{S} with $X - \{s\} \subseteq \langle \mathcal{S} \rangle$. \square

By using the same reasoning as in Section 2.3, we now obtain

Corollary 37. *The expected complexity of Algorithm 6 with line 4 implemented as in Algorithm 13 is $O((t_{\text{OC}_1}(n, m) + n \log n) \cdot \log^5 n \cdot \log \log n)$ where $t_{\text{OC}_1}(n, m)$ is the complexity of procedure $\text{OrderedCuts}_1(\cdot, G)$ on graph with $O(n)$ nodes and $O(m)$ edges.*

References

- [1] Amir Abboud, Robert Krauthgamer, Jason Li, Debmalya Panigrahi, Thatchaphol Saranurak, and Ohad Trabelsi. Breaking the cubic barrier for all-pairs max-flow: Gomory-Hu tree in nearly quadratic time. In *FOCS*, 2022.
- [2] Amir Abboud, Robert Krauthgamer, and Ohad Trabelsi. Cut-equivalent trees are optimal for min-cut queries. In *FOCS*, 2020. Full version: arXiv:2009.06090.
- [3] Amir Abboud, Robert Krauthgamer, and Ohad Trabelsi. APMF < APSP? Gomory-Hu tree for unweighted graphs in almost-quadratic time. In *FOCS*, pages 1135–1146, 2021.
- [4] Amir Abboud, Robert Krauthgamer, and Ohad Trabelsi. Subcubic algorithms for Gomory-Hu tree in unweighted graphs. In *STOC*, pages 1725–1737, 2021. Full version at arXiv:2012.10281.
- [5] Amir Abboud, Robert Krauthgamer, and Ohad Trabelsi. Friendly cut sparsifiers and faster Gomory-Hu trees. In *SODA*, pages 3630–3649, 2022.
- [6] Takuya Akiba, Yoichi Iwata, Yosuke Sameshima, Naoto Mizuno, and Yosuke Yano. Cut tree construction from massive graphs. In *Proceedings of the IEEE 16th International Conference on Data Mining (ICDM)*, pages 775–780, 2016.
- [7] A. Bhalgat, R. Hariharan, T. Kavitha, and D. Panigrahi. An $o(mn)$ Gomory-Hu tree construction algorithm for unweighted graphs. In *STOC*, pages 605–614, 2007.

- [8] H. N. Gabow. Applications of a poset representation to edge connectivity and graph rigidity. In *FOCS*, pages 812–821, 1991.
- [9] G. Gallo, M. D. Grigoriadis, and R. E. Tarjan. A fast parametric maximum flow algorithm and applications. *SIAM J. Computing*, 18:30–55, 1989.
- [10] A. V. Goldberg and K. Tsoutsoulis. Cut tree algorithms: an experimental study. *Journal of Algorithms*, 38(1):51–83, 2001. Code: <https://web.archive.org/web/20140115171857/http://www.cs.princeton.edu/~kt/cut-tree/experi>
- [11] R. E. Gomory and T. C. Hu. Multi-terminal network flows. *Journal of the Society for Industrial and Applied Mathematics*, 9:551–570, 1961.
- [12] J. Hao and J. B. Orlin. A faster algorithm for finding the minimum cut in a directed graph. *Algorithmica*, 17:424–446, 1994.
- [13] Vladimir Kolmogorov. A computational study of Gomory-Hu tree construction algorithms. *arXiv:2204.10169v3*, August 2022.
- [14] Jason Li, Danupon Nanongkai, Debmalya Panigrahi, and Thatchaphol Saranurak. Fair cuts, approximate isolating cuts, and approximate gomory-hu trees in near-linear time. *arXiv:2203.00751*, March 2022.
- [15] Jason Li and Debmalya Panigrahi. Deterministic min-cut in poly-logarithmic maxflows. In *FOCS*, 2020.
- [16] Jason Li and Debmalya Panigrahi. Approximate Gomory-Hu tree is faster than $n - 1$ maxflows. In *STOC*, pages 1738–1748, 2021.
- [17] Jason Li, Debmalya Panigrahi, and Thatchaphol Saranurak. A nearly optimal all-pairs min-cuts algorithm in simple graphs. In *FOCS*, pages 1135–1146, 2021.
- [18] K. Mulmuley, U. V. Vazirani, and V. V. Vazirani. Matching is as easy as matrix inversion. *Combinatorica*, 7(1):105–113, 1987.