A novel multi-party semiquantum private comparison protocol of size relationship with *d*-dimensional singleparticle states

Tian-Yu Ye*, Jiang-Yuan Lian

College of Information & Electronic Engineering, Zhejiang Gongshang University, Hangzhou 310018, P.R.China

E-mail: happyyty@aliyun.com (T.Y. Ye)

Abstract: By using d -level single-particle states, the first multi-party semiquantum private comparison (MSQPC) protocol which can judge the size relationship of private inputs from more than two classical users within one execution of protocol is put forward. This protocol requires the help of one quantum third party (TP) and one classical TP, both of whom are allowed to misbehave on their own but cannot conspire with anyone else. Neither quantum entanglement swapping nor unitary operations are necessary for implementing this protocol. TPs are only required to perform d-dimensional single-particle measurements. The correctness analysis validates the accuracy of the compared results. The security analysis verifies that both the outside attacks and the participant attacks can be resisted.

Keywords: Semiquantum cryptography; multi-party semiquantum private comparison; size relationship comparison; *d* -level single-particle state.

1 Introduction

It is well known that quantum mechanics is one of the greatest scientific discoveries up to now. A novel kind of cryptography, which is called quantum cryptography, was put forward by combining quantum mechanics and classical cryptography in the year of 1984 [1]. In 1982, Yao [2] proposed the famous millionaire problem, which aims to determine who is richer on the basis that the wealth of two millionaires is not leaked out. The millionaire problem is essentially a problem of classical privacy comparison, whose security is based on the computational complexity of solving the corresponding mathematical problem. Later, in 2009, Yang and Wen [3] proposed the novel concept of quantum private comparison (QPC) by absorbing quantum mechanics into classical privacy comparison. Hereafter, a variety of QPC protocols [4-20] were proposed one after another. According to the function, there are two different types of QPC protocols, i.e., QPC of size relationship [4-10] and QPC of equality [3,11-20]. QPC of size relationship can determine the size relationship (i.e., greater than, smaller than and equal to) for the private inputs from different users, but QPC of equality just judges whether the private inputs from different users are identical or not. To some extent, QPC of size relationship may have wider applications than QPC of equality in reality. In practice, not all users have the ability to acquire all kinds of quantum equipment. To get over this problem, Boyer *et al.* [21] proposed the innovative concept of semiquantum. In a semiquantum scheme, partial users are exempt from the preparation and measurement of quantum superposition states and quantum entangled states. Later, Ye *et al.* [22,23] employed single photons in two degrees of freedom to design two novel semiquantum key distribution (SQKD) protocols. In 2016, the first semiquantum private comparison (SQPC) scheme [24] was suggested by introducing the concept of semiquantum into QPC. Same to QPC, SQPC can be also classified into two different types: SQPC of equality [24-30] and SQPC of size relationship [31-35]. With respect to SQPC of size relationship, the ones in Refs.[32,33], Refs.[31,34] and Ref.[35] are based on d - dimensional singleparticle states, d - dimensional Bell states and d -dimensional GHZ states, respectively. Obviously, each of the SQPC protocols in Refs.[31-35] is only suitable for two classical users. At present, there is no SQPC protocol which can judge the size relationship for private inputs from more than two classical users within one execution of protocol.

Based on the above analysis, in this paper, we adopt d -dimensional single-particle states to propose the first multi-party semiquantum private comparison (MSQPC) protocol which can judge the size relationship of private inputs from more than two classical users within one execution of protocol. One quantum third party (TP) and one classical TP, both of whom are allowed to misbehave on their own but cannot conspire with anyone else, help accomplish the comparison task. This protocol requires neither quantum entanglement swapping nor unitary operations. This protocol only needs TPs to perform d -dimensional single-particle measurements.

2 Protocol description

In a d -dimensional quantum system, the Z -basis and the X -basis can be described as

$$T_1 = \left\{ |0\rangle, |1\rangle, \dots, |d-1\rangle \right\} \tag{1}$$

and

$$T_2 = \left\{ F \left| 0 \right\rangle, F \left| 1 \right\rangle, \dots, F \left| d - 1 \right\rangle \right\},\tag{2}$$

respectively. Here, *F* is the *d* - dimensional discrete quantum Fourier transform, and $F|t\rangle = \frac{1}{\sqrt{d}} \sum_{\delta=0}^{d-1} e^{\frac{2\pi i \delta t}{d}} |\delta\rangle$, $t = 0, 1, ..., d-1 \cdot T_1$ and T_2 constitute two common conjugate bases.

Assume that there are N classical users, $P_1, P_2, ..., P_N$, where P_n possesses a L -length private integer sequence $p_n = \{p_n^1, p_n^2, ..., p_n^L\}$. Here, $p_n^i \in \{0, 1, ..., h\}$, $h = \frac{d-1}{2}$, n = 1, 2, ..., N and i = 1, 2, ..., L. Besides, $P_1, P_2, ..., P_N$ pre-share a secret key sequence $K = \{k_1, k_2, ..., k_L\}$ through a

secure mediated SQKD protocol [36], where $k_i \in \{0, 1, ..., d-1\}$ and i = 1, 2, ..., L. In the proposed MSQPC protocol, TP_1 is the quantum TP who has full quantum capabilities while TP_2 is the classical TP who merely possesses limited quantum abilities. By virtue of Ref.[37], TP_1 and TP_2 are permitted to launch all types of attacks according to their own will but cannot collude with anyone else. We describe the proposed MSQPC protocol in detail as follows.

Step 1: TP1 prepares N singe-particle state sequences whose particles are randomly chosen from

two sets T_1 and T_2 . These N singe-particle state sequences are represented by $S_1, S_2, ..., S_N$, where $S_n = \{q_n^1, q_n^2, ..., q_n^{16L}\}$ and n = 1, 2, ..., N. Then, TP_1 sends S_n to P_n via a quantum channel. Note that except the first particle, TP_1 sends out the next particle of S_n to P_n only after receiving the previous one from TP_2 .

Step 2: P_n produces a random binary sequence r_n , where $r_n = \{r_n^1, r_n^2, \dots, r_n^{16L}\}$, $r_n^l \in \{0,1\}$, $n = 1, 2, \dots, N$ and $l = 1, 2, \dots, 16L$. After receiving the *l* th particle of S_n , P_n enters into the REFLRCT mode or the MEASURE mode according to r_n^l . To be specific, when $r_n^l = 0$, P_n selects the REFLECT mode; otherwise, P_n chooses the MEASURE mode. Here, the RFFLECT mode replies to reflecting the received particle back to the sender without any interference, while the MEASURE mode means to measuring the received particle in the T_1 basis, preparing the same quantum state as found and sending it back to the sender. Note that P_n needs to record her measurement results when entering into the MEASURE mode. The new sequence after P_n performs her operations on S_n is represented by $S_n^{'}$, where $S_n^{'} = \{q_n^{1'}, q_n^{2'}, \dots, q_n^{16L'}\}$. Finally, P_n sends $S_n^{'}$ to TP_2 via a quantum channel.

Step 3: TP_2 produces a random binary sequence v_n , where $v_n = \{v_n^1, v_n^2, ..., v_n^{16L}\}$, $v_n^l \in \{0,1\}$, n = 1, 2, ..., N and l = 1, 2, ..., 16L. After receiving the *l* th particle of S_n^i , TP_2 enters into the REFLRCT mode or the MEASURE mode according to v_n^l . Concretely speaking, when $v_n^l = 0$, TP_2 selects the REFLECT mode; otherwise, P_n chooses the MEASURE mode. Note that when choosing the MEASURE mode, TP_2 should record her measurement results. The new sequence after TP_2 's operations on S_n^i is denoted as S_n^n , where $S_n^i = \{q_n^{1^n}, q_n^{2^n}, ..., q_n^{16L^n}\}$. Finally, TP_2 sends S_n^i to TP_1 via a quantum channel.

Step 4: TP_1 publishes the positions of particles prepared within the set T_2 in Step 1. In the meanwhile, P_n and TP_2 announce r_n and v_n , respectively, where n = 1, 2, ..., N. Based on the announced information, TP_1 executes the corresponding operations as listed in Table 1.

Case 1: In this case, the initial particles are prepared by TP_1 within the T_1 basis in Step 1; both P_n and TP_2 have selected the REFLECT mode; and TP_1 measures the corresponding particles in her

hand with the T_1 basis. By comparing her measurements with the corresponding initial prepared states, TP_1 can judge whether there is an eavesdropper or not. If there is no eavesdropper, this protocol will be proceeded;

Case 2: In this case, the initial particles are prepared by TP_1 within the T_2 basis in Step 1; both P_n and TP_2 have selected the REFLECT mode; and TP_1 measures the corresponding particles in her hand with the T_2 basis. By comparing her measurements with the corresponding initial prepared states, TP_1 can judge whether there is an eavesdropper or not. If there is no eavesdropper, this protocol will be proceeded;

Case 3: In this case, the initial particles are prepared by TP_1 within the T_1 basis in Step 1; P_n and TP_2 have chosen the MEASURE mode and the REFLECT mode, respectively; and TP_1 measures the corresponding particles in her hand with the T_1 basis. P_n needs to tell TP_1 the states of the newly generated particles. TP_1 compares her measurement results with the states of the newly generated particles from P_n and the corresponding initial prepared states. If there is no eavesdropper, this protocol will be proceeded;

Case 4: In this case, the initial particles are prepared by TP_1 within the T_1 basis in Step 1; P_n and TP_2 have chosen the REFLECT mode and the MEASURE mode, respectively; and TP_1 measures the corresponding particles in her hand with the T_1 basis. TP_2 needs to tell TP_1 the states of the newly generated particles. TP_1 compares her measurement results with the states of the newly generated particles from TP_2 and the corresponding initial prepared states. If there is no eavesdropper, this protocol will be proceeded;

Case 5, Case 6 and Case 7: In these three Cases, the initial particles are prepared by TP_1 within the T_2 basis in Step 1; at least one party from P_n and TP_2 has chosen the MEASURE mode; and TP_1 takes no action. Note that these three Cases are ignored;

Case 8: In this case, the initial particles are prepared by TP_1 within the T_1 basis in Step 1; both P_n and TP_2 have chosen the MEASURE mode; and TP_1 measures the corresponding particles in her hand with the T_1 basis. If the number of the corresponding particles in this Case on the site of TP_1 is less than 2L, the protocol will be suspended.

Step 5: TP_1 randomly picks out L particles from the ones belonging to Case 8 in her hand, and publishes their positions. Then, P_n and TP_2 announce their measurement results on these chosen

positions, respectively. Afterward, TP_1 checks the error rate for these chosen particles by comparing her measurement results with P_n and TP_2 's measurement results and the corresponding initial prepared states. If the error rate is zero, they will continue the protocol.

Step 6: P_n , TP_1 and TP_2 use the remaining L particles in Case 8 for private comparison. Note that all of P_n , TP_1 and TP_2 's measurement results on the particles in Case 8 are same. P_n , TP_1 and TP_2 's measurement results on the remaining L particles in Case 8 are denoted as $m_n = \{|m_n^1\rangle, |m_n^2\rangle, ..., |m_n^L\rangle\}$, where $m_n^i \in \{0, 1, ..., d-1\}$, n = 1, 2, ..., N and $i = 1, 2, ..., L \cdot P_n$ calculates

$$c_n^i = m_n^i \oplus k_i \oplus p_n^i, \qquad (3)$$

where the symbol \oplus denotes the modulo *d* addition. Finally, P_n sends c_n to TP_1 via an authenticated classical channel, where $c_n = \{c_n^1, c_n^2, \dots, c_n^L\}$.

Case	TP_1 's preparation basis	r_n^l	v_n^l	TP_1 's action	
Case 1	The T_1 basis	0	0	Measuring $q_n^{l^*}$ with the T_1 basis	
Case 2	The T_2 basis	0	0	Measuring $q_n^{l^*}$ with the T_2 basis	
Case 3	The T_1 basis	1	0	Measuring $q_n^{l^n}$ with the T_1 basis	
Case 4	The T_1 basis	0	1	Measuring $q_n^{l^*}$ with the T_1 basis	
Case 5	The T_2 basis	0	1	Ignored	
Case 6	The T_2 basis	1	0	Ignored	
Case 7	The T_2 basis	1	1	Ignored	
Case 8	The T_1 basis	1	1	Measuring $q_n^{I^n}$ with the T_1 basis	

Table 1 TP_1 's actions under different Cases

Step 7: After receiving c_n , for n = 1, 2, ..., N and i = 1, 2, ..., L, TP_1 calculates

$$f_n^i = c_n^i \Theta m_n^i. \tag{4}$$

Then, TP1 computes

$$R_{nn}^{i} = f_{n}^{i} \ominus f_{n}^{i}, \qquad (5)$$

where n' = 1, 2, ..., N and $n' \neq n$. TP_1 makes

$$y(R_{nn}^{i}) = \begin{cases} -1, & if \quad h < R_{nn}^{i} \le 2h; \\ 0, & if \quad R_{nn}^{i} = 0; \\ 1, & if \quad 0 < R_{nn}^{i} \le h. \end{cases}$$
(6)

Here, $y(R_{nn}^i) = -1$ means $p_n^i < p_n^i$; $y(R_{nn}^i) = 0$ means $p_n^i = p_n^i$; $y(R_{nn}^i) = 1$ means $p_n^i > p_n^i$. Finally,

 TP_1 publishes the final comparison results to P_1, P_2, \dots, P_N .

To be more clearly, the flow chart of the proposed MSQPC protocol is drawn in Fig.1 after the processes of security check are ignored.

3 Correctness analysis

3.1 Output correctness

After inserting Eq.(3) and Eq.(4) into Eq.(5), we can obtain

$$R_{nn'}^{i} = f_{n}^{i} \bigoplus f_{n'}^{i}$$

$$= \left(c_{n}^{i} \bigoplus m_{n}^{i}\right) \bigoplus \left(c_{n'}^{i} \bigoplus m_{n'}^{i}\right)$$

$$= \left(m_{n}^{i} \oplus k_{i} \oplus p_{n}^{i} \bigoplus m_{n}^{i}\right) \bigoplus \left(m_{n'}^{i} \oplus k_{i} \oplus p_{n'}^{i} \bigoplus m_{n'}^{i}\right)$$

$$= \left(k_{i} \oplus p_{n}^{i}\right) \bigoplus \left(k_{i} \oplus p_{n'}^{i}\right)$$

$$= p_{n}^{i} \bigoplus p_{n'}^{i}.$$
(7)

Here, n, n' = 1, 2, ..., N, $n' \neq n$ and i = 1, 2, ..., L. Since $p_n^i, p_n^i \in \{0, 1, 2, ..., h\}$ and $h = \frac{d-1}{2}$, according to Eq.(6) and Eq.(7), the following points stand: when $y(R_{nn'}^i) = -1$, it has $h < p_n^i \ominus p_{n'}^i \le 2h$, which implies $p_n^i < p_{n'}^i$; when $y(R_{nn'}^i) = 0$, it has $p_n^i \ominus p_{n'}^i = 0$, which implies $p_n^i = p_{n'}^i$; and when $y(R_{nn'}^i) = 1$, it has $0 < p_n^i \ominus p_{n'}^i \le h$, which implies $p_n^i > p_{n'}^i$. It can be concluded that the comparison result of the proposed MSQPC protocol is correct.

3.2 Examples

To further prove the correctness of the proposed MSQPC protocol, we give a specific example.

Assume that the dimension of quantum system is d = 19; there are four classical users, P_1, P_2, P_3, P_4 ; the first private integers of P_1, P_2, P_3, P_4 are $p_1^1 = 5$, $p_2^1 = 3$, $p_3^1 = 5$ and $p_4^1 = 6$, respectively; the first private key integer pre-shared among P_1, P_2, P_3, P_4 is $k_1 = 16$; the measurement results of P_1, P_2, P_3, P_4 , on the first remaining particles in Case 8 are $|m_1^1\rangle = |7\rangle$, $|m_2^1\rangle = |2\rangle$, $|m_3^1\rangle = |9\rangle$ and $|m_4^1\rangle = |10\rangle$, respectively. According to Eq.(3), P_1, P_2, P_3, P_4 can obtain $c_1^1 = 7 \oplus 16 \oplus 5 = 9$, $c_2^1 = 2 \oplus 16 \oplus 3 = 2$, $c_3^1 = 9 \oplus 16 \oplus 5 = 11$ and $c_4^1 = 10 \oplus 16 \oplus 6 = 13$, respectively. Then, P_1, P_2, P_3, P_4 send $c_1^1, c_2^1, c_3^1, c_4^1$ to TP_1 via an authenticated classical channel, respectively. After receiving $c_1^1, c_2^1, c_3^1, c_4^1$, by virtue of Eq.(4), TP_1 can get $f_1^{-1} = c_1^1 \oplus m_1^1 = 9 \oplus 7 = 2$, $f_2^{-1} = c_2^1 \oplus m_2^1 = 2 \oplus 2 = 0$, $f_3^{-1} = c_3^1 \oplus m_3^1 = 11 \oplus 9 = 2$ and $f_4^1 = c_4^1 \oplus m_4^1 = 13 \oplus 10 = 3$. Afterward, through Eq.(5), TP_1 can obtain $R_{12}^1 = f_1^{-1} \oplus f_2^1 = 2 \oplus 0 = 2$, $R_{13}^1 = f_1^{-1} \oplus f_3^{-1} = 2 \oplus 2 = 0$, $R_{14}^{-1} = f_3^1 \oplus f_4^{-1} = 2 \oplus 3 = 18$, $R_{23}^2 = f_2^1 \oplus f_3^{-1} = 0 \oplus 2 = 17$, $R_{24}^1 = f_2^1 \oplus f_4^1 = 0 \oplus 3 = 16$ and $R_{34}^1 = f_3^1 \oplus f_4^1 = 2 \oplus 3 = 18$. According to Eq.(6), TP_1 makes $y(R_{12}^1) = 1$, $y(R_{13}^1) = 0$, $y(R_{14}^1) = -1$, $y(R_{23}^1) = -1$, $y(R_{24}^1) = -1$ and $y(R_{34}^1) = -1$, which imply $p_1^1 > p_2^1$, $p_1^1 = p_3^1$, $p_1^1 < p_1^1 < p_4^1$, $p_2^1 < p_4^1$, $p_2^1 < p_4^1$, $p_2^1 < p_4^1$, $p_2^1 < p_4^1$, respectively. In short, it has $p_2^1 < p_1^1 < p_4^1$.

4 Security analysis

4.1 Outside attacks

An outsider Eve may do her best to acquire p_n (n = 1, 2, ..., N) by launching some famous attacks, e.g., the intercept-resend attack, the measure-resend attack and the entangle-measure attack.

(1) The intercept-resend attack

There are three types of intercept-resend attacks according to the process of the proposed protocol. We will do the detailed analysis for them one by one in the following.

Firstly, Eve intercepts the particle of S_n and sends the fake one she has already prepared in the T_1 basis to P_n in Step 1; after P_n executes her operation, Eve intercepts the particle of $S_n^{'}$ and sends the original genuine one to TP_2 in Step 2. When P_n has chosen the REFLECT mode, Eve's attack cannot be detected, no matter what the original genuine particle is and which mode TP_2 has chosen. Consider the situation that P_n has chosen the MEASURE mode: if the original genuine particle is in the T_2 basis, as ignored according to Table 1, Eve's attack will not be detected in Step 4; if the original genuine particle is in the T_1 basis, Eve's attack will be discovered with the probability of $\frac{d-1}{d}$ in Step 4 and the probability of $\frac{d-1}{2d}$ in Step 5 when TP_2 has chosen the REFLECT mode and the MEASURE mode in Step 3, respectively.



Fig.1 The flow chart of the proposed MSQPC protocol

Secondly, Eve intercepts the particle of S_n and sends the fake one she has generated in advance in the T_1 basis to P_n in Step 1; then in Step 3, Eve intercepts the particle of $S_n^{"}$ and sends the original genuine one to TP_1 . Considering that the original genuine particle is in the T_1 basis, if P_n and TP_2 have chosen the REFLECT mode and the MEASURE mode, respectively, the existence of Eve will be detected with the probability of $\frac{d-1}{d}$ in Step 4; if both P_n and TP_2 have chosen the MEASURE mode, the existence of Eve will be detected with the probability of $\frac{d-1}{2d}$ in Step 5; if P_n and TP_2 have chosen the MEASURE mode and the REFLECT mode, respectively, the existence of Eve will be detected with the probability of $\frac{d-1}{d}$ in Step 4; if both P_n and TP_2 have chosen the REFLECT mode, the existence of Eve will be detected in Step 4; if both P_n and TP_2 have chosen the REFLECT mode, the existence of Eve will not be detected in Step 4. Considering that the original genuine particle is in the T_2 basis, no matter what mode P_n and TP_2 have chosen, the existence of Eve cannot be detected in Step 4.

Thirdly, Eve intercepts the particle of S_n and sends the fake one she has generated in advance in the T_1 basis to TP_2 in Step 2; after TP_2 applies her operation on the fake one, Eve intercepts the particle sent from TP_2 and sends the genuine one to TP_1 in Step 3. Considering that the original genuine particle is in the T_1 basis, if both P_n and TP_2 have chosen the MEASURE mode, the presence of Eve will be detected with the probability of $\frac{d-1}{2d}$ in Step 5; if P_n and TP_2 have chosen the REFLECT mode and the MEASURE mode, respectively, the presence of Eve will be detected with the probability of $\frac{d-1}{d}$ in Step 4; if P_n and TP_2 have chosen the MEASURE mode and the REFLECT mode, respectively, the presence of Eve will be detected with the probability of 0 in Step 4; if both P_n and TP_2 have chosen the REFLECT mode, the presence of Eve will be detected with the probability of 0 in Step 4. Considering that the original genuine particle is in the T_2 basis, no matter what mode P_n and TP_2 have chosen, the existence of Eve cannot be detected in Step 4.

(2) The measure-resend attack

In the following, we analyze three kinds of measure-resend attacks.

Eve intercepts the particle of $S_n / S_n' / S_n''$, measures it with the T_1 basis and sends the resulted

state to $P_n / TP_2 / TP_1$. If the original particle is in the T_1 basis, this attack cannot be discovered, no matter what mode P_n and TP_2 have chosen. Considering that the original particle is in the T_2 basis, if at least one of P_n and TP_2 has selected the MEASURE mode, Eve's attack will not be detected either; if both P_n and TP_2 have chosen the REFLECT mode, Eve's attack will be detected in Step 4, as the state of original particle was destroyed by Eve's measurement.

(3) The entangle-measure attack

Eve may launch her entangle-measure attack, as shown in Fig.2, by using two unitaries, U_E and U_F , where U_E and U_F share a common probe space with the state $|E\rangle$. Here, Eve applies U_E on the particle from TP_1 to P_n and performs U_F on the particle from P_n to TP_2 . As depicted in Ref.[21], Eve is allowed by the shared probe to perform the attack on the particle which are transmitted back according to the knowledge acquired by U_E .



Fig.2 Eve's entangle-measure attack with U_E and U_F

Theorem 1. Suppose that Eve applies U_E on the particle from TP_1 to P_n and performs U_F on the particle from P_n to TP_2 . For introducing no error in Step 4 and Step 5, the final state of Eve's probe should be independent of not only the operation of P_n but also the measurement results of P_n and TP_2 . As a result, Eve has no access to m_n .

Proof. For simplicity, we use $|t\rangle$ and $|J_t\rangle$ to denote the particle in the sets T_1 and T_2 , respectively, where $|J_t\rangle = F|t\rangle = \frac{1}{\sqrt{d}} \sum_{k=0}^{d-1} e^{\frac{2\pi i \delta t}{d}} |\delta\rangle$ and $t = 0, 1, \dots, d-1$. (1) Consider the situation that the particle of S_n is prepared in the T_1 basis. When TP_1 sends out the particle of S_n , Eve performs U_E on it, thus we can get [38]

$$U_{E}\left(\left|t\right\rangle\left|E\right\rangle\right) = \sum_{i=0}^{d-1} \gamma_{ti} \left|t'\right\rangle\left|e_{ti}\right\rangle, \qquad (8)$$

where $|e_{u'}\rangle$ (*t*,*t'* = 0,1,...,*d*-1) are the probe states of Eve decided by U_E , and

$$\sum_{t=0}^{d-1} \left| \gamma_{tt} \right|^2 = 1.$$
(9)

When P_n performs the MEASURE operation, the global composite system is collapsed into $\gamma_{u'} |t'\rangle |e_{u'}\rangle$. In order to avoid being discovered during the security checks of Case 3 and Case 8, after Eve performs U_F , the global state of the composite system should satisfy

$$U_{F}\left(\gamma_{n}\left|t\right\rangle\right)\left|e_{n}\right\rangle\right) = \begin{cases} \gamma_{n}\left|t\right\rangle\left|F_{n}\right\rangle, & \text{if } t=t^{'};\\ 0, & \text{if } t\neq t^{'}. \end{cases}$$
(10)

which implies

$$\gamma_{tt} = \begin{cases} \gamma_{tt}, & \text{if } t = t; \\ 0, & \text{if } t \neq t \end{cases}.$$
(11)

When P_n performs the REFLECT operation, according to Eq.(8) and Eq.(10), the global composite system after Eve performs U_F is turned into

$$U_{F}\left[U_{E}\left(\left|t\right\rangle\left|E\right\rangle\right)\right] = U_{F}\left(\sum_{t=0}^{d-1}\gamma_{tt}\left|t\right\rangle\right|e_{tt}\right)\right) = \sum_{t=0}^{d-1}U_{F}\left(\gamma_{tt}\left|t\right\rangle\right|e_{tt}\right)\right) = \gamma_{tt}\left|t\right\rangle\left|F_{tt}\right\rangle$$
(12)

for t = 0, 1, ..., d - 1. In order to avoid being discovered during the security checks of Case 1 and Case 4, Eve cannot change the state of the original particle of S_n . According to Eq.(12), this requirement is automatically satisfied.

(2) Consider the situation that the particle of S_n is prepared in the T_2 basis. After Eve performs U_E , the global composite system is evolved into

$$U_{E}(|J_{t}\rangle|E\rangle) = U_{E}\left[\left(\frac{1}{\sqrt{d}}\sum_{\delta=0}^{d-1}e^{\frac{2\pi i\delta t}{d}}|\delta\rangle\right)|E\rangle\right]$$
$$= \frac{1}{\sqrt{d}}\sum_{\delta=0}^{d-1}e^{\frac{2\pi i\delta t}{d}}U_{E}(|\delta\rangle|E\rangle).$$
(13)

When P_n chooses the REFLECT operation, the global composite system after Eve performs

 U_F is turned into

$$U_{F}\left[U_{E}\left(\left|J_{t}\right\rangle\right|E\right)\right] = \frac{1}{\sqrt{d}}\sum_{\delta=0}^{d-1} e^{\frac{2\pi i \delta t}{d}} U_{F}\left[U_{E}\left(\left|\delta\right\rangle\right|E\right)\right].$$
(14)

Inserting Eq.(12) into Eq.(14) generates

$$U_{F}\left[U_{E}\left(\left|J_{t}\right\rangle\left|E\right\rangle\right)\right] = \frac{1}{\sqrt{d}}\sum_{\delta=0}^{d-1} e^{\frac{2\pi i\delta t}{d}} \gamma_{\delta\delta}\left|\delta\right\rangle\left|F_{\delta\delta}\right\rangle.$$
(15)

By virtue of the inverse quantum Fourier transform, we have

$$\left|\delta\right\rangle = \frac{1}{\sqrt{d}} \sum_{\alpha=0}^{d-1} e^{-\frac{2\pi i \alpha \delta}{d}} \left|J_{\alpha}\right\rangle,\tag{16}$$

where $\delta = 0, 1, \dots, d-1$. Inserting Eq.(16) into Eq.(15) produces

$$U_{F}\left[U_{E}\left(|J_{t}\rangle|E\rangle\right)\right] = \frac{1}{\sqrt{d}}\sum_{\delta=0}^{d-1} e^{\frac{2\pi i\delta t}{d}}\gamma_{\delta\delta}\left(\frac{1}{\sqrt{d}}\sum_{\alpha=0}^{d-1} e^{-\frac{2\pi i\alpha\delta}{d}}|J_{\alpha}\rangle\right)|F_{\delta\delta}\rangle$$
$$= \frac{1}{d}\sum_{\delta=0}^{d-1}\sum_{\alpha=0}^{d-1} e^{\frac{2\pi i\delta(t-\alpha)}{d}}\gamma_{\delta\delta}|J_{\alpha}\rangle|F_{\delta\delta}\rangle$$

$$=\frac{1}{d}\left(\left|J_{0}\right\rangle_{\delta=0}^{d-1}e^{\frac{2\pi i\delta(t-0)}{d}}\gamma_{\delta\delta}\left|F_{\delta\delta}\right\rangle+\left|J_{1}\right\rangle_{\delta=0}^{d-1}e^{\frac{2\pi i\delta(t-1)}{d}}\gamma_{\delta\delta}\left|F_{\delta\delta}\right\rangle+\ldots+\left|J_{d-1}\right\rangle_{\delta=0}^{d-1}e^{\frac{2\pi i\delta[t-(d-1)]}{d}}\gamma_{\delta\delta}\left|F_{\delta\delta}\right\rangle\right).$$
 (17)

In order that Eve cannot be discovered during the security check of Case 2, it should meet

$$\sum_{\delta=0}^{d-1} e^{\frac{2\pi i \delta(t-\alpha)}{d}} \gamma_{\delta\delta} \left| F_{\delta\delta} \right\rangle = 0$$
(18)

for $t \neq \alpha$ and $t, \alpha = 0, 1, \dots, d-1$. It is obvious that for $t \neq \alpha$, we have

$$\sum_{\delta=0}^{d-1} e^{\frac{2\pi i \delta(t-\alpha)}{d}} = 0.$$
⁽¹⁹⁾

Thus, by virtue of Eq.(18) and Eq.(19), we have

$$\gamma_{00} | F_{00} \rangle = \gamma_{11} | F_{11} \rangle = \dots = \gamma_{(d-1)(d-1)} | F_{(d-1)(d-1)} \rangle = \gamma | F \rangle .$$
⁽²⁰⁾

(3) Applying Eq.(20) into Eq.(10) generates

$$U_{F}\left(\gamma_{n}\left|t\right\rangle\left|e_{n}\right\rangle\right) = \begin{cases} \gamma\left|t\right\rangle\left|F\right\rangle, & \text{if } t=t;\\ 0, & \text{if } t\neq t. \end{cases}$$
(21)

Applying Eq.(20) into Eq.(12) creates

$$U_{F}\left[U_{E}\left(\left|t\right\rangle\right|E\right)\right] = \gamma\left|t\right\rangle\left|F\right\rangle.$$
(22)

Applying Eq.(20) into Eq.(17) produces

$$U_{F}\left[U_{E}\left(\left|J_{t}\right\rangle\right|E\right)\right] = \gamma\left|J_{t}\right\rangle\left|F\right\rangle.$$
⁽²³⁾

Based on Eq.(21), Eq.(22) and Eq.(23), when Eve applies U_E on the particle from TP_1 to P_n and

performs U_F on the particle from P_n to TP_2 , for introducing no error in Step 4 and Step 5, the final state of Eve's probe should be independent of not only the operation of P_n but also the measurement results of P_n and TP_2 . As a result, Eve has no access to m_n , let alone p_n .

In addition, there are other two scenarios: one is that Eve performs U_E on the particle from TP_1 to P_n and performs U_F on the particle from TP_2 to TP_1 ; the other is that Eve applies U_E on the particle from P_n to TP_2 and applies U_F on the particle from TP_2 to TP_1 . After a similar proof as above, it is easy to find that in each of these two scenarios, Eve acquires no information about m_n either, not to mention p_n .

4.2 Participant attacks

In 2007, Gao *et al.* [39] put forward a novel concept of attack named as participant attack for the first time. Participant attacks are generally more serious and are worth being paid more attentions to. In this section, we consider four kinds of participant attacks.

(1) The participant attack from one dishonest user

In the proposed MSQPC protocol, it is easy to see that each user is of equal importance. Without loss of generality, assume that P_1 is the dishonest user who tries to steal the remaining N-1 users' private inputs. P_1 may try her best to obtain the secret input of P_j (j = 2, 3, ..., N) by launch all possible attacks. In this protocol, P_1 is independent from P_j , TP_1 and TP_2 . As a result, when P_1 launches her attacks, she essentially plays the role of an outside attacker. As illustrated in Sect.4.1, her illegal behaviors can be inevitably detected.

In addition, P_1 may hear of c_j when P_j sends it to TP_1 in Step 6. However, although P_1 knows k_i , she still cannot get p_j^i (i = 1, 2, ..., L) from c_j^i , due to lack of m_j^i . P_1 may hear the final comparison results from TP_1 in Step 7. However, it is still helpless for her to know p_j^i .

(2) The participant attack from two or more dishonest users

Here, we discuss the extreme situation that N - 1 dishonest users collude together to obtain the private input of the remaining one user. Without loss of generality, suppose that $P_1, P_2, ..., P_{b-1}, P_{b+1}, ..., P_N$ try to get the private input of P_b , where b = 2, 3, ..., N - 1. In this protocol, each of $P_1, P_2, ..., P_{b-1}, P_{b+1}, ..., P_N$ is independent from P_b , TP_1 and TP_2 . Hence, when $P_1, P_2, ..., P_{b-1}, P_{b+1}, ..., P_N$ conspire to impose their attacks, they act as an outside attacker in fact. As

a result, as proved in Sect.4.1, their attacks can be discovered undoubtedly.

In addition, $P_1, P_2, ..., P_{b-1}, P_{b+1}, ..., P_N$ may hear of c_b while it is sent from P_b to TP_1 in Step 6. Although $P_1, P_2, ..., P_{b-1}, P_{b+1}, ..., P_N$ knows k_i , they still cannot decode out p_b^i (i = 1, 2, ..., L) from c_b^i , because of being short of $m_b^i \cdot P_1, P_2, ..., P_{b-1}, P_{b+1}, ..., P_N$ may hear the final comparison results from TP_1 in Step 7. Unfortunately, they still have no way to gain p_b^i .

(3) The participant attack from semi-honest TP_1

In the proposed MSQPC protocol, TP_1 is not allowed to conspire with anyone else. Apparently, TP_1 automatically knows m_n^i , where n = 1, 2, ..., N and i = 1, 2, ..., L. Moreover, TP_1 gets c_n when P_n sends it to her in Step 6. Nevertheless, TP_1 has no idea about k_i , which means that she cannot infer p_n^i from c_n^i . In addition, although TP_1 can calculate out the final comparison results in Step 7, she still cannot get p_n^i .

(4) The participant attack from semi-honest TP_2

In the proposed MSQPC protocol, TP_2 is not permitted to collude with anyone else. TP_2 naturally knows m_n^i , where n = 1, 2, ..., N and i = 1, 2, ..., L. In addition, TP_2 may hear of c_n when P_n informs TP_1 of it in Step 6. Unfortunately, TP_2 still cannot decode out p_n^i from c_n^i , due to lack of k_i . Furthermore, TP_2 may hear the final comparison results from TP_1 in Step 7, but still has no knowledge about p_n^i .

5 Discussions and conclusions

Ref.[32] adopts the qudit efficiency, which is converted from the qubit efficiency defined in Ref.[40], to compute the efficiency of a quantum communication protocol adaptive for the d - dimensional system. According to Ref.[32], the qudit efficiency can be depicted as

$$\eta = \frac{\theta}{\sigma + \mu},\tag{24}$$

where σ , μ and θ are the number of qudits used, the length of classical information consumed during the classical communication and the length of private inputs compared, respectively. In the following, we calculate the qudit efficiency of the proposed MSQPC protocol by neglecting the classical resources consumed during the security check processes and the resources consumed for producing the pre-shared key sequence K.

In the proposed MSQPC protocol, the length of p_n (n = 1, 2, ..., N) is L, so we obtain $\theta = L \cdot TP_1$ needs to prepare S_n , whose length is 16L; after getting the qudits from TP_1 , when P_n enters into the MEASURE mode, she needs to generate 8L qudits; after receiving the qudits from P_n , when TP_2 enters into the MEASURE mode, she needs to produce 8L qudits; so we have $\sigma = 16L \times N + 8L \times N + 8L \times N = 32LN$. Furthermore, P_n needs to send c_n to TP_1 , so we get $\mu = L \times N = LN$. Therefore, the qudit efficiency of the proposed MSQPC protocol is equal to $\eta = \frac{L}{32LN + LN} = \frac{1}{33N}$.

In addition, we compare the proposed MSQPC protocol with previous SQPC protocols in detail, and describe the comparison outcomes in Table 2. From Table 2, we easily know that the proposed MSQPC protocol exceeds the protocols of Ref.[31], Ref.[34] and Ref.[35] in quantum resources, as d -dimensional single-particle states are much easier to prepare than d -dimensional Bell states and d -dimensional GHZ states; the proposed MSQPC protocol defeats the second protocol of Ref.[33] in usage of unitary operation, as it doesn't need any unitary operation; the proposed MSQPC protocol exceeds the protocols of Ref.[31], Ref.[34] and Ref.[35] in TP's quantum measurement, as it doesn't require d -dimensional Bell state measurements or d -dimensional GHZ state relationship of private inputs from more than two classical users within one execution of protocol.

In short, in this paper, the first MSQPC protocol which can judge the size relationship of private inputs from more than two classical users within one execution of protocol is designed by using d dimensional single-particle states. This protocol has two TPs, one possessing complete quantum capabilities and the other owning limited quantum capabilities. Both TPs are permitted to misbehave on their own but cannot conspire with anyone else. This protocol requires neither quantum entanglement swapping nor unitary operations. This protocol only requires TPs to implement d dimensional single-particle measurements. This protocol can prevent both the outside attacks and the participant attacks.

Table 2 The comparison outcomes of the proposed MSQPC protocol with previous SQPC protocols

	Ref.[31]	Ref.[32]	The first	The second	Ref.[34]	Ref.[35]	Our protocol
			protocol of	protocol of			
			Ref.[33]	Ref.[33]			
Quantum	<i>d</i> -						
resources	dimensional						

	Bell states	single-	single-particle	single-particle	Bell states	GHZ states	single-
		particle	states	states			particle
		states					states
Number of	2	2	2	2	2	2	Ν
users							
Number of	1	1	1	1	1	1	2
TP							
Туре	Semi-honest	Semi-honest	Semi-honest	Semi-honest	Semi-honest	Semi-honest	Semi-hones
of TP							
Usage of	Yes	Yes	Yes	Yes	Yes	Yes	Yes
pre-shared							
key							
Comparison	Yes	Yes	Yes	Yes	Yes	Yes	Yes
of size							
relationship							
Usage of	No	No	No	No	No	No	No
quantum							
entanglemen							
t swapping							
Usage of	No	No	No	Yes	No	No	No
unitary							
operation							
TP's	<i>d</i> -	<i>d</i> -	<i>d</i> -	<i>d</i> -	<i>d</i> -	<i>d</i> -	<i>d</i> -
quantum	dimensional	dimensional	dimensional	dimensional	dimensional	dimensional	dimensional
measuremen	Bell state	single-	single-particle	single-particle	Bell state	GHZ state	single-
t	measuremen	particle	measurements	measurements	measuremen	measuremen	particle
	ts and d -	measureme			ts and d -	ts, <i>d</i> -	measuremer
	dimensional	nts			dimensional	dimensional	ts
	single-				single-	Bell state	
	particle				particle	measuremen	
	measuremen				measuremen	ts and d -	
	ts				ts	dimensional	
						single-	
						particle	
						measuremen	

						ts	
Classical	<i>d</i> -	<i>d</i> -	<i>d</i> -	<i>d</i> -	No	<i>d</i> -	<i>d</i> -
users'	dimensional	dimensional	dimensional	dimensional		dimensional	dimensional
quantum	single-	single-	single- particle	single- particle		single-	single-
measuremen	particle	particle	measurements	measurements		particle	particle
t	measuremen	measureme				measuremen	measuremen
	ts	nts				ts	ts
TP's	Yes	No	Yes	Yes	Yes	Yes	Yes
knowledge							
about the							
comparison							
result							

Acknowledgments

Funding by the National Natural Science Foundation of China (Grant No.62071430 and No.61871347) and the Fundamental Research Funds for the Provincial Universities of Zhejiang (Grant No.JRK21002) is gratefully acknowledged.

Reference

- Bennett, C.H., Brassard, G.: Quantum cryptography: public key distribution and coin tossing. In:Proceedings of the IEEE International Conference on Computers, Systems and Signal Processing, Bangalore, pp.175-179 (1984)
- [2] Yao, A.C.: Protocols for secure computations. In Proc. of the 23rd Annual IEEE Symposium on Foundations of Computer Science, pp.160-164 (1982)
- [3] Yang, Y.G., Wen, Q.Y.: An efficient two-party quantum private comparison protocol with decoy photons and two-photon entanglement. J. Phys. A: Math. Theor. 42(5):055305 (2009)
- [4] Lin, S., Sun, Y., Liu, X.F., Yao, Z.Q.: Quantum private comparison protocol with d -dimensional Bell states. Quantum Inf. Process.12: 559-568 (2013)
- [5] Guo, F.Z., Gao, F., Qin, S.J., Zhang, J., Wen, Q.Y.: Quantum private comparison protocol based on entanglement swapping of *d* -level Bell states. Quantum Inf. Process. 12(8):2793-2802(2013)
- [6] Luo, Q.B., Yang, G.W., She, K., Niu, W.N., Wang, Y.Q.: Multi-party quantum private comparison protocol based on *d* -dimensional entangled states. Quantum Inf. Process. 13: 2343-2352 (2014)
- [7] Ye, C.Q., Ye, T.Y.: Multi-party quantum private comparison of size relation with *d* -level singleparticle states. Quantum Inf. Process. 17(10):252 (2018)
- [8] Song, X., Wen, A., Gou, R.: Multiparty quantum private comparison of size relation based on single-particle states. IEEE Access 99:1-7 (2019)
- [9] Cao, H., Ma, W.P., Lü, L.D., He, Y.F., Liu, G.: Multi-party quantum comparison of size based on *d* -level GHZ states. Quantum Inf. Process. 18: 287 (2019)
- [10] Chen, F.L., Zhang, H., Chen, S.G., Cheng, W.T.: Novel two-party quantum private comparison via quantum walks on circle. Quantum Inf. Process. 20(5):1-19 (2021)

- [11] Tseng, H.Y., Lin, J., Hwang, T.: New quantum private comparison protocol using EPR pairs. Quantum Inf. Process. 11:373-384 (2012)
- [12] Chang, Y.J., Tsai, C.W., Hwang, T.: Multi-user private comparison protocol using GHZ class states. Quantum Inf. Process.12(2):1077-1088 (2013)
- [13] Ji, Z.X., Ye, T.Y.: Quantum private comparison of equal information based on highly entangled six-qubit genuine state. Commun. Theor. Phys. 65(6):711-715 (2016)
- [14] Ye, T.Y.: Multi-party quantum private comparison protocol based on entanglement swapping of Bell entangled states. Commun. Theor. Phys. 66(3):280-290 (2016)
- [15] Ye, T.Y.: Quantum private comparison via cavity QED. Commun. Theor. Phys. 67(2):147-156 (2017)
- [16] Ye, T.Y., Ji, Z.X.: Two-party quantum private comparison with five-qubit entangled states. Int. J. Theor. Phys. 56(5):1517-1529 (2017)
- [17] Ye, T.Y., Ji, Z.X.: Multi-user quantum private comparison with scattered preparation and oneway convergent transmission of quantum states. Sci. China Phys. Mech. Astron. 60(9):090312 (2017)
- [18] Ji, Z.X., Ye, T.Y.: Multi-party quantum private comparison based on the entanglement swapping of *d* -level Cat states and *d* -level Bell states. Quantum Inf. Process. 16(7):177 (2017)
- [19] Ye, C.Q., Ye, T.Y.: Circular multi-party quantum private comparison with *n* -level single-particle states. Int. J. Theor. Phys. 58:1282-1294 (2019)
- [20] Ye, T.Y., Hu, J.L.: Multi-party quantum private comparison based on entanglement swapping of Bell entangled states within *d* -level quantum system. Int. J. Theor. Phys. 60(4): 1471-1480 (2021)
- [21] Boyer, M., Kenigsberg, D., Mor, T.: Quantum key distribution with classical Bob. Phys. Rev. Lett. 99(14):140501 (2007)
- [22] Ye, T.Y., Li, H.K., Hu, J.L.: Semi-quantum key distribution with single photons in both polarization and spatial-mode degrees of freedom. Int. J. Theor. Phys. 59: 2807-2815 (2020)
- [23] Ye, T.Y., Geng, M.J., Xu, T.J., Chen, Y.: Efficient semiquantum key distribution based on single photons in both polarization and spatial-mode degrees of freedom. Quantum Inf. Process. 21:123 (2022)
- [24] Chou, W.H., Hwang, T., Gu, J.: Semi-quantum private comparison protocol under an almostdishonest third party. https://arxiv.org/abs/1607.07961 (2016)
- [25] Ye, T.Y., Ye. C.Q.: Measure-resend semi-quantum private comparison without entanglement. Int. J. Theor. Phys. 57(12):3819-3834 (2018)
- [26] Thapliyal, K., Sharma, R.D., Pathak, A.: Orthogonal-state-based and semi-quantum protocols for quantum private comparison in noisy environment. Int. J. Quantum Inf., 16(5): 1850047 (2018)
- [27] Lang, Y.F.: Semi-quantum private comparison using single photons. Int. J. Theor. Phys. 57: 3048-3055 (2018)
- [28] Lin, P.H., Hwang, T., Tsai, C.W.: Efficient semi-quantum private comparison using single photons. Quantum Inf. Process. 18:207 (2019)
- [29] Jiang, L.Z.: Semi-quantum private comparison based on Bell states. Quantum Inf. Process., 19: 180 (2020)
- [30] Ye, C.Q., Li, J., Chen, X.B. Yuan. T.: Efficient semi-quantum private comparison without using entanglement resource and pre-shared key. Quantum Inf. Process. 20:262 (2021)
- [31] Zhou, N.R., Xu, Q.D., Du, N.S., Gong, L.H.: Semi-quantum private comparison protocol of size relation with *d* -dimensional Bell states. Quantum Inf. Process. 20:124 (2021)

- [32] Geng, M.J., Xu, T.J., Chen, Y., Ye, T.Y.: Semiquantum private comparison of size relationship based *d* -level single-particle states. Sci. Sin. Phys. Mech. Astron. 52(9): 290311 (2022)
- [33] Li, Y.C., Chen, Z.Y., Xu, Q.D., Gong, L.H.: Two semi-quantum private comparison protocols of size relation based on single particles. Int. J. Theor. Phys. 61: 157 (2022)
- [34] Luo, Q.B., Li, X.Y., Yang, G.W., Lin, C.: A mediated semi-quantum protocol for millionaire problem based on high-dimensional Bell states. Quantum Inf. Process. 21:257 (2022)
- [35] Wang, B., Liu, S.Q., Gong, L.H.: Semi-quantum private comparison protocol of size relation with *d* -dimensional GHZ states. Chin. Phys. B 31: 010302 (2022)
- [36] Krawec, W.O.: Mediated semiquantum key distribution. Phys. Rev. A 91(3):032323 (2015)
- [37] Yang, Y.G., Xia, J., Jia, X., Zhang, H.: Comment on quantum private comparison protocols with a semi-honest third party. Quantum Inf. Process. 12:877-885 (2013)
- [38] Qin, H., Dai, Y.: Dynamic quantum secret sharing by using d -dimensional GHZ state. Quantum Inf. Process. 16(3): 64 (2017)
- [39] Gao, F., Qin, S.J., Wen, Q.Y., Zhu, F.C.: A simple participant attack on the Bradler-Dusek protocol. Quantum Inf. Comput.7:329 (2007)
- [40] Cabello, A.: Quantum key distribution in the Holevo limit. Phys. Rev. Lett. 85:5635 (2000)