Translationally Invariant Constraint Optimization Problems

Dorit Aharonov^{*}

Sandy Irani[†]

September 20, 2022

Abstract

We study the complexity of classical constraint satisfaction problems on a 2D grid. Specifically, we consider the computational complexity of function versions of such problems, with the additional restriction that the constraints are *translationally invariant*, namely, the variables are located at the vertices of a 2D grid and the constraint between every pair of adjacent variables is the same in each dimension. The only input to the problem is thus the size of the grid. This problem is equivalent to one of the most interesting problems in classical physics, namely, computing the lowest energy of a classical system of particles on the grid. We provide a tight characterization of the complexity of this problem, and show that it is complete for the class FP^{NEXP} . Gottesman and Irani (FOCS 2009) also studied classical constraint satisfaction problems using this strong notion of translational-invariance; they show that the problem of deciding whether the cost of their result from the decision version to the function version of the problem. Our result can also be viewed as a generalization to the translationally invariant setting, of Krentel's famous result from 1988, showing that the function version of SAT is complete for the class FP^{NP} .

An essential ingredient in the proof is a study of the computational complexity of a gapped variant of the problem. We show that it is NEXP-hard to approximate the cost of the optimal assignment to within an additive error of $\Omega(N^{1/4})$, where the grid size is $N \times N$. To the best of our knowledge, no gapped result is known for CSPs on the grid, even in the non-translationally invariant case. This might be of independent interest. As a byproduct of our results, we also show that a decision version of the optimization problem which asks whether the cost of the optimal assignment is odd or even is also complete for P^{NEXP}.

*dorit.aharonov@gmail.com [†]irani@ics.uci.edu

Contents

1	Intr	roduction	1
	1.1	Problem Definitions, Results and Main Challenges	2
	1.2	Tiling Rules and Layers	4
	1.3	Proofs Overview	5
	1.4	Discussion, Related Work, and Open Problems	9
	1.5	Paper Outline	11
2	Tili	ings and Turing Machines	11
	2.1	Equivalence of Tiling Variants	11
	2.2	Encoding Turing Machine Computations in Tilings	11
3	Lay	ver 1 Construction: Creating the Intervals	13
	3.1	Overview of Layer 1	13
	3.2	The Turing Machine for Layer 1	15
	3.3	Layer 1: Additional Constraints for Fault Tolerance	18
4	Ana	alysis of Layer 1: Proving Fault Tolerance	22
	4.1	The Cost of a Row	23
	4.2	Intervals and their Properties	24
	4.3	Segments and Complete Segments	27
	4.4	Lower Bound on the Number of Segments	29
	4.5	Upper Bound on the Length of a Row	36
	4.6	Clean and Corrupt Intervals	38
	4.7	The Potential Function A	41
		4.7.1 Features of the function A	41
		4.7.2 Bound on the value of A in a tiling \ldots	42
	4.8	Characterizing the intervals in an fault-free tiling	46
5	$\Theta(\Lambda$	$N^{1/4}$)-Gapped Weighted Tiling is NEXP-complete	48
	5.1	Layer 2	48
		5.1.1 Layer 2 Intervals	52
	5.2	Layer 3 for Gapped Weighted Tiling	53
6	Fun	action Weighted Tiling is FP ^{NEXP} -complete	56
	6.1	Containment	56
	6.2	Hardness	56
	6.3	Analysis of Layer 2 for Weighted Tiling Parity	56
	6.4	Layer 3 for Weighted Tiling Parity	58
		6.4.1 Translation from Layer 2 to Layer 3	58
		6.4.2 Horizontal Rules for Layer 3	60
		6.4.3 The Layer 3 Turing Machine	62

8	Ack	nowledgements	74
7	Par	ity Weighted Tiling	73
	6.6	Putting the Layers Together	70
		6.5.1 The Layer 4 Computation	68
	6.5	Layer 4	67
		6.4.4 Analysis of Layer 3	64

1 Introduction

More than half a century ago, Cook and Levin inaugurated the field of NP-completness. The fact that the Constraint Satisfaction Problem (CSP) is NP-complete has been the cornerstone of our understanding and approach to important optimization problems arising in countless applications. The NP completeness of deciding whether a CSP instance is satisfiable, plays an important role also in physics. This is because constraint satisfaction corresponds to a classical local Hamiltonian which expresses the total energy of a system of particles; the energy is the sum of terms, each of which describes the energy interaction between constantsized clusters of particles. Finding whether the lowest energy of such systems is below some threshold or above it, is a special class of CSP, and was famously shown to be NP-complete in many cases by Barahona and others [Bah82, Ist00]. The theory of NP-completeness has a natural generalization in the quantum setting; the Cook-Levin theorem was generalized by Kitaev [KSV02] to show that the following problem is QMAcomplete: Given a local Hamiltonian with quantum energy interactions describing the energy in a quantum many-body system, decide whether the ground energy is above some value or below another; this problem has been intensely studied in recent years [KSV02, GHLS15, OT05, AGIK09].

A natural variant of the NP-complete decision CSP, is the function version of the CSP. In this version, the question is not whether all constraints can be satisfied, but what is the *maximum number* of constraints that can be satisfied by any assignment. One could also consider a weighted variant, as we do here, where the goal is compute the cost of the optimal assignment which minimizes the weighted sum of violated constraints. Computing the cost of the optimal solution is in fact the more natural version of CSP problems in a large number of combinatorial applications (to give just two examples, max-cut and max independent set). Importantly, in classical physics, when considering the local Hamiltonian corresponding to a CSP, the function version of the problem is in fact the problem of finding the lowest possible energy for the Hamiltonian over all possible states – one of the most important notions in physics. In the quantum case, the function version corresponds to providing an estimate of the lowest energy of the system over all possible quantum states, which is one of the main subjects of interest in condensed matter physics.

What is known from the computational complexity angle, about this physically motivated question, the function versions of CSPs? In 1988, Krentel [Kre86] proved that the function problem for constraint satisfaction is FP^{NEXP}-complete. Krentel's proof is significantly more involved technically that that of the Cook-Levin's theorem which characterizes the complexity of the decision variant of CSPs. Furthermore, and in stark contrast to the theory of decision problems and NP-completeness, the function version of CSP seems to have received less attention in the TCS literature.

From the physics point of view, an additional point becomes extremely important. By and large, physicists study local Hamiltonians, be them classical or quantum, in a *translational-invariant* (TI) setting. In this setting the particles are located at the vertices of a geometric lattice and all the terms acting on adjacent pairs of particles along a particular dimension are the same. In particular, the model most relevant to physics is TI in a very strong sense: the dimension of the individual particles and the Hamiltonian term acting on each pair of adjacent particles in a lattice are fixed parameters of the problem. When considering finite systems, the only input is an integer N indicating the size of the system. This set-up corresponds to the fact that in physics, different Hamiltonians represent completely different physical systems. Thus, studying the ground energy (or some other quantity) in the AKLT model is considered to be a completely different problem than studying the same quantity in, say, the Ising model ¹.

For decision problems, Gottesman and Irani [GI13] show hardness results for both quantum and classical TI Hamiltonians. Since the size of the grid can be given by logarithmically many bits, and there is no

¹Some of the recent work on the quantum TI local Hamiltonian problem [BCO17] adopt a weaker notion in which the input also includes the Hamiltonian term that is applied to each pair of particles, allowing the Hamiltonian to be tuned to the size of the system. This model is mainly considered in quantum Hamiltonian complexity, but have not been a topic of study in physics.

other input, one encounters an exponential factor compared to the common CSP problems; thus the results in [GI13] show NEXP and QMA_{EXP} completeness for the classical and quantum variants of the problem, respectively. We note that a tightly related line of works studies TI infinite systems [AI21, WC21, CPGW15] and considers computability and computational complexity of decision problems in that domain, namely in the so called thermodynamic limit. Although the focus here is on finite systems, constructions for finite systems have played an important role for the results in the thermodynamic limit. In particular, all the results in [AI21, WC21, CPGW15] use a finite construction layered on top of a certain type of aperiodic tiling of the infinite grid.

To the best of our knowledge, the computational complexity of function CSPs in the TI setting, has remained open. In this paper we provide a tight characterization of its complexity, and show that the function version of TI CSP on a 2-dimensional grid is complete for FP^{NEXP}. This result thus strengthens Krentel's construction for general CSPs to apply even TI systems for two and higher dimensions. The result is also a generalization of Gottesman-Irani who prove hardness for 2D TI systems for the standard decision problem, where one only needs to determine if the ground energy is below a given threshold. One of the key technical challenges in our result is to effectively create large ($\Theta(N^{\epsilon})$) costs on an $N \times N$ grid using only two constant-sized terms which apply in the horizontal and vertical directions. Thus, as a stepping stone to the more complex result on the function version of TI 2D CSPs, we show a fault-tolerant result which we believe is of interest on its own, namely that it is NEXP-complete to even approximate the ground energy to within an additive $\Theta(N^{1/4})$.

1.1 Problem Definitions, Results and Main Challenges

It is most convenient to present our results using the language of the weighted tiling problem, where we focus here on the two dimensional case². In this tiling problem, one is asked to tile an $N \times N$ 2D grid with a set of 1×1 tiles. The tiles come in different colors and only some pairs of colors can be placed next to each other in either the horizontal or vertical directions. More precisely, a set of tiling rules \mathcal{T} is a triple (T, δ_H, δ_V) , where T is a finite set of tile types $T = \{t_1, \ldots, t_d\}$, and δ_H and δ_V are functions from $T \times T$ to \mathbb{Z} . For $(t, t') \in T \times T$, $\delta_h(t, t')$ is the cost of putting a tile of type t immediately to the left of a tile of type t' and $\delta_v(t, t')$ is the cost of putting a tile of type t immediately above a tile of type t'. Let $\lambda_0(\mathcal{T}(N))$ be the minimum cost of tiling an $N \times N$ grid with tiling rules \mathcal{T} . The goal is to tile the grid with minimal total cost. Note that this problem is directly analogous to a classical Hamiltonian in 2D. We first define a function version of the problem.

Definition 1 \mathcal{T} -FWT (FUNCTION WEIGHTED TILING)

Input: An integer N specified with $\lfloor \log N + 1 \rfloor$ bits

Output: $\lambda_0(\mathcal{T}(N))$

Theorem 1.1 (Main) There exists a set of tiling rules \mathcal{T} such that \mathcal{T} -FWT is FP^{NEXP}-complete.

We note that the fact that the function problem is complete for 2D immediately implies that it is complete for any grid of dimension at least 2 since the 2D construction can be embedded into a higher dimensional grid. The 1D CSP case is poly-time computable using dynamic programming.

The upper bound in Theorem 1.1 is easy: it can be achieved by binary search with access to an oracle for the decision problem. For the lower bound, one encounters a challenge. The reduction must encode in the tiling rules the computation of a polynomial time Turing Machine with access to a NEXP oracle. If an instance given to the oracle is a *yes* instance, the computation of the verifier can be encoded into the tiling rules. However *no* instances cannot be directly verified in this way. Krentel's proof that the function problem

²Our version of tiling is equivalent to the more common Wang tiles [Wan60].

of weighted SAT is FP^{NP} -complete [Kre86] overcomes this challenge; let us recall it and then explain the problem in carrying it over to the TI setting. Krentel uses an accounting scheme [Kre86, Pap94] that applies a cost to every string z representing guesses for the sequence of responses to all the oracle queries made. The accounting scheme needs to ensure that the minimum cost z is equal to the correct sequence of oracle responses, \tilde{z} . yes and no guesses are treated differently, due to the fact that the verifier can check yes instances (and thus incorrect yes guesses can incur a very high cost), but no guesses, cannot be directly verified. In Krentel's scheme, no guesses incur a more modest cost, whether correct or not, and their cost must decrease exponentially. This is because the oracle queries are adaptive; an incorrect oracle response could potentially change all the oracle queries made in the future and so it is important that the penalty for an incorrect guess on the i^{th} query is higher than the cost that could potentially be saved on all future queries. The weights on clauses that implement this accounting scheme are multiplied by a large power of two to ensure that they are the dominant factor in determining the optimal assignment.

The difficulty in applying Krentel's accounting scheme in the TI setting is that the costs must grow with the size of the input. Therefore, it is not possible to apply the costs directly into the tiling rules which are of fixed constant size. A natural attempt to circumvent the problem is to assign the required large penalty by many tiles, each of which would acquire a constant penalty; however, the problem in implementing this approach is that Cook-Levin type reductions from computations to tilings are very brittle, as a single error can potentially derail the entire computation. For example, imagine inserting a row that does not have a Turing Machine head. There will be a single fault where the head disappears from one row to the next, but every row thereafter will contain the unchanging contents of the Turing Machine tape without a head to execute a next step. This imposes a challenge since when enforcing large costs by using many tiles, or constraints, we need to make sure that many of these constraints are indeed violated in order to incur the required large penalty.

We provide a construction which circumvents this issue by exhibiting some *fault tolerance* properties. We thus prove what can be viewed as a gapped version or a hardness of approximation result, which is then a natural stepping stone to implementing the more intricate function required in Krentel's accounting scheme. To this end we define an approximation version of weighted tiling:

Definition 2 (\mathcal{T}, f) -GWT (GAPPED WEIGHTED TILING)

Input: An integer N specified with $\lfloor \log N + 1 \rfloor$ bits. Two integers a and b such that $b - a \ge f(N)$. Output: Determine whether $\lambda_0(\mathcal{T}(N)) \le a$ or $\lambda_0(\mathcal{T}(N)) \ge b$.

Theorem 1.2 There exists a set of tiling rules \mathcal{T} such that (\mathcal{T}, f) -GWT is NEXP-complete for a function $f(n) = \Omega(N^{1/4})$.

This shows that it is NEXP-hard to even approximate the cost of the optimal tiling to within an additive error that is $\Omega(N^{1/4})$. This can be viewed as a gapped version of the results of [GI13]; the proof constructs a reduction mapping the computation into a tiling such that even in the presence of $O(N^{1/4})$ faults, the computation encoded by the tiling is able to proceed and produce approximately correct results.

Theorem 1.2 is of potential interest on its own. It might resemble a PCP type result, but the model we consider differs from the standard PCP setting in two ways: the first is that the underlying graph is a grid, rather than a graph with much higher connectivity, and the second is translational-invariance. It is not possible to obtain a hardness of approximation result with an additive error that is linear in N (as one has in the PCP theorem) on any finite dimensional lattice because such graphs do not have the necessary expansion properties. For example, in 2D, one could divide the grid into $b \times b$ squares for $b = \Theta(\sqrt{\log N})$ and solve each square optimally in polynomial time. The resulting solution would be within an additive $N/\sqrt{\log N}$ of the optimal solution. To the best of our knowledge, no gapped version was proven before for CSP problem set on a constant dimensional grid, even without the TI restriction.

Finally, our results provide tight characterizations of the complexity of the following decision problem;

Definition 3 \mathcal{T} -PWT (PARITY WEIGHTED TILING)

Input: An integer N specified with $|\log N + 1|$ bits

Output: Determine whether $\lambda_0(\mathcal{T}(N))$ is odd or even.

The proof is very similar to the proof of Theorem 1.1. The result on Parity Weighted Tiling illustrates that decision problems related to CSP can be complete for an oracle class just like the function problem. The crucial difference between the threshold decision problem (is the cost of the optimal solution less than t?) which is NEXP-complete and the parity problem which is P^{NEXP}-complete is that the parity problem still seems to require determining the optimal cost. This seems to make the characterization of its complexity as challenging as for the function version of the problem.

Organization of remainder of the introduction: We next proceed to an overview of the proofs. We start with the setup of tiling rules and layers in Subsection 1.2. The proofs of the Theorems are given in subsection 1.3. We end with related work and open questions in Subsection 1.4.

1.2 Tiling Rules and Layers

We assume that there is a special tile denoted by \Box which must be placed around the perimeter of the grid to be tiled. Moreover, no \Box tile can be placed in the interior of the grid. We will return later to enforcing this condition in the context of the different problems. The tiles on the interior will be composed of multiple layers where each layer has its own set of tile types. A tile type for an internal tile in the overall construction is described by a tile type for each of the layers.

For ease of exposition, we allow our tiling rules to also apply to local *squares* of four tiles. This can easily then be translated to two-local constraints on tiles, as in our definition of the tiling problem. This simple transition is described more fully in Section 2.1. For the remainder of the paper our tiling rules include constraints on local squares of four tiles, as well as pairs of horizontal tiles.

If the four tiles in a square are all interior tiles, then each possible pattern of four square tiles within a layer will be designated as legal or illegal. The overall cost of placing four interior tiles in a local square together will be function of whether the square for each layer is legal or illegal. For the Gapped Weighted Tiling, the cost will be just the number of layers for which the square pattern is illegal. For the Function Weighted Tiling and Weighted Tiling Parity, illegal squares at different layers will contribute different amounts to the cost.

In general, a no-cost tiling of each Layer represents a computational process where each row represents the state of a Turing Machine. The computation reverses direction from one layer to the next. The rows of a tiling of an $N \times N$ grid will be numbered r_0 through r_{N-1} from bottom to top. When referring to the rows in a particular layer, we will exclude the border rows and order the rows according to the computation direction. So the first row of Layer 1, which proceeds from bottom to top, is row r_1 and the last row of Layer 1 is r_{N-2} . Layer 2 proceeds from top to bottom, so the first row for Layer 2 is r_{N-2} and the last row is r_1 .

For the most part, the rules governing the tiling apply to the tile types within each individual layer. The different layers only interact at the lower and upper border of the grid. This is how the output of one process (on Layer i) is translated into the input for the next process (on Layer i + 1). For example, a square may be illegal if the two lower tiles are $\Box \Box$, and the two upper tiles violate certain constraints between the Layer i and Layer i + 1 types. Some of the layers will also have additional constraints on which tiles can be next to each other in the horizontal direction. Each type of violated constraint is given a name described below.

Definition 4 [Faults in a Tiling] An occurrence of any of the illegal patterns described in the constructions is called a fault. A tiling with no faults, will correspond to a fault-free computation.

There will be some additional costs (described later) associated with a computation ending in a rejecting state. These are not considered faults because they can happen in correct computations. Figure 1 illustrates the different types of tiling constraints.

- **Illegal Computation Squares:** For each layer, every pattern of four tile types will be designated as a *legal computation square* or an *illegal computation square*. In general, these rules enforce that the tiling within the layer represents a consistent execution of a Turing Machine. We describe in Subsection 2.2 how to translate the rules of a Turing Machine into legal and illegal computation squares.
- **Illegal Pairs:** Some of the layers will have additional constraints on which tiles can be placed next to each other in the horizontal direction. Each ordered pair of tiles types for that layer will be designated as a *legal pair* or an *illegal pair*.
- **Illegal Initialization Squares:** For each layer, there are also some initialization rules that constrain the initial configuration of the Turing Machine. If the layer runs bottom to top, then these rules apply to r_0 , which consists of all \Box tiles, and the first row of the layer. For example, if tile t_1 can not be immediately to the left of t_2 in the first row of Layer *i*, then the square with \Box \Box directly below t_1 t_2 is an *illegal initialization square* for Layer *i*. If the Turing Machine for the layer runs top to bottom, then the square with \Box \Box directly above t_1 t_2 in Layer *i* is illegal.
- **Illegal Translation Squares:** Finally, we add rules that control how the last row of Layer i is translated to the first row of Layer i + 1. If Layer i runs top to bottom, then the rules apply to rows r_0 and r_1 . For example, if tile t in Layer i cannot be translated to t' in Layer i + 1, then any square with a \Box directly below a tile whose Layer i type is t and whose Layer i + 1 type is t' would be illegal. The translation rules can also apply to pairs of adjacent tiles. E.g., it could be illegal to have a square whose bottom two tiles are \Box \Box and whose top two tiles have t_1 t_2 in Layer i and t_3 t_4 in Layer i + 1.



Figure 1: Interior tiles have four layers. Border tiles have one layer and are labeled with the \Box symbol. (a) An illegal computation square for Layer 2. The constraint applies to the four tile types for Layer 2 shown in gray. (b) An illegal translation square from Layer 2 to Layer 3. The constraint applies to two border tiles and the tile types for Layers 2 and 3 for the other two interior tiles. (d) An illegal initialization square for Layer 2. The constraint applies to square for Layer 2. The constraint applies to two border tiles and the tile types for Layers 2 and 3 for the other two interior tiles. (d) An illegal initialization square for Layer 2. The constraint applies to two border tiles and the tile types for the other two interior tiles.

1.3 Proofs Overview

Thoeorem 1.2: Gapped Weighted Tiling Recall that the standard encoding of a Turing Machine into tiling rules is very brittle in that a single fault can derail the entire computation. The most straight forward

way to overcome this is using a construction which embeds many repetitions of the computation, so that many faults would be required to derail a large number of those computations. Multiple computations thus need to be set up and initiated, using a single faulty Turing machine with TI rules. In our construction, this is achieved by a first stage of the computation (implemented in Layer 1, as we describe below), which, roughly, creates intervals in the top row of Layer 1, such that the independent repetitions of the computations will occur in different strips on the grid; the boundaries of the strips are determined by those intervals. The difficulty is how to implement the initial set up using a single Turing machine, in a fault tolerant way. We now describe the details.

The tiling rules for the first two layers, as well as the reduction mapping x to N are independent of the language $L \in \text{NEXP}$, the language we are reducing from. Let V denote the exponential time verifier for L. Subsection 2.2 describes the details of how a Turing Machine computation is encoded in a set of tiling rules. In general tiles will be either *tape* tiles which encode a single symbol from the Turing Machine's tape alphabet or *head* tiles which encode both the state of the Turing Machine as well as the current tape symbol to which the head is pointing.

The Turing Machine computation represented in Layer 1 starts with two non-blank symbols and proceeds to write a sequence of intervals on the tape, where an interval is a sequence of B symbols bracketed on either side by a *delimiter* tile from the set $\{X, \overline{X}, \triangleleft, \triangleright\}$. The Turing Machine just repeatedly executes a single loop which we refer to as the *Outer Loop*. In one iteration of the Outer Loop, an additional B symbol is inserted into every interval and a new interval with no B's in the middle is added to the right end of the non-blank symbols. In an fault-free execution of the Turing Machine, after m iterations of the loop, there are m + 1 intervals. The number of symbols in each interval (including the delimiter tiles on either end) is $m + 2, m + 1, m, \dots, 2$. For m = 4, the row should look like:



When the top row of Layer 1 is translated to Layer 2, the head tile for the Layer 1 Turing Machine is translated to a tape tile (so the state information is lost) and a head tile is inserted on the left end of every interval. For example, an interval $X \ B \ B \ B \ \cdots \ B \ X$ at the end of Layer 1 is translated to $X \ (q_s/S) \ B \ B \ \cdots \ B \ T \ X$ in the first row of Layer 2. In Layers 2 and 3 the sizes and locations of the intervals do not change within a row unless the interval contains an illegal square. Thus, a single interval over all the rows of Layer 2 forms a vertical strip of tiles, and a separate, independent computation takes place within each strip. See Figure 7 for an example. Once the intervals are created on Layer 1, each computation on Layers 2 and 3 is fault-free unless the strip contains an illegal square. Thus, the number of illegal squares is at least the number of strips that fail to complete their computation correctly.

In Layer 2, the computation is just a binary counter Turing Machine that continually increments a binary counter. All the strips that do not contain an illegal square will have the same string x represented in the final row of Layer 2. The string x then serves as the input to the computation in Layer 3. The binary counter Turing Machine in Layer 2 runs for exactly N - 3 steps. The reduction is the function that maps x to N, where the string x is written on the tape of a binary counting Turing Machine after N - 3 steps. Lemma 5.3 gives an exact formula mapping x to N and shows that the value of the number represented by the string x is $\Theta(N)$, the dimension of the grid. The idea of using a binary counting Turing Machine to translate the size of the grid to a binary input for a computation was used previously in [GI13]. Although since the construction in [GI13] had a gap of 1, only a single execution of the verifier was needed. Since we are trying to produce a gap of f(N), we need at least f(N) separate computations each of which simulates the verifier on input x.

Each interval $X(q_s/S) \times B \cdots B T X$ is translated unchanged to Layer 3. The computation in each strip in Layer 3 simulates the verifier on input x using a witness that is guessed in the tiling. There is a final

cost for any rejecting computation. If $x \in L$, it will be possible to tile each strip at 0 cost. If $x \notin L$, every strip will contain an illegal square or will incur a cost for the correct rejecting computation. Thus, the gap is essentially created by these parallel computations, each of which contributes a constant cost if $x \notin L$.

Since the sizes of the intervals go down to 0, some of the intervals will be too narrow to complete the computation in either Layers 2 or 3. If the head ever hits the right end of its interval, it transitions to an infinite loop, causing no additional cost. A standard padding argument (Claim 5.1) guarantees that an interval need only be $\Theta(N^{1/4})$ wide to complete the computations in Layers 2 and 3. The analysis of Layer 1 then needs to guarantee that despite the faults, there will be sufficiently many sufficiently wide intervals.

The main challenge in the proof is in making the computation in Layer 1 fault-tolerant, meaning that each illegal pair or square cannot derail the computation too much. The horizontal rules in Layer 1 are critical for enforcing that this cannot happen. We show that a row in the tiling that has no illegal pairs corresponds to a sensible configuration of the Turing Machine. In particular such a row has exactly one head tile that lies in between the \triangleleft and \triangleright tiles. Note that faults can still alter the computation in potentially strange ways. Nonetheless, we also show that starting from a row with no illegal pairs, the Layer 1 Turing Machine will be able to make progress, and after a sequence of fault-free steps (corresponding to a sequence of rows containing no illegal squares), the computation will perform a complete iteration of the loop. Since the number of illegal pairs and squares is bounded by $O(N^{1/4})$, there are enough complete iterations of the loop to ensure that the last row of Layer 1 has enough intervals that are wide enough to complete the computations in Layers 2, 3.

By far the most technically involved part of the paper is the analysis of Layer 1 described in Section 4. All of the results use the final Lemma 4.23, which gives a tight characterization of the difference between the final row in Layer 1 of a fault-free tiling and the final row of a tiling with faults. In fact, the result on Gapped Weighted Tiling could be established with looser bounds, but we provide the analysis once in Section 4 in a form that can be used for all the results in the paper. Section 1.3 describes more fully how this tight characterization is accomplished. A more in-depth overview is then given in the beginning of Section 4.

Theorem 1.1: Weighted Tiling Function The hardness reduction for Function Weighted Tiling reduces from an oracle class. The function f is computed by a polynomial time Turing Machine M with access to an oracle for language $L' \in \text{NEXP}$. Let V denote the exponential time verifier for L'. Using a standard padding argument (see for example Lemma 2.30 from [AI21]) we can assume that for a constant c of our choice, for every |x| = n, there is a $\overline{n} \leq cn$, such that the size of f(x) is at most \overline{n} , and M makes at most \overline{n} oracle calls to L'. Let z denote an \overline{n} -bit string denoting the responses to the oracle queries made on input x. With x and z fixed, the set of inputs to the oracle $(o_1, \ldots, o_{\overline{n}})$ is also determined. $V(o_j)$ is an indicator function denoting whether o_j is in L'. Note that since L' is in NEXP, if $V(o_j) = 1$, there exists a witness that will cause the verifier to accept and if $V(o_j) = 0$, V will always reject regardless of the witness. Define:

$$\mathcal{C}(x,z) = \sum_{j=1}^{\overline{n}} \left[(1-z_j) \cdot 2^{\overline{n}-j} + z_j \cdot (1-V(o_j)) \cdot 2^{\overline{n}} \right]$$

Let f(x, z) be the output of Turing Machine M on input x with oracle responses z. Note that since $|f(x, z)| \leq \overline{n}$, $f(x, z) \leq 2^{\overline{n}}$. The construction will ensure that the minimum cost tiling for a particular x and z will be $2^{\overline{n}+5}\mathcal{C}(x,z)+2^3 \cdot f(x,z)$. Note that $\mathcal{C}(x,z)$ represented in the \overline{n} high-order bits of the cost has the necessary structure where the costs for a *no* oracle response decrease exponentially in j, the index of the oracle query. The cost for a *yes* guess will be 0 if the input to the oracle o_j is in fact in L' (i.e., $V(o_j) = 1$) and will be a very large cost of $2^{2\overline{n}+5}$ if o_j is not in L'. This function will guarantee that the overall cost is minimized when z is the correct string of oracle responses. In addition, the low order bits encode the output of the function f(x, z). So if the minimum cost tiling can be computed, this will correspond to f(x), which is $f(x, \overline{z})$, where \overline{z} is the string of correct oracle responses. The factor of 8 ensures that even if the minimum

cost is off by ± 3 , the value of f(x) can still be recovered.

So far what we have described just implementing the original accounting scheme devised by Krentel. The challenge is to implement this cost function in 2D with TI terms. Note that since the tiling rules are fixed parameters of the problem, it is not possible to encode the cost function directly into the penalty terms. As with the Gapped Weighted Tiling problem the function is collectively computed by a set of parallel processes within each strip created by the intervals from Layer 1. However, instead of a threshold function which is either +f(N) or 0, the parallel processes must collectively compute the more intricate function described above, which requires that the individual processes have some additional information.

We will describe first what happens in a fault-free computation (with no illegal pairs or computation squares) and then describe how fault-tolerance is enforced and proven. The construction for Layers 1 and 2 are exactly the same as for the Gapped Weighted Tiling problem. Layer 1 creates a set of intervals. We definite the function $\mu(N)$ to denote the number of intervals on the tape if the Turing Machine for Layer 1 executes N-3 steps. If after N-3 steps, the computation just happens to finish at the end of an execution of the Outer Loop then the intervals have sizes (from left to right) $\mu(N) + 1, \mu(N), \ldots, 2$. If the computation finishes in the middle of an execution of the Outer Loop, the actual sequence of interval sizes will be close to $\mu(N) + 1, \mu(N), \ldots, 2$. The largest interval could have size $\mu(N) + 2$ and there may be a couple missing values in the range where the current interval is being increased. Lemma 4.24 describes the possible deviations in detail. $\mu(N)$ is $\Theta(N^{1/4})$ and we show using a standard padding argument that for the constant c of our choice, all of the computations require at most $c\mu(N)$ space. This allows us to establish that at least half of the intervals will be large enough to complete the required computations.

As in the previous construction, Layer 2 then executes a binary counting Turing Machine which results in the string x written to the left of each interval which is large enough to complete the computation. Note that Layer 1 is a *global* Turing Machine which executes a single process across the entire grid, while Layer 2 represents *local* computations within each strip. When x is translated from Layer 2 to Layer 3 it is augmented with a guess string z for the oracle queries. x. However, there is no guarantee that the guess for each interval is the same. Note that z can be arbitrary but it must be consistently the same for each interval. Layer 3 then executes a global Turing Machine which imposes a high penalty if the z strings in each strip are not all the same. This penalty is higher than the cost function for any z, so the lowest cost tiling will correspond to a configuration in which each strip has the same x and z.

Finally, in Layer 4, there is a local computation in each interval, each of which makes a +1 or 0 contribution towards the overall cost. The computation within each interval requires a unique tag in order to determine which term of the cost it will contribute to. The tag comes from the size of the interval. The computation begins with counting the number of locations in the interval. This can be accomplished by having the head shuttle back and forth between the two ends of the interval implementing both a unary and binary counter until the unary counter extends across the entire interval. The head returns to the left end of the interval and begins the next phase of the computation. Since the size of an interval is at most $O(N^{1/4})$ this phase of the computation will take at most $O(N^{1/2})$ steps.

Now each computation has the same pair (x, z) and a its own integer r indicating the size of the interval. From x, the values of N and $\mu(N)$ can be determined. Lemma 4.24 shows that in a fault-free computation, the sizes of the intervals will decrease from left to right. Moreover, all interval sizes are in the set $\{\mu(N) + 2, \mu(N) + 1, \ldots, 2\}$ with at most one missing value from that set and at most two duplicates. Thus, the value $\mu(N) - r + 2$, will be an almost unique identifier for each interval, starting with 0 or 1 on the left and increasing to the right. Using this tag, each interval determines which portion of the cost it will contribute to. The number of intervals assigned to compute a particular term in the cost will depend on the value of the term since each interval can contribute at most 1 to the overall cost. If an interval is assigned to check a *yes* guess $(z_k = 1)$ the computation uses x and z to determine the k^{th} input to the oracle o_k , guesses a witness and simulates V on input o_k with the guessed witness. There is a cost of +1 if V rejects and 0 if V accepts. If o_k is in fact in L', there is a witness which will allow for a zero cost tiling withing that interval. If $o_k \notin L$, then every witness will lead to a +1 cost. Thus, the optimal set of witnesses will result in the minimum value for $2^{\overline{n}+5}\mathcal{C}(x,z)$. In addition, exactly $2^3f(x,z)$ of the intervals will just transition to the rejecting state, incurring a cost of +1. The total cost due to those intervals is $2^3f(x,z)$. For the remaining intervals, no cost is incurred.

The cost of a computation fault (illegal pair or square) is a constant that is larger than the cost of ending in a rejecting computation. Therefore, for each independent computation (in Layers 2 and 4) the optimal tiling will correspond to a correct computation which may or may not incur a cost for ending in a rejecting state. Technically, the most challenging part of the proof is to show that the process on Layer 1 which creates the intervals is fault-tolerant. The proof for Function Weighted Tiling requires stronger conditions than for Gapped Weighted Tiling since we not only have to show that there are a large number of large intervals at the end of Layer 1 but we need to establish that the sequence of interval sizes is close to what one would have in a fault-free computation. To this end, we use a potential function A which captures how much a sequence of interval sizes (s_1, s_2, \ldots, s_m) deviates from the expected sequence $(m + 1, m, m - 1, \ldots, 2)$. The main part of the proof is to show that each illegal square or pair can cause the value of A to increase by at most a constant amount. At the end of Layer 1, the ideal sequence of interval sizes is ($\mu(N) + 1, \mu(N), \ldots, 2$). Every interval size that is missing from the actual sequence of interval sizes has caused A to increase by at least a fixed amount which in turn corresponds to faults incurred in the computation. Thus, we show that it is more cost-effective to complete the computation correctly (and not incur the higher cost of a fault) and incur the smaller potential cost of a rejecting computation.

The most important measure of progress of the tiling/computation in Layer 1 is the number of times the encoded Turing Machine completes an iteration of the Outer Loop in which the size of every interval increases by 1 and a new interval of size 2 is added. Faults can potentially cause an iteration of the Outer Loop to take longer as they may force the head to shuttle back and forth more times which in turn could result in fewer iterations. Even in a fault-free computation, the number of steps per iteration increases with each iteration because there are more intervals. One of the main lemmas in the analysis is Lemma 4.10 which lower bounds the number of times the loop is completed in relation to that number in a fault-free computation. The proof is a delicate inductive argument which uses the fact that the increase in the running time of a loop is not accelerated too much with each additional fault.

Proof Overview for Parity Weighted Tiling The proof for parity weighted tiling is very similar to the function problem. Suppose that a language $L \in \mathbb{P}^{NEXP}$ is computed by a Turing Machine M with access to an oracle for $L' \in NEXP$. Let M(x, z) be the indicator function that is 0 if M(x, z) accepts and 1 if M(x, z) rejects. The overall cost computed by the collective computations is: $4\mathcal{C}(x, z) + M(x, z)$. The left-most interval computes M(x, z) and results in a +1 cost in the case that M rejects. The remaining intervals which collectively compute Krentel's cost function all impose costs of +2 or 0. Thus the expression $4\mathcal{C}(x, z) + M(x, z)$ will guarantee that the minimum $\mathcal{C}(c, z)$ corresponds to the correct guess \overline{z} . Furthermore, the rightmost bit will be M(x, z) which will cause the minimum cost to be odd or even, depending on whether M accepts.

1.4 Discussion, Related Work, and Open Problems

Despite the fact that the function version of classical local-Hamiltonians describes the task of the computational (classical) physicist much more naturally than decision problems, complexity of function problems was hardly studied even in the non-TI setting, in the literature of classical theory of computer science.

Recently, related results were discovered in the domain of quantum computational complexity. In particular, in [AI21], Aharonov and Irani use a construction for the function version of (finite) quantum local Hamiltonian as a component for a hardness result for the infinite 2D grid. More specifically, they prove that the problem of estimating the ground energy of a local Hamiltonian on a finite 2D grid, is hard for FP^{NP}. Importantly,

their results do not imply the hardness result presented in this paper, and it seems impossible to extend their proof to deduce the classical hardness result of Theorem 1.1. Like [AI21] we implement Krentel's cost function using a fixed Hamiltonian term, but since their construction is quantum (as opposed to the classical construction in this paper), they are able to prove the result using a completely different set of tools which do not carry over to the classical case. In quantum constructions, the lowest energy is an eigenvalue of a general Hermitian matrix and the matrix can be constructed to fine tune the ground energy to an inverse polynomial precision. In classical constructions, the total energy will be a sum over terms where each term is chosen from a constant-sized set of values determined by the finite horizontal and vertical tiling rules. This allows far less control in the classical setting over the precision of the minimum cost tiling.

Incidentally, note that the results for the quantum case proven in [AI21] are not tight, which follows from the fact that they use a quantum construction to obtain hardness for FP^{NEXP}, a classical complexity class. It seems challenging to make the characterization tight in the quantum case. In contrast to the class NP, the class QMA is a class of promise-problems and in simulating a P^{QMA} machine, there is no guarantee that the queries sent to the QMA oracle will be valid queries. The cost/energy applied for a particular query will depend on the probability that a QMA verifier accepts on the provided input. If the input is invalid, then the probability of acceptance can be arbitrary. Thus, Krentel's cost function will potentially be an uncontrolled quantity. Typically in a reduction where we want to embed the output of a function into the value of the minimum energy, the low order bits of the energy are used to encode the output of the function. It's not clear how to do this without being able to control the binary representation of the minimum energy. Note that by embedding a classical computation in the Hamiltonian, the issue of invalid queries is circumvented.

Both [AI21] and [WC21] study the complexity of computing the ground energy density of infinite TI Hamiltonians to within a desired precision making use of the technique introduced by Cubitt, Prerez-Garcia, and Wolf which embeds *finite* Hamiltonian constructions of exponentially increasing sizes, into the 2D infinite lattice, using Robinson tiles. Robinson tiling rules [Rob71] force an aperiodic structure on the tiling of the infinite plane, with squares of exponentially increasing size. The quantum construction of [AI21] layers a TI 1D Hamiltonian on top of one of the sides of all the squares. The classical construction of [WC21] layers a classical finite construction on each square. Neither work obtains tight results due to the same issue with invalid queries, although the two papers compromise in completely different ways. The primary technical innovation introduced in [WC21] is to devise a more robust version of Robinson tiles which ensures that the lowest energy state corresponds to a correct Robinson tiling, even though the cost of the classical finite construction layered on top may introduce a penalty. If it were possible to obtain an even more robust version of Robinson tiles, one potentially could layer the finite construction from the current paper on top the more robust constructions in the hopes of showing that computing the ground energy density of a classical TI Hamiltonian in the thermodynamic limit is complete for EXP^{NEXP} under Karp reductions.

The results in this paper are also related to the work of Ambainis [Amb14] which characterizes the complexity of measuring local observables of ground states of local Hamiltonians (APX-SIM), showing that the problem is complete for $P^{\text{QMA}[\log n]}$. $P^{\text{QMA}[\log n]}$ contains those problems that can be solved by a polynomial time classical Turing Machine with access to $O(\log n)$ queries to a QMA oracle. This type of question (determining a property of the ground state) is similar to our classical result about determining whether the cost of the optimal tiling is odd or even. The results on APX-SIM [Amb14, GY19, GPY19] are not hindered by the issue of invalid queries because the quantity being measured is not the actual energy itself. Note that the important point here is the property that distinguishes the state to be measured (minimum energy) is different than the local observable applied to the measured state. By contrast, computing the energy of the lowest energy state appears to be more difficult. The issue of invalid queries appears to be an obstacle, even when the Hamiltonian terms are position-dependent as in the constructions of [GY19, GPY19], as well as in the TI constructions in [AI21, WBG20]. Finally, it was mentioned earlier that the approximation problem considered here differs from the standard PCP setting in that the underlying graph is a grid and the terms are TI. It remains an open question as to whether there is a family of TI instances of constraint satisfaction on general graphs for which it is hard to estimate the optimal solution to within an additive $\Theta(N)$.

1.5 Paper Outline

Section 2.2 describes how the rules of a Turing Machine are translated into tiling rules. For all the results presented here, Layer 1 encodes the execution of a Turing Machine that creates intervals within the grid that marks off where parallel computations will take place in subsequent layers. Since the construction and analysis is common to all the results, we present that first. Section 3 gives the construction and Section 4 proves the main lemmas that are needed for the analysis of each construction. Section 5.2 then describes the rest of the construction and proof for Gapped Weighted Tiling which only requires two additional layers. Section 7 describes the rest of the construction and analysis for Parity Weighted Tiling. Finally, Section 6 describes the modifications to the construction for Parity Weighted Tiling that is requires for Function Weighted Tiling.

2 Tilings and Turing Machines

2.1 Equivalence of Tiling Variants

We defined the translationally-invariant tiling problem to use two constraints: one is applied to each pair of adjacent tiles in the vertical direction and the other is applied to each pair of adjacent tiles in the horizontal direction. For convenience, the local constraints described throughout the paper apply to local configurations in a square of four tiles as well as to pairs of tiles in the horizontal direction.

We sketch here how one can transform a set of a set of tiling rules that applies to squares into an equivalent one that applies to only pairs. For each pair of tiles t_1 and t_2 in the original tiling rules, create a new combined tile type $[t_1, t_2]$. A large (but constant) constraint can be added to ensure that a tiling with the new tile types is *consistent*, meaning that a tile of the form [*, t] must go to the left of a tile of the form [t, *]. More specifically, an inconsistent tiling can be transformed into a consistent tiling in a way that strictly reduces the cost.

There is now a one-to-one correspondence between consistent tilings with the new tile types and tilings with the original tile types. Moreover, a vertically aligned pair with tile $[t_a, t_b]$ on top of $[t_c, t_d]$ can enforce the same constraint as a square in the original tiling rules with tiles t_a and t_b in the top row of the square and with t_c and t_d in the bottom row of the square. Constraints on the new tiles can be fixed so that the cost of corresponding tilings are the same.

2.2 Encoding Turing Machine Computations in Tilings

In this subsection we describe how the rules of a Turing Machine are translated into legal and illegal *computation* squares so that a tiling that contains no illegal computation squares corresponds to a correct execution of the Turing Machine. Note that the illegal and legal computation squares described in this subsection would apply to one particular Layer of the tiling. We assume here that the Turning Machine proceeds from the bottom to the top. If the direction were reversed, the the top and bottom rows of the legal and illegal computation squares would be swapped.

Consider a Turing Machine M with tape alphabet Γ and set of states Q. The set of tiles types for the layer corresponds to $\Gamma \cup (\Gamma \times Q)$. A tile is called a *tape* tile if it is labeled with a symbol from the tape alphabet. A tile is called a *head* tile if it is labeled with a state and tape alphabet symbol, e.g. (q/c).

Each configuration of the Turing Machine is represented by a row of tiles. In general, we will have Turing Machines whose non-blank tape symbols are bracketed on the left by the symbol \triangleleft and on the right by symbol \triangleright . The tape contents to the right of \triangleright is an infinite sequence of blank (#) symbols. The corresponding row of tiles will have # tiles extending to the \Box tile at the right side of the grid. For example, consider a Turing Machine with state q and whose tape symbols include B, X, \triangleleft , and \triangleright . The Turing Machine configuration

 $\square \ \lhd \ B \ B \ B \ B \ X \ B \ B \ B \ X \ B \ X \ >$

will be represented by the row

\bigtriangledown	В	В	В	В	X	В	В	B	Х	q/B	Х	\triangleright	#	#	 #	

For ease of notation, we will represent this row of tiles by the string:

```
\Box \triangleleft B B B B X B B B X (q/B) X \rhd \# \cdots \# \Box
```

Suppose the Turing Machine has rule $\delta(q_0, a) \to (q_1, b, L)$ then the following four squares would be legal for any tape symbols x and y:

q_1/x	b	b	у	у	q_1/x		q_1/x
x	q_0/a	q_0/a	у	у	х		x

Thus if two adjacent rows do not contain any illegal computation squares, then the next row up reflects the head location and tape contents after the rule has been applied.

Similarly, if the Turing Machine has rule $\delta(q_0, a) \to (q_1, b, R)$ then the following four squares would be legal for any tape symbols x and y:

b	q_1/x	у	b		b	q_1/x	у
q_0/a	х	у	q_0/a		q_0/a	x	у

There can also be Turing Machine rules in which the head does not change location: $\delta(q_0, a) \to (q_1, b, -)$. Then the following three squares would be legal for any tape symbol x:

q_1/b	х	x	q_1/b		q_1/b
q_0/a	х	x	$ q_0/a $]	q_0/a

In the absence of a head tile, two vertically neighboring tiles must be the same tile type. Thus for any two tape symbols x and y the following square is legal:

All squares that have four interior tiles and whose tile types for the layer are not one of the legal squares described above is an illegal computation square.

In general, we will design TMs where each state q is reached from a unique direction. In other words, for each state q, the TM can not have rules corresponding to more the one of the following three forms:

- 1. $\delta(*,*) = (q,*,R)$
- 2. $\delta(*,*) = (q,*,L)$

3. $\delta(*,*) = (q,*,-)$

Any TM that doesn't have this property can be transformed into a TM that does have this property by adding some additional states and rules. This restriction ensures that for each state q, and any tape symbols x, y, and z, only one of the squares below can be legal:

у	q/x	q/x	у	q/x	у
у	х	х	у	q'/z	у

Thus the only legal way for a head tile to appear in a row, is for there to be another head tile just below it or to the immediate left or right in the preceding row.

Definition 5 The number of illegal pairs and squares in Layer *i*, denoted by F_i is the number of illegal pairs, illegal computation squares, and illegal initialization squares in Layer *i*, plus, if i > 1, the number of illegal translation squares from Layer i - 1 to Layer *i*. We will refer to F_i as the **cost** of Layer *i*.

The cost of the whole tiling will be a linear combination of the F_i 's.

A square is called a a *head* square if one of the two lower tiles is a head tile and one of the two upper tiles is a head tile. Note that a head square can be illegal or legal. The next two facts about the encoding of Turing Machines in tiling rules will be useful in analyzing Layer 1 of the constructions. Based on the method described above for translating Turing Machine rules into legal and illegal computation squares, the following two sets of facts can be easily verified.

Fact 2.1 Consider a tiling where a tile t' is directly above tile t. If any of the following conditions hold, then both squares containing t' and t are illegal computation squares:

- 1. t' and t are both tape tiles and $t \neq t'$
- 2. t' is a head tile (q/c'), t is a tape tile c and $c \neq c'$.
- 3. t' is a tape tile c', t is a head tile (q,c) and $\delta(q,c) = (*,c',L/R)$ is not a TM rule.
- 4. t' is a head tile (q'/c'), t is a head tile (q/c) and $\delta(q,c) = (q',c',-)$ is not a TM rule.

Fact 2.2 Consider a tiling where a tile t' is directly above tile t. If either of the following two conditions hold, then the vertically aligned pair is in a legal head square or an illegal computation square

- 1. t' is a head tile (q/c'), t is a tape tile c and c = c'.
- 2. t' is a tape tile c', t is a head tile (q/c) and $\delta(q,c) = (*,c',*)$ is a valid TM rule.
- 3. t' is a head tile (q'/c'), t is a head tile (q/c) and $\delta(q,c) = (q',c',-)$ is a TM rule.

3 Layer 1 Construction: Creating the Intervals

3.1 Overview of Layer 1

The role of Layer 1 is to create what we call "intervals" whose beginning and ends will mark the regions where separate computations which we want to repeat in the next layer, can occur.

We will refer to an *interval* as a sequence of characters that start with a heavy tile from the set $\{X, X, \triangleright, \triangleleft\}$ and includes all the B's to the right, up to and including the next heavy tile so that neighboring intervals overlap in one location. The *size* of the interval is the number of characters, including the heavy on either end, so neighboring intervals overlap by one symbol. In general intervals will begin and end with X or \overline{X} , except that the left-most interval begins with a \triangleleft on the left and the right-most interval ends with \triangleright on the right side.

The idea is to design a computation which ends up at the top row of layer 1, such that this row can be viewed as a concatenation of intervals whose sizes begin with the largest one and decreases by one from one interval to the next.

This is done by running a TM with an Outer Loop containing and Inner Loop, as follows. In each iteration of the outer loop, the size of each interval increases by 1 and there is a new interval of size 2 added to the right end of the tape. This is done by iterating over an Inner Loop, which increases the size of just a single interval (and pushes all intervals to its right one site further).

To describe this we will define the Turing Machine that is simulated in Layer 1. The transition rules of this TM define a set of legal squares for Layer 1 as described in Section 2.2.

The tape symbols are: $\{X, B, \overline{X}, \triangleleft, \triangleright, \#\}$. B is the blank symbol that is written by the Turing Machine. The unwritten tape symbols are all set to #. The states can be divided into groups:

- 1. q_{OS} . OS stands for *Outer Start*. This computation is in q_{OS} during a set up phase of the outer loop.
- 2. The inner loop states are: $q_{IS}, q_{left}, q_{wX}, q_{wB}, q_{w\overline{X}}, q_{w\triangleright}$.
 - (a) q_{IS} is the starting state for the inner loop.
 - (b) q_{left} just moves left until \overline{X} is reached.
 - (c) q_{wt} stands for *write* character t. This is how the contents are moved to the right. The state remembers the tape symbol t that it just wrote over.
- 3. q_{e1} and q_{e2} are special states for the very end of an iteration of the outer loop.

Figure 2 shows the steps of the Outer Loop in pseudo-code.

$(1) O^{\dagger}$	UTERLOOP:
(2)	Set Up Phase
(3)	Sweep left in state q_{OS} until \triangleleft is reached
(4)	Transition to q_{IS} and move right
(5)	Start of Inner Loop
(6)	Move right in state q_{IS} until an X is reached
(7)	If \triangleright is reached before X, go to (14)
(8)	Replace X with B and move right, transition to $q_{w\overline{X}}$
(9)	Insert an \overline{X} :
(10)	Sweep right, moving every symbol to the right $(q_{wt} \text{ for } t \in \{B, X, \triangleright\})$
(11)	When state $q_{w \triangleright}$ is reached, replace $\#$ with \triangleright , transition to q_{left}
(12)	Move left in state q_{left} until \overline{X} is reached
(13)	Replace \overline{X} with X, transition to q_{IS} and move right. Go to (5).
(14)	Wind Down Phase
(15)	Replace \triangleright with B, X, \triangleright (states q_{e1} and q_{e2}).
(16)	Transition to q_{OS} . Go to (1).

Figure 2: Pseudo-code for an integration of the Outer Loop.

We now describe the exact transition rules of the TM which is simulated in layer 1.

3.2 The Turing Machine for Layer 1

The Outer Loop

The start of an Outer Loop:

The start of the next Outer Loop:

														q_{OS}	
														\downarrow	
\triangleleft	В	В	В	В	Х	В	В	В	Х	В	В	Х	В	Х	\triangleright

Set Up Phase

Each iteration of the outer loop starts with a set-up phase in which the head moves to the far left:

This is achieved by the rule $\delta(q_{OS}, t) = (q_{OS}, t, L)$, for any tape symbol $t \neq \triangleleft$.

This continues until the head reaches \triangleleft . Then the state transitions to q_{IS} and moves to the right.

Rules: $\delta(q_{OS}, \triangleleft) = (q_{IS}, \triangleleft, R)$. This configuration will be the start of an iteration of the inner loop. **The Inner Loop**

The state q_{IS} will move right past any B's until it reaches a X:

 $\begin{array}{c} q_{IS} \\ \downarrow \\ \lhd & \mathbf{B} \quad \mathbf{B} \quad \mathbf{B} \quad \mathbf{X} \quad \mathbf{B} \quad \mathbf{B} \quad \mathbf{X} \quad \mathbf{B} \quad \mathbf{X} \quad \mathbf{D} \\ \end{array}$

Rules: $\delta(q_{IS}, B) = (q_{IS}, B, R).$

Then it replaces the X with B and inserts a \overline{X} to the right of the B. This has the effect of increasing the size of the current interval. The \overline{X} symbol tells the head where to return to in the next inner loop iteration.

 $q_{w\overline{X}}$ \downarrow Х В Х ⊳ В В В B B B \triangleleft q_{wB} \downarrow В \overline{X} В B B Х В \triangleleft В X Þ $\text{Rules: } \delta(q_{IS}, X) = (q_{w\overline{X}}, B, R), \text{ and } \delta(q_{w\overline{X}}, t) = (q_{wt}, \overline{X}, R), \text{ for } t \in \{B, X, \rhd\}.$

The head moves to the right, moving each character over by one space. The state remembers, the last symbol that was overwritten. This continues until the head reaches \triangleright .

Rules: $\delta(q_{wb}, t) = (q_{wt}, b, R)$, for $b \in \{B, X\}$ and $t \in \{B, X, \triangleright\}$. The state $q_{w\triangleright}$ writes a \triangleright , transitions to q_{left} and moves left:

Rules: $\delta(q_{w\triangleright}, t) = (q_{left}, \triangleright, L)$. Then the head then moves all the way to the left until it reaches \overline{X} :

Rules: $\delta(q_{left}, b) = (q_{left}, b, L)$, for $b \in \{X, B\}$. When \overline{X} is reached, the \overline{X} is replaced with a X, the state transitions to q_{IS} and a new inner loop begins.

Rules: $\delta(q_{left}, \overline{X}) = (q_{IS}, X, R).$

At the beginning of each iteration of the inner loop, the location of the head has moved over by one interval. The intervals to the left of the head have all been increased. The current interval and the ones to the right have yet to be increased. Working through our example, after the next iteration of the inner loop we have:

Then after the next inner loop:

Wind Down Phase

In the last iteration of the inner loop, there is no X in between q_{IS} and \triangleright . This situation is detected when the TM is in the state q_{IS} and it encounters a \triangleright instead of an X. In this case, the last interval is increased and a new X is added. So \triangleright is replaced by $B X \triangleright$.

\triangleleft	В	В	В	В	х	В	В	В	х	В	В	х	$q_{IS} \downarrow \ \triangleright$		
\bigtriangledown	В	В	В	В	Х	В	В	В	Х	В	В	Х	В	$\begin{array}{c} q_{e1} \\ \downarrow \\ \# \end{array}$	
\bigtriangledown	В	В	В	В	X	В	В	В	X	В	В	X	В	Х	$\begin{array}{c} q_{e2} \\ \downarrow \\ \# \end{array}$
\triangleleft	В	В	В	В	Х	В	В	В	Х	В	В	Х	В	$\begin{array}{c} q_{OS} \\ \downarrow \\ \mathrm{X} \end{array}$	\triangleright

Rules: $\delta(q_{IS}, \rhd) = (q_{e1}, B, R), \ \delta(q_{e1}, \#) = (q_{e2}, X, R), \ \delta(q_{e2}, \#) = (q_{OS}, \rhd, L).$ The following notion will play an important role in the analysis.

Definition 6 End configuration The configuration $\triangleleft \{B, X, \overline{X}\}^*$ $(q_{e2}/\#)$ is called an end configuration

An end configuration is the final configuration in an iteration of the Outer Loop. Even if there have been some faults in previous steps of the computation, if the Turing Machine is in an end configuration and computes future steps without faults, the Turing Machine will begin a new iteration of the Outer Loop.

Figure 3 summarizes the Turing Machine transition rules. Note that not every state/input symbol combination will occur in a fault-free computation. However, we are defining the transition function on a wider set of inputs so that the Turing Machine can recover from errors due to faults that occurred earlier in the computation.

	\triangleleft	X	B	\overline{X}	\triangleright	#
q_{OS}	(q_{IS}, \lhd, R)	Left	Left	(q_{OS}, X, L)	Left	*
q_{left}	(q_{IS}, \lhd, R)	Left	Left	(q_{IS}, X, R)	Left	*
q_{IS}	(q_{IS}, \lhd, R)	$(q_{w\overline{X}}, B, R)$	Right	Right	(q_{e1}, B, R)	*
$q_{w\overline{X}}$	Right	Insert	Insert	Insert	Insert	*
q_{wX}	Right	Insert	Insert	Insert	Insert	*
q_{wB}	Right	Insert	Insert	Insert	Insert	*
$q_{w \triangleright}$	*	*	*	*	*	(q_{left}, \rhd, L)
q_{e1}	*	*	*	*	*	$(q_{e2}, \overline{X, R})$
q_{e2}	*	*	*	*	*	(q_{OS}, \rhd, L)

Figure 3: A summary of the rules for the Layer 1 Turing Machine. The word **Left** stands for $\delta(q, c) = (q, c, L)$. The word **Right** stands for $\delta(q, c) = (q, c, R)$. The word **Insert** stands for $\delta(q_{wt}, c) = (q_{wc}, t, R)$. A * indicates that the Turing Machine does not have a legal transition on that state/tape symbol combination.

Initialization Rules for Layer 1

The rules that constrain the initial configuration of the Layer 1 Turing Machine shown in Figure 4. A square with $\Box \Box$ in the lower row and $t_1 t_2$ in Layer 1 of the upper row is legal if and only if there is an edge



Figure 4: These rules constraint the Layer 1 contents of the bottom row of the tiling.

from a vertex with t_1 to a vertex with t_2 in the graph. If a tile does not appear in the graph, then there is no legal square in which that tile appears in Layer 1 directly above a \Box tile.

If a tiling does not have an illegal initialization square for Layer 1, then the first row for Layer 1 must correspond the to the Turing Machine configuration shown below:

 $\begin{array}{c} q_{e2} \\ \downarrow \\ \triangleleft & \# \end{array}$

3.3 Layer 1: Additional Constraints for Fault Tolerance

The TM definition above still allows for a single fault to completely halt the computation. For example, suppose that a row doesn't have a head tile at all. There would be a local fault where the head tile disappears from one row to the next. All rows thereafter would just be a replication of the same tape contents from the row before and would not contain any illegal computation squares.

To this end we expand the tile types we have so far, so that the tiles \overline{X} , X and B come in two different colors: red and blue. Note that there are now six different tiles corresponding to \overline{X} , X and B: $\{\overline{X}, X, B, \overline{X}, X, B\}$.

We can now partition the ordered pairs of Layer 1 tile types into illegal and legal pairs. If two tiles are an illegal pair for Layer 1 and those two tiles are adjacent in the horizontal direction in a tiling, then that pair of tiles will contribute to the overall cost of the tiling. The set of legal pairs is best illustrated as a directed graph as show in Figure 5.

Definition 7 Legal pairs The pair (t_1, t_2) is a legal pair if one of the following two conditions hold:

- 1. There is an edge (v_1, v_2) such that t_1 is in v_1 's set and t_2 is in v_2 's set.
- 2. There is a vertex w such that (v_1, w) and (w, v_2) are edges, t_1 is in v_1 's set, t_2 is in v_2 's set and ϵ is in w's set.

All other pairs of tiles are illegal.

The ϵ option is included only to reduce the number of edges in the graph. Suppose instead we added an edge (v_1, v_2) whenever there is a vertex w that contains ϵ such that (v_1, w) and (w, v_2) are also edges. Then the ϵ 's could be removed from the graph and the resulting graph would define the same set of legal pairs.

Definition 8 A row of tiles is said to be valid if no two adjacent tiles are an illegal pair. Otherwise the row is invalid.

The set of valid rows corresponds to TM configurations that are a superset of the configurations that the TM would reach in any fault-free³ computation. We will prove below that each valid row corresponds to a

³i.e. all rules are obeyed, zero cost



Figure 5: Graphical representation of the set of valid rows. The state q in the diagram can be any state that is not in $\{q_{e1}, q_{e2}, q_{w \triangleright}\}$

unique Turing Machine configuration to which a rule can be applied. Thus, if a row r is valid, then there is exactly one way to tile the next highest row without any illegal computation squares so that the resulting row is also valid.

Since every row must begin and end with a \Box tile and contains no other \Box tiles, a row of tiles is valid if and only if it can be generated by the following process: Follow any path in the graph from the source to the sink. As each vertex is reached, select any tile type from the current vertex and place a tile of the type next in the row. ϵ denotes the option of not selecting a tile for the current vertex.

Augmenting tiling rules with colors

The definition of legal/illegal computation squares must be augmented to address the fact that now \overline{X} , X and B tiles come in two different colors. In a head square, a tile to the left of a head tile must be blue and a tile to the right of a head tile must be red. For example, consider the following computation legal square below:

(q_{left}/X)	В
X	(q_{left}/B)

The B in the upper-right corner must be red and the X in the lower-left corner must be blue in order for the square to be a legal computation square.

It will als be important to enforce that the only way for a tile to change color from one row to another will be in the presence of the head. so any square of the form



where the two vertically aligned \overline{X} , X's or B's have different colors will be an illegal computation square. To summarize, a square pattern of four Layer 1 tile types is a legal computation square if the square is legal according to the rules translating a Turing Machine to legal and illegal computation squares outlined in Section 2.2 and:

- if the square is a head square, then any $\overline{X}/X/B$ tile the left of a head tile is blue and any $\overline{X}/X/B$ tile the left of a head tile is red
- if a tile $t \in \{X, \overline{X}, B\}$ is directly above a tile $t' \in \{X, \overline{X}, B\}$, then t and t' have the same color.

Otherwise, the square is an illegal computation square.

Properties of Valid Rows

The graphical representation of valid rows given in Figure 5 makes it clear that local constraints can be used to enforce that a row is valid. In particular, any row that is not valid must contain at least one illegal pair. However, the lemma below is a more useful description of valid rows which will allow us to establish that a valid row corresponds to a configuration of the Turing Machine to which one of the transition rules can be applied. It will be convenient to refer to the *tape contents* of a row of tiles. This is the row that would result from replacing every tile of the form (q/c) with c.

Lemma 3.1 A row is valid if and only if the row has the following properties:

1. The tape contents of the row has the form:

$$\triangleleft \{X, B, \overline{X}\}^* \{ \rhd, \epsilon \} \#^*$$

- 2. Exactly one tile is a head tile.
- 3. Any $\overline{X}/X/B$ tiles to the left of the head tile are blue. Any $\overline{X}/X/B$ tiles to the right of the head tile are red.
- 4. If there is a \triangleright or (q/ \triangleright) tile, then the state is not in $\{q_{e1}, q_{e2}, q_{w\triangleright}\}$ and the head is pointing to one of the tiles from the \triangleleft to the \triangleright (inclusive).
- 5. If there is no \triangleright or (q/ \triangleright) tile, then the head is pointing to the leftmost # tile and is in state q_{e1}, q_{e2} or $q_{w \triangleright}$.

Proof: We first establish that any valid row must have the five properties outlined in the lemma, starting with property 1. If a row is valid, then it corresponds to a path from the source to the sink in the graph in Figure 5. Note that every path from the source to the sink must first go through vertex 1 or 2, so the tape contents of the first tile must be \triangleleft . There is no path back to vertices 1 or 2, so the first tile is the only \triangleleft tile. If there is a \triangleright or (q/\triangleright) tile, then the path must pass through vertices 6 or 8. There is no path back to vertices 6 or 8, so \triangleright or (q/\triangleright) only appear once. The only vertices that can come after vertices 6 or 8 is vertex 7, so only

tiles can appear after a \triangleright or (q/\triangleright) tile. Once vertex 7 is reached, only vertex 7 can be reached before the sink. So after the first #, there can only be # tiles until the final \Box tile at the sink.

The head tiles are all contained in vertices 1, 4, 8, or 9. To establish property 2, note that every path from the source to the sink passes through one of the vertices 1, 4, 8, or 9 exactly once.

If vertex 3 is reached, it occurs before vertices 1, 4, 8, or 9 in the path. Therefore only blue $\overline{X}/X/B$ tiles can be to the left of the head tile. If vertex 5 is reached, it occurs after vertices 1, 4, 8, or 9 in the path. Therefore only red $\overline{X}/X/B$ tiles can be to the right of the head tile.

If there is no \triangleright , then the path must pass through vertex 9. The state must be q_{e1} , q_{e2} , or $q_{w\triangleright}$, and the head points to the leftmost #. If there is a \triangleright symbol, then the path passes through vertices 1, 4, or 8, in which case the state is not q_{e1} , q_{e2} , or $q_{w\triangleright}$ and the head points to one of the symbols from the \triangleleft to the \triangleright .

For the converse, the location of the head determines which vertex from 1, 4, 8, or 9 the path goes through. Any row in which the head points to the \lhd symbol that also satisfies all five properties from the lemma can be generated by a path: $1 \rightarrow 5^* \rightarrow 6 \rightarrow 7^*$. Any row in which the head points to the \triangleright symbol that also satisfies all five properties from the lemma can be generated by a path: $2 \rightarrow 3^* \rightarrow 8 \rightarrow 7^*$. Any row in which the head points to a $\overline{X}/X/B$ symbol that also satisfies all five properties from the lemma can be generated by a path: $2 \rightarrow 3^* \rightarrow 4 \rightarrow 5^* \rightarrow 6 \rightarrow 7^*$. Finally any row in which the head points to a # symbol that also satisfies all five properties from the lemma can be generated by a path: $2 \rightarrow 3^* \rightarrow 9 \rightarrow 7^*$.

Lemma 3.2 If r is a valid row, then there is exactly one row r' that can be placed above r such that there are no illegal computation squares that span the two rows r and r'. Row r' is valid. Moreover, row r corresponds to a Turing Machine configuration and r' represents the configuration resulting from executing one step in configuration r.

Proof: Consider a valid row r. We will first argue that if there is a row r' such that if r' is placed directly above r, there are no illegal computation squares, then r' must be unique.

Since r is valid, by Lemma 3.1, it has exactly one head tile. Since each state in the Turing Machine is reached from a well defined direction, a head tile in row r' must come from a specific location in r. Moreover, each head tile in r moves to a well-defined location in r'. This defines a one-to-one correspondence between head tiles in row r and head tiles in row r'. For example, if (q'/c') is a head tile in r' and the state q' is reached from the left, then there must be a head tile (q/c) in row r one location to the left such that $\delta(q, c) = (q', *, R)$. Since there is a matching between head tiles in row r and head tiles in row r' and there is exactly one head tile in row r'.

Since there are no rules in the Layer 1 Turing Machine in which the head stays in the same location, there will be exactly one head square spanning rows r and r' with a head tile in one of the bottom two tiles and a head tile in one of the top two tiles. The square will have one of the following two forms, depending on whether the corresponding rule moves the head right or left:

b	(q'/y)	(q'/y)	b
q/c	У	У	q/c

Note that the contents of the top two tiles are completely determined by the contents of the lower two tiles and the output of the transition function on input (q, c). If either y or b are a $\overline{X}/X/B$ tiles, then their color is also determined by the rules for legal/illegal computation squares and the fact that the head square is a legal computation square.

All other locations in the row have a tape tile in both r and r'. If two vertically aligned tape tiles do not have the same tape symbol and color, then they must be contained in an illegal computation square. If tile b

in the head square is a $B/X/\overline{X}$ tile and is to the left of the head then b must be blue. If tile b is a $B/X/\overline{X}$ tile and is to the right of the head then b must be red. Therefore if r and r' are both valid and there are no illegal computation squares spanning rows r and r', then the contents of r' are completely determined.

Next we need to show that if r is valid, then there is a valid r' such that there are no illegal computation squares spanning rows r and r' Since r is valid, there is exactly one head tile in r and therefore r corresponds uniquely to a configuration of the Turing Machine. If the head is pointing to a # tile in row r, then the state is q_{e1}, q_{e2} or $q_{w\triangleright}$. If the head is pointing to a non-# tile in row r, then the state is not q_{e1}, q_{e2} or $q_{w\triangleright}$. Therefore row r corresponds to a configuration of the Turing Machine and there is a transition rule from Figure 3 that applies to this configuration. Let r' be the row resulting from applying one step of the Turing Machine to the configuration represented by row r. Color all the $B/X/\overline{X}$ tiles to the left of the head tile blue and all the $B/X/\overline{X}$ tiles to the right of the head tile red.

We will first establish that there are no illegal squares spanning rows r and r'. The head square must be legal because it represents one correctly executed step of the Turing Machine. All other tiles outside of the head square are tape tiles and are the same in r and r' because they did not change in the computation step. Moreover since r is valid, all $B/X/\overline{X}$ tiles to the left of the head square are blue and all $B/X/\overline{X}$ tiles to the right of the head square are red. Therefore any $B/X/\overline{X}$ tiles outside of the head square have the same color in r and r'.

The final step is argue that the resulting row r' is valid. Property 3 is satisfied by construction. Row r' also satisfies Property 2 because it corresponds to a valid Turing Machine configuration and therefore only has one head tile. It remains to establish that r' satisfies properties 1, 4, and 5. According to the Turing Machine rules (shown in Figure 3) if the head is pointing to a \triangleleft symbol, it will write a \triangleleft symbol and move right into state q_{IS} or q_{wt} , where $t \neq \triangleright$. The tape contents remain the same and the head is still in between the \triangleleft and \triangleright symbols. If the head is pointing to a $B/X/\overline{X}$ symbol, it writes a $B/X/\overline{X}$ symbol and moves left or right. The new state will not be $q_{e1}, q_{e2},$ or $q_{w\triangleright}$. The tape contents still have the form $\triangleleft \{B, X, \overline{X}\}^* \triangleright \#^*$ and the head is still in between the \triangleleft and \triangleright symbols. If the head \triangleright symbols and move left into a state that is not in $\{q_{e1}, q_{e2}, q_{w\triangleright}\}$ or the Turing Machine will either write \triangleright and move left into a state that is not in $\{q_{e1}, q_{e2}, q_{w\triangleright}\}$ or the Turing Machine will write a $B/X/\overline{X}$ symbol and move right into state $q_{e1}, q_{e2}, q_{w\triangleright}\}$ or the former case, the tape contents will be of the form $\triangleleft \{B, X, \overline{X}\}^* \triangleright \#^*$ and the head is in between the \triangleleft and \triangleright symbols. In the former case, the tape contents will be of the form $\triangleleft \{B, X, \overline{X}\}^* \triangleright \#^*$ and the head is in between the \triangleleft and \triangleright symbols. In the former case, the tape contents will be of the form $\triangleleft \{B, X, \overline{X}\}^* \triangleright \#^*$ and the head is in between the \triangleleft and \triangleright symbols. In the latter case, the tape contents will be of the form $\triangleleft \{B, X, \overline{X}\}^* \bowtie \#^*$ and the head is in between the \triangleleft and \triangleright symbols. In the latter case, the tape contents will be of the form $\triangleleft \{B, X, \overline{X}\}^* \bowtie \#^*$ and the head will point to the leftmost # symbol.

4 Analysis of Layer 1: Proving Fault Tolerance

The goal of the analysis of Layer 1 is to show that as long as the number of faults is not too large $(O(N^{1/4}))$ then the end result will approximate the result of a fault free computation reasonably well.

Section 4.1 associates each illegal pair or square with a particular row and bounds how much a tiling can change from one row to the next as a function of the number illegal configurations associated with that row. Then in order to show that the computation encoded in the tiling makes progress, even in the presence of faults, we define a notion of a *complete segment* which corresponds to a sequence of rows that represent a complete and fault-free iteration of the Outer Loop of the Layer 1 Turing Machine. In a complete segment, each interval increases in size by 1 and a new interval of length 2 is added to the right end of the non-blank tape symbols. The main goal of Subsection 4.4 is to prove Lemma 4.10 which says that the number of complete segments in Layer 1 is at least $\mu(N) - O(F)$, where F is the number of faults and $\mu(N)$ the number of intervals in the last row of a fault-free tiling.

In general, the number of steps in an iteration of the Outer Loop will depend on the number of intervals as well as the total length of all the intervals. Thus, it's possible for faults to create spurious intervals which can cause an iteration of the Outer Loop to take more steps. We define the *weight* of a row to be the number of intervals and the *length* of a row to be the number of non-blank tiles, corresponding to non-blank symbols on the Turing Machine tape. In order to lower bound the number of complete segments, we need to bound the effect of faults on the weight and length of a row and prove that they do not slow down the computation by too much. These bounds are given in Section 4.2.

The analysis on the number of complete segments is made more precise in Section 4.4 where we define the function X which takes as input a sequence of positive integers (s_1, \ldots, s_m) and outputs the exact number of steps in one iteration of the Outer Loop if the sequence of interval sizes (from left to right) at the beginning of the iteration is (s_1, \ldots, s_m) . Section 4.4 gives upper bounds on how much the function X can change in a sequence of correct steps as well as how much X can change as a result of faults. While the function X can be used to bound the number of rows in a complete segment, it is also important to bound the number of rows outside of complete segments. For example a fault could cause the computation to pop into the middle of an iteration of the Outer Loop by having the head move to a completely arbitrary location. Alternatively, a sequence of correct steps could end in a fault before the end of the iteration of the Outer Loop is reached. These bounds are put together to prove Lemma 4.10 which says that the number of complete segments in Layer 1 is at least $\mu(N) - O(F)$.

While each complete segment (i.e. iteration of the Outer Loop) results in the creation of a new interval, it is also necessary to argue that the collection of sizes of the the intervals roughly corresponds to that in a correct faulty-free tiling. To that end, we introduce a means of identifying and tracking the intervals as they grow in size and move to the right. Section 4.6 also defines the notion of *clean* and *corrupt* intervals. Intuitively, clean intervals are those that have not been affected by a fault lower down in the tiling. The clean intervals are given a unique tag which they keep for the duration of the computation. The analysis only provides a guarantee for the collection of interval sizes for the clean intervals. The lower bound on the number of complete segments proven in Section 4.4 is used to prove a lower bound on the number of clean intervals in Section 4.6. Suppose that the sizes of the clean intervals, from left to right, in the last row of Layer 1 is $\vec{s} = (s_1, s_2, \ldots, s_m)$. Lemma 4.17 states that m, the number of clean intervals, in any tiling for Layer 1 is at least $\mu(N) - O(F)$.

Section 4.7 defines a potential function which captures how much the sequence \vec{s} differs from the idealized sequence $(m + 1, m, \ldots, 3, 2)$. Lemma 4.22 shows that the value of the potential function is at most O(F). The final lemma required for analyzing the rest of the constructions is Lemma 4.23 which combines Lemmas 4.17 and 4.22 and says that if the sequence of clean intervals at the end of Layer 1 is \vec{s} , then the number of integers in the range $2, \ldots, \mu(N) + 2$ that do not appear as an entry in \vec{s} is bounded by $44F_1 + 3$.

Layer 3 of the construction for Parity Weighted Tiling and Function Weighted Tiling uses a Turing Machine that sweeps across all of the non-blank symbols. In order to establish that this Turing Machine completes its work in N steps, we need an upper bound on the length of a row as a function of N and the number of faults in Layer 1. This analysis is given in Section 4.5. Note that this section is not used in the proof of Gapped Weighted Tiling. We present these bounds just after Section 4.4 because they use the definition for the function X which is developed there.

Finally, in order to compare a tiling with faults to an fault-free tiling, we will eventually need to characterize the sequence of interval sizes in an fault-free tiling. This characterization is given in Section 4.8.

4.1 The Cost of a Row

To begin the analysis, it will be convenient to associate each illegal square or pair to a particular row in the tiling. This will be important for accounting for the discrepancy between a faulty tiling and a fault-free tiling with specific occurrences of illegal pairs or squares. The number of such illegal configurations attributed to a row is the cost of a row. Note that when analyzing the overall construction, we will refer to the number

of illegal pairs and squares in Layer i by F_i . In this subsection, which focuses on Layer 1, we will drop the subscript and use F to denote the number of illegal pairs and squares in Layer 1.

Definition 9 [Cost of a Row] Fix a tiling of the $N \times N$ grid. The rows of the grid will be numbered from bottom to top r_0, \ldots, r_{N-1} . Let $h(r_t)$ denote the number of illegal pairs in row r_t . (Note that since r_0 is assumed to consist only of \Box tiles, $h(r_0) = 0$.) If $t \ge 1$, then $v(r_t)$ is defined to be the number of illegal computation squares contained in rows r_t and r_{t+1} . $v(r_0)$ is defined to be the number of illegal initialization squares (which are by definition contained in rows r_0 and r_1). We denote by F the total cost of Layer 1 of the tiling, namely the total number of illegal pairs and squares, or the sum of the costs of all rows: $F = \sum_{i=0}^{N-1} h(r_i) + v(r_i) = \sum_i c(r_i)$.

The following claim which is used throughout the analysis shows that the number of illegal pairs or squares attributed to a row can be used to bound the number of locations where the row differs from the row above it.

Claim 4.1 [Upper Bound on the Distance Between Consecutive Rows] If r_{t-1} is an invalid row, then $d(r_{t-1}, r_t) \leq 4h(r_{t-1}) + 2v(r_{t-1})$, where $d(r_{t-1}, r_t)$ is the number of locations where r_{t-1} and r_t differ.

Proof: Suppose that row r_{t-1} is an invalid row (i.e. $h(r_{t-1}) > 0$). Let Q be the number of legal head squares that span rows r_{t-1} and r_t . The number of differences between r_{t-1} and r_t inside the legal head squares is at most 2Q.

Now consider a pair of vertically aligned tiles, t' and t, outside of any legal head square such that $t \neq t'$. The two tiles must satisfy at least one of the conditions in Facts 2.1 and 2.2 and are therefore contained in at least one illegal computation square. Since each illegal computation square contains two pairs of vertically aligned tiles, the number of differences between r_{t-1} and r_t outside of legal head squares is at most $2v(r_{t-1})$.

 $d(r_{t-1}, r_t) \leq 2Q + 2v(r_{t-1})$. We have that the number of head tiles in the row is at least Q (since two legal head squares cannot overlap, and each head squares contains a head tile in its bottom row). There is no path in the graph shown in Figure 5 from a vertex with a head tile back to another vertex with a head tile. So $h(r_{t-1}) \geq Q - 1$. Furthermore, since r_{t-1} is not a valid row, $h(r_{t-1}) \geq 1$. The two bounds on Q together imply that $Q \leq 2h(r_{t-1})$. Therefore $d(r_{t-1}, r_t) \leq 4h(r_{t-1}) + 2v(r_{t-1})$.

4.2 Intervals and their Properties

We would like to argue roughly that in any tiling that does not contain a large number of faults, the intervals are organized "more or less" like in the correct computation. To be able to make this kind of statement precise, we will need to expand the definition for intervals in a row so that intervals are well defined during all points in a valid computation as well as for invalid rows.

We start by defining a *weight function* on tape symbols, TM states, and tile types.

Definition 10 [Weights of Tape Symbols and TM States] If c is a tape symbol, then the weight of c, denoted w(c), equals 0 if c = B or c = #, and is 1 otherwise. If q is a TM state, then w(q) = 1 if $q \in \{q_{wX}, q_{w\triangleright}, q_{w\overline{X}}, q_{e1}, q_{e2}\}$ and w(q) = 0 otherwise.

Note that the weight 1 states are all states that write a weight-1 tile, so they encode the presence of a weight-1 tile in the state. These definitions allow us to assign weights to the tile types.

Definition 11 [Tile Weights] If t is a tape tile corresponding to tape symbol c, then w(t) = w(c). If t is a head tile corresponding to (q/c), then w(t) = w(c) + w(q). If a tile has weight greater than 0, it is referred to as a heavy tile. Otherwise, the tile is called a 0-weight tile.

We can now formally describe the intervals in a way that is well-defined for an arbitrary row, in particular, the definition is precise, even for a row that represents a Turing Machine configuration in the middle of an execution of the Outer Loop.

Definition 12 [Intervals and their Sizes] An interval is a sequence of more than one tiles in a row, that begin and end with heavy tiles and otherwise contain only 0-weight tiles. A single tile whose weight is 2 is an interval as well. If I is an interval, then s(I) denotes the size of I, which is the number of tiles in I.

For example, the sequence of two tiles $X(q_{wX}/B)$ is an interval of size 2 and the single tile (q_{wX}/X) is an interval of size 1. The tile (q_{wX}/X) would also be the right end of the interval extending to the left and the left end of the interval extending to the right. Therefore, a single tile can potentially be contained in three different intervals. In any row, the sequence of tiles from the leftmost to the rightmost heavy tile define a sequence of intervals. Consecutive intervals overlap by one tile. See Figure 6 for an example.



Figure 6: Each interval in the row of tiles is represented by an arrow. The interval begins at the tile under the tail of the edge and includes all the tiles to the right up to and including the tile under the head of the edge. The tile representing (q_{wX}/X) is part of three intervals.

The *length* of row r is the number of tiles that are not # or \square and is denoted by l(r). The *weight* of a row of tiles r is the sum of the weights of the tiles in that row and is denoted bey w(r).

Fact 4.2 The number of intervals in a row r is w(r) - 1.

Proof: We prove by induction that the number of intervals contained in the row up to the i^{th} heavy tile is the weight of the tiles up to and including that tile, minus 1. This is true for the first heavy tile, and assuming it is true up to the i^{th} tile, the next heavy tile adds one interval if its weight is 1, and adds two intervals if its weight is 2.

The next two lemmas upper bound how much the length and the width of the rows change. The first lemma upper bounds the change over a sequence of rows that do not contain illegal pairs or squares, corresponding to correct Turing Machine steps. The second lemma bounds the change from one row to the next in the presence of faults.

Lemma 4.3 [Change in Length and Weight over Correct Computation Steps] Consider a sequence of rows from r_s to r_t such that the sequence of rows does not contain any illegal pairs or illegal squares. If rows r_{s+1} through r_{t-1} are not end rows, then $l(r_t) \leq l(r_s) + w(r_s) + 1$ and $w(r_t) \leq w(r_s) + 1$. If r_s is an end row, then $l(r_t) \leq l(r_s) + w(r_s)$.

Proof: The only Turing Machine rule that increases the weight of the configuration is the rule $\delta(q_{e1}, \#) = (q_{e2}, X, R)$ which leads to an end row. Therefore all the rows r_s through r_{t-1} have the same weight and $w(r_t) \leq w(r_s) + 1$.

Each iteration of the inner loop (from an IS[k] configuration to an IS[j] configuration where j > k) increases the size of one interval by one. So each iteration of the inner loop increases the total length by

1. There are at most $m = w(r_s) - 1$ iterations of the inner loop. Then the last step $\delta(q_{e1}, \#) = (q_{e2}, X, R)$ also increase the length by 1. If r_s is in state q_{wt} then there can be an additional increase of one for the symbol t that is inserted. Thus the length will increase by at most $w(r_s) + 1$ and $l(r_t) \leq l(r_s) + w(r_s) + 1$. If r_s is an end configuration, the state is q_{e2} and there is not the additional +1 increase to the length and $l(r_t) \leq l(r_s) + w(r_s)$.

Claim 4.4 [Change in Length and Weight in the Presence of Faults] Consider two consecutive rows r_p and r_{p+1} in a tiling. Then

$$\begin{aligned} l(r_{p+1}) &\leq l(r_p) + 2v(r_p) + h(r_p) + 1 \\ w(r_{p+1}) &\leq w(r_p) + 2v(r_p) + h(r_p) + 1 \end{aligned}$$

Moreover, if r_{p+1} is a valid row, then $l(r_{p+1}) \leq l(r_p) + \max\{1, v(r_p)\}$. If r_{p+1} is a valid row that is not an end row, then $w(r_{p+1}) \leq w(r_p) + 2v(r_p)$.

Proof: We first account for any increase to the width and length from r_p to r_{p+1} that occurs inside legal head squares. Consider each legal head square in rows r_p and r_{p+1} . Suppose there are Q such squares. Each of these squares contains a head tile in the lower level. Also, the total increase in length or weight from r_p to r_{p+1} inside these squares is at most Q since a valid step of the computation will cause the length or weight to increase by at most 1. There is no path in the graph shown in Figure 5 from a vertex with a head tile to another vertex with a head tile. So $h(r_p) \ge Q - 1$. Therefore the total increase in length or weight inside these legal head squares is at most $h(r_p) + 1$.

If r_{p+1} is valid, then there is only one head tile in r_{p+1} and therefore at most one legal head square. The only TM step that increases the weight is $\delta(q_{e1}, \#) = (q_{e2}, X, R)$. If r_{p+1} is not an end row (i.e. a valid row that contains q_{e2}), then the weight does not increase in this square.

Now we will show that any increase to the length or weight from r_p to r_{p+1} that occurs outside the legal head squares will be at most $2v(r_p)$. Each illegal square will be given two tokens that can be used to compensate for any increase to the width or length that occurs inside that square. Consider a tile t' on top of tile t. If any of the conditions from Fact 2.1 apply, then both squares that include t and t' are illegal. The width and length can increase by at most 2. The increase is paid for by a token from each of the two illegal squares that contain t' and t.

If any of the cases from Fact 2.2 apply to t' and t, the weight and length can increase by at most 1. According to Fact 2.2, t' and t are in a legal head square or an illegal square. In the latter case, the increase in weight is accounted for by a token from the illegal square that contains t' and t.

The only case not covered by Facts 2.1 and 2.2 is when t' and t are both tape tiles and t' = t, in which case the length and weight does not increase in that location. This covers the general upper bounds that apply regardless of whether r_{p+1} is valid as well as the upper bound on the increase in weight when r_{p+1} is valid.

Finally, to bound the increase in length for the special case where r_{p+1} is valid, we use again the fact that r_{p+1} has exactly one head tile. Suppose that tile is in location j. The total increase in length from r_p to r_{p+1} at location j is at most 1. Any other increase in length is due to a tape tile t in row r_{p+1} on top of a # tile in row r_p . If there are no such occurrences, then $l(r_{p+1}) \leq l(r_p) + 1$. If there is at least one such vertically aligned pair, then each one can increase the length by at most 1. Also, by Fact 2.1, each such vertical pair participates in two illegal squares, one to the left and one to the right. Although these squares can overlap, the number of illegal squares is at least the number of such vertical pairs plus 1. In other words, the total increase in the lengths due to tiles at locations other than j is at most $v(r_p) - 1$. In this case $l(r_{p+1}) \leq l(r_p) + v(r_p)$.

4.3 Segments and Complete Segments

In a complete iteration of the Outer Loop of the Turing Machine, each interval increases in size by 1 and a new interval of size 2 is added. Thus, we want to show a lower bound for the number of fault-free iterations of the Outer Loop represented in the tiling (Lemma 4.10). We partition the rows into segments. The end of a segment is reach whenever a row has non-zero cost or is a valid end row. A segment is said to be complete if the last row in the segment as well as the last row in the previous segment are zero-cost rows. Note that this implies that the last row in the two consecutive segments are end rows. Since there are no illegal computation squares contained in the rows of the segment, the segment corresponds to a sequence of fault-free steps of the Turing Machine from one end configuration to the next, which is a complete iteration of the Outer Loop of the Turing Machine.

Definition 13 [Segments and Complete Segments] We will partition the sequence of rows a tiling in to segments going from bottom to top. The first segment consists of the first two rows r_0 and r_1 . Each new segment begins at the row above the previous segment and ends at the next row r that is either an end row or has v(r) + h(r) > 0. Let r be the last row of a segment and r' be the last row of the previous segment. A segment is complete if v(r) + h(r) = v(r') + h(r') = 0.

We can now combine the bounds from the previous sections to upper bound the weight and length of a row r as a function of the number of segments and the cumulative cost below row r in the tiling.

Lemma 4.5 [Upper Bounds on Length and Weight as a Function of Number of Segments and Number of Faults] Let r be a row in segment t. Then

$$w(r) \le 1 + t + 2C_t$$
$$l(r) \le 1 + 2tC_t + \sum_{j=1}^t j,$$

where $C_t = \sum_{j=0}^{t-1} [v(r_j) + h(r_j)].$

Proof: Proof by induction on t.

Base Case: t = 1. The first segment consists of r_0 and r_1 . $C_1 = v(r_0)$, which is the number of illegal initialization squares. We will number the locations of tiles in r_1 from left to right so that tiles 1 through N-2 are the tiles between the \Box tiles. Square j will be the tiles in locations j-1 and j in rows r_0 and r_1 . For any $S \subseteq \{2, \ldots, N-2\}$ let v(S) be the number of $j \in S$ such that square j is an illegal initialization square.

Each tile in r_1 can contribute at most 1 to the length and at most 2 to the weight. Let S_1 be the locations in r_1 that have a tile that is not \triangleleft , $(q_{e2}/\#)$ or #. For every $j \in S_1$, square j is illegal, so $v(S_1) = |S_1|$. The total contribution to the weight or length of r_1 from tiles that are in locations in S_1 is at most $2v(S_1)$. Let S_2 be the set of locations with a \triangleleft tile. Square j is illegal for every $j \in S_2$, except j = 1, so $|S_2| \leq v(S_2) + 1$. Each \triangleleft tile contributes +1 to the weight and length of r_1 , so the total contribution to the weight or length from tiles in S_2 is at most $v(S_2) + 1$. If a tile in location j is $(q_{e2}/\#)$, then either square j is illegal or location j - 1 has a \triangleleft tile. Let S_3 be the set of locations with a $(q_{e2}/\#)$ tile. The total contribution to the weight or length from tiles in S_3 is at most $v(S_3) + |S_2| \leq v(S_3) + v(S_2) + 1$. A # tile does not contribute to the weight or length of r_1 . The total weight or length of r_1 is at most

$$2v(S_1) + [v(S_2) + 1] + [v(S_3) + v(S_2) + 1] \le 2 + 2[v(S_1) + v(S_2) + v(S_3)] = 2 + 2 \cdot C_1.$$

Induction step: We will bound the length and weight of the row at the end of segment t > 1. Note that if a row r is not the last row in the segment, then it must have zero cost. The sequence of rows from r to the end of the segment do not contain any illegal pairs or squares and thus correspond to a set of correctly executed Turing Machine steps applied to valid row. Note that the length and width of the row do not decrease with any step of the Turing Machine applied to a valid row. Therefore, it is enough to bound the length and width of the last row in the segment.

Let r' be the row at the end of previous segment. We consider three cases:

Case 1: v(r') + h(r') = 0. Then $C_t = C_{t-1}$. Rows r' through r do not contain any illegal squares or pairs. Row r' must be an end row, so by Lemma 4.3,

$$w(r) \le 1 + w(r') \le 1 + 1 + (t - 1) + 2C_{t-1} \le 1 + t + 2C_t$$

$$l(r) \le l(r') + w(r') \le \left[1 + 2(t-1)C_{t-1} + \sum_{j=1}^{t-1} j\right] + \left[1 + (t-1) + 2C_{t-1}\right] = 1 + 2tC_t + \sum_{j=1}^{t} j.$$

Case 2: v(r') + h(r') > 0 and r is the row right after r'. Let Δ denote $C_t - C_{t-1} = v(r') + h(r')$ By Claim 4.4,

$$w(r) \le w(r') + 2v(r') + h(r') + 1 \le 1 + (t-1) + 2C_{t-1} + 2\Delta + 1 \le 1 + t + 2C_t$$

$$\begin{aligned} l(r) &\leq l(r') + 2v(r') + h(r') + 1 \\ &\leq 1 + \sum_{j=1}^{t-1} j + 2(t-1)C_{t-1} + 2\Delta + 1 \\ &\leq 1 + \sum_{j=1}^{t-1} j + 2tC_{t-1} + 2t\Delta + t \\ &\leq 1 + \sum_{j=1}^{t} j + 2tC_t \end{aligned}$$

Case 3: v(r') + h(r') > 0 and r is not the row right after r'. Then the intervening rows between r' and r are valid. Let \bar{r} be the row right after r'. The row \bar{r} is valid and not an end row. Otherwise, the segment would have ended at \bar{r} instead of r. By Claim 4.4, $w(\bar{r}) \leq w(r') + 2v(r')$. By Lemma 4.3, $w(r) \leq 1 + w(r')$. Therefore,

$$w(r) \le w(\bar{r}) + 1 \le w(r') + 2v(r') + 1 \le 1 + (t-1) + 2C_{t-1} + 2v(r') + 1 \le 1 + t + 2C_t$$

By Claim 4.4, and $l(\bar{r}) \leq l(r') + \max\{v(r'), 1\}$. Let $\Delta = C_t - C_{t-1} = v(r') + h(r')$. Since $\Delta > 0$, $l(\bar{r}) \leq l(r') + \Delta$. The rows \bar{r} through r do not contain any illegal pairs and are valid. Therefore Lemma 4.3,

$$\begin{split} l(r) &\leq l(\bar{r}) + w(\bar{r}) + 1 \\ &\leq [l(r') + \Delta] + [w(r') + 2v(r')] + 1 \\ &\leq \left[1 + \sum_{j=1}^{t-1} j + 2(t-1)C_{t-1} + \Delta \right] + [1 + (t-1) + 2C_{t-1} + 2\Delta] + 1 \\ &\leq 1 + \sum_{j=1}^{t} j + 2tC_{t-1} + 2t\Delta = 1 + \sum_{j=1}^{t} j + 2tC_t \end{split}$$

The last inequality follows from the facts that $\Delta \geq 1$ and $t \geq 2$.

4.4 Lower Bound on the Number of Segments

In a fault-free tiling the number of intervals is equal to the number of complete segments because each iteration of the Outer Loop adds one segment. The goal of this section is to show that faults do not change the number of complete segments in the final row of Layer 1 by too much.

Definition 14 [The function μ] Define $\mu(N)$ to be the number of intervals in the last row of Layer 1 in an fault-free tiling of an $N \times N$ grid.

The goal in this Section is to prove Lemma 4.10 which says that the number of complete segments in any tiling in Layer 1 is at least $\mu(N) - 14F_1$, where F_1 is the number of faults in the Layer 1 tiling. Note that when F is $o(\mu(N))$, which is the case we will be interested in for all the problems we consider, we are characterizing the number of complete segments tightly, up to low order terms. In order to achieve this tight characterization, we need to specify the exact number of rows in a complete segment which will depend on the sequence of interval lengths. To this end, we define the following function which characterizes the number of steps in a complete segment that starts with a row r. Let s_1, \ldots, s_m be the sizes of all the intervals in row r from left to right. Define the function X as:

$$X(r) = \sum_{j=1}^{m} \left[2j(s_j - 1) + 1 \right].$$
(1)

If the first row r of a segment is a no-cost row, then the segment consists of one or more valid computation steps ending with either a fault or an end row. Lemma 4.6 provides an upper bound on the number of rows in the segment in this case. The upper bound is the function X applied to the start row plus some additional terms in the cases where the segment begins or ends with a row with non-zero cost. The proof is a somewhat tedious case analysis because if the previous segment ended with a fault, the computation represented in the segment could begin at any point in the execution of the Outer Loop and it is necessary to consider each possible starting point separately. For example, the fault could cause the head to appear in any location and in any state that is consistent with the horizontal constraints.

The next three lemmas (Lemmas 4.7 through 4.9) then upper bound the amount by which X can increase in a sequence of rows. Lemma 4.8 considers the situation described above where the rows are contained within a segment and first row of the segment is a no-cost row. Lemma 4.8 considers a maximal sequence of rows with non-zero cost. Lemma 4.9 considers the initial sequence of non-zero cost rows.

Finally Lemma 4.10 puts all these bounds together to lower bound the number of complete segments.

Lemma 4.6 [Upper Bound on the Length of a Segment] Consider a sequence of rows from r_s to r_t such that the sequence of rows does not contain any illegal pairs or illegal squares. Suppose that the sizes of the intervals from left to right (both clean and corrupt) in row r_s are s_1, \ldots, s_m . If rows r_{s+1} through r_{t-1} are not end rows, then

$$t - s \le l(r_s) + 2w(r_s) - 2 + X(r_s)$$

If r_s is an end row, then $t - s \leq X(r_s)$. If r_s and r_t are both end rows, then $t - s = X(r_s)$.

Proof: We will show that if the Turing Machine starts in a valid configuration, then the Turing Machine will reach an end row within $S = l(r_s) + 2w(r_s) - 2 + \sum_{j=1}^{m} [2j(s_j - 1) + 1]$ correctly executed steps.

Consider a configuration of the Turing Machine that corresponds to a valid row. The configuration is an IS[k] configuration if the state of the Turing Machine is q_{IS} and the head is pointing to one of the internal weight-0 symbols in interval k or the weight-1 symbol at the right end of interval k.

We will establish that the Turing Machine will reach an end configuration or an IS[j] configuration for j > k within a certain number of steps. The head moves right in state q_{IS} until it reaches a X or \triangleright symbol. If it reaches a \triangleright symbol first, then it transitions to q_{e1} and then q_{e2} pointing to a # symbol. This is an end state. The number of steps has been

$$s_k - 2 + \sum_{i=k+1}^m (s_i - 1) + 2 = 1 + \sum_{j=k}^m (s_j - 1) \le S.$$

If the head reaches an X symbol first in state q_{IS} , it writes a B, and then inserts an \overline{X} by moving all the non # symbols over by one. Interval k + 1 now has a \overline{X} symbol on its left end. The number of steps has been at most $\sum_{i=k}^{m} (s_i - 1)$. When it reaches the $q_{w\triangleright}$ state, it replaces the # with a \triangleright , transitions to q_{left} and moves left. The head moves left in state q_{left} until it reaches a \overline{X} symbol. We are guaranteed that the left end of interval k + 1 has \overline{X} symbol but there could be a \overline{X} that comes earlier. Let j be the largest index such that the left end of interval j is \overline{X} . When the head reaches the left end of interval j, it replaces the \overline{X} with X, transitions to q_{IS} and moves right. This has been an additional $1 + \sum_{i=j}^{m} (s_i - 1)$ steps. The cycle from the IS[k] configuration to the IS[j] configuration is an iteration of the Inner Loop. The total number of steps has been

$$1 + \sum_{i=k}^{m} (s_i - 1) + \sum_{i=j}^{m} (s_i - 1) = 1 + \sum_{i=k}^{j-1} (s_i - 1) + 2\sum_{i=j}^{m} (s_i - 1).$$

The number of steps to get to an end configuration from an IS[k] configuration is maximized if we start in an IS[1] configuration and for each k, after the Turing Machine leaves the IS[k] configurations, the next time it reaches state q_{IS} is in interval j = k + 1 (an IS[k+1] configuration). After reaching an IS[m] configuration, the Turing Machine is guaranteed to reach an end configuration in $1 + (s_m - 1)$ steps. The maximum number of steps required to reach an end configuration when starting in any IS[k] state is:

$$\sum_{k=1}^{m-1} \left[1 + (s_k - 1) + \sum_{i=k+1}^m 2(s_i - 1) \right] + 1 + (s_m - 1)$$
(2)

$$= m + \sum_{i=1}^{m} (s_i - 1) + 2 \sum_{j=2}^{m} \sum_{i=j}^{m} (s_i - 1)$$
(3)

Next we will argue that as long as the initial configuration of the Turing Machine is valid, it will reach the state q_{IS} or an end configuration within a certain number of steps.

If the initial configuration is in state q_{OS} or q_{left} , the head moves left until a \triangleleft or \overline{X} symbol is reached. Then the state transitions to q_{IS} and moves right. This will be at most an additional $1 + \sum_{i=1}^{m} (s_i - 1)$ steps. Adding this value to the bound from Expression (3):

$$m + 1 + 2\sum_{j=1}^{m} \sum_{i=j}^{m} (s_i - 1) = 1 + \sum_{i=1}^{m} [2j(s_i - 1) + 1]$$
(4)

If the initial configuration is in state q_{e1} then the current symbol is # and the configuration is one step away from an end configuration.

If the initial configuration is in state q_{e2} or $q_{w\triangleright}$, then the Turing Machine writes \triangleright and moves left into state q_{OS} or q_{left} . The head then moves left until a \triangleleft or \overline{X} symbol is reached. Then the state transitions to q_{IS} and moves right. This will be at most an additional $1 + \sum_{i=1}^{m} (s_i - 1)$ steps and an IS[k] configuration has been reached. The same bound from (4) applies.

Finally, suppose that if the Turing Machine is in a state q_{wt} . If the current symbol is \triangleleft , it writes a \triangleleft symbol, and moves right into state q_{IS} . The current configuration is a IS[1] configuration. In this case, the number of steps is the bound from Expression (3) plus 1.

If the Turing Machine starts in a state q_{wt} and the current symbol is not \triangleleft , then let j be the index of the interval that the head starts in. The Turing Machine will insert a t symbol and shift the contents of the tape to the right. When the Turing Machine reaches the $q_{w\triangleright}$ state, it writes a \triangleright , and moves left into state q_{left} . The number of steps has been at most $\sum_{i=1}^{m} (s_i - 1)$. Interval j has now increased in size by 1. The bound from (4) applies, except that the size of interval j is now $s_j + 1$ instead of j. The total number of steps to reach an end row is at most

$$\sum_{i=1}^{m} (s_i - 1) + 1 + 2j + \sum_{i=1}^{m} [2j(s_i - 1) + 1].$$

The 2*j* term comes from the fact that the size of interval *j* is $s_j + 1$ instead of s_j . Plugging in the expressions $\sum_{i=1}^{m} (s_i - 1) = l(r_s) - 1$ and $j \le m = w(r_s) - 1$:

$$\sum_{i=1}^{m} (s_i - 1) + 1 + 2j + \sum_{i=1}^{m} [2j(s_i - 1) + 1]$$

$$\leq l(r_s) + 2(w(r_s) - 1) + \sum_{i=1}^{m} [2j(s_i - 1) + 1]$$

$$\leq l(r_s) + 2(w(r_s) - 1) + m + 2m \sum_{i=1}^{m} (s_i - 1)$$

$$\leq l(r_s) + 2(w(r_s) - 1) + w(r_s) - 1 + 2(w(r_s) - 1)(l(r_s) - 1)$$

$$< 2w(r_s)l(r_s)$$

The simplification in the last line of the equations above use the fact that $l(r_s) \ge w(r_s)$. The second line gives the first upper bound for t - s stated in the lemma and the last line gives the second upper bound for t - s.

If the initial configuration is an end row, then the Turing Machine writes \triangleright and moves left into state q_{OS} until it reaches the \triangleleft symbol. The head then moves right into state q_{IS} , which is an IS[1] configuration. The number of steps so far is exactly $1 + \sum_{i=1}^{m} (s_i - 1)$. The q_{OS} state changes all \overline{X} symbols to X symbols. The Turing Machine maintains the invariant that when in state q_{left} or q_{wt} , the \overline{X} symbol will mark the right end point of the last interval that has been increased. Therefore, if an iterations of the inner loop that starts in an IS[k] configuration, the next iteration will start in an IS[k+1] configuration. Therefore the number of steps is exactly the bound given in (4). If the sequence ends before an end row is reached, then the number of rows is less than the bound given in (4).

The following three lemmas will be used to bound the growth of the function X. Lemma 4.7 bounds how much X can increase as the result of fault-free steps of the Turing Machine applied to valid configurations. Lemmas 4.8 and 4.9 bound how much illegal pairs or squares can cause X to increase.

Lemma 4.7 [Upper Bound on Change in X in Fault-Free Steps] Consider a sequence of rows r_a through r_b that do not contain any illegal pairs or squares and such that rows r_{a+1} through r_{b-1} are not end rows. Then

$$X(r_b) - X(r_a) \le 1 + (w(r_b) - 1)w(r_b) + 2w(r_b).$$

If r_a is an end row, then $X(r_b) - X(r_a) \le 1 + (w(r_b) - 1)w(r_b)$.

Proof: Since rows r_a through r_b do not contain any illegal pairs or squares, they correspond to b-a steps applied to the valid configuration represented in row r_a . Moreover, the computation does not reach the end of an iteration of the Outer Loop until possibly the last step. Let $m = w(r_a) - 1$ be the number of intervals in row r_a . If configuration r_a starts in a state q_{wt} , then some interval j may increase by one as the head sweeps right, moving all the symbols over by 1. After this point, each interval can increase by at most 1 before the end of the Outer Loop is reached. Thus, the summation in (1) can increase by at most $2j + \sum_{j=1}^{m} 2j$. If r_a is an end row, then the summation increases by at most $\sum_{j=1}^{m} 2j$. If r_b is not an end row, then $w(r_b) = w(r_a)$ and

$$\sum_{j=1}^{m} 2j = (w(r_b) - 1)w(r_b).$$
$$2j + \sum_{j=1}^{m} 2j \le 2m + (w(r_b) - 1)w(r_b) \le (w(r_b) - 1)w(r_b) + 2w(r_b).$$

The first expression above bounds $X(r_b) - X(r_a)$ in the case that r_a is an end row and r_b is not an end row. The second expression bounds $X(r_b) - X(r_a)$ in the case that neither r_a nor r_b are end rows.

If r_b is an end row, then $w(r_b) = w(r_a) + 1$ and a new interval of size 2 is added to to the right end, increasing X by an additional 2m + 3.

$$2m + 3 + \sum_{j=1}^{m} 2j = 1 + \sum_{j=1}^{m+1} 2j = 1 + (w(r_b) - 1)w(r_b).$$
$$2m + 3 + 2j + \sum_{j=1}^{m} 2j \le 1 + (w(r_b) - 1)w(r_b) + 2w(r_b).$$

The first expression above bounds $X(r_b) - X(r_a)$ in the case that r_a and r_b are both end rows. The second expression bounds $X(r_b) - X(r_a)$ in the case that r_a is not an end row, but r_b is an end row.

Lemma 4.8 [Upper Bound on Change in X in a Sequence of Rows with Non-Zero Cost] Consider a no-cost row r_{a-1} such that row r_a has a positive cost. Let r_b be the next highest no-cost row after r_a . Let f be the number of illegal pairs or squares contained in the rows r_a through r_b . Let F be the total number of illegal pairs or squares in Layer 1. If row r_b is in the tth segment, then

$$X(r_b) - X(r_a) \le 8f[t^2 + 4tF + t + 2F + 8f].$$

Proof: By Claim 4.1, $d(r_b, r_a) \leq 4 \sum_{j=a}^{b-1} [v(r_j) + h(r_j)] = 4f$. We will let d denote $d(r_b, r_a)$. Note that r_a must be a valid row because the row before it, r_{a-1} is a no-cost row. Let s_1, \ldots, s_m be the sizes of the intervals in r_a . We start by re-expressing the summation in the definition of X(r) from (1):

$$\sum_{j=1}^{m} [2j(s_j - 1) + 1] = \sum_{j=1}^{m} \left[1 + \sum_{k=j}^{m} 2(s_k - 1) \right].$$

We will account for how the summation in (1) changes from r_a to r_b . In the worst case, all of the heavy tiles in row r_a are unchanged in r_b and all the locations where the two rows differ result in new heavy tiles in row r_b .

Since r_a and r_b are both valid rows, they have exactly one \triangleright tile which is the right end of the right-most interval. The sum $\sum_{k=j}^{m} (s_k - 1)$ is exactly the distance from the left end of interval j to the \triangleright tile. The

position of the \triangleright tile is at most d spaces to the right in r_b than it is in r_a , so the value of the summation in (1) increases from r_a to r_b by at most 2dm as a result of the existing heavy tiles in r_a . There are at most d new heavy tiles in r_b that were not in r_a , each of which can create at most two new intervals (since the weight of every tile is at most 2). Each new interval can increase the sum by at most $1 + 2d + \sum_{k=1}^{m} 2(s_k - 1)$ which is at most $2(l(r_a) + d)$. The increase due to the new intervals is therefore at most $4d(l(r_a) + d)$. Therefore $X(r_b) - X(r_a) \leq 2dm + 4d(l(r_a) + d)$.

Since r_a has non-zero cost, it is the last row in some segment t', where t' < t. The number of intervals m in row r_a is $w(r_a) - 1$, which according to Lemma 4.5, is at most 2F + t' < 2F + t. Using the same lemma, we can bound $l(r_a)$ by 2t'F + 1 + t'(t'+1)/2 which is at most $2tF + t^2/2$ since $t \ge 2$. Plugging the bounds in, and using the fact that $d \le 4f$, we get

$$X(r_b) - X(r_a) \le 8f[t^2 + 4tF + t + 2F + 8f].$$

Lemma 4.9 [Upper Bound on Change in X the Initial Sequence of Rows with Non-Zero Cost] Let t be the smallest index such that r_t is a no-cost row. Let f be the number of illegal pairs and squares contained in rows r_0 through r_t . Then $X(r_t) \leq 18f^2 + 18f + 3$.

Proof: By Lemma 4.5, the weight and length of r_1 is at most $2 + 2c_1$, where c_1 is the number of illegal initialization squares. By Claim 4.4, the weight and length can increase from r_1 to r_t by at most $2c_2 + (t-1)$, where c_2 is the sum of the costs of rows r_1 through r_{t-1} . $c_2 \ge t-1$ because the first t-1 rows all have non-zero cost. Also $c_1 + c_2 = f$. Therefore the weight and length of r_t is at most

$$[2+2c_1] + [2c_2 + (t-1)] \le 2 + 2c_1 + 3c_2 \le 2 + 3f.$$

The summation in the definition of $X(r_t)$ is maximized if the contents of the row consists of 2+3f heavy tiles, in which case there are 3f+1 intervals all of size 2. Then $X(r_t)$ is $(3f+2)^2-1$ which is at most $9f^2+12f+3$. The additional cost of $l(r_t) + 2w(r_t)$ is incurred only if r_1 is not an end row, in which case f > 0. Therefore

$$X(r_t) \le [9f^2 + 12f + 3] + f(l(r_t) + 2w(r_t)) \le [9f^2 + 12f + 3] + 3f(2 + 3f) \le 18f^2 + 18f + 3.$$

Lemma 4.10 [Lower Bound on the Number of Complete Segments] Let F be the number of illegal squares or pairs in Layer 1 of a tiling of the $N \times N$ grid. Then the number of complete segments in Layer 1 is at least $\mu(N) - 14F$.

Proof: The main work of the proof is to show that the number of segments (complete or not) in Layer 1 is at least $\mu(N) - 12F_1$. Each segment ends on a row that incurs a cost or ends on an *end row*, corresponding to the last row of an iteration of the Outer Loop. Each illegal square or pair can cause the end of at most one segment. Therefore, if there are at least $\mu(N) - 12F_1$ segments, then there must be at least $\mu(N) - 12F_1 - 2F_1 = \mu(N) - 14F_1$ segments that end with a zero cost row and such that the segment before also ends on a zero cost row. These are, be definition, complete segments.

Consider a tiling of the $N \times N$ grid that has a total of F illegal pairs and squares. Number the segments S_1, S_2, \ldots from bottom up. We will denote the number of row in segment S_t by $|S_t|$. Let $\bar{S}_1, \bar{S}_2, \ldots$ be the segments in the unique tiling in Layer 1 that has no illegal squares or pairs, which we call the *no-cost* tiling. There is one interval after the first segment (which just consists of the initial row). Then in a fault-free tiling
every segment corresponds to one iteration of the Outer Loop in which exactly one interval is added in the last step. Therefore in a fault-free tiling the number of complete segments is equal to the number of intervals in the last row, which is $\mu(N)$. We will show that

$$\sum_{t=1}^{\mu(N)-12F} |S_t| \le \sum_{t=1}^{\mu(N)} |\bar{S}_t|.$$

Thus if N is large enough to accommodate $\mu(N)$ segments in an fault-free tiling, then N is large enough to accommodate $\mu(N) - 12F$ segments in a tiling with F illegal pairs or squares.

A segment will be called *big* if it has more than one row and otherwise it is called *small*. In a big segment, all the rows except possibly the last row of the segment have v(r) + h(r) = 0. If a row is valid (h(r) = 0)and there are no illegal squares contained in the row and the row above it (v(r) = 0), then according to Lemma 3.2, the row above r is the unique row representing one step of the Turing Machine applied to the configuration corresponding to r, which is also a valid row. Therefore, if a segment has more than one row, all the rows in the segment are valid and there are no illegal pairs or squares contained in the rows of the segment.

Finally, we will partition the illegal pairs and squares in Layer 1 according to where they are located with respect to the big segments. If S_t is small, then $f_t = 0$. Otherwise if S_t is big, let t' be the largest $2 \le t' < t$ such that $S_{t'}$ is also big. The quantity f_t is defined to be the number of illegal squares contained in the set of rows from the last row in $S_{t'}$ through the first row in S_t . If S_t is the first big segment then, f_t is the number of illegal pairs and squares contained in the rows from r_0 through the first row in S_t , including the illegal initialization squares. Note that $\sum_t f_t = F$.

Note that in any tiling, the first segment consists of rows r_0 and r_1 , so we will only be concerned with bounding the number of rows in all the segments, except the first segment. We will define a quantity X_t for each segment indexed by t. If the t^{th} segment is small, then $X_t = 1$. If the t^{th} segment is big, then $X_t = X(r)$, where r is the first row in the segment. If the last row of the previous segment is a no-cost row, then it must be an end row. According to Lemma 4.6, X_t is an upper bound on the number of rows in the segment. If the last row of the previous segment has non-zero cost, then $f_t > 0$ and the number of rows of the segment is at most $X_t + l(r) + 2w(r)$, where r is the first row in the segment. Therefore

$$\sum_{t=1}^{m} |S_t| \le \sum_{t=1}^{m} X_t + \max_r \{l(r) + 2w(r)\} \sum_t f_t = \sum_{t=1}^{m} X_t + F \cdot \max_r \{l(r) + 2w(r)\}$$

Using the bounds from Lemma 4.5 and simplifying, $l(r) \leq 3mF + m^2$ and $w(r) \leq 2(m+F)$,

$$\sum_{t=1}^{m} |S_t| \le 3mF^2 + Fm^2 + 4mF + 4F^2 + \sum_{t=1}^{m} X_t \le Fm^2 + 11mF^2 + \sum_{t=1}^{m} X_t$$
(5)

We would like to bound how much the parameter X_t can grow from one big segment to the next. To that end, we define Δ_t to be the increase in X_t . If S_t is small, then $\Delta_t = 1$. Otherwise $\Delta_t = X_t - X_{t'}$, where t' is the largest $2 \leq t' < t$ such that $S_{t'}$ is also big. If S_t is the first big segment then, $\Delta_t = X_t$. For any m:

$$\sum_{t=2}^{m} X_t \le \sum_{t=2}^{m} (m-t+1)\Delta_t.$$

The goal then is to bound Δ_t . Suppose that S_t is a big segment that is not the first big segment. Let $S_{t'}$ be the last big segment before S_t . Let r be the first row of $S_{t'}$, r' be the last row of $S_{t'}$ and r'' the first row of S_t . $\Delta_t = X(r'') - X(r)$. We will bound X(r'') - X(r') and X(r') - X(r) separately.

We first bound X(r'') - X(r'). There are two cases:

Case 1: r' has zero cost. Let \bar{r} be the row after r'. Since r' is the last row in segment $S_{t'}$, it must be an end row. Row \bar{r} represents the first configuration in the next iteration of the Outer Loop. Since the intervals do not change in the first step of the Outer Loop, $X(\bar{r}) - X(r') = 0$. If \bar{r} is also a no-cost row, then it is the first row in a big segment, which means that \bar{r} is the first row in S_t and $\bar{r} = r''$. In this case, $f_t = 0$ and X(r'') - X(r') = 0. If \bar{r} has positive cost, we can apply Lemma 4.8 with $r_a = \bar{r}$ and $r'' = r_b$ to get that

$$X(r'') - X(r') = X(r'') - X(\bar{r}) \le 8f_t[t^2 + 4tF + t + 2F + 8f_t].$$

Case 2: r' has positive cost. We can apply Lemma 4.8 with $r_a = r'$ and $r'' = r_b$ to get that

$$X(r'') - X(r') = \le 8f_t[t^2 + 4tF + t + 2F + 8f_t].$$

We now use Lemma 4.7 to bound X(r') - X(r). If the row before r has zero cost, then it must be an end row, and $X(r') - X(r) \le 1 + w(r')(w(r') - 1)$. If the row before r has positive cost, then $X(r') - X(r) \le 1 + w(r')(w(r') - 1) + 2w(r')$. Note that if the row before r has positive cost, then F > 0. Therefore, we can combine the bounds to get:

$$X(r') - X(r) \le 1 + w(r')(w(r') - 1) + 2Fw(r')$$

By Claim 4.4, $w(r') \leq 1 + t' + 2F \leq 2F + t$. Therefore

$$X(r') - X(r) \le (2F+t)^2 - (2F+t) + 1 + 2F(2F+t) \le (t^2 - t + 1) + 8F^2 + 6Ft$$

The bound for $\Delta_t = X(r'') - X(r)$ comes from adding the bounds for X(r'') - X(r') and for X(r') - X(r), to get

$$\Delta_t \le \left[8f_t(t^2 + 4tF + t + 2F + 8f_t)\right] + \left[(t^2 - t + 1) + 8F^2 + 6Ft\right].$$
(6)

The bound for Δ_t in 6 applies to the case where S_t is a big segment that is not the first segment in Layer 1. If S_t is the first big segment, then by Lemma 4.9,

$$X_t = \Delta_t \le (18(f_t)^2 + 18f_t + 3)$$

If S_t is not a big segment, then $\Delta_t = 1$. In either case, using the fact that $t \ge 2$, one can verify that Δ_t is bounded by the expression given in 6. Therefore

$$\sum_{t=2}^{m} X_t = \sum_{t=2}^{m} (m-t+1)\Delta_t$$

$$\leq \sum_{t=2}^{m} (m-t+1) \left[8f_t(t^2+4tF+t+2F+8f_t) + (t^2-t+1) + 8F^2 + 6Ft \right]$$

$$= \sum_{t=2}^{m} (m-t+1) \left[8f_tt^2 + (t^2-t+1) \right]$$

$$+ \sum_{t=2}^{m} (m-t+1) \left[8f_t(4tF+t+2F+8f_t) + 8F^2 + 6Ft \right]$$

By replacing t or m - t + 1 with m and replacing f_t with F, the second summation can be upper bounded by $72F^2m + 18Fm^2$. The dominant term in the expression above is from the $8t^2f_t$ term. Using the fact that $\sum_{t} f_t \leq F$ and $t \leq m$, we can bound

$$\sum_{t=2}^{m} 8(m-t+1)t^2 f_t \leq \sum_{t=2}^{m} 8t^2 f_t + \max_t 8F(m-t)t^2 \leq 8Fm^2 + 8(4/27)Fm^3 \leq 8Fm^2 + 2Fm^3$$

The expression in the max function is maximized for t = 2m/3. Therefore:

$$\sum_{t=2}^{m} X_t \le 2Fm^3 + 72F^2m + 26Fm^2 + \sum_{t=2}^{m} (m-t+1)(t^2 - t + 1)$$

Putting this bound together with the bound from (5):

$$\sum_{t=1}^{m} |S_t| \le 2Fm^3 + 83mF^2 + 27Fm^2 + \sum_{t=2}^{m} (m-t+1)(t^2 - t + 1)$$

Now we turn to the fault-free tiling. For $t \ge 2$, in the first row of \bar{S}_t , there are t-1 intervals of sizes $t, t-1, \ldots, 2$. Therefore $X_2 = 3$ and $\Delta_t = 1 + \sum_{j=1}^{t-1} 2j = t^2 - t + 1$. Letting $m = \mu(N) - 12F$, we want to show that

$$2Fm^3 + 83mF^2 + 27Fm^2 + \sum_{t=2}^{m} (m-t+1)(t^2+t+1) \le \sum_{t=2}^{m+12F} (m+12F-t+1)(t^2-t+1)$$

We will lower bound the difference of the two summations:

$$\sum_{t=2}^{m+12F} (m+12F-t+1)(t^2-t+1) - \sum_{t=2}^{m} (m-t+1)(t^2-t+1)$$

$$\geq \sum_{t=2}^{m} 12F(t^2-t+1) + \sum_{j=1}^{12F} (12F-j+1)[(m+j)^2-(m+j)+1]$$

$$\geq 12F\left(\frac{m^3}{3} - \frac{m}{3}\right) + [(m+1)^2 - (m+1) + 1] \sum_{j=1}^{12F} (12F-j+1)$$

$$\geq 4Fm^3 - 4Fm + 72F^2(m^2+m+1)$$

$$\geq 2Fm^3 + 83mF^2 + 27Fm^2$$

_		
_		
_		
_		
_		

4.5 Upper Bound on the Length of a Row

Layer 3 of the construction for Parity Weighted Tiling and Function Weighted Tiling uses a Turing Machine that sweeps across all of the non-blank symbols. In order to establish that this Turing Machine completes its work in N steps, we need an upper bound on the length of a row as a function of N and the number of faults in Layer 1. In this section we present the upper bound on the length of a row required for this analysis. Note that this section is not used in the proof of Gapped Weighted Tiling. We present these bounds here because they use the definition for the function X which is developed in the previous section.

Lemma 4.11 [Lower Bound on the Change in X] Consider any two consecutive segments which end at rows r_a and r_b , respectively. Then $X(r_b) - X(r_a) \ge -2l(r_a)$. If r_a and r_b are no-cost rows (meaning the segment ending in row r_b is a complete segment, then $X(r_b) - X(r_a) \ge w(r_a)^2$.

Proof: In a complete segment, the size of each segment increases by 1 and there is a new segment of size 2 added to the right end. Therefore the sequence (s_1, s_2, \ldots, s_m) becomes $(s_1 + 1, \ldots, s_m + 1, 2)$. Therefore the value of X goes from

$$\sum_{j=1}^{m} [2j(s_j - 1) + 1] \quad \text{to} \quad \sum_{j=1}^{m} [2js_j + 1] + 2(m+1) + 1$$

The overall increase is $\sum_{j=1}^{m} 2j + 2m + 3 \ge (m+1)^2$. The length of row r_a is equal to m+1, so the value of X increase by at least $w(r_a)^2$.

Consider a sequence of of rows that do not contain any invalid squares. This sequence of rows represent correctly executed steps of the Turing Machine applied to a valid row. Each iteration of the inner loop causes one of the intervals to increase in size and the other intervals to remain the same which can only increase X. The only point at which the value of X can decrease is when the head is moving right as it inserts a new blank symbol into an interval. As the rest of the tape symbols are moved to the right, one interval which holds the current location of the head can be temporarily decreased in size by 1. This can decrease the value of X by at most 2m. By the time the head reaches the right end of the tape symbols, the sizes of all the intervals are at least their original size. This can contribute a decrease of at most $2(w(r_a) - 1)$. If the last row in the previous segment has non-zero cost, There may be tiles that change from one row to the next outside of a valid computation square. The worst case is if a tile of weight 2 changes to a tile of weight 0. This would cause three consecutive intervals of sizes s_j , $1, s_{j+2}$ to be merged into one interval of size $s_j + s_{j+2} + 1$. The net effect is that X can increase by at most four times the length of row r_a . Therefore, $X(r_b) - X(r_a) \ge -2(l(r_a) + w(r_a) - 1)$.

Lemma 4.12 [Upper Bound on the Number of Segments] If row r is the last row in a tiling in Layer 1 and F_1 is the number of illegal pairs or squares in Layer 1 of the tiling, then if $F_1 \leq N^{1/4}/40$, the number of segments in Layer 1 is at most $4N^{1/4} + 2F_1$.

Proof: Consider a complete segment. The weight of the row at the end of the segment is exactly one larger than the weight of the last row of the previous segment. At the end of the t^{th} segment, there have been $t - 2F_1$ such increases overall. Furthermore, none of the valid Turing Machine rules decrease the weight of a row, so in any valid computation square the weight of the two top tiles is at least the weight of the two bottom squares. The difference in weight between two vertically aligned tiles is at most two. The number of vertically aligned tiles that are not the same and are outside of valid computation squares is at most F_1 . Therefore the weight of any row after the first t segments is at least max $\{0, t - 4F_1\}$.

Let r be the row just before the beginning of a complete segment. Then the value of X increases by at least $w(r)^2$. This means that by the end of the t^{th} segment, the total increases that occurred during complete segments is at least

$$\sum_{j=1}^{t-2F_1} (t-4F_1)^2 \ge \frac{(t-6F)}{3}$$

In each incomplete segment, the value of X can decrease by at most 2(l+w+1), where l and w are an upper bounds on the length and weight of a row that has occurred so far. By Lemma 4.5, $l \leq 1 + 2tF_1 + t^2/2$ and $w \leq 1 + t + 2F_1$. Therefore the total decrease which has occurred so far in all the incomplete segments is at most $4F_1(2+2tF_1+t+2F_1+t^2)$. Therefore, by the end of the t^{th} segment, the value of X is at least

$$\frac{(t-6F)^3}{3} - 4F(2+2tF_1+t+2F_1+t^2)$$

. For $t \ge 3N^{1/4}$ and $F \le N^{1/4}/40$, then this function is at least $.15t^3$.

If a complete segment begins in row r, then by Lemma 4.6, the length of the segment is exactly X(r). If the total number of segments is larger than $4N^{1/4} + 2F_1$, then the total number of complete segments that happen after the first $3N^{1/4}$ segments is at least $N^{1/4}$. Each of these segments lasts for at least $.15(3N^{1/4})^3 \ge 4N^{3/4}$ rows. This contradicts the fact that there are at most N rows.

Lemma 4.13 [Upper Bound on the Length of a Row] If row r is the last row in a tiling in Layer 1 and F_1 is the number of illegal pairs or squares in Layer 1 of the tiling and $F_1 \leq N^{1/4}/40$, then $l(r) \leq 9N^{1/2} + 2N^{1/4} + 1$.

Proof: Lemma 4.5 gives an upper bound on the length of a row r at the end of the t^{th} segment as a function of F_1 and t. Plugging in the bound from Lemma 4.12 on t, we get that

$$\begin{split} l(r) &\leq 2tF_1 + 1 + \sum_{j=1}^t j \\ &\leq 1 + 2(4N^{1/4} + 2F_1)F_1 + \frac{(4N^{1/4} + 2F_1)(4N^{1/4} + 2F_1 + 1)}{2} \end{split}$$

When $F_1 \leq N^{1/4}/40$, the expression can lower bounded by $9N^{1/2} + 2N^{1/4} + 1$.

4.6 Clean and Corrupt Intervals

In order to track the sizes of the intervals, we will need a somewhat sophisticated definition, which will recursively designate each interval in row r_t clean or corrupt. Intuitively, a clean interval in row r_t is an interval that is unaffected by an illegal pair or square in rows r_0 through r_{t-1} . Each clean interval in a row is given a tag. The clean intervals within a row all have unique tags. The tags allow us to track the intervals while the intervals shift and grow as the computation progresses (extending upwards in the tiling). Lemma 4.17 then uses the lower bound on the number of complete segments from Section 4.4 (Lemma 4.10) to lower bound the number of clean intervals in the last row of Layer 1. Tagging the clean intervals will be useful so that we can argue more precisely about how the sizes of those intervals grow.

We are only be able to characterize the sizes of the clean intervals as faults can cause the sizes and number of an intervals to change in unpredictable ways. Consider for example an interval of size s and a fault which causes a B in the middle of that interval to change to an X in the following row. The interval of size s splits into two different intervals whose sizes sum to s + 1.

To write down the definition of *clean* and *corrupt* intervals, we need a notion of a distance between sequences of tiles:

Definition 15 [Row Distance on a Sequence of Locations] The distance between two tiling rows r and r' is the number of locations where r and r' differ and is denoted by d(r, r'). If S is a sequence of tile locations in a row of length N, and r and r' are two tiling rows, then $d_S(r, r')$ is the number of location in S where r and r' differ.

We will also need the following notation: For any valid row r, let next(r) denote the unique row that can be placed above r with no illegal squares. According to Lemma 3.2, next(r) represents the application of one step of the Turing Machine to row r.

Consider two consecutive rows in the tiling r and r'. If r is valid, then next(r) is well-defined and we want to assess whether a clean interval in row r remains clean in r' according to whether it is equal to the corresponding interval in next(r). On the other hand if r is not valid, then the row will not necessarily correspond to a valid Turing Machine configuration and there is not a well-defined expectation for what r' should be. In this case, we just compare r' to r in determining whether each clean interval in r remains clean in r'.

Definition 16 [Clean and Corrupt Intervals and Tags] r_0 is assumed to consist of all \Box tiles, so the definition of clean or corrupt starts with r_1 . For t = 1, ..., N - 1 the intervals in row r_t are designated as clean or corrupt, and the clean intervals will be tagged by positive integer numbers (which can be viewed as "names" of the clean intervals). This is done recursively, as follows.

First, a comparison row \tilde{r} is determined, the intervals in \tilde{r} are designated as clean or corrupt, and the clean intervals in \tilde{r} are tagged. This is then used to decide about the clean and corrupt intervals of r_t as well as the tags for the clean intervals in r_t . We consider three cases:

1. Case 1: t = 1. The comparison row \tilde{r} is set to be the correct starting row:

$$\Box \triangleleft (q_{e2}/\#) \{\#\}^{N-4} \Box$$

Since this row is correct, we already know the assignment of its clean and corrupt intervals: The only interval in \tilde{r} is $\triangleleft (q_{e2}/\#)$, which is designated as clean and assigned the tag 1.

- 2. Case 2: t > 1 and r_{t-1} is invalid. Then $\tilde{r} = r_{t-1}$. The intervals in r_{t-1} have recursively been designated as clean or corrupt. Moreover, the clean intervals have been assigned tags.
- 3. Case 3: t > 1 and r_{t-1} is valid. Then $\tilde{r} = next(r_{t-1})$. Order the intervals in r_{t-1} and $next(r_{t-1})$ from left to right. The jth interval in $next(r_{t-1})$ is given the same clean/corrupt designation as the jth interval in r_{t-1} . If the jth interval is clean, then the tag is also the same. Claim 4.14 below shows that since r_{t-1} is valid, the number of intervals in r_t is either the same or one larger than that of r_{t-1} . If $next(r_{t-1})$ has one more interval than r_{t-1} , then the new interval is the rightmost interval. The new interval is designated as clean and given the tag t.

We now use the designation of clean or corrupt intervals in \tilde{r} to determine which intervals are clean and corrupt in r_t . For each interval in r_t , let S be the sequence of tiles in that interval. If $d_S(r_t, \tilde{r}) > 0$, then the interval is corrupt in r_t . If $d_S(r_t, \tilde{r}) = 0$, then the interval adopts the same clean/corrupt designation as in \tilde{r} . If the interval is clean then it adopts the same tag as the corresponding interval in \tilde{r} .

The following Claim shows that Case 3 of the above definition is indeed well defined.

Claim 4.14 [Change in the Number of Intervals in One TM Step] If r is a valid row, then r and next(r) have the same number of intervals, except if r has the form $\Box \triangleleft \{B, X, \overline{X}\}^*(q_{e1}/\#)\{\#\}^* \Box$ in which case next(r) has a new interval. The new interval is the right-most interval in next(r) and has size 2.

Proof: By Fact 4.2, we know that the number of intervals is one less than the weight of the row. The only TM rule that increases the total weight of the tiles (namely, the only legal head square whose weight of top two tiles is bigger than that of its bottom two tiles) is $\delta(q_{e1}, \#) = (q_{e2}, X, R)$. By inspection of Figure 5, the

only valid row which has the tile $(q_{e1}/\#)$ as its head tile, is of the form $\Box \triangleleft \{B, X, \overline{X}\}^* (q_{e1}/\#)\{\#\}^* \Box$. Therefore if any other rule is applied, the number of intervals is the same between the two rows. Note that $(q_{e1}/\#)$ is a heavy tile so $(q_{e1}/\#)$ is the right end of the right-most interval in r. When the rule is applied, the two tiles $(q_{e1}/\#), \#$ in r become $X, (q_{e2}/\#)$ in next(r). Since X and $(q_{e2}/\#)$ are both heavy tiles, the interval to the left of the X does not change and the new interval has size 2.

In order to use the tags in Definition 16 to track intervals, we need the following lemma about the tags:

Lemma 4.15 [Interval Tags are Unique] Within a row r_t , all the tags of clean intervals are unique and $\leq t$. If a clean interval in r_t has a tag j < t, then there is a clean interval with tag j in row r_{t-1} .

Proof: By induction on t. There is only one possible clean interval in row r_1 . If row r_1 has that interval, then its tag is 1.

For the inductive step, suppose that r_{t-1} is invalid. Then in Definition 16, $\tilde{r} = r_{t-1}$. The only way for an interval to be clean in r_t is for that interval to be identical to a clean interval in r_{t-1} in which case the interval has the same tag in r_t as it does in r_{t-1} . If the intervals all have unique tags $\leq t - 1$ in r_{t-1} then they also have unique tags $\leq t$ in r_t .

If r_{t-1} is valid, then $\tilde{r} = \operatorname{next}(r_{t-1})$. There is a one-to-one correspondence (that preserves tags) between the clean intervals in $\operatorname{next}(r_{t-1})$ and the intervals in r_{t-1} , except for the fact that $\operatorname{next}(r_{t-1})$ might contain an additional new interval with tag t. If all the intervals in r_{t-1} are unique and $\leq t-1$, then all the intervals in $\operatorname{next}(r_{t-1})$ are unique and $\leq t$. The only way for an interval to be clean in r_t is for that interval to be identical to a clean interval in $\operatorname{next}(r_{t-1})$. If the tag of a clean interval in r_t is $\leq t-1$, then it corresponds to a clean interval in $\operatorname{next}(r_{t-1})$ whose tag is $\leq t-1$, which in turn corresponds to a clean interval in r_{t-1} .

Lemma 4.16 [Upper Bound on the Loss of Clean Intervals] The number of tags j such that there is a clean interval with tag j in r_t but there is no clean interval with tag j in r_{t+1} is at most $12h(r_t) + 6v(r_t)$.

Proof: By Lemma 3.2, if $h(r_t) + v(r_t) = 0$, then r_{t+1} is the same as $next(r_t)$, which means that r_{t+1} represents a correctly executed step of the Turing Machine on the configuration represented in the valid row r_t , and row r_{t+1} is also valid. Thus no clean intervals are lost from r_t to r_{t+1} , although it's possible that a clean interval with tag t + 1 is added in row r_{t+1} .

If $h(r_t) > 0$, then row r_t is not valid. By Definition 16, r_{t+1} is compared to r_t in determining which intervals in r_{t+1} are clean. Each clean interval in r_t that is unchanged in r_{t+1} remains clean in r_{t+1} . Therefore if a clean interval with tag j that is present in r_t does not appear in r_{t+1} , there must be a tile in the interval where r_t and r_{t+1} differ. Each tile in r_t is included in at most 3 intervals, so the number of intervals that are clean in r_t that are no longer clean intervals in r_{t+1} is at most $3d(r_t, r_{t+1})$, which by Claim 4.1 is at most $12h(r_t) + 6v(r_t)$.

Now suppose that r_t is valid $(h(r_t) = 0)$ but $v(r_t) > 0$. r_{t+1} is compared to $next(r_t)$ in determining which intervals are clean or corrupt. Every clean interval in r_t corresponds to a clean interval in $next(r_t)$ with the same tag. Every clean interval in $next(r_t)$ that fails to appear in r_{t+1} must contain a location where $next(r_t)$ and r_{t+1} differ. Since each tile participates in at most 3 intervals in $next(r_t)$, the number of clean intervals in r_t that are no longer clean intervals in r_{t+1} is at most $3 \cdot d(next(r_t), r_{t+1})$. We will now argue that $d(next(r_t), r_{t+1}) \leq 2(v_t)$.

 r_t and next (r_t) only differ in two locations. The other locations are all tape tiles. If one of these tape tiles in r_t is not the same in r_{t+1} , then those two vertically aligned tiles are in an illegal computation square. Now consider the legal head square resulting from putting next (r_t) on top of r_t . If either tile in the top row of this square differs from the two corresponding tiles in r_{t+1} then the head square is illegal. Therefore in

each location where $next(r_t)$ and r_{t+1} differ, the two vertically aligned tiles in r_t and r_{t+1} in that location are contained in an illegal computation square. Since each illegal computation square contains at most two pairs of vertically aligned tiles, the number of locations where $next(r_t)$ and r_{t+1} differ is at most $2(v_t)$.

Lemma 4.17 [Lower Bound on the Number of Clean Intervals] Let F_1 be the number of illegal squares or pairs in Layer 1 of a tiling of the $N \times N$ grid. Then the number of clean intervals in the last row of Layer 1 is at least $\mu(N) - 26F_1$.

Proof: By Lemma 4.10, the number of complete segments in Layer 1 is at least $\mu(N) - 14F_1$. Since each complete segment corresponds to an fault-free iteration of the Outer Loop and since one new clean interval is added in each iteration of the Outer Loop, the number of clean intervals that are created in Layer 1 is at least $\mu(N) - 14F_1$. Each of these clean intervals is tagged with the row number in which it first appears, which is the last row in that segment. Therefore, each of the $\mu(N) - 14F_1$ clean intervals created has a unique tag. By Lemma 4.16, the number of tags such there is a clean interval in some row r_{t-1} but no clean interval with tag j in row r_t is at most $12F_1$. Therefore the number of clean intervals in the last row of Layer 1 is at least $\mu(N) - 14F_1 - 12F_1 = \mu(N) - 26F_1$.

4.7 The Potential Function A

In addition to giving a lower bound on the number of clean intervals in a tiling, we will want to show that the sizes of those intervals do not deviate too much from the sizes of the intervals in a tiling with no illegal pairs or squares. In an fault-free computation, if the number of intervals at the end of an iteration of the Outer Loop is m, then the sizes of those intervals from left to right will be $m + 1, m, m - 1, \ldots, 2$. The function A captures the extent to which the interval sizes differ from this ideal case.

Definition 17 Consider a sequence of m positive integers s_1, \ldots, s_m .

$$A(s_1, \dots, s_m) = \sum_{j=1}^{m-1} |s_j - s_{j+1} - 1| + |s_m - 2|.$$

Note that $A(m+1, m, \ldots, 2) = 0$. It will also be convenient to refer to the value of A for a row in Layer 1 of a tiling. If the sizes of the intervals in row r (from left to right) is s_1, \ldots, s_m , then $A(r) = A(s_1, \ldots, s_m)$. If r does not have any clean intervals, then A(r) is defined to be 0.

The primary goal of the analysis in this section is to prove Lemma 4.22, which says that if r is the last row of Layer 1 in a tiling, and F_1 is the number of illegal pairs or squares in Later 1, then A is bounded by $3 + O(F_1)$.

4.7.1 Features of the function A

The analysis of each layer will bound the value of A by a constant times the number of illegal pairs and squares. At various points in the analysis, we will need to deduce features about the sequence of sizes of the clean intervals based on the bound for the value on the value of A. The following three technical lemmas describe the required features and argue that they follow from the bound on A.

Lemma 4.18 Consider a sequence s_1, \ldots, s_m such that each $s_i \ge 2$. Let S denote the set of integers occurring in the sequence s_1, \ldots, s_m with repetitions removed. Then

$$|\{2,\ldots,r\} - S| \le \max\{r - m - 1, 0\} + A(s_1,\ldots,s_m).$$

Proof: The value of $A(s_1, \ldots, s_m)$ is minimized if the s_i 's are sorted in decreasing order, so we will assume this is the case. Let S_m be the set of integers in the range from 2 through s_m . Define $N_{skip} = |S_m - S|$ and $N_{dup} = m - |S|$. If the sequence (s_1, \ldots, s_m) is sorted in decreasing order then value of $A(s_1, \ldots, s_m)$ is equal to $N_{skip} + N_{dup}$. Furthermore $s_m \ge m + 1 - N_{dups}$. If $r \le s_m$, then

$$|\{2,\ldots,r\}-S| \le N_{skip} \le A(s_1,\ldots,s_m)$$

If $r > s_m$, then

 $|\{2,\ldots,r\}-S| = r - s_m + N_{skip} \le r - m - 1 + N_{dup} + N_{skip} \le (r - m - 1) + A(s_1,\ldots,s_m)$

Lemma 4.19 Consider a sequence s_1, \ldots, s_m whose A value is at most d. Then at least (m-d)/2 of the s_j 's are at least at least (m-d)/2.

Proof: We will prove that if there less than (m-d)/2 of the s_j 's are at least at least (m-d)/2, then the value of A is strictly larger than d. The value of A is minimized when the sequence s_1, \ldots, s_m is sorted in non-increasing order, so we will also assume that the s_j 's are sorted accordingly.

If there are less than (m-d)/2 of the s_j 's in the sequence that are at least at least (m-d)/2, then there are more than m - (m-d)/2 = (m+d)/2 of the s_j 's that fall in the range from 1 to $\lfloor (m-d)/2 \rfloor$. This implies that there are more than d of the s_j 's such that $s_j = s_{j-1}$. Each such value contributes at least +1 to the sum defining A. Since all the terms in A are non-negative, the lemma follows.

Lemma 4.20 Consider a sequence s_1, \ldots, s_m . If $s_j = 1$ and s_j is removed from the sequence then the value of A for the sequence decreases. If any s_j is removed from the sequence, the value of A increase by at most 1.

Proof: If $s_1 = 1$ then the first term in the sum defining A is $|1 - s_2 - 1| = s + 2$. Since s_2 is positive, the value of A increases when s_1 is removed. If $s_m = 1$, the last two terms in the sum defining A are $|s_{m-1} - 1 + 1| + |2 - 1| = s_{m-1} + 1$. If s_m is removed, these two terms are placed by $|s_{m-1} - 2|$, which for positive s_{m-1} is less than $s_{m-1} + 1$.

Finally, we consider the case that j is neither, 1 nor m. When $s_j = 1$ is removed, the two terms $|1 - s_{j+1} - 1| + |s_{j-1} - 1| = s_{j+1} + |s_{j-1} - 2|$ are replaced by $|s_{j-1} - s_{j+1} - 1|$. If $s_{j-1} = 1$, then the original expression is $s_{j+1} + 1$ which is replaced by s_{j+1} and the sum decreases.

If $s_{j-1} > 1$, then $s_{j+1} + |s_{j-1} - 2| = s_{j+1} + s_{j-1} - 2$. Meanwhile the new expression $|s_{j-1} - s_{j+1} - 1|$ is maximized when $s_{j+1} < s_j$ in which case $|s_{j-1} - s_{j+1} - 1| < s_{j+1} + 1 - s_{j-1}$. We have that

$$s_{j+1} + |s_{j-1} - 2| = s_{j+1} + (s_{j-1} - 2) \ge s_{j+1} - (s_{j-1} - 2) > s_{j+1} + 1 - s_{j-1} \ge |s_{j-1} - s_{j+1} - 1|.$$

4.7.2 Bound on the value of A in a tiling

The analysis for Layer 1 must bound the value of A in the last row of Layer 1 as a function of the number of illegal squares and pairs in Layer 1. We start by analyzing a sequence of rows with no illegal pairs. Lemma 4.21 gives an upper bound on the amount by which A can increase over a sequence of fault-free steps (corresponding to no-cost rows). Then Lemma 4.22 gives an upper bound on A(r) as a function of the number of faults in all the rows below r in the tiling.

Lemma 4.21 [Upper Bound on the Increase in A Over a Sequence of No-Cost Rows] Consider a sequence of consecutive rows in a tiling of the $N \times N$ grid, beginning with row r_s and ending on row r_t . Suppose that the tiling from r_s through r_t does not contain any illegal pairs or squares. Then $A(r_t) \leq A(r_s) + 6$. If r_s is an end row then $A(r_t) \leq A(r_s) + 3$.

Proof: Each row proceeding upwards from r_s corresponds to one step in the computation of the Turing machine. All the intervals (clean and corrupt) will be numbered from left to right, and we will track the changes to the interval sizes by δ functions. So a $\delta(j) = +1$ would indicate that the j^{th} interval as increased in size by 1. Note that a change to interval j will only affect the value of A if j is a clean interval. We will use m to denote the number of clean intervals and M to denote the total number of intervals. Note that the number of intervals does not change in one iteration of the Outer Loop, except in the last step.

At the start of an iteration of the Inner Loop, the state is q_{IS} . We will call a row an IS[k] row, if the state is q_{IS} and the head is in interval k. Since the intervals overlap, the head could possibly be in two intervals at the same time, such as (q_{IS}/X) . In this case, we say that the head is in the interval to the left. In analyzing the sizes of the intervals, it doesn't matter where in interval k that the head begins. When the TM is in state q_{IS} , the head moves to the right past any B symbols until it reaches an X or a > tile at which point it changes state. Thus, in any consecutive sequence of rows in which the state is q_{IS} , the head remains in the same interval and the interval sizes do not change.

We will consider different subsequences of rows corresponding to different portions of an iteration of the Outer Loop.

- 1. The subsequence starts with an IS[k] row and ends with an IS[k+l] row. After the l-1 iterations of the inner loop, the intervals k through k+l-1 will have increased in size by 1 and all other interval sizes will stay the same: $\delta(k) = \delta(k+1) = \cdots \delta(k+l-1) = +1$.
- 2. The subsequence starts with an $\mathbf{IS}[k]$ row and ends before an $\mathbf{IS}[k+1]$ row is reached. If the head never reaches the right end of interval k, the intervals do not change. If the head sweeps past the right end of interval k, then the size of interval k increases by 1. $(\delta(k) = +1)$. If the sequence ends while the head is in interval j before reaching the \triangleright tile, then the left end of interval j has been moved over but the right end has not been moved over. The effect is that interval j has decreased in size by 1: $\delta(j) = -1$. If the subsequence ends after the head has reached the \triangleright tile, the state will be $q_{w\triangleleft}$ or q_{left} . In this case, all the tiles have been moved over and there is no $\delta(j) = -1$ change.
- 3. The subsequence starts in a row that is not an IS row and ends when the first IS[k] is reached. If the initial state in the subsequence is $q_{w\triangleleft}$ or q_{left} , then the head just moves left until it reaches a \overline{X} or \triangleleft symbol, at which point the state transitions to q_{IS} . The intervals do not change. If the head is in the middle of sweeping right, then the state is $q_{w\overline{X}}$, q_{wX} or q_{wB} . Suppose that the head starts in interval *i*. The size of interval *i* is increased as the head sweeps right. When the head has finished sweeping to the right, all the tiles have been moved over and the net effect is $\delta(i) = +1$.
- 4. The subsequence starts in the state q_{OS} and stops on or before IS[1]. The head sweeps left until reaching \triangleleft . The intervals do not change, so all δ 's are 0.
- 5. The subsequence starts in an IS[M] row and ends on or before the next end row. The head moves right until it reaches the \triangleright symbol. The tile (q_{IS}/ \triangleright) # become $B(q_{e1}/\#)$ which means that $\delta(M) = +1$. Then $(q_{e1}/\#)$ # become $X(q_{e2}/\#)$ which means a new interval of size 2 has been added. The last step in which $X(q_{e2}/\#)$ changes to $(q_{OS}/X) \triangleright$ does not change any of the intervals.

Let c_1, \ldots, c_m be the indices of the clean intervals in r_s . Let s_j denote the size of interval c_j . The value of A is:

$$A = \sum_{i=1}^{m-1} |s_i - s_{i+1} - 1| + |s_m - 2|.$$

We first consider the case in which r_s is a end row. If the sequence ends before the first Inner Loop begins, the net effect on A is 0 because none of the intervals change in size. Otherwise, the sequence can then go on to k complete iterations of the inner loop which causes the first k intervals to increase in size by 1. If a is the number of clean intervals among the first k intervals, then $\delta(c_1) = \delta(c_2) = \cdots \delta(c_a) = +1$, which can increase A by at most 1 because only the $|s_a - s_{a+1} - 1|$ term changes and that term can only change by 1. If the sequence goes on to an incomplete iteration of the Inner Loop, the next clean interval could have increased $(\delta(c_{a+1}) = +1)$ and the change to A is still at most 1. It's also possible that the sequence ends while the head is sweeping right, in which case $\delta(c_j) = -1$ for some clean interval c_j . This can increase A by an additional +2 for a total increase of +3. If the sequence completes all the Inner Loops, then all the clean intervals will have increased in size. In this case, none of the terms inside the sum in the expression for A change. However the last term $|s_m - 2|$ will increase by 1. Finally, if the sequence completes the entire Outer Loop, an additional interval of size 2 is added to the end, so there is a new $s_{m+1} = 2$. The net effect on A from the beginning of the sequence is 0.

$$A(r_t) - A(r_s) = (|(s_m + 1) - s_{m+1} - 1| + |s_{m+1} - 2|) - |s_m - 2| = 0.$$

Thus if r_s is a end row, and the sequence ends before the next end row, A can increase by at most 3. Moreover if the sequence is one complete iteration of the outer loop (i.e. if r_s and r_t are end rows), then $A(r_t) - A(r_s) = 0$.

Now suppose that the sequence begins in an arbitrary location in the middle of the middle of the Outer Loop. The worst case, is that the sequence starts during a right sweep in an inner loop. There is possibly a $\delta(i) = +1$ if the head starts out in a clean interval which is increased as the head sweeps right. (A can increase by at most +2.) Then after a one or more complete iterations of the Inner Loop, a consecutive sequence of clean intervals could have increased in size by 1. (A can increase again by at most +2.) Then the sequence can end in the middle of an iteration of the inner loop in which case, there could also be a $\delta(j) = -1$ for the interval where the head ends up. (Another increase to A of at most +2.) The total increase to A is bounded by 6. Thus, if the sequence does not contain any end rows (i.e. the sequence is contained within one iteration of the Outer Loop), then the increase to A is at most 6.

If the sequence begins at an arbitrary location in the middle of the Outer Loop and completes the Outer Loop (i.e. ends on an end row), then there could be a $\delta(i) = +1$ if the head starts out in a clean interval which will be increased as the head sweeps right. (A can increase by at most +2.) In addition, the next iterations of the Inner Loop will start with some interval k and increase all the intervals to the right of k, this will result in $\delta(c_a) = \delta(c_{a+1}) = \cdots = \delta(c_m) = +1$ and finally, a new clean interval of size 2 will be added to the right end. These changed can increase A by at most 1 because only the $|s_{a-1} - s_a - 1|$ term increases by 1. The effect of increasing the last clean interval by 1 and adding a new interval of size 2 cancels out as argued above. Thus if the sequence starts in the middle of an Outer Loop and runs to the end of the Outer Loop, A increases by at most 3.

We have argued that if the sequence from r_s through r_t does not contain any end rows (i.e. the sequence is contained within one iteration of the Outer Loop), then the increase to A is at most 6. If sequence does contain an end row, let r_a be the first end row and r_b be the last end row of the sequence. Since going from end row to end row, does not change the value of A, $A(r_b) - A(r_a) = 0$. A sequence that is contained in an Outer Loop and ends on a end row increases A by at most 3, so $A(r_a) - A(r_s) \leq 3$. A sequence that is contained in an Outer Loop and begins with an end row increases A by at most 3, so $A(r_t) - A(r_b) \leq 3$. Putting the inequalities together gives that $A(r_t) - A(r_s) \leq 3$. Lemma 4.22 For any $t \ge 1$,

$$A(r_t) \le 3 + 12[h(r_{t-1}) + v(r_{t-1})] + \sum_{j=2}^{t-2} 18[h(r_j) + v(r_j)].$$

Proof: By induction on t. Base case: r = 1. The only possible clean interval in row r_1 is $\triangleleft (q_{e2}/\#)$. If r_1 has this clean interval, then $A(r_1) = |s_1 - 2| = 0$. If r_1 does not have any clean intervals, then $A(r_1) = 0$ by definition.

Inductive step: Suppose the intervals in r_t are determined by comparison to row \tilde{r} . Every clean interval in r_t corresponds to a clean interval in \tilde{r} . The only way A can change from \tilde{r} to r_t is if a clean interval is removed. Each location where r_t and \tilde{r} differ can remove at most three clean intervals from \tilde{r} to row r_t . Each removed clean interval can increase A by at most 1. If s_j , s_{j+1} , and s_{j+2} are the sizes of three consecutive clean intervals in \tilde{r} and the interval of size s_{j+1} is not present in r_t then:

$$|s_{j+2} - s_j - 1| \le |s_{j+2} - s_{j+1} - 1| + |s_{j+1} - s_j| \le |s_{j+2} - s_{j+1} - 1| + |s_{j+1} - s_j - 1| + 1.$$

Therefore $A(r_t) - A(\tilde{r}) \leq 3d(\tilde{r}, r_t)$.

Case 1: r_{t-1} is invalid. Then $\tilde{r} = r_{t-1}$.

$$A(r_t) - A(r_{t-1}) = A(r_t) - A(\tilde{r}) \le 3d(\tilde{r}, r_t) \le 6v(r_{t-1}) + 12h(r_{t-1})$$

The last inequality is due to by Claim 4.1.

Case 2: r_{t-1} is valid and there is an illegal square in rows r_{t-1} and r_t . Since r_{t-1} is valid, $\tilde{r} = \text{next}(r_{t-1})$. If we were to put row $\text{next}(r_{t-1})$ on top of row r_{t-1} , the two rows would not contain any illegal pairs or squares and would therefore satisfy the conditions of Lemma 4.21. So $A(\text{next}(r_{t-1})) - A(r_{t-1}) \leq 6$.

Every location where $next(r_{t-1})$ and r_t differ must be contained in at least one illegal square and a square contains two locations. To see why this is true, consider placing $next(r_{t-1})$ over r_{t-1} . The two rows do not contain any illegal pairs or squares. Since r_{t-1} is valid, there is exactly one head square that contains the head tile in the two rows. If r_t differs from $next(r_{t-1})$ at eiher of those two locations, then the square must be illegal. In all other locations, r_{t-1} and $next(r_{t-1})$ contain the same tape tile. If r_t differs from the $next(r_{t-1})$ in any of those locations, then that would correspond to two vertically aligned tape tiles that are not the same. Any such vertically aligned pair is contained in two illegal squares.

Therefore

$$A(r_t) - A(\operatorname{next}(r_{t-1})) = A(r_t) - A(\tilde{r}) \le 3d(\operatorname{next}(r_{t-1}), r_t) \le 6v(r_{t-1}).$$

Putting the two inequalities together and using the fact that $v(r_{t-1}) \ge 1$, we get that

$$A(r_t) - A(r_{t-1}) \le 6v(r_{t-1}) + 6 \le 12v(r_{t-1}).$$

Case 3: Rows r_0 through r_t do not have any illegal pairs or squares. Then r_1 is an end row. By Lemma 4.21, $A(r_t) - A(r_1) \le 3$. Since $A(r_1) = 0$, then $A(r_t) \le 3$.

Case 4: $v(r_{t-1}) + h(r_{t-1}) = 0$ and there is a $0 \le p \le t-2$ such that $v(r_p) + h(r_p) > 0$. Let p be the largest p such that $p \le t-2$ and $v(r_p) + h(r_p) > 0$.

The rows r_{p+1} through r_t do not contain any illegal pairs or squares. By Lemma 4.21, $A(r_t) - A(r_{p+1}) \le 6$. By the inductive hypothesis,

$$A(r_{p+1}) \le 3 + 12[h(r_p) + v(r_p)] + \sum_{j=2}^{p-1} 18[h(r_j) + v(r_j)]$$

Therefore, using the fact that $v(r_p) + h(r_p) \ge 1$ and $p \le t - 2$, we have that

$$\begin{aligned} A(r_t) &\leq 6 + 3 + 12[h(r_p) + v(r_p)] + \sum_{j=2}^{p-1} 18[h(r_j) + v(r_j)] \\ &\leq 3 + 18[h(r_p) + v(r_p)] + \sum_{j=2}^{p-1} 14[h(r_j) + v(r_j)] \\ &\leq 3 + \sum_{j=2}^{t-2} 18[h(r_j) + v(r_j)] \end{aligned}$$

We can put Lemmas 4.17 and 4.22 together to get the following Lemma which summarizes what is needed from the analysis of Layer 1 for the next Layer. In particular Lemma 4.23 bounds the number of interval sizes in the range 2 through $\mu(N) + 1$ not represented in the last row of Layer 1.

Lemma 4.23 [Bound on the Number of Missing Interval Sizes] Consider a tiling of the $N \times N$ grid. Let r be the tiling in the last row of Layer 1. Let S denote the set of integers such that $s \in S$ if there is a clean interval of size s in row r. Let F_1 denote the total number of faults in Layer 1. Then

$$|\{2, 3, \dots, \mu(N) + 1\} - S| \le 44F_1 + 3$$

Proof: Let (s_1, \ldots, s_m) denote the sizes of the clean intervals, from left to right, in row r. We can remove all the intervals of size 1 and according to Lemma 4.20, the value of A for that sequence will only decrease. Since the size of the remaining intervals is at least 2, we can apply Lemma 4.18 with $r = \mu(N) + 1$,

$$|\{2,\ldots,\mu(N)+1\} - S| \le \max\{\mu(N) - m, 0\} + A(s_1,\ldots,s_m).$$

By Lemma 4.17, m, the number of clean intervals in the last row of Layer 1 is at least $\mu(N) - 26F_1$, and therefore $\max\{\mu(N) - m, 0\} \le 26F_1$. Since $F_1 = \sum_{t=0}^{N-1} [h(r_t) + v(r_t)]$, by Lemma 4.22, the value of $A(s_1, \ldots, s_m)$, which is the value of A for the last row of Layer 1 is at most $18F_1 + 3$.

4.8 Characterizing the intervals in an fault-free tiling

In order to compare a tiling with faults to an fault-free tiling, we will eventually need to characterize the sequence of interval sizes in an fault-free tiling. At the end of every iteration of the outer loop, the sequence of intervals starts at some number m and decreases by 1, going from left to right, until the last interval which has size 2. In the middle of an iteration of the Outer Loop, the sequence of interval lengths can differ slightly from this ideal case. The extent of the difference is characterized in the lemma below.

Lemma 4.24 [The Sequence of Interval Sizes in a Fault-Free Tiling] Consider a row r that represents the configuration of the Turing Machine in an fault-free execution in which the TM is in the m^{th} iteration of the Outer Loop. The number of intervals in r is m. Define the set S such that $j \in S$ if and only if there is an interval of size j in row r.

- 1. The sizes of the intervals form a non-increasing sequence from left to right.
- 2. There are at most two intervals with the same size and the largest size only appears once.

3. $S \subseteq \{1, 2, \dots, m+2\}$ 4. $|\{2, \dots, m+2\} - S| \le 2$

Proof: The Turing Machine starts with one interval of size 2. After m-1 complete iterations of the Outer Loop, m-1 intervals have been added, for a total of m intervals. The sizes of those intervals is $(m+1, m, \ldots, 2)$. This sequence satisfies properties 1 through 4. Now consider the next execution of the Outer Loop. After the j-1 complete iterations of the Inner Loop, the leftmost j-1 intervals have increased in size by 1, so the sequence is $(m+2, m+1, \ldots, m-j+4, m-j+2, m-j+1, \ldots, 2)$. This sequence also satisfies 1 through 4. At this point $s_{j-1} = m-j+4$ and $s_j = m-j+2$.

In the middle of the j^{th} iteration of the Inner Loop, the intervals stay the same as the head sweeps left. When the head reaches the left end of interval j, it sweeps right and increases the size of that interval by 1 when it reaches the right end of the interval. As the head sweeps to the right moving all the tape symbols over by 1, one of the intervals to the right of interval j is decreased temporarily by 1. So if $\vec{s} =$ $(m+2, m+1, \ldots, m-j+4, m-j+3, m-j+1, \ldots 2)$ and \vec{t} is the current sequence, then $s_i = t_i$, except for one $k \in j+1, \ldots, m$ where $t_k = s_k - 1$. The sizes are non-increasing from left to right (property 1). The only two intervals with the same size are t_k and t_{k+1} (property 2). All numbers are in the range $\{1, 2, \ldots, m+2\}$ (property 3), and the two numbers in the range $\{1, 2, \ldots, m+2\}$ which are not in S are m - j + 2 and s_k (property 4).

After *m* iterations of the inner loop, the sequence of interval sizes is $(m+2, m+1, \ldots, 3)$. The next iteration of the Outer Loop begins when an interval of size 2 is added to the right end.

Lemma 4.25 [Bounds on $\mu(N)$] The function $\mu(N) \ge N^{1/4}/2$. In addition $\mu(N)$ is $O(N^{1/4})$ and the exact value of $\mu(N)$ can be computed in time that is poly-logarithmic in N.

Proof: In an fault-free tiling, the number of intervals increases by 1 whenever an end row is reached. Row r_1 is an end row which has one interval. After the t^{th} end row, there are t intervals, of sizes $t+1,\ldots,2$. By Lemma 4.6, the number of rows until the next end row is $\sum_{j=1}^{t} [2j(s_j-1)+1]$, where the sizes of the intervals s_1,\ldots,s_t are numbered from left to right. Plugging in $s_j = t - j + 2$, for $j = 1,\ldots,t$ gives $\sum_{j=1}^{t} [2j(t-j+1)+1]$. Thus $\mu(N)$ is the largest value of m such that

$$1 + \sum_{t=1}^{m-1} \sum_{j=1}^{t} [2j(t-j+1)+1] \le N-2.$$
(7)

Let f(m) be defined to be

$$f(m) = \sum_{t=1}^{m-1} \sum_{j=1}^{t} [2j(t-j+1)+1] = \sum_{t=1}^{m-1} \left[\frac{1}{3}t^3 + t^2 + \frac{5}{6}t\right].$$

Note that $f(m) = \Theta(m^4)$. Therefore there is a constant c such that if $m \ge cN^{1/4}$, then $f(m) \ge N$ which means that $\mu(N) = O(N^{1/4})$. To get the more precise lower bound on $\mu(N)$:

$$f(m) = \sum_{t=1}^{m-1} \left[\frac{1}{3}t^3 + t^2 + \frac{5}{6}t \right] \le \frac{13}{6}(m-1)^4 = \frac{13}{6}[m^4 - 4m^3 + 6m^2 - 4m + 1] \le \frac{13}{2}m^4 - 3.$$

If $\mu(N) = N^{1/4}/2$, then f(m) + 1 < N-2, which means that $\mu(N) \ge N^{1/4}/2$. Finally, since f(m) has a closed form that is a degree 4 polynomial in m, it is possible to binary search on the range $N^{1/4}/2 \le m \le cN^{1/4}$ to find the larges value m for which the Inequality (7) holds. The number of iterations is $O(\log N)$ and computing the value of f(m) can be done in time that is polynomial in $\log N$.

5 $\Theta(N^{1/4})$ -Gapped Weighted Tiling is NEXP-complete

Containment is straight-forward since given a number N expression in binary and a tiling of an $N \times N$ grid, which is exponential in log N, the size of the input the cost of the tiling can be computed in $O(N^2)$ time and it can be verified whether the cost of the tiling is 0 or at least $cN^{1/4}$ for some constant c.

To establish the hardness of the Gapped Weighted Tiling Problem, we will show for and arbitrary $L \in$ NEXP, a reduction to a translationally invariant 2D Tiling with an $n^{1/4}$ gap. Specifically, we will show a finite set of tiling rules so that, by a polynomial time computable function $x \to f(x) = N$,

- If $x \in L$, then there is a 0 cost tiling of an $N \times N$ grid using the tiling rules.
- If $x \notin L$, then any tiling of an $N \times N$ grid has cost at least $\Omega(N^{1/4})$.

Since $L \in \text{NEXP}$, there is an exponential time verifier V that can verify that a string $x \in L$ given a witness whose size is exponential in |x|. We will assume that on input x, if |x| = n, then the verifier V runs in time and space at most $2^{\delta n}$, including the space required for the witness. This can be achieved by padding:

Claim 5.1 [Padding Argument] If LNEXP, then for any constant δ , L is polynomial-time reducible to $L' \in NEXP$ such that the verifier V' for L' uses time and space $2^{\delta n}$.

Proof: Suppose that the verifier for L uses time (and space) at most 2^{cn} . Define a new language L'

$$L' = \{x0^{dn} | x \in L \text{ and } |x| = n\},\$$

where $d = c/\delta - 1$. A verifier V' for L' will first make sure there are the correct number of 0's at the end of the input, then will erase the 0's (incurring a small overhead). Then V' will simulate V on x. The running time is close to 2^{cn} . The length of the input is (d + 1)n. So as long as $c = \delta(d + 1)$, the running time will be $n^{\delta(d+1)n}$.

The large cost for $x \notin L$ is achieved by $\Theta(N^{1/4})$ independent computations, each of which will run the verifier for L on the input x. First we need to establish that there are enough intervals created in Layer 1 that are wide enough to simulate the execution of the verifier. Lemma 5.2 shows that the analysis provided in Section 4 is sufficient to establish that there will be at least $N^{1/4} - O(F_1)$ intervals of size at least $N^{1/4}$.

Lemma 5.2 [Results From Layer 1] Consider a tiling of Layer 1 and let F_1 be the total number of illegal pairs or squares in the tiling. Then there are at least $N^{1/4}/4 - 44F_1 + 3$ clean intervals of size at least $N^{1/4}/4$.

Proof: Let (s_1, \ldots, s_m) be the sequence of sizes of the clean intervals in a tiling of Layer 1. Lemma 4.23 says that the number of integers in the range $2, \ldots, \mu(N)$ that are not present in the sequence (s_1, \ldots, s_m) is at most $44F_1 + 3$. By Lemma 4.25, $\mu(N) \ge N^{1/4}/2$, so there are at least $N^{1/4}/4$ numbers in the range $2, \ldots, \mu(N) + 1$ of value at least $N^{1/4}/4$. At most $44F_1 + 3$ are missing. Therefore the number of clean intervals of size at least $N^{1/4}/4$ is at least $N^{1/4}/4 - 44F_1 + 3$.

It now remains to give the description of the constructions for Layers 2 and 3.

5.1 Layer 2

Since Layer 1 runs bottom to top and Layer 2 runs top to bottom, the only interaction between Layers 1 and 2 takes place in r_{N-2} , which is the last row for Layer 1 and the first row for Layer 2. The translation rules

from Layer 1 to Layer 2 will ensure that the heavy tiles from Layer 1 are copied as X tiles in Layer 2. Thus, the intervals in Layer 2 will have an X on each end.

The Layer 2 tiling rules also enforce that an X tile must go above an X tile and can not be placed above any other tile. This implies that in a no-cost tiling, the X tiles form columns of X's in Layer 2. In the vertical strip of tiles between each column of X's, there will be an independent Turing Machine computation. The tiling rules will enforce that the head of each Turing Machine stays within it's strip.

The tile types for Layer 2 include \Box , X, and #. Any square in which X is directly above or below a tile that is not X or \Box is illegal. Similarly for #, any square in which # is directly above or below a tile that is not # or \Box is illegal. Since the \Box tiles are only around the perimeter of the grid, the X's and the #'s must form columns in the interior of the grid. An example is shown in Figure 7.



Figure 7: A schematic of a Layer 2 tiling. Each strip between the column of X's will contain a tiling corresponding to an independent Turing Machine computation. In the example shown here, there are three independent computations.

There will also be tile types representing the execution of a Turing Machine in between the two columns of X tiles. The tape symbols for the Turing Machine will be $\{S, 0, 1, B, T\}$ and the states will be $\{q_r, q_l\}$. Thus, there will be tile types for each of the tape symbols (called *tape* tiles) and tile types for state-symbol pairs (called *head* tiles) of the form (q/c) where q is a state and c is a tape symbol.

The relationship between Layer 1 and 2 tiles is summarized below. The rules will enforce the condition that for any tile directly below a \Box tile, if the tile type in Layer 1 is as indicated on the left, then the tile type for Layer 2 must be one of the choices on the right.

$$\begin{array}{rcl} \# & \to & \# \\ \text{Tile type } t \neq \# \text{ and } w(t) > 0 & \to & X \\ \text{Tile type } t \neq \# \text{ and } w(t) = 0 & \to & B \text{ or } (q_l/S) \text{ or } T \end{array}$$

The translation rules enforce that the intervals in the last row of Layer 1 are preserved in the first row of Layer 1, except for intervals of size 1 which correspond to a tile of weight 2 in Layer 1.

In addition, Figure 8 shows the initialization rules for Layer 2. The meaning of the graph is that any square with $\Box \Box$ in the top row and two Layer 2 tiles $t_1 t_2$ in the bottom row that do not correspond to an edge from t_1 to t_2 in the graph is illegal. This resolves the ambiguity in whether a weight-0 tile in Layer 1 gets copied to a B, T, or a (q_l/S) . If an interval has no illegal initialization squares, the interval could be X X or X T X. These are the only possibilities for intervals of size 2 or 3. If an interval has has no illegal initialization squares and has size at least 4, the the interval must have the form $X (q_l/S) B^* T X$.



Figure 8: These rules constrain the contents of the first row in Layer 2.

Figure 9 shows and example of a possible last row for Layer 1 and its correct translation to the first row of Layer 2.



Figure 9: An example showing the last row from Layer 1 and its correct translation to the first row of Layer 2. The intervals in the two rows are shown with arrows. Every interval in Layer 1 is translated to an interval of equal size in Layer 2, except for the interval of size 1.

The Turing Machine that is executed within each strip continually increments a binary counter that is written in reverse on the tape. We call this the Binary Counter Turing Machine. The rules are summarized below.

 $\begin{array}{lll} \delta(q_l,S) &=& (S,q_r,R) \\ \delta(q_r,1) &=& (0,q_r,R) \\ \delta(q_r,b) &=& (1,q_l,L) \text{ for } b \in \{0,B\} \\ \delta(q_l,b) &=& (b,q_l,L) \text{ for } b \in \{0,1\} \\ \delta(q,T) &=& (T,q,-) \text{ for } q \in \{q_r,q_l\} \end{array}$

In a single iteration, the head starts pointing to the S in state q_l . It transitions to q_r and moves right. The

head then moves right (in state q_r) changing 1's to 0's until a 0 or B is encountered. The 0 or B is overwritten with 1 and the head transitions to q_l and moves left until the S is reached again. If the head ever reaches the T symbol at the right end of the interval, the Turing Machine hits an infinite loop and never changes state again.

The TM rules are translated into legal and illegal squares as described in Section 2.2. The X tile is treated as a tape symbol. For example, the rule $\delta(q_l, S) = (S, q_r, R)$ would mean that the square shown is legal. (Recall that the computation for Layer 2 goes from top to bottom.)

X	(q_l/S)
X	S

The rule $\delta(q_r, T) = (T, q_r, -)$ would mean that the square shown is legal.

(q_r/T)	X
(q_r/T)	X

The tape symbol S prevents the head from trying to move left into the X on the left and the symbol T prevents the head from moving into the X on the right. Thus, if the strip is not wide enough for the computation, the head reaches the T symbol and the computation eventually gets stuck and does not advance. This does not cause any additional cost, so for every strip in which the computation starts in configuration $(q_l/S) B^* T$, there is always a unique way to tile that strip so that it does not contain any illegal squares.

If the goal is to produce a string x in the last row of Layer 2, one could calculate the number N such that after N-3 steps, the Turing Machine is in state (q_l/S) and contents of the counter is x. Note that the contents of the counter always ends in 1, so in order to produce an arbitrary string x, one can produce x1 and then ignore the last bit. The lemma below implies that the function mapping x to N is polynomial time computable and is the function used for the reduction.

Lemma 5.3 [Number of Steps Use by the Binary Counter TM] Consider a binary string x. Let x^R denote the reverse of the string x. Let n(1x) be the value of the number whose binary representation is 1x and let w(x1) denote the number of 1's in the string x1. Then the number of steps required by the Binary Counter Turing Machine to write the string x and end up with the head pointing to S is $4n(1x^R) - 2w(x1)$.

Proof: Let f(n) be the number of steps until the Turing Machine ends up in configuration $(q_l/S) \ 0^n \ 1$. f(0) = 2. In order to end up in configuration $(q_l/S) \ 0^n \ 1$, the BCTM must first reach $(q_l/S) \ 1^n \ B$. Then it takes 2(n+1) steps to complete the next increment step and reach $(q_l/S) \ 0^n \ 1$. The number of steps to reach $(q_l/S) \ 1^n \ B$ is $f(n-1) + f(n-2) + \cdots + f(0)$. Therefore the function f obeys the recurrence:

$$f(n) = \sum_{j=0}^{n-1} f(j) + 2(n+1).$$

The solution to this recurrence relation is $f(n) = 2(2^{n+1} - 1)$. If the bits of x are numbered from left to right $x_1x_2\cdots x_n 1$, then the number of steps to reach $(q_l/S) x$ is

$$2(2^{n+1}-1) + \sum_{j=1}^{n} x_j \cdot 2(2^j-1) = 4 \cdot 2^n + \sum_{j=1}^{n} 4x_j \cdot 2^{j-1} - 2w(1x) = 4n(1x^R) - 2w(x1).$$

5.1.1 Layer 2 Intervals

We now need to extend the definition of intervals, as well as clean and corrupt intervals to Layer 2. In Layer 2, an interval begins with an X tile and extends to the right up to and including the next X tile. Note that since heavy tiles on Layer 1 get translated to X's on Layer 2, the intervals of size greater than 1 stay intact if the translation is done correctly.

The translation is done at the top end of the grid, so the last row for Layer 1, which is also the first row for Layer 2, is row r_{N-2} . Row r_{N-1} is the top row of the grid which contains all \Box tiles. An interval in the first row of Layer 2 is clean if the interval does not contain any illegal translation or initialization squares spanning rows r_{N-2} and r_{N-1} and the corresponding interval in the last row of Layer 1 was also clean. Otherwise the interval is corrupt. Lower down in the tiling, an interval in a row of Layer 2 is clean if the sequence of tiles is also a clean interval in row above it and there are no illegal computation squares spanning the two consecutive rows in that interval. Since clean intervals do not move or change in size, two clean intervals in rows r_t and r_{t+1} have the same tag (i.e. they "correspond") if they occupy the same set of locations in their respective rows.

Let F_2 be the number illegal squares in Layer 2 of a tiling plus the number of illegal translation and initialization squares between Layers 1 and 2.

Lemma 5.4 [Number of Clean Intervals Lost from Layer 1 to Layer 2] Let T_1 be the set of tags corresponding to clean intervals of size at least 2 in the last row of Layer 1. Let T_2 be the set of tags corresponding to clean intervals in the last row of Layer 2. Then $T_2 \subseteq T_1$ and $|T_1 - T_2| \leq F_2$. The size and location of a clean interval with tag j is the same in the last row of Layer 1 and any row in Layer 2.

Proof: We will account for any changes in the set of clean intervals from the last row of Layer 1 to the first row of Layer 2 by illegal translation squares in each interval. Note since two neighboring intervals only overlap on one tile, an illegal square can be contained in at most one interval.

If an interval of size at least 2 is clean in the last row of Layer 1 then that sequence of tiles consists of a heavy tile, followed by a sequence of weight-0 tiles, followed by a final heavy tile. Since heavy tiles are translated into X tiles and weight-0 tiles are translated into non-X tiles, then if the sequence is correctly translated, it results in an interval in the first row of Layer 2. In this case, the two intervals occupy the same locations in the row and have the same tag. If a clean interval at the end of Layer 1 does not correspond to a clean interval in Layer 2, then the interval must contain an illegal translation square.

Similarly, consider a clean interval in row r_t of Layer 2. The interval starts with an X, is followed be a sequence of non-X tiles, and finally ends with an X tile. If there are no illegal squares in the interval spanning rows r_t and r_{t-1} , then in row r_{t-1} , the sequence begins and ends with X and only has non-X tiles in between and therefore corresponds to an interval. This follows from the fact that any square with an X tile above or below a non-X tile is illegal. The interval is clean in r_t only if the interval is clean in r_{t-1} in which case the two intervals occupy the same set of locations in their respective rows and have the same tag. A clean interval in row r_t that does not correspond to a clean interval in row r_{t-1} , must contain an illegal computation square spanning rows r_t and r_{t-1} .

Lemma 5.5 [Contents in Each Clean Interval at the End of Layer 2] Consider a tiling of an $N \times N$, where $N = 4n(1x^R) - 2w(x1) + 3$ for some binary string x. Then every clean interval in the last row of Layer 2 of size at least 4 that does not contain a (q_r/T) or (q_l/T) tile has the form:

$$X (q_l/S) x 1 B^* T X$$

Moreover, every clean interval in the last row of Layer 2 of size at least $\log N + 5$ does not contain a tile of the form (q_r/T) or (q_l/T) .

Proof: If an interval is clean in the first row of Layer 2 (row r_{N-2}), then there are no illegal initialization squares in that interval spanning r_{N-1} and r_{N-2} which means that the interval must correspond to a path in the graph denoted in Figure 8. The interval begins and ends with X and has no X tiles in the middle. The only possible path in the graph in Figure 8 that begins and ends with X with no other intervening X's and has length at least 4, corresponds to X $(q_l/S) B^* T X$.

By induction on t, if the interval is clean in row r_{N-2-t} , then it is clean in rows r_{N-2} through r_{N-2-t} and the contents of the interval in row r_{N-2-t} represents the configuration of the Turing Machine after t steps, starting with X (q_l/S) $B^* T X$.

If an interval is clean in row r_1 , then it represents the state of the Turing Machine after N-3 time steps, starting with $X (q_l/S) B^* T X$. If at any point in these N-3 time steps, the head reached the T at the right end of the interval, then the head will stay in that position and the interval will contain a (q/T) tile in row r_1 .

If the interval row r_1 does not contain a (q/T) tile, then the head never reached the T during the first N-3 time steps. This implies that the configuration is the same as it would have been if there had been an infinite sequence of B symbols to the right of (q_l/S) in the initial time step. By Lemma 5.3, the contents of the interval will be X (q_l/S) $x_1 B^* T X$ in row r_1 .

After N-3 time steps, by Lemma 5.3, the length of the counter is at most log N+1. Therefore, the number of tape symbols that the head has reached is at most log N + 2, including the S to the left of the counter. If the interval has size at least log N + 5, then excluding the X on the left end and the T X on the right end, there are log N + 2 tiles. This is enough room for the Turing Machine to complete N - 3 steps without reaching the T on the right end of the interval which means that the interval in row r_1 does not contain a (q/T) tile.

5.2 Layer 3 for Gapped Weighted Tiling

In this subsection, we describe the translation rules from Layer 2 to Layer 3 and give a high level description of the Turing Machine that operates within each strip. For every $t \in \{X, \Box, S, T, B, 0, 1, \#\}$, a t tile is translated to another t tile from Layer 2 to Layer 3. The translation of the head tiles of the form (q/c), depend on the tape symbol c. For any state q and tape symbol c in the Layer 2 Turing Machine, the following translation rules apply:

$$(q/T) \rightarrow (q_{s1}/T)$$

for $c \neq T, (q/c) \rightarrow (q_{s2}/c)$

To summarize, in translating from Layer 2 to Layer 3, the state information from Layer 2 is lost and the new state depends only on whether the head of the Turing Machine in Layer 2 reached the T on the right end of the interval. If the head is pointing to T, then the new state on Layer 3 is q_{s1} , otherwise the new state is q_{s2} . The tape symbols are translated without change.

The Turing Machine that starts in state q_{s1} repeatedly executes the single move $\delta(q_{s1}, T) = (q_{s1}, T, -)$ until the last row of Layer 3. Thus if a computation in Layer 2 reaches the T at the right end of its interval, then it remains stuck for the rest of Layer 3. As long as each step is executed correctly, there are no additional costs in these small intervals.

Recall that we would like to show that for any language L in NEXP, we will construct a set of tiling rules and a mapping from any string x to a number N such that if $x \in L$, then there is a way to tile the $N \times N$ grid with zero cost (no illegal pairs or squares) and if $x \notin L$, then any tiling of the $N \times N$ will require cost that is $\Omega(N^{1/4})$. The Turing Machine that starts in state q_{s2} will guess a witness w and launch the verifier Turing Machine for a language $L \in \text{NEXP}$ with input x and witness w, where x1 is the string written on the tape at the end of Layer 2. Note that the Turing Machine in Layer 2 always produces a string that ends in 1, so in order to produce an arbitrary string, the last bit of the string produced is ignored. If at the end of Layer 2, the interval is clean and the head has not reached the T at the right end of the interval, then according to Lemma 5.5, it has the correct x written on the tape of the Turing Machine. The second Turing Machine (that starts in q_{s2}) will also have the rule $\delta(q, T) = (q, T, -)$ for any q. Thus, intervals which are not wide enough to complete the computation of V on (x, w) (for any guess w) can be tiled without any additional cost. If the computation is able to complete and accepts, then there is no cost. Any square that contains a rejection state of the Turing Machine V will incur a *rejection cost*. So an interval that is clean at the beginning of Layer 3 and is wide enough to perform the computation that ends up in a rejecting state will contain at least one illegal square or square with a rejection cost.

Costs of tiles and the perimeter tiles

Recall that the tile types consist of border tiles \Box or interior tiles. Each interior tile is specified by it's tile type for each of the three layers. For any configuration of four tiles arranged in a square, let p = 1 if the bottom two tiles are an illegal pair for Layer 1 and let $f_i = 1$ if the square is an illegal square for Layer *i* or an illegal translation square from Layer i - 1 to Layer *i*. Let r = 1 if the square contains a rejecting state for Layer 3. The values p, r, and f_i are 0 otherwise. The cost for that square is then $p + f_1 + f_2 + f_3 + r$. If F_i is the number of illegal pairs or squares in Layer *i* in a tiling, and R is the number of square on Layer 3 that contain rejecting states, then the cost of that tiling is $F_1 + F_2 + F_3 + R$.

The last technical point that we need to address before proving the hardness result for Gapped Weighted Tiling is to address the assumption that the perimeter of the grid consists of \Box tiles and that there are no \Box tiles on the interior of the grid. Towards this end, we create four types of \Box tiles: NW, NE, SE, SW. The designation of a square that contains a \Box tile as legal or illegal does not depend on the type of the \Box tile. Let C = 21. We will adjust the costs for each square by adding the following amount to the cost of a square if a tile of the given type is in that location of the square:

	upper left	upper right	lower right	lower left
NW-□	-C		+2C	
NE-□		-C		+2C
$SE-\Box$	+2C		-C	
$SW-\Box$		+2C		-C

Lemma 5.6 [Validating the Assumption About Perimeter Tiles] In any minimum cost tiling, the perimeter of the grid will consist of \Box tiles and no border tile will be contained in the interior of the grid. Moreover, there is a way to tile the perimeter with \Box tiles so that the total contribution due to the benefits and penalties from \Box tiles is -4C(N-1).

Proof: The cost of any square before the adjustments due to the border tiles is at most 5. Since each tile participates in at most four squares, changing a tile can cause the cost to change by at most 20, ignoring the penalties and benefits due to the \Box tiles. Consider a tiling of the grid with at least one \Box tile on the interior. If a \Box tile on the interior is changed to a non- \Box tile, the cost will increase by at most 20 due to changes in legal/illegal squares, one square will lose the -C benefit by having a \Box tile in one of its corners. This will amount to a total increase of 20 + C. However at least one square will lose the 2C penalty of having a border tile in the wrong corner. The change in the cost of the tiling will be (20+C)-2C = 20-C, which is negative.

If there is a non- \Box tile on the perimeter, then replace that tile with a type of \Box tile that will get the -C

benefit to the cost and no 2C penalty. The cost will increase by at most 20 due to changes in legal/illegal squares, so the total change in cost will be 20 - C which is negative.

These changes can be continued until there are no \Box tiles on the interior and only \Box tiles on the perimeter. Each swap decreases the cost of the tiling.

For each location on the border, there is a type of \Box tile such that placing that type of \Box tile in that location will result in one square with the -C benefit and no squares with the 2C penalty. Since there are 4(N-1) tiles on the perimeter, the claim follows.

We are now ready to prove the hardness result for Gapped Weighted Tiling:

Theorem 5.7 f(n)-GWT in 2-dimensions is NEXP-hard for some f(n) that is $\Omega(n^{1/4})$.

Proof: Given binary string x, let N be the number such that after N-3 steps of the binary counter Turing Machine from Layer 2, the contents of the tape are x1 and the head is pointing to S in state q_l . Note that the string representing the binary counter in the Layer 2 Turing Machine always ends in 1, so to get an arbitrary string x, we pick N to produce x1 and then ignore the last 1. According to Lemma 5.3, the function mapping x to N is polynomial time computable and $|x| \leq \log N$.

If $x \in L$, then there a way to tile the grid with $\cos t - 4C(N-1)$. This is achieved by first tiling the perimeter with \Box tiles so that the total benefit from the \Box tiles is -4C(N-1). For the interior, have every Turing Machine in every layer executed without a fault. This means that every interval at the end of Layer 2 is a clean interval. If the interval contains (q/T) at the end of Layer 2, the state is translated to q_{s1} in Layer 3 which initiates the Turing Machine that stays in the same state, incurring no cost. For all the intervals that do not contain (q/T) at the end of Layer 2, the state is translated to q_{s2} in Layer 3. According to Lemma 5.5, these intervals all have the correct binary string x which is translated to Layer 3 and serves as the input to the second Turing Machine (that starts in q_{s2}). If the head hits the right end of the interval in the Layer 3 computation, then the Turing Machine stays in the same state for all the remaining steps, incurring no cost. The remaining intervals that are wide enough to complete a computation of V, will guess the correct witness w and will accept on input x and w. Since accepting computations do not incur a cost, the overall cost of the tiling is 0.

Now supposed that $x \notin L$. Because of Lemma 5.6, we can assume that the minimum tiling has only \Box tiles along the perimeter and no \Box tiles on the interior of the grid. The total benefit from the border tiles will be at most -4C(N-1). We will prove that the cost due to legal/illegal squares or rejecting computations will be at least $N^{1/4}/c$ for some constant c.

For $i \in \{1, 2, 3\}$, let F_i denote the number of illegal squares and pairs in Layer *i*. For $i \ge 2$, F_i also includes the number of illegal translation squares from Layer i - 1 to Layer *i*. By Lemma 5.2, at the end of Layer 1, there will be at least $N^{1/4}/4 - 44F_1 - 3$ clean intervals of size at least $N^{1/4}/4$. By Lemma 5.4, the number of clean intervals of size at least 2 decreases by at most F_2 from the end of Layer 1 to the end of Layer 2. Therefore, the number of clean intervals of size at least $N^{1/4}/4$ at the end of Layer 2 will be at least $N^{1/4}/4 - 44F_1 - F_2 - 3$. According to Lemma 5.5, as long as $N^{1/4}/4 \ge \log N + 5$, these intervals will all have the correct x at the end of Layer 2.

|x| = n is at most log N, which means that there is a δ such that for large enough n, $2^{\delta n} \leq N^{1/4}/4$. Therefore, in any interval of size at least $N^{1/4}$, the computation in Layer 3 has enough room to finish. Thus, if $x \notin L$, then each interval that is clean at the end of Layer 2 and has size at least $N^{1/4}/4$ will either contain an illegal translation square (from Layer 2 to Layer 3), an illegal square in Layer 3 corresponding to an incorrect step of the Turing Machine, or a square containing a rejecting state. Therefore, the total cost due to rejecting computations is at least $N^{1/4}/4 - 44F_1 - F_2 - F_3 - 3$. Either $44F_1 + F_2 + F_3 + 3 \geq N^{1/4}/8$ or $R \geq N^{1/4}/8$.

6 Function Weighted Tiling is FP^{NEXP}-complete

We now turn our attention to the Function Weighted Tiling Problem, which is to compute the cost of the minimum cost tiling for an $N \times N$ grid. We will show that FWT in 2-dimensions is complete for FP^{NEXP}.

6.1 Containment

We will first argue that FWT is in FP^{NEXP}. Consider the decision problem whose input is a a positive integer N and threshold τ . The question is whether the minimum cost tiling for \mathcal{T} on an $N \times N$ grid is less than or equal to τ . This problem is in NEXP since a tiling of cost less than or equal to τ is of size N^2 and can be checked in time $O(N^2)$. We can therefore use an oracle to NEXP to binary search for the energy of the optimal tiling. The cost of any tiling is between $c_1(N-1)^2$ and $c_2(N-1)^2$, where c_1 is the smallest cost for any square and c_2 is the largest cost for any square. Therefore, the number of queries will be $O(\log N)$ which is polynomial in the size of the input.

6.2 Hardness

An outline of the proof is given in Section 1.3. We will reduce from a function $f \in P^{NEXP}$. Let M denote the polynomial-time Turing Machine that computes f. M has access to an oracle for language $L' \in NEXP$. We will use V to denote the exponential time verifier for L'.

We will need to bound the space and running time used by the verifier V as well as the size of the output f(x) and number of oracle calls made by M. This can achieved by a standard padding argument. We borrow the following version from [AI21] which has the elements we need:

Claim 6.1 [Padding Argument: Lemma 2.30 from [AI21]] If $f \in FP^{NEXP}$, then for any constants, c_1 and c_2 , f is polynomial time reducible to a function $g \in FP^{NEXP}$ such that g can computed by polynomialtime Turing Machine M with access to a NEXP oracle for language L. The verifier for L is a Turing Machine V. Moreover, on input x of length n, M runs in O(n) time, makes at most c_1n queries to the oracle. Also, the length of the queries made to the oracle is at most c_1n and the running time of V as well as the size of the witness required for V on any query made by M is $O(2^{c_2n})$. In addition the length of the output of g is at most c_1n .

6.3 Analysis of Layer 2 for Weighted Tiling Parity

In the last row of Layer 2, the clean intervals can be designated as *long-form* or *short-form*. The long-form intervals are wide enough to complete the computation of the Binary Counter Turing Machine from Layer 2. In the short-form intervals, the head gets stuck on the right end of the interval. These short-form intervals will not cause any cost to the overall tiling assuming they do not contain any illegal pairs or sqares.

Definition 18 [Long-form and Short-form Intervals] In the last row of Layer 2, a clean interval is a short-form interval if it has size 2 or 3 or contains a (q/T) tile. Otherwise, it is a long-form interval.

Lemma 6.2 [Summary of Analysis of Layer 2] Consider a tiling of an $N \times N$, where $N = 4n(1x^R) - 2w(x1) + 3$ for some string x. Let F_2 be the number of illegal squares and pairs in Layer 2. Let F_1 denote the number of illegal squares and pairs in Layer 1. Let r be the last row of Layer 2 and let S denote the set of sizes of the clean intervals in row r. Then if $F_1 \leq N^{1/4}/40$,

1. $l(r) \le F_2 + 9N^{1/2} + 2N^{1/4} + 1.$

- 2. $|\{2, 3, \dots, \mu(N) + 1\} S| \le 44F_1 + F_2 + 3$
- 3. Every clean interval of size at least $\log N + 5$ is a long-form interval.
- 4. Every long-form interval has the form X (q_l/S) x1 B^{*} T X.
- 5. Every short-form interval has the form X X or X T X, or X S 0^* (q/T) X.

Proof: Any increase in length from the last row of Layer 1 to the first row of Layer 2 must correspond to a # in Layer 1 that was not translated to a # in Layer 2, which would be contained in an illegal translation square. Any increase in length from row r_t to row r_{t-1} must come from a # tile in r_t that has a non-# below it in r_{t-1} . Both squares containing the pair of vertically aligned tiles are illegal. Therefore, an increase in the length from the last row of Layer 1 to the last row of Layer 2 is accounted for by an illegal square in Layer 2. The bound given in Item 1 on the length of the last row in Layer 2 is the expression from Lemma 4.13 which is an the upper bound on the length of the last row of Layer 1 plus F_2 . Note that Lemma 4.13 requires that $F_1 \leq N^{1/4}/40$, which is assumed in this lemma as well.

Let r' be the last row in Layer 1 and let S' be the set of sizes of the clean intervals in row r'. By Lemma 4.23, $|\{2, 3, \ldots, \mu(N) + 1\} - S'| \le 44F_1 + 3$. Also by Lemma 5.4, the set of the sizes of the clean intervals in row r' is the same as row r, except that all the intervals of size 1 are dropped and at most F_2 clean intervals are dropped. Therefore $|\{2, 3, \ldots, \mu(N) + 1\} - S| \le 44F_1 + F_2 + 3$.

Items 3 and 4 follow from Lemma 5.5.

To prove item 5, notice that the Figure 8 shows the initialization rules for Layer 2. The only possible interval of size 2 is X and the only possible interval of size 3 is X T X. Since these intervals do not contain a head tile, they will remain unchanged in the last row of Layer 2 unless they contain an illegal square somewhere in Layer 2.

Finally, if an interval has size at least 4 and does not contain any illegal translation or initialization squares (a requirement for being a clean interval), then it has the form $X(q_l/S) B^j T X$ in the first row of Layer 2, where j is a non-negative integer. If the interval remains clean until the last row of Layer 2, then the interval represents the state of the Binary Counter Turing Machine after N-3 steps. If the interval contains a (q/T)tile, then the head must have reached the T at the right end of the interval. Since the head always starts moving left when it encouners a 0, the head can only reach the T if all of the bits of the counter are 1. From the state $X(q_l/S) 1^r T X$, the head sweeps right, changing all the 1's to 0's. Then when it reaches the T, it remains stuck in that location for the remainder of the computation, resulting in $X S 0^j (q/T) X$.

The running time of the Outer Loop in Layer 3 will be bounded by a function of the length of the longest binary string in the last row of Layer 2. Therefore, we would like to bound the number of consecutive tiles that are 0 or 1 as a function of N and the number of illegal pairs and squares. Towards this goal, we will require the following additional lemma.

Lemma 6.3 [Bounding the Length of Binary Strings from Layer 2] Consider a tiling of the $N \times N$ grid. Let S be a sequence of m consecutive tiles in the last row of Layer 2 occupying locations l through l+m-1. Then one of the following must hold:

- 1. The sequence contains a tile that is not 0, 1, (q/0) or (q/1).
- 2. The sequence has length at most $\log N + 3$
- 3. There is a row r_t in Layer 2 such that there is an illegal square in locations l through l + m 1 spanning r_t and r_{t+1} .

Proof: Any T or (q/T) that is directly above a tile that is not a T or (q/T) the vertically aligned pair of tiles is contained in an illegal square to the left and to the right. The same holds for S or (q/S) tiles, as well as X and # tiles. Therefore, if locations l through l + m - 1 contain an #, X, (q/S) or T tile in the first row of Layer 2 and those locations consist of only 0 and 1 tiles in the last row of Layer 2, there must be an illegal square in those locations somewhere in Layer 2. The only other possibility is for locations l through l + m - 1 to consist entirely of B tiles in the first row of Layer 2.

Let h_1, \ldots, h_r be the indices of the rows in which locations l through l + m - 1 do not contain a head tile. We will prove by induction on j that the tiles in locations l through l + m - 1 are $x B^{m-s}$, where $x \in \{0, 1\}^s$ and $N - 2 - h_j \ge n(x^R)$. Recall that $n(x^R)$ is the numerical value of the binary number represented by the reverse of string R. Since $n(x^R) \ge 2^{s-1}$, this means that $s = |x| \le \log N + 1$. As long as $m \ge \log N + 3$, there will be at least two B tiles. As we will argue below, the appearance of a head tile can cause the number of B symbols in the sequence to decrease by at most 1, so if the last row of Layer 2 contains a head tile, there will still be at least one B tile in locations l through l + m - 1.

The first row in Layer 2 is r_{N-2} and the tiles in locations l through l + m - 1 are B^m , so $h_1 = N - 2$ and the claim holds.

Now consider the sequence of rows $r_{h_{j-1}}$ through r_{h_j} . In the first and last rows of this sequence, locations l through l + m - 1 do not contain a head tile. In the other rows, locations l through l + m - 1 do contain a head tile. By induction, the tiles in locations l through l + m - 1 are $x \ B^{m-s}$, where $x \in \{0, 1\}^s$ and $N - 2 - h_{j-1} \ge n(x^R)$. Therefore $|x| \le \log N + 1$ and as long as $m \ge \log N + 3$, there are at least two B's at the right end of the sequence of tiles $x \ B^{m-s}$. If the head appears at the right end of the sequence in state q_r , it will change the B to a 1, but then will transition to (q_l/B) and get stuck. If the head appears on the right end in state q_l , it gets stuck at the first step.

Therefore, the head must appear at the left end of the sequence of tiles. If the head appears in state q_l it will leave the sequence in the next step without changing x. If the head appears in state q_r at the left end of the sequence, assuming the sequence of tiles does not contain any illegal squares, the head will sweep right, increment x and then sweep left and leave the sequence of tiles. The value of $n(x^R)$ goes up by at most 1, the sequence of tiles is $x' B^{m-s}$, where x' is the reverse of the string representing $n(x^R) + 1$. Since $h_{j-1} \ge h_j + 1$, we have:

$$N - 2 - h_j \ge N - 2 - (h_{j-1} - 1) \ge n(x^R) + 1.$$

6.4 Layer 3 for Weighted Tiling Parity

At the end of Layer 2, each long-form clean interval contains a string x that is deterministically computed from N the size of the grid. When then string x is translated to Layer 3, each interval will also contain a non-deterministically chosen binary string z. The strings x and z will be co-located in the same |x| tiles in the form a string y over $\{0, 1, 2, 3\}$. The string z will represent a set of guesses for the oracle responses when the Turing Machine M is run on input x. The role of Layer 3 is to ensure that each interval makes the same non-deterministic guess in each interval. Thus, Layer 3 will represent a global computation (across all the intervals) that penalizes tilings that do not have a consensus for the guess z over all the intervals.

6.4.1 Translation from Layer 2 to Layer 3

This subsection will describe the translation of tiles from the last row of Layer 2 to the first row of Layer 3.

The translation rules for Layer 2 in combination with the initialization rules for Layer 3 ensure that longform and short-form intervals are translated differently from Layer 2 to Layer 3. The translation rules from Layer 2 to Layer 3 are summarized below. The rules will enforce the condition that for any tile directly above a \Box tile, if the tile type in Layer 2 is as indicated on the left, then the tile type for Layer 3 must be one of the choices on the right. The state q represents any state q in the Turing Machine for Layer 2.

$$\begin{array}{rcl} X & \rightarrow & \lhd & \mathrm{or} \ (q_r/ \rhd) \ \mathrm{or} \ X \\ 0 & \rightarrow & 0 \ \mathrm{or} \ 1 \ \mathrm{or} \ + \\ (q/0) & \rightarrow & 0 \ \mathrm{or} \ 1 \\ 1 \ \mathrm{or} \ (q/1) & \rightarrow & 2 \ \mathrm{or} \ 3 \\ S & \rightarrow & S \ \mathrm{or} \ + \\ (q/S) & \rightarrow & S \\ (q/B) \ \mathrm{or} \ B & \rightarrow & B \\ T & \rightarrow & T \\ (q/T) & \rightarrow & + \\ \# & \rightarrow & \# \end{array}$$

The intervals on Layer 3 begin and end with a tile from the set $\{X, \triangleleft, \triangleright\}$ or any head tile (q/c) where $c \in \{X, \triangleleft, \triangleright\}$. So if the last row of Layer 2 is correctly translated to Layer 3, then the intervals are preserved. The Turing Machine for layer 3 will also have the property that it does not change the intervals, if executed correctly.

Therefore, the definition of clean and corrupt intervals can be naturally extended from Layer 2 to Layer 3. In the first row of Layer 3, an interval is clean if there are no illegal squares (translation or initialization) in rows r_1 and r_2 and the corresponding interval in the last row of Layer 2 was clean. An interval in a higher row r_t of Layer 3 is clean if there are no illegal squares in that interval in Layer 3 spanning rows r_{t-1} and r_t and the interval was clean in row r_{t-1} . The tag for each interval also remains unchanged. If an interval is clean, it adopts the tag for the corresponding interval (occupying the same locations) in the previous row. Clean intervals also adopt the same long/short-form designation of the corresponding clean interval in the previous row.

There is still a high degree of flexibility in a legal translation of the last row of Layer 2 to the first row of Layer 3. The initialization rules for Layer 3, summarized in Figure 10, introduces some additional constraints.



Figure 10: These rules constrain the contents of the first row in Layer 3.

Definition 19 [Functions f and g mapping digits base 4 to two bits] We will use \mathcal{D} to denote the set $\{0, 1, 2, 3\}$. The digits in \mathcal{D} are used to encode two separate bits. We will think of a string $y \in \mathcal{D}^n$ as mapping

to two different binary strings based on the first and second bits in the binary encoding of each digit. Thus $f_1(y) = x$, where $x_i = 0$ if $y_i = 0$ or 1, and $x_i = 1$ if $y_i = 2$ or 3. Also, $f_2(y) = z$, where $z_i = 0$ if $y_i = 0$ or 2, and $z_i = 1$ if $y_i = 1$ or 3.

Lemma 6.4 [Form of the Intervals Translated to Layer 3] Consider a tiling of an $N \times N$ grid, where $N = 4n(1x^R) - 2w(x1) + 3$, for some binary string x. Let t and t' represent two tiles from the set $\{X, \triangleleft, (q_r/ \triangleright)\}$. In the first row of Layer 3, every clean short-form interval has the form

$$t t'$$
 or $t T t'$ or $t +^* t'$.

Every clean long-form interval has the form:

$$t S y B^* T^* t'$$

where $y \in \mathcal{D}^n$ and $f_1(y) = x1$.

Proof: According to Lemma 6.2, a clean short-form interval at the end of Layer 2 has the form X X, X T X or $X S 0^* (q/T) X$. According the the tanslation rule, each X must be translated to a tile from $\{X, \triangleleft, (q_r/ \triangleright)\}$. Also the T must be translated to T. So if an interval at the end of Layer 2 has the form X X or X T X and it does not contain any illegal translation squares from Layer 2 to Layer 3, then it has the form t t' or t T t', where t and t' are from the set $\{X, \triangleleft, (q_r/ \triangleright)\}$.

Alternatively, if the interval has the form $X \ S \ 0^* \ (q/T) \ X$, the (q/T) tile must be translated to a + tile. The S could be translated to S or + and the 0 tiles could be translated to 0, 1, or +. However, the initialization rules shown in Figure 10, show that the only tiles that can go to the left of a + is either a + or a tile from $\{X, \lhd, (q_r/ \triangleright)\}$. Therefore, the only way to translate the tiles in the interval so that there are in illegal initialization or translation squares is to translate the interval to t + t'.

According to Lemma 6.2, a long form interval will look like $X(q_l/S) x 1 B^* T X$ in the last row of Layer 2. The (q_l/S) tile must be translated to an S tile. This means that the translated interval can not contain any + tiles because the only tiles that can be next to a + tile are another + tile or a tile from $\{X, \triangleleft, (q_r/\triangleright)\}$. Thus, the bits in x1 are translated non-determistically, so that the resulting string y has $f_1(y) = x1$. Note that 0 must go to 0 or 1, and 1 must go to 2 or 3. The B tiles are translated to B tiles and the T tile to a T tile. Thus, the resulting interval, if there are no illegal translation or initialization squares, will have the form $t S y B^* T^* t'$, where f(y) = x1 and t and t' are from $\{X, \triangleleft, (q_r/\triangleright)\}$.

There is still ambiguity in how tiles are translated from Layer 2 to Layer 3. The horizontal rules described in the next subsection will constrain how an X from Layer 2 is translated to Layer 3, since there is an option of any tile from the set $\{X, \triangleleft, (q_r/ \triangleright)\}$ in the translation rules. The final ambiguity is whether a 0 is translated to 0 or 1 and whether a 1 is translated to 2 or 3. Note that the first bit of 0, 1, 2, 3 (expressed in binary) is the same as the underlying bit from Layer 2, but the second bit can be chosen arbitrarily. The goal of the Turing Machine in Layer 3 is to check that the second bits are all translated consistently across the intervals. There will be a large tiling cost if any of the strings are translated inconsistently.

6.4.2 Horizontal Rules for Layer 3

Since the Turing Machine in Layer 3 is a global computation that operates across the whole row and not just within a strip, we will need additional horizontal rules to ensure that a valid row has exactly one head tile and that the tape contents are bracketed on the left and right by \triangleleft and \triangleright , respectively. The tape symbols for the Turing Machine will be:

$$\Gamma = \{ \lhd, \rhd, X, 0, 1, 2, 3, \overline{0}, \overline{1}, \overline{2}, \overline{3}, B, S, T, + \}$$

We define a subset of the tape tiles $\Gamma' = \Gamma - \{ \lhd, \triangleright \}$. For every $c \in \Gamma'$, there will be a blue version of that tile and a red version of that tile: c and c. Figure 11 summarizes the horizontal rules for Layer 3. The set Q is the set of all states for the Turing Machine in Layer 3. A pair of tiles t_1 t_2 is legal if there is an edge from the vertex containing t_1 to the vertex containing t_2 in the graph. All other pairs are illegal. A row of tiles for Layer 3 is said to be *valid* if it does not contain any pair of adjacent tiles that are an illegal pair. Otherwise the row is *invalid*.

The rules enforce that the \Box tile on the left must be followed by a \triangleleft symbol, followed by a sequence of tape symbols, followed by \triangleright , followed by a sequence of # tiles, followed by the final \Box tile. In addition, exactly one of the tiles from the \triangleleft to the \triangleright must be a head tile. Thus, in a valid row, the intervals all begin and end with an X tile, except the leftmost interval which begins with \triangleleft and the rightmost interval which ends with \triangleright .



Figure 11: This graph shows the horizontal rules for Layer 3.

Lemma 6.5 [Properties of a Valid Row in Layer 3] A row is valid if and only if the row satisfies the following conditions:

1. The tape contents of the row has the form:

$$\Box \lhd (\Gamma')^* \vartriangleright \#^* \Box$$

- 2. There is exactly one tile is a head tile.
- 3. The head is located at one of the tiles from the \triangleleft to the \triangleright .
- 4. Any tiles from Γ' to the left of the head tile are blue and any tiles from Γ' to the right of the head tile are red.

Proof: Any path in the graph in Figure 11 must pass through vertex 1, 4, or 7 exactly once and therefore has exactly one head tile. In addition, the path goes through 1 or 2, then vertices from 3, 4, and 5, followed by one of vertices 6 or 7 and then vertex 8. Therefore, the tape contents of each such path must have the form $\Box \lhd (\Gamma')^* \rhd \#^* \Box$. There are no vertices in the graph in which the head is located at a \Box or # tile, so the head must point to one of the symbols between the \lhd and \triangleright tiles. If vertex 3 is reached, then it comes before vertex 4 or 7, which means that all the blue tiles from Γ' precede the head tile. If vertex 5 is reached, then it comes after vertex 1 or 4, which means that all the read tiles from Γ' come after the head tile.

For the converse, consider a row that satisfies all the properties in the lemma. If the head points to the \triangleleft symbol, then it can be generated by a path of the form $1 \rightarrow 5^* \rightarrow 6 \rightarrow 8^*$. If the head points to the a symbol from Γ' , then it can be generated by a path of the form $2 \rightarrow 3^* \rightarrow 4 \rightarrow 5^* \rightarrow 6 \rightarrow 8^*$. If the head points to the \triangleright symbol, then it can be generated by a path of the form $2 \rightarrow 3^* \rightarrow 7 \rightarrow 8^*$.

We describe the Turing Machine rules in the next section. It will be important that there is a unique next step for any Turing Machine configuration that corresponds to a valid row.

6.4.3 The Layer 3 Turing Machine

The Turing Machine in Layer 3 is global in the sense that it works across all the intervals. The tape alphabet is the set:

$$\Gamma = \{ \triangleleft, \triangleright, X, 0, 1, 2, 3, \overline{0}, \overline{1}, \overline{2}, \overline{3}, B, S, T, + \}$$

The symbols in $\{\overline{0}, \overline{1}, \overline{2}, \overline{3}\}$ are called *marked* digits. For digit $j \in \mathcal{D}$, marking j corresponds to replacing j with \overline{j} and unmarking j corresponds to replacing \overline{j} with j. Other than marking or unmarking digits, the Turing Machine never changes the information on the tape.

The program of the Turing Machine consists of two nested loops. The TM will just continually run the Outer Loop for as many steps as it is allowed to run. Consider the row at the beginning of an iteration of the Outer Loop. Let l_1, \ldots, l_m be the locations of the S tiles in this row. For each such S tile, let y_i be the string of digits immediately to the right of the S tile. Note that y_i could be the empty string if S is followed by a non-digit. If the Outer Loop is executed without error, there will be a cost in an iteration of the Outer Loop for each y_k , where k > 1 and $y_k \neq y_1$.

The digits in each string that have already been checked are marked. In an iteration of the Inner Loop, the Turing Machine reads the first unchecked digit in y_1 and checks that digit against the first unmarked digit in each of the other y_j 's. When a digit is checked, it becomes marked.

Figure 12 shows the steps of the Outer Loop in pseudo-code. Figure 13 gives a table with all the Turing Machine rules. An iteration of the Outer Loop begins with the head just one space to the left of \triangleright . The Turing Machine sweeps left, unmarking all the digits until \triangleleft is reached. This begins an iteration of the inner loop. The head sweeps right all the way from \triangleleft to \triangleright , starting in state q_{read} . When the first S is encountered, the Turing Machine reads and remembers the next unmarked digit j and transitions to q_{1j} . This is the next unchecked digit of y_1 . The digit j is checked. In state q_{1j} the head is looking for an S which indicates the beginning of the next y. After an S is reached, it transitions to q_{2i} indicating that it is looking for the next unmarked digit. When the next unmarked digit is found, it checks if j = k. If $j \neq k$, a cost is incurred. The digit k is marked and the head transitions to q_{i1} in order to look for the next S. The Turing Machine also incurs a cost if in state q_{2j} and a non-digit is encountered, indicating that the current y being checked is shorter than y_1 . When the \triangleright is reached, then the Turing Machine transitions to q_{ret} and sweeps left to the \triangleleft to begin a new iteration of the inner loop. The Outer Loop terminates when all the digits in y_1 have been checked. This happens, when the state is q_{read} and the head encounters a non-digit before an unmarked digit. The head then transitions to q_{sweep} and sweeps right to the \triangleright . While the Turing Machine is in state q_{sweep} , any unchecked digit causes the Turing Machine to incur a cost. This happens is one of the strings y is longer than y_1 . When the head reaches \triangleright , it transitions to q_{clear} which begins a new iteration of the Outer Loop.

The Turing Machine rules are translated into legal and illegal computation squares for as described in Section 2.2. As with Layer 1, a legal head square is legal as long as any tiles from Γ' to the left of a head tile is blue and any tiles from Γ' to the right of a head tile are red. Also, a square is illegal if it has a tape tile directly above another tape tile that are different in any way, including the color.

There is one final type of illegal square which occurs only in Layer 3. These introduce the costs indicated in the pseudo-code shown in Figure 12. Any square which contains a tile of the form (q_{2j}/k) where $j \neq k$ or (q_{2j}/c) , where $c \in \{B, S, T, +, X, \triangleright\}$, is an illegal square. In addition, any square that contains (q_{sweep}/j) where $j \in \mathcal{D}$ is also an illegal square. We will call these *illegal verification squares*.

Lemma 6.6 [Sequential Rows Represent TM Steps in Layer 3] Consider a row r that is valid in Layer 3. There is a unique row r' that can be placed above r such that there are no illegal computation squares that span the two rows r and r'. r' is valid. Moreover, row r corresponds to a Turing Machine configuration and r' represents the configuration resulting from executing one step in the configuration r.

(1)	OUTERLOOP:
(3)	Sweep left in state q_{clear} , unmarking every digit.
(4)	When \triangleleft is reached, transition to q_{finds} and move right
(5)	Start of Inner Loop
(6)	Move right in state q_{findS} until an S or \triangleright is reached
(7)	If \triangleright is reached before S, transition to q_{clear} . Go to (1).
(8)	When S is reached, transition to q_{read}
(9)	Move right in state q_{read} past any marked digits
(10)	If $c \in \{B, X, +, S, T\}$ is reached before a digit, go to (24)
(11)	If \triangleright is reached before a digit, go to (26)
(12)	If unmarked digit j is reached, mark j , transition to q_{1j} .
(13)	Move right in state q_{1j} until an S or \triangleright is found.
(14)	If \triangleright is reached, go to (22).
(15)	If S is reached, transition to q_{2j} .
(16)	Move right in state q_{2j} past any marked digits.
(17)	If an unmarked digit k is reached, mark k and transition to q_{1j} .
(18)	If $j \neq k$, then Cost.
(19)	If non-digit c is reached for any $c \neq \triangleright, S$, transition to q_{1j} . Cost.
(20)	If S is reached, stay in q_{2j} . Cost.
(21)	If \triangleright is reached, go to (22). Cost.
(22)	Transition to q_{ret} . Move left until \triangleleft is found.
(23)	Transition to q_{findS} . Go to (5)
(24)	Transition to state q_{sweep} , move right until \triangleright is reached
(25)	If an unmarked j is encountered in state q_{sweep} , there is a Cost .
(26)	Transition to q_{clear} . Go to (1).

Figure 12: Pseudo-code for an integration of the Outer Loop for the Turing Machine in Layer 3.

Proof: Consider a valid row r. If there is a row r' such that if r' is placed directly above r, there are no illegal computation squares, then r' must be unique. The argument is almost identical to the analogous lemma proved for the Layer 1 Turing Machine given in Lemma 3.2.

Next we need to show that if r is valid, then there is a valid r' such that there are no illegal computation squares spanning rows r and r'. Since r is valid, there is exactly one head tile in r and therefore r corresponds uniquely to a configuration of the Turing Machine. Let r' be the row resulting from applying one step of the Turing Machine to the configuration represented by row r. Color all the Γ' tiles to the left of the head tile blue and all the Γ' tiles to the right of the head tile red.

We will first establish that there are no illegal squares spanning rows r and r'. The head square must be legal because it represents one correctly executed step of the Turing Machine. All other tiles outside of the head square are tape tiles and are the same in r and r' because they did not change in the computation step. Moreover since r is valid, all Γ' tiles to the left of the head square are blue and all Γ' tiles to the right of the head square are red. Therefore any Γ' tiles outside of the head square have the same color in r and r'.

To establish that r' is valid, we will show that r' has all the properties from Lemma 6.5. If the head is

	q_{findS}	q_{read}	q_{j1}	q_{j2}
k	Right	$(q_{k1}, \overline{k}, R)$	Right	$(q_{j2}, \overline{k}, R)^*$
\overline{k}	Right	Right	Right	Right
S	Right	(q_{sweep}, S, R)	(q_{j2}, S, R)	$\operatorname{Right}^\dagger$
\triangleleft	Right	Right	(q_{j2}, \lhd, R)	(q_{j1}, \lhd, R)
\triangleright	(q_{clear}, \rhd, L)	(q_{clear}, \rhd, L)	$(q_{ret}, \rhd, L)^{\dagger}$	$(q_{ret}, \triangleright, R)$
c	Right	(q_{sweep}, c, R)	Right	$\operatorname{Right}^\dagger$

	q_{ret}	q_{sweep}	q_{clear}
k	Left	${ m Right}^\dagger$	Left
\overline{k}	Left	Right	(q_{clear}, k, L)
S	Left	Right	Left
\Box	Right	(q_{sweep}, \lhd, R)	(q_{findS}, \lhd, R)
\triangleright	Left	$(q_{clear}, \triangleright, L)$	Left
c	Left	Right	Left

Figure 13: A summary of the rules for the Layer 3 Turing Machine. The word c is any tape character in $\{X, +, B, T\}$. j is any digit from \mathcal{D} . Left stands for $\delta(q, c) = (q, c, L)$. The word **Right** stands for $\delta(q, c) = (q, c, R)$. Rule * incurs a cost if $j \neq k$. Rules marked with \dagger incur a cost.

pointing to a \triangleleft symbol, it writes a \triangleleft and moves right. If the head is pointing to a \triangleright symbol, it writes a \triangleright and moves left. If the head is pointing to a symbol from Γ' , it writes a symbol from Γ' and moves left or right. This guarantees properties 1 through 3. Property 4 is guaranteed by construction.

6.4.4 Analysis of Layer 3

We would like to argue that if the number of illegal pairs or squares in Layer 3 is less than a certain value, then there will be a complete error-free iteration of the Outer Loop.

Definition 20 [End Row for Layer 3] An end row for Layer 3 is a valid row in which the head is pointing to \triangleright symbol in state $q_{sweep}, q_{read}, q_{findS}$ or q_{clear} .

Note that since an end row is valid, it corresponds to a valid configuration of the Turing Machine. In the next next step of the Turing Machine, the head is just to the left of the \triangleright symbol in state q_{clear} , which begins a new iteration of the Outer Loop.

Lemma 6.7 [Number of Steps to Reach an End Row in Layer 3] Consider a valid row r_s in Layer 3 of a tiling. Let y be the maximal string of digits to the immediate right of the left-most S tile in r_s . If there is no S tile, then y is empty. If rows r_s through r_t are all valid and do not contain any illegal computation squares and $t - s \ge 2(|y| + 2) \cdot l(r_s)$, then one of the rows in r_{s+1} through r_t must be an end row.

Proof: We will argue that if the Turing Machine starts in a valid configuration, then it will reach an end configuration within $2(|y|+2) \cdot l(r_s)$ steps.

Each iteration of the Inner Loop begins with the head just to the right of the \triangleleft symbol in state q_{findS} . We will first establish that it takes at most $2l(r_s)$ steps to reach the beginning of an iteration of the Inner Loop or

an end configuration. If the state of r_s is q_{clear} or q_{ret} , the head moves left until a \triangleleft symbol is reached. Then the head moves right into state q_{findS} , for a total of at most $l(r_s)$ steps. If the state of r_s is q_{sweep} , q_{findS} , q_{read} , q_{1j} or $q_{2,j}$ then the head will continue moving right and remain in one of those states until the \triangleright is reached. If the state is q_{sweep} , q_{findS} or q_{read} when the \triangleright is reached, this is an end configuration. If the state is q_{1j} or $q_{2,j}$ when the \triangleright is reached, the Turing Machine will move left in state q_{ret} until the \triangleleft is reached, at which point it transitions to q_{findS} and moves right. This is the beginning of an iteration of the Inner Loop. The total number of steps so far has been $2l(r_s)$.

If the Turing Machine starts an iteration of the Inner Loop and the head never reaches an S in state q_{findS} , it will reach the \triangleright symbol in state q_{findS} , which is an end configuration. In this case, $|y_1| = 0$ and the number of steps spent in the Inner Loop is $l(r_s)$. Otherwise, the head will eventually reach an S and will transition to q_{read} . If the head reaches a digit before a symbol from $\{B, S, +, X, T, \triangleright\}$ in state q_{read} , the digit will be marked and the head will continue going right in state q_{1j} or q_{2j} until it hits the \triangleright symbol, in which case it transitions to q_{ret} , sweeps left until the \triangleleft symbol is reached and then moves right into q_{findS} to start another iteration of the Inner Loop. The marked digit is part of y because at the beginning of an iteration of the Inner Loop, the state is initially q_{findS} and can only transition to q_{read} when the first S is reached. The state remains in state q_{read} until a symbol from $\{B, S, +, X, T, \triangleright\}$ or a digit is reached. Thus, if a digit is reached before a symbol from $\{B, S, +, X, T, \triangleright\}$ method still y. Therefore, in each iteration of the inner loop, one additional digit from y_1 becomes marked and there can be at most $|y_1|$ iterations of the inner loop, each of which takes at most $2l(r_s)$ steps. The Inner Loop Iterations take a total of at most $2|y_1|l(r_s)$ steps.

Finally, if the state is q_{read} and the Turing Machine reaches a symbol from $\{B, X, +, X, T, \triangleright\}$, it will sweep right in state q_{sweep} (if it is not already at the \triangleright symbol) until the \triangleright is reached. Within an additional $l(r_s)$ steps, the head will reach \triangleright in state q_{sweep} or q_{read} , which is and end configuration. The total number of steps is at most $2l(r_s) + 2|y_1|l(r_s) + l(r_s) \leq 2(|y| + 2) \cdot l(r_s)$.

The set \mathcal{D} is the set of digits in $\{0, 1, 2, 3\}$. We can augment \mathcal{D} to include the marked digits as well: $\mathcal{D}' = \mathcal{D} \cup \{\overline{0}, \overline{1}, \overline{2}, \overline{3}\}$. The function *val* maps strings in \mathcal{D}' to strings in \mathcal{D} by changing marked digits to the corresponding unmarked digits, so \overline{j} is mapped to j. The functions f_1 and f_2 can be extended to strings from $(\mathcal{D}')^*$ by first applying the function *val* and then applying f_1 or f_2 .

Lemma 6.8 [Bound on the Length of a String of Digits in Layer 3] Let r be any row in Layer 3 of a tiling of an $N \times N$ grid. Let y be a string of consecutive tiles from \mathcal{D}' in r. Then $|y| \leq (F_2 + F_3)(\log N + 4)$

Proof: Consider a sequence of consecutive tiles in locations l through l + s - 1 that are all from \mathcal{D}' , where $s = \log N + 4$. If locations l through l + s - 1 in the last row in Layer 2 are either bits (0 or 1) or head tiles with bits ((q/0) or (q/1)) then by Lemma 6.3, there is an illegal square contained in locations l through l + s - 1 spanning two consecutive rows in Layer 2. If the last row of Layer 2, locations l through l + s - 1 contain a tile that is not 0, 1, (q/0), or (q/1), then either there is an illegal translation square contained in those locations or those locations contain a tile that is not from the set \mathcal{D} in the first row of Layer 3. Furthermore, any two vertically aligned tiles in Layer 3 in which a tile not from \mathcal{D}' is directly below a tile that is from \mathcal{D} prime must be contained in illegal squares on both sides. Therefore, if the locations l through l + s - 1 contain tiles from \mathcal{D}' in a row from Layer 3, then those locations must contain an illegal square somewhere in Layers 2 or 3. Partition the locations of y into consecutive locations of length log N + 4. There must be an illegal square from Layers 2 or 3 contained within each set of locations, which means that there can be at most $F_2 + F_3$ sets of locations. Therefore the length if y is at most ($F_2 + F_3$)(log N + 4).

Lemma 6.9 [Layer 3 Completes At Least One Iteration of the Outer Loop] As long as $F_1 \leq N^{1/4}/40$ and $F_2 + F_3 \leq N^{1/4}/10 \log N$, there is a sequence of rows in Layer 3 with no illegal pairs or computation squares, in which the Turing Machine executes a complete iteration of the Outer Loop. *Proof:* Consider a set of consecutive rows in Layer 3 with no illegal pairs or computation squares. Let r be the first row in the sequence or rows. Let y be the maximal sequence of tiles in row r from the set \mathcal{D}' that are directly to the right of the leftmost S tile in row r. By Lemma 6.7, if the sequence lasts for at least 2(|y|+2)l(r) rows, then the computation represented in the sequence of rows will reach the end of an iteration of the Outer Loop. Note that l(r) and y do not change in the course of these rows because there are no illegal computation squares and the computation does not change the contents of the Turing Machine tape other than marking or unmarking digits. Thus, if the sequence lasts for yet another 2(|y|+2)l(r) rows, then the computation represented in the sequence of rows will include one full iteration of the Outer Loop. So as long as the sequence contains at least 4(|y|+2)l(r) rows, it will be guaranteed to contain a complete iteration of the Outer Loop with no computation errors.

Lemma 6.2 gives an upper bound on the length of the last row of Layer 2 which for now we will call L. Any two vertically aligned tiles with a non-# tile on top of a # tile will be contained in illegal computation squares on both sides. So the length of row r can be at most the upper bound from Lemma 6.10 plus F_3 . Meanwhile, Lemma 6.8 gives an upper bound of $(F_2 + F_3)(\log N + 4)$ for |y|. Putting these bounds together means that if we are guaranteed to have a sequence of at least

$$4\left[(F_2 + F_3)(\log N + 4) + 2\right](L + F_3)$$

consecutive rows with no illegal squares or computation squares, then there will be a complete iteration of the Outer Loop with no computation errors.

Besides the first and last rows which are all filled with \Box tiles, there are a total of N-2 rows. There are at most F_3 rows with an illegal pair or square. Therefore there must be at least one sequence of at least $(N-2-F_3)/(F_3+1)$ rows with no illegal pairs or squares. So as long as the following inequality holds:

$$\frac{N-2-F_3}{F_3+1} \geq 4 \left[(F_2+F_3)(\log N+4) + 2 \right] (F_3+L)$$

If $F_1 \leq N^{1/4}/40$, then the bound from Lemma 6.2 says that $L \leq F_2 + 11N^{1/2} + 1$. Using the assumption from the Lemma that $F_2 + F_3 \leq N^{1/4}/10 \log N$, the inequality above can be verified.

Lemma 6.10 [Summary of Analysis of Layer 3] Consider a tiling of an $N \times N$ grid, where $N = 4n(1x^R) - 2w(x1) + 3$, for some binary string x. Let F_i be the total number of illegal squares and pairs in Layer i, for i = 1, 2, 3. At the end of Layer 3, the following conditions hold:

- 1. If S is the set of sizes of clean intervals in the last row of Layer 3, then $|\{2, 3, \dots, \mu(N) + 1\} S| \le 44F_1 + F_2 + F_3 + 3$.
- 2. Every clean short-form interval at the end of Layer 3 has the form X X, X T X or $X +^* X$.
- 3. Any clean interval of size at least $\log N + 5$ is a long-form interval.
- 4. If $F_1 \leq N^{1/4}/40$ and $F_2 + F_3 \leq N^{1/4}/10 \log N$, then there exists a $y \in \mathcal{D}^*$ such that every long-form clean interval of has the form $X S y_i B B^* T X$, where $y_i \in \mathcal{D}'$ and $val(y_i) = y$ and $f_1(y) = x$.

Proof: Let T_2 be the set of tags corresponding to clean intervals in the last row of Layer 2. Let T_3 be the set of tags corresponding to clean intervals in the last row of Layer 3. Since no clean intervals are created from the last row of Layer 2 to the last row of Layer 3 and each clean interval adopts the same tag as the corresponding clean interval in the preceding row, $T_3 \subseteq T_2$. If there is a clean interval in the last row of Layer 2 with tag j and no such clean interval in the first row of Layer 3, then the interval contains an illegal translation square.

Similarly, a clean interval with tag j that does not correspond to a clean interval with tag j in the next row, must contain an illegal square. Since every lost clean interval corresponds to an illegal translation square or illegal computation square in Layer 3, $|T_2 - T_3| \leq F_3$. If S' is the set of sizes of clean intervals at the end of Layer 2m then by Lemma 6.2, $|\{2, 3, \ldots, \mu(N) + 1\} - S'| \leq 44F_1 + F_2 + 3$. At most F_3 clean intervals are lost from the end of Layer 2 to the end of Layer 3. Therefore, $|\{2, 3, \ldots, \mu(N) + 1\} - S| \leq 44F_1 + F_2 + F_3 + 3$.

Item 2 follows from the fact that the Turing Machine in Layer 3 does not change any tile from one row to another, except for the movement of the head and marking or unmarking digit tiles. Therefore, if an interval is clean in Layer 3, it has the same form as it did in the first row of Layer 3. Lemma 6.4, indicates what the short-form and long-form intervals look like in the first row of Layer 3. Also, the intervals do not switch between being long-form or short-form intervals from the last row of Layer 2. Therefore, by Lemma 6.2, any clean interval of size at least $\log N + 5$ must be a long-form interval in the last row of Layer 3, which proves item 3.

Now to prove item 4. The assumption for this Lemma are the same as the conditions for Lemma 6.9, so there is a sequence of consecutive rows in Layer 3 that do not contain any illegal pairs or computation squares that correspond to a complete iteration of the Outer Loop. The r_s be the first row in this sequence. Find the location of the leftmost S tile in r_s and let y be the maximal sequence of consecutive tiles from \mathcal{D}' that are immediately to the right of the S tile. After the head sweeps left in state q_{clean} at the beginning of the Outer Loop, every clean interval has the form X S $y_i B^* T X$, where $y_i \in \mathcal{D}$. Each y_i corresponds to the i^{th} clean interval as they are numbered from left to right. y may or may not be the same as y_1 .

If there is an s where digit s of y_1 differs from digit s of y_i , then on the s^{th} iteration of the inner loop, there will be an illegal verification square in interval i when the Turing Machine is in state q_{2j} and the first unmarked digit in interval i is $k \neq j$. This occurs in line (18) of the pseudo-code in Figure 12. Otherwise, if $y_1 \neq y_i$, then y_1 must be a proper prefix of y_i or y_i is a proper prefix of y_1 . If y_1 is be a proper prefix of y_i , in the last iteration of the Inner Loop, when there are no longer unchecked digits in y_1 , there will remain unchecked digits in y_i . These will trigger an illegal verification square when the Turing Machine is in state q_{sweep} and encounters the unchecked digit in interval i. Finally if y_i is a proper prefix of y_1 , after $|y_i|$ iterations, the Turing Machine will read digit $|y_i| + 1$ of y_1 but will encounter no unmarked digits in interval S. The state will transition to q_{2j} when it reaches the S in interval i and it will encounter a non-digit before it encounters an unmarked digit. Thus triggering a cost in Line (19) in the pseudo-code.

Thus, every interval such that $y_i \neq y$ will no longer be clean after the iteration of the Outer Loop. Since every clean interval started with $f_1(y_i) = x_1$, and the string of digits in the interval does not change as long as the interval remains clean, then $f_1(y_i) = x_1$ will remain true after the iteration of the Outer Loop. In the remainder of the rows, if the interval remains clean, then it contains no illegal computation squares and the string of digits remains the same, except perhaps that some digits become marked, so Item 4 will still hold for the last row of Layer 3.

6.5 Layer 4

The translation rules from Layer 3 to Layer 4 translate any j or \overline{j} tile to j, for $j \in \mathcal{D}$. S is translated to (q_s/S) , and t is translated to t for any $t \in \{+, \#, X, B, T, \triangleright, \triangleleft\}$. The states from Layer 3 are all dropped, so any tile of the form (q/c) is translated to whatever c would be translated to, according to the rules above. These translation rules ensure that every clean interval is translated to a clean interval as long as the tiles in the interval are translated correctly. Thus every clean long-form interval has the form: $X(q_s/S)\mathcal{D}^*B^*T X$.

Recall that the functions f_1 and f_2 map a string of length n over \mathcal{D} to two binary strings of length n. The variable x will denote the binary string $f_1(y)$ with the last bit removed and z will denote $f_2(y)$. x will be used as the input to the computation and z will be used as a guess of the answers to the queries to the oracle L'. We will use \bar{n} to denote the number of oracle queries made by M on input x, so we will only be concerned

with the first \bar{n} bits of z.

The tiling rules in Layer 4 enforce that an X tile must have a \Box or X tile above and below it. Similarly for + and #, so the only tiles that change from one row to another are tiles inside long-form interval unless there is an illegal square. Every clean long-form interval will contain an independent Turing Machine computation. The Turing Machine rules are translated into legal and illegal squares as described in Section 2.2. If the head reaches the T at the right end of the interval, then the interval is not wide enough to complete the computation. In this case, the computation halts and does not incur any additional cost.

The definitions for clean and corrupt intervals carry over to Layer 4 as well. Since clean intervals do not change locations within a row, two clean intervals will have the same tag and long/short-form designation if they occupy the same locations within their respective rows. An interval in the first row of Layer 4 is clean if those tiles corresponded to a clean interval at the end of Layer 3 and the interval does not contain any illegal translation or initialization squares. In going from one row to the next row in the computation in Layer 4, an interval is clean if those tiles corresponded to a clean interval to a clean interval in the previous row and there are no illegal squares spanning the current and previous rows in the interval.

Lemma 6.11 [Bound on the Missing Clean Interval Sizes] Let F_i be the total number of illegal squares and pairs in Layer *i*, for i = 1, 2, 3, 4. If S is the set of clean intervals at the end of Layer 4 then $|\{2, 3, \ldots, \mu(N) + 1\} - S| \le 44F_1 + F_2 + F_3 + F_4 + 3$.

Proof: Let T_3 be the set of tags corresponding to clean intervals in the last row of Layer 3. Let T_4 be the set of tags corresponding to clean intervals in the last row of Layer 4. Since no clean intervals are created from the last row of Layer 3 to the last row of Layer 4 and each clean interval adopts the same tag as the corresponding clean interval in the preceding row, $T_4 \subseteq T_3$. If there is a clean interval in the last row of Layer 3 with tag j and no such clean interval in the first row of Layer 4, then the interval contains an illegal translation square. Similarly, a clean interval with tag j that does not correspond to a clean interval with tag j in the next row, must contain an illegal square. Since every clean interval that is lost in Layer 4 corresponds to an illegal square in Layer 4, $|T_3 - T_4| \ge F_4$. If S' is the set of sizes of the clean intervals at the end of Layer 3, then by Lemma 6.10, $|\{2, 3, \ldots, \mu(N) + 1\} - S'| \le 44F_1 + F_2 + F_3 + 3$. Since at most F_4 clean intervals are lost from the end of Layer 3 to the end of Layer 4, $|\{2, 3, \ldots, \mu(N) + 1\} - S'| \le 44F_1 + F_2 + F_3 + 3$.

6.5.1 The Layer 4 Computation

Recall that we are reducing from a generic language $f \in \text{FP}^{\text{NEXP}}$ to Function Weighted Tiling. M denotes the poly-time Turing Machine that computes f with access to a NEXP oracle. L' is the the NEXP-time language that is the oracle for M. V denotes the exp-time Turing Machine that is the verifier for L'.

The reduction maps a string x to an integer N such that after N-3 steps of the Binary Counter Turing Machine described in Section 5.1, the string on the tape is x1 and the head is at the left end of the tape. According to Lemma 5.3, $N = 4n(1x^R) - 2w(x1) + 3$, where x^R is the reverse of string x, n(x) is the numerical value of the string x in binary, and w(x) is the number of 1's in x.

All the clean long-form intervals start out with configuration

$$(q_s/S) \ y \ B \cdots B \ T.$$

The computation that is initiated by state q_s proceeds in several stages.

Stage 1: The computation in Stage 1 "measures" the size of the interval and writes the size of the interval in binary. This is accomplished by a counter similar to the one used in [GI13]. The Turing Machine uses a binary and a unary counter. The head shuttles back and forth between the two ends of the interval (using the

S and the T tiles to know when it has reached one of the two ends). In each cycle, the head increments both counters. When the unary counter has reached the T on the right end of the interval, it transitions to a new state which begins the next phase of the computation. The counting procedure actually counts the number of interior tiles in the interval and the definition of the size of an interval includes the two endpoint tiles, so we add 2 to the final count to get the size of the interval. We will call this value r for a particular interval. Note that a clean interval can increase in size by at most 1 per segment, so the size of any clean interval is bounded by the number of segments, which by Lemma 4.12, is $O(N^{1/4} + F_1)$. We will argue below that the cost of the minimum tiling, which is at least F_1 is $O(N^{1/4})$. As long as the size of a clean interval is $O(N^{1/4})$, this phase of the computation takes time $O(N^{1/2})$.

Stage 2: The next stage of the computation uses x, z, and r to select a term in the cost function towards which it will contribute. Recall that \bar{n} is an upper bound on the number of oracle queries made by M on an input of length n. The i^{th} bit of z will be denoted by z_i . The goal will be to have $\operatorname{check}_k(z)$ intervals checking the k^{th} bit of z, where

$$\operatorname{check}_k(z) = 2^{\overline{n}+5} [(1-z_j) \cdot 2^{\overline{n}-j} + z_j \cdot 2^{\overline{n}}]$$

From the string x, the size of the grid N is computed, as is $\mu(N)$ the number of intervals after N-3 steps of a correct computation of the Layer 1 Turing Machine. The time and space complexity of the computation in Stage 2 is bounded by a polynomial in n, which is polylogarithmic in N. By Lemmas 5.3 and 4.25, given x of length n, the values of N and $\mu(N)$ can be computed in poly(n) time, which is polylogarithmic in N.

The output of the function f on input x with oracle responses z is denoted by f(x, z) which is also computed by the Turing Machine. Note that in the idealized case in which the interval sizes go from $\mu(N) + 1$ down to 2, the value $I = \mu(N) + 2 - r$ is an almost unique identifier for each interval going from 1 up to $\mu(N)$ from left to right. Note that even in a fault-free computation, if the computation in Layer 1 finishes in the middle of an iteration of the Outer Loop, the sequence of interval sizes will deviate slightly from the idealized case. The computation in each interval will perform different tasks, depending on the value of I.

Value of $I = \mu(N) + 2 - r$	Action Taken
$I \leq 0$	Transition to q_{acc} and halt
	Compute the bit to check $k(r)$
$1 \le I \le \sum_{k=1}^{\overline{n}} \operatorname{check}_k(z)$	as described below
	Go to Stage 3
$\sum_{k=1}^{\overline{n}} \operatorname{check}_k(z) + 1 \le I \le \sum_{k=1}^{\overline{n}} \operatorname{check}_k(z) + 2^3 f(x, z)$	Transition to q_{rej} and halt
$\sum_{k=1}^{\overline{n}} \operatorname{check}_k(z) + 2^3 f(x, z) < I$	Transition to q_{acc} and halt

There is a cost of +1 for any computation square that enters a q_{rej} state, so rejecting computations incur a cost of exactly 1. Accepting computations do not incur any cost. The value of k(r) is defined to be the smallest index k such that

$$\mu(N) - r + 2 \le 2^{\overline{n} + 5} \sum_{j=1}^k \operatorname{check}_k(z)$$

In the next stage, the computation (if it did not stop in Stage 2) will check the $k(r)^{th}$ bit of z.

Stage 3: If $z_{k(r)} = 0$, then the TM transitions to q_{rej} and halts. If $z_{k(r)} = 1$, then the TM simulates the Turing Machine M until the point of the $k(r)^{th}$ query, using $z_1, \ldots, z_{k(r)-1}$ as the oracle responses for the first k(r) - 1 oracle queries. Let s be the input to the $k(r)^{th}$ oracle query. The computation now simulates
the verifier V on input s using a witness that is guessed. If V accepts, the cost is 0 and if V rejects the cost is 1. If $s \in L'$, there is a witness that causes V to accept s, which implies that there is a 0-cost tiling of that strip in Layer 4. If $s \notin L'$, then any tiling will either have an illegal square because the TM was not correctly executed or will have a cost of 1 when V terminates.

6.6 Putting the Layers Together

The costs for computations are realized by having any legal computation square which transitions to q_{rej} have a cost of 1. We will call these *rejecting* squares in order to distinguish them from illegal squares which in general have a higher cost. We are finally ready to define the cost of a square over all four layers of the tiling. Consider a square of four tiles where each tile is described by it's tile type for each later. Let f_i denote the indicator variable that is 1 if the Layer *i* tile types are an illegal square for Layer *i*, and is 0 otherwise. Let p_1 and p_3 designate if the square has an illegal pair in its bottom two tiles for Layers 1 and 3. Let *r* be an indicator variable denoting whether the square is a rejecting square in Layer 4. The cost of the square is:

$$r + 48(f_1 + p_1) + 5(f_2 + p_3 + f_3 + f_4)$$

Thus if F_i is the number of illegal pairs or squares in Layer *i*, and if *R* is the number of rejecting squares in Layer 4, the total cost of a tiling is

$$R + 48F_1 + 5(F_2 + F_3 + F_4)$$

 $48F_1 + 5(F_2 + F_3 + F_4)$ is the cost from illegal pairs and squares. We will call R the rejection cost for the tiling.

We need to establish that regardless of whether $x \in L$, the minimum cost tiling has no illegal pairs or squares and the choice of z corresponds the correct oracle responses for the queries to language L'. We first establish an upper bound on the minimum cost tiling of an $N \times N$ grid.

Lemma 6.12 [Upper Bound on the Minimum Cost of a Tiling] There is a tiling of the $N \times N$ grid whose cost is at most $N^{1/4}/4 \log N$.

Proof: Consider a tiling with no illegal pairs or squares in which the string z used for the oracle output bits is all 0's. According to Lemma 4.24, the sizes of the intervals are contained in $\{\mu(N) + 2, \ldots, 1\}$ with at most one duplicate. Let $T = \sum_{k=1}^{\overline{n}} \operatorname{check}_k(z) + 2^3 f(x, z)$. The leftmost T intervals will incur a cost of 1 since all the query responses are assumed to be 0. The other intervals will not incur any cost. Since there can be at most one duplicate in the range $\mu(N) + 1, \ldots, \mu(N) - (T - 2)$, the total cost will be at most T + 1. The highest order bit of check₁(z) is in location $\overline{n} - 1$. Therefore, the highest order bit of T is $2\overline{n} + 4$ and the value of T + 1 is at most $2^{2\overline{n}+5}$, which by Claim 6.1 for large enough N can assumed to be at most $N^{1/4}/4 \log N$.

Lemma 6.13 For sufficiently large N, the minimum cost tiling has at least one clean long-form interval at the end of Layer 4.

Proof: If S is the set of sizes of clean intervals in the last row of Layer 4, then Lemma 6.11 says that $|\{2, 3, \ldots, \mu(N) + 1\} - S| \leq 44F_1 + F_2 + F_3 + F_4 + 3$. By Lemma 4.25, the value of $\mu(N)$ is at least $N^{1/4}/2$. If the tiling has a minimum cost then by Lemma 6.12,

$$44F_1 + F_2 + F_3 + F_4 \le \frac{N^{1/4}}{4\log N}.$$

Therefore $|\{2, 3, \ldots, N^{1/4}/2 + 1\} - S| \le N^{1/4}/4 \log N + 3$. By Lemma 6.10, any clean interval of size at least $\log N + 5$ is a long-form interval. Therefore for large enough N, there is at least one long-form interval.

Any tiling in which F_3 , the number of illegal pairs or squares in Layer 3, is greater than $N^{1/4}/10 \log N$ will have cost at least $\frac{5}{10}N^{1/4}/\log N$ since each illegal pair or square in Layer 3 contributes 5 to the overall cost. We know from Lemma 6.12 that such a tiling will not be a minimum cost tiling. Therefore, we can ignore those tilings and assume that the condition in Item 4 of Lemma 6.10 are met. This implies that there is a single $y \in \mathcal{D}^*$ in every clean long-form interval at the end of Layer 3. Define Cost(y, c) to be the cost of the minimum cost tiling whose clean large-form intervals all have string y and that have c illegal pairs or squares.

The following Lemma says that we can ignore tilings with illegal pairs or squares.

Lemma 6.14 For every y, and every c > 0, $Cost(y, 0) \le Cost(y, c)$.

Proof: Fix the string $y \in \mathcal{D}^n$. Let T_c be a minimum cost tiling with string y and c illegal squares. Similarly for T_0 . Let C_i denote the number of illegal squares on Layer i in T_c . We only know that at least one of the C_i 's is positive. The cost of T_c from illegal squares is $48F_1 + 5(F_2 + F_3 + F_4)$. The cost of T_0 from illegal squares is 0. Let R(T) denote the rejection cost of tiling T. We will prove that $R(T_0) - R(T_c) \leq 48F_1 + 5(F_2 + F_3 + F_4)$.

Let s_1, \ldots, s_m be the lengths of the clean intervals in the last row of Layer 4 for T_c . Any clean interval of size s in T_c incurs exactly the same cost as a clean interval of size s in T_0 . Because the intervals are clean, the computations inside those intervals is the same and correct. Since the size of the interval is the same, the value of y and r for the two intervals is the same. Therefore the bit k(r) of z that is checked in the interval is the same. Since T_c and T_0 are both assumed to be minimum cost tilings, the best witness for each computation in Layer 4 is chosen. In other words, if there is a 0-cost tiling for that interval, it will be used in both T_c and T_0 .

If T_0 has $\mu(N)$ intervals, those intervals will all have sizes in the range 1 through $\mu(N) + 2$. Furthermore, according to Lemma 4.24, there is only one number in that range such that T_0 has two intervals of that size. This one extra interval will contribute a cost of at most 1 to the overall cost. If S is the set of sizes of the clean intervals at the end of Layer 4 in T_c , then the difference in rejection costs between T_0 and T_c is at most $|\{2, 3, \ldots, \mu(N) + 1\} - S| + 1$.

According to Lemma 6.11, $|\{2, 3, \dots, \mu(N) + 1\} - S| \le 44F_1 + F_2 + F_3 + F_4 + 3$, which means that

$$R(T_0) - R(T_c) \le 44F_1 + F_2 + F_3 + F_4 + 4$$

Since at least one F_i is positive,

$$44F_1 + F_2 + F_3 + F_4 + 4 \le 48F_1 + 5(F_2 + F_3 + F_4)$$

We can now focus on tilings that have no illegal squares.

Lemma 6.15 In any tiling with no illegal squares, the largest T intervals will be wide enough to complete their computations, where $T = \sum_{k=1}^{\overline{n}} check_k(z) + 2^3 f(x, z)$.

Proof: Suppose input string x maps to the number N in the reduction. According to Lemma 4.25, the number of intervals at the end of Layer 1 is at least $N^{1/4}/2$. The largest $N^{1/4}/4$ of these intervals have size at least $N^{1/4}/4$. By Claim 6.1, any of these intervals will be large enough to complete a computation of the verifier V. All the other computations in Layer 4 as well as the other layers are polynomial in n and therefore polylogarithmic in N.

We need to establish that $T \leq N^{1/4}/4$ so that the intervals used in the computation are among the $N^{1/4}/4$ largest. The value of T is maximized if the string z is all 1's. In this case the value of T is at most $2^{2\overline{n}+5}$. By Claim 6.1, we can assume that $2^{2\overline{n}+5} \leq N^{1/4}/4$.

Let $\operatorname{num}(k)$ be the number of intervals that check the k^{th} bit of z. The goal is to have $\operatorname{num}(k) = \operatorname{check}_k(z)$. Let $\operatorname{num}(f)$ be the number of intervals whose value $\mu(N) - r + 2$ is in the range $\sum_{k=1}^{\overline{n}} \operatorname{check}_k(z) + 1$ through $\sum_{k=1}^{\overline{n}} \operatorname{check}_k(z) + 2^3 f(x, z)$. The goal is to have $\operatorname{num}(f) = 2^3 f(x, z)$. The following lemma shows that actual values for the num functions are not far from the goal.

Lemma 6.16 For any $S \subseteq [\bar{n}]$, in a fault-free tiling:

$$\sum_{j \in S} check_j(z) + 2^3 f(x, z) - 1 \le num(f) + \sum_{j \in S} num(b) \le \sum_{j \in S} check_j(z) + 2^3 f(x, z) + 2^3 f($$

Proof: The set of interval sizes r that check the k^{th} bit are exactly those for which $\mu(N) + 2 - r$ is in the range

$$\sum_{j=1}^{k-1} \operatorname{check}_j(z) + 1 \quad \text{through} \quad \sum_{j=1}^k \operatorname{check}_j(z).$$

The value of num(f) are the number of intervals with size r such that $\mu(N) + 2 - r$ is in the range

$$\sum_{j=1}^{\overline{n}} \operatorname{check}_j(z) + 1 \quad \text{through} \quad \sum_{j=1}^{\overline{n}} \operatorname{check}_j(z) + 2^3 f(x, z).$$

Note that all of the above ranges are disjoint and contained in $\{2, \ldots, \mu(N) + 2\}$. If the multi-set of all $\mu(N) - r + 2$ for all the intervals is exactly 1 through $\mu(N)$, then for every k, $\operatorname{num}(k)$ is exactly $\operatorname{check}_k(z)$ and $\operatorname{num}(f) = 2^3 f(x, z)$. According the Lemma 4.24, the multi-set of interval sizes for a correct computation is contained in $\{2, \ldots, \mu(N) + 2\}$. Moreover, there are at most two integers missing from this range and at most one duplicate. The Lemma follows.

Let \bar{y} be a string such that $f(\bar{y}) = x1$ and $g(\bar{y}) = \bar{z}$, where \bar{z} is the correct answer to all of the oracle queries made by M to the L' oracle on input x. Note that the string \bar{y} may not be unique because the number of oracle calls \bar{n} is less than n, the number of bits in \bar{z} , so bits $\bar{n} + 1$ through n of \bar{z} can be arbitrary.

Lemma 6.17 Consider a tiling of an $N \times N$ grid, where $N = 4n(1x^R) - 2w(x1) + 3$, for some binary string x. Let \bar{y} be a string such that $f_1(\bar{y}) = x1$ and $g(\bar{y}) = \bar{z}$, where the j^{th} bit of \bar{z} is the correct answer answer to the j^{th} oracle query, for $j = 1, \ldots, \bar{n}$. For every $y \in \mathcal{D}^n$, $Cost(\bar{y}, 0) \leq Cost(y, 0)$.

Proof: By Lemma 6.10, in the last row of Layer 3 every clean long-form interval has a y such that $f_1(y) = x1$. Since the translation rules preserve the string, then any clean interval in the first row of Layer 4 will also have $f_1(y) = x1$.

Let \overline{n} be the number of oracle calls made by Turing Machine M on input x. We need to establish that the minimum is achieved when the first \overline{n} bits of $f_2(y) = z$ are the same as the first \overline{n} bits of \overline{z} .

By induction. Assume that we have established that the first k bits of the minimum z must match \bar{z} in order to achieve the minimum cost. The inputs to the first k + 1 oracle queries are now fixed. Call these s_1, \ldots, s_{k+1} . Now suppose that $\bar{z}_{k+1} = 1$. That means $s_{k+1} \in L'$. Any string that agrees with \bar{z} in the first k bits and has $z_{k+1} = 0$, will pay a cost of num(k+1) which is at least check_{k+1} $(x, z) - 1 = 2^{2\bar{n}-k+4} - 1$. Suppose instead we use the string that has $z_{k+1} = 1$ followed by a string of zeros. The intervals that are checking bit k + 1 can be tiled at 0 cost because s_{k+1} is in fact in L. The intervals that are checking bits k + 2 through \bar{n} as well as the intervals implementing the cost $2^3 f(x, z)$ will incur a cost of num $(f) + \sum_{j=k+2}^{\bar{n}} \text{num}(j)$ which by Lemma 6.16, is at most

$$2^{3}f(x,z) + \sum_{j=k+2}^{\bar{n}} \operatorname{check}_{j}(x,z) + 2 \le 2^{3}(2^{2\bar{n}-k+1}-1) + 2 = 2^{2\bar{n}-k+4} - 6$$

Since this is less than the cost of the incorrect guess $z_{k+1} = 0$, the incorrect guess for z_{k+1} can not yield the minimum cost when the correct guess $\bar{z}_{k+1} = 1$.

Now suppose that $\bar{z}_{k+1} = 0$. That means $s_{k+1} \notin L'$. Any string that agrees with \bar{z} in the first k bits and has $z_{k+1} = 1$, will pay a cost of $\operatorname{num}(k+1)$ which is at least $2^{2\bar{n}+5}$. Note that since $s_{k+1} \notin L'$, when the verifier V is run on input s_{k+1} , it must reject, which means that the intervals that check bit k+1 will incur a cost of 1. Suppose instead we use $z_{k+1} = 0$ and 0's for the remaining bits of z. The cost will be $\operatorname{num}(f) + \sum_{i=k+1}^{\bar{n}} \operatorname{num}(j)$ which by Lemma 6.16, is at most

$$2^{3}f(x,z) + \sum_{j=k+1}^{\bar{n}} \operatorname{check}_{j}(x,z) + 2 \le 2^{3}(2^{2\bar{n}-k+2}-1) + 2 = 2^{2\bar{n}-k+5} - 6.$$

Since this is less than the cost of the incorrect guess $z_{k+1} = 1$, the incorrect guess for z_{k+1} can not yield the minimum cost when the correct guess $\bar{z}_{k+1} = 0$.

We have shown that regardless of the true value for \bar{z}_{k+1} , an incorrect guess for \bar{z}_{k+1} will result in a higher cost than the correct guess.

We now have all the pieces in place to prove the reduction.

Theorem 6.18 Consider a tiling of an $N \times N$ grid, where $N = 4n(1x^R) - 2w(x1) + 3$, for some binary string x. Then the value of f(x) can be recovered from the cost of the minimum cost tiling of an $N \times N$ grid.

Proof: By Lemmas 6.14 and 6.17, the minimum cost tiling does not have any illegal pairs or squares and guesses a y that maps to the correct x for the input and the correct z for the oracle responses. The overall cost of the tiling will be

$$\sum_{j=1}^{n} (1-z_j) \operatorname{num}(j) + \operatorname{num}(f)$$

According to Lemma 6.16, the value will be one larger or two smaller than

$$2^{\overline{n}+5} \sum_{j=1}^{\overline{n}} (1-z_j) 2^{\overline{n}-j} + 2^3 f(x,\bar{z})$$

By dividing the minimum cost tiling by 8 and rounding to the nearest integer, the lowest order \overline{n} bits will be the value of $f(x, \overline{z}) = f(x)$.

7 Parity Weighted Tiling

The construction for Parity Weighted Tiling is almost exactly the same as with Function Weighted Tiling. We slightly modify the translation of intervals from Layer 3 to Layer 4 as follows. The translation rules from Layer 3 to Layer 4 translate any j or \overline{j} tile to j, for $j \in \mathcal{D}$. S is translated to (q_{s1}/S) or (q_{s2}/S) , and t is translated to t for any $t \in \{+, \#, X, B, T, \triangleright, \lhd\}$. The states from Layer 3 are all dropped, so any tile of the form (q/c) is translated to whatever c would be translated to, according to the rules above. These translation rules ensure that every clean interval is translated to a clean interval as long as the tiles in the interval are translated correctly. Thus every clean long-form interval has the form: $X(q_s/S)\mathcal{D}^*B^*T X$. The ambiguity in whether S is translated to (q_{s1}/S) or (q_{s2}/S) is resolved by the translation rule that $\lhd S$ must be translated to $\lhd (qs1/S)$ and X S must be translated to X(qs2/S). Thus the leftmost interval (if it is a clean long-form interval) looks like $(q_{s1}/S)\mathcal{D}^*B^*E$ and every other clean long-form interval looks like $(q_{s2}/S)\mathcal{D}^*B^*E$. We are now reducing from a language $L \in \mathbb{P}^{NEXP}$ which is computed by a polynomial time Turing Machine M with access to a NEXP oracle. All intervals except for the leftmost interval behave in exactly the same way as for the function version, except that they incur a cost of 2 for entering a rejection state. Note that we can think of the function for the decision problem as just mapping to a single bit, depending on whether M accepts or rejects. The computation in the leftmost interval starts in a different start state which indicates that it will simulate the Turing Machine M on input (x, z) and incur a rejection cost of +1 depending on whether M accepts or not.

Finally multiply the cost of an illegal pair or square from the Function Weighted Tiling construction by 2. Note that all costs, except the cost of the computation in the leftmost interval are all a multiple of 2 times their corresponding cost in the Function Weighted Tiling construction, so the analysis in Section 6 comparing costs of different tilings still holds.

Theorem 7.1 Consider a tiling of an $N \times N$ grid, where $N = 4n(1x^R) - 2w(x1) + 3$, for some binary string x. Then the minimum cost tiling of an $N \times N$ grid is odd if $x \in L$ and is even if $x \notin L$.

Proof: By Lemmas 6.14 and 6.17, the minimum cost tiling does not have any illegal pairs or squares and guesses a y that maps to the correct x for the input and the correct z for the oracle responses. Since the string y is the same in all the long-form intervals, the the leftmost interval has the correct input x and the correct outputs to the oracle queries. All costs in the tiling are even, except for the penalty at the end of the computation of the leftmost interval. This computation will accept if and only if $x \in L$. If the computation accepts, the cost in this interval is 0 and the overall cost of the minimum cost tiling is even. If the computation rejects, then the cost in this interval is 1 and the cost of the entire tiling is odd.

8 Acknowledgements

We are grateful to the Simons Institute for the Theory of Computing, at whose program on the "The Quantum Wave in Computing" this collaboration began.

References

- [AGIK09] Dorit Aharonov, Daniel Gottesman, Sandy Irani, and Julia Kempe. The power of quantum systems on a line. *Communications in Mathematical Physics*, 287(1):41–65, Jan 2009.
- [AI21] Dorit Aharonov and Sandy Irani. Hamiltonian complexity in the thermodynamic limit. arXiv:2107.06201, 2021.
- [Amb14] Andris Ambainis. On physical problems that are slightly more difficult than qma. In 2014 IEEE 29th Conference on Computational Complexity (CCC), pages 32–43, 2014.
- [Bah82] F Baharona. On the computational complexity of ising spin glass models. Journal of Physics A: Mathematical and General, 15(10):3241–3253, 1982.
- [BCO17] Johannes Bausch, Toby Cubitt, and Maris Ozols. The complexity of translationally invariant spin chains with low local dimension. *Annales Henri Poincaré*, 18(11):3449–3513, Oct 2017.
- [CPGW15] Toby S. Cubitt, David Perez-Garcia, and Michael M. Wolf. Undecidability of the spectral gap. Nature, 528(7581):207–211, Dec 2015.

- [GHLS15] Sevag Gharibian, Yichen Huang, Zeph Landau, and Seung Woo Shin. Quantum hamiltonian complexity. Foundations and Trends® in Theoretical Computer Science, 10(3):159–282, 2015.
- [GI13] Daniel Gottesman and Sandy Irani. The quantum and classical complexity of translationally invariant tiling and hamiltonian problems. *Theory of Computing*, 9(2):31–116, 2013.
- [GPY19] Sevag Gharibian, Stephen Piddock, and Justin Yirka. Oracle complexity classes and local measurements on physical hamiltonians. arXiv:1909.05981, 2019.
- [GY19] Sevag Gharibian and Justin Yirka. The complexity of simulating local measurements on quantum systems. *Quantum*, 3:189, September 2019.
- [Ist00] Sorin Istrail. Statistical mechanics, three-dimensionality and np-completeness. i. universality of intractability for the partition function of the ising model across non-planar lattices. pages 87–96, 01 2000.
- [Kre86] Mark W. Krentel. The complexity of optimization problems. In Alan L. Selman, editor, *Structure in Complexity Theory*, pages 218–218, Berlin, Heidelberg, 1986. Springer Berlin Heidelberg.
- [KSV02] A. Yu. Kitaev, A. H. Shen, and M. N. Vyalyi. Classical and Quantum Computation. American Mathematical Society, USA, 2002.
- [OT05] R. Oliveira and B. Terhal. The complexity of quantum spin systems on a two-dimensional square lattice. *arXiv:0504050*, 2005.
- [Pap94] Christos H. Papadimitriou. Computational complexity. Addison-Wesley, 1994.
- [Rob71] Raphael Robinson. Undecidability and nonperiodicity for the tilings of the plane. *Invent. Math.*, 12:177–209, 1971.
- [Wan60] Hao Wang. Proving theorems by pattern recognition. Communications of the ACM, 3(4):220–234, 1960.
- [WBG20] James D. Watson, Johannes Bausch, and Sevag Gharibian. The complexity of translationally invariant problems beyond ground state energies. arXiv:2012.12717, 2020.
- [WC21] James D. Watson and Toby S. Cubitt. Computational complexity of the ground state energy density problem. *arXiv:2107.05060*, 2021.