

Making Digital Objects FAIR in High Energy Physics: An Implementation for Universal FeynRules Output (UFO) Models

Mark S. Neubauer¹, Avik Roy^{1*} and Zijun Wang¹

¹ University of Illinois at Urbana-Champaign

* avroy@illinois.edu

March 17, 2023

Abstract

Research in the data-intensive discipline of high energy physics (HEP) often relies on domain-specific digital contents. Reproducibility of research relies on proper preservation of these digital objects. This paper reflects on the interpretation of principles of Findability, Accessibility, Interoperability, and Reusability (FAIR) in such context and demonstrates its implementation by describing the development of an end-to-end support infrastructure for preserving and accessing Universal FeynRules Output (UFO) models guided by the FAIR principles. UFO models are custom-made python libraries used by the HEP community for Monte Carlo simulation of collider physics events. Our framework provides simple but robust tools to preserve and access the UFO models and corresponding metadata in accordance with the FAIR principles.

Contents

1	Introduction	2
2	The Need to FAIRify UFO Models	3
3	Cyberinfrastructure for FAIRifying UFOs	4
3.1	UFOManager	5
3.2	UFOMetadata	7
3.3	FAIRifying UFOManager and UFOMetadata	8
4	Outlook and Conclusion	8
A	Example Content of Enriched Metadata	10
B	Demonstration of Usage of UFODownload	12
C	List of UFO models FAIRified via UFOManager and UFOMetadata	12
	References	13

1 Introduction

Much of ongoing research in the discipline of high energy physics (HEP) require using high-end computational resources. Examples include analyzing petabyte scale data collected at the Large Hadron Collider (LHC) [1] or obtaining precise theoretical predictions that may require taking into account matrix element calculation from thousands of Feynman diagrams [2]. Being such a computationally intensive research discipline, HEP research uses different kinds of digital objects (DOs). These DOs used in HEP include large datasets obtained from detector operation or Monte Carlo (MC) simulations, data analysis software like [ROOT](#) [3], MC simulation software like [Pythia](#) [4], [Sherpa](#) [5], [Herwig](#) [6], and [MadGraph](#) [7], dedicated libraries like [LHAPDF](#) [8] for calculating the parton distribution functions, as well as numerous privately developed codes and software packages, documentations, tutorials and notebooks. While collaborations facilitate the preservation of their data and common software frameworks for usage both within and outside of the collaboration¹, preservation of digital resources independently developed by smaller research groups or individuals is equally important to be able to reproduce the results from HEP research. Hence, a significant amount of community-wide effort and resources has been put forward in order to preserve these DOs. For instance, the Durham High-Energy Physics Database ([HEPData](#)) [11] is an open-access repository established for preserving and sharing scattering data from HEP experiment, containing digitized details of plots and tables from thousands of physics analysis publications. Similar efforts have been put forward to preserve and reuse data analysis code and frameworks as well as statistical models (see Refs. [12–14] for example). These efforts emphasize the importance of a holistic approach in preserving different kinds of digital objects. The importance of such preservation has been repeatedly iterated in literature, especially in the context of reinterpretation and reproduction of analysis results in HEP [13, 15–17].

In order to make datasets Findable, Accessible, Interoperable, and Reusable (FAIR), a set of data principles have been defined so that scientific datasets could be readily reused by both humans and machines [18]. Originally envisioned for preservation of scientific datasets, the FAIR principles have been interpreted in the context of different kinds of digital objects, including research software [19], notebooks [20], and machine learning models [21, 22]. Interpretation and application of FAIR principles for HEP datasets has been explored in Ref. [23]. Exploring FAIR principles in the context of DOs other than datasets is also becoming popular in HEP. For instance, the [NNPDF collaboration](#) has developed a FAIR-inspired open-source framework for parton distribution analyses [24]. Making DOs FAIR (i.e. FAIRification) requires dedicated efforts on two fronts- (i) establishing guidelines for developing new digital contents so that they conform to the FAIR principles and (ii) developing tools to allow FAIRification of existing digital contents. Given the diversity of digital resources used in HEP research, it is in general expected that the exact manifestation of FAIR principle-driven tools will depend on the nature of the digital object itself.

¹For example, the ATLAS collaboration supports dedicated data storage facility [9] and maintenance of data processing software [10] for its members

Developing dedicated cyberinfrastructure is a novel paradigm in facilitating open and FAIR science. For instance, the [Cookiecutter](#) tool [25] allows structural organization of machine learning model repositories, development of containers, and publishing such codebases with persistent identifiers like digital object identifiers (DOIs). In this paper, we demonstrate the development of dedicated FAIRification tool in order to preserve **Universal FeynRules Output** (UFO) [26] models. These models are customized python libraries with a predefined format, often used to store information about beyond standard model (BSM) physics models, and can be used as plug-in libraries for MC simulation of BSM physics with event generator software. In the following section, we briefly describe the content and format of UFO models and motivate the necessity of their FAIRification. Section 3 introduces the proposed framework for making UFO models FAIR and finally, the broader outlook inspired by this work in FAIRifying UFO models is discussed in the final remarks in Section 4.

2 The Need to FAIRify UFO Models

The physics program of large collider experiments like the LHC spends major efforts in search of BSM physics. These searches for BSM physics are motivated by novel theoretical extensions of the standard model (SM). The UFO model format was first introduced in Ref. [26] in order to streamline the process of matrix element calculations for BSM physics models in a generator independent way.

The UFO model format organizes the contents of the new physics as a self-contained python library. It contains a collection of *model-independent* and *model-dependent* python scripts (Table 1). While the model-independent scripts include general technical functionalities of the model, the model-dependent files contain physics-specific information. For instance, the script `particles.py` contains information about all fundamental particles defined within the scope of the model and their corresponding properties like color, charge, and spin quantum numbers, PDG identifier [27], parameters representing their mass and widths etc.

Model-independent files	Model-dependent files
<code>__init__.py</code>	<code>particles.py</code>
<code>object_library.py</code>	<code>coupling_orders.py</code>
<code>function_library.py</code>	<code>parameters.py</code>
<code>write_param_card.py</code>	<code>vertices.py</code>
	<code>couplings.py</code>
	<code>lorentz.py</code>

Table 1: List of model-independent and model-dependent files traditionally included in the UFO format

The primary motivation of developing the UFO format philosophically coincides with the FAIR principles. Content of BSM physics Lagrangians were generally organized as text files, whose format depended on the choice of MC generation software. Developing new physics models as python libraries enabled using the same digital format to be interoperable across different MC generation platforms like MadGraph, Herwig, and Sherpa [6, 7, 28]. Since its introduction, the UFO format has been widely used to develop phenomenological BSM physics models. At the LHC experiments, these models are regularly used to generate MC events for

BSM physics searches. In many cases, these models are developed in association with physics publications that explain and validate the underlying theoretical models. However, the preservation of these models as persistent digital contents has not been ideal. Since its inception, many of the UFO models have typically been hosted in the [FeynRules Model Database](#) [29]. Most of these models are simply hosted as compressed containers like a `.tar` or `.zip` file, without any persistent identifier, trackable version controlling, or well-documented machine readable metadata. Some models like the SMEFTsim [30] package are now maintained with modern software management tools like `git` based version controlling [31] and hosted as [Github](#) repositories. However, the standard FAIRification practices like use of persistent digital identifiers or developing machine-readable metadata are yet to be normative within the community. Moreover, hosting a project on [Github](#) or similar platforms alone does not make DOs FAIR as these repositories are not persistent and often offer additional challenges to maintain the reliability and integrity of the DOs they host [32]. Without any well-defined guideline on community-wide agreed upon practices to preserve such digital contents, it can be difficult to validate, reproduce, reinterpret, or recast any research that relies on these models. For instance, the analysis performed by the ATLAS collaboration in Ref. [33] uses a number of UFO models for generating MC events for dark matter signal. These models were hosted by CERN’s `svnweb` service² that used the `subversion` version controlling tool [34]. Since the discontinuation of this service and a complete shift to [gitlab](#) (another `git` based version controlling system) as the designated DO repository for CERN, the URLs pointed to by the corresponding references are no longer valid. Moreover, those references neither identify the authors of the model nor refer to any metadata that might allow a reader to access any information about the construction of the model. In situations like this, having no persistent identifiers associated with these contents makes it virtually impossible to identify the content or version of a UFO model used in a certain physics analysis, track changes across versions, or attribute citation credit to developers of these digital contents. Also, reusing these models to reproduce validation results or reinterpret physics analyses can become challenging. Given these UFO models directly contribute to a large number of HEP publications, ensuring reproducibility of these results require these models to be preserved in an open and FAIR way.

3 Cyberinfrastructure for FAIRifying UFOs

Facilitating FAIRification of UFO models must consider certain aspects of current practices of developing and using UFO models. Given that the UFO format is widely used, any tool to facilitate their FAIRification must not interfere with the processes of how to develop or use them. Also, the tool should be capable of FAIRifying pre-existing UFO models and allow distinct and persistent identification of different versions of the same model. Additionally, these tools should facilitate generation and preservation of rich metadata with proper context and details regarding the model while allow users to make use of this metadata to search for and download these models. Finally, any tool dedicatedly developed to FAIRify UFO models should itself be made FAIR.

Keeping these criteria in mind, the cyberinfrastructure for FAIRification of UFO models

²It used to be hosted on <http://svnweb.cern.ch/>. Currently, this web service is discontinued and this link is no longer active

has been developed in two independently maintained public repositories- [UFOManager](#) and [UFOMetadata](#). The following subsections address the functionality of each of these repositories.

3.1 UFOManager

The `UFOManager` repository contains a collection of python scripts that can be used to-

- i. perform validation checks on a UFO model
- ii. develop enriched machine-readable metadata for each model
- iii. publish these models with persistent DOIs and independently preserve their metadata
- iv. upload a new version of the previously uploaded model
- v. search for models with keywords
- vi. download models according to user's choice

Among the aforementioned functionalities, (i)-(iv) are facilitated by the script `UFUUpload.py` while the remaining functionalities are supported by the script `UFODownload.py`. Many of the existing UFO models were developed using Python 2. Hence, the module `UFUUpload.py` has been developed to be compatible with both versions of Python. The `UFODownload` script, however, is only compatible with Python 3. The instructions for creating the appropriate environments and installing dependencies are included in the `README` of the package.

The `UFUUpload` and `UFODownload` scripts can be run as standalone scripts to perform the desired task. The `UFUUpload` script can be run in five independent modes, which has to be mentioned as a command line argument when running the script in standalone mode. The script can be run on the command-line interface as a simple Python script using either of the following commands-

```
python UFUUpload.py <operation-mode>
python -m UFOManager.UFUUpload <operation-mode>
```

where `<operation-mode>` refers to one of the following five strings- `Validation Check`, `Generate metadata`, `Upload model`, `Update new version`, and `Upload metadata to GitHub`. The functionality provided by each of these operation modes can be easily understood from their names. The script is designed to run interactively, so necessary inputs are requested from the user at different stages of executing the script. In order to use the `UFUUpload` script, the user must provide a list of locally accessible directories in a `.txt` file where each directory houses a single UFO model along with an initial metadata file called `metadata.json`, in the format of a `json` file. Storing metadata in the format of `json` files ensures that it is simultaneously human and machine-readable, and also compatible with multiple programming platforms ensuring its interoperability. In the process of FAIRifying these models with persistent DOIs, they are uploaded to [Zenodo](#) [35]. This also allows trackable version controlling for the models since [Zenodo](#) provides unique DOIs for different versions of the same entry as well as a unique *concept DOI* that can be used to locate all versions of a given content.

`UFOManager` can also be used as a dedicated Python package and can be imported and used as a Python package using the following syntax-

```
from UFOManager import UFUUpload
UFUUpload.UFUUpload(<operation-mode>,<model-list>)
```

where `<operation-mode>` represents one of the previously mentioned operation modes and `<model-list>` is the text file with a list of UFO models.

Successful publishing of model relies on creation of enriched metadata, which eventually relies on the successful completion of validation checks. Hence, any attempt to upload a new model or update the version of an existing model will automatically perform validation checks and create enriched metadata. This enriched metadata is built upon the information provided by the user in the initial `metadata.json` file. This initial metadata must contain at least three fields- (i) the names of the authors of the model along with contact information (an email address) for at least one of the authors, (ii) a brief description of the model, and (iii) a digital identifier (an arxiv ID or a DOI) for an associated publication that explains the underlying model and provides physics validation. The initial metadata can also contain additional information like the link to the webpage that hosts the model (e.g. a [Github](#) repository or the link to a model's location within FeynRules Model Database). The content provided in the `metadata.json` file to register one of the UFO models used to describe the physics of Vector-like Quarks (VLQs) [36] using our tool is given in Table 2.

```
{
  "Author": [
    {
      "name": "Luca Panizzi",
      "affiliation": "Uppsala University",
      "contact": "luca.panizzi@physics.uu.se",
    },
    {
      "name": "Benjamin Fuks",
      "affiliation": "Sorbonne University",
      "contact": "fuks@lpthe.jussieu.fr"
    }
  ],
  "Paper_id": {
    "doi": "10.1140/epjc/s10052-017-4686-z",
    "arXiv": "1610.04622"
  },
  "Description": "Vector-like Quark UFO Model at NLO QCD with four flavour scheme",
  "Model Homepage": "https://feynrules.irmp.ucl.ac.be/wiki/NLOModels"
}
```

Table 2: Content of initial `metadata.json` file used to FAIRify the UFO model in Ref. [36]

The validation check looks for the presence of required files in the UFO model, inspects the initial metadata for the necessary content and their validity (e.g. if the provided arxiv ID represents a valid entry). Then, it checks if the model can be imported as a standalone python package, since that is the intended mode of usage for these models. Afterwards, it inspects each of the independent scripts within the UFO model. These inspections include tests on whether the script can be imported as a Python module, each essential script contains a non-zero count of required objects, and some basic validation checks. These checks include validating the uniqueness and validity of the PDG IDs assigned to the particles as well as whether the model supports Next-to-Leading-Order (NLO) calculations. Validation of PDG IDs is performed using the `Particles` package [37]. During these checks, it also collects information for the enriched metadata.

Besides the fields provided with the initial metadata, the enriched metadata, which also

is stored as a `json` file, contains additional information about the number of parameters, couplings, coupling orders, vertices, lorentz tensors, propagators, and decays contained in different scripts within the model. It also contains maps of fundamental particles and their PDG IDs defined in the model. The enriched metadata also records the version of Python the model has been validated with and the version identifier of the model itself. A field for storing the model's DOI is created. If the user wishes to upload the model or update an existing model with the current content, the model is uploaded to **Zenodo** using its REST-API service. The DOI generated during uploading the model to **Zenodo** is stored in the enriched metadata. The content of the enriched metadata generated by the tool for the previously mentioned VLQ UFO model [36] is given in Table A1.

The enriched metadata is finally uploaded in the **UFOMetadata** repository. To perform these uploads the user needs to have registered accounts with both **Zenodo** and **Github** and obtain secure access tokens for the respective accounts. These access tokens allow validating the registered user accounts and use the APIs in a secure manner.

The final piece of the **UFOManager** tool is the **UFODownload** script, which allows the users to search for and access these models. It can be run as a standalone Python script from the command line interface using either of the following commands-

```
python UFODownload.py <operation-mode>
python -m UFOManager.UFODownload <operation-mode>
```

where `operation-mode` refers to one of the following strings- `Search for model`, `Download model`, and `Search and Download`. To use it within a facilitator script, it can be run as-

```
from UFOManager import UFODownload
UFODownload.UFODownload(<operation-mode>)
```

The **UFODownload** script allows the user to search for UFO models based on a number of keywords, including arxiv ID or DOI of associated publication, PDG ID of new elementary particles, DOI of the model, and model name. Table B2 shown an example of the usage of this script using the interactive command line interface to search for models with a certain PDG ID. When searching for models, it lists all available versions of the models whose metadata are available in **UFOMetadata**. It uses the `zenodo_get` package [38] to allow users to download the desired models. The script interfaces with the latest version of the **UFOMetadata** repository and offers the user a set of options based on the search criteria. Upon request, the metadata and corresponding model are downloaded by this script.

3.2 UFOMetadata

FAIRification of DOs require their metadata to include qualifying reference to the original content and be stored independently of the data [18]. Hence, the enriched metadata generated by the **UFOManager** is stored as independent `json` files in the **UFOMetadata** repository. Every time a user decides to upload their model using the **UFOManager** tool, the corresponding metadata is sent to the **UFOMetadata** repository. However, it is also possible for users to independently register their model and submit the corresponding metadata for addition to the repository. Every request to add metadata must be done via a *pull request*, which triggers an automated **Github** workflow for continuous integration. The workflow performs a validation check on the new content to ensure- (i) none of the previously existing files has been renamed,

modified, or deleted, (ii) the newly added metadata files have all the fields that are generated with the `UFOManager` tool, and (iii) newly added models have unique and valid DOIs. These pull requests are currently merged by the maintainers of repository in a regular interval to keep the repository updated with the latest additions. It should be noted that the `UFODownload` script makes use of the latest version of the `main` branch of the `UFOMetadata` repository, so access to any new metadata is only made available after the pull requests are merged.

3.3 FAIRifying UFOManager and UFOMetadata

While the tools facilitated via `UFOManager` and `UFOMetadata` enable FAIRification of UFO models, it is only expected to have these tools made available as FAIR DOs themselves. The latest stable releases of these repositories are made available with persistent DOIs via `Zenodo`. The metadata can for these repositories can be accessed via URLs and obtained with JSON Schema with `Zenodo`'s REST API. The use of JSON Schema provides clear human and machine readable documentation. The following table gives the DOIs for the latest versions of these packages.

Content	Latest Version	DOI/URL
<code>UFOManager</code>	2.0.0	10.5281/zenodo.7066042 [39]
Metadata for <code>UFOManager</code>	N/A	https://zenodo.org/api/records/7066042
<code>UFOMetadata</code>	2.0.0	10.5281/zenodo.7066046 [40]
Metadata for <code>UFOMetadata</code>	N/A	https://zenodo.org/api/records/7066046

Table 3: DOIs for the latest stable releases of `UFOManager` and `UFOMetadata` and URLs to access their corresponding metadata

4 Outlook and Conclusion

With an ever-increasing volume of DOs required in mainstream HEP research, FAIR management and preservation of these contents is necessary to ensure transparent, reliable, and reproducible results. We discussed in this paper in the context of UFO models why having standardized FAIRification practices is necessary and developed a set of simple, customized tools to facilitate such practices. `UFOManager` and `UFOMetadata` rely on well-established and widely used programming tools and practices and offer a unified approach to save UFO models as FAIR DOs. Our work additionally serves as an example on developing customized, automatic FAIRification tools for DOs used in HEP research that can serve as a guide to establishing similar practices in orthodox DO management.

Acknowledgements

We thank Benjamin Fuks for permitting the use of publicly available UFO models authored by him. We also thank Olivier Mattelaer for encouraging discussions and suggestions on improving the content of enriched metadata for UFO models. *A.R.*: This work was supported by the FAIR Data program of the U.S. Department of Energy, Office of Science, Advanced

Scientific Computing Research, under contract number DE-SC0021258. *M.S.N.*: This work was supported by the National Science Foundation under OAC-1841456. *Z.W.*: This work was supported by the National Science Foundation under Cooperative Agreement OAC-1836650.

A Example Content of Enriched Metadata

```

{
  "Model name": "UFO model for Vector-like Quarks at NLO QCD with four flavor scheme",
  "Model Doi": "10.5281/zenodo.6977663",
  "Author": [
    {
      "name": "Luca Panizzi",
      "affiliation": "Uppsala University",
      "contact": "luca.panizzi@physics.uu.se",
    },
    {
      "name": "Benjamin Fuks",
      "affiliation": "Sorbonne University",
      "contact": "fuks@lpthe.jussieu.fr"
    }
  ],
  "Paper_id": {
    "doi": "10.1140/epjc/s10052-017-4686-z",
    "arXiv": "1610.04622"
  },
  "Description": "Vector-like Quark UFO Model at NLO QCD with four flavour scheme",
  "Model Homepage": "https://feynrules.irmp.ucl.ac.be/wiki/NLOModels",
  "Number of decays": 10,
  "Number of coupling orders": 3,
  "Number of coupling tensors": 97,
  "Number of lorentz tensors": 39,
  "Number of parameters": 98,
  "Number of vertices": 125,
  "Number of propagators": 4,
  "Model Python Version": 2,
  "Model Version": 1.0,
  "Allows NLO calculations": true,
  "All Particles": {
    "ve": 12, "ghG~": -82, "y~": -6000008,
    "u~": -2, "vm~": -14, "vt": 16, "s": 3,
    "c~": -4, "t~": -6, "G0": 250, "u": 2,
    "ve~": -12, "tp": 6000006,
    "x~": -6000005, "G-": -251,
    "ta+": -15, "G+": 251, "vt~": -16, "e-": 11,
    "y": 6000008, "e+": -11, "H": 25, "t": 6,
    "vm": 14, "d~": -1, "s~": -3,
    "mu~": 13, "ghG": 82, "bp": 6000007, "a": 22,
    "x": 6000005, "ta-": 15,
    "b~": -5, "Z": 23,
    "d": 1, "g": 21,
    "W-": -24, "W+": 24,
    "tp~": -6000006, "mu+": -13,
    "bp~": -6000007, "c": 4, "b": 5, },
    "SM Particles": {
      "ve": 12, "u~": -2, "vm~": -14, "vt": 16, "s": 3,
      "c~": -4, "t~": -6, "u": 2, "ve~": -12,
      "ta+": -15, "vt~": -16, "e-": 11,
      "e+": -11, "H": 25, "t": 6,
      "vm": 14, "d~": -1, "s~": -3,
      "mu~": 13, "a": 22, "ta-": 15,
      "b~": -5, "Z": 23,
      "d": 1, "g": 21,
      "W-": -24, "W+": 24,
      "tp~": -6000006, "mu+": -13,
      "bp~": -6000007, "c": 4, "b": 5, },
    "New elementary particles": {
      "G0": 250, "y~": -6000008, "tp": 6000006,
      "bp": 6000007, "x~": -6000005, "x": 6000005,
      "y": 6000008, "tp~": -6000006, "G-": -251,
      "G+": 251, "bp~": -6000007 }
    "BSM particles with standard PDG codes": {
      "G-": -251, "G+": 251,
      "tp": 6000006, "tp~": -6000006,
      "G0": { "charge": 0.0, "spin": 1, "id": 250 },
      "bp": { "charge": -1/3, "spin": 2, "id": 6000007 },
      "x": { "charge": -5/3, "spin": 2, "id": -6000005 },
      "y": { "charge": 4/3, "spin": 2, "id": -6000008 },
      "y~": { "charge": -4/3, "spin": 2, "id": 6000008 },
      "x~": { "charge": 5/3, "spin": 2, "id": 6000005 },
      "bp": { "charge": 1/3, "spin": 2, "id": -6000007 }
    }
  }
}

```

Table A1: Content of the enriched metadata file obtained from the Uploadv2.py to FAIRify the UFO model in Ref. [36]

B Demonstration of Usage of UFODownload

```
$ python -m UFOManager.UFODownload 'Search for model'
Please enter you Github access token:
You can search for model with Paper_id, Model Doi, pdg code, name (of certain particles).
Please choose your keyword type: pdg code
Please enter your needed pdg code: 6000006
Based on your search, we find models below:
```

Metadata file	Model Name	Paper ID	Model DOI
VLQ_v5_5FNS_NLO_UFO.V2.0.json	UFO model for Vector-like Quarks at NLO QCD with five flavor scheme (third generation)	1610.04622	10.5281/zenodo.7038823
VLQ_v5_4FNS_only3rd_NLO_UFO.json	UFO model for Vector-like Quarks at NLO QCD with four flavor scheme (third generation)	1610.04622	10.5281/zenodo.7041539
vlq_v4_4fns.json	UFO model for Vector-like Quarks at NLO QCD with four flavor scheme	1610.04622	10.5281/zenodo.6977663
VLQ_v4_5FNS_UFO.json	UFO model for Vector-like Quarks at NLO QCD with five flavor scheme	1610.04622	10.5281/zenodo.6991118
VLQ_v5_4FNS_NLO_UFO.V2.0.json	UFO model for Vector-like Quarks at NLO QCD with four flavor scheme	1610.04622	10.5281/zenodo.7038908
VLQ_v5_4FNS_NLO_UFO.V3.0.json	UFO model for Vector-like Quarks at NLO QCD with four flavor scheme	1610.04622	10.5281/zenodo.7039382
VLQ_v5_5FNS_only3rd_NLO_UFO.json	UFO model for Vector-like Quarks at NLO QCD with five flavor scheme (third generation)	1610.04622	10.5281/zenodo.7041528

Do you still want to search for models? Please type in Yes or No: No

Table B2: Sample output from an interactive command line usage of the UFODownload script

C List of UFO models FAIRified via UFOManager and UFOMetadata

The following table contains a set of example UFO models that were FAIRified by using the UFOManager and UFOMetadata tools. These models are hosted at the publicly available FeynRules Model Database [29].

Model Name	Version	DOI	Metadata
universal framework for t-channel dark matter models [42]	1.0	10.5281/zenodo.6991108 [41]	DMSimpt_NLO_v1_2_UFO
Spin-2 simplified model [43]	1.0	10.5281/zenodo.6908818 [44]	DMspin2
NLO predictions in supersymmetric QCD [45]	1.0	10.5281/zenodo.6991116 [46]	SUSYQCD_UFO
Vector-like Quarks at NLO QCD	1.0	10.5281/zenodo.6991118 [47]	VLQ_v4_5FNS_UFO
with five flavor scheme [48]	2.0	10.5281/zenodo.7038823 [49]	VLQ_v5_5FNS_NLO_UFO.V2.0
Vector-like Quarks at NLO QCD with five flavour scheme (third generation) [48]	1.0	10.5281/zenodo.7041528 [50]	VLQ_v5_5FNS_only3rd_NLO_UFO
Vector-like Quarks at NLO QCD with four flavor scheme [48]	1.0	10.5281/zenodo.6977663 [51]	vlq_v4_4fns
	2.0	10.5281/zenodo.7038908 [52]	VLQ_v5_4FNS_NLO_UFO.V2.0
Vector-like Quarks at NLO QCD with four flavour scheme (third generation) [48]	1.0	10.5281/zenodo.7041539 [53]	VLQ_v5_4FNS_only3rd_NLO_UFO
NLO predictions for sgluon pair production [54]	1.0	10.5281/zenodo.6991112 [55]	sgluons_NLO
stop pair production to ttbar and missing energy [54]	1.0	10.5281/zenodo.6991114 [56]	stop_ttmet_NLO
pseudo-Nambu-Goldstone Dark Matter [57]	1.0	10.5281/zenodo.7065996 [58]	SM_with_pNG_UFO
	2.0	10.5281/zenodo.7066011 [59]	SM_with_pNG_UFO_py3.V2.0

Table C3: DOIs for some of the UFO models made FAIR by the UFOManager and UFOMetadata tools

References

- [1] G. Brumfiel et al., Down the petabyte highway, Nature **469**(20), 282 (2011), doi:<https://doi.org/10.1038/469282a>.
- [2] M. Gerlach, F. Herren and M. Steinhauser, Wilson coefficients for Higgs boson production and decoupling relations to $\mathcal{O}(\alpha_s^4)$, Journal of High Energy Physics **2018**(11), 1 (2018), doi:[https://doi.org/10.1007/JHEP11\(2018\)141](https://doi.org/10.1007/JHEP11(2018)141).
- [3] R. Brun and F. Rademakers, ROOT—an object oriented data analysis framework, Nuclear instruments and methods in physics research section A: accelerators, spectrometers, detectors and associated equipment **389**(1-2), 81 (1997), doi:[https://doi.org/10.1016/S0168-9002\(97\)00048-X](https://doi.org/10.1016/S0168-9002(97)00048-X).
- [4] T. Sjöstrand, S. Mrenna and P. Skands, A brief introduction to PYTHIA 8.1, Computer Physics Communications **178**(11), 852 (2008), doi:<https://doi.org/10.1016/j.cpc.2008.01.036>.
- [5] T. Gleisberg, S. Höche, F. Krauss, M. Schönherr, S. Schumann, F. Siegert and J. Winter, Event generation with SHERPA 1.1, Journal of High Energy Physics **2009**(02), 007 (2009), doi:<https://doi.org/10.1088/1126-6708/2009/02/007>.
- [6] J. Bellm, G. Bewick, S. Ferrario Ravasio, S. Gieseke, D. Grellscheid, P. Kirchgaßer, F. Loshaj, M. R. Masouminia, G. Nail, A. Papaefstathiou et al., Herwig 7.2 release note, The European Physical Journal C **80**(5), 1 (2020), doi:<https://doi.org/10.1140/epjc/s10052-020-8011-x>.
- [7] J. Alwall, M. Herquet, F. Maltoni, O. Mattelaer and T. Stelzer, MadGraph 5: going beyond, J. High Energy Phys. **2011**(6), 128 (2011), doi:[10.1007/JHEP06\(2011\)128](https://doi.org/10.1007/JHEP06(2011)128).
- [8] A. Buckley, J. Ferrando, S. Lloyd, K. Nordström, B. Page, M. Rüfenacht, M. Schönherr and G. Watt, LHAPDF6: parton density access in the LHC precision era, The European Physical Journal C **75**(3), 1 (2015), doi:<https://doi.org/10.1140/epjc/s10052-015-3318-8>.
- [9] M. Branco, D. Cameron, B. Gaidioz, V. Garonne, B. Koblitz, M. Lassnig, R. Rocha, P. Salgado and T. Wenaus, Managing ATLAS data on a petabyte-scale with DQ2, In Journal of Physics: Conference Series, vol. 119, p. 062017. IOP Publishing, doi:<https://doi.org/10.1088/1742-6596/119/6/062017> (2008).
- [10] K. Cranmer, The ATLAS analysis architecture, Nucl. Phys. B, Proc. Suppl. **177**(ATL-SLIDE-2007-028), 126 (2007), doi:[10.1016/j.nuclphysbps.2007.11.096](https://doi.org/10.1016/j.nuclphysbps.2007.11.096).
- [11] E. Maguire, L. Heinrich and G. Watt, HEPData: a repository for high energy physics data, In Journal of Physics: Conference Series, vol. 898, p. 102006. IOP Publishing, doi:[10.1088/1742-6596/898/10/102006](https://doi.org/10.1088/1742-6596/898/10/102006) (2017).
- [12] K. Cranmer and I. Yavin, RECAST—extending the impact of existing analyses, Journal of High Energy Physics **2011**(4), 1 (2011), doi:[10.1007/JHEP04\(2011\)038](https://doi.org/10.1007/JHEP04(2011)038).

- [13] K. Cranmer, S. Kraml, H. Prosper, P. Bechtle, F. Bernlochner, I. M. Bloch, E. Canonero, M. Chrzaszcz, A. Coccaro, J. Conrad et al., Publishing statistical models: Getting the most out of particle physics experiments, SciPost Physics **12**(1), 037 (2022), doi:<https://doi.org/10.21468/SciPostPhys.12.1.037>.
- [14] B. Dumont, B. Fuks, S. Kraml, S. Bein, G. Chalons, E. Conte, S. Kulkarni, D. Sengupta and C. Wymant, Toward a public analysis database for LHC new physics searches using MADANALYSIS 5, The European Physical Journal C **75**(2), 1 (2015), doi:<https://doi.org/10.1140/epjc/s10052-014-3242-3>.
- [15] P. Ivie, C. Zheng, K. Lannon and D. Thain, An analysis of reproducibility and non-determinism in hep software and ROOT data, In Journal of Physics: Conference Series, vol. 898, p. 102007. IOP Publishing, doi:<https://doi.org/10.1088/1742-6596/898/10/102007> (2017).
- [16] W. Abdallah, S. AbdusSalam, A. Ahmadov, A. Ahriche, G. Alguero, B. Allanach, J. Y. Araz, A. Arbey, C. Arina, P. Athron et al., Reinterpretation of LHC results for new physics: status and recommendations after run 2, SciPost physics **9**(2), 022 (2020), doi:[10.21468/SciPostPhys.9.2.02](https://doi.org/10.21468/SciPostPhys.9.2.02).
- [17] V. D. Elvira, S. Gottlieb, O. Gutsche, B. Nachman, S. Bailey, W. Bhimji, P. Boyle, G. Cerati, K. Cranmer, G. Davies et al., The future of high energy physics software and computing, arXiv preprint arXiv:2210.05822 (2022).
- [18] M. D. Wilkinson, M. Dumontier, I. J. Aalbersberg, G. Appleton, M. Axton, A. Baak, N. Blomberg, J.-W. Boiten, L. B. da Silva Santos, P. E. Bourne et al., The FAIR guiding principles for scientific data management and stewardship, Scientific data **3**(1), 1 (2016), doi:<https://doi.org/10.1038/sdata.2016.18>.
- [19] N. P. Chue Hong, D. S. Katz, M. Barker, A.-L. Lamprecht, C. Martinez et al., Introducing the FAIR principles for research software (FAIR4RS principles) **9**, 622 (2022), doi:[10.1038/s41597-022-01710-x](https://doi.org/10.1038/s41597-022-01710-x).
- [20] R. A. Richardson, R. Celebi, S. Van Der Burg, D. Smits, L. Ridder, M. Dumontier and T. Kuhn, User-friendly composition of FAIR workflows in a notebook environment, In Proceedings of the 11th on Knowledge Capture Conference, pp. 1–8, doi:<https://doi.org/10.1145/3460210.3493546> (2021).
- [21] D. S. Katz, F. E. Psomopoulos and L. J. Castro, Working towards understanding the role of FAIR for machine learning, In DaMaLOS, pp. 1–6, doi:[10.4126/FRL01-006429415](https://doi.org/10.4126/FRL01-006429415) (2021).
- [22] N. Ravi, P. Chaturvedi, E. Huerta, Z. Liu, R. Chard, A. Scourtas, K. Schmidt, K. Chard, B. Blaiszik and I. Foster, FAIR principles for AI models, with a practical application for accelerated high energy diffraction microscopy, arXiv preprint arXiv:2207.00611 (2022), doi:<https://doi.org/10.48550/arXiv.2207.00611>.
- [23] Y. Chen, E. Huerta, J. Duarte, P. Harris, D. S. Katz, M. S. Neubauer, D. Diaz, F. Mokhtar, R. Kansal, S. E. Park et al., A FAIR and AI-ready Higgs boson decay dataset, Scientific Data **9**(1), 1 (2022), doi:<https://doi.org/10.1038/s41597-021-01109-0>.

- [24] R. D. Ball, S. Carrazza, J. Cruz-Martinez, L. Del Debbio, S. Forte, T. Giani, S. Iranipour, Z. Kassabov, J. I. Latorre, E. R. Nocera et al., An open-source machine learning framework for global analyses of parton distributions, The European Physical Journal C **81**(10), 1 (2021), doi:<https://doi.org/10.1140/epjc/s10052-021-09747-9>.
- [25] Cookiecutter data science: A logical, reasonably standardized, but flexible project structure for doing and sharing data science work, Available at <https://drivendata.github.io/cookiecutter-data-science>.
- [26] C. Degrande, C. Duhr, B. Fuks, D. Grellscheid, O. Mattelaer and T. Reiter, UFO—the universal FeynRules output, Computer Physics Communications **183**(6), 1201 (2012), doi:<https://doi.org/10.1016/j.cpc.2012.01.022>.
- [27] P. D. Group, R. Workman, V. Burkert, V. Crede, E. Klempt, U. Thoma, L. Tiator, K. Agashe, G. Aielli, B. Allanach et al., Review of particle physics, Progress of Theoretical and Experimental Physics **2022**(8), 083C01 (2022), doi:<https://doi.org/10.1093/ptep/ptac097>.
- [28] S. Höche, S. Kuttimalai, S. Schumann and F. Siegert, Beyond standard model calculations with sherpa, The European Physical Journal C **75**(3), 1 (2015), doi:<https://doi.org/10.1140/epjc/s10052-015-3338-4>.
- [29] Feynrules model database, Available at <https://feynrules.irmp.ucl.ac.be/wiki/ModelDatabaseMainPage>.
- [30] I. Brivio, Y. Jiang and M. Trott, The SMEFTsim package, theory and tools, Journal of High Energy Physics **2017**(12), 1 (2017), doi:[https://doi.org/10.1007/JHEP12\(2017\)070](https://doi.org/10.1007/JHEP12(2017)070), The package is hosted at <https://github.com/SMEFTsim/SMEFTsim>.
- [31] J. Loeliger and M. McCullough, Version Control with Git: Powerful tools and techniques for collaborative software development, O'Reilly Media, Inc. (2012).
- [32] E. Kalliamvakou, G. Gousios, K. Blincoe, L. Singer, D. M. German and D. Damian, The promises and perils of mining github, In Proceedings of the 11th working conference on mining software repositories, pp. 92–101, doi:[10.1109/MSR.2009.5069475](https://doi.org/10.1109/MSR.2009.5069475) (2014).
- [33] The ATLAS Collaboration, Constraints on mediator-based dark matter and scalar dark energy models using $\sqrt{s}=13$ TeV pp collision data collected by the ATLAS detector, Journal of High Energy Physics **2019**(5), 1 (2019), doi:[https://doi.org/10.1007/JHEP05\(2019\)142](https://doi.org/10.1007/JHEP05(2019)142).
- [34] B. W. Fitzpatrick, C. M. Pilato and B. Collins-Sussman, Version control with Subversion, O'Reilly Media (2004).
- [35] European Organization For Nuclear Research (CERN) and OpenAIRE, Zenodo, doi:[10.25495/7GXX-RD71](https://doi.org/10.25495/7GXX-RD71) (2013).
- [36] L. Panizzi and B. Fuks, VLQ UFO model at NLO QCD with 4FS, doi:[10.5281/zenodo.6977663](https://doi.org/10.5281/zenodo.6977663), Can be obtained from <https://doi.org/10.5281/zenodo.6977663> (2022).
- [37] E. Rodrigues and H. Schreiner, scikit-hep/particle: Version 0.21.1, doi:[10.5281/zenodo.7503366](https://doi.org/10.5281/zenodo.7503366) (2023).

- [38] D. Völgyes, Zenodo_get: a downloader for zenodo records, doi:[10.5281/zenodo.1261812](https://doi.org/10.5281/zenodo.1261812), Available for download from <https://doi.org/10.5281/zenodo.126181> (2020).
- [39] Z. Wang, A. Roy and M. Neubauer, UFOManager: Tools to preserve and download Universal FeynRules Output (UFO) models, doi:[10.5281/zenodo.7069342](https://doi.org/10.5281/zenodo.7069342), DOI: <https://doi.org/10.5281/zenodo.7069342>. Available at <https://github.com/Neubauer-Group/UFOManager> (2022).
- [40] Z. Wang, A. Roy and M. Neubauer, UFOMetadata: Repository to preserve enriched metadata for Universal FeynRules Output (UFO) models, doi:[10.5281/zenodo.7070131](https://doi.org/10.5281/zenodo.7070131), DOI: <https://doi.org/10.5281/zenodo.7070131>. Available at <https://github.com/Neubauer-Group/UFOMetadata> (2022).
- [41] B. Fuks, UFO for universal framework for t-channel dark matter models, doi:[10.5281/zenodo.6991108](https://doi.org/10.5281/zenodo.6991108), Available at: <https://doi.org/10.5281/zenodo.6991108> (2022).
- [42] C. Arina, B. Fuks and L. Mantani, A universal framework for t-channel dark matter models, The European Physical Journal C **80**(5), 1 (2020), doi:[10.1140/epjc/s10052-020-7933-7](https://doi.org/10.1140/epjc/s10052-020-7933-7).
- [43] G. Das, C. Degrande, V. Hirschi, F. Maltoni and H.-S. Shao, NLO predictions for the production of a spin-two particle at the LHC, Physics Letters B **770**, 507 (2017), doi:<https://doi.org/10.1016/j.physletb.2017.05.007>.
- [44] G. Das, C. Degrande, V. Hirschi, F. Maltoni and H.-S. Shao, Spin 2 simplified model, doi:[10.5281/zenodo.6908818](https://doi.org/10.5281/zenodo.6908818), Available at: <https://doi.org/10.5281/zenodo.6908818> (2022).
- [45] C. Degrande, B. Fuks, V. Hirschi, J. Proudom and H.-S. Shao, Matching next-to-leading order predictions to parton showers in supersymmetric QCD, Physics Letters B **755**, 82 (2016), doi:<https://doi.org/10.1016/j.physletb.2016.01.067>.
- [46] B. Fuks, C. Degrande, V. Hirschi, H.-S. Shao and J. Proudom, UFO for NLO predictions in supersymmetric QCD, doi:[10.5281/zenodo.6991116](https://doi.org/10.5281/zenodo.6991116), Available at: <https://doi.org/10.5281/zenodo.6991116> (2022).
- [47] L. Panizzi and B. Fuks, VLQ UFO model at NLO QCD with 5FS, doi:[10.5281/zenodo.6991118](https://doi.org/10.5281/zenodo.6991118), Available at: <https://doi.org/10.5281/zenodo.6991118> (2022).
- [48] B. Fuks and H.-S. Shao, QCD next-to-leading-order predictions matched to parton showers for vector-like quark models, The European Physical Journal C **77**(2), 1 (2017), doi:<https://doi.org/10.1140/epjc/s10052-017-4686-z>.
- [49] L. Panizzi, Vector-like quark UFO model at NLO QCD with five flavour scheme, doi:[10.5281/zenodo.7038823](https://doi.org/10.5281/zenodo.7038823), Available at: <https://doi.org/10.5281/zenodo.7038823> (2022).
- [50] L. Panizzi, Vector-like quark UFO model at NLO QCD with five flavour scheme (third generation), doi:[10.5281/zenodo.7041528](https://doi.org/10.5281/zenodo.7041528), Available at: <https://doi.org/10.5281/zenodo.7041528> (2022).

- [51] L. Panizzi and B. Fuks, VLQ UFO model at NLO QCD with 4FS, doi:[10.5281/zenodo.6977663](https://doi.org/10.5281/zenodo.6977663), Available at: <https://doi.org/10.5281/zenodo.6977663> (2022).
- [52] L. Panizzi, Vector-like quark UFO model at NLO QCD with four flavour scheme, doi:[10.5281/zenodo.7038908](https://doi.org/10.5281/zenodo.7038908), Available at: <https://doi.org/10.5281/zenodo.7038908> (2022).
- [53] L. Panizzi, Vector-like quark UFO model at NLO QCD with four flavour scheme (third generation), doi:[10.5281/zenodo.7041539](https://doi.org/10.5281/zenodo.7041539), Available at: <https://doi.org/10.5281/zenodo.7041539> (2022).
- [54] C. Degrande, B. Fuks, V. Hirschi, J. Proudom and H.-S. Shao, Automated next-to-leading order predictions for new physics at the LHC: the case of colored scalar pair production, Physical Review D **91**(9), 094005 (2015), doi:<https://doi.org/10.1103/PhysRevD.91.094005>.
- [55] B. Fuks, UFO for NLO predictions for sgluon pair production, doi:[10.5281/zenodo.6991112](https://doi.org/10.5281/zenodo.6991112), Available at: <https://doi.org/10.5281/zenodo.6991112> (2022).
- [56] B. Fuks, UFO for stop pair production to ttbar and missing energy, doi:[10.5281/zenodo.6991114](https://doi.org/10.5281/zenodo.6991114), Available at: <https://doi.org/10.5281/zenodo.6991114> (2022).
- [57] C. Arina, A. Beniwal, C. Degrande, J. Heisig and A. Scaffidi, Global fit of pseudo-nambu-goldstone dark matter, Journal of High Energy Physics **2020**(4), 1 (2020), doi:[https://doi.org/10.1007/JHEP04\(2020\)015](https://doi.org/10.1007/JHEP04(2020)015).
- [58] A. Beniwal, pseudo-Nambu-Goldstone (pNG) dark matter, doi:[10.5281/zenodo.7065996](https://doi.org/10.5281/zenodo.7065996), Available at: <https://doi.org/10.5281/zenodo.7065996> (2022).
- [59] A. Beniwal, pseudo-Nambu-Goldstone (pNG) dark matter, doi:[10.5281/zenodo.7066011](https://doi.org/10.5281/zenodo.7066011), Available at: <https://doi.org/10.5281/zenodo.7066011> (2022).