An Automatically Verified Prototype of the Android Permissions System

Maximiliano Cristiá^{1*†}, Guido De Luca^{2†} and Carlos Luna^{3†}

^{1*}Universidad Nacional de Rosario and CIFASIS, Argentina.
²Universidad Nacional de Rosario, Argentina.
³Universidad de la República, Uruguay.

*Corresponding author(s). E-mail(s): cristia@cifasis-conicet.gov.ar; Contributing authors: gdeluca@dcc.fceia.unr.edu.ar; cluna@fing.edu.uy; †All authors contributed equally to this work

Abstract

In a previous work De Luca and Luna presented formal specifications of idealized formulations of the permission model of Android in the Coq proof assistant. This formal development is about 23 KLOC of Coq code, including proofs. This work aims at showing that $\{log\}$ ('setlog')—a satisfiability solver and a constraint logic programming language—can be used as an effective automated prover for the class of proofs that must be discharged in the formal verification of systems such as the one carried out by De Luca and Luna. We show how the Coq model is encoded in $\{log\}$ and how automated proofs are performed. The resulting $\{log\}$ model is an automatically verified executable prototype of the Android permissions system. Detailed data on the empirical evaluation resulting after executing all the proofs in $\{log\}$ is provided. The integration of Coq and $\{log\}$ as to provide a framework featuring automated proof and prototype generation is discussed.

Keywords: Android, Coq, {log}, security properties, automated proof

1 Introduction

Mobile devices have become an integral part of how people perform tasks in their work and personal lives. The benefits of using mobile devices, however, are sometimes offset by increasing security risks.

Android [1] is an open platform for mobile devices—developed by the Open Handset Alliance led by Google, Inc—that captures more than 85% of the total market-share [2]. Android offers many critical applications in terms of privacy. In order to provide their users the security they expect, Android relies on a multi-party consensus system where user, OS and application must be all in favor of performing a task. Android embodies security mechanisms at both OS and application level. In particular, Android behaves like a multi-threaded Linux system; its security model is similar to that of a multi-user server. Application-level access control is implemented by an Inter-Component Communication reference monitor that enforces mandatory access control policies regulating access among applications and components. Application security is built primarily upon a system of permissions, which specify restrictions on the operations a particular process can perform.

In previous works two of the authors present formal specifications in the Coq proof assistant [3, 4] of idealized formulations of different versions of the permission model of Android [5, 6, 7]. These works formulate and demonstrate, in a non-automatic way, a set of properties of the Android security model. In particular, De Luca and Luna [8] formalize the Android permissions system introduced in versions Nougat, Oreo, Pie and 10. The formal development is about 23 KLOC of Coq code, proofs included.

The present work aims at showing that $\{log\}$ [9]—a satisfiability solver and a constraint logic programming language—can be used as an effective automated prover for the class of proofs that must be discharged in the formal verification of systems such as the one carried out by De Luca and Luna. In this way much of the manual, expert work needed to prove properties in Coq can be avoided. In particular, Cristiá, assisted by De Luca and Luna, encoded in $\{log\}$ the Coq model developed by his coauthors. Hence, this paper shows in detail how different elements and properties of the Coq model can be encoded and proved in $\{log\}$. The resulting $\{log\}$ model is an executable prototype. Additionally, detailed data on the empirical evaluation resulting after executing all the proofs in $\{log\}$ is provided. Finally, the integration of Coq and $\{log\}$ as to provide a framework with automated proof and prototype generation is briefly discussed.

To the best of our knowledge this is the first time that Coq and $\{log\}$ are put together for the verification of a critical system.

Organization of the paper. The rest of the paper is organized as follows. Section 2 provides some background on the Android permission system, its Coq model and $\{log\}$. Next, Section 3 shows how different elements of the Coq model are encoded in the $\{log\}$ language, whereas Section 4 shows how the properties proved true of the Coq model can be encoded as $\{log\}$ satisfiability queries. Section 4.3 provides detailed data on the empirical evaluation resulting after executing all the $\{log\}$ queries described. Section 5 considers related work and finally, Section 6 concludes with a summary of our contributions and directions for future work.

2 Background

This section contains some background on the Android permissions system (2.1); the Coq model developed by De Luca and Luna (2.2); and the $\{log\}$ constraint solver (2.3). Readers may skip any of these subsections if they are familiarized with those topics.

2.1 The Android Permissions System

The Android security model takes advantage of the fact that the entire platform is built upon a Linux kernel and relies primarily on a user-based protection to identify and isolate the resources from each application. In other words, each Android application will have a unique user ID (UID), with restricted permissions, and will run its own process in a private virtual machine. This means that by default, applications will not be able to interact with each other and they will also have limited access to OS resources.

In the Android permissions system, every resource is protected by unique tags or names, called *permissions*, that applications must have been granted before being able to interact with the resource. Permissions can be defined by applications, for the sake of self-protection; and are predefined by Android so applications can get access to system resources, such as the camera or other kind of sensors. Applications must list the permissions they need in the so-called application *manifest*. Permissions are also associated to a *protection level*, depending on how critical the resource that they are securing is. The protection level also determines if the permission will be automatically granted upon installation or if user consent will be required at runtime. Android defines three protection levels: *normal, signature* and *dangerous*.

Permissions related to the same device capability, are grouped into *permissions groups*. For example, reading and editing contacts, are two different permissions. However, when an application requests one of these permissions for the first time, the user will be asked to authorize the "contacts group". If the user accepts, then the behavior goes as follows:

- 1. The requested permission is granted and the system is notified that the user authorized the "contacts group".
- 2. As soon as the application requests another permission from the same group, the system will automatically grant it, without informing the user.

2.2 A Verified Coq Model

As we have said, the Android permissions system has been modeled using the Coq proof assistant [5, 6, 7, 8]. Coq is a formal proof management system based

on higher order logic that allows to write formal specifications and interactively generate machine-checked proofs of theorems. It also provides a (dependently typed) functional programming language that can be used to write executable algorithms. The Coq environment also provides program extraction towards languages like Ocaml and Haskell for execution of certified algorithms [10]. Proofs in Coq are essentially manual and interactive.

The Coq model of the Android permissions system follows the structure of an abstract state machine. In this sense, the model defines a tuple representing the set of states of that machine (Section 2.2.1) and a number of state transitions (called operations) given by means of their pre- and post-conditions (Section 2.2.2). The state of the machine contains both dynamic and static data of the system. In turn, the operations correspond to the actions that either the user, applications or Android can perform concerning the permission system. The security properties that have been proved true of the the model are discussed in Section 2.2.3.

The source code of the Coq model and the proof scripts can be found in a Github repository [11]. File names mentioned in this section refer to that repository.

2.2.1 The State Space

In Figure 1, we show a fragment of Coq code corresponding to the state definition, called System. As can be seen, System is the union of State and **Environment**. The former contains information such as which applications are currently installed (apps), which applications have been executed at least once (alreadyVerified), which groups of permissions were already authorized (grantedPermGroups) and which permissions were granted to each application (perms). In turn, Environment takes care of tracking information that will not change once each application is installed. For example, it contains a mapping between each application and its manifest (manifest), and a mapping between each application and the permissions defined by it (defPerms). In this way System sums up a total of 13 components that represents the whole state of the model. The definitions of more detailed types are not included, for the sake of keeping the presentation brief. The types starting with lowercase correspond to basic parameters modelled as Set in Coq, whereas those starting with a capital letter were defined by more complex Records. From now on, whenever we mention the model's states, we will be referring to elements of type System, unless stated otherwise.

Valid states. The model defines a notion of valid state that captures several well-formedness conditions. This is so to avoid reasoning over some values of System that make no sense either in a real world scenario or in the Coq representation of the system. For example, the valid state predicate forces the permissions defined by applications to be uniquely identified. In other words, if two user-defined permissions have the same ID, then they were defined by the same application (and therefore, they are the same permission). This Coq predicate, called notDupPerm, is shown in Figure 2. Note that without

5

```
1 Record System := sys {
            state: State;
 2
            environment: Environment
 3
 4 }.
 5 Record State := st {
       apps: list idApp;
 6
       alreadyVerified: list idApp;
 7
       grantedPermGroups : mapping idApp (list idGrp);
 8
       perms: mapping idApp (list Perm);
 a
10
        . . .
11 }.
12 Record Environment := env {
       manifest: mapping idApp Manifest;
13
       defPerms: mapping idApp (list Perm);
14
15
        . . .
16 }.
Fig. 1 State definition in Coq
 1 Definition notDupPerm : Prop :=
     forall (a a':idApp) (p p':Perm) (l l':list Perm),
 2
       defPermsForApp a l -> defPermsForApp a' l' ->
 3
       In p l \rightarrow In p' l' \rightarrow idP p = idP p' \rightarrow
 4
        (p=p' /\ a=a').
 5
 6 Definition defPermsForApp (a:idApp) (1:list Perm) : Prop :=
     map_apply (defPerms (environment s)) a = Value 1
 7
     \/ (exists sysapp:SysImgApp,
 8
            In sysapp (systemImage (environment s)) /\
 9
            defPermsSI sysapp = 1 / idSI sysapp = a).
10
Fig. 2 One of the constraints defining the valid state condition
```

notDupPerm, an application could get access to a permission that is protecting some resource just by defining a permission of its own with the same ID.

The valid state predicate also forces that every mapping in the state is a partial function. Figure 3 shows a fragment of this predicate, called allMapsCorrect. The fixpoint declaration map_correct in line 7 is a recursive function that returns true only if there are no repeated elements in the domain of the map. The definition of the valid state property is the result of conjoining 13 different predicates, which are defined within 200 lines of code (file Estado.v).

2.2.2 Operations as State Transitions

The state transitions of the model, called "actions" or "operations", cover the main functionalities of the Android permission system. As an example, Figure 4 shows the semantics of the operation grantAuto, which is responsible for granting a permission to an application that already has an authorization for automatically granting permissions from a certain group. This action is

```
1 Definition allMapsCorrect : Prop :=
     map_correct (manifest (environment s)) /\
 2
     map_correct (cert (environment s)) /\
 3
     map_correct (defPerms (environment s)) /\
 4
     map_correct (grantedPermGroups (state s)) /\
 \mathbf{5}
 6
     . .
 7 Fixpoint map_correct (mp:mapping) : Prop :=
     match mp with
 8
       | nil => True
 9
       (a::rest)=> ~(In (item_index a) (map_getKeys rest)) /\
10
                      map_correct rest
11
     end.
12
Fig. 3 Fragment of allMapsCorrect
```

executed whenever a dangerous permission is granted without explicit consent from the user.

The precondition (pre_grantAuto) establishes that the permission p is listed on the application's manifest (and this manifest, of course, is required to exist). Regarding p, it is also required that it is defined either by the user or the system, that its level is **dangerous** and that it has not been already granted to **app**. Note that the latter is required because lists (instead of sets) are used to keep track of the already granted permissions (see more on sets and lists in Coq in Remark 2 below). Last but not least, the precondition of this action also requires that p belongs to a group **g** that the user has previously authorized for automatic permission granting.

The postcondition (post_grantAuto) basically adds p to (perms a) in the new state s'. This behavior is handled by the auxiliary predicate (grantPerm a p s s'). The rest of the components of the state remain the same.

A non-extensive list of other actions that can be performed in the model is: i) grant, which is the complementary operation of grantAuto, since it represents a permission being granted with explicit consent from the user; ii) revoke or revokeGroup, to remove an ungrouped permission or all of the permission from a group, respectively; iii) hasPermission, to check whether an application has a certain permission or not at a given moment. The model supports 22 operations in total, some of them being considerably more complex than grantAuto. The definition of the formal semantics of these operations comprises around 1,400 lines of Coq code (file Semantica.v).

We close this section with the following important observations.

Remark 1 (State validity is invariant). *De Luca and Luna demonstrated using Coq that each operation preserves valid states.*

Lemma 1 (Validity is invariant).

 $\forall (s \ s' : \mathsf{AndroidST})(a : \mathsf{Action}), valid_state(s) \land s \stackrel{a}{\hookrightarrow} s' \to valid_state(s')$

```
1 Definition grantAuto (p:Perm) (a:idApp) (s s':System) : Prop :=
     pre_grantAuto p a s /\ post_grantAuto p a s s'.
 3 Definition pre_grantAuto (p: Perm) (a: idApp) (s: System) : Prop :=
     (exists m:Manifest, isManifestOfApp a m s /\ In p (use m)) /\
 4
     (isSystemPerm p \/ usrDefPerm p s) /\
 5
     ~(exists lPerm:list Perm,
 6
         map_apply (perms (state s)) a = Value lPerm /\ In p lPerm) /\
 7
     pl p = dangerous /
 8
     (exists (g: idGrp) (lGroup: list idGrp),
 9
         maybeGrp p = Some g / 
10
         map_apply (grantedPermGroups (state s)) a = Value lGroup /\
11
         In g lGroup).
12
13 Definition post_grantAuto (p:Perm) (a:idApp) (s s':System) : Prop :=
     grantPerm a p s s' /\
14
15
     (environment s) = (environment s') /\
     (apps (state s)) = (apps (state s')) /\
16
              (* Other state components remain the same *)
17
     . . .
18 Definition grantPerm (a:idApp) (p:Perm) (s s':System) : Prop :=
     (forall (a':idApp) (lPerm:list Perm),
19
         map_apply (perms (state s)) a' = Value lPerm ->
20
         exists lPerm':list Perm,
21
             map_apply (perms (state s')) a' = Value lPerm' /\
22
             forall p':Perm, In p' lPerm -> In p' lPerm') /\
23
     (forall (a':idApp) (lPerm':list Perm),
24
         map_apply (perms (state s')) a' = Value lPerm' ->
25
         exists lPerm:list Perm,
26
             map_apply (perms (state s)) a' = Value lPerm /\
27
28
             forall p':Perm,
                 In p' lPerm' -> ~In p' lPerm -> (a=a' /\ p=p')) /\
29
     (exists lPerm':list Perm,
30
         map_apply (perms (state s')) a = Value lPerm' /\
31
         In p lPerm') /\
32
     map_correct (perms (state s')).
33
Fig. 4 Semantics of grantAuto in Coq
```

Remark 2 (Sets and lists in Coq). In Coq sets of type T can be encoded as $T \rightarrow Prop$, i.e. functions from T onto Prop. An evident consequence of this choice is that the resulting specification is not executable. In particular, the program extraction mechanism provided by Coq to extract programs from specifications cannot be used in this case. Hence, a specification encoding sets as $T \rightarrow Prop$ should be refined into an specification encoding sets as list, i.e. list T, if a prototype is needed. In this case, the new specification must take care of repetitions and permutations. The Coq model of the Android permissions system developed by De Luca and Luna [8] was meant to produce a certified program. Then, De Luca and Luna use list T to encode sets. \Box

```
1 Theorem CannotAutoGrantWithoutGroup :
    forall (s s': System) (p: Perm) (g: idGrp) (a: idApp),
2
      pl p = dangerous ->
3
      maybeGrp p = Some g ->
4
       ~(exists (lGroup: list idGrp),
\mathbf{5}
            map_apply (grantedPermGroups (state s)) a = Value lGroup /\
6
            In g lGroup) ->
7
       ~ exec s (grantAuto p a) s' ok.
8
Fig. 5 Safety property about automatic granting
```

2.2.3 Properties of the Model

De Luca, Luna and their colleagues use Coq [5, 6, 7, 8] to analyze properties of the Coq model. In particular, several security properties establish that the model provides protection against unauthorized access to sensitive resources of a device running Android [5, 6]. Using the Coq specification several lemmas were proved showing that the Android security model meets the so-called *principle of least privilege*, i.e. that "each application, by default, has access only to the components that it requires to do its work and no more" [12].

In a recent work, De Luca and Luna [8] present and discuss some properties about Android 10. In that work the focus is on safety-related properties concerning the changes introduced on the later versions of Android (mainly Oreo and 10) rather than on security issues.

Furthermore, using the Coq model, De Luca and Luna precisely state the conditions that would help preventing the exploitation of some well-known vulnerabilities of the Android system [13, 14], like the unauthorized monitoring of information (*eavesdropping*) or inter-application communication (*intent spoofing*). They also prove that, under certain hypotheses, these attacks cannot be carried out [5, 6]. Some of these potentially dangerous behaviors may not be considered in the informal documentation of the platform.

A total of 14 properties have been analyzed with Coq. Next we comment on two of them.

Figure 5 shows the Coq definition of the property stating that the system automatically grants a dangerous permission only when the user had previously authorized the permission group that contains it. Note that in the expression defined in lines 5-7, it is claimed that the group of the permission is not granted to the application in the state **s**. Therefore, line 8 concludes that the execution of **grantAuto** cannot be successful.

In turn, Figure 6 shows the Coq encoding of a scenario where the system is able to automatically grant a dangerous permission to an application even though the application has no other permission of the same group at the moment. This "vulnerable" state is reached when the user authorized that group at some point, then all the permissions of that group were removed but the ability of automatic granting was still kept by the system.

9

```
Theorem ExecAutoGrantWithoutIndividualPerms :
1
         exists (s: System) (p: Perm) (g: idGrp) (a: idApp),
2
         validstate s /
3
         ~ (exists (p': Perm) (permsA: list Perm),
4
               map_apply (perms (state s)) a = Value permsA /\
\mathbf{5}
               In p' permsA /\ maybeGrp p' = Some g) /\
6
         pl p = dangerous /
7
         maybeGrp p = Some g / 
8
         pre_grantAuto p a s.
9
Fig. 6 Edge case scenario found for the automatic granting feature
```

2.3 The {log} Constraint Solver

This paper aims at showing that $\{log\}$ can be used as an effective automated prover for systems such as the Android permissions system. In this way much of the manual, expert work needed to prove properties in Coq can be avoided. Consider that proving all the properties of the Coq model described in Section 2.2 requires 18 KLOC of Coq proof commands.

 $\{log\}$ is a publicly available satisfiability solver and a declarative, set-based, constraint-based programming language implemented in Prolog [9]. $\{log\}$ is deeply rooted in the work on Computable Set Theory [15, 16], combined with the ideas put forward by the set-based programming language SETL [17]. Below we briefly introduce $\{log\}$; more material can be found in Appendix A.

The automated proving power of $\{log\}$ comes from the implementation of several decision procedures for different theories on the domain of finite sets, finite set relation algebra and linear integer arithmetic [18, 19, 20, 21, 22, 23, 24]. All these procedures are integrated into a single solver, implemented in Prolog, which constitutes the core part of the $\{log\}$ tool. Several in-depth empirical evaluations provide evidence that $\{log\}$ is able to solve non-trivial problems [19, 20, 21, 25, 26], including the security domain [27, 28].

 $\{log\}$ provides constraints encoding most of the set and relational operators used in set-based specification languages such as B [29] and Z [30]. For example: un(A, B, C) is a constraint interpreted as $C = A \cup B$; in is interpreted as set membership (i.e., \in); dom(F, D) corresponds to dom F = D; subset(A, B) to $A \subseteq B$; comp(R, S, T) to $T = R \circ S$ (i.e., relational composition); applyTo(F, X, Y) is a weak form of function application; and pfun(F) constrains F to be a (partial) function. The language supports some forms of sets such as the empty set ($\{\}$) and extensional sets ($\{t/A\}$, interpreted as $\{t\}\cup A$); more in Appendix A.1. Formulas in $\{log\}$ are built in the usual way by using the propositional connectives (e.g., &, or, neg, implies), and restricted universal and existential quantifiers (foreach and exists, see Section A.4).

 $\{log\}$ can be used as both a programming language and a satisfiability solver. Within certain limits, $\{log\}$ code enjoys the *formula-program duality*.

Example 1. The following {log} predicate computes the maximum of a set:

```
dec_p_type(smax(set(int),int)).
smax(S,Max) :- Max in S & foreach(X in S, X =< Max & dec(X,int)).</pre>
```

The first line declares the type of smax: the first argument is a set of integers whereas the second is an integer (more in Appendix A.2). The second line defines a clause (as in Prolog) whose body is a {log} formula making use of a restricted universal quantifier (RUQ). dec declares the type of X.

smax is a program, so we can execute it:

{log}=> smax({3,5,1,7,4},Max).
Max = 7

But smax is also a formula, so we can prove properties true of it by proving that their negations are unsatisfiable:

{log}=> neg(smax(S,M) & Y =< M & smax({Y / S},K) implies M = K). false

That is, $\{log\}$ failed to find a finite set S and integer numbers Y, M and K satisfying the above formula. Furthermore, if we attempt to prove an unvalid property $\{log\}$ returns a counterexample:

```
{log}=> neg(smax(S,M) & smax({Y / S},K) implies M = K).
S = {M/N}, K = Y
Constraint: foreach(X in N,M>=X), Y>=M, foreach(X in N,Y>=X), M neq Y
```

In $\{log\}\$ we do not need an specification and a program; the same piece of code is both the program and its specification. This duality is not the result of integrating two tools but a consequence of the mathematical and computational models behind $\{log\}$. However, the formula-program duality pays the price of reduced efficiency. For this reason a $\{log\}$ program must be considered as a prototype of a real implementation.

3 Encoding the Coq Model in {log}

In this section we show how different elements of the Coq model described in Section 2.2 are encoded in the $\{log\}$ language. The complete $\{log\}$ code of the Android permissions system is publicly available¹.

Figure 7 shows the $\{log\}$ encoding of the Coq code shown in Figure 4. Differently from the Coq code, the $\{log\}$ code gathers all the three Coq definitions in a single $\{log\}$ clause (grantAuto). This is so, for example, because the pre- and post-condition may access the same component of the state or may use the same external function. As $\{log\}$ performs a sort of symbolic execution over this code, these double accesses or calls imply more computations thus making automated proof to take considerably longer. These differences

¹https://www.clpset.unipr.it/SETLOG/APPLICATIONS/android.zip

```
1 dec_p_type(grantAuto(set(perm),system,perm,idApp,system)).
 2 grantAuto(SystemPerm,S,P,A,S_) :-
     state(S,St) & state(S_,St_) &
 3
     perms(St,Perms) & grantedPermGroups(St,MG) & perms(St_,Perms_) &
 4
 5
     isManifestOfApp(A,M,S) &
                                                    % pre_grantAuto
     use(M,PM) & P in PM &
 6
     (P in SystemPerm or usrDefPerm(P,S)) &
 7
     (comp({[A,A]},Perms,{}) & PS = {} or applyTo(Perms,A,PS) & P nin PS) &
 8
     pl(P,dangerous) &
 9
     maybeGrp(P,grp(G)) & applyTo(MG,A,SG) & G in SG &
10
     foplus(Perms,A,{P/PS},Perms_) &
                                                    % post_grantAuto
11
     updateGrantAuto(S,Perms_,S_).
12
Fig. 7 \{log\} encoding of the Coq code shown in Figure 4
```

between proof assistants and automated provers should be considered when the model is written for either of both. We will further discuss this in Section 5. Below we explain the encoding in more detail.

The first line declares the type of grantAuto whose head is given in line 2 and whose body is given from line 3 on. The first parameter of grantAuto, SystemPerm, is implicit in the Coq code as there is declared as a global parameter. $\{log\}$ does not support implicit parameters so they have to be explicitly included in every clause where they are needed. Then, s corresponds to S, p to P, app to A and s' to S_ (in $\{log\}$ variables begin with a capital letter). For example, the dec_p_type declaration states that the type of S is system which is defined as a tuple. In this case, each field in the Coq record corresponds to a component in the tuple, as follows (see Figure 1):

[set(idApp),	% apps
<pre>set(idApp),</pre>	% alreadyVerified
<pre>rel(idApp,set(idGrp)),</pre>	% grantedPermGroups
]	

In order to access each component, we have defined predicates, named as the Coq fields, that use Prolog unification:

```
dec_p_type(apps(state,set(idApp))).
apps(S,Apps) :- S = [Apps,2,3,4,5,6,7,8,9].
```

More importantly, the type of each component of system is different from (although equivalent, in some sense, to) the corresponding Coq type. For instance, the Coq type for apps is list idApp, where idApp is of type Set. In turn, in {log}, the type is set(idApp), where idApp is a basic type. According to Coq's and {log}'s semantics idApp means roughly the same in both systems: it is just a set of elements. Conversely, the semantics of list idApp and set(idApp) is quite different because the former means that apps is a list in

Coq whereas the latter implies that it is a finite set in $\{log\}$. Recall that in Coq **apps** is declared as a list although the model uses it as a set.

Similarly, the Coq type of grantedPermGroups is mapping (list idGrp), mapping : Set := list item and item where isthe record {idx:index; inf:info}. That is, grantedPermGroups is basically a list of ordered pairs. However, as the name suggests, the indented usage is for grantedPermGroups to be a finite map or partial function. Furthermore, the range of the map is supposed to be composed of sets rather than lists. The Coq model includes a state invariant stating that this component should be a partial function (recall Figure 3). Instead, the $\{log\}$ type of grantedPermGroups is rel(idApp,set(idGrp)). That is, in {log} this component is a binary relation whose range are sets. Following the Coq model, the {log} model includes a similar state invariant constraining grantedPermGroups to be a partial function (see Section 4.1).

Returning to Figure 7, lines 3 and 4 extract from S and S_t the system components that are needed in the clause. Differently from Coq, in $\{log\}$ we need new variables to access each component. For example, in Coq we can do (state s) to access the state of the system whereas in $\{log\}$ we do state(S,St) where St is a new variable and then we use St to access the components of the state.

In line 5 we call isManifestOfApp(A,M,S) where M is a new variable implicitly existentially quantified. That is, the existential quantifier (exists m:Manifest,...) in line 2 of Figure 4 is not necessary in $\{log\}$. The code in lines 6 and 7 corresponds to the Coq code (isSystemPerm p \/ usrDefPerm p s). In Coq isSystemPerm has type Perm -> Prop which in $\{log\}$ is encoded as set membership to SystemPerm.

Line 8 is interesting because it shows how some complex Coq predicates are encoded as $\{log\}$ constraints. Indeed, line 8 corresponds to (exists lPerm:list Perm,...) in lines 5-6 of Figure 4. That existential quantifier states that: i) a does not belong to the domain of (perms (state s)); or ii) if it does belong then p is not in its image. In $\{log\}$ i) is encoded as comp({[A,A]},Perms,{}) where comp(R,S,T) is a constraint interpreted as $T = R \ S \ S$ (where $\ S$ is relational composition), and [A,A] is an ordered pair. In turn, ii) is encoded as applyTo(Perms,A,PS) which is a constraint stating minimum conditions to apply a binary relation to a point. If Perms can be applied to A, then it has some image (PS); and when Perms cannot be applied to A, we take PS as the empty set. See that PS is used in line 11 to set the new state of the system.

Encoding predicates such as ~(exists lPerm:list Perm,...) as $\{log\}$ constraints is not the same than putting those predicates behind Coq definitions. Indeed, $\{log\}$ implements those constraints at the semantic level. Therefore, encoding complex predicates as constraints is not just a matter of increasing the readability of the model but of increasing $\{log\}$'s automated proving capabilities.

This is particularly noticeable in line 11 of Figure 7 as it encodes grantPerm of Figure 4. {log} defines foplus as follows:

foplus(F,X,Y,G) :- $F = \{[X,Z]/H\} \& comp() \& G = \{[X,Y]/H\}$ or $comp(\{[X,X]\},F,\{\}) \& G = \{[X,Y]/F\}.$ (1)

That is, G is equal to F except in X where: if X is in the domain of F then Y becomes the new image of X; if not, [X, Y] is added. When F is a function then only one pair is changed.

Hence, line 11 is equivalent to state that (perms (state s)) is equal to (perms (state s')) except in app where either (app,{p}) is added to (perms (state s)) or the new image of app is its old image plus {p}. All this, in turn, is expressed in Coq with the quantified predicates of grantPerm.

In the last line, updateGrantAuto updates the system as follows:

updateGrantAuto(S,P,S_) :-S = [St,_S2] & St = [_1,_2,_3,_4,_5,_6,_7,_8,_9] & S_ = [St_,_S2] & St_ = [_1,_2,_3,P,_5,_6,_7,_8,_9].

That is, lines 11-12 of Figure 7 correspond to post_grantAuto in Figure 4.

Remark 3. The $\{log\}$ encoding of Android enjoys the formula-program duality, as explained in Section 2.3. That is, on one hand, clauses such as grantAuto can be executed, thus turning them into a sort of prototype API that can be used to program security-related scenarios. On the other hand, the same $\{log\}$ code is an specification of the Android permissions system. As such, it is possible to use $\{log\}$ to (automatically) prove properties true of the specification. This is the subject of the next section.

4 Encoding Security Properties in {log}

As we have explained in Sections 2.2.1 and 2.2.3 the Coq model verifies several properties. These properties can be divided into two classes: invariance lemmas concerning the concept of valid state (Section 2.2.1), and security properties (Section 2.2.3). In the introduction we set as one of the main goals of this paper assessing $\{log\}$ as an automated prover for the kind of properties used to validate the Coq model—having as a long term goal integrating $\{log\}$ and Coq to optimize the proof process for certain classes of problems.

Hence, in this section we show how the properties proved true of the Coq model can be encoded as $\{log\}$ satisfiability queries. Then, these queries can be executed against the $\{log\}$ program described in Section 3. Every time we get a **false** answer we know that the query is unsatisfiable meaning that its negation is a theorem (see Example 1). If, on the contrary, we get a solution (counterexample) we know the query is satisfiable meaning that its negation is not a theorem (property) derivable from the program.

4.1 Valid State

In this section we show how two of the properties defining the set of valid states are encoded in $\{log\}$. We start with allMapsCorrect defined in Figure 3. As can be seen, this predicate is the conjunction of several map_correct predicates. In turn, map_correct states that its argument is a partial function. In $\{log\}$ pfun(F) constrains F to be a partial function. Hence, when in Coq we have map_correct (grantedPermGroups (state s)) in $\{log\}$ we write²:

```
dec_p_type(allMapsCorrect4(system)).
allMapsCorrect4(S) :-
  dec(GR,rel(idApp,set(idGrp))) &
  state(S,St) & grantedPermGroups(St,GR) & pfun(GR).
```

Note that in {log}, as well as in Coq, we use a combination of types and constraints to state the desired property. That is, dec(GR,rel(idApp,set(idGrp))) restricts the domain of GR to idApp and the range to set(idGrp), whereas pfun(GR) constraints GR to be a function. The dec predicate is enforced during type checking (cf. Appendix A.2) whereas the pfun constraint is enforced during constraint solving (cf. Appendix A.3).

Now we turn our attention to predicate notDupPerm shown in Figure 2. As can be seen, this predicate begins with a universal quantification over several variables of different types. The Coq predicate then goes to restrict the quantified variables to belong to different sets³. For instance, a and 1 must verify defPermsForApp a 1. In turn, defPermsForApp is divided into two cases; let's analyze the first one. In this case 1 is the image of a through (defPerms (environment s)). Then, in a set-based notation such as {log} this is equivalent to:

environment(S,E) & defPerms(E,DP) & [A,L] in DP

where S corresponds to s, and E and DP are new variables. Hence, in {log}, instead of quantifying over types, we can use a RUQ (cf. Example 1 and Section A.4). In other words, we turn Coq's forall (a:idApp) (1:list Perm),... into foreach([A,L] in DP,...). The second case of defPermsForApp can be treated in a similar way because in this case a and 1 are components of sysapp which in turn is an element of the set (systemImage (environment s)). The quantification over p and p' will be discussed shortly.

Therefore, as a general rule, we turn Coq's universal quantifications into $\{log\}$'s RUQ.

Finally, in order to encode notDupPerm in $\{log\}$ we define three clauses corresponding to the result of distributing the two cases of defPermsForApp into the rest of the predicate. That is, in $\{log\}$, we have:

- notDupPerm1 where a, a', 1 and 1' are quantified over defPerms
- notDupPerm2 where a, a', 1 and 1' are quantified over systemImage

²Some dec predicates are avoided for readability.

³In Coq they are, formally, lists.

 notDupPerm3 where a and l are quantified over defPerms, whereas a' and l' are quantified over systemImage

As an example we show notDupPerm3:

```
dec_p_type(notDupPerm3(system)).
notDupPerm3(S) :-
environment(S,E) & defPerms(E,DP) & systemImage(E,SS) &
foreach([[A1,L1] in DP, A2 in SS],[ID2,L2],
foreach([P1 in L1, P2 in L2],[IP1,IP2],
IP1 = IP2 implies P1 = P2 & A1 = ID2,
idP(P1,IP1) & idP(P2,IP2)
),
idSI(A2,ID2) & defPermsSI(A2,L2)
).
```

As can be seen, the universal quantification over p and p' present in the Coq model becomes the inner formula of the outermost RUQ in $\{log\}$. For instance, L1 quantifies over the range of DP and then P1 quantifies over L1.

As explained in Section 2.2.1, the definition of valid state is given in terms of a state invariant (see Lemma 1). In $\{log\}$, instead of proving that the encoding of *valid_state* is a state invariant, we prove that each of the properties included in it is a state invariant. In other words, we prove the encoding in $\{log\}$ of:

for all a: Action where $valid_state(s) \cong I_1(s) \land \cdots \land I_n(s)$. This is so because attempting to prove Lemma 1 may make $\{log\}$ to incur in a lengthy computation due to the presence of unnecessary hypothesis. For example, if in order to prove $I_k(s')$ the only necessary hypothesis are $I_k(s)$ and a, the presence of $I_j(s)$ $(j \neq k)$ may make $\{log\}$ to attempt to prove the lemma by first exploring $I_j(s)$ instead of $I_k(s)$. Once this proof path is exhausted, $\{log\}$ will attempt the proof by exploring $I_k(s)$, which will eventually succeed. The net result is $\{log\}$ taking longer than necessary.

Each of the proof obligations in (2) is encoded in $\{log\}$ as the following query:

neg(I_k(S) & a(S,S_) implies I_k(S_))

where I_k , $a(S,S_)$ and $S_$ correspond to I_k , $s \xrightarrow{a} s'$ and s', respectively.

4.2 Security Properties

In order to encode in $\{log\}$ the security properties described in Section 2.2.3, we classified them as follows:

A. Properties given in terms of a sequence of operations.

- B. Existential properties, i.e. properties establishing the existence of a state where some predicate holds.
- C. Universal properties, i.e. classical system properties.

In general, properties in class A cannot be expressed in $\{log\}$. However, the proof of some of these properties can be divided into two steps: firstly, some predicate is proved to be invariant w.r.t. every operation; secondly, the first result is used to prove that any sequence of operations verifies the desired property. The first step is hard, whereas the second is rather simple. $\{log\}$ can be used in the first step by proving that the involved predicate is indeed an invariant (as shown in Section 4.1). Once all these proof obligations have been discharged they could be used in the second step. Hence, we encoded in $\{log\}$ the first step and used $\{log\}$ to discharge the corresponding invariance lemmas.

A typical property in class B is ExecAutoGrantWithoutIndividualPerms, shown in Figure 6. Its $\{log\}$ encoding is the following:

```
execAutoGrantWithoutIndividualPerms :-
state(S,St) & perms(St,Perms) &
validstate(SystemPerm,S) &
applyTo(Perms,A,PermsA) &
neg(exists(P_ in PermsA,[MG],MG = grp(G),maybeGrp(P_,MG))) &
pl(P,dangerous) &
maybeGrp(P,grp(G)) &
pre_grantAuto(SystemPerm,P,A,S).
```

As can be seen, the existential quantification of Figure 6 is implicit in $\{log\}$. Instead of quantifying over p' and permsA we first get PermsA as the image of A through Perms; if A is not in Perms's domain, applyTo(Perms, A, PermsA) fails. Then, we only need P_ to quantify over PermsA in the exists constraint. In Coq, Some g is part of an *option type* which in $\{log\}$ is encoded as grp(G), where grp is a functor and G an existential variable.

When execAutoGrantWithoutIndividualPerms is executed $\{log\}$ attempts to find values for the variables satisfying the formula. In this way $\{log\}$ generates a witness (solution) satisfying the query. The following is a simplified, pretty-printed form of that witness.

```
P = [V9,grp(G),dangerous],
SystemPerm = {P/Q9},
S = [St,Env],
St = [[apps,{A/Q1}],V1,[grantedPermGroups,{[A,{G/Q2}]/Q3}],
        [perms,{[A,PermsA]/Q4}],...],
Env = [[manifest,{[A,[V2,V2,V3,{P/Q5},V4,V5]]/Q6}],[cert,{[A,V6]/Q7}],
        [defPerms,{[A,V7]/Q8}],V8]
```

Variables V? and Q? are new (existential) variables. This witness is followed by a number of constraints restricting the values the variables at the righthand side can take. For example, one such constraint is $comp(\{[A,A]\},Q6,\{\})$ meaning that A is not in the domain of Q6, which is the 'rest' of manifest. This ensures that manifest is a partial function, as required by validstate. In order to come out with a more concrete witness every Q? variable can be replaced by the empty set. For instance, a more concrete value for manifest can be obtained by replacing Q5 and Q6 with {} thus getting {[A, [V2,V2,V3,{P},V4,V5]]}. {log} guarantees that the constraints following a witness are always satisfied by such a simple replacement because those constraints are of an special kind called *irreducible constraints* [18, 19, 21, 22, 23].

Finally, CannotAutoGrantWithoutGroup, shown in Figure 5, is a typical property of class C. The following is its $\{log\}$ encoding.

```
cannotAutoGrantWithoutGroup :-
neg(
   state(S,St) & grantedPermGroups(St,GR) &
   pl(P,dangerous) &
   maybeGrp(P,grp(G)) &
   applyTo(GR,A,GA) &
   G nin GA
   implies neg(grantAuto(SystemPerm,P,A,S,S_))
).
```

Clearly, the Coq theorem based on proving a universal property becomes a $\{log\}$ query attempting to satisfy the negation of that property. The only issue worth to be noted in this encoding is that exec s (grantAuto p a) s' ok is implemented by simply calling grantAuto. If the outcome of exec is ok it means that grantAuto could be executed which in $\{log\}$ corresponds to grantAuto being satisfiable.

In this case when cannotAutoGrantWithoutGroup is executed $\{log\}$ is unable to find values satisfying the formula so it returns false. If, for some reason, there would have been an error in grantAuto such that cannotAutoGrantWithoutGroup would not hold, then $\{log\}$ would return a counterexample when the query is executed. The counterexample would help to find the error.

As a summary, it is reasonable to say that the $\{log\}$ code is a straightforward, set-based encoding of the Coq model.

Remark 4 (An Automatically Verified Prototype). Once all queries representing properties are successfully run, the {log} program can be regarded as an automatically verified (or certified or correct) prototype of the Android permissions system w.r.t. the proven properties. As we will see in Section 4.3, {log} is able to automatically discharge in a reasonable time 24 out of 27 (\approx 90%) of the properties proposed in the Coq model.

4.3 Empirical Evaluation

In this section we provide detailed data on the empirical evaluation resulting after executing all the $\{log\}$ queries representing valid state and security properties, described above. The goal of the empirical evaluation is to measure

Project Size (specification $+$ proof)				
	LOC (K)		CHAR (K)	
	Model	Proofs	Model	Proofs
$\{log\}$	4.2	11	11	448
Coq	3.5	18	154	502
Performance of Automated Proof ({log})				
	Coq	$\{log\}$		Time (s)
		Lemmas	Queries	
Valid-state invariance lemmas	13	13	756	920
Security properties	14	11	45	381
Totals	27	24	801	1,302

18 A Verified Prototype of the Android Permissions System

the number of properties that $\{log\}$ is able to prove and the amount of time it spends on that. The $\{log\}$ code and instructions on how to reproduce this empirical evaluation can be found online⁴.

Table 1 summarizes the results of the empirical evaluation and provides some figures as to compare the $\{log\}$ and Coq developments. The upper part of the table gives some figures about the size of both projects. The Coq development encompasses the model described in Section 2.2 and a Coq functional implementation proved to refine the model. In this way we are comparing all the work needed to get an executable prototype in Coq as well as in $\{loq\}$. As can be seen, the $\{log\}$ code is larger than the Coq code in terms of LOC but the latter needs forty times more characters than the former (recall granPerm). $\{log\}\$ lines tend to be really shorter—many times only one constraint per line is written. Concerning proofs, Coq needs almost twice as many LOC than {log} although in terms of characters Coq uses not many more than $\{loq\}$. Here, however, it is important to observe that most of the proof text in $\{log\}$ can be automatically generated. In effect, 90% of the proof text in $\{log\}$ corresponds to the *statement* of the invariance lemmas that ensure that each operation preserves valid states, and not to the actual proofs. These statements can be automatically generated by conveniently annotating clauses representing operations and invariants and then calling a verification condition generator which generates lemmas such as 2. On the other hand, most of the proof text in Coq corresponds to the proof commands written by the user. However, these proofs use standard Coq strategies and tactics that do not apply automated methods such as those proposed by Chlipala [31] for engineering large scale formal developments. The use of such methods could reduce the number of lines and the number of tactics used in the proofs.

In turn, the lower part of the table provides figures about the performance of $\{log\}$ concerning automated proof. As we have said in Section 2.2, there

Table 1
 Summary of the empirical evaluation

 $^{{}^{4}} https://www.clpset.unipr.it/SETLOG/APPLICATIONS/android.zip$

are 13 valid-state invariance lemmas and 14 security properties defined and proved in Coq. {log} is able to automatically discharge all the invariance lemmas and 11 of the security properties. That is 24 out of 27 (\approx 90%) Coq proofs are automatic in {log}. In order to prove the 13 invariance lemmas we defined 756 {log} queries. Recall from Section 4.1 that some Coq predicates defining the notion of valid state are split in two or more {log} clauses (e.g. notDupPerm). {log} needs 920 s (\approx 15 m) in order to execute all these queries. Same considerations apply to security properties. That is, the 11 properties are encoded as 45 {log} queries which are discharged in 381 s (\approx 6 m). For example, some security properties of class A (Section 4.2) are expressed as several state invariants. In summary, {log} needs 1,302 s (\approx 22 m) to prove 24 properties expressed as 801 satisfiability queries.

The above figures were obtained on a Latitude E7470 (06DC) with a 4 core Intel(R) CoreTM i7-6600U CPU at 2.60GHz with 8 Gb of main memory, running Linux Ubuntu 18.04.6 (LTS) 64-bit with kernel 4.15.0-184-generic. $\{log\}$ 4.9.8-11h over SWI-Prolog (multi-threaded, 64 bits, version 7.6.4) was used during the experiments.

5 Discussion and Related Work

Besides the Coq model discussed in Section 2.2, De Luca and Luna [8] developed a Coq functional implementation. Then, they demonstrated, using Coq, that this implementation satisfies the model. Finally, thanks to the program extraction mechanism offered by Coq, they obtained a Haskell implementation of the Android permission system satisfying the model. This is the way a verified prototype is usually generated in Coq. Conversely, in $\{log\}$ it is enough to write the specification and then to prove properties to gain confidence on its correctness.

As the empirical evidence shows, combining the automated proof capabilities of $\{log\}$ with the proving power of Coq would be beneficial in terms of human effort and development time. $\{log\}$ is able to automatically discharge all but three of the proposed properties, thus saving a lot of time and human effort; these three properties are manually proved in Coq. Hence, the question is which is the better integration strategy to make $\{log\}$ and Coq to work together. Traditionally, automated theorem provers (ATP) have been integrated *into* interactive theorem provers (ITP) such as Coq. For example, CoqHammer [32] uses external ATPs to automate Coq proofs. Likewise, Isabelle/HOL uses Sledgehammer extended with SMT solvers [33]. In these cases, the current goal in the ITP is encoded in the input languages of the external solvers.

We instead propose to integrate $\{log\}$ with Coq in the other way around: encoding $\{log\}$ models as Coq specifications⁵. That is, we envision the following methodology:

 $^{{}^{5}}$ In this work the Coq model was encoded in $\{log\}$ simply because our collaboration started when the Coq model was already available.

- 1. Write a $\{log\}$ model.
- 2. Prove as many properties as possible using $\{log\}$.
- 3. If there are unproven properties, encode the $\{log\}$ model as a Coq specification.
- 4. Use Coq to prove the remaining properties.

In this way, the $\{log\}$ model becomes a correct-by-construction prototype. This implies that it would not be necessary to write a Coq abstract model, its implementation and perform the refinement proofs in order to get a certified executable prototype.

The justification for encoding $\{log\}$ models as Coq specifications can be sought in Figures 4 and 7. As we have shown, grantPerm is encoded in $\{loq\}$ as line 11 of Figure 7. Consider for a moment (automatically) translating grantPerm into $\{log\}$ in a way that line 11 is obtained. The task seems overwhelming. It might be tempting to consider more literal Coq-to-{log} translations where the $\{log\}$ code would look like much as grantPerm. The problem with this approach is that it will severely reduce the automated proving capabilities of $\{log\}$. Indeed, $\{log\}$ is able to discharge many proofs because predicates like grantPerm are encoded as simple {log} constraints. That is, {log} "knows" what to do with foplus but it will not necessarily know what to do if that is written in a different way. On the other hand, (automatically) encoding {log} constraints (e.g. foplus) in Coq is rather easy. Considering the definition of **foplus** in equation (1), it is easy to see that it can be encoded in terms of set equality and relational composition which are already defined in Coq. If duly unfolded, the resulting translation would look much as grantPerm. Evidently, Coq is more expressive than $\{log\}$ making the proposed translation easier than the opposite. Once the $\{loq\}$ model is encoded as a Coq specification, properties can be proved as usual.

We believe that one of the core constructs that allow $\{log\}$ to discharge many proof obligations are RUQ. Other tools (e.g SMT solvers) provide (unrestricted) universal quantification. Although universal quantification is important to gain expressiveness it is harder to deal with when performing automated proofs. Given that RUQ quantify over a set, a set solver can deal with them in a more controlled and decidable way [27, 24]. At the same time, RUQ provide just the necessary expressiveness when it comes to software specification.

Sooner or later, automated proof hits a computational complexity wall that makes progress extremely difficult. We use *hypothesis minimization* and *predicate delay* to move that wall as far away as possible. Hypothesis minimization consists in calling $\{log\}$ to prove a property just with the necessary hypothesis. That is, instead of calling $\{log\}$ to prove $p \land q \Rightarrow r$ we call it to prove $q \Rightarrow r$ if p does not contribute to the proof. Predicate delay instructs $\{log\}$ to delay the processing of a given predicate until nothing else can be done. This is achieved by means of $\{log\}$'s delay directive. Similar techniques are used, for instance, by SMT solvers. For example Dafny [34] provides the opaque attribute and

the **reveal** directive to selectively hide irrelevant predicates from Z3. Hawblitzel et al. [35, Section 6.3.2] use these constructs and add to Dafny more such constructs in order to tame the complexity of the correctness proofs of distributed systems.

In anyway, some times these techniques are not enough to make the solver to finish in a reasonable time. As we have pointed out, $\{log\}$ is unable to prove three properties that were proved in Coq by De Luca and Luna. These proofs require less than 500 LOC of Coq code meaning a reduced manual effort ($\approx 2\%$ of the total Coq proof effort). This is another piece of evidence suggesting that the proposed integration between $\{log\}$ and Coq could work in practice.

 $\{log\}\$ has been used in a similar fashion with other systems. It can discharge in 2 seconds all the 60 proof obligations proving the correctness of the Bell-LaPadula security model [36, 37] w.r.t. to the security condition and the *-property [27]. The Tokeneer ID Station (TIS) was proposed by the NSA as a benchmark for the production of secure software. NSA asked Altran UK to provide an implementation of TIS conforming to Common Criteria EAL5 [38]. Altran UK applied its own Correctness by Construction development process to the TIS software including a Z specification of the user requirements. Cristiá and Rossi [28] encoded that Z specification in $\{log\}$ as well as all the proof obligations set forth by the Altran UK team as 523 proof queries. $\{log\}$ is able to prove all the 523 queries in 14 minutes. Boniol and Wiels proposed a reallife, industrial-strength case study, known as the Landing Gear System (LGS) [39]. Mammar and Laleau [40] developed an Event-B specification of the LGS on the Rodin platform [41]. This specification was encoded in $\{loq\}$ along with all the proof obligations generated by Rodin [26]. The tool discharges all the 465 proof obligations in less than 5 minutes.

Few works study the permission system of Android by using a formal specification language. An example of this is the work of Shin et. al. [42], where they specified an abstract model of the Android permission system very similarly to the way that De Luca and Luna did in their last work. The main difference, though, is that the work by Shin is based on an older version of Android and was never updated. More examples of Coq being used to study Android at a formal level are the recent work carried out by El-Zawawy et. al. [43] or the CrashSafe tool [44]. These works are focused, thou, on studying Inter-Component Communication (ICC) properties rather than security properties of the permission system.

On the other hand, not everyone chooses Coq to formalize and analyze a model of Android. For instance, Bagheri et. al. [45] formalized and studied the Android permission system using Alloy [46]. As another example of a formal language being used to study Android, we can mention the Terminator tool [47] which uses the TLA+ model checker to analyze and identify permission induced threats. The main difference between these approaches and a Coq formalization, is that the latter provides stronger guarantees about the safety and security properties of the platform although requires more human effort to identify potential flaws. Our goal in this work is to bring together the

robustness of the properties that one can get from a Coq model combined with the automation that tools like Alloy or $\{log\}$ can provide. However, it should be observed that Alloy can only prove that formulas are satisfiable, whereas $\{log\}$ can prove both, satisfiability and unsatisfiability. There are more works using formal methods to study a specific aspect of Android which not necessarily conduct formal verification [48, 49, 50]. These approaches require a high amount of human effort, not only for identifying flaws but also to prove any desired property.

6 Conclusions

We present a $\{log\}$ model from one in Coq that constitutes an automatically verified executable prototype of the Android permissions system. In particular, we show in detail how the Coq model is encoded in the $\{log\}$ language and how automated proofs are performed. We conclude that $\{log\}$ can be used as an effective automated prover for systems such as the Android permissions system. In this way much of the manual, expert work needed to prove properties in Coq can be avoided.

Detailed data on the empirical evaluation resulting after executing all the proofs in $\{log\}$ is provided. The empirical evidence shows that the combination of the automated proof capabilities of $\{log\}$ with the proving power of Coq would be beneficial in terms of human effort and development time.

We have not seen other verification efforts combining Coq and $\{log\}$ to produce a certified prototype of a critical system.

Finally, we discuss possible ways to integrate Coq and $\{log\}$ as to provide a framework featuring automated proof and prototype generation. Advancing in this direction for the analysis of critical systems (in general) is part of our future work.

Declarations

- Funding: no funding.
- Conflict of interest: no conflicts of interest.

A More Details on {log}

In this appendix we provide more details on $\{log\}$ for those readers unfamiliar with it. Cristiá and Rossi [51] give a more thorough presentation of $\{log\}$ in a user-oriented stile.

A.1 The {log} language

The arguments passed in to the set and relational constraints supported by $\{log\}$ are terms called *set terms* or just *sets*. In turn, the elements of these sets can be, basically, any Prolog uninterpreted term, integers numbers, ordered

pairs (written [x, y]), other set terms, etc. In this way, in $\{log\}$ binary relations are just sets of ordered pairs. The following are the set terms available in $\{log\}$:

- Variables can be set terms.
- {} is the term interpreted as the empty set.
- $\{t/A\}$, where A is a set term and t is an element is called *extensional* set and is interpreted as $\{t\} \cup A$. Terms such as $\{t_1, t_2, \ldots, t_n/t\}$ and $\{t_1, t_2, \ldots, t_n\}$ are also accepted.
- $ris(X in A, \phi)$, where ϕ is any $\{log\}$ formula, A is a any of the above set terms, and X is a bound variable local to the **ris** term, is called *restricted* intensional set (RIS) and is interpreted as $\{x : x \in A \land \phi\}$. Actually, RIS have a more complex and expressive structure [21].
- cp(A, B), where A and B are any set term among the first three, is interpreted as $A \times B$, i.e., the Cartesian product between A and B.
- int(m, n), where m and n are either integer constants or variables, is interpreted as the integer interval [m, n].

With some exceptions any of the above terms can be passed as arguments to the set and relational constraints available in $\{log\}$.

Negation in $\{log\}$ has to be treated carefully. **neg** computes the proposi*tional* negation of its argument. In particular, if ϕ is an atomic constraint, $neg(\phi)$ returns the corresponding negated constraint. For example, neg(x inA & $z \min C$ becomes $x \min A$ or $z \lim C$. However, the result of neg is not always correct because, in general, the negated formula may involve existentially quantified variables, whose negation calls into play (general) universal quantification that $\{loq\}$ cannot handle properly. Hence, there are cases where $\{log\}$ users must manually compute the negation of some formulas. The same may happen for some logical connectives, such as **implies**, whose implementation uses the predicate neg: F implies G is implemented in $\{loq\}$ as neg(F) or G.

A.2 Types in $\{log\}$

 $\{log\}$'s type system is thoroughly described elsewhere [52, 53]. Typed as well as untyped formalisms have advantages and disadvantages [54]. For this reason, $\{log\}$ users can activate and deactivate the typechecker according to their needs.

{log} types are defined according to the following grammar:

$$\tau ::= \operatorname{int} | \operatorname{str} | \operatorname{Atom} | \operatorname{sum}([\operatorname{Constr}, \dots, \operatorname{Constr}]) | [\tau, \dots, \tau] | \operatorname{set}(\tau)$$

Constr ::= Atom | Atom(\tau)

where *Atom* is any Prolog atom other than int and str. int corresponds to the type of integer numbers; str corresponds to the type of Prolog strings; if $atom \in Atom$, then it defines the type given by the set $\{atom: t \mid$ t is a Prolog atom} (these are called *basic types*); $sum([c_1, \ldots, c_n])$, with $2 \leq c_1 \leq c_2 < c_2 \leq c_2 \leq c_2 \leq c_2 < c_2 \leq c_2 < c_2 \leq c_2 < c_2$

n, defines a sum type⁶; $[T_1, \ldots, T_n]$ with $2 \le n$ defines the Cartesian product of types T_1, \ldots, T_n ; and $\mathtt{set}(T)$ defines the powerset type of type T. Besides, $\{log\}$ defines: $\mathtt{rel}(\tau_1, \tau_2)$ as $\mathtt{set}([\tau_1, \tau_2])$ (i.e. the type of all binary relations); and $\mathtt{enum}([c_1, \ldots, c_n])$ as $\mathtt{sum}([c_1, \ldots, c_n])$ where all c_i are nullary terms (i.e. enumerated types). This type system is inspired in Z's.

When in typechecking mode, all variables and user-defined predicates must be declared to be of a precise type. Variables are declared by means of the $dec(V, \tau)$ predicate, meaning that variable V is of type τ . In this mode, every $\{log\}$ atomic constraint has a polymorphic type much as in the Z notation. For example, in comp(R, S, T) the type of the arguments must be $rel(\tau_1, \tau_2)$, $rel(\tau_2, \tau_3)$ and $rel(\tau_1, \tau_3)$, for some types τ_1, τ_2, τ_3 .

Concerning user-defined predicates, if the head of a predicate is $p(X_1, \ldots, X_n)$, then a declaration of the form $dec_p_type(p(\tau_1, \ldots, \tau_n))$, where τ_1, \ldots, τ_n are types, must precede p's definition. This is interpreted by the typechecker as X_i is of type τ_i in p, for all $i \in 1 \ldots n$.

This type system permits to encode the types used in the Coq model of the Android permissions system as shown in Section 3.

A.3 Constraint solving

As concerns constraint solving, $\{log\}$ is a rewriting system composed of a collection of specialized rewriting procedures. Each rewriting procedure applies a few non-deterministic rewrite rules to constraints of one kind. At the core of these procedures is set unification [55]. Rewriting finishes either when the resulting formula is **false** or when no constraint can be further rewritten. In the last case the resulting formula is returned as part of the computed answer. This formula is guaranteed to be satisfiable. Note that many of these formulas can be returned, due to the presence of non-deterministic rewrite rules. The disjunction of these formulas represents all the concrete (or ground) solutions of the input formula.

The collection of rewriting procedures implements various decision procedures for different theories on the domain of finite sets, finite set relation algebra and integer numbers. Specifically, $\{log\}$ implements: a decision procedure for the theory of *hereditarily finite sets* (\mathcal{HFS}), i.e., finitely nested sets that are finite at each level of nesting [18]; a decision procedure for a very expressive fragment of the theory of finite set relation algebras (\mathcal{BR}) [19, 20]; a decision procedure for \mathcal{HFS} extended with restricted intensional sets (\mathcal{RIS}) [21]; a decision procedure for \mathcal{HFS} extended with cardinality constraints (\mathcal{CARD}) [22]; a decision procedure for \mathcal{CARD} extended with integer intervals (\mathcal{INTV}) [23]; a decision procedure for \mathcal{RQ}) [24]; and integrates an existing decision procedure for the theory of linear integer arithmetic (\mathcal{LIA}) [56].

 $^{^{6}\}mathrm{Tagged}$ union, variant, variant record, choice type, discriminated union, disjoint union, or coproduct.

A.4 Restricted quantifiers

As we have said, {log} supports restricted quantifiers (RQ) called foreach and exists. RQ have been used across the {log} encoding of the Coq model of the Android permissions system and they have a rather complex structure. For these reasons here we present foreach with more detail—exists is used in the same way. foreach is a restricted universal quantifier (RUQ). The most general form of foreach is the following:

$$\texttt{foreach}(x \texttt{ in } A, [e_1, \dots, e_n], \phi(x, e_1, \dots, e_n), \psi(x, e_1, \dots, e_n)) \tag{3}$$

where x can be a variable or an ordered pair of two distinct variables; e_1, \ldots, e_n are variables implicitly existentially quantified inside the **foreach**; ϕ is a $\{log\}$ formula; and ψ is a conjunction of so-called *functional predicates*. A predicate p of artity n + 1 (0 < n) is a functional predicate iff for each x_1, \ldots, x_n there exists exactly one y such that $p(x_1, \ldots, x_n, y)$ holds; y is called the *result* of p. For instance, un, dom and comp are functional predicates. In a **foreach**, e_1, \ldots, e_n must be the results of the functional predicates in ψ . The second and last parameters are optional. The semantics of (3) is:

$$\forall x(x \in A \Rightarrow (\exists e_1, \dots, e_n(\psi(x, e_1, \dots, e_n) \land \phi(x, e_1, \dots, e_n))))$$

The structure of the **foreach** predicate was designed to avoid the introduction of as many 'uncontrolled' existential variables as possible. The introduction of existential variables brings in the problem of negating the predicate in such a way that the result is a formula laying inside the decidable fragment. This structure proved to be expressive enough as to work with real-world problems [27, 26, 24].

Nested foreach can be written as follows:

 $foreach([x in A, y in B], \phi) \cong foreach(x in A, foreach(y in B, \phi))$

References

- [1] Open Handset Alliance: Android project. Available at: //source.android.com/. Last access: Jun. 2022
- [2] International Data Corporation: Smartphone market share. Technical report, International Data Corporation (IDC) (2022)
- [3] The Coq Team: The Coq Proof Assistant Reference Manual Version V8.12.0. LogiCal Project, Palaiseau, France (2020). LogiCal Project. http://coq.inria.fr
- [4] Bertot, Y., Castéran, P.: Interactive Theorem Proving and Program Development - Coq'Art: The Calculus of Inductive Constructions. Texts in Theoretical Computer Science. An EATCS Series. Springer, ??? (2004). https://doi.org/10.1007/978-3-662-07964-5. https://doi.org/10.1007/978-3-662-07964-5

26 REFERENCES

- [5] Betarte, G., Campo, J.D., Luna, C.D., Romano, A.: Verifying Android's permission model. In: Leucker, M., Rueda, C., Valencia, F.D. (eds.) Theoretical Aspects of Computing - ICTAC 2015 - 12th International Colloquium Cali, Colombia, October 29-31, 2015, Proceedings. Lecture Notes in Computer Science, vol. 9399, pp. 485– 504. Springer, ??? (2015). https://doi.org/10.1007/978-3-319-25150-9_28. https://doi.org/10.1007/978-3-319-25150-9_28
- [6] Betarte, G., Campo, J.D., Luna, C., Romano, A.: Formal analysis of Android's permission-based security model, Sci. Ann. Comp. Sci. 26(1), 27–68 (2016). https://doi.org/10.7561/SACS.2016.1.27
- [7] Betarte, G., Campo, J.D., Gorostiaga, F., Luna, C.: A certified reference validation mechanism for the permission model of Android. In: Fioravanti, F., Gallagher, J.P. (eds.) Logic-Based Program Synthesis and Transformation - 27th International Symposium, LOP-STR 2017, Namur, Belgium, October 10-12, 2017, Revised Selected Papers. Lecture Notes in Computer Science, vol. 10855, pp. 271–288. Springer, ??? (2017). https://doi.org/10.1007/978-3-319-94460-9_16. https://doi.org/10.1007/978-3-319-94460-9_16
- [8] De Luca, G., Luna, C.: Towards a certified reference monitor of the Android 10 permission system. In: de'Liguoro, U., Berardi, S., Altenkirch, T. (eds.) 26th International Conference on Types for Proofs and Programs, TYPES 2020, March 2-5, 2020, University of Turin, Italy. LIPIcs, vol. 188, pp. 3–1318. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, ??? (2020). https://doi.org/10.4230/LIPIcs.TYPES.2020.3. https://doi.org/10.4230/LIPIcs.TYPES.2020.3
- [9] Rossi, G.: $\{log\}$. Last access 2022
- [10] Letouzey, P.: Programmation fonctionnelle certifiée l'extraction de programmes dans l'assistant Coq. PhD thesis, Université Paris-Sud (July 2004)
- C.: [11] Luca, G.D., Luna, Formal verification of the securitv model of Android 10:Coq code. Available at: https://github.com/g-deluca/android-coq-model. Last access: Jun. 2022
- [12] Android Developers: Application Fundamentals. Available at: http://developer.android.com/guide/components/fundamentals.html. Last access: Jun. 2022
- [13] Sbirlea, D., Burke, M.G., Guarnieri, S., Pistoia, M., Sarkar, V.: Automatic detection of inter-application permission leaks in Android applications 57(6). https://doi.org/10.1147/JRD.2013.2284403
- [14] Chin, E., Felt, A.P., Greenwood, K., Wagner, D.A.: Analyzing interapplication communication in android. In: Agrawala, A.K., Corner, M.D., Wetherall, D. (eds.) Proceedings of the 9th International Conference on Mobile Systems, Applications, and Services (MobiSys 2011), Bethesda, MD, USA, June 28 - July 01, 2011, pp. 239–252. ACM, ??? (2011). https://doi.org/10.1145/1999995.2000018. https://doi.org/10.1145/1999995.2000018

- [15] Cantone, D., Ferro, A., Omodeo, E.: Computable Set Theory. Clarendon Press, USA (1989)
- [16] Cantone, D., Omodeo, E.G., Policriti, A.: Set Theory for Decision Procedures Computing From toDeclarative Programming with Sets. Monographs inComputer Science. ??? (2001).https://doi.org/10.1007/978-1-4757-3452-2. Springer, http://dx.doi.org/10.1007/978-1-4757-3452-2
- [17] Schwartz, J.T., Dewar, R.B.K., Dubinsky, Е., Schonberg. E.: Programming with Sets An Introduction SETL. _ to Texts and Monographs inComputer Science. Springer, ??? https://doi.org/10.1007/978-1-4613-9575-1. (1986).http://dx.doi.org/10.1007/978-1-4613-9575-1
- [18] Dovier, A., Piazza, C., Pontelli, E., Rossi, G.: Sets and constraint logic programming. ACM Trans. Program. Lang. Syst. 22(5), 861–931 (2000)
- [19] Cristiá, M., Rossi, G.: Solving quantifier-free first-order constraints over finite sets and binary relations. J. Autom. Reason. 64(2), 295–330 (2020). https://doi.org/10.1007/s10817-019-09520-4
- [20] Cristiá, M., Rossi, G.: A set solver for finite set relation algebra. In: Desharnais, J., Guttmann, W., Joosten, S. (eds.) Relational and Algebraic Methods in Computer Science - 17th International Conference, RAMiCS 2018, Groningen, The Netherlands, October 29 - November 1, 2018, Proceedings. Lecture Notes in Computer Science, vol. 11194, pp. 333– 349. Springer, ??? (2018). https://doi.org/10.1007/978-3-030-02149-8_20. https://doi.org/10.1007/978-3-030-02149-8_20
- [21] Cristiá, М.. G.: Rossi. Automated reasoning with restricted intensional sets. J. Autom. Reason. **65**(6), 809-890 (2021).https://doi.org/10.1007/s10817-021-09589-w
- [22] Cristiá, M., Rossi, G.: Integrating cardinality constraints into constraint logic programming with sets. Theory and Practice of Logic Programming, 1–33 (2021)
- [23] Cristiá, M., Rossi, G.: A decision procedure for a theory of finite sets with finite integer intervals. CoRR abs/2105.03005 (2021) arXiv:2105.03005. Under consideration in Theoretical Computer Science
- Rossi, G.: A set-theoretic decision procedure for [24] Cristiá, М., quantifier-free, decidable languages extended with restricted quantifiers. CoRR abs/2208.03518 (2022)2208.03518. https://doi.org/10.48550/arXiv.2208.03518
- [25] Cristiá, M., Rossi, G., Frydman, C.S.: {log} as a test case generator for the Test Template Framework. In: Hierons, R.M., Merayo, M.G., Bravetti, M. (eds.) SEFM. Lecture Notes in Computer Science, vol. 8137, pp. 229–243. Springer, ??? (2013)
- [26] Cristiá, M., Rossi, G.: An automatically verified prototype of a landing gear system. CoRR abs/2112.15147 (2021) 2112.15147
- [27] Cristiá, M., Rossi, G.: Automated proof of Bell-LaPadula security properties. J. Autom. Reason. 65(4), 463–478 (2021).

28 REFERENCES

https://doi.org/10.1007/s10817-020-09577-6

- [28] Cristiá, M., Rossi, G.: An automatically verified prototype of the Tokeneer ID station specification. J. Autom. Reason. 65(8), 1125–1151 (2021). https://doi.org/10.1007/s10817-021-09602-2
- [29] Abrial, J.-R.: The B-book: Assigning Programs to Meanings. Cambridge University Press, New York, NY, USA (1996)
- [30] Spivey, J.M.: The Z Notation: a Reference Manual. Prentice Hall International (UK) Ltd., Hertfordshire, UK, UK (1992)
- [31] Chlipala, A.: Certified Programming with Dependent Types A Pragmatic Introduction to the Coq Proof Assistant. MIT Press. http://mitpress.mit.edu/books/certified-programming-dependent-types
- [32] Czajka, L., Kaliszyk, C.: Hammer for Coq: Automation for dependent type theory. J. Autom. Reasoning 61(1-4), 423–453 (2018). https://doi.org/10.1007/s10817-018-9458-4
- [33] Blanchette, J.C., Böhme, S., Paulson, L.C.: Extending sledgehammer with SMT solvers. J. Autom. Reason. 51(1), 109–128 (2013). https://doi.org/10.1007/s10817-013-9278-5
- [34] Leino, K.R.M.: Dafny: An automatic program verifier for functional correctness. In: Clarke, E.M., Voronkov, A. (eds.) Logic for Programming, Artificial Intelligence, and Reasoning - 16th International Conference, LPAR-16, Dakar, Senegal, April 25-May 1, 2010, Revised Selected Papers. Lecture Notes in Computer Science, vol. 6355, pp. 348– 370. Springer, ??? (2010). https://doi.org/10.1007/978-3-642-17511-4_20. https://doi.org/10.1007/978-3-642-17511-4_20
- [35] Hawblitzel, C., Howell, J., Kapritsos, M., Lorch, J.R., Parno, B., Roberts, M.L., Setty, S.T.V., Zill, B.: Ironfleet: proving practical distributed systems correct. In: Miller, E.L., Hand, S. (eds.) Proceedings of the 25th Symposium on Operating Systems Principles, SOSP 2015, Monterey, CA, USA, October 4-7, 2015, pp. 1–17. ACM, ??? (2015). https://doi.org/10.1145/2815400.2815428. https://doi.org/10.1145/2815400.2815428
- [36] Bell, D.E., LaPadula, L.: Secure computer systems: Mathematical foundations. MTR 2547, The MITRE Corporation (May 1973)
- [37] Bell, D.E., LaPadula, L.: Secure computer systems: Mathematical model. ESD-TR 73-278, The MITRE Corporation (November 1973)
- [38] Common Criteria Recognition Arrangement: Common criteria for information technology security evaluation, part 1: Introduction and general model, version 3.1. release 5. Technical report (2017). https://www.commoncriteriaportal.org/files/ccfiles/CCPART1V3.1R5.pdf
- [39] Boniol, F., Wiels, V.: The landing gear system case study. In: Boniol, F., Wiels, V., Ameur, Y.A., Schewe, K. (eds.) ABZ 2014: The Landing Gear Case Study - Case Study Track, Held at the 4th International Conference on Abstract State Machines, Alloy, B, TLA,

VDM, and Z, Toulouse, France, June 2-6, 2014. Proceedings. Communications in Computer and Information Science, vol. 433, pp. 1– 18. Springer, ??? (2014). https://doi.org/10.1007/978-3-319-07512-9_1. https://doi.org/10.1007/978-3-319-07512-9_1

- [40] Mammar, A., Laleau, R.: Modeling a landing gear system in Event-B. Int. J. Softw. Tools Technol. Transf. 19(2), 167–186 (2017). https://doi.org/10.1007/s10009-015-0391-0
- [41] Coleman, J., Jones, C., Oliver, I., Romanovsky, A., E.Troubitsyna: RODIN (Rigorous open Development Environment for Complex Systems). In: Fifth European Dependable Computing Conference: EDCC-5 Supplementary Volume, pp. 23–26 (2005)
- [42] Shin, W., Kiyomoto, S., Fukushima, K., Tanaka, T.: A formal model to analyze the permission authorization and enforcement in the Android framework. In: Elmagarmid, A.K., Agrawal, D. (eds.) Proceedings of the 2010 IEEE Second International Conference on Social Computing, SocialCom / IEEE International Conference on Privacy, Security, Risk and Trust, PASSAT 2010, Minneapolis, Minnesota, USA, August 20-22, 2010, pp. 944–951. IEEE Computer Society, ??? (2010). https://doi.org/10.1109/SocialCom.2010.140. https://doi.org/10.1109/SocialCom.2010.140
- [43] El-Zawawy, M.A., Faruki, P., Conti, M.: Formal model for intercomponent communication and its security in android. Computing 104(8), 1839–1865 (2022). https://doi.org/10.1007/s00607-022-01069-2
- [44] Khan, W., Ullah, H., Ahmad, A., Sultan, K., Alzahrani, A.J., Khan, S.D., Alhumaid, M., Abdulaziz, S.: Crashsafe: a formal model for proving crashsafety of android applications. Hum. centric Comput. Inf. Sci. 8, 21 (2018). https://doi.org/10.1186/s13673-018-0144-7
- Н., Е., S., [45] Bagheri, Kang, Malek, Jackson, D.: Α formal approach for detection of security flaws in the android permission system. Formal Aspects Comput. 30(5),525 - 544(2018).https://doi.org/10.1007/s00165-017-0445-z
- [46] Jackson, D.: Alloy: A logical modelling language. In: Bert, D., Bowen, J.P., King, S., Waldén, M.A. (eds.) ZB 2003: Formal Specification and Development in Z and B, Third International Conference of B and Z Users, Turku, Finland, June 4-6, 2003, Proceedings. Lecture Notes in Computer Science, vol. 2651, p. 1. Springer, ??? (2003). https://doi.org/10.1007/3-540-44880-2_1. http://dx.doi.org/10.1007/3-540-44880-2_1
- [47] Sadeghi, A., Jabbarvand, R., Ghorbani, N., Bagheri, H., Malek, S.: A temporal permission analysis and enforcement framework for android. In: Chaudron, M., Crnkovic, I., Chechik, M., Harman, M. (eds.) Proceedings of the 40th International Conference on Software Engineering, ICSE 2018, Gothenburg, Sweden, May 27 June 03, 2018, pp. 846–857. ACM, ??? (2018). https://doi.org/10.1145/3180155.3180172. https://doi.org/10.1145/3180155.3180172

30 REFERENCES

- [48] Micinski, K.K., Fetter-Degges, J., Jeon, J., Foster, J.S., Clarkson, M.R.: Checking interaction-based declassification policies for android using symbolic execution. In: Pernul, G., Ryan, P.Y.A., Weippl, E.R. (eds.) Computer Security - ESORICS 2015 - 20th European Symposium on Research in Computer Security, Vienna, Austria, September 21-25, 2015, Proceedings, Part II. Lecture Notes in Computer Science, vol. 9327, pp. 520– 538. Springer, ??? (2015). https://doi.org/10.1007/978-3-319-24177-7_26. https://doi.org/10.1007/978-3-319-24177-7_26
- [49] Fragkaki, E., Bauer, L., Jia, L., Swasey, D.: Modeling and enhancing android's permission system. In: Foresti, S., Yung, M., Martinelli, F. (eds.) Computer Security ESORICS 2012 17th European Symposium on Research in Computer Security, Pisa, Italy, September 10-12, 2012. Proceedings. Lecture Notes in Computer Science, vol. 7459, pp. 1–18. Springer, ??? (2012). https://doi.org/10.1007/978-3-642-33167-1_1. https://doi.org/10.1007/978-3-642-33167-1_1
- [50] Talegaon, S., Krishnan, R.: A formal specification of access control in android with URI permissions. Inf. Syst. Frontiers 23(4), 849–866 (2021). https://doi.org/10.1007/s10796-020-10066-9
- [51] Cristiá, M., Rossi, G.: {log}: set formulas as programs. Rend. Ist. Mat. Univ. Trieste 53, 24 (2021). https://doi.org/10.13137/2464-8728/33309. Id/No 23
- [52] Cristiá, M., Rossi, G.: A typechecker for a set-based constraint logic programming language. CoRR abs/2205.01713 (2022) 2205.01713. https://doi.org/10.48550/arXiv.2205.01713
- [53] Rossi, G., Cristiá, M.: {log} user's manual. Technical report, Dipartimento di Matematica, Universitá di Parma (2020). http://people.dmi.unipr.it/gianfranco.rossi/SETLOG/manual_4_9_ 8.pdf. http://people.dmi.unipr.it/gianfranco.rossi/SETLOG/manual_4_ 9_8.pdf
- [54] Lamport, L., Paulson, L.C.: Should your specification language be typed? ACM Trans. Program. Lang. Syst. 21(3), 502–526 (1999). https://doi.org/10.1145/319301.319317
- [55] Dovier, A., Pontelli, E., Rossi, G.: Set unification. Theory Pract. Log. Program. 6(6), 645–701 (2006). https://doi.org/10.1017/S1471068406002730
- [56] Holzbaur, C.: OFAI CLP(Q,R) manual. Technical report, edition 1.3.3. Technical Report TR-95-09, Austrian Research Institute for Artificial Intelligence (1995). http://www.ofai.at/cgi-bin/tr-online?number+95-09