# **Better Transcription of UK Supreme Court Hearings**

# Hadeel Saadany\*

Centre for Translation Studies University of Surrey United Kingdom

## Constantin Orăsan

Centre for Translation Studies University of Surrey United Kingdom

#### **Abstract**

Transcription of legal proceedings is very important to enable access to justice. However, speech transcription is an expensive and slow process. In this paper we describe part of a combined research and industrial project for building an automated transcription tool designed specifically for the Justice sector in the UK. We explain the challenges involved in transcribing court room hearings and the Natural Language Processing (NLP) techniques we employ to tackle these challenges. We will show that fine-tuning a generic off-theshelf pre-trained Automatic Speech Recognition (ASR) system with an in-domain language model as well as infusing common phrases extracted with a collocation detection model can improve not only the Word Error Rate (WER) of the transcribed hearings but avoid critical errors that are specific of the legal jargon and terminology commonly used in British courts.

# 1 Introduction

There has been a recent interest in employing NLP techniques to aid in the textual processing of the legal domain (Elwany et al., 2019; Nay, 2021; Mumcuoğlu et al., 2021; Frankenreiter and Nyarko, 2022). In contrast, understanding spoken court hearings has not received the same attention as understanding the legal text documents. In the UK legal system, the court hearings sessions have a unique tradition of verbal argument. Moreover, these hearings crucially aid in new case preparation, provide guidance for court appeals, help in legal training and even guide future policy. However, the audio material for a case typically spans over several hours, which makes it both time and effort consuming for legal professionals to extract

Email: hadeel.saadany@surrey.ac.uk

# **Catherine Breslin**

Kingfisher Labs Ltd United Kingdom

# Sophie Walker

Just Access United Kingdom

Model	Transcript
Reference	So my lady um it is difficult to
AWS ASR	So <b>melody</b> um it is difficult to
Reference	it makes further financial order
AWS ASR	it makes further five natural

Table 1: Examples of Errors Produced by AWS ASR on Legal Hearings. Errors are typed in bold.

important information relevant to their needs. Currently, the existing need for legal transcriptions (covering 449K cases p.a in the UK across all court tribunals (Sturge, 2021) is largely met by human transcribers.

Although there are several current speech-to-text (STT) technology providers which could be used to transcribed this data automatically, most of these systems are trained on general domain data which may result in domain-specific transcription errors if applied to a specialised domain. One way to address this problem is for end-users to train their own ASR engines using their in-domain data. However, in most of the cases the amount of data available is too low to enable them to train a system which can compete with well-knows cloud-based ASR systems which are trained on much larger datasets. In commercial scenarios, using generic cloud-based ASR systems to transcribe a specialised domain may result in a sub-optimal quality transcriptions for clients who require this service.

This holds particularly true for British court room audio procedures. When applying a generic cloud-based ASR system on British court rooms, the Word Error Rate (WER) remains relatively high due to long hearings, multiple speakers, complex speech patterns as well as unique pronunciation and vocabulary. Examples in Table 1 show common problems with transcribing speech from the legal domain using an on-the-shelf ASR systems such as

AWS Transcribe<sup>1</sup>. The references are taken from gold-standard edited transcripts of the UK Supreme Court Hearings<sup>2</sup> created by the legal editors in our project. The first error is due to a special pronunciation of the phrase 'my lady' in British court rooms as it is pronounced like 'mee-lady' when barristers address a female judge. In the second example, the error is related to legal terminology critical of the specific transcribed case. Errors like in the second example are numerous in our dataset and affect also names and numbers. These errors can lead to serious information loss and cause confusion.

In this paper, we describe a joint research and commercial effort to perform domain adaptation of a generic ASR system to mitigate the errors in the automated UK court transcription services. We propose to minimise legal-specific errors by finetuning off-the-shelf ASR systems with a custom language model (CLM) trained on legal documents as well as 139 hours of gold-standard transcriptions of UK Supreme Court hearings. We also employ NLP techniques to automatically build a custom vocabulary of common multi-word expressions and word n-gram collocations that are critical in court hearings. We infuse our custom vocabulary to the CLM at transcription time. In this research, we evaluate the benefits of our proposed domain adaptation methods by comparing the WER of the CLM output with two off-the-shelf ASR systems: Amazon Web Services (AWS) Transcribe (commercial) and the OpenAI Whisper model (open-source) (Radford et al., 2022). We also compare the general improvement in the ASR system's ability to correctly transcribe legal entities with and without adopting our proposed methods.

### 2 Related Work

Automatic speech recognition (ASR) models convert audio input to text and they have optimal performance when used to transcribe data which is similar to the one they were trained on. However, performance degrades when there is a mismatch between the data used for training and the one that is being transcribed. Additionally, some types of audio material is intrinsically harder for speech recognition systems to transcribe. In practice, this means that speech recognition system performance degrades when, for example, there is background

noise (Watanabe et al., 2020), non-native accents (Feng et al., 2021; Zhang, 2022), young or elderly speakers (Feng et al., 2021), or a shift in domain (Mai and Carson-Berndsen, 2022).

Performance degradation is typically mitigated by adapting or fine-tuning ASR models towards the domain of the targeted data by using a domainspecific dataset (Huo et al., 2021; Sato et al., 2022; Dingliwa et al., 2022). Some methods for domain adaptation adopt NLP techniques such as using machine translation models to learn a mapping from out-of-domain ASR errors to in-domain terms (Mani et al., 2020). An alternative approach is to build a large ASR model with a substantially varied training set, so that the model is more robust to data shifts. An example of this latter approach is the recently released OpenAI Whisper model which is trained on 680k hours of diverse domain data to generalise well on a range of unseen datasets without the need for explicit adaptation (Radford et al., 2022).

Moreover, ASR models are evaluated using Word Error Rate (WER), which treats each incorrect word equally. However, ASR models do not perform equally on different categories of words. Performance is worse for categories like names of people and organisations as compared to categories like numbers or dates (Del Rio et al., 2021). ASR research targeted improving specific errors such as different named entities using NLP techniques (Wang et al., 2020; Das et al., 2022).

In this paper, we propose simple techniques to improve the effect of the domain mismatch between a generic ASR model and the specialised domain of British court room hearings. Our proposed method, improves both the system's WER rate as well as its ability to capture case-specific terms and entities. In the next section, we present our experiment set up and the evaluation results.

#### 3 Experiment Set up

Figure 1 illustrates our proposed pipeline to improve ASR systems performance by legal domain-adaptation techniques. First, we build a custom language model (CLM) by fine-tuning a base ASR system, such as AWS Transcribe base system, using training data from the domain and a corpus of gold-standard legal transcriptions. Then, we use NLP techniques to extract domain-specific phrases and legal entities from the in-domain data to create a vocabulary list. We use both the CLM and the

<sup>1</sup>https://aws.amazon.com/transcribe/

<sup>2</sup>https://www.supremecourt.uk/
decided-cases/index.html




Figure 1: Pipeline for Improving ASR Output for Legal Specific Errors

vocabulary list for transcribing legal proceedings. The following sections explain details of our experiment where we implemented this pipeline on the AWS Transcribe base model. We compare the performance of our CLM model with different settings to AWS Transcribe base ASR system and OpenAI Whisper open-source ASR system when transcribing  $\approx 12 \ hours$  of UK Supreme Court Hearings.

#### 3.1 Dataset

For training our CLM, we use two datasets from the legal domain. The first is Supreme Court written judgements of 43 cases consisting of 3.26M tokens scraped from the official site of the UK Supreme Court<sup>3</sup>. The second dataset consists of  $\approx$  81 hours of gold-standard transcripts of 10 Supreme Court hearings. The gold-standard transcripts are created by post-editing the AWS Transcribe output of the court hearings by a team of legal professionals using a specially designed interface. We use both datasets to train CLM on the AWS platform.

For the vocabulary list, we use a dataset of  $\approx 139$ hours of gold-standard transcriptions of Supreme Court hearings along with the supreme court judgements used for training the CLM. To extract the vocabulary from this dataset, we implement two methods. First, we use this dataset to train a phrase detection model that collocates bigrams based on Pointwise Mutual Information (PMI) scoring of the words in context (Mikolov et al., 2013)<sup>4</sup>. Then, the collocation model is used to extract a list of most common bigrams in the dataset. This list includes frequent legal terms and phrases specific of the Supreme Court cases included in the training corpus. Second, we use Blackstone<sup>5</sup>, an NLP library for processing long-form and unstructured legal text, to extract a list of legal entities from the

dataset. The list of legal entities included: Case Name, Court Name, Provision (i.e. a clause in a legal instrument), Instrument (i.e. a legal term of art) and Judge. We concatenated this Blackstone entity list with the spaCy v3.4 library list of non-legal entities such as: Cardinals, Persons and Dates. The results of applying our methods for the transcription of 2 Supreme Court case hearings consisting of 12 hours is explained in the next section.

### 4 Results

Table 2 shows the WER scores and WER average score for the 2 transcribed cases with different CLM system settings, as well as, for the two baseline systems: the AWS Transcribe (AWS base) and Whisper. The different CLM settings are as follows: CLM1 is trained on only the texts of the Supreme Court judgements, CLM2 is trained on both the judgements and the gold-standard transcripts, CLM2+Vocab uses CLM2 for transcription plus the global vocabulary list extracted by our phrase detection model, and CLM2+Vocab2 uses CLM2 for transcription plus the legal entities vocabulary list extracted by Blackstone library.

As can be seen in Table 2, the ASR performance is consistently better with the CLM models than with the generic ASR systems for the two transcribed cases. CLM2 model, trained on textual data (i.e. the written judgements) and goldstandard court hearing transcriptions, outperforms AWS base and Whisper with a 9% and 8% WER improvement, respectively. Moreover, we observe around 9% improvement in average WER score over the two generic models when concatenating the list of legal phrases that is extracted by our phrase detection model with the CLM2 system. While ASR error correction indicates an improved transcription quality with our proposed domain adaptation methods, we also evaluated the ASR systems performance with specific errors such as

<sup>3</sup>https://www.supremecourt.uk/decided-cases/

<sup>&</sup>lt;sup>4</sup>We train the model using the Gensim Python library (Řehůřek and Sojka, 2010)

<sup>&</sup>lt;sup>5</sup>https://research.iclr.co.uk/blackstone

Model	WER	WER	WER	Transcription Time	
	Case1	Case2	Average		
AWS base	8.7	16.2	12.3	85 mins	
CLM1	8.5	16.5	12.4	77 mins	
CLM2	7.9	15.5	11.6	77 mins	
CLM2+Vocab	7.9	15.6	11.6	132 mins	
CLM2+Vocab2	8.0	15.6	11.7	112 mins	
Whisper	9.6	15.3	12.4	191 mins	

Table 2: Average WER and Transcription Time

Entity	AWS BASE	Whisper	CLM2+vocab
Judge	0.66	0.77	0.84
CASE NAME	0.69	0.85	0.71
Court	0.98	1	0.93
Provision	0.88	0.95	0.97
Cardinal	1	0.97	1

Table 3: Ratio of Correctly Captured Legal Entities by the ASR Systems

legal entities and terms.

Table 3 shows the average ratio of correctly transcribed legal entities in the two studied court room hearings. We compare the performance of CLM2 infused with the legal terms list (CLM2+Vocab) to the two generic ASR systems. The ratios in Table 3 indicate that CLM2+Vocab is generally more capable of transcribing legal-specific terms than the other two models. It is also better at transcribing critical legal entities such as Provisions.<sup>6</sup> Such legal terminology needs to be accurately transcribed. Our CLM2 model with legal vocabulary demonstrates better reliability in transcribing these terms.

A similar trend is evident with the legal entity Judge which refers to the forms of address used in British court rooms (e.g. 'Lord Phillips', 'Lady Hale'). This entity is typically repeated in court hearings whenever a barrister or solicitor addresses the court. We see that both the generic ASR systems perform badly on this category with ratios of 0.66 and 0.69, respectively. On the other hand, we observe a significant improvement in correctly transcribing this entity by the CLM2+Vocab with a ration of 0.84 correct transcriptions.

In addition to evaluating the output of the ASR engines, we also recorded the time required to produce the transcription. The models based on AWS were run in the cloud using the Amazon infrastructure. Whisper was run on a Linux desktop with an

NVIDIA GeForce RTX 2070 GPU with 8G VRAM. For all the experiments, the medium English-only model was used. As expected the fastest running time is obtained using the AWS base model. Running the best performing model increases the time by 155%, whilst Whisper more than doubles it.

### 5 Conclusion

In this paper, we present a study to show the effect of domain adaption methods on improving the offthe-shelf ASR system performance in transcribing a specialised domain such as British court hearings. We optimised the performance of the ASR system by training an ASR custom language model on gold-standard legal transcripts and textual data from the legal domain. We also trained a phrase detection model to incorporate extracted list of dataspecific bigram collocations at transcription time. We evaluated the ASR quality improvements both in terms of average WER and ratio of correctly transcribed legal-specific terms. We observe significant gains in the ASR transcription quality by our domain adaptation techniques. For commercial use of ASR technologies, improving error rate in general and transcription quality of critical legal terms in particular would minimise manual post-editing effort and hence save both time and money. We plan to evaluate the impact of different configurations proposed in this paper on the editors' postediting effort.

In the future, we will expand to record data from

<sup>&</sup>lt;sup>6</sup>A Provision, a statement within an agreement or a law, typically consists of alphanumeric utterances in British court hearings (e.g. 'section 25(2)(a)-(h)' or 'rule 3.17').

a variety of accents to address another axis of degradation in British audio procedures different than the Supreme Court hearings which are mostly a homogeneous group of speakers. We will also explore the ability to use NLP topic modelling techniques to connect legal entities that were crucial in a court's case decision.

# References

- Nilaksh Das, Duen Horng Chau, Monica Sunkara, Sravan Bodapati, Dhanush Bekal, and Katrin Kirchhoff. 2022. Listen, Know and Spell: Knowledge-Infused Subword Modeling for Improving ASR Performance of OOV Named Entities. In *ICASSP* 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 7887–7891. IEEE.
- Miguel Del Rio, Natalie Delworth, Ryan Westerman, Michelle Huang, Nishchal Bhandari, Joseph Palakapilly, Quinten McNamara, Joshua Dong, Piotr Zelasko, and Miguel Jetté. 2021. Earnings-21: a practical benchmark for asr in the wild. *arXiv* preprint arXiv:2104.11348.
- Saket Dingliwa, Ashish Shenoy, Sravan Bodapati, Ankur Gandhe, Ravi Teja Gadde, and Katrin Kirchhoff. 2022. Domain prompts: Towards memory and compute efficient domain adaptation of ASR systems. In *Interspeech 2022*.
- Emad Elwany, Dave Moore, and Gaurav Oberoi. 2019. Bert goes to law school: Quantifying the competitive advantage of access to large legal corpora in contract understanding. *arXiv preprint arXiv:1911.00473*.
- Siyuan Feng, Olya Kudina, Bence Mark Halpern, and Odette Scharenborg. 2021. Quantifying bias in automatic speech recognition. *arXiv preprint arXiv:2103.15122*.
- Jens Frankenreiter and Julian Nyarko. 2022. Natural language processing in legal tech. *Legal Tech and the Future of Civil Justice (David Engstrom ed.)*.
- Zhouyuan Huo, Dongseong Hwang, Khe Chai Sim, Shefali Garg, Ananya Misra, Nikhil Siddhartha, Trevor Strohman, and Françoise Beaufays. 2021. Incremental layer-wise self-supervised learning for efficient speech domain adaptation on device. *arXiv* preprint arXiv:2110.00155.
- Long Mai and Julie Carson-Berndsen. 2022. Unsupervised domain adaptation for speech recognition with unsupervised error correction. *Proc. Interspeech* 2022, pages 5120–5124.
- Anirudh Mani, Shruti Palaskar, Nimshi Venkat Meripo, Sandeep Konam, and Florian Metze. 2020. Asr error correction and domain adaptation using machine translation. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6344–6348. IEEE.

- Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. 2013. Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems*, 26.
- Emre Mumcuoğlu, Ceyhun E Öztürk, Haldun M Ozaktas, and Aykut Koç. 2021. Natural language processing in law: Prediction of outcomes in the higher courts of turkey. *Information Processing & Management*, 58(5):102684.
- John J. Nay. 2021. *Natural Language Processing* for Legal Texts, DOI=10.1017/9781316529683.011, page 99–113. Cambridge University Press.
- Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2022. Robust Speech Recognition via Large-Scale Weak Supervision. *OpenAI*.
- Radim Řehůřek and Petr Sojka. 2010. Software Framework for Topic Modelling with Large Corpora. In *Proceedings of the LREC 2010 Workshop on New Challenges for NLP Frameworks*, pages 45–50, Valletta, Malta. ELRA. http://is.muni.cz/publication/884893/en.
- Hiroaki Sato, Tomoyasu Komori, Takeshi Mishima, Yoshihiko Kawai, Takahiro Mochizuki, Shoei Sato, and Tetsuji Ogawa. 2022. Text-Only Domain Adaptation Based on Intermediate CTC. *Proc. Inter*speech 2022, pages 2208–2212.
- Georgina Sturge. 2021. Court statistics for England and Wales. Technical report, House of Commons Library.
- Haoyu Wang, Shuyan Dong, Yue Liu, James Logan, Ashish Kumar Agrawal, and Yang Liu. 2020. ASR Error Correction with Augmented Transformer for Entity Retrieval. In *Interspeech*, pages 1550–1554.
- Shinji Watanabe, Michael Mandel, Jon Barker, Emmanuel Vincent, Ashish Arora, Xuankai Chang, Sanjeev Khudanpur, Vimal Manohar, Daniel Povey, Desh Raj, et al. 2020. CHiME-6 Challenge: Tackling multispeaker speech recognition for unsegmented recordings. In CHiME 2020-6th International Workshop on Speech Processing in Everyday Environments.
- Yuanyuan Zhang. 2022. Mitigating bias against nonnative accents. *Delft University of Technology*.