

# PRIMEQA: The Prime Repository for State-of-the-Art Multilingual Question Answering Research and Development

Avirup Sil\*, Jaydeep Sen, Bhavani Iyer, Martin Franz, Kshitij Fadnis,  
Mihaela Bornea, Sara Rosenthal, Scott McCarley, Rong Zhang, Vishwajeet Kumar,  
Yulong Li, Md Arafat Sultan, Riyaz Bhat, Radu Florian, Salim Roukos  
IBM Research AI

## Abstract

The field of Question Answering (QA) has made remarkable progress in recent years, thanks to the advent of large pre-trained language models, newer realistic benchmark datasets with leaderboards, and novel algorithms for key components such as retrievers and readers. In this paper, we introduce PRIMEQA: a one-stop and open-source QA repository with an aim to democratize QA research and facilitate easy replication of state-of-the-art (SOTA) QA methods. PRIMEQA supports core QA functionalities like retrieval and reading comprehension as well as auxiliary capabilities such as question generation. It has been designed as an end-to-end toolkit for various use cases: building front-end applications, replicating SOTA methods on public benchmarks, and expanding pre-existing methods. PRIMEQA is available at: <https://github.com/primeqa>.

## 1 Introduction

Question Answering (QA) is a major area of interest in Natural Language Processing (NLP), consisting primarily of two subtasks: information retrieval (IR) (Manning, 2008; Schütze et al., 2008) and machine reading comprehension (MRC) (Rajpurkar et al., 2016, 2018; Kwiatkowski et al., 2019a; Chakravarti et al., 2020). IR and MRC systems, also referred to as *retrievers* and *readers*, respectively, are commonly assembled in an end-to-end open-retrieval QA pipeline (henceforth, OpenQA) (Chen et al., 2017; Lee et al., 2019; Karpukhin et al., 2020; Santhanam et al., 2022b) that accepts a query and a large document collection as its input and provides an answer as output. The specific role of the retriever is to identify documents or passages (i.e., *contexts*) that contain information relevant to the query, while the reader component extracts a precise answer from such contexts.

While QA as a field has advanced rapidly, software to perform and replicate QA experiments has mostly been written in silos. At the time of this writing, no central repository exists that facilitates the training, analysis and augmentation of state-of-the-art (SOTA) models for different QA tasks at scale. In view of the above, and with an aim to democratize QA research by providing easy replicability, here, we propose PRIMEQA: an open-source repository<sup>1</sup> designed as an end-to-end toolkit, with all the necessary tools to easily and quickly create a custom QA application. We provide a main repository that contains easy-to-use scripts for retrieval, machine reading comprehension, and question generation with the ability to perform training, inference, and performance evaluation. Additionally, several sibling repositories provide features for easily connecting various retrievers and readers and creating a front-end user interface (UI) for end users. PRIMEQA has been designed as a platform for QA development and research and encourages collaboration from everyone in the field from beginners to experts. PRIMEQA already has a growing developer base with contributions from major academic institutions.

Our paper makes several major contributions:

- We present PRIMEQA, a first-of-its-kind repository for comprehensive QA research. It is free to use, well documented, easy to contribute to, and license friendly (Apache 2.0) for both academic and commercial usage.
- PRIMEQA provides the mechanism via accompanying repositories to create custom OpenQA applications containing both retrievers and readers for industrial deployment including a front-end UI.
- We provide *easy-to-use* implementations of SOTA retrievers and readers that are at the

\*Corresponding author

<sup>1</sup><https://github.com/primeqa>

top of major QA leaderboards, with capabilities for performing training, inference and performance evaluation of these models.

- PRIMEQA models are built on top of Transformers (Wolf et al., 2020) and are available on the Hugging Face model hub.<sup>2</sup>

## 2 Related Work

One of the largest open source community efforts for NLP software is Papers with Code (Robert and Thomas, 2022). Their mission is to create a free and open resource for NLP papers, code, datasets, methods and evaluation tables. Their focus is to cater to the wider NLP and Machine Learning community and not just QA. Even though the QA section includes over 1800 papers with their code, the underlying software components (written in various versions of both pytorch and tensorflow, with no central control whatsoever) do not communicate with each other. These disjoint QA resources hinder replicability and effective collaboration, and ultimately lead to quick sunseting of new capabilities.

Recently, among the most used repositories for NLP users have been the Transformers repository (Wolf et al., 2020). However, while being widely adopted by the community, they lack a distinct focus on QA. Unlike PRIMEQA, they only support one general script for extractive QA and several stand-alone python scripts for retrievers. Similarly FairSeq, (Ott et al., 2019) and AllenNLP (Gardner et al., 2018) also focus on a wide array of generic NLP tasks and hence do not solely present a QA repository allowing anyone plug and play components for their custom search application. There exists several toolkits catered to build customer-specific search applications (NVIDIA, 2022; Deepset, 2021) or search-based virtual assistants (IBM, 2020). However, while they have a good foundation for software deployment, unlike PRIMEQA, they lack the focus on replicating (and extending) the latest SOTA for QA on academic benchmarks which is an essential component needed in order for us to make rapid progress in this field.

## 3 PRIMEQA

PRIMEQA is a comprehensive open-source resource for cutting-edge QA research and development, governed by the following design principles:

<sup>2</sup><https://huggingface.co/PrimeQA>

Core Models	Extensions
<b>Retriever</b>	
BM25 (Robertson and Zaragoza, 2009)	Dr.DECR * (Li et al., 2022)
DPR (Karpukhin et al., 2020)	
ColBERT (Santhanam et al., 2022b)	
<b>Reader</b>	
General MRC (Alberti et al., 2019b)	ReasonBERT
FiD (Izacard and Grave, 2020)	OmniTab (Jiang et al., 2022a)
Boolean* (McCarley et al., 2022)	
Lists	
Tapas (Herzig et al., 2020a)	
Tapex (Liu et al., 2021)	
<b>Question Generation</b>	
Table QG (Chemmengath et al., 2021)	
Passage QG	
Hybrid QG	

Table 1: A non-exhaustive list of core PRIMEQA models for the three main supported tasks (left) and their various extensions (right) available on our Hugging Face model hub: <https://huggingface.co/PrimeQA>. \* SOTA leaderboard systems.

- **Reproducible:** Users can easily reproduce SOTA published results and combine or “plug and play” the corresponding methods with companion modules, e.g., a reader with a retriever. The various supported applications and the associated PRIMEQA components are listed in Table 1.

- **Customizable:** We allow users to customize and extend SOTA models for their own applications. This often entails fine-tuning on users’ custom data, which they can provide through one of several supported data formats, or process on their own by writing a custom data processor.

- **Reusable:** We aim to make it straightforward for developers to quickly deploy pre-trained off-the-shelf PRIMEQA models for their QA applications, requiring minimal code change.

- **Accessible:** We provide easy integration with Hugging Face Datasets and the Model Hub, allowing users to quickly plug in a range of datasets and models as shown in Table 1.

PRIMEQA in its entirety is a collection of four different repositories: a primary *research and replicability*<sup>3</sup> repository and three accompanying repositories<sup>4,5,6</sup> for industrial deployment. Figure 1 shows a diagram of the PrimeQA repository. It provides several entry points, supporting the needs

<sup>3</sup><https://github.com/primeqa/primeqa>

<sup>4</sup><https://github.com/primeqa/create-primeqa-app>

<sup>5</sup><https://github.com/primeqa/primeqa-orchestrator>

<sup>6</sup><https://github.com/primeqa/primeqa-ui>




Figure 1: The PRIMEQA Repository: the core components and features.

of different users, as shown at the top of the figure. The repository is centered around three core components: a **retriever**, a **reader**, and a **question generator** for data augmentation. These components can be used as individual modules or assembled into an end-to-end QA pipeline. All components are implemented on top of existing AI libraries.

### 3.1 The Core Components

Each of the three core PRIMEQA components supports different flavors of the task it has been built for, as we detail in this section.

#### 3.1.1 Retriever: `run_ir.py`

Retrievers predict documents (or passages) from a document collection that are relevant to an input question. PRIMEQA has both sparse and SOTA dense retrievers along with their extensions, as shown in Table 1. We provide a single Python script `run_ir.py` that can be passed arguments to switch between different retriever algorithms.

**Sparse:** BM25 (Robertson and Zaragoza, 2009) is one of the most popular sparse retrieval methods, thanks to its simplicity, efficiency and robustness. Our Python-based implementation of BM25 is powered by the open-source library `PySerini`.

**Dense:** Modern neural retrievers have utilized dense question and passage representations to achieve SOTA performance on various benchmarks, while needing GPUs for efficiency. We currently support ColBERT (Santhanam et al., 2022b) and DPR (Karpukhin et al., 2020): both fine-tune pre-trained language models to train question and passage encoders (Devlin et al., 2019; Conneau et al.,

2020). They utilize FAISS (Johnson et al., 2017) for K-nearest neighbor clustering and compressed index representations, respectively, and support multilingual retrieval with the question and the documents being in the same (Lee et al., 2019; Longpre et al., 2021) or different languages (cross-lingual) (Asai et al., 2021).

#### 3.1.2 Reader: `run_mrc.py`

Given a question and a retrieved passage—also called the *context*—a reader predicts an answer that is either extracted directly from the context or is generated based on it. PRIMEQA supports training and inference of both extractive and generative readers through a single Python script: `run_mrc.py`. It works out-of-the-box with different QA models extended from the Transformers library (Wolf et al., 2020).

**Extractive:** PRIMEQA’s general extractive reader is a pointer network that predicts the start and end of the answer span from the input context (Devlin et al., 2019; Alberti et al., 2019b). It can be initialized with most large pre-trained language models (Devlin et al., 2019; Liu et al., 2019; Conneau et al., 2020). In addition, our reader is extremely versatile as it can provide responses to questions with list answers (Khashabi et al., 2021), *yes/no* responses to Boolean questions (Clark et al., 2019, 2020a; Kwiatkowski et al., 2019b), answer spans found in tables (Herzig et al., 2020b) and in multimodal (text+image) documents (Mathew et al., 2021). Examples of several extractive readers along with their extensions are provided in Table 1.

**Generative:** PRIMEQA provides generative read-

ers based on the popular Fusion-in-Decoder (FiD) (Izacard and Grave, 2020) algorithm. Currently, it supports easy initialization with large pre-trained sequence-to-sequence (henceforth, seq2seq) models (Lewis et al., 2019; Raffel et al., 2022). With FiD, the question and the retrieved passages are used to generate relatively long and complex multi-sentence answers providing support for long form question answering tasks, *e.g.*, ELI5 (Petroni et al., 2021; Fan et al., 2019).

### 3.1.3 Question Generation: `run_qg.py`

Data augmentation through synthetic question generation (QG) can be a powerful tool for improving QA model generalization (Alberti et al., 2019a; Sultan et al., 2020; Gangi Reddy et al., 2022a), including in domain adaptation (Shakeri et al., 2021; Gangi Reddy et al., 2021, 2022b), domain generalization (Sultan et al., 2022) and few-shot learning (Yue et al., 2022) settings. QG can also circumvent the problem of not having labeled data in the target domain of application. Question generators take a span of text (*e.g.*, a sentence) from a document as input, hypothesize an answer (*e.g.*, a named entity) and generate a question as output. PRIMEQA’s QG component (Chemmengath et al., 2021) is based on SOTA sequence-to-sequence generation architectures (Raffel et al., 2022), and supports both unstructured and structured input text through a single Python script `run_qg.py`. A list of available question generators and their extensions are provided in Table 1.

**Unstructured Input:** Our first variant of QG is a multilingual text-to-text model capable of generating questions in the language of the input passage. It fine-tunes a pre-trained T5 language model (Raffel et al., 2022) on publicly available multilingual QA data (Clark et al., 2020b).

**Structured Input:** We also provide QG capability over tables, for which the generator is trained on examples of SQL and natural language question pairs extracted from the popular Table QA dataset (Zhong et al., 2017a). As in (Chemmengath et al., 2021), during inference, PRIMEQA uses a controllable SQL sampler to select SQL queries for a given table and answer text, and then applies the trained QG model to generate natural language questions.

## 3.2 Entry Points

We cater to different user groups in the QA community by providing different entry points to PRIMEQA, as shown in Figure 1.

- **Top-level Scripts:** Researchers can use the top level scripts, `run_ir/mrc/qg.py`, to reproduce published results as well as train, fine-tune and evaluate associated models on their own custom data.

- **Jupyter Notebooks:** These demonstrate how to use built-in classes to run the different PRIMEQA components and perform the corresponding tasks. These are useful for developers and researchers who want to reuse and extend PRIMEQA functionalities.

- **Inference APIs:** The Inference APIs are primarily meant for developers, allowing them to use PRIMEQA components on their own data with only a few lines of code. These APIs can be initialized with the pre-trained PRIMEQA models provided in the HuggingFace hub, or with a custom model that has been trained for a specific use case.

- **Service Layer:** The service layer helps developers set up an end-to-end QA system quickly by providing a wrapper around the core components that exposes an endpoint and an API.

- **UI:** The UI is for end-users, including the non-technical layman who wants to use PRIMEQA services interactively to ask questions and get answers.

## 3.3 Pipelines for OpenQA

PRIMEQA core components and entry points make it intuitive for users to build an OpenQA *pipeline* and configure it to use any of the PRIMEQA retrievers and readers. This is facilitated through a lightweight wrapper built around each core component, which implements a training and an inference API. The retrieval component of the pipeline predicts relevant passages/contexts for an input question, and the reader predicts an answer from the retrieved contexts. PRIMEQA pipelines are easy to construct using the pre-trained models in the model hub and our inference APIs.

An example of such a pipeline can be connecting a ColBERT retriever to an FiD reader to construct a long form QA (LFQA) system. This pipeline uses the retriever to obtain supporting passages that are subsequently used by the reader to generate complex multi-sentence answers. A different pipeline can also be instantiated to use an extractive reader instead that is available through our model hub.

## 4 Services and Deployment

Industrial deployment often necessitates running complex models and processes at scale. We use Docker to package these components into micro-






Figure 2: PRIMEQA’s end-to-end application. Each container contains a development (blue), build (yellow) and deployment (green) stack.

services that interact with each other and can be ported to servers with different hardware capabilities (e.g. GPUs, CPUs, memory). The use of docker makes the addition, replacement or deletion of services easy and scalable. All components in the PRIMEQA repository are available via REST and/or gRPC micro-services. Our docker containers are available on the public [DockerHub](#) and can be deployed using technologies such as OpenShift and Kubernetes.

In addition to the main [PrimeQA](#) repository, we provide three sibling repositories for application deployment:

[primeqa-ui](#) is the front-end UI. Users can personalize the front-end UI by adding custom organization logos or changing the display fonts.

[primeqa-orchestrator](#) is a REST server and is the central hub for the integration of PRIMEQA services and external components and the execution of a pipeline. For instance, the orchestrator can be configured to search a document collection with either a retriever from PrimeQA such as ColBERT, or an external search engine such as Watson Discovery.<sup>7</sup>

[create-primeqa-app](#) provides the scripts to launch the demo application by starting the orchestrator and UI services.

Figure 2 illustrates how to deploy a QA application at scale using the core PrimeQA services (e.g. Reader and Retriever) and our three sibling repositories. We provide this end-to-end deployment for our demo, however users can also utilize PrimeQA as an application with their own orchestrator or UI.

Figure 3 shows an OpenQA demo application built with PRIMEQA components. Our demo application provides a mechanism to collect user feedback. The *thumbs up / down* icons next to each result enables a user to record feedback which is then stored in a database. The user feedback data can then be retrieved and used as additional training data to further improve a retriever and reader model.

## 5 Community Contributions

While being relatively new, PRIMEQA has already garnered positive attention from the QA community and is receiving constant successful contributions from both international academia and industry via Github pull requests. We describe some instances here and encourage further contributions from all in the community. We provide support for those interested in contributing through a dedicated slack channel<sup>8</sup>, Github issues and PR reviews.

**Neural Retrievers:** ColBERT, one of our core neural retrievers, was contributed by [Stanford NLP](#). Since PRIMEQA provides very easy entry points

<sup>7</sup><https://www.ibm.com/cloud/watson-discovery>

<sup>8</sup><https://ibm.biz/pqa-slack>




Figure 3: A custom OpenQA search application built with PRIMEQA. Additional screenshots are in Appendix A.

into its core library, they were able to integrate their software into the retriever script `run_ir.py` independently. Their contribution to PRIMEQA provides the QA community with the ability to obtain SOTA performance on OpenQA benchmark datasets by performing ‘late interaction’ search on a variety of datasets. They also contributed ColBERTv2 (Santhanam et al., 2022b) and its PLAID (Santhanam et al., 2022a) variant. The former reduces the index size by 10x over its predecessor while the latter makes search faster by almost 7x on GPUs and 45x on CPUs.

**Few shot learning:** The SunLab from Ohio State University provided the ability to easily perform few-shot learning in PRIMEQA. Their first contribution, ReasonBERT (Deng et al., 2021), provides a pretrained methodology that augments language models with the ability to reason over long-range relations. Under the few-shot setting, ReasonBERT in PRIMEQA substantially outperforms a RoBERTa (Liu et al., 2019) baseline on the extractive QA task. PRIMEQA gives any researcher or developer the capability to easily integrate this component in their custom search application e.g. a DPR retriever and a ReasonBERT reader.

**Table Readers:** Beihang University and Microsoft Research Asia contributed Tapex (Liu et al., 2021) as the first generative Table reader within PRIMEQA. Tapex proposes a novel table pre-training strategy based on neural SQL executor and achieves the SOTA on Wiki-SQL (Zhong et al., 2017a) and Wiki-TableQuestions (Pasupat

and Liang, 2015a). Their contribution reused the seq2seq trainer from Transformers (Wolf et al., 2020) for a seamless integration into PRIMEQA. Another contribution comes from LTI CMU’s NeuLab which integrated OmniTab (Jiang et al., 2022b). It proposes an efficient pre-training strategy combining natural and synthetic pre-training data. This integration happened organically as OmniTab builds on top of Tapex in PRIMEQA. Currently, their model produces the best few-shot performance on Wiki-TableQuestions, making it suitable for domain adaptation experiments for anyone using PRIMEQA.

**Custom search app for Earth Science:** Joint work between NASA and University of Alabama in Huntsville, involved creating a custom search application over scientific abstracts and papers related to Earth Science. First, using the top level scripts in PRIMEQA, they easily trained an OpenQA system on over 100k abstracts by training a ColBERT retriever and an extractive reader. Then, they were able to quickly deploy the search application using the `create-primeqa-app` and make it available publicly<sup>9</sup>.

## 6 Conclusion

PRIMEQA is an open-source library designed by QA researchers and developers to easily facilitate reproducibility and reusability of existing and future works. This is an important and valuable contri-

<sup>9</sup><http://primeqa.nasa-impact.net/qa>

bution to the community as it enables these models to be easily accessible to researchers and end-users in the rapidly progressing field of QA. Our library also provides a ‘service layer’ that allows developers to take pre-trained PRIMEQA models and deploy them for their custom search application. PRIMEQA is built on top of the largest NLP open-source libraries and tools and provides simple python scripts as entry points to easily reuse its core components across different applications. Our easy access and reusability has already garnered significant positive traction and enables PRIMEQA to grow organically as an important resource for the rapid state-of-the-art progress within the QA community.

## References

- Chris Alberti, Daniel Andor, Emily Pitler, Jacob Devlin, and Michael Collins. 2019a. [Synthetic QA corpora generation with roundtrip consistency](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 6168–6173, Florence, Italy. Association for Computational Linguistics.
- Chris Alberti, Kenton Lee, and Michael Collins. 2019b. A bert baseline for the natural questions. *arXiv preprint arXiv:1901.08634*.
- Akari Asai, Jungo Kasai, Jonathan Clark, Kenton Lee, Eunsol Choi, and Hannaneh Hajishirzi. 2021. [XOR QA: Cross-lingual open-retrieval question answering](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 547–564, Online. Association for Computational Linguistics.
- Rishav Chakravarti, Anthony Ferritto, Bhavani Iyer, Lin Pan, Radu Florian, Salim Roukos, and Avirup Sil. 2020. Towards building a robust industry-scale question answering system. In *Proceedings of the 28th International Conference on Computational Linguistics: Industry Track*, pages 90–101.
- Saneem Chemmengath, Vishwajeet Kumar, Samarth Bharadwaj, Jaydeep Sen, Mustafa C¸anim, Soumen Chakrabarti, Alfio Gliozzo, and Karthik Sankaranarayanan. 2021. [Topic transferable table question answering](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 4159–4172, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Danqi Chen, Adam Fisch, Jason Weston, and Antoine Bordes. 2017. [Reading Wikipedia to answer open-domain questions](#). In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1870–1879, Vancouver, Canada. Association for Computational Linguistics.
- Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. 2019. [BoolQ: Exploring the surprising difficulty of natural yes/no questions](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 2924–2936, Minneapolis, Minnesota. Association for Computational Linguistics.
- Jonathan H. Clark, Eunsol Choi, Michael Collins, Dan Garrette, Tom Kwiatkowski, Vitaly Nikolaev, and Jennimaria Palomaki. 2020a. [TyDi QA: A benchmark for information-seeking question answering in typologically diverse languages](#). *Transactions of the Association for Computational Linguistics*, 8:454–470.
- Jonathan H Clark, Eunsol Choi, Michael Collins, Dan Garrette, Tom Kwiatkowski, Vitaly Nikolaev, and Jennimaria Palomaki. 2020b. Tydi qa: A benchmark for information-seeking question answering in typologically diverse languages. *Transactions of the Association for Computational Linguistics*, 8:454–470.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzm¸an, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. [Unsupervised cross-lingual representation learning at scale](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.
- Deepset. 2021. [Haystack](#).
- Xiang Deng, Yu Su, Alyssa Lees, You Wu, Cong Yu, and Huan Sun. 2021. [ReasonBERT: Pre-trained to reason with distant supervision](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6112–6127, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of deep bidirectional transformers for language understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Angela Fan, Yacine Jernite, Ethan Perez, David Grangier, Jason Weston, and Michael Auli. 2019. [ELI5: Long form question answering](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3558–3567, Florence, Italy. Association for Computational Linguistics.

- Revanth Gangi Reddy, Bhavani Iyer, Md Arafat Sultan, Rong Zhang, Avirup Sil, Vittorio Castelli, Radu Florian, and Salim Roukos. 2021. Synthetic target domain supervision for open retrieval qa. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 1793–1797.
- Revanth Gangi Reddy, Md Arafat Sultan, Martin Franz, Avirup Sil, and Heng Ji. 2022a. Entity-conditioned question generation for robust attention distribution in neural information retrieval. *arXiv preprint arXiv:2204.11373*.
- Revanth Gangi Reddy, Vikas Yadav, Md Arafat Sultan, Martin Franz, Vittorio Castelli, Heng Ji, and Avirup Sil. 2022b. [Towards robust neural retrieval with source domain synthetic pre-finetuning](#). In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 1065–1070, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.
- Matt Gardner, Joel Grus, Mark Neumann, Oyvind Tafjord, Pradeep Dasigi, Nelson Liu, Matthew Peters, Michael Schmitz, and Luke Zettlemoyer. 2018. Allennlp: A deep semantic natural language processing platform. *arXiv preprint arXiv:1803.07640*.
- Jonathan Herzig, Pawel Krzysztof Nowak, Thomas Mueller, Francesco Piccinno, and Julian Eisenschlos. 2020a. Tapas: Weakly supervised table parsing via pre-training. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4320–4333.
- Jonathan Herzig, Pawel Krzysztof Nowak, Thomas Müller, Francesco Piccinno, and Julian Eisenschlos. 2020b. [TaPas: Weakly supervised table parsing via pre-training](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4320–4333, Online. Association for Computational Linguistics.
- IBM. 2020. [Watson assistant](#).
- Mohit Iyyer, Scott Wen-tau Yih, and Ming-Wei Chang. 2017. [Search-based neural structured learning for sequential question answering](#). In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics.
- Gautier Izacard and Edouard Grave. 2020. Leveraging passage retrieval with generative models for open domain question answering. In *Conference of the European Chapter of the Association for Computational Linguistics*.
- Zhengbao Jiang, Yi Mao, Pengcheng He, Graham Neubig, and Weizhu Chen. 2022a. Omnitab: Pretraining with natural and synthetic data for few-shot table-based question answering. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 932–942.
- Zhengbao Jiang, Yi Mao, Pengcheng He, Graham Neubig, and Weizhu Chen. 2022b. [OmniTab: Pre-training with natural and synthetic data for few-shot table-based question answering](#). In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 932–942, Seattle, United States. Association for Computational Linguistics.
- Jeff Johnson, Matthijs Douze, and Hervé Jégou. 2017. [Billion-scale similarity search with gpus](#). *CoRR*, abs/1702.08734.
- Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. [Dense passage retrieval for open-domain question answering](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6769–6781, Online. Association for Computational Linguistics.
- Daniel Khashabi, Amos Ng, Tushar Khot, Ashish Sabharwal, Hannaneh Hajishirzi, and Chris Callison-Burch. 2021. [GooAQ: Open question answering with diverse answer types](#). In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 421–433, Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. 2019a. [Natural questions: A benchmark for question answering research](#). *Transactions of the Association for Computational Linguistics*, 7:452–466.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Matthew Kelcey, Jacob Devlin, Kenton Lee, Kristina N. Toutanova, Llion Jones, Ming-Wei Chang, Andrew Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. 2019b. Natural questions: a benchmark for question answering research. *Transactions of the Association of Computational Linguistics*.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Matthew Kelcey, Jacob Devlin, Kenton Lee, Kristina N. Toutanova, Llion Jones, Ming-Wei Chang, Andrew Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. 2019c. Natural questions: a benchmark for question answering research. *Transactions of the Association of Computational Linguistics*.
- Kenton Lee, Ming-Wei Chang, and Kristina Toutanova. 2019. [Latent retrieval for weakly supervised open domain question answering](#). In *Proceedings of the*



- 57th Annual Meeting of the Association for Computational Linguistics, pages 6086–6096, Florence, Italy. Association for Computational Linguistics.
- Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. 2019. Bart: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Annual Meeting of the Association for Computational Linguistics*.
- Yulong Li, Martin Franz, Md Arafat Sultan, Bhavani Iyer, Young-Suk Lee, and Avirup Sil. 2022. [Learning cross-lingual IR from an English retriever](#). In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4428–4436, Seattle, United States. Association for Computational Linguistics.
- Qian Liu, Bei Chen, Jiaqi Guo, Morteza Ziyadi, Zeqi Lin, Weizhu Chen, and Jian-Guang Lou. 2021. Tapex: Table pre-training via learning a neural sql executor. In *International Conference on Learning Representations*.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. [Roberta: A robustly optimized bert pretraining approach](#).
- Shayne Longpre, Yi Lu, and Joachim Daiber. 2021. Mkqa: A linguistically diverse benchmark for multilingual open domain question answering. *Transactions of the Association for Computational Linguistics*, 9:1389–1406.
- Christopher D Manning. 2008. *Introduction to information retrieval*. Syngress Publishing,.
- Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. 2021. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 2200–2209.
- Scott McCarley, Mihaela Bornea, Sara Rosenthal, Anthony Ferritto, Md Arafat Sultan, Avirup Sil, and Radu Florian. 2022. [Gaama 2.0: An integrated system that answers boolean and extractive questions](#).
- NVIDIA. 2022. [Tao toolkit](#).
- Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. 2019. fairseq: A fast, extensible toolkit for sequence modeling. *arXiv preprint arXiv:1904.01038*.
- Panupong Pasupat and Percy Liang. 2015a. [Compositional semantic parsing on semi-structured tables](#). In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1470–1480, Beijing, China. Association for Computational Linguistics.
- Panupong Pasupat and Percy Liang. 2015b. [Compositional semantic parsing on semi-structured tables](#). In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1470–1480, Beijing, China. Association for Computational Linguistics.
- Fabio Petroni, Aleksandra Piktus, Angela Fan, Patrick Lewis, Majid Yazdani, Nicola De Cao, James Thorne, Yacine Jernite, Vladimir Karpukhin, Jean Maillard, Vassilis Plachouras, Tim Rocktäschel, and Sebastian Riedel. 2021. [KILT: a benchmark for knowledge intensive language tasks](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2523–2544, Online. Association for Computational Linguistics.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2022. Exploring the limits of transfer learning with a unified text-to-text transformer. 21(1).
- Pranav Rajpurkar, Robin Jia, and Percy Liang. 2018. [Know what you don’t know: Unanswerable questions for SQuAD](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 784–789, Melbourne, Australia. Association for Computational Linguistics.
- Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. 2016. [SQuAD: 100,000+ questions for machine comprehension of text](#). In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 2383–2392, Austin, Texas. Association for Computational Linguistics.
- Marcin-Elvis Guillemin Andrew Robert, Ross and Thomas. 2022. [Papers with code](#). In *Meta AI Research*.
- Stephen Robertson and Hugo Zaragoza. 2009. [The probabilistic relevance framework: Bm25 and beyond](#). *Foundations and Trends in Information Retrieval*, 3:333–389.
- Keshav Santhanam, Omar Khattab, Christopher Potts, and Matei Zaharia. 2022a. [PLAID: An efficient engine for late interaction retrieval](#). In *Proceedings of the 31st ACM International Conference on Information and Knowledge Management, CIKM ’22*, page 1747–1756, New York, NY, USA. Association for Computing Machinery.
- Keshav Santhanam, Omar Khattab, Jon Saad-Falcon, Christopher Potts, and Matei Zaharia. 2022b. [ColBERTv2: Effective and efficient retrieval via](#)

[lightweight late interaction](#). In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3715–3734, Seattle, United States. Association for Computational Linguistics.

Hinrich Schütze, Christopher D Manning, and Prabhakar Raghavan. 2008. *Introduction to information retrieval*, volume 39. Cambridge University Press Cambridge.

Siamak Shakeri, Noah Constant, Mihir Kale, and Linting Xue. 2021. [Towards zero-shot multilingual synthetic question and answer generation for cross-lingual reading comprehension](#). In *Proceedings of the 14th International Conference on Natural Language Generation*, pages 35–45, Aberdeen, Scotland, UK. Association for Computational Linguistics.

Md Arafat Sultan, Shubham Chandel, Ramón Fernández Astudillo, and Vittorio Castelli. 2020. [On the importance of diversity in question generation for QA](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5651–5656, Online. Association for Computational Linguistics.

Md Arafat Sultan, Avirup Sil, and Radu Florian. 2022. Not to overfit or underfit? a study of domain generalization in question answering. *arXiv preprint arXiv:2205.07257*.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander Rush. 2020. [Transformers: State-of-the-art natural language processing](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.

Xiang Yue, Ziyu Yao, and Huan Sun. 2022. Synthetic question value estimation for domain adaptation of question answering. In *ACL*.

Victor Zhong, Caiming Xiong, and Richard Socher. 2017a. Seq2sql: Generating structured queries from natural language using reinforcement learning. *CoRR*, abs/1709.00103.

Victor Zhong, Caiming Xiong, and Richard Socher. 2017b. Seq2sql: Generating structured queries from natural language using reinforcement learning. *CoRR*, abs/1709.00103.

## A Appendix

### A.1 PrimeQA Applications

Figure 4 shows a screen-shot of three **PrimeQA** applications.

Datasets
OpenNQ
XOR-TyDi (Asai et al., 2021)
ELI5 SQuAD (Rajpurkar et al., 2016)
TyDiQA (Clark et al., 2020b)
NQ (Kwiatkowski et al., 2019c)
ELI5
SQA (Iyyer et al., 2017)
WTQ (Pasupat and Liang, 2015b)
DocVQA (Mathew et al., 2021)
WikiSQL (Zhong et al., 2017b)

Table 2: A list of some of the supported datasets in PrimeQA

retriever	<a href="#">simple python script</a>
reader	<a href="#">inference APIs</a>
unstructured qg	<a href="#">inference APIs</a>
pipeline	<a href="#">inference APIs</a>

Table 3: Links to PrimeQA

Retrieval

Question

What are the sources of black carbon in the atmosphere?

5 documents from articles

Title: Document 0

Text: Black carbon, also known as soot, emitted from combustion of fuels and biomass burning absorbs solar radiation in the atmosphere and is one of the major causes of global warming, after carbon dioxide emissions. When black carbon is deposited on snow and ice, the soot-covered snow or ice absorbs more sunlight, leading to surface warming. Due to the large amount of snow and ice in the Arctic—which has warmed twice as fast as the global average over the past century—the region is likely to be especially sensitive to black carbon.

Confidence: 100%

Score:27.21875

Was this document useful?

Title: Document 1

Text: Black carbon, or soot, is the second most important anthropogenic driver of global climate change, taking a backseat only to carbon dioxide. Whether from wood in a cookstove, coal in a power plant, or trees charred by a wildfire, black carbon is produced by the incomplete combustion of organic matter. Once it gets into the environment, black carbon lowers the albedo when it settles on land, increasing warming and enhancing snow and ice melt. In the atmosphere, black carbon both helps and inhibits the formation of clouds.

Confidence: 93%

Score:27.140625

Was this document useful?

Reading

Demographically, Warsaw was the most diverse city in Poland, with significant numbers of foreign-born residents.[121] In addition to the Polish majority, there was a large and thriving Jewish minority. According to the Imperial Census of 1897, out of the total population of 638,000, Jews constituted 219,000 (equivalent to 34%). [122] Prior to the Second World War, Warsaw hosted the world's second largest Jewish population after New York – approximately 30 percent of the city's total population in the late 1930s.[51] In 1933, 833,500 out of 1,178,914 people declared Polish as their mother tongue.[123] There was also a notable German community.[124] The ethnic composition of contemporary Warsaw is incomparable to the diversity that existed for nearly 300 years.[51] Most of the modern-day population growth is based on internal migration and urbanisation.

Question

How many of Warsaw's inhabitants spoke Polish in 1933?

Ask

Question

How many of Warsaw's inhabitants spoke Polish in 1933?

Found 3 answers matching your question.

Answer

833,500

Evidence

Confidence: 100%

Was this answer useful?

Question Answering

What is the name of the Voldemort's snake ?

Found 10 answers matching your question.

Answer

Nagini

Evidence

Voldemort dropped his gaze once more to the wand in his fingers. It troubled him ... and those things that troubled Lord Voldemort needed to be rearranged. ... "Go and fetch Snape." "Snape, m-my Lord?" "Snape. Now. I need him. There is a — service — I require from him. Go." Frightened, stumbling a little through the gloom, Lucius left the room. Voldemort continued to stand there, twirling the wand between his fingers, staring at it. "It is the only way, **Nagini**," he whispered, and he looked around, and there was the great thick snake, now suspended in midair, twisting gracefully within the enchanted, protected space he had made for her, a starry, transparent sphere somewhere between glittering cage and tank. With a gasp, Harry pulled back and opened his eyes; at the same moment his ears were assaulted with the screeches and cries, the smashes and bangs of battle. "He's in the Shrieking Shack. The snake's with him, it's got some sort of magical protection around it. He's just sent Lucius Malfoy to find Snape."

Confidence: 83%

Source: Book7

Document: Paragraph 1148

Was this answer useful?

Figure 4: PrimeQA Applications