

Out of Distribution Performance of State of Art Vision Model

Md Salman Rahman
 NYU
 salman@nyu.edu

Wonkwon Lee
 NYU
 w12733@nyu.edu

Abstract

The vision transformer (ViT) has advanced to the cutting edge in the visual recognition task. Transformers are more robust than CNN, according to the latest research. ViT's self-attention mechanism, according to the claim, makes it more robust than CNN. Even with this, we discover that these conclusions are based on unfair experimental conditions and just comparing a few models, which did not allow us to depict the entire scenario of robustness performance. In this study, we investigate the performance of 58 state-of-the-art computer vision models in a unified training setup based not only on attention and convolution mechanisms but also on neural networks based on a combination of convolution and attention mechanisms, sequence-based model, complementary search, and network-based method. Our research demonstrates that robustness depends on the training setup and model types, and performance varies based on out-of-distribution type. Our research will aid the community in better understanding and benchmarking the robustness of computer vision models. The code and models are publicly available at https://github.com/salman-lui/vision_course_project

[6, 12, 13, 75].

The Transformer's success in NLP is beginning to be seen in computer vision [14, 30]. The ground-breaking work, Vision Transformer (ViT), shows that the pure Transformer architectures can perform astounding on many visual benchmarks, mainly when massive datasets (like JFT-300M) are available for pre-training [52]. The tokenization module of Transformers is enhanced, multi-resolution feature maps are built on Transformers, parameter-efficient Transformers are designed for scalability, and other improvements are made after carefully curating the training pipeline and distillation method [64, 74]. Our goal in this work is to present a fair and fully comprehend of the out-of-distribution performance of almost all the states of the computer vision model, each of which is based on a unique recipe.

Paul et al. compare the performance of ViT models with the state-of-the-art convolutional neural networks (CNNs), Big-Transfer, in a thorough performance comparison in order to investigate the robustness of the Vision Transformer [46]. ViT is a robust learner, according to the analysis, which the author credits to its use of large-scale pre-training and attention modules, its capacity to recognize images that have been randomly masked, its low sensitivity to perturbations in the Fourier spectrum domain, and its ability to exhibit a wider energy distribution and a smoother loss landscape in the face of adversarial input perturbations. Mahmood et al. find that vision transformers are robust to adversarial examples [42]. Naseer et al. investigate the intriguing properties of vision transformers and find that ViTs are highly robust to severe occlusions, perturbations, and domain shifts [45]. Bhojanapalli et al. discover that ViT models, when pre-trained with enough data, are at least as robust to various perturbations as their ResNet counterparts [4].

Transformers are supposedly more robust than CNNs, according to the literature currently in circulation, although different sets of the model require a different training setup for comparison. Additionally, to our knowledge, there is no literature that examines the performance of each SOTA vision model's robustness. We compare the robustness performance of vision models built upon various mechanisms,

1. Introduction and Motivating Works

The shift in data distribution is a challenging machine-learning problem, especially in computer vision. Distribution shifts are caused by poor data quality, out-of-distribution, and adversarial problems [2]. Transformer is a powerful visual recognition tool. Recent research also claims that Transformers are far more robust than Convolutional Neural Networks, as well as having competitive performance on several visual benchmarks (CNNs) [42, 46].

Natural language processing dramatically advanced thanks to the Transformers invention by Vaswani et al. in 2017 [66]. With the addition of the self-attention module, the Transformer can now accurately grasp the non-local interactions between all of the input sequence parts and achieve cutting-edge performance on various NLP tasks

such as convolution, attention, multi-layer perceptron, MobileNet, and sequence, in this work by trying to adhere to a unified training setup for not only CNN and the ViT model but also all other existing vision models.

2. Methods

2.1. Design and Settings

We aim to provide fair and in-depth comparisons Transformers, CNNs, and other combinations on robustness evaluations. Our models are tested on a variety of benchmark robustness datasets, including ImageNet-A, ImageNet-R, ImageNet-O, ImageNet-Sketch, and Stylized ImageNet. Recent research on robustness comparison between Transformers and CNNs is largely conducted in unfair experimental settings, where models are not compared at the same scale of parameters. For example, a comparison between a small CNN ResNet-50 with 25 million parameters and a large Transformer ViT-B with 86 million parameters is not fair evaluation. Also distinct training frameworks are applied to distinct models, in terms of training datasets, number of epochs, and augmentation strategies. In our research, we evaluate small baseline models of each of the recipes in a fair experimental environment of out-of-distribution benchmark sets.

2.1.1 Convolution Based Model Training

Convolutional neural network Among the 29 state-of-the-art convolutional neural network models, ResNet-50, DenseNet121, EfficientNet-B, and TinyNet-A are implemented following the standard recipes. All CNNs are trained on ImageNet using Adam optimizer and an initial learning rate of 0.01. For the rest of the models, pre-trained models are used to evaluate the robustness performance due to the challenge in training.

2.1.2 Attention Based Model Training

By effectively transferring Transformers from natural language processing to computer vision, ViT outperforms CNNs on a number of visual benchmarks. In this experiment, DeiT-S, BEiT-B, ViFormer-S, and PiT-B are implemented as the default Transformer architecture. All transformers are trained on ImageNet using Adam optimizer and an initial learning rate of 0.01.

The same training framework used on CNN models is also used on our Transformer models (e.g., 100 training epochs, the same optimizer and learning rate, etc). Pre-trained weights are used for the rest of the Transformer models due to the challenge of training.

2.1.3 Combined Attention and Convolution Based Training

ConViT is a state-of-the-art ViT enhanced with soft convolutional inductive biases. The model is constructed based on the DeiT-B, an open-sourced hyperparameter-optimized version of the ViT. The 3×3 convolutional filters are applied in the form of 6 attention heads as in [62]. For other combined models like ConvNext, EdgeNeXt, and LeViT, baseline pre-trained models are used for faster evaluation.

2.1.4 Model (not Convolution or Attention) Training

For models with a combination of other models (not convolution-based or attention-based), such as MLP-Mixer, MobileNet, RegNet, and Sequencer, pre-trained weights are used for convenience [71].

2.2. Out of Distribution Robustness

Several benchmarks using out-of-distribution samples have recently been presented to assess how deep neural networks perform when tested outside the box. Two such benchmarks are present in our robustness evaluation suite in particular:

- **ImageNet - A:** ImageNet-A [26] contains real-world images gathered from scenes with complex recognizing tasks like occlusion and fog. Such images can lead to misclassification for reasons such as multiple objects associated with to a single discrete label. In table 1 and 3, we report the top-1 accuracy of various models on the ImageNet-A dataset. MViT v2 achieves the highest top-1 accuracy score on the dataset, while MobileViT only reports the lowest score. Transformer models show superior performance than CNN and other models, and thus self-attention is considered a key to solving these problems.
- **ImageNet - R:** ImageNet-R(endition) [25] contains 30000 images containing various renditions (e.g., art, cartoons, graphics, paintings, etc) of ImageNet 1000 object classes. Such representations are naturally occurring and differ from ImageNet images in terms of textures and local image statistics, allowing us measures the synthetic robustness of the vision network by semantic shifts under various domains. In our experiment, the attention-based models report a superior performance over the convolution-based and other models. Among attention-based models, DeiT3 achieves the highest accuracy of 53.63%, and EfficientNet V2 achieves the highest of 52.97% among convolution-based models.
- **ImageNet - O:** ImageNet-O [26] comprises images from 200 different classes that a model did not observe during training and are regarded as anomalies.

A robust model is expected to achieve low confidence scores on such images. The dataset is adversarially filtered samples for ImageNet out-of-distribution detectors and contains the 200-class subset of ImageNet’s 1000 classes. For the evaluation strategy, the *area under the precision-recall curve* (AUPR) is used as in the paper [26]. MobileViT and BEiT report the highest out-of-distribution scores among all the models.

- **ImageNet - Sketch:** ImageNet-Sketch [68] contains 50000 black and white sketch images, 50 images for each of the 1000 ImageNet classes. It is a unique ImageNet-scale out-of-domain evaluation dataset for classification and the images are gathered independently from the original validation set. Such out-of-domain black-and-white sketch images can measure a model’s ability to extrapolate out of domain.
- **Stylized ImageNet:** Stylized ImageNet [17] is a stylized version of ImageNet generated by AdaIN style transfer such as greyscale, silhouette, edges, texture, and etc. While global object shapes remain intact after stylization, local textures are severely distorted. This allows Stylized-ImageNet to induce CNNs to learn about shapes and less about local textures.

3. Robustness Experiments and Results

We conduct a thorough robustness analysis (on six out of distribution data) of 58 cutting-edge computer vision models based on different mechanisms, including convolution [24], attention [14], attention & convolution combined [15], multi-layer perceptrons [61], complementary search methods (MobileNet) [28], networks (RegNet) [47], and sequence [60].

3.1. Convolution Mechanism

Based on a comprehensive convolution process inspired by LeNet [32] and AlexNet [31], we choose 29 state-of-the-art computer vision models along with their accuracy listed in Table 1 and 2 alphabetically.

ConvNeXt is a pure ConvNet model that can compete favorably across several computer vision benchmarks with state-of-the-art hierarchical vision Transformers while retaining the simplicity and efficiency of standard ConvNets [40]. It achieves the highest ImageNet top-1 accuracy with 87.8%. It also reports 35.79% accuracy on ImageNet-A, 19.24% and 38.22% on Stylized ImageNet and Sketch. ConvNeXt demonstrates a better out-of-distribution classification than Transformers and others. Using a cross-stage partial network, Wang et al. CSPNet solution reduced computation by 20% without sacrificing accuracy while addressing the issue of high inference computations from the perspective of network design [67]. While CSPNet’s

Table 1. Performance of convolution-based model on ImageNet, ImageNet-A, and ImageNet-O

Architecture	ImageNet	ImageNet -A	ImageNet -O
ConvNext	87.8	35.79	2.18
CSPNet	77.9	6.71	2.19
DenseNet	77.36	4.97	2.17
DLA34	79.44	3.21	2.22
DPN68	80.16	3.63	2.23
EfficientNetV2	87.3	22.31	2.21
EfficientNet	77.1	7.07	2.18
MIXNet	78.9	8.43	2.17
MnasNet	75.2	2.88	2.16
FBNet	74.10	4.09	2.16
SPNASNet	74.96	3.57	2.18
TinyNet	59.9	7.89	2.18
GhostNet	75.7	3.24	2.18
HRNet	77.3	5.51	2.23
InceptionResNetV2	81.3	5.72	2.25
InceptionV3	78.8	5.65	2.29
NASNet-A	82.7	3.49	2.97
NFResNet	75.9	6.77	2.17
PNASNet	74.2	3.39	2.34
Res2Net	79.19	5.05	2.11
ResNeSt	83.9	5.47	2.2
ResNet	79.29	1.88	2.23
ReXNet	81.63	8.8	2.17
SelecSLS	78.4	4.53	2.16
SKNet	80.15	2.75	2.17
TResNet	80.8	17.17	2.2
VGG19	76.3	2.11	2.37
VoVNet	79.31	6.59	2.18
Xception	79.88	3.53	2.28

ImageNet performance is 77.9%, testing on ImageNet-A and ImageNet-O reveals a dramatic decline in performance. Yet, CSPNet reports fairly high scores in ImageNet-R, Stylized ImageNet, and ImageNet Sketch among CNNs, even comparable to Transformers. Another kind of neural net, DenseNet solves the vanishing-gradient issue, strengthens feature propagation, promotes feature reuse, and significantly lowers the number of parameters by connecting each layer to every other layer in a feed-forward fashion [29]. DenseNet’s ImageNet performance is 77.36%, yet it decreases drastically when evaluated on out-of-distribution datasets.

Deep Layer Aggregation (DLA) by Yu et al. iteratively and hierarchically combines the feature hierarchy to create networks with more accuracy and fewer parameters [76]. While DLA achieves 79.44% accuracy in ImageNet, it reports one of the lowest scores in ImageNet-A, O, and Stylized. DLA also achieves average scores in ImageNet-R and

Sketch. The state-of-the-art Residual Network (ResNet) and Densely Convolutional Network (DenseNet) feature reuse and new feature exploration systems are combined into one framework by the Dual Path Network (DPN). It employs a small model, incurs a little computational cost, and uses less GPU memory to achieve 80.16% accuracy on ImageNet data [8]. The model under-performs with ImageNet-A and O but achieves high accuracy of 11.04% on Stylized-ImageNet. A novel convolutional network architecture called EfficientNetV2 has improved parameter efficiency and faster training time. These models are created by combining scaling with training-aware neural architecture search to enhance training efficiency and speed jointly [59]. Another member of the EfficientNet family uses a simple yet very efficient compound coefficient to scale all depth, breadth, and resolution dimensions uniformly [58]. EfficientNetV2 achieves 87.3% on ImageNet and reports the highest score on ImageNet-A, R, Stylized, and Sketch among CNNs, with 22.31%, 52.97%, 23.3%, and 40.33% accuracy respectively. Further, its performance on ImageNet-R and Stylized is the second highest, and the performance on ImageNet-Sketch is the highest among all the tested models, showing that CNNs can be more robust than Transformers. EfficientNet achieves 77.1% on ImageNet, but it decreases dramatically on robustness datasets.

In a study of the effects of various kernel sizes for depthwise convolution, MIXNet finds that the single kernel size constraint is a problem for conventional depthwise convolution [58]. This was the driving force for the author’s suggestion of a mixed depthwise convolution, which incorporates several kernel sizes into a single convolution. MIXNet achieves the third-highest ImageNet-A score and fairly high performance on other datasets as well. Model latency is explicitly incorporated into the primary purpose of Tan et al. Mobile Neural Architecture Search (MnasNet) proposal so that the search can find a model that successfully balances accuracy and latency [57]. Wu et al. suggests a differentiable neural architecture search (DNAS) framework that employs gradient-based techniques to optimize ConvNet designs rather than defining and training each architecture independently as in earlier approaches. A family of models called FBNNets (Facebook-Berkeley-Nets), which DNAS identified, outperforms the most advanced models created manually and automatically [72]. In less than 4 hours, Single-Path NAS (SPNASNet), a novel differentiable Neural architecture search approach, can create hardware-efficient ConvNets and reach top-1 accuracy of 74.96% on ImageNet [50]. All MnasNet, FBNNet, and SPNASNet scores a high prediction accuracy on ImageNet, yet their performance all decreased on out-of-distribution datasets.

With the FLOPs limitation, TinyNet achieves 59.9% top-1 accuracy on ImageNet by breaking down neural architectures into a series of smaller models generated from

Table 2. Performance of convolution-based model on ImageNet-R, Stylized-ImageNet, and ImageNet-Sketch

Architecture	ImageNet-R	Stylized-ImageNet	ImageNet-Sketch
ConvNext	51.71	19.24	38.22
CSPNet	43.06	10.58	31.25
DenseNet	39.19	8.13	26.83
DLA34	35.63	7.61	23.68
DPN68	39.31	11.04	26.18
EfficientNetV2	52.97	23.3	40.33
EfficientNet	37.05	11.45	25.07
MIXNet	38.64	11.13	25.64
MnasNet	34.35	7.63	21.67
FBNet	34.25	7.66	21.49
SPNASNet	33.49	7.39	20.87
TinyNet	38.57	12.04	26.54
GhostNet	33.19	9.94	21.63
HRNet	38.27	9.05	25.98
InceptionResNetV2	40.68	13.27	27.99
InceptionV3	38.05	11.8	26.78
NASNet-A	30.11	11.52	8.72
NFResNet	43.41	11.19	31.48
PNASNet	31.21	9.07	16.03
Res2Net	38.72	8.85	26.47
ResNeSt	37.77	7.39	25.28
ResNet	28.93	3.59	16.84
ReXNet	37.5	11.04	26.94
SelecSLS	36.67	6.75	23.98
SKNet	36.94	9.25	24.88
TResNet	39.23	12.56	21.03
VGG19	28.58	3.03	17.94
VoVNet	35.05	8.5	23.84
Xception	33.52	9.33	18.26

EfficientNet-B0 [21]. Interestingly, TinyNet achieves one of the highest scores on ImageNet-A, R and Stylized, with 7.89%, 38.57%, and 12.04% respectively. Recent deep learning networks have high computational costs. GhostNet suggests a unique Ghost module to produce more feature maps from cheap operations based on a set of intrinsic feature maps [20]. By connecting high-to-low-resolution convolutions in parallel and continuously performing fusions across parallel convolutions, the high-resolution network (HRNet) designed for human pose estimation preserves high-resolution representations throughout the entire process [53, 54]. Both GhostNet and HRNet achieves similarly high accuracy on ImageNet, yet HRNet slightly outperforms GhostNet on all of the datasets except Stylized ImageNet.

The Inception architecture and residual connections are combined in InceptionResNetV2, which dramatically enhances recognition performance and achieves 81.3% top-

1 accuracy in ImageNet [55]. With the help of aggressive regularization and properly factorized convolutions, InceptionV3 obtained 78.8% top-1 accuracy in ImageNet [56]. Both models demonstrate high performance among CNNs, especially InceptionResNetV2 achieves the second highest top-1 accuracy on Imagenet-R (40.68%) and Stylized (13.27%), comparable to Transformers.

The idea of NASNet-A is to find an architectural building block on a small dataset and then transfer it to a larger dataset [79]. A brand-new technique called Progressive Neural Architecture Search (PNASNet) is more effective than current state-of-the-art techniques based on reinforcement learning, and evolutionary algorithms for learning the structure of convolutional neural networks (CNNs) [37]. NASNet achieves one of the highest scores of ImageNet with 82.7% and also reports the highest AUPR of 2.97 on ImageNet-O among convolution-based models and is the third highest in all of the tested models on ImageNet-O. Although PNASNet achieves 75.9% on ImageNet, it outperforms NASNet on ImageNet-R and Sketch.

The milestone architecture ResNet has a number of variations, and amongst NResNet, Res2Net, ResNeSt, ResNet, and ReXNet are evaluated. To build highly effective ResNets without activation normalization layers, NResNet presents a straightforward collection of analysis tools to quantify signal propagation on the forward pass [5]. Gao et al. suggest Res2Net as a unique CNN building block by creating hierarchical residual-like connections within a single residual block [16]. ResNeSt is a modularized architecture that uses channel-wise attention to focus on various network branches to take advantage of their success in capturing cross-feature interactions and learning various representations [78]. The state-of-the-art computer vision model, ResNet, uses a residual learning framework to make it easier to train far deeper networks than previously employed [24]. RexNet is a simple yet efficient channel setup that achieves 81.63% top-1 accuracy on ImageNet when parameterized by the layer index [19]. All of the models achieve more than 75% top-1 accuracy on ImageNet, though they did not perform well on ImageNet-A and O. On ImageNet-R, Stylized, and Sketch datasets, all of them except ResNet achieve high scores. Therefore, ResNet is the least robust model among its variations. Also NResNet achieves the highest accuracy on ImageNet-R and Sketch with 43.41% and 31.48%.

SelecSLS improves information flow by utilizing new selective long and short-range skip connections, enabling a significantly faster network without sacrificing accuracy [43]. It achieves 78.4% top-1 accuracy on ImageNet. A dynamic selection technique in CNN's called selective kernel networks (SKNet) enables each neuron to adaptively change the size of its receptive field based on various scales of input data. Selective Kernel (SK) units are a type of building block that fuse several branches with various ker-

nel sizes utilizing softmax attention directed by the information in these branches [34]. SKNet achieves 80.15% accuracy on ImageNet. Yet, both SelecSLS and SKNet decrease dramatically on ImageNet -A, O, R, and others.

TResNet is a high-performance GPU-dedicated architecture that outperforms earlier ConvNets in terms of accuracy and efficiency [48]. TResNet achieves fairly high accuracy of 80.8% on ImageNet, and it reports 17.17% accuracy on ImageNet-A and 39.23% on ImageNet-R, which are one of the highest scores among CNNs.

VGGNet is a deep convolutional neural network that achieves 76.3% top-1 accuracy in ImageNet [49]. However, VGGNet's performance on out-of-distribution robustness is below expectation, reporting the lowest Stylized ImageNet accuracy.

CenterMask, a straightforward yet effective anchor-free instance segmentation method for VoVNet, combines two successful strategies: effective Squeeze-Excitation (eSE), which addresses the issue of channel information loss associated with original Squeeze-Excitation, and residual connection, which addresses the optimization issue of larger VoVNet [33]. In convolutional neural networks, Inception modules are interpreted by Xception as a transitional stage between the depthwise separable convolution operation, and ordinary convolution [10]. While VoVNet and Xception achieve more than 79% top-1 accuracy on ImageNet, their metric scores decrease on robust image classification.

3.2. Attention Mechanism

A self-supervised vision representation methodology called Bidirectional Encoder representation from Image Transformers (BEiT) tokenizes the original image into visual tokens, randomly masks some image patches, and decodes them into the main Transformer [3]. Although BEiT achieves 82.9% accuracy on ImageNet, it's accuracy on ImageNet-A, R, Stylized, and Sketch are one of the lowest, even lower than convolution-based models. Yet, it reports AUPR of 3.46 on ImageNet-O dataset, which is the second highest among all the models.

CaiT is a deeper transformer network for image classification that was created in the style of encoder/decoder architecture. Two improvements to the transformer architecture made by the author greatly increase the deep transformers' accuracy [64]. Using co-scale and Conv-attentional principles, Co-scale Conv-attentional image Transformers (CoaT) is a Transformer-based image classification [73]. On ImageNet, CoaT achieves an accuracy of about 81.9%. In Chen et al. CrossViT approach, image patches (i.e., tokens in a transformer) of various sizes are combined to create stronger image features using a dual-branch transformer [7]. CaiT, CoaT, and CrossViT all reports high ImageNet accuracy and fair performance on out-of-distribution

Table 3. Performance of attention-based vision model on ImageNet, ImageNet-A, and ImageNet-O

Architecture	ImageNet	ImageNet-A	ImageNet-O
BEiT	82.9	3.92	3.46
CaiT	86.5	34.4	2.2
CoaT	81.9	16.68	2.2
CrossViT	81.5	31.8	2.2
DeiT	81.8	27.85	2.21
DeiT3	83.1	40.12	2.22
EfficientFormer	79.2	13.93	2.24
GCViT	83.4	42.71	2.2
MaxViT	86.5	23.32	2.2
MobileViT	78.4	0.33	3.92
MViTv2	88.8	43.09	2.24
NesT	81.5	34.15	2.22
PiT	82.0	33.89	2.2
PVT V2	82.0	4.05	2.18
Swin	87.3	39.41	2.19
Swin V2	84.0	31.59	2.21
TNT	81.5	17.17	2.2
TwinsPcPvt	83.2	30.11	2.18
Visformer	78.6	26.03	2.21
ViT	85.17	11.25	2.61
VOLO	87.1	41.03	2.23
XCiT	83.4	40.69	2.2

datasets. Yet, CoaT achieves only half of top-1 accuracy on ImageNet-A, compared to CaiT and CrossViT.

DeiT is a transformer without convolution that presents a teacher-student approach unique to transformers. It makes use of a distillation token to make sure that the student pays close attention to the teacher [62]. DeiT3 revisits the supervised training of ViTs and introduces a new straightforward data-augmentation method that uses just three augmentations, moving it closer to the self-supervised learning method [63]. They achieve 81.8% and 83.1% accuracy on ImageNet respectively. DeiT3 reports the highest ImageNet-R and Stylized top-1 accuracy among all the models, with 53.63% and 25.45% respectively.

As a design paradigm, EfficientFormer introduces a dimension-consistent pure transformer (without MobileNet blocks) and uses latency-driven slimming to produce many final models under EfficientFormer. The author demonstrates how EfficientFormer may shorten inference times and how well-designed transformers can achieve extremely low latency on mobile devices while achieving top performance [36]. While EfficientFormer reports 79.2% accuracy on ImageNet, it does not perform well on out-of-distribution samples.

Hatamizadeh et al. proposed a global context vision transformer (GCViT), which improves parameter and compute usage for computer vision tasks that rely on global

Table 4. Performance of attention-based vision model on ImageNet-R, Stylized-ImageNet, and ImageNet-Sketch

Architecture	ImageNet -R	Stylized -ImageNet	ImageNet -Sketch
BEiT	10.25	2.05	2.05
CaiT	49.95	19.48	36.03
CoaT	42.81	14.27	28.12
CrossViT	47.1	18.51	33.49
DeiT	45.36	17.99	32.35
DeiT3	53.63	25.45	40.06
EfficientFormer	43.4	12.21	30.91
GCViT	49.57	17.81	36.29
MaxViT	47.8	17.75	35.19
MobileViT	0.57	0.12	0.11
MViTv2	51.89	19.16	38.11
NesT	46.57	18.27	33.36
PiT	44.37	16.4	32.7
PVT V2	44.21	10.02	21.72
Swin	48.64	18.36	34.37
Swin V2	43.76	13.54	30.99
TNT	39.23	12.56	21.03
TwinsPcPvt	45.92	15.97	32.57
Visformer	43.39	13.58	30.11
ViT	38.42	14.37	17.36
VOLO	48.53	17.74	36.11
XCiT	46.51	15.28	34.53

context self-attention modules combined with conventional local self-attention to accurately yet efficiently model both long and short-range spatial interactions as alternatives to complex operations like an attention mask or local windows shifting [23]. GCViT achieves the second highest ImageNet-A accuracy of 42.71% and the third highest ImageNet-R and Sketch accuracy of 49.57% and 36.29% among Transformers.

The multi-axis attention paradigm, called MaxViT, is effective and scalable and has two components: blocked local and dilated global attention [65]. It obtains 86.5% top-1 accuracy on ImageNet. MobileViT, a general-purpose vision transformer that is lightweight and mobile-friendly, obtains 78.4% accuracy [44]. MobileViT’s performance on ImageNet -A, R, Stylized, and Sketch are the lowest, yet it scores AUPR of 3.92 on ImageNet-O, the highest score among all the models. MaxViT outperforms MobileViT on robustness datasets.

A unified architecture for image and video classification called Multiscale Vision Transformer (MViT2) uses residual pooling connections and decomposed relative positional embeddings [35]. On both ImageNet and small datasets like CIFAR, Zhang et al. Nested Hierarchical Transformer (NesT) converges faster and needs less training data to achieve good generalization. NesT results in a robust de-

coder eight times faster when applying key concepts to image generation than earlier transformer-based generators [78]. With the incorporation of a pooling layer, the pooling-based Vision Transformer (PiT) improves model capability, and generalization performance in comparison to ViT [27]. MViT2 obtains the highest ImageNet score with 88.8% accuracy, and NesT and PiT also obtain more than 81% accuracy. MViT2 reports the second highest ImageNet-R score with 51.89% top-1 accuracy and fairly high scores on out-of-distribution classification. NesT and PiT also performs well on various datasets.

With the addition of a linear complexity attention layer, overlapping patch embedding, and a convolutional feed-forward network, PVTv2 [70] is an improved version of the original Pyramid Vision Transformer (PVTv1) [69]. Although it obtains 81% ImageNet score, it decrease drastically on robustness datasets, only obtaining 4.05% ImageNet-A accuracy.

Swin is a hierarchical transformer whose representation is computed via shifted windows. This method increases performance by restricting self-attention computation to non-overlapping local windows while allowing a cross-window connection [39]. SwinV2 propose a residual-post-norm method coupled with cosine attention to enhance training stability, a log-spaced continuous position bias method to successfully transfer models pre-trained using low-resolution images to downstream tasks with high-resolution input, and a self-supervised pretraining method, SimMIM, to lessen the requirement for large labeled image datasets [38]. They both reports 87.3% and 84% accuracy on ImageNet. Interestingly, Swin outperforms SwinV2 on all of the out-of-distribution datasets.

TNT (Transformer iN Transformer) is a novel neural architecture that encodes input data into powerful features using the attention mechanism [22]. TwinsPcPvt explores the design of spatial attention and shows that a well-developed yet simple spatial attention mechanism outperforms state-of-the-art techniques [11]. They achieve 81.5% and 83.2% top-1 accuracy respectively. Visformer, a Transformer-based visual recognition model, achieves 78.6% top-1 accuracy on ImageNet [9]. TwinsPcPvt outperforms other two models on other datasets, and TNT does not perform well on ImageNet-A and Sketch.

Vision Transformer (ViT) proposed by Dosovitskiy et al., is a pure transformer that can be applied directly to sequences of picture patches and performs very well on image classification tasks [14, 51]. It achieves 85.17% top-1 accuracy on ImageNet, but its performance on robustness datasets is not satisfactory. It scores only 17.36% on ImageNet-Sketch, which is even lower than most of CNNs, and 11.25% accuracy on ImageNet-A, one of the lowest score among Transformers.

Yuan et al. introduce novel viewpoint attention and

Table 5. Performance of a combination of CNN and attention-based vision models on ImageNet, ImageNet-A, and ImageNet-O

Architecture	ImageNet	ImageNet -A	ImageNet -O
ConViT	81.3	29.69	2.21
EdgeNeXt	71.2	21.83	2.23
LeViT	80.0	11.51	2.22

Table 6. Performance of a combination of CNN and attention-based vision models on ImageNet-R, Stylized-ImageNet, and ImageNet-Sketch

Architecture	ImageNet -R	Stylized -ImageNet	ImageNet -Sketch
ConViT	48.79	19.81	35.53
EdgeNeXt	51.04	16.26	37.13
LeViT	40.28	15.59	26.39

present Vision Outlooker (VOLO), a basic and universal neural network architecture [77]. XCiT is a transposed version of self-attention that operates across feature channels rather than tokens, where the interactions are based on the cross-covariance matrix between keys and queries [1]. Both models achieve high scores on most of the datasets. VOLO obtains the second-highest ImageNet-A top-1 accuracy, along with the third-highest ImageNet-Sketch top-1 accuracy among Transformers. XCiT also reports the third highest ImageNet-A accuracy.

3.3. Hybrid (combination of convolution and attention) Mechanism

ConViT is a gated positional self-attention (GPSA) proposed by d’Ascoli et al., a type of positional self-attention that can be equipped with a ”soft” convolutional inductive bias [15]. EdgeNeXt is a hybrid architecture that combines the strengths of both the CNN and Transformer models. The author introduces the split depth-wise transpose attention (STDA) encoder, which divides input tensors into numerous channel groups and use depth-wise convolution and self attention across channel dimensions to implicitly extend the receptive field and encode multi-scale features [41]. LeViT is a hybrid Vision Transformer in ConvNet’s guise that optimizes the trade-off between accuracy and efficiency in a high-speed regime [18]. Each model obtains 81.3%, 71.2%, and 80% accuracy on ImageNet. While EdgeNeXt achieves the lowest ImageNet accuracy among the three, it performs well on ImageNet-O, R, and Sketch. On the other hand, LeViT reports low scores on out-of-distribution samples despite its performance on ImageNet.

Table 7. Performance of a combination of other (not CNN or attention-based) models on ImageNet, ImageNet-A, and ImageNet-O

Architecture	ImageNet	ImageNet -A	ImageNet -O
MLPMixer	76.44	5.79	2.25
MobileNetV3	75.77	4.59	2.2
RegNet	80.25	26.48	2.17
Sequencer	84.6	35.36	2.18

Table 8. Performance of a combination of other (not CNN or attention-based) models on ImageNet-R, Stylized-ImageNet, and ImageNet-Sketch

Architecture	ImageNet -R	Stylized -ImageNet	ImageNet -Sketch
MLPMixer	32.75	10.04	19.32
MobileNetV3	35.11	10.85	22.95
RegNet	44.74	11.88	32.93
Sequencer	48.56	16.74	35.87

3.4. Multi-layer Perceptron Mechanism

MLP-Mixer, a multi-layer perceptron (MLP)-based architecture with two types of layers: one with MLPs applied individually to image patches (i.e. "mixing" per-location characteristics) and one with MLPs applied across patches (i.e. "mixing" spatial information) [61]. MLP-Mixer obtains 76.44% top-1 accuracy on ImageNet, but its performance decreases on other datasets. It only scores 5.79% on ImageNet-A and 10.04% on Style, lower than most of CNNs or Transformers.

3.5. Complementary Search Mechanism

MobileNetV3 is based on a complimentary search technique as well as a novel architecture design customized to mobile phone CPUs via a mix of hardware-aware network architecture search (NAS) augmented by the NetAdapt algorithm and then improved through novel architecture developments [28]. It obtains 75.77% accuracy on ImageNet, but similarly to MLP-Mixer, it only achieves 4.59% and 10.85% on ImageNet-A and Style.

3.6. Others Mechanism

RegNet is a two-dimensional design space made of simple, regular networks [47]. Sequencer is a unique and competitive architecture representing long-term dependencies using LSTMs rather than self-attention layers [60]. Both RegNet and Sequencer obtain more than 80% top-1 accuracy on ImageNet, and demonstrate high score on robustness datasets. Especially, Sequencer outperforms most of the convolution-based and attention-based models.

4. Discussion and Conclusion

Vision transformers are becoming state-of-the-art image recognition tasks, and researchers are investigating their robustness compared to CNNs. Recent studies indicated that transformers are more robust than CNN; however, our observations indicate that the analysis is not fair and not particularly deep because the available literature only considers one or two basic models for comparison from each family. However, we offered comprehensive robustness research comparing 58 computer vision models not limited to convolution or attention families. We discover that if CNN is given the same training scenario as the transformer, it is just as resilient. Among all the 58 models, DeiT3 performs best in terms of robustness due to its teacher-student approach. ConvNext, a newly developed convolution-based model, outperforms out-of-distribution data. Our research also reveals that the convolution and attention model performs similarly to transformers. Aside from convolution and attention-based models, the sequencer (sequence-based model) is robust. On out-of-distribution data, base versions of state-of-the-art models like ResNet, VGG, and ViT perform poorly. This work provides a thorough robustness analysis of almost each available state-of-the-art computer vision model based on almost all available robustness data. In the future, we hope to look at the behavior of neural networks when they classify data from distributions. Looking at the problem from a causal standpoint, mainly studying the spurious correlation between non-robust features, may be helpful in designing a robust computer vision model with generalization capabilities.

References

- [1] Alaaeldin Ali, Hugo Touvron, Mathilde Caron, Piotr Bojanowski, Matthijs Douze, Armand Joulin, Ivan Laptev, Natalia Neverova, Gabriel Synnaeve, Jakob Verbeek, et al. Xcit: Cross-covariance image transformers. *Advances in neural information processing systems*, 34:20014–20027, 2021. 7
- [2] Yutong Bai, Jieru Mei, Alan L Yuille, and Cihang Xie. Are transformers more robust than cnns? *Advances in Neural Information Processing Systems*, 34:26831–26843, 2021. 1
- [3] Hangbo Bao, Li Dong, and Furu Wei. Beit: Bert pre-training of image transformers. *arXiv preprint arXiv:2106.08254*, 2021. 5
- [4] Srinadh Bhojanapalli, Ayan Chakrabarti, Daniel Glasner, Daliang Li, Thomas Unterthiner, and Andreas Veit. Understanding robustness of transformers for image classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10231–10241, 2021. 1
- [5] Andrew Brock, Soham De, and Samuel L Smith. Characterizing signal propagation to close the performance gap in unnormalized resnets. *arXiv preprint arXiv:2101.08692*, 2021. 5
- [6] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakan-

- tan, Pranav Shyam, Girish Sastry, Amanda Askill, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020. [1](#)
- [7] Chun-Fu Richard Chen, Quanfu Fan, and Rameswar Panda. Crossvit: Cross-attention multi-scale vision transformer for image classification. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 357–366, 2021. [5](#)
- [8] Yunpeng Chen, Jianan Li, Huaxin Xiao, Xiaojie Jin, Shuicheng Yan, and Jiashi Feng. Dual path networks. *Advances in neural information processing systems*, 30, 2017. [4](#)
- [9] Zhengsu Chen, Lingxi Xie, Jianwei Niu, Xuefeng Liu, Longhui Wei, and Qi Tian. Visformer: The vision-friendly transformer. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 589–598, 2021. [7](#)
- [10] François Chollet. Xception: Deep learning with depthwise separable convolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1251–1258, 2017. [5](#)
- [11] Xiangxiang Chu, Zhi Tian, Yuqing Wang, Bo Zhang, Haibing Ren, Xiaolin Wei, Huaxia Xia, and Chunhua Shen. Twins: Revisiting the design of spatial attention in vision transformers. *Advances in Neural Information Processing Systems*, 34:9355–9366, 2021. [7](#)
- [12] Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc V Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. *arXiv preprint arXiv:1901.02860*, 2019. [1](#)
- [13] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018. [1](#)
- [14] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020. [1](#), [3](#), [7](#)
- [15] Stéphane d’Ascoli, Hugo Touvron, Matthew L Leavitt, Ari S Morcos, Giulio Biroli, and Levent Sagun. Convit: Improving vision transformers with soft convolutional inductive biases. In *International Conference on Machine Learning*, pages 2286–2296. PMLR, 2021. [3](#), [7](#)
- [16] Shang-Hua Gao, Ming-Ming Cheng, Kai Zhao, Xin-Yu Zhang, Ming-Hsuan Yang, and Philip Torr. Res2net: A new multi-scale backbone architecture. *IEEE transactions on pattern analysis and machine intelligence*, 43(2):652–662, 2019. [5](#)
- [17] Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. Imagenet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. In *International Conference on Learning Representations*, 2019. [3](#)
- [18] Benjamin Graham, Alaeldin El-Nouby, Hugo Touvron, Pierre Stock, Armand Joulin, Hervé Jégou, and Matthijs Douze. Levit: a vision transformer in convnet’s clothing for faster inference. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 12259–12269, 2021. [7](#)
- [19] Dongyoon Han, Sangdoon Yun, Byeongho Heo, and YoungJoon Yoo. Rethinking channel dimensions for efficient model design. In *Proceedings of the IEEE/CVF conference on Computer Vision and Pattern Recognition*, pages 732–741, 2021. [5](#)
- [20] Kai Han, Yunhe Wang, Qi Tian, Jianyuan Guo, Chunjing Xu, and Chang Xu. Ghostnet: More features from cheap operations. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1580–1589, 2020. [4](#)
- [21] Kai Han, Yunhe Wang, Qiulin Zhang, Wei Zhang, Chunjing Xu, and Tong Zhang. Model rubik’s cube: Twisting resolution, depth and width for tinynets. *Advances in Neural Information Processing Systems*, 33:19353–19364, 2020. [4](#)
- [22] Kai Han, An Xiao, Enhua Wu, Jianyuan Guo, Chunjing Xu, and Yunhe Wang. Transformer in transformer. *Advances in Neural Information Processing Systems*, 34:15908–15919, 2021. [7](#)
- [23] Ali Hatamizadeh, Hongxu Yin, Jan Kautz, and Pavlo Molchanov. Global context vision transformers. *arXiv preprint arXiv:2206.09959*, 2022. [6](#)
- [24] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016. [3](#), [5](#)
- [25] Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, et al. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 8340–8349, 2021. [2](#)
- [26] Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15262–15271, 2021. [2](#), [3](#)
- [27] Byeongho Heo, Sangdoon Yun, Dongyoon Han, Sanghyuk Chun, Junsuk Choe, and Seong Joon Oh. Rethinking spatial dimensions of vision transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 11936–11945, 2021. [7](#)
- [28] Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, et al. Searching for mobilenetv3. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 1314–1324, 2019. [3](#), [8](#)
- [29] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4700–4708, 2017. [3](#)
- [30] Salman Khan, Muzammal Naseer, Munawar Hayat, Syed Waqas Zamir, Fahad Shahbaz Khan, and Mubarak Shah. Transformers in vision: A survey. *ACM computing surveys (CSUR)*, 54(10s):1–41, 2022. [1](#)

- [31] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60(6):84–90, 2017. [3](#)
- [32] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998. [3](#)
- [33] Youngwan Lee and Jongyoul Park. Centermask: Real-time anchor-free instance segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 13906–13915, 2020. [5](#)
- [34] Xiang Li, Wenhai Wang, Xiaolin Hu, and Jian Yang. Selective kernel networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 510–519, 2019. [5](#)
- [35] Yanghao Li, Chao-Yuan Wu, Haoqi Fan, Karttikeya Mangalam, Bo Xiong, Jitendra Malik, and Christoph Feichtenhofer. Mvitv2: Improved multiscale vision transformers for classification and detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4804–4814, 2022. [6](#)
- [36] Yanyu Li, Geng Yuan, Yang Wen, Eric Hu, Georgios Evangelidis, Sergey Tulyakov, Yanzhi Wang, and Jian Ren. Efficientformer: Vision transformers at mobilenet speed. *arXiv preprint arXiv:2206.01191*, 2022. [6](#)
- [37] Chenxi Liu, Barret Zoph, Maxim Neumann, Jonathon Shlens, Wei Hua, Li-Jia Li, Li Fei-Fei, Alan Yuille, Jonathan Huang, and Kevin Murphy. Progressive neural architecture search. In *Proceedings of the European conference on computer vision (ECCV)*, pages 19–34, 2018. [5](#)
- [38] Ze Liu, Han Hu, Yutong Lin, Zhuliang Yao, Zhenda Xie, Yixuan Wei, Jia Ning, Yue Cao, Zheng Zhang, Li Dong, et al. Swin transformer v2: Scaling up capacity and resolution. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12009–12019, 2022. [7](#)
- [39] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10012–10022, 2021. [7](#)
- [40] Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie. A convnet for the 2020s. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11976–11986, 2022. [3](#)
- [41] Muhammad Maaz, Abdelrahman Shaker, Hisham Cholakkal, Salman Khan, Syed Waqas Zamir, Rao Muhammad Anwer, and Fahad Shahbaz Khan. Edgenext: efficiently amalgamated cnn-transformer architecture for mobile vision applications. *arXiv preprint arXiv:2206.10589*, 2022. [7](#)
- [42] Kaleel Mahmood, Rigel Mahmood, and Marten Van Dijk. On the robustness of vision transformers to adversarial examples. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 7838–7847, 2021. [1](#)
- [43] Dushyant Mehta, Oleksandr Sotnychenko, Franziska Mueller, Weipeng Xu, Mohamed Elgharib, Pascal Fua, Hans-Peter Seidel, Helge Rhodin, Gerard Pons-Moll, and Christian Theobalt. Xnect: Real-time multi-person 3d motion capture with a single rgb camera. *Acm Transactions On Graphics (TOG)*, 39(4):82–1, 2020. [5](#)
- [44] Sachin Mehta and Mohammad Rastegari. Mobilevit: lightweight, general-purpose, and mobile-friendly vision transformer. *arXiv preprint arXiv:2110.02178*, 2021. [6](#)
- [45] Muhammad Muzammal Naseer, Kanchana Ranasinghe, Salman H Khan, Munawar Hayat, Fahad Shahbaz Khan, and Ming-Hsuan Yang. Intriguing properties of vision transformers. *Advances in Neural Information Processing Systems*, 34:23296–23308, 2021. [1](#)
- [46] Sayak Paul and Pin-Yu Chen. Vision transformers are robust learners. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36(2), pages 2071–2081, 2022. [1](#)
- [47] Ilija Radosavovic, Raj Prateek Kosaraju, Ross Girshick, Kaiming He, and Piotr Dollár. Designing network design spaces. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10428–10436, 2020. [3](#), [8](#)
- [48] Tal Ridnik, Hussam Lawen, Asaf Noy, Emanuel Ben Baruch, Gilad Sharir, and Itamar Friedman. Tresnet: High performance gpu-dedicated architecture. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1400–1409, 2021. [5](#)
- [49] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014. [5](#)
- [50] Dimitrios Stamoulis, Ruizhou Ding, Di Wang, Dimitrios Lymberopoulos, Bodhi Priyantha, Jie Liu, and Diana Marculescu. Single-path nas: Designing hardware-efficient convnets in less than 4 hours. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 481–497. Springer, 2019. [4](#)
- [51] Andreas Steiner, Alexander Kolesnikov, Xiaohua Zhai, Ross Wightman, Jakob Uszkoreit, and Lucas Beyer. How to train your vit? data, augmentation, and regularization in vision transformers. *arXiv preprint arXiv:2106.10270*, 2021. [7](#)
- [52] Chen Sun, Abhinav Shrivastava, Saurabh Singh, and Abhinav Gupta. Revisiting unreasonable effectiveness of data in deep learning era. In *Proceedings of the IEEE international conference on computer vision*, pages 843–852, 2017. [1](#)
- [53] Ke Sun, Bin Xiao, Dong Liu, and Jingdong Wang. Deep high-resolution representation learning for human pose estimation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5693–5703, 2019. [4](#)
- [54] Ke Sun, Yang Zhao, Borui Jiang, Tianheng Cheng, Bin Xiao, Dong Liu, Yadong Mu, Xinggang Wang, Wenyu Liu, and Jingdong Wang. High-resolution representations for labeling pixels and regions. *arXiv preprint arXiv:1904.04514*, 2019. [4](#)
- [55] Christian Szegedy, Sergey Ioffe, Vincent Vanhoucke, and Alexander A Alemi. Inception-v4, inception-resnet and the impact of residual connections on learning. In *Thirty-first AAAI conference on artificial intelligence*, 2017. [5](#)
- [56] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception archi-

- ecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2818–2826, 2016. 5
- [57] Mingxing Tan, Bo Chen, Ruoming Pang, Vijay Vasudevan, Mark Sandler, Andrew Howard, and Quoc V Le. Mnasnet: Platform-aware neural architecture search for mobile. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2820–2828, 2019. 4
- [58] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pages 6105–6114. PMLR, 2019. 4
- [59] Mingxing Tan and Quoc Le. Efficientnetv2: Smaller models and faster training. In *International Conference on Machine Learning*, pages 10096–10106. PMLR, 2021. 4
- [60] Yuki Tatsunami and Masato Taki. Sequencer: Deep lstm for image classification. *arXiv preprint arXiv:2205.01972*, 2022. 3, 8
- [61] Ilya O Tolstikhin, Neil Houlsby, Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Thomas Unterthiner, Jessica Yung, Andreas Steiner, Daniel Keysers, Jakob Uszkoreit, et al. Mlp-mixer: An all-mlp architecture for vision. *Advances in Neural Information Processing Systems*, 34:24261–24272, 2021. 3, 8
- [62] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pages 10347–10357. PMLR, 2021. 2, 6
- [63] Hugo Touvron, Matthieu Cord, and Hervé Jégou. Deit iii: Revenge of the vit. *arXiv preprint arXiv:2204.07118*, 2022. 6
- [64] Hugo Touvron, Matthieu Cord, Alexandre Sablayrolles, Gabriel Synnaeve, and Hervé Jégou. Going deeper with image transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 32–42, 2021. 1, 5
- [65] Zhengzhong Tu, Hossein Talebi, Han Zhang, Feng Yang, Peyman Milanfar, Alan Bovik, and Yinxiao Li. Maxvit: Multi-axis vision transformer. *arXiv preprint arXiv:2204.01697*, 2022. 6
- [66] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017. 1
- [67] Chien-Yao Wang, Hong-Yuan Mark Liao, Yueh-Hua Wu, Ping-Yang Chen, Jun-Wei Hsieh, and I-Hau Yeh. Cspnet: A new backbone that can enhance learning capability of cnn. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops*, pages 390–391, 2020. 3
- [68] Haohan Wang, Songwei Ge, Zachary Lipton, and Eric P Xing. Learning robust global representations by penalizing local predictive power. In *Advances in Neural Information Processing Systems*, pages 10506–10518, 2019. 3
- [69] Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 568–578, 2021. 7
- [70] Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pvt v2: Improved baselines with pyramid vision transformer. *Computational Visual Media*, 8(3):415–424, 2022. 7
- [71] Ross Wightman. Pytorch image models. <https://github.com/rwightman/pytorch-image-models>, 2019. 2
- [72] Bichen Wu, Xiaoliang Dai, Peizhao Zhang, Yanghan Wang, Fei Sun, Yiming Wu, Yuandong Tian, Peter Vajda, Yangqing Jia, and Kurt Keutzer. Fbnet: Hardware-aware efficient convnet design via differentiable neural architecture search. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10734–10742, 2019. 4
- [73] Weijian Xu, Yifan Xu, Tyler Chang, and Zhuowen Tu. Co-scale conv-attentional image transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9981–9990, 2021. 5
- [74] Fuzhao Xue, Ziji Shi, Futao Wei, Yuxuan Lou, Yong Liu, and Yang You. Go wider instead of deeper. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36(8), pages 8779–8787, 2022. 1
- [75] Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *Advances in neural information processing systems*, 32, 2019. 1
- [76] Fisher Yu, Dequan Wang, Evan Shelhamer, and Trevor Darrell. Deep layer aggregation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2403–2412, 2018. 3
- [77] Li Yuan, Qibin Hou, Zihang Jiang, Jiashi Feng, and Shuicheng Yan. Volo: Vision outlooker for visual recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2022. 7
- [78] Zizhao Zhang, Han Zhang, Long Zhao, Ting Chen, Sercan Ö Arik, and Tomas Pfister. Nested hierarchical transformer: Towards accurate, data-efficient and interpretable visual understanding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36(3), pages 3417–3425, 2022. 5, 7
- [79] Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V Le. Learning transferable architectures for scalable image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 8697–8710, 2018. 5