Understanding the Effectiveness of Very Large Language Models on Dialog Evaluation

Jessica Huynh, Cathy Jiao, Prakhar Gupta, Shikib Mehri, Payal Bajaj, Vishrav Chaudhary, Maxine Eskenazi

Abstract Language models have steadily increased in size over the past few years. They achieve a high level of performance on various natural language processing (NLP) tasks such as question answering and summarization. Large language models (LLMs) have been used for generation and can now output human-like text. Due to this, there are other downstream tasks in the realm of dialog that can now harness the LLMs' language understanding capabilities. Dialog evaluation is one task that this paper will explore. It concentrates on prompting with LLMs: BLOOM, OPT, GPT-3, Flan-T5, InstructDial and TNLGv2. The paper shows that the choice of datasets used for training a model contributes to how well it performs on a task as well as on how the prompt should be structured. Specifically, the more diverse and relevant the group of datasets that a model is trained on, the better dialog evaluation performs. This paper also investigates how the number of examples in the prompt and the type of example selection used affect the model's performance.

Jessica Huynh

Carnegie Mellon University, e-mail: jhuynh@cs.cmu.edu

Cathy Jiac

Carnegie Mellon University, e-mail: cljiao@cs.cmu.edu

Prakhar Gunta

Carnegie Mellon University, e-mail: prakharg@cs.cmu.edu

Shikib Mehri

Amazon, e-mail: asmehri@amazon.com (work done while at Carnegie Mellon University)

Payal Bajaj

Microsoft Turing, e-mail: pabajaj@microsoft.com

Vishrav Chaudhary

Microsoft Turing, e-mail: vchaudhary@microsoft.com

Maxine Eskenazi

Carnegie Mellon University, e-mail: max@cs.cmu.edu

1 Introduction

In recent years, language models such as GPT-3 [5] have grown larger, and their performance on downstream natural language processing (NLP) tasks has significantly improved in low-resource settings where only a few instances per task are available (few-shot). The larger these models are, the higher their performances trend on tasks such as language generation and evaluation [39]. They can generate coherent, fluent and interesting responses. However, they can also produce responses that are repetitive and un-engaging [29], in addition to being hard to control. Dialog evaluation is the task of assessing the quality of responses generated by dialog models in terms of properties like those mentioned above. However, one significant impediment for open-domain dialog generation research is the lack of meaningful automatic metrics for open-domain dialog evaluation. Standard language generation metrics have been shown to be ineffective for dialog evaluation [11], a large part of which is because conversations can be followed by multiple valid responses. Standard automatic metrics (e.g. BLEU [24]), which use references for evaluation, cannot deal with this quality, known as the *one-to-many* response problem. Many recently introduced automatic metrics for dialog evaluation [21, 12] have attained increasingly stronger correlations with human judgment. Since human dialog evaluation typically measures multiple fine-grained properties (e.g. appropriate, interesting, consistent), automatic evaluation metrics should be expected to do the same. This paper explores several fine-grained metrics that are measured both at turn-level (i.e. relevance and fluency), and dialog-level (i.e. consistency and coherence).

Automatic dialog evaluation continues to be an evolving topic, but with fine-grained metrics and definitions varying across different human-annotated datasets [22, 46], it is important to be able to create reasonable automatic metrics with limited data. Large language models (LLMs) that have been pre-trained on large-scale datasets are able to perform zero and few-shot inference [26, 32], and they have exhibited good reasoning skills [5, 39] in addition to having implicitly learned some notion of dialog quality [21]. This makes them suitable for open-domain dialog evaluation in zero-shot and extreme few-shot settings. While there have been a few attempts to use LLMs for dialog evaluation [36], there has not, to our knowledge, been a systematic study of LLMs for this task. This paper explores several aspects of LLM use in dialog evaluation: the effect of model type and size and the choice of training data as well as the use of in-context examples for dialog evaluation (the number and quality of the examples used). The experiments herein employ benchmarks to test both how well LLMs can be used for fine-grained evaluation, and how generalizable the models' performance is across multiple domains and datasets.

2 Related Work

2.1 LLMs

Several LLMs have been released recently: T5 [27], GPT-3 [5], BLOOM [4], OPT [42], and TNLGv2 [34]. The following models, the sizes of which are shown in Figure 1, are explored here:

- T5, trained on the 750B Colossal Clean Crawled Corpus (C4) contains heuristically cleaned natural language English text from the web. Specific models considered are:
 - Flan-T5 [8], T5 fine-tuned on 1836 tasks, including dialog tasks and data.
 - InstructDial [13], T5 fine-tuned specifically on 48 dialog tasks.
- GPT-3 includes a 570B filtered CommonCrawl corpus [27] in addition to Web-Text [26], Books1, Books2, and Wikipedia [16].
 - InstructGPT (text-davinci-002) [23], GPT-3 fine-tuned with a prompting dataset and 175B parameters.
- BLOOM was trained on 46 languages and 13 programming languages with a multilingual focus.
- OPT contains data from the RoBERTa corpus [18], the Pile [9], and PushShift.io Reddit [2, 29].
- TNLGv2 is trained on a subset of the Pile (notably excluding corpora classified as having natural dialog), two CommonCrawl snapshots [27], RealNews [40], and CC-Stories [37].




Fig. 1 Large Language Models, comparison of select approximate sizes

As the number of parameters in these models increases, performance also increases: TNLGv2 530B, with around three times the number of parameters, outperforms the original GPT-3 on a variety of NLP tasks [34]. LLMs are also generalizable; they perform well on many NLP tasks in few-shot settings and zero-shot settings [38, 32]. However, several drawbacks and areas for exploration remain for LLMs that should be noted. Recent work has shown that performance on certain zero-shot tasks plateaus as model parameter size grows exponentially [5]. LLMs also struggle with parsing social situations [33] and correctly using context [1], which are important in dialog settings. This raises questions on the performance of LLMs for dialog evaluation, and how an LLM's performance changes as it increases in size.

The data that a model is trained on also influences the performance of down-stream tasks. T5 is fine-tuned on various subtasks, but pre-trained with C4. When pre-trained with domain-specific data, T5 performs better on tasks in that domain [3, 27]. Furthermore, adding several domains of data during pre-training makes the model likely to perform better [18, 42, 7]. Notably, BLOOM, OPT, Flan-T5, InstructGPT, and InstructDial are partially trained or fine-tuned on dialog datasets. Details on the content of these datasets can be found in Appendix A. This is important because natural dialog data is difficult to obtain, so either scripted conversations or Reddit threads are used since they are the most readily available. This dearth of data is the reason that few-shot prompting is of interest. While work such as [39] acknowledges emergent abilities in larger language models in few-shot prompting settings, this paper explores discrepancies in performance specifically for dialog evaluation.

2.2 Dialog Evaluation

Dialog evaluation presents a unique combination of challenges; it must consider multiple speakers [44], context that informs the current dialog turn, and the one-to-many aspect mentioned above [45].

Metrics such as USR [22] and FED [21] were created to address some of these challenges; they are reference-free, capture complex aspects of dialog, and have good correlation with human evaluation. These metrics use models such as RoBERTa (125 million parameters) [18] and DialoGPT (345 or 762 million parameters) [43] respectively. However, the best performing versions of these models are smaller than most models examined in this paper, and are fine-tuned on dialog data or on a specific dialog task. Other automatic evaluation metrics include GRADE [14] and DEB [31]. With current LLMs' large increase in hyperparameters, their plethora of training data, and their promising generalizable performance on NLP tasks, these model-based metrics should improve as well.

2.3 Example selection for few-shot learning

The example selection process for prompting LLMs is of great interest. Prompting an LLM with a task and a few examples enables the model to adapt to a new task without completely fine-tuning it. In particular, in-context examples can provide important cues to help LLMs make predictions on tasks. Recent work has used a variety of methods to examine example selection. Common methods measure semantic similarity between example embeddings [17, 35]. Alternatively, retrieval methods (e.g. BM25 [28]) have been used directly, or as a precursor to training a selection retriever [30].

These example selection methods have shown promise in few-shot NLP tasks. In [35], the two-step framework for annotating and selecting in-context examples from large unlabeled data showed competitive performance across 10 tasks such as classification, commonsense reasoning, dialog state tracking, and code generation. [17] showed that selecting examples with similar sentence embeddings yields higher GPT-3 performance than random selection. However, the authors acknowledge that further investigation is required to find more efficient in-context example retrieval methods.

Moreover, the wording and order of examples presented in prompts can also affect model performance [10, 17, 15]. Lu et al [19] observed order sensitivity across 0.1B to 175B parameter GPT-2 and GPT-3 models when the models were probed with different text classification tasks and several in-context examples. Also, the wording of the in-context examples depends on the data used for model training; for unfamiliar prompt formats, model performance may decrease [15]. Increasing the size of the model and the amount of data does not resolve the issue since the same instability is still prevalent [47]. Thus this paper studies the effect of example selection on dialog evaluation.

3 Evaluation Settings

Two settings for dialog evaluation are explored: fine-grained evaluation and multidomain evaluation. In-context examples are explored in both.

3.1 Fine-Grained Evaluation

Fine-grained metrics can be measured at both the turn level (e.g. informativeness and relevance), and the dialog level (e.g. coherence and diversity). The FED dataset [21] is used. It consists of 124 open-domain dialogs of humans with humans or with machines, for which each dialog has 3 responses that are chosen for annotation (8 turn-level and 10 dialog-level qualities along with overall turn- and dialog-level quality). This dataset was chosen due to the large number of previously studied fine-

grained qualities as listed in Section 4.1, with the exception of correctness and error recovery, which are only specifically present in FED.

In the experiments, the LM is prompted to output a rating (an integer value - see Appendix B) to evaluate each fine-grained quality in a response. The final rating for each fine-grained quality is a weighted sum of the K-top ratings outputted from the LM. Formally, given the K-top predicted ratings $r_1, r_2, ..., r_K$ along with their corresponding log probabilities, $p_1, ..., p_K$, the weight, w_i , of each rating r_i is derived as:

$$w_i = \frac{p_i}{\sum_{j=1}^K p_j}$$

The final rating, r, is calculated as:

$$r = \sum_{i=1}^{K} r_i * w_i$$

In order to provide a more accurate view of the LM's performance, K = 3 in the following experiments. Additionally, this scoring mechanism converts the LM predictions onto a continuous scale, which more closely mirrors the average of human ratings. Results are reported with the Spearman correlations to the average human ratings for each fine-grained quality.

3.2 Multi-domain Evaluation

This task tests automatic dialog evaluation metrics for robustness across multiple dialog domains. The analysis uses only the overall quality metric since many of the domain datasets do not have fine-grained annotations. The Spearman correlation is used between human ratings and model predictions on the evaluation sets released by DSTC 10 Track 5 [6] "Automatic Evaluation and Moderation of Opendomain Dialogue Systems". These sets contain human judgement ratings for dialog responses. In this setting, a model is shown a dialog context and a response, and it outputs "yes" if the response is a good response to that context, otherwise it outputs "no". An example can be seen in Appendix C. The probability of the "goodness" of the response (i.e., the rating), g, is calculated as:

$$g = \frac{p_{model}(yes)}{p_{model}(yes) + p_{model}(no)}$$

where $p_{model}(yes)$ and $p_{model}(no)$ are the log probilities of the model outputs for "yes" and "no". Evaluation is carried out on 8 representative evaluation sets out of the 14 DSTC10 evaluation sets [6]. This subset was chosen because it covers multiple domains and datasets, such as persona, topic and chitchat-based responses. A robust dialog metric should perform well across all the domains and evaluation sets considered.

The evaluation sets used for fine-grained evaluation, FED-Turn (FT) and FED-Dial (FD) [21], are included as two of the eight datasets. The other datasets include: TopicalChat-USR (TU, knowledge-grounded open-domain conversations rated for six different dialog qualities) [22]; PersonaChat-USR (PU, persona-conditioned conversations annotated with the USR schema) [22]; DailyDialog-Zhao (DZ, more formal language conversations rated for appropriateness) [46]; DailyDialog-Gupta (DGU, rated for appropriateness) [11]; DailyDialog-GRADE (DGR; annotated for coherence) [14]; and Empathetic-GRADE (EG, emotionally grounded conversations annotated for coherence) [14]. Although some of these datasets are not directly annotated for whether a response is good, the metric they use remains a component for overall quality, and thus it is treated as the indicator of the overall quality of the response in the experiments.

3.3 In-Context Examples

This paper uses two methods for example selection: random selection, and algorithmic selection using BM25 [20] which calculates document similarity. The examples remain consistent for each evaluation test point. The random selection experiment is run three times, and the mean and standard deviation of the runs are reported. There are three configurations for BM25 between the test point and each possible example point - comparing the context only $(BM25_C)$, the response only $(BM25_R)$, and the concatenated context and response together $(BM25_{C+R})$.

With the FED dataset, an additional method, manual selection, is added for example selection. For each fine-grained dialog quality, a set of three dialogs which span a wide range of ratings is chosen that remains constant over every test point. In theory, the model should be able to show increased performance if it sees examples of very good, good and bad responses for fine-grained metrics. For the DSTC10 datasets, an additional experiment tested how the number of examples used affects model performance.

4 Experiments and Results

The in-context example experiments are carried out on the largest available model, 530B TNLGv2, to explore the ceiling of model performance on the dialog evaluation task. 6.7B TNLGv2 is used for a direct comparison of how much performance gain is provided by using more parameters.

BLOOM and OPT are examined up to 7B and 30B respectively for the fine-grained metric evaluation task. ¹ Smaller LLMs do not perform as well with in-

¹ Due to limitations in compute power, larger BLOOM and OPT models were not explored. However, as the largest available GPT-3 model is explored, the comparisons appear sufficient to show the performance of a variety of LLMs.

context examples unless they have been specifically tuned for the task, so only the 7B and 6.7B models for BLOOM and OPT respectively are explored for the DSTC10 datasets. Flan-T5 and InstructDial are analyzed in the 3B setting for consistency. Lastly, InstructGPT (text-davinci-002) is used, which has 175B parameters.

4.1 Fine-grained Metric Evaluation

FED is separated into turn-level and dialog-level metrics. The dataset has annotations for 8 different turn-level metrics, consisting of *interestingness*, *engagingness*, *specificity*, *relevance*, *correctness*, *semantic appropriateness*, *understandability*, and *fluency*, with the addition of *overall quality*. FED annotates three different responses for each dialog context; one FED dialog is treated as one example. The corresponding rating is inserted after the response statement in the prompt, an example of which can be seen in Appendix B. FED also looks at 10 different dialog-level metrics for a system's responses: *coherence*, *error recovery*, *consistency*, *diversity*, *topic depth*, *likeability*, *understandingness*, *flexibility*, *informativeness*, and *inquisitiveness*, with *overall quality* included. The model is prompted with the full dialog context with the rating.

The FED metric was previously evaluated with both fine-tuned (ft) and from-scratch 345M and 762M DialoGPT [43] models. In the following experiments on FED, 3 in-context examples were used for prompting in Tables 1, 2, 3 and 4 and Appendix D and E.

4.1.1 In-Context Example Selection

This setting evaluates 2 versions of the TNLGv2 model: 6.7B and 530B. These models are compared to the 762M ft DialoGPT model and the results are shown in Tables 1 and 2 and Appendix D.

First, the performances of these models are compared over the three example selection methods: manual, random, and algorithmic. With manually chosen incontext examples, the 530B TNLGv2 model outperforms the DialoGPT model on almost all turn-level metrics except for *understandability* and *fluency*. There are significant gains in all of the dialog-level metrics as well. Since DialoGPT is fine-tuned on Reddit threads, more casual language is expected, compared to models like TNLGv2 where many of the training datasets consist of more formal language. Since the wording of conversational responses tends to be more casual, it is not surprising that the fine-tuned DialoGPT model outperforms even the largest TNLGv2 model for *fluency* and *understandability*. However, the TNLGv2 models show large improvement on predicting *turn-* and *dialog-level quality*. This suggests that the TNLGv2 models have a strong grasp on overall quality, which may be due to training on more formal language.

 $BM25_{C+R}$ generally outperforms $BM25_{C}$ and $BM25_{R}$. However, when choosing examples with $BM25_{C+R}$, the correlation of *understandability* with human annotations increases significantly when using the 6.7B TNLGv2 model. 6.7B TNLGv2 consistently outperforms 530B TNLGv2 in this aspect with any BM25 method. It appears that the smaller model is more influenced by the similarity of language in the examples than the larger one.

Even when given random examples, the TNLGv2 models outperform the 762M ft DialoGPT model on a majority of the fine-grained metrics. This shows that larger models can better detect what constitutes a good response based on these metrics even if they are not given hand-picked examples. However, they generally do not outperform the manually or algorithmically chosen examples as expected.

An additional observation is that there are certain factors that cause models to perform better or worse on specific metrics: number of parameters the model has, the type of training data, and the difficulty of the task. LLMs are able to provide increases in performance of over 50% for 15 out of 20 turn- and dialog-level metrics compared to DialoGPT with 530B TNLGv2 and manually-chosen examples. However, if the 530B TNLGv2 model is compared to the 6.7B TNLGv2 model, this increase is only observed for 2 out of the 20 metrics: *correctness* and *understandability*. LLMs can achieve high correlations with human judgement, but there is a limit to how much more performance gains can increase with extremely large models.

Specificity, relevance, and correctness all relate to the context of the conversation while the other metrics are more turn-specific. It follows that relevance and correctness with BM25_{C+R} on the 6.7B TNLGv2 model outperform the 530B TNLGv2 model with manual examples. However, specificity performs worse. Choosing both diverse ratings and similar example points are important. This finding further supports the idea that the nature of the data used to train these LLMs is important. Had the training data been more similar to conversational language, an increase could have been observed in the correlations for these metrics without choosing algorithmically similar examples.

TNLGv2 struggles with *understandability*; it performs the worst at the highest correlation of 0.193. It also has unstable performance; performing at significance with random examples and with algorithmically chosen examples on 6.7B, but not with manually chosen ones. This shows that choosing examples with diverse ratings helps a model less for metrics that it already performs poorly on; it would better benefit from examples that are similar.

In general, even with the difference in training data, it is easier to obtain an overall sense of the conversation than a metric for a single turn for the larger models due to the large amount of parameters and variety of data that they have seen. When choosing examples based on context, the larger models generally perform worse; it appears that having different examples is more important for dialog-level metrics than for turn-level metrics.

		manual random		dom	BM2	5 _{C+R}	
Quality	762M ft	6.7B	530B	6.7B	530B	6.7B	530B
Interesting	0.408	0.455	0.474	0.293 ± 0.03	0.398 ± 0.02	0.358	0.383
Engaging	0.318	0.459	0.484	0.235 ± 0.04	0.352 ± 0.02	0.378	0.383
Specific	0.267	0.305	0.450	0.188 ± 0.02	$0.289 {\pm}~0.01$	0.268	0.322
Relevant	0.152	0.214	0.300	0.179 ± 0.04	0.299 ± 0.03	0.392	0.357
Correct	0.133	0.195	0.393	0.171 ± 0.04	0.338 ± 0.04	0.399	0.377
Sem. Approp.	0.155	0.292	0.395	0.163 ± 0.03	0.270 ± 0.01	0.291	0.294
Understandable	0.111	0.021*	0.036*	0.146 ± 0.02	0.129 ± 0.02	0.193	0.062*
Fluent	0.224	0.164	0.195	$0.052*\pm0.03$	$0.112*\pm0.01$	0.096*	0.178
Overall	0.209	0.371	0.475	$0.256 {\pm}~0.02$	$0.380 {\pm}~0.01$	0.474	0.514

Table 1 Turn-level fine-grained metrics on the FED dataset for manually, randomly, and BM25 chosen examples over the TNLGv2 6.7B and 530B models. BM25 $_{\rm C+R}$ stands for examples chosen by BM25 considering both the context and the response of the test point. **Bold** values indicate the best value for the metric and * values indicate correlations that are not statistically significant.

		mai	nual	random		BM	125 _C
Quality	762M ft	6.7B	530B	6.7B	530B	6.7B	530B
Coherent	0.251	0.599	0.727	0.443 ± 0.03	0.533 ± 0.02	0.618	0.512
Error Recovery	0.165*	0.474	0.578	0.348 ± 0.04	0.463 ± 0.06	0.492	0.419
Consistent	0.116*	0.276	0.382	0.270 ± 0.02	$0.205* \pm 0.04$	0.238	0.046*
Diverse	0.420	0.625	0.620	0.434 ± 0.06	0.490 ± 0.02	0.496	0.548
Topic Depth	0.476	0.640	0.659	0.361 ± 0.03	0.531 ± 0.04	0.559	0.472
Likeable	0.262	0.619	0.686	0.511 ± 0.03	0.580 ± 0.01	0.568	0.515
Understanding	0.306	0.517	0.638	0.479 ± 0.06	0.496 ± 0.02	0.567	0.428
Flexible	0.293	0.617	0.656	0.491 ± 0.05	0.553 ± 0.03	0.614	0.451
Informative	0.288	0.569	0.547	0.391 ± 0.04	0.452 ± 0.04	0.523	0.419
Inquisitive	0.163	0.537	0.527	0.436 ± 0.05	0.444 ± 0.02	0.334	0.252
Overall	0.443	0.630	0.688	0.479 ± 0.05	0.570 ± 0.02	0.607	0.531

Table 2 Dialog-level fine-grained metrics on the FED dataset for manually, randomly, and BM25 chosen examples over the TNLGv2 6.7B and 530B models. BM25 $_{\rm C}$ stands for examples chosen by BM25 considering only the context of the test point.

4.1.2 Comparisons Across LLMs

These model comparisons are performed using manually chosen in-context examples, since that is what generally performed the best in both turn-level and dialog-level metrics in Tables 3 and 4. Comparisons across smaller versions of BLOOM and OPT can be found in Appendix E.

Even though the large versions of BLOOM and OPT could not be run, it is apparent that both of these models outperform TNLGv2 on *understandability*, and that OPT 6.7B can outperform TNLGv2 530B on *fluency*. Data dissimilarities were noted above in Section 4.1.1 between the TNLGv2 model and the FED data. Although BLOOM was only trained on some English data, it has still seen some casual language, while OPT was partially trained on Reddit data. Thus the language appearing in the BLOOM and OPT training sets more closely matches that of the conversations used here. This explains the increase in performance.

BLOOM 7B outperforms 6.7B TNLGv2 on correctness, while OPT 6.7B outperforms 6.7B TNLGv2 on relevance, correctness, semantic appropriateness and

	TN	TNLG		OPT		Flan-T5	InstructGPT	
Quality	6.7B	530B	7B	6.7B	30B	3B	175B	
Interesting	0.455	0.474	0.291	0.429	0.399	0.519	0.551	
Engaging	0.459	0.484	0.435	0.446	0.349	0.425	0.489	
Specific	0.305	0.450	0.296	0.275	0.207	0.433	0.421	
Relevant	0.214	0.300	0.109	0.272	0.289	0.435	0.471	
Correct	0.195	0.393	0.235	0.342	0.354	0.378	0.376	
Sem. Approp.	0.292	0.395	0.258	0.371	0.382	0.277	0.374	
Understandable	0.021*	0.036*	0.159	0.131	0.073*	0.297	0.382	
Fluent	0.164	0.195	0.111	0.201	0.188	0.200	0.204	
Overall	0.371	0.475	0.274	0.368	0.433	0.445	0.536	

Table 3 Turn-level fine-grained metrics on the FED dataset for manually chosen examples over the TNLGv2, BLOOM, OPT, Flan-T5, and InstructGPT models.

	TN	LG	BLOOM	O	PT	FLAN-T5	InstructGPT
Quality	6.7B	530B	7B	6.7B	30B	3B	175B
Coherent	0.599	0.727	0.613	0.558	0.584	0.730	0.707
Error Recovery	0.474	0.578	0.474	0.377	0.479	0.398	0.560
Consistent	0.276	0.382	0.323	0.237	0.309	0.410	0.517
Diverse	0.625	0.620	0.498	0.454	0.607	0.544	0.628
Topic Depth	0.640	0.659	0.637	0.544	0.609	0.650	0.680
Likeable	0.619	0.686	0.566	0.544	0.571	0.659	0.672
Understanding	0.517	0.638	0.484	0.505	0.483	0.637	0.694
Flexible	0.617	0.656	0.499	0.528	0.592	0.595	0.688
Informative	0.569	0.547	0.462	0.497	0.522	0.662	0.647
Inquisitive	0.537	0.527	0.539	0.461	0.537	0.487	0.578
Overall	0.630	0.688	0.531	0.374	0.530	0.585	0.690

Table 4 Dialog-level fine-grained metrics on the FED dataset for manually chosen examples over the TNLGv2, BLOOM, OPT, Flan-T5, and InstructGPT models.

fluency in addition. As previously noted, relevance and correctness are turn-level metrics that take more of the context into account, so with training data that is more similar to casual language, these models perform better. It should be noted that the overall turn- and dialog-level quality results were not surpassed by any smaller model, thus the very large models will have an advantage for overall metrics.

Flan-T5 outperforms the largest model, TNLGv2 530B, on *interestingness*, *relevance*, and *understandability* at turn level and *coherence*, *consistency*, and *informativeness* at dialog level. There is a larger performance drop for the *semantic appropriateness*, *error recovery*, and *overall dialog-level quality* metrics. *Error recovery* is a relatively new metric [21]. Even though Flan-T5 was fine-tuned on many dialog tasks, it may not have seen data that addresses this specific metric. Flan-T5 only has 3B parameters, and the fact that it outperforms 530B TNLGv2 shows the importance of use of dialog data during pre-training or fine-tuning.

InstructGPT, being fine-tuned with prompting at 175B parameters, is more suitable for the present experiments. It performs very well on both turn- and dialog-level metrics, outperforming 530B TNLGv2 on almost all metrics. Since InstructGPT has already seen prompting, the model can better understand a task through only instructions or combinations of instructions and in-context examples.

Model	TU	DZ	PU	DGU	DGR	FT	EG	FD
Experiments with Random	Examples							
4ex	0.112 ± 0.03	0.428 ± 0.01	0.403 ± 0.02	0.542 ± 0.00	0.338 ± 0.01	0.318 ± 0.02	0.248 ± 0.04	0.290 ± 0.05
8ex	0.169 ± 0.03	0.430 ± 0.03	0.331 ± 0.03	0.570 ± 0.01	$\textbf{0.429}\pm0.05$	0.337 ± 0.01	0.200 ± 0.04	0.339 ± 0.18
12ex	0.148 ± 0.03	0.453 ± 0.02	0.384 ± 0.02	0.565 ± 0.01	0.410 ± 0.06	0.412 ± 0.03	0.160 ± 0.02	0.351 ± 0.08
Experiments with Algorith	mically Retr	ieved Exam	ples					
4ex BM25 _R	0.247	0.424	0.252	0.482	0.342	0.364	0.144	0.264
4ex BM25 _C	0.129	0.424	0.339	0.510	0.370	0.172	0.192	0.549
4ex BM25 _{C+R}	0.213	0.441	0.432	0.479	0.371	0.137	0.211	0.479
8ex BM25 _R	0.309	0.487	0.275	0.536	0.304	0.426	0.121	0.419
8ex BM25 _C	0.227	0.564	0.460	0.627	0.387	0.323	0.123	0.518
8ex BM25 _{C+R}	0.185	0.458	0.439	0.526	0.308	0.377	0.171	0.530
12ex BM25 _R	0.300	0.474	0.358	0.570	0.337	0.393	0.095*	0.414
12ex BM25 _C	0.278	0.688	0.449	0.674	0.397	0.377	0.106*	0.492
12ex BM25 _{C+R}	0.202	0.491	0.452	0.465	0.349	0.358	0.148	0.493
Best of DSTC10 baselines	0.319	0.532	0.493	0.596	0.363	0.247	0.395	0.555

Table 5 Spearman correlation of model predictions for overall quality with human ratings for TNLGv2 530B model with algorithmically chosen examples. TU, PU, PZ, DZ, CG, DGU, DGR, EG, FT and FD are abbreviations for TopicalChat-USR, PersonaChat-USR [22], PersonaChat-Zhao [46], DailyDialog-Zhao [46], ConvAI2-GRADE [14], DailyDialog-Gupta [11], DailyDialog-GRADE [14], Empathetic-GRADE [14], FED-Turn and FED-Dial [21].

Model	TU	DZ	PU	DGU	DGR	FT	EG	FD
Few-shot in-context Experim	ents							
BLOOM-7B-4ex	0.027*	0.075	0.123	0.127	0.131	0.117	0.012	0.289
OPT-6.7B-4ex	0.115	0.258	0.444	0.228	0.091*	0.486	0.044*	0.657
TNLG-6.7B-4ex	0.124	0.198	0.237	0.209	0.214	0.296	0.057*	0.314
TNLG-530B-4ex	0.129	0.424	0.339	0.510	0.370	0.172	0.192	0.549
Flan-T5-3B-4ex	0.447	0.657	0.578	0.714	0.379	0.442	0.396	0.492
InstructGPT-175B-4ex	0.616	0.716	0.687	0.746	0.472	0.506	0.305	0.412
Zero-shot Experiments								
Flan-T5-3B-0ex	0.357	0.599	0.533	0.677	0.351	0.380	0.418	0.444
InstructDial-3B-0ex	0.446	0.601	0.376	0.634	0.286	0.263	0.475	0.228
Best of DSTC10 baselines	0.319	0.532	0.493	0.596	0.363	0.247	0.395	0.555
Best TNLGv2 value	0.309	0.688	0.460	0.678	0.429	0.426	0.248	0.549

Table 6 Spearman correlation of model predictions for overall quality with human ratings with 4 examples chosen with BM25 using context. Macro average scores are also shown.

4.2 DSTC10 Datasets

The same set of experiments were carried out on the 8 datasets in the DSTC10 challenge in Tables 5 and 6, and Appendix F. The previous best performing metrics on DSTC10 are compiled from [13], which include both reference-free and fine-tuned metrics (see Appendix G). Quality is evaluated in terms of how good a response is to the context.

4.2.1 In-Context Example Selection

Experiments are performed with randomly chosen examples and examples that were chosen by BM25 over 4, 8, and 12 examples in Table 5 and Appendix F. Higher correlation results are obtained on 4 datasets (DZ, DGU, DGR, and FT) with comparable results on 3 datasets (TU, PU, and FD), as compared to the best DSTC10 baselines. Most of the best results are on the 530B TNLGv2 model, which will be

discussed in this section, as compared to the 6.7B TNLGv2 model. Several factors are relevant here: the language of the dataset, the way the dataset was created, and how the dataset was annotated.

DailyDialog contains more formal language, thus TNLGv2 should perform well since its training dataset includes data sources with formal language. DZ, DGU, and DGR almost always perform the best when examples are chosen from looking at the context; adding the response generally leads to poorer performance. Since these datasets are annotated for *appropriateness* and *coherence*, context is more important than a more turn-specific metric.

TopicalChat was created through knowledge-grounding. The conversations could thus have more substance than a purely open-domain un-prompted conversation. It thus follows that response selection will work the best when choosing examples. PersonaChat has conversations that are persona-conditioned, so the quality of the conversation should take into account the entire conversation for each persona. It performs better with examples chosen for context and response or with just context.

FED is split into turn- and dialog-level annotations, thus, for turn-level annotations choosing examples based on responses should work best, and for dialog-level annotations choosing examples based on either the context or the context and response should perform the best. Choosing examples with context and response performs the best for EG, but randomly choosing examples outperforms that result. It may be that with emotionally grounded conversations, the model needs more, or more diverse examples due to the different ways emotion can be expressed.

In general, choosing examples algorithmically improves performance over randomly choosing examples. This is consistent with previous experiments above. However, randomly-chosen examples perform better on the DGR and EG datasets on the 530B TNLGv2 model. This may be because these two datasets were rated for *coherence*. Algorithmically, choosing examples based on context and response performs the best on EG, as was seen for coherence in FED in Section 4.1.1.

4.2.2 Comparisons Across LLMs

Table 6 compares the evaluation results across various LLMs. Due to model input length restrictions, the following experiments were carried out using 4 in-context examples or in a zero-shot setting. BM25 is only used with the context as the example selection strategy, since it performed well with the TNLGv2 models.

In the few-shot setting, models that were not fine-tuned or trained with prompting (BLOOM, OPT) did not have consistent results across the datasets. However, those that were fine-tuned or prompted (Flan-T5, InstructGPT, InstructDial) had results that were close to or surpassed the previous best DSTC10 baselines. InstructGPT performed the best. Even in the zero-shot setting, Flan-T5 outperforms the baseline in 6 of the datasets, and InstructDial in 5.

These results clearly show that for dialog evaluation, it is insufficient to simply train on large amounts of general internet data. Specialized approaches such as instruction tuning on multiple tasks improve the generalization capabilities of models

in zero- and few-shot settings. It is not surprising that InstructGPT performs the best since it fine-tunes a very large language model with instructions.

5 Conclusion

LLMs have the potential to significantly contribute to dialog evaluation. Current LLMs perform well for this task in a few-shot setting. However, this performance varies greatly depending on the content of and number of examples in the prompt. Models prefer more similar examples for metrics that they struggle to evaluate, while preferring examples with more diverse ratings for metrics that they can evaluate well. Very large language models also still afford performance gains, especially for overall quality evaluation at the turn and dialog level. Even though large language models perform better at dialog-level fine-grained metrics, there are still previously shown issues with how these models understand social situations and use context that may hinder further improvement if not addressed.

Performance is also affected by the model's training data. Smaller language models that are fine-tuned on instructions, trained on dialog data, and/or trained on multiple dialog tasks outperform larger language models. These smaller models also perform more consistently over different domains. This indicates that LLMs should have more diverse pre-training data in order to be able to handle a larger variety of tasks in few or zero-shot settings.

More work needs to be done on understanding how a large language model models different types of tasks. In-context example selection and example wording still remains unstable across large language models in many tasks, and the performance variation over different dialog domains in this paper demonstrates that as well.

Presently, the LLMs explored in this paper have their own strengths. Smaller models such as BLOOM and OPT could share more training data similarity with dialog tasks based on their objective. TNLGv2 530B provides a very large language model that has shown improvement in dialog evaluation along with other NLP tasks. Flan-T5 and InstructDial show the efficacy of fine-tuning a LLM on dialog tasks, and InstructGPT shows the importance of training a model to better recognize prompts. The evaluations of these models provide suggestions for the characteristics of the best LLMs to use for dialog evaluation. Future work in using LLMs for other NLP tasks can benefit from such comprehensive analyses. Once a better understanding of LLMs is realized, the capabilities of large language models for zero- and few-shot tasks will increase greatly.

6 Acknowledgements

We would like to thank Microsoft for allowing us to use TNLGv2. J.H. was supported by the NSF Graduate Research Fellowship under Grant Nos. DGE1745016

and DGE2140739. The opinions expressed in this paper do not necessarily reflect those of that funding agency.

References

- Agarwal O, Yang Y, Wallace BC, Nenkova A (2021) Interpretability analysis for named entity recognition to understand system predictions and how they can improve. Computational Linguistics 47(1):117–140
- [2] Baumgartner J, Zannettou S, Keegan B, Squire M, Blackburn J (2020) The pushshift reddit dataset. In: Proceedings of the international AAAI conference on web and social media, vol 14, pp 830–839
- [3] Beltagy I, Lo K, Cohan A (2019) Scibert: A pretrained language model for scientific text. arXiv preprint arXiv:190310676
- [4] BigScience Workshop (2022) Bloom (revision 4ab0472). DOI 10.57967/hf/0003, URL https://huggingface.co/bigscience/bloom
- [5] Brown T, Mann B, Ryder N, Subbiah M, Kaplan JD, Dhariwal P, Neelakantan A, Shyam P, Sastry G, Askell A, et al (2020) Language models are few-shot learners. Advances in neural information processing systems 33:1877–1901
- [6] Chen Z, Sadoc J, D'Haro LF, Banchs R, Rudnicky A (2021) Automatic evaluation and moderation of open-domain dialogue systems. arXiv preprint arXiv:211102110
- [7] Chowdhery A, Narang S, Devlin J, Bosma M, Mishra G, Roberts A, Barham P, Chung HW, Sutton C, Gehrmann S, et al (2022) Palm: Scaling language modeling with pathways. arXiv preprint arXiv:220402311
- [8] Chung HW, Hou L, Longpre S, Zoph B, Tay Y, Fedus W, Li E, Wang X, Dehghani M, Brahma S, et al (2022) Scaling instruction-finetuned language models. arXiv preprint arXiv:221011416
- [9] Gao L, Biderman S, Black S, Golding L, Hoppe T, Foster C, Phang J, He H, Thite A, Nabeshima N, Presser S, Leahy C (2020) The Pile: An 800gb dataset of diverse text for language modeling. arXiv preprint arXiv:210100027
- [10] Gao T, Fisch A, Chen D (2020) Making pre-trained language models better few-shot learners. arXiv preprint arXiv:201215723
- [11] Gupta P, Mehri S, Zhao T, Pavel A, Eskenazi M, Bigham J (2019) Investigating evaluation of open-domain dialogue systems with human generated multiple references. In: Proceedings of the 20th Annual SIGdial Meeting on Discourse and Dialogue, Association for Computational Linguistics, Stockholm, Sweden, pp 379–391, DOI 10.18653/v1/W19-5944, URL https: //aclanthology.org/W19-5944
- [12] Gupta P, Tsvetkov Y, Bigham J (2021) Synthesizing adversarial negative responses for robust response ranking and evaluation. In: Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021, Association for Computational Linguistics, Online, pp 3867–3883, DOI 10.18653/v1/2021.findings-acl.338, URL https://aclanthology.org/2021. findings-acl.338
- [13] Gupta P, Jiao C, Yeh YT, Mehri S, Eskenazi M, Bigham JP (2022) Improving zero and fewshot generalization in dialogue through instruction tuning. arXiv preprint arXiv:220512673
- [14] Huang L, Ye Z, Qin J, Lin L, Liang X (2020) GRADE: Automatic graph-enhanced coherence metric for evaluating open-domain dialogue systems. In: Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), Association for Computational Linguistics, Online, pp 9230–9240, DOI 10.18653/v1/2020.emnlp-main.742, URL https://aclanthology.org/2020.emnlp-main.742
- [15] Jiang Z, Xu FF, Araki J, Neubig G (2020) How can we know what language models know? Transactions of the Association for Computational Linguistics 8:423–438

[16] Kaplan J, McCandlish S, Henighan T, Brown TB, Chess B, Child R, Gray S, Radford A, Wu J, Amodei D (2020) Scaling laws for neural language models. DOI 10.48550/ARXIV.2001. 08361, URL https://arxiv.org/abs/2001.08361

- [17] Liu J, Shen D, Zhang Y, Dolan B, Carin L, Chen W (2021) What makes good in-context examples for gpt-3? DOI 10.48550/ARXIV.2101.06804, URL https://arxiv.org/ abs/2101.06804
- [18] Liu Y, Ott M, Goyal N, Du J, Joshi M, Chen D, Levy O, Lewis M, Zettlemoyer L, Stoyanov V (2019) Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:190711692
- [19] Lu Y, Bartolo M, Moore A, Riedel S, Stenetorp P (2021) Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity. DOI 10.48550/ARXIV. 2104.08786, URL https://arxiv.org/abs/2104.08786
- [20] Manning CD (2008) Introduction to information retrieval. Syngress Publishing,
- [21] Mehri S, Eskenazi M (2020) Unsupervised evaluation of interactive dialog with DialoGPT. In: Proceedings of the 21th Annual Meeting of the Special Interest Group on Discourse and Dialogue, Association for Computational Linguistics, 1st virtual meeting, pp 225–235, URL https://aclanthology.org/2020.sigdial-1.28
- [22] Mehri S, Eskenazi M (2020) USR: An unsupervised and reference free evaluation metric for dialog generation. In: Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, Association for Computational Linguistics, Online, pp 681–707, DOI 10.18653/v1/2020.acl-main.64, URL https://aclanthology.org/2020.acl-main.64
- [23] Ouyang L, Wu J, Jiang X, Almeida D, Wainwright CL, Mishkin P, Zhang C, Agarwal S, Slama K, Ray A, et al (2022) Training language models to follow instructions with human feedback. arXiv preprint arXiv:220302155
- [24] Papineni K, Roukos S, Ward T, Zhu WJ (2002) Bleu: a method for automatic evaluation of machine translation. In: Proceedings of the 40th annual meeting of the Association for Computational Linguistics, pp 311–318
- [25] Phy V, Zhao Y, Aizawa A (2020) Deconstruct to reconstruct a configurable evaluation metric for open-domain dialogue systems. In: Proceedings of the 28th International Conference on Computational Linguistics, International Committee on Computational Linguistics, Barcelona, Spain (Online), pp 4164–4178, DOI 10.18653/v1/2020.coling-main.368, URL https://aclanthology.org/2020.coling-main.368
- [26] Radford A, Wu J, Child R, Luan D, Amodei D, Sutskever I, et al (2019) Language models are unsupervised multitask learners. OpenAI blog 1(8):9
- [27] Raffel C, Shazeer N, Roberts A, Lee K, Narang S, Matena M, Zhou Y, Li W, Liu PJ (2020) Exploring the limits of transfer learning with a unified text-to-text transformer. Journal of Machine Learning Research 21(140):1-67, URL http://jmlr.org/papers/v21/ 20-074.html
- [28] Robertson S, Zaragoza H (2009) The probabilistic relevance framework: Bm25 and beyond. Found Trends Inf Retr 3(4):333-389, DOI 10.1561/1500000019, URL https://doi.org/10.1561/1500000019
- [29] Roller S, Dinan E, Goyal N, Ju D, Williamson M, Liu Y, Xu J, Ott M, Smith EM, Boureau YL, Weston J (2021) Recipes for building an open-domain chatbot. In: Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume, Association for Computational Linguistics, Online, pp 300–325, DOI 10.18653/v1/2021.eacl-main.24, URL https://aclanthology.org/2021.eacl-main.24
- [30] Rubin O, Herzig J, Berant J (2021) Learning to retrieve prompts for in-context learning. DOI 10.48550/ARXIV.2112.08633, URL https://arxiv.org/abs/2112.08633
- [31] Sai AB, Mohankumar AK, Arora S, Khapra MM (2020) Improving dialog evaluation with a multi-reference adversarial dataset and large scale pretraining. Transactions of the Association for Computational Linguistics 8:810–827

- [32] Sanh V, Webson A, Raffel C, Bach SH, Sutawika L, Alyafeai Z, Chaffin A, Stiegler A, Scao TL, Raja A, et al (2021) Multitask prompted training enables zero-shot task generalization. arXiv preprint arXiv:211008207
- [33] Sap M, LeBras R, Fried D, Choi Y (2022) Neural theory-of-mind? on the limits of social intelligence in large lms. arXiv preprint arXiv:221013312
- [34] Smith S, Patwary M, Norick B, LeGresley P, Rajbhandari S, Casper J, Liu Z, Prabhumoye S, Zerveas G, Korthikanti V, et al (2022) Using deepspeed and megatron to train megatron-turing nlg 530b, a large-scale generative language model. arXiv preprint arXiv:220111990
- [35] Su H, Kasai J, Wu CH, Shi W, Wang T, Xin J, Zhang R, Ostendorf M, Zettlemoyer L, Smith NA, Yu T (2022) Selective annotation makes language models better few-shot learners. DOI 10.48550/ARXIV.2209.01975, URL https://arxiv.org/abs/2209.01975
- [36] Thoppilan R, De Freitas D, Hall J, Shazeer N, Kulshreshtha A, Cheng HT, Jin A, Bos T, Baker L, Du Y, et al (2022) Lamda: Language models for dialog applications. arXiv preprint arXiv:220108239
- [37] Trinh TH, Le QV (2018) A simple method for commonsense reasoning. DOI 10.48550/ ARXIV.1806.02847, URL https://arxiv.org/abs/1806.02847
- [38] Wei J, Bosma M, Zhao VY, Guu K, Yu AW, Lester B, Du N, Dai AM, Le QV (2021) Fine-tuned language models are zero-shot learners. arXiv preprint arXiv:210901652
- [39] Wei J, Tay Y, Bommasani R, Raffel C, Zoph B, Borgeaud S, Yogatama D, Bosma M, Zhou D, Metzler D, et al (2022) Emergent abilities of large language models. arXiv preprint arXiv:220607682
- [40] Zellers R, Holtzman A, Rashkin H, Bisk Y, Farhadi A, Roesner F, Choi Y (2019) Defending against neural fake news. DOI 10.48550/ARXIV.1905.12616, URL https://arxiv.org/abs/1905.12616
- [41] Zhang C, Chen Y, D'Haro LF, Zhang Y, Friedrichs T, Lee G, Li H (2021) DynaEval: Unifying turn and dialogue level evaluation. In: Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), Association for Computational Linguistics, Online, pp 5676–5689, DOI 10.18653/v1/2021.acl-long.441, URL https://aclanthology.org/2021.acl-long.441
- [42] Zhang S, Roller S, Goyal N, Artetxe M, Chen M, Chen S, Dewan C, Diab M, Li X, Lin XV, et al (2022) Opt: Open pre-trained transformer language models. arXiv preprint arXiv:220501068
- [43] Zhang Y, Sun S, Galley M, Chen YC, Brockett C, Gao X, Gao J, Liu J, Dolan B (2019) Dialogpt: Large-scale generative pre-training for conversational response generation. arXiv preprint arXiv:191100536
- [44] Zhang Z, Guo T, Chen M (2021) Dialoguebert: A self-supervised learning based dialogue pre-training encoder. In: Proceedings of the 30th ACM International Conference on Information & Knowledge Management, pp 3647–3651
- [45] Zhao T, Zhao R, Eskenazi M (2017) Learning discourse-level diversity for neural dialog models using conditional variational autoencoders. arXiv preprint arXiv:170310960
- [46] Zhao T, Lala D, Kawahara T (2020) Designing precise and robust dialogue response evaluators. In: Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, Association for Computational Linguistics, Online, pp 26–33, DOI 10.18653/v1/2020.acl-main.4, URL https://aclanthology.org/2020.acl-main.4
- [47] Zhao Z, Wallace E, Feng S, Klein D, Singh S (2021) Calibrate before use: Improving few-shot performance of language models. In: International Conference on Machine Learning, PMLR, pp 12,697–12,706

A LLMs and Their Training/Fine-tuning Data

	Seen Dialog	Fine-tuned
Flan-T5	✓	✓
InstructDial	✓	\checkmark
InstructGPT	✓	\checkmark
BLOOM	✓	×
OPT	✓	×
TNLGv2	×	×

Table 7 LLMs with the datasets they were trained on. During training or fine-tuning: "Seen Dialog" indicates that the model has explicitly seen dialog datasets and therefore elements of casual language, and "fine-tuned" indicates that the model was fine-tuned on dialog data. TNLGv2 has not seen datasets explicitly categorized as having dialog, but elements of casual language may be included in the Common Crawl snapshots and other internet-based corpora. Symbols: ✓ means that the category is included and × means that the category is not included.

B Prompt format examples FED

Task: Given a dialog history and a response, rate how interesting the response is with regards to the dialog history.

== Example 1 ==

A: Hi!

B: Hi. This is a pleasant surprise.

A: Haha...thanks! how did you like the gift?

Response: Currently unpacking it I guess. How's your morning?

Rating: 1/2

A: Hope you like it! Morning is good. Busy finishing up stuff before the holidays.

B: I think I traveled too much the last couple of months so no holiday for me. But I'm okay with that. Going anywhere exciting?

A: Yes

Response: Where to?

Rating: 1/2

A: Hawaii... looking forward to warm beaches. **Response**: WOW. Which island? I like Hawaii.

Rating: 2/2

Table 8 An example of a prompt with one example from FED [21]. Interestingness was rated in FED over three values corresponding to 0/2, 1/2, and 2/2. The resulting output is truncated to the integer value of 0, 1, or 2 to be used in evaluation.

C Prompt format examples DSTC10

Instruction: Given a conversation and a response, choose if the response is a good response

to the context

Example

Background info: none

Conversation:

Person A: did your meal meet with your approval?

Response: yes, i did. it was a good meal.

Question: Is the above response a good response to the conversation?

Answer: Yes

Background info: none

Conversation:

Person B: i really do hate public transportation. Person A: i agree, it 's just never on time.

Response: you 're right.

Question: Is the above response a good response to the conversation?

Answer:

Table 9 An example of a prompt with examples from DSTC 10.

D Additional algorithmically chosen FED examples

	BM	125 _C	BM	25 _R	
Quality	7B	530B	7B	530B	
Interesting	0.336	0.389	0.355	0.385	
Engaging	0.308	0.332	0.328	0.389	
Specific	0.217	0.224	0.297	0.329	
Relevant	0.338	0.314	0.311	0.356	
Correct	0.333	0.341	0.300	0.383	
Sem. Approp.	0.261	0.270	0.287	0.337	
Understandable	0.141	0.028*	0.169	0.029*	
Fluent	0.106	0.147	0.096*	0.121	
Overall	0.435	0.438	0.360	0.407	

Table 10 Turn-level fine-grained metrics on the FED dataset for algorithmically chosen examples over the TNLGv2 6.7B and 530B models. $BM25_{C}$ stands for examples chosen by BM25 considering the context and $BM25_{R}$ stands for examples chosen by BM25 considering the response.

E Additional LLM sizes on FED

	BLC	OOM		OPT					
560M	1.1B	1.7B	3B	125M	350M	1.3B	2.7B		
0.282	0.331	0.336	0.328	0.187	0.186	0.388	0.245		
0.217	0.320	0.278	0.418	0.121	0.252	0.398	0.292		
0.030*	0.065*	0.204	0.353	0.197	0.004*	0.217	0.222		
0.076*	0.056*	0.072*	0.091*	0.146	0.105	0.231	0.177		
0.106	0.146	0.124	0.173	0.119	0.152	0.327	0.270		
0.048*	0.228	0.205	0.265	0.148	0.278	0.274	0.296		
-0.017*	0.043*	-0.005*	0.087*	0.058*	0.021*	0.189	0.205		
0.158	0.223	0.097*	0.091*	0.109	0.087*	0.158	0.163		
0.086*	0.179	0.076*	0.285	0.134	0.219	0.338	0.197		
	0.282 0.217 0.030* 0.076* 0.106 0.048* -0.017* 0.158	560M 1.1B 0.282 0.331 0.217 0.320 0.030* 0.065* 0.076* 0.056* 0.106 0.146 0.048* 0.228 -0.017* 0.043* 0.158 0.223	0.282 0.331 0.336 0.217 0.320 0.278 0.030* 0.065* 0.204 0.076* 0.056* 0.072* 0.106 0.146 0.124 0.048* 0.228 0.205 -0.017* 0.043* -0.005* 0.158 0.223 0.097*	560M 1.1B 1.7B 3B 0.282 0.331 0.336 0.328 0.217 0.320 0.278 0.418 0.030* 0.065* 0.204 0.353 0.076* 0.056* 0.072* 0.091* 0.106 0.146 0.124 0.173 0.048* 0.228 0.205 0.265 -0.017* 0.043* -0.005* 0.087* 0.158 0.223 0.097* 0.091*	560M 1.1B 1.7B 3B 125M 0.282 0.331 0.336 0.328 0.187 0.217 0.320 0.278 0.418 0.121 0.030* 0.065* 0.204 0.353 0.197 0.076* 0.056* 0.072* 0.091* 0.146 0.106 0.146 0.124 0.173 0.119 0.048* 0.228 0.205 0.265 0.148 -0.017* 0.043* -0.005* 0.087* 0.058* 0.158 0.223 0.097* 0.091* 0.109	560M 1.1B 1.7B 3B 125M 350M 0.282 0.331 0.336 0.328 0.187 0.186 0.217 0.320 0.278 0.418 0.121 0.252 0.030* 0.065* 0.204 0.353 0.197 0.004* 0.076* 0.056* 0.072* 0.091* 0.146 0.105 0.106 0.146 0.124 0.173 0.119 0.152 0.048* 0.228 0.205 0.265 0.148 0.278 -0.017* 0.043* -0.005* 0.087* 0.058* 0.021* 0.158 0.223 0.097* 0.091* 0.109 0.087*	560M 1.1B 1.7B 3B 125M 350M 1.3B 0.282 0.331 0.336 0.328 0.187 0.186 0.388 0.217 0.320 0.278 0.418 0.121 0.252 0.398 0.030* 0.065* 0.204 0.353 0.197 0.004* 0.217 0.076* 0.056* 0.072* 0.091* 0.146 0.105 0.231 0.106 0.146 0.124 0.173 0.119 0.152 0.327 0.048* 0.228 0.205 0.265 0.148 0.278 0.274 -0.017* 0.043* -0.005* 0.087* 0.058* 0.021* 0.189 0.158 0.223 0.097* 0.091* 0.109 0.087* 0.158		

Table 11 Turn-level fine-grained metrics on the FED dataset for manually chosen examples over the smaller sizes of BLOOM and OPT.

		BLO	OM			OP	T	
Quality	560M	1.1B	1.7B	3B	125M	350M	1.3B	2.7B
Coherent	0.499	0.533	0.531	0.531	0.490	0.514	0.528	0.435
Error Recovery	0.293	0.298	0.322	0.448	0.168	0.380	0.342	0.348
Consistent	0.217	0.238	0.129*	0.264	0.193	0.191	0.250	0.268
Diverse	0.345	0.430	0.461	0.518	0.451	0.304	0.491	0.531
Topic Depth	0.418	0.414	0.519	0.462	0.228	0.302	0.462	0.454
Likeable	0.310	0.374	0.421	0.476	0.467	0.395	0.462	0.535
Understanding	0.276	0.312	0.257	0.371	0.389	0.283	0.414	0.494
Flexible	0.269	0.432	0.400	0.441	0.458	0.377	0.460	0.432
Informative	0.149*	0.384	0.372	0.537	0.378	0.402	0.381	0.544
Inquisitive	0.198	0.350	0.318	0.339	0.489	0.300	0.439	0.413
Overall	0.262	0.146*	0.207	0.261	-0.000*	0.319	0.452	0.437

Table 12 Dialog-level fine-grained metrics on the FED dataset for manually chosen examples over the smaller sizes of BLOOM and OPT.

F DSTC10 Results For TNLGv2 6.7B

Model	TU	DZ	PU	DGU	DGR	FT	EG	FD
Experiments with	Random Exa	ımples						
4ex	$0.034* \pm 0.05$	0.117 ± 0.02	0.206 ± 0.02	$0.080 * \pm 0.05$	0.121 ± 0.05	0.191 ± 0.06	$0.005 \text{*} \pm 0.04$	0.228 ± 0.03
8ex	$0.054* \pm 0.05$	0.160 ± 0.02	0.206 ± 0.03	$0.109 * \pm 0.03$	0.139 ± 0.08	0.178 ± 0.02	$0.060 * \pm 0.06$	0.238 ± 0.11
12ex	$0.063* \pm 0.03$	0.149 ± 0.00	0.225 ± 0.01	0.114 ± 0.05	0.143 ± 0.06	0.210 ± 0.03	$0.052 \text{*} \pm 0.02$	0.127 ± 0.04
Experiments with	Algorithmica	ally Retrieve	ed Examples					
4ex BM25 _R	0.148	0.218	0.223	0.202	0.094*	0.273	-0.012*	0.335
4ex BM25 _C	0.124	0.198	0.237	0.209	0.214	0.296	0.057*	0.314
4ex BM25 _{C+R}	0.05*	0.142	0.169	0.167	0.083*	0.274	0.038*	0.339
8ex BM25 _R	0.077*	0.270	0.203	0.222	0.128	0.199	0.042*	0.335
8ex BM25 _C	0.184	0.328	0.343	0.526	0.176	0.363	0.073*	0.387
8ex BM25 _{C+R}	0.029*	0.152	0.020*	0.092	0.022*	0.348	0.024*	0.440
12ex BM25 _R	0.069*	0.338	0.153	0.213	0.110*	0.250	0.026*	0.401
12ex BM25 _C	0.285	0.544	0.325	0.678	0.208	0.330	0.042*	0.365
12ex BM25 _{C+R}	0.035*	0.168	0.088*	0.086*	0.100*	0.407	0.092*	0.343

Table 13 Spearman correlation of model predictions with human ratings for TNLGv2 6.7B model with algorithmically chosen examples. TU, PU, PZ, DZ, CG, DGU, DGR, EG, FT and FD are abbreviations for TopicalChat-USR, PersonaChat-USR [22], PersonaChat-Zhao [46], DailyDialog-Zhao [46], ConvAI2-GRADE [14], DailyDialog-Gupta [11], DailyDialog-GRADE [14], Empathetic-GRADE [14], FED-Turn and FED-Dial [21].

G DSTC10 Baseline Results

Model	Fine-Tuned on	TU	DZ	PU	DGU	DGR	FT	EG	FD
	DTSC 10 datasets								
USL-H [25]	✓	0.319	0.385	0.493	0.481	0.09	0.115	0.237	0.202
GRADE [14]	✓	0.176	0.532	0.329	0.596	0.254	0.048	0.300	0.106
DynaEval [41]	✓	-0.013	0.169	0.148	0.038	0.122	0.247	0.159	0.555
USR [22]	×	0.291	0.363	0.140	0.353	0.066	0.055	0.268	0.084
FED [21]	×	-0.090	-0.080	-0.004	0.025	-0.009	0.173	0.005	0.178
DEB [31]	×	0.123	0.486	0.351	0.579	0.363	0.044	0.395	0.141
Best		0.319	0.532	0.493	0.596	0.363	0.247	0.395	0.555

Table 14 Spearman correlation of model predictions with human ratings. The models fine-tuned on DSTC 10 datasets tend to perform better on the DSTC 10 datasets. TU, PU, PZ, DZ, CG, DGU, DGR, EG, FT and FD are abbreviations for TopicalChat-USR, PersonaChat-USR [22], PersonaChat-Zhao [46], DailyDialog-Zhao [46], ConvAI2-GRADE [14], DailyDialog-Gupta [11], DailyDialog-GRADE [14], Empathetic-GRADE [14], FED-Turn and FED-Dial [21].