The energy consumption of Proof-of-Stake systems: A replication and expansion

Juan Ignacio Ibañez Francisco Rua UCL Centre for Blockchain Technologies

Abstract

Blockchain technology and, more generally, distributed ledger technology (DLT) systems, face public scrutiny for their energy consumption levels. However, many point out that high energy consumption is a feature of (small block size and large block time) proof-of-work (PoW) DLTs, but not of proof-of-stake (PoS) DLTs. With the energy consumption of PoS systems being an under-researched area, we replicate, expand and update embryonary work modelling it and comparing different PoS-based DLTs with each other and with other non-PoS systems. In doing so, we suggest and implement a number of improvements to an existing PoS energy consumption model. We find that there may be significant differences in the energy consumption of PoS systems analysed, and confirm that regardless of these differences, their energy consumption is several orders of magnitude below that of Bitcoin Core.

<u>Keywords</u>: energy consumption, blockchain, DLT, sustainability, proof-of-stake, technological innovation.

Introduction

Distributed ledger technology (DLT) has positioned itself as one of the main technologies challenging the current technological landscape. DLT, usually in the form of blockchain technology, is as innovative as it is controversial. As the rate of adoption of DLT and crypto assets increases (Thomson Reuters, 2022), so does the inquiry into its potential drawbacks and risks.

One of the issue areas increasingly under the public eye is the environmental impact of DLT, specifically through GHG emissions that may aggravate climate change. This concern is echoed by the, The White House Office of Science and Technology Policy, that recently released a report (OSTP, 2022) seeking to summarise the state of the art in this regard. This is a part of the broader process triggered by the United States President's Executive Order 14067: "Ensuring Responsible Development of Digital Assets," which further illustrates this concern.

The discussion is characterised by arguably three dimensions. First, the debate around whether proof-of-work (PoW) mining should be considered environmentally harmful or environmentally friendly due to its energy-intensiveness or its non-rival consumption of energy, respectively (OSTP, 2022; Ibañez and Freier, 2023). Second, the interest in proof-of-stake (PoS) as an alternative DLT consensus mechanism requiring significantly less energy consumption (Platt et al, 2021). Third, the potential of DLT to enable distributed energy resources and environmental markets (OSTP, 2022; Mollah et al, 2021).

This article focuses on the second dimension, i.e. the characteristics of PoS as an alternative consensus mechanism. The consensus mechanism in a DLT performs several tasks, with the prevention of Sybil attacks¹ (Platt et al, 2022) being one of the most important. These attacks occur due to the low cost of creating identities in digital systems (ibid). DLTs typically solve this issue by attaching the ability to influence the state of the network to a scarce resource. In PoW, a validator ("miner") needs to spend energy ("work") to find a number ("nonce") by trying as many hashes at random as possible ("mining"). The ability to influence the network state is proportional to the work spent in it, not to the number of identities controlled by the miner, hence solving the Sybil attack. Nevertheless, this is an energy-intensive process. Although this very feature is by design, it has led to criticism.

PoS, instead, replaces the scarce resource of energy with that of "stake," thereby eliminating mining itself as an activity. Because the deliberate energy expenditures of mining are what originates most of PoW-based DLT's energy consumption, the consumption of PoS-based DLTs is considered minuscule in comparison. However, the exact extent to which this reduction goes, as well as the differences in this regard between the various PoS-based DLTs in the market, remains an under-studied area (Platt et al, 2021).

¹ A sybil attack is a scenario in which "a node illegitimately claims multiple identities" (Patel and Mistry, 2017: 184), pretending "to be many nodes simultaneously by using many different addresses while transmitting" (Piro et al, 2006: 1). In other words, it is the "forging of multiple identities (...) [to] control a substantial fraction of the system" (Doceur, 2002: 251; see also Trifa and Khemakhemb, 2014).

Previous work

In 2021, Platt et al (2021) began to fill this gap by analysing the energy consumption of leading PoS DLTs, namely Algorand, Cardano, Ethereum 2.0, Hedera, Polkadot and Tezos. The paper furthermore compared their energy consumption to that of Bitcoin Core as well as VisaNet.

The paper provides a useful contribution to the literature on many grounds. It provides a first exploration, it sets up a benchmark basic methodology for future studies, it considers how meaningful energy consumption comparisons should be considered not just in global terms nor just on a per transaction basis but also controlling by throughput, and it includes several of the leading PoS-based DLTs.

The authors developed a simple method to quantify the potential energy consumption per transaction (kWh/tx) of a PoS-based DLT. In short, it consists in taking observations of the throughput and number of validators at different points in time and using this data to extrapolate a function where the number of validators (and, indirectly, their energy consumption) is a function of throughput. They resort to different assumptions for the energy consumption per validator to arrive at a range of possible energy consumption values for each throughput value per PoS-based DLT (with the function's domain being established by the DLT's energy consumption at maximum throughput). They supplement this with the upper and lower thresholds of Bitcoin's electricity consumption per transaction according to the Cambridge Bitcoin Electricity Consumption Index (CCAF, 2022); and with VisaNet's energy consumption and the average of transactions per day according to its annual ESG Report.

Because the Platt et al (2021) paper pre-dates the Ethereum Merge, no actual measurements of Ethereum's (then called "Ethereum 2.0") throughput and energy consumption were used under PoS. The authors instead resort to Ethereum's pre-Merge throughput and to ex-ante estimations of the lower and upper bounds of Ethereum post-Merge energy consumption.

One of the main outputs of the aforementioned paper is reproduced in *Figure 1*. The figure shows the comparison of the several PoS-based DLTs in terms of energy consumption per transaction for different levels of throughput. It suggests that the energy consumption of different PoS-based DLTs may differ substantially, that the Bitcoin network offers a high energetic cost in contrast to PoS-based alternatives,² and that distributed options may compete with centralised systems such as VisaNet also on energy terms.

 $^{^{\}rm 2}$ The paper shows that, for the same amount of transactions, the energy cost can be between 400 and 100,000 times lower.




Figure 1

Throughput and energy consumption per transaction in Platt et al (2021: 1140). The lower boundary for each curve indicates the energy consumption under an optimistic validator hardware assumption while the upper boundary indicates a pessimistic scenario. The two points per DLT indicate the latest observation.

Replication and expansion

This article seeks to replicate, expand and update the work laid out by Platt et al (2021). The reasons for this are intuitive: replication is a fundamental aspect of the scientific process, two important blockchains had not been included in Platt et al (2021), Platt et al's paper was supported but a very limited number of observations, and there was no real-world data for post-Merge Ethereum in 2021.

The current article is thus designed as follows:

- The universe of PoS-based DLTs studied includes Algorand, Cardano, Ethereum 2.0, Hedera, Tezos and Polkadot, <u>but also Avalanche and Solana</u>. An update to this paper furthermore including BNB Chain, Elrond/MultiversX, Flow, NEAR, Toncoin and Tron is also under production.
- Real-world observations are taken for post-Merge Ethereum.³
- The original measurements included by Platt et al (2021) are replicated and used, but also other, newer, empirical observations. As a result, <u>the number of observations per</u> <u>DLT grows to 7 instead of 2</u> and covers a longer timeframe.
- With a greater number of observations available, we do not just extrapolate an affine function from two points but <u>conduct a linear regression</u> to describe the association between throughput and the number of validators.
- <u>An additional assumption is introduced that with a throughput of zero, the number of validators is also zero</u>. This is included as an observation at t₀ in the aforementioned regression.

³ Note that we take Ethereum's "node count" (<u>https://www.ethernodes.org/</u>) and not its "validator count" (<u>https://ethereum.org/en/staking/</u>), the latter of which does not adequately reflect the network's number of validator nodes.

- The same methodology is employed to estimate Bitcoin's energy consumption, but the Cambridge Centre for Alternative Finance's <u>data is updated</u> (CCAF, 2022).
- The same methodology is employed to estimate VisaNet's energy consumption, but the <u>latest Visa energy report</u> (VISA, 2021) is used.
- The assumption that throughput and the number of validators are positively correlated is maintained.
- The <u>lower and upper bounds for the power demand of a validator are improved and updated</u> where possible by resorting to empirical measurements for each DLT (Gallersdörfer et al, 2022: 15; CCRI, 2022b: 23), except where they contradict official estimates (Solana Foundation, 2022a, 2022b). Where new data is unavailable, the bounds are assumed to be the same as in Platt et al (2021). *Table III* (Appendix) specifies both bounds for each DLT.
- The <u>maximum throughput figures are reviewed</u> through a bibliography review via online search engines. Where maximum recorded throughput exceeds our sources for maximum throughput estimates,⁴ the former records are preferred. This resulted in an upward revision of Tezos' and Algorand's maximum throughput and a downward revision of Ethereum's maximum throughput (before sharding).

Methodology

The first step in our methodology is to observe the number of validators (n_{val}) and throughput (l) for a given DLT at a given moment in time (see dates in *Table VIII*, <u>Appendix</u>). A function extrapolating the relationship between the two variables is built therefrom, specifically with n_{val} as a function of l. The n_{val} variable is then translated to an energy consumption value using different assumptions on the possible electricity usage per validator. By introducing the number of transactions as a denominator, the energy consumption "per transaction" is arrived at.

The energy consumption of a given validator, called p, depends on the hardware used. The product between p and n_{val} is the energy cost of the network with that specific configuration of hardware and number of validators. If we divide this energy consumption by the number of transactions in the corresponding period, we obtain the consumption per transaction (Platt et al, 2021).

Energy consumption per transaction is however only comparable at the same level of throughput, with comparisons that exclude this denominator being misleading. For this reason, energy consumption is modelled as a function of throughput, whereby the number of validators depends on the number of transactions. The hypothesis, which Platt et al (202) find to have some empirical support and hence plausibility, is that as more users join a network, "of the new users, a share becomes validators and another non-disjoint share executes transactions, meaning that n_{val} and l are positively correlated" (Platt et al, 2021: 1137).

$$fc_{tx}(l) = \frac{(N_{val} \times p)}{l}$$

⁴ E.g. <u>https://metrics.algorand.org/#/protocol/</u>

$$N_{val} = Number of validators$$

 $p = Energy consumption per validator$
 $l = Transactions per second (throughput)$

Although the precise information of the hardware (and, hence, the energy consumption) of each validator is not available, we seek to improve upon the optimistic and pessimistic energy consumption thresholds proposed by Platt et al (2021) as described in section <u>Replication and expansion</u>.

As a result, we obtain a function describing the n_{val} of each DLT for a given level of *l*. The number of validators is then translated to a *p* range using the aforementioned thresholds. The domain of the function is defined by the energy consumption at the maximum postulated throughput without layer 2 solutions, which can be seen in *Table VII* (Appendix).

Platt et al (2021) proposed an affine function relating the number of validators on the DLT and its throughput. We do the same, and assume it is valid to use a linear regression to adjust the following model:

$$N_{val} = k \times \lambda l$$

This gives the next expression:

$$fc_{tx}(l) = \frac{(k \times \lambda l) \times p}{l}$$

For Platt (2021) two values were derived for affining k and λ , resulting in the next table;

Platform	k	λ
Algorand	102.8	103.9
Cardano	1267.8	2959.2
Polkadot	297	0
Tezos	440.7	-24.6
Hedera	7.6	0.3

Table I

Estimates for k and λ for different DLT platforms used in (3) to model the number of validators depending on the number of transactions per second, Table III Platt et al (2021: 1138).

Our new values for k and λ can be observed in *Figure 2* (section <u>Results</u>).

Limitations

As a replication study, this article brings forward some of the limitations already outlined by Platt et al (2021: 1137-1140):

"We therefore only consider validators (...) The overall number of nodes, including other full nodes that replicate the transaction history without participating in consensus, is likely higher for all systems analysed."

"We have used broad consumption ranges to model the energy consumption of individual validator nodes. While we are confident that the actual energy consumption is in fact within these ranges, the underlying characteristics of different PoS protocols that might impact energy consumption, such as the accounting model, have been ignored."

"While assuming that the electricity consumption of a validator node is independent of system throughput is well justified for the permissionless systems analysed [32], permissioned systems that are designed to support high throughput may not warrant such an assumption."

"We have not so far distinguished between transaction types."⁵

"While our model suggests that PoS systems can remain energy-efficient while scaling up to VisaNet throughput levels, there is no hard evidence in support of this argument, as, to our knowledge, no DLT-based system has experienced a sustained volume of this magnitude to date on the base level."

"We ignored the possibility of achieving effectively higher throughput than the specified maximum through layer 2 (L2) solutions, such as the Lightning Network or via optimistic rollups and zero-knowledge (zk)-rollups that are receiving increasing attention"

We may furthermore identify the following limitations:

Univariable model and predictive power

This paper models n_{val} as a function of a single variable, namely *l*. In doing so, it does not seek to achieve maximal predictive power. We are aware that many factors may influence n_{val} and do not seek to construct a complex and comprehensive model to predict the evolution of this variable. Rather, we undertake an exploratory task by attempting to conduct a first approximation to meaningful energy consumption comparisons, understanding that it is essential to control for *l* (and that it is plausible to expect throughput to impact the number of validators).

⁵ Exploring this further is an area for <u>Future work</u>. For instance, the site Metrika (<u>https://app.metrika.co/</u>) distinguishes multiple transaction types for Hedera (Crypto Create Account, HCS, HTS - Fungible Tokens, HTS - NFTs, Smart Contract, File) and Algorand (Stpf, Keyreg, Afrz, Acfg, Appl, Pay, Axfer).

A high R^2 is thus not expected for all DLTs. A low R^2 should be considered both a legitimate and natural result, but also a limitation on the ability to predict based on this model.

Linearity

This paper assumes both the relationship

- 1. between n_{val} and l; and
- 2. between n_{val} and p

to be linear. This replicates the methodology established in Platt et al (2021). This is assumed because we find it plausible that:

- 1. as more users join a network to execute transactions, a share of them becomes validators (Platt et al, 2021);
- 2. the main source of a node's electricity consumption is its idle consumption and replicated execution, which (unlike the number of edges between nodes, i.e. network complexity) evolve linearly with n_{val} .

However, if:

- 1. the evolution of n_{val} depending on l could be better explained as a polynomial function; and/or
- 2. there were significant performance/efficiency degradation with network scale/complexity within the function domain,⁶

this could have implications for our findings. In the first case, there would be a need for proper curve-fitting and interpretation, requiring an in-depth evaluation of the characteristics of each DLT. In the second case, our model would unfairly benefit DLTs that are relatively smaller at the time of observation, and should be amended to consider that energy consumption evolves quadratically with the number of validators. Nevertheless, we assume that performance stays within reasonable boundaries for the range of n_{val} values under study (i.e. n_{val} values corresponding to l values lower within the domain established by *Table VII* in the <u>Appendix</u>).

Our findings (see <u>Results</u>) already suggest that, for some local periods in the short run, some of the DLTs under study do not display a linear relationship between n_{val} and l. For the period studied, for instance, Polkadot maintained a fixed number of 297 validators, meaning that l rose and fell independently of n_{val} . Hedera also maintained fixed numbers of validators, which it periodically increased with the addition of new Council members; in some periods, a fall in l meant there were negative relationships between n_{val} and l. However, and even if this may reduce the R², we believe that the function positively associating n_{val} and l plausibly holds in the long term,⁷ as a scenario where throughput falls and yet more and more validators join the network seems unsistainable in the long run. This would suggest that the energy consumption of these DLTs might be overestimated in this paper.

⁶ See also SedImeir et al (2021).

⁷ This statement applies both generally and to the aforementioned DLTs in particular, considering that the plans to grow Polkadot to 1,000 validators (Polkadot 2022) and for Hedera's "step function" (Harmon, 2022).

Data availability

The methodology used to compute the validator count may differ across the sources used in this paper (*Table IV*, <u>Appendix</u>). For instance, Solana Foundation's (2022c)⁸ validator count includes "delinquent" consensus nodes which other sources do not consider as current nodes.⁹ To avoid a slippery slope, we take validator count figures at face value. Data availability also means that different sources are used to compute the ranges for validator power consumption for Ethereum (CCRI, 2022), Hedera (Platt, 2021), Solana (Gallersdörfer et al, 2022; Solana Foundation, 2022a, 2022b) and the other DLTs (Gallersdörfer et al, 2022).¹⁰ Future work should obtain comparable real-world data for all other DLTs.

Sometimes available data sources differed and we were unable to ascertain the reason therefor. Specifically, for Polkadot, Polkastats¹¹ throughput data differed from Subscan¹² data; we resorted to the former for consistency as Polkastats also provides validator count data. However, when past values displayed at Polkastats were not retrievable through web archive search engines, we used Subscan. On that note, it should be highlighted that, unlike throughput data (for which both current and past data was usually available), historic validator count data was rarely available, which hampered data collection. We resorted to web archives where needed to mitigate this issue.

Observation period and observation randomness

Due to manpower limitations, the dates of empirical observations of the number of validator nodes and throughput are not distributed homogeneously. Nevertheless, observation dates were randomly chosen in the sense that no specific pattern was involved in their selection other than data availability and the availability of the research team.

Because of this, and our experience of a marginally decreasing usefulness of each additional data point introduced, we are confident that the introduction of additional measurements within the observation period will not substantially change the results of this paper. Nevertheless, we encourage replication.

However, the observation window is in itself a limitation indeed. It barely exceeds one year, which we deem as insufficient to ideally derive a function describing the evolution of n_{val} with l, especially considering that in the short run many other factors may affect the evolution of n_{val} and l (see <u>Discussion</u>). For this reason, this paper will continue to be updated with additional observations following the release of the working paper, to improve the density and quality of the data.

⁸ <u>https://solanabeach.io/</u>

⁹ <u>https://solscan.io/validator</u>

¹⁰ In the upcoming update to this paper, we also take Platt et al (2021) as a source for Elrond/MultiversX, Flow, NEAR and Toncoin, but we use different sources for Binance Smart Chain (Opentaps, 2022 and Gallersdörfer et al, 2022).

¹¹ <u>https://polkastats.io/</u>

¹² <u>https://polkadot.subscan.io/transfer</u>

Additionally, the reader should note that observations for Ethereum cover only a fraction of the observation period for other DLTs, as Ethereum is only considered in the post-Merge period.

Data comparability

In the year 2022, one of the networks studied – Solana – suffered several public relations scandals (Nambiampurath, 2022), one of which impacts the source data used in this article. Specifically, it became known that Solana's most widely circulated throughput figures include a combination of both "vote" and "nonvote" transactions, the majority of which were the former. While it is technically true that vote transactions are transactions in Solana, many argued that they should be excluded from Solana's tps count, as vote transactions are a part of the consensus mechanism, and not "real" transactions in the meaningful sense that enables comparison with DLTs (SolanaFM, 2022; Zhu, 2022). To address this issue, we switched to a different data source that counts only nonvote transactions (https://solana.fm/). For observations executed before the scandal, we apportioned Solana's tps in the proportion of nonvote transactions to total (vote + nonvote) transactions for the observation day according to https://analytics.solscan.io/ (see Table V in Appendix). For Solana's maximum throughput, we divided Solana's maximum postulated throughput in official sources by the average ratio of nonvote transactions to total (vote + nonvote) transactions.

Energy consumption "per transaction"

Our methodology does not account for transaction complexity, and relies on an unrealistic assumption that either one transaction is equal to any other in terms of both value and energy consumption, or that the distribution of transaction complexity is comparable across DLTs. <u>Future work</u> should seek to incorporate this nuance in its modelling and observations.

Furthermore, the reader should note that the measurement of energy transaction on a "per-transaction" basis has in itself been criticised, particularly when used to benchmark against Bitcoin Core (see Carter, 2021; Saylor, Carter and Feinstein, 2022). The "per-transaction" basis is used in this paper as it constitutes the standard proxy for energy intensiveness used to in the field for comparison purposes, and its usage for comparison purposes has some plausibility, as transactions may be considered a driver of energy consumption¹³ in PoS-based DLTs.

However, usage of this metric should not be taken to mean that the number of transactions processed is a direct and proximate cause of energy consumption, especially for PoW systems. Bitcoin's energy consumption is almost entirely a subproduct of mining, which in turn depends on Bitcoin's price, that only depends on the number of transactions in a very indirect manner (Saylor, Carter and Feinstein, 2022).

Most importantly, Bitcoin advocates are concerned that the "per-transaction" metric is misused to suggest that if Bitcoin already consumes an already significant amount of energy with low throughput, it will need to consume an even greater amount of energy to replace

¹³ See above the assumption that throughput drives adoption by user, which drives n_{val} .

higher throughput systems like VisaNet. This is not the case because (a) throughput is not the cause of Bitcoin's electricity consumption; (b) Bitcoin's low layer-1 (L1) throughput is enshrined in its parameters, i.e. it is a protocol limitation by design; (C) therefore, Bitcoin could scale arbitrarily without increasing its energy usage by changing its parameters or adopting L2 solutions such as the Lightning Network, meaning it may even scale its "value settled" arbitrarily without scaling its energy consumption (Saylor, Carter and Feinstein, 2022).

We do not make any of these claims and moreover consider some of them partially applicable to PoS-based DLTs as well. In this context, the "per-transaction" metric is introduced as a useful proxy for comparison purposes, which has value within these limitations.

Trade-offs and fairness

This paper does not consider other variables such as network security, fault-tolerance, ordering fairness, access fairness, timestamping fairness, decentralisation of state maintenance,¹⁴ decentralisation of digital asset distribution, risk of capture, censorship-resistance, etc. (Madsen, 2019; Baird, Luykx and Madsen, 2020; Biner, 2022; Saylor, Carter and Feinstein, 2022). Consequently, the trade-offs between these variables and energy consumption are outside the scope of this paper; any comparison assuming otherwise would not consitute a fair assessment.¹⁵

In addition, there is a sense of efficiency whereby what matters is the (throughput-controlled) energy consumption per transaction "per validator." algorithm efficiency. This paper does not use this metric because the number of validators is already controlled by modelling many possible values of n_{val} , and because energy consumption is a proxy of environmental impact,¹⁶ a variable that its interesting as a whole (total energy consumption) or in terms of cost-benefit (energy consumption per transaction) but not directly in terms of how many validator participated in its generation (energy consumption per transaction per validator). Nevertheless, learning the efficiency of the PoS algorithm itself is of indirect environmental value and, shall comparable testing conditions be built (see <u>Future work</u> and Gallersdörfer et al, 2022), their investigation should be encouraged.

Despite these limitations, we are confident that this article accurately replicates, expands, and updates the methodology proposed by Platt et al (2021) and that this constitutes a substantial contribution to the state of the art.


¹⁴ This includes the relationship between decentralisation and membership size, see Vergne (2020).

¹⁵ In an extreme scenario, a naïve application of this paper's methodology could be misused to make a broken, unfair and unsafe system "look good" because of its very low energy consumption. The reader should note, however, that although unfairly misused, stating the fact of the broken system's low energy consumption would nonetheless be "true" and energy consumption is the only variable within the scope of this paper.


¹⁶ Insofar GHG emissions are assumed to be the same, which may not be the case (Ibañez and Freier, 2023).

Results

The replication and update of the paper provided the results (global and per transaction energy consumption estimations) that can be observed Table VIII (Appendix). With these measures we re-adjust the k and λ , resulting in the following:



Replication of function estimates for $fc_{tx}(l)$, i.e. update of table III of Platt et al (2021: 1138).






Figure 3

Extrapolation of throughput-controlled energy consumption per transaction. For each system's range, the lower boundary indicates the energy consumption under an optimistic validator hardware assumption while the upper threshold indicates a pessimistic scenario.

Discussion

With these findings, we reaffirm the usefulness of the energy consumption estimation methodology introduced in Platt et al (2021), and suggest improvements. We confirm that the energy consumption of PoS-based DLT systems is several orders of magnitude lower than that of Bitcoin Core, and the potential combinations of throughput and energy consumption for PoS-based DLTs are on par, if not superior, to VisaNet in terms of energy efficiency.

consumption. Ethereum's latest global energy consumption is estimated to range 963 kW to 33 kW, whereas its energy consumption per transaction is estimated between 0.02095 kWh and 0.0007188724 kWh, which compares to the range expected by Platt et al (2021: 1139): 445.3 to 14.6 and 0.00803 to 0.00026, respectively. This means that the global energy consumption for Ethereum has fallen as expected but the energy consumption per transaction has decreased further than anticipated.We observe that "The Merge" led to a significant decrease in Ethereum's energy

We observe that not all PoS-based DLTs are born equal, and that this statement holds in various different dimensions:

- In terms of their absolute energy consumption.
- In terms of their energy consumption per transaction.
- In terms of their energy consumption per transaction for a given level of throughput.
- In terms of the shape of the function describing the evolution of their energy consumption per transaction with throughput.

The progressive addition of additional data points also allowed us to observe that the after the fifth data point. This is not to be interpreted as disregarding the need for more data: strongly to the contrary, more data would be highly beneficial to this model and its improvement. However, it suggests that additional data should be incorporated *over a longer period of time*. In contrast, the addition of further data points in the time period already studied is not expected to materially affect the findings.marginal improvements in the resulting energy consumption functions were not substantial

We also observe that the R² of the functions describing the correlation of throughput with the number of validators varies significantly across DLTs. This implies that variation in the energy consumption of the DLTs under study may be caused by many other factors other than network throughput, and that this paper only uncovers a part of this variables behavior. We hold thus that this paper produces a comparison of throughput-controlled energy consumption that is valid and useful, but also seriously limited as a predictor and should not be treated as such.

Specific observations about particular DLT networks may be formulated. We note that Solana's energy consumption per transaction (relative to its peers) is substantial at low throughput; however, it is estimated to be significantly more efficient, in relative terms, at high levels of throughput.

We may also note that the curve describing Polkadot's energy consumption per transaction is slightly flatter than than its peers' and than itself in Platt et al (2021). This may be

attributed at the current 297 validator cap that was in place during the entire observation period for both this paper and Platt et al's. In the latter, global energy consumption was estimated to be constant, with the energy consumption per transaction decreasing with throughput increases, as a result. In our paper, the assumption of zero throughput with zero validators changes this, producing a different function to describe Polkadot's behavior. However, as long as the validator cap is on place, the values this function may be safely assumed to change substantially with the number of observations in the same period, because the intercept will have a greater "weight" in the computation of the function with a smaller number of observations. For reasons explained at the beginning of this paper, we believe our assumption to result in a more plausible function than Platt et al's. Nevertheless, the utility of the function remains very limited and only effectuating observations in the long run¹⁷ may improve it.

Both in this study and in Platt et al (2021), Cardano is consistently shown to be one of the DLTs with the highest energy consumption in relative terms (despite being negligible in all cases). Although further research would be required to confirm this, this may be due the high number of validators and comparatively low throughput that it displayed throughout the entire observation period. This could be hypothesised to be related to Cardano's usage of the UTXO model (Platt et al, 2021) at a low block size.

We have noted a series of <u>Limitations</u> to our methodology and encourage the reader to familiarise with them, as well as <u>Future work</u> to be focused in addressing them.

To continue improving the work presented in this article, data collection will continue after the release of this working paper. Furthermore, the source data and methodology is made available for free at the <u>Online Appendix</u>, to encourage feedback, replication and expansion of the work presented in this article.

Finally, we note that it is of interest to the blockchain ecosystem to obtain simple figures comparing the energy consumption per transaction and the throughput and validator value for the various DLTs. If we take the latest observation ("contemporary" observation in Platt et al, 2021) and average out lower and upper bounds for energy consumption, we obtain the following:

DLT	Global energy consumption (kW)	Energy consumption / tx (kWh)	TPS	Validators
Algorand	106.82	0.003411	8.70	1,227
Avalanche	101.62	0.002395	11.79	1,209
Bitcoin	92,325,000,000.00	2,927	2.56	10,000+
BNB Chain	7.02	0.000059	33.4	56
Cardano	142.63	0.041270	0.96	1,209
Elrond/ MultiversX	277 76	0.102875	0.75	3,200
Wullive 3A	211.10	0.102075	0.75	5,200
Ethereum	450.15	0.009956	12.56	5,294

¹⁷ In this context, we define the long run as a time period long enough such that it exceeds the period in which the 297 validator cap is in place.

Flow	37.15	0.003318	3.11	428
Hedera	6.45	0.000003	568.45	26
Near	13.71	0.000602	6.33	158
Polkadot	16.66	0.035593	0.13	297
Solana	917.29	0.000517	493	2,512
Tezos	29.81	0.009203	0.90	407
Toncoin	21.18	0.001948	3.02	244
Tron	391.92	0.001202	33.40	56

Table II

Estimations for global and per-transaction energy consumption (average between upper and lower bound) and values for throughput and number of validators, in the latest observation.

Despite they are not considered for Figures 2 and 3 because data collection for these chains only started recently, we include the latest observation for BNB Chain, Elrond/MultiversX, Flow, NEAR, Toncoin and Tron, in anticipation of the next update to this paper.

However, we encourage the reader to use *Figure 3* instead, as energy consumption per transaction may be a misleading metric when the throughput that underlies the observation differs significantly.

Future work

As established also in Platt et al (2021), future work should consider factors such as transaction complexity, the energy consumption of non-validating nodes (e.g. auxiliary nodes), comparable empirical measurements for the actual hardware configurations in each DLT, and the effects of moving from a permissioned to a permissionless DLT setting. Future research should also expand even further the universe of PoS-based DLTs studied. In the upcoming update to this paper, once an additional period of data collection ends, Elrond/MultiversX, Flow, Near, Toncoin and Tron will be included, hence capturing the top 50 PoS-based DLTs by market cap at the time of release of this working paper.

We furthermore encourage researchers to undertake the complex task of building a more comprehensive model of n_{val} , depending not just on *l*, to achieve proper predictive capacity of not just n_{val} itself but also energy consumption. There is also much potential for additional work that does consider L2 solutions, as this paper assumes exclusively L1 technology.

Future work may also construct meaningful comparisons of (throughput-controlled) energy consumption per transaction "per validator," to better comprehend the nuances across different PoS algorithms, inefficiencies in implementation, etc. This should not be achieved by merely dividing energy consumption by the number of validators, however, but with physical measurements, by building test networks to impose comparable throughput levels, networking requirements and hardware requirements (see Gallersdörfer et al, 2021).

As anticipated earlier, there is also potential for future work whereby the goal is more ambitious, namely of *prediction* of energy consumption under different values for throughput. This would require curve-fitting, which is beyond the scope of our paper.

Finally, and as anticipated in the <u>Limitations</u> section, future research may explore nonlinear relationships between variables, efficiency degradation with scale, trade-offs of energy efficiency with other variables (such as decentralisation, security, fault-tolerance, fairness), and nuances with validator count figures across diferent sources, as well as both extend the observation period and introduce additional (random) observations within it.

Conclusion

With this article, we show that the model proposed by Platt et al (2021) for measuring the energy consumption of a PoS-based DLT is replicatable. We suggest improvements and furthermore expand the model with additional DLTs, data and assumptions. Overall, we confirm the core finding of Platt et al (2021) that, regardless of the nuances and differences across PoS-based DLTs, all of the PoS-based DLTs analysed have an energy consumption that is negligible compared to that of major PoW blockchains. To the extent that energy consumption may be considered problematic, this is not an issue in any PoS design.

We invite the scientific community to further expand this work, and encourage DLT foundations to share with us further data to iterate this model.

Acknowledgments

We thank Jiahua Xu and Paolo Tasca for their invitation and support to write his entry. We thank Emin Gün Sirer for the comments provided to the co-authors of Platt et al (2021) which enriched this article as well.

COI statement

Juan Ignacio Ibañez was one of the original co-authors in the paper by Platt et al (2021), as well as one of the co-authors in the current article. Both authors are affiliated to the UCL Centre for Blockchain Technologies (UCL CBT), which maintains professional and institutional relationships with organisations promoting the several of the DLTs under review.

Literature

- Baird, L.; Luykx, A.; Madsen, P. (2020) "Hedera Technical Insights: Fair Timestamping and Fair Ordering of Transactions." <u>Hedera</u>. Available at <u>https://hedera.com/blog/fair-timestamping-and-fair-ordering-of-transactions</u>
- Biner, M. R. (2022) "Fair transaction order in Hedera Hashgraph." *University of Bern*. Available at https://crypto.unibe.ch/archive/theses/2021.bsc.matteo.biner.pdf
- Carter, N. (2021) "How Much Energy Does Bitcoin Actually Consume?" *Harvard Business Review.* <u>https://hbr.org/2021/05/how-much-energy-does-bitcoin-actually-consume</u>

- CCAF (2022) "Cambridge Bitcoin Electricity Consumption Index." *Cambridge Centre for Alternative Finance*. Available at <u>https://ccaf.io/cbeci/index</u>
- CCRI (2022a) "Energy Efficiency and Carbon Footprint of the TRON Blockchain." *Crypto Carbon Ratings Institute*. Available at <u>https://carbon-ratings.com/tron-report-2022</u>
- CCRI (2022b) "The Merge Implications on the Electricity Consumption and Carbon Footprint of the Ethereum Network." *Crypto Carbon Ratings Institute*. Available at <u>https://carbon-ratings.com/dl/eth-report-2022</u>
- Douceur, J. R. (2002) "The Sybil Attack." In International Workshop on Peer-to-Peer Systems (IPTPS 2002), 251-260.
- Gallersdörfer, U.; Klaaßen, L.; Stoll, C. (2022) "Energy Efficiency and Carbon Footprint of Proof of Stake Blockchain Protocols." *Crypto Carbon Ratings Institute (CCRI)*. Available at <u>https://carbon-ratings.com/dl/pos-report-2022</u>
- Harmon, M. (2022) Interview by Godschalk, Z., min. 19:55. In "Hedera Community Town Hall | March 2022," *Hedera*. Available at <u>https://youtu.be/dnJGrnkBd3s?t=1195</u>
- Ibañez, J. I.; Freier, A. (2023) "SoK: Bitcoin, Energy Consumption and Environmental Impact." *Arxiv*. Forthcoming.
- Madsen, P. (2019) "Fair Access v. Fair Ordering, & Transactions Per Second Examined & Explained." *Hedera*. Available at <u>https://hedera.com/blog/fair-access-v-fair-ordering-and-transactions-per-second-exa</u> mined-and-explained
- Mollah, M. B.; Zhao, J.; Niyato, D.; Lam, K.-Y.; Zhang, X.; Ghias, A. M. Y. M.; Koh, L. H.; Yang, L. (2021) "DLT for Future Smart Grid: A Comprehensive Survey." *IEEE Internet* of Things Journal, 8(1), 18–43.
- Nambiampurath, R. (2022) "Solana Is Deceptively Designed to Falsely Inflate Usage,' Alleges Crypto Researcher." *BeinCrypto*. Available at <u>https://beincrypto.com/solana-deceptively-designed-falsely-inflate-usage-alleges-cryp</u> to-researcher/
- Opentaps (2022) "Estimating the Energy Impact of the Binance Smart Chain." *Opentaps*. Available at

https://opentaps.org/2022/03/24/estimating-the-energy-impact-of-the-binance-smart-c hain/

- OSTP (2022) "Climate and Energy Implications of Crypto-assets in the United States." *White House Office of Science and Technology Policy (OSTP)*. Available at https://www.whitehouse.gov/wp-content/uploads/2022/09/09-2022-Crypto-Assets-and -Climate-Report.pdf
- Patel, S. T.; Mistry, N. H. (2017) "A review: Sybil attack detection techniques in WSN." In 2017 4th International Conference on Electronics and Communication Systems (ICECS), 184-188.
- Piro, C.; Shields, C.; Levine, B. N. (2006) "Detecting the Sybil Attack in Mobile Ad hoc Networks." In 2006 Securecomm and Workshops, 1-11.
- Platt, M.; Sedlmeier, J.; Platt, D.; Xu, J.; Tasca, P.; Vadgama, N.; Ibañez, J. I. (2021) "Energy Footprint of Blockchain Consensus Mechanisms Beyond Proof-of-Work." 2021 IEEE 21st International Conference on Software Quality, Reliability and Security Companion (QRS-C), pp. 1135-1144.
- Polkadot (2022) "Introduction to Staking." *Polkadot Wiki*. Available at <u>https://wiki.polkadot.network/docs/learn-staking</u>
- Saylor, M.; Carter, N.; Feinstein, D. (2022) "Bitcoin Letter to the Environmental Protection Agency." *Bitcoin Mining Council.* Available at

https://bitcoinminingcouncil.com/wp-content/uploads/2022/05/Bitcoin_Letter_to_the_ Environmental Protection Agency.pdf

SedImeir, J.; Ross, P.; Luckow, A.; Lockl, J.; Miehle, D.; Fridgen, G. (2021) "The DLPS: A New Framework for Benchmarking Blockchains." In *Proceedings of the 54th Hawaii International Conference on System Sciences*, 6855-6864.

SolanaFM (2022) "SolanaFM." SolanaFM. Available at https://solana.fm/

- Solana Foundation (2022a) "Data files/analysis for Solana climate report." Raw data for Solana's Energy Use Report. *Github*. Available at <u>https://github.com/Othersphere/solana-climate</u>
- Solana Foundation (2022b) "Solana's Energy Use Report: September 2022." Solana. Available at <u>https://solana.com/es/news/solanas-energy-use-report-september-2022</u>
- Solana Foundation (2022c) "Validator Health Report: August 2022." *Solana*. Available at <u>https://solana.com/news/validator-health-report-august-2022</u>
- Thomson Reuters (2022) "Cryptos on the rise 2022." *Thomson Reuters*. Available at <u>https://www.thomsonreuters.com/en/reports/cryptos-on-the-rise-2022.html</u>
- Trifa, Zied; Khemakhem, Maher (2014). <u>"Sybil Nodes as a Mitigation Strategy Against Sybil Attack"</u>. *Procedia Computer Science*, 32: 1135–40.
- Vergne, J. P. (2020) "Decentralized vs. distributed organization: blockchain, machine learning and the future of the digital platform." *Organization Theory*, 1(4).
- VISA (2021) "2021 Environmental, Social & Governance Report." VISA. Available at https://usa.visa.com/content/dam/VCOM/regional/na/us/about-visa/documents/2021environmental-social-and-report.pdf
- Zhu, A. (2022) "Real TPS." Available at https://realtps.net/

BTC	Bitcoin Core
DLT	Distributed Ledger Technology
GHG	Greenhouse Gas
L1	Layer-1
L2	Layer-2
PoS	Proof-of-Stake
PoW	Proof-of-Work
Тх	Transaction
Tx/s or tps	Transactions per second
UCL CBT	UCL (University College London) Centre for Blockchain Technologies
UTXO	Unspent Transaction Output

Appendix

DLT	Lower bound (W)	Source	Upper bound (W)	Source
Algorand	5.53	Measurement in lab setting (Gallersdörfer et al, 2022: 15)	168.59	Measurement in lab setting (Gallersdörfer et al, 2022: 15)
Avalanche	23.44	Measurement in lab setting (Gallersdörfer et al, 2022: 15)	144.67	Measurement in lab setting (Gallersdörfer et al, 2022: 15)
BNB Chain	29.25	Minimum possible value in Gallersörfer et al (2022: 15) for the hardware options estimated by Opentaps (2022)	221.33	Maximum possible value in Gallersörfer et al (2022: 15) for the hardware options estimated by Opentaps (2022)
Cardano	3.90	Measurement in lab setting (Gallersdörfer et al, 2022: 15)	84.47	Measurement in lab setting (Gallersdörfer et al, 2022: 15)
Elrond/ MultiversX	5.50	Estimate of typical power consumption for a small singleboard computer Raspberry Pi 4 (Platt et al, 2021: 1138)	168.10	Estimate of typical power consumption for a general-purpose rackmount server Dell PowerEdge R730 (Platt et al, 2021: 1138)
Ethereum	20.00	Measurement in lab setting (CCRI, 2022b: 23)	150.06	Measurement in lab setting (CCRI, 2022b: 23)
Flow	5.50	Estimate of typical power consumption for a small singleboard computer Raspberry Pi 4 (Platt et al, 2021: 1138)	168.10	Estimate of typical power consumption for a general-purpose rackmount server Dell PowerEdge R730 (Platt et al, 2021: 1138)
Hedera	168.10	Estimate of typical power consumption for a general-purpose rackmount server Dell PowerEdge R730 (Platt et al, 2021: 1138) ¹⁸	328.00	Power consumption under 80% load for a high-performance server Hewlett Packard Enterprise ProLiant ML350 Gen10 (Platt et al, 2021: 1138)
NEAR	5.50	Estimate of typical power consumption for a small singleboard computer Raspberry Pi 4 (Platt et al, 2021: 1138)	168.10	Estimate of typical power consumption for a general-purpose rackmount server Dell PowerEdge R730 (Platt et al, 2021: 1138)
Polkadot	4.31	Measurement in lab setting (Gallersdörfer et al, 2022: 15)	107.86	Measurement in lab setting (Gallersdörfer et al, 2022: 15)
Solana	221.33	Measurement in lab setting (Gallersdörfer et al, 2022: 15)	509.00	Official average power consumption estimation (Solana Foundation, 2022a)
Tezos	4.86	Measurement in lab setting (Gallersdörfer et al, 2022: 15)	141.65	Measurement in lab setting (Gallersdörfer et al, 2022: 15)
Toncoin	5.50	Estimate of typical power consumption for a small singleboard computer Raspberry Pi 4 (Platt et al, 2021: 1138)	168.10	Estimate of typical power consumption for a general-purpose rackmount server Dell PowerEdge R730 (Platt et al, 2021: 1138)
Tron	16.80	Measurement in lab setting (CCRI, 2022a: 13)	123.50	Measurement in lab setting (CCRI, 2022a: 13)

Table III

Conceivable upper and lower bounds for the power consumption of the average validator of each PoS-based DLT under study.

¹⁸ See <u>https://docs.hedera.com/guides/mainnet/mainnet-nodes/node-requirements/reference-configuration</u>

Platform	Validators	Throughput	Variable taken for throughput calculation
Algorand	https://algoexplorer.io/	https://metrics.algorand.org/	Transactions per second (last 24 hours)
Avalanche	<u>https://su</u>	https://subnets.avax.network/	
BNB Chain	https://bscscan.com/valida	tors https://bsctrace.com/	Transactions per second (last 5 minutes)
Cardano	https:/	//cardanoscan.io/	Transactions per day
Elrond/ MultiversX	https://multiversx.com/	https://explorer.elrond.com/	Transactions per day
Ethereum	<u>https://www.ethernodes.or</u> g/history	https://etherscan.io/chart/tx	Transactions per day
Flow	<u>https://flowscan.org/stakin</u> g/overview	https://flowscan.org/metrics/blocks	Transactions per day
Hedera	https://status.hedera.com/	https://hedera.com/dashboard	Transactions per day
NEAR	https://	/explorer.near.org/	Transactions per day
Polkadot	https://polkastats.io/es	https://polkadot.subscan.io/extrinsic; https://polkastats.io/es	Transactions per day
Solana	Solana Foundation (2022c), ¹⁹ <u>https://solscan.io/validator</u>	https://analytics.solscan.io/, https://solana.fm/	Transactions per hour; Transactions per second
Tezos	https://tzstats.com/bakers	https://tzstats.com/	Transaction per day
Toncoin	https://ton.org/	https://tonapi.io/	Transactions over 60 seconds (empirical observation)
Tron	https://tronscan.org/#/bloc kchain/nodes	https://tronscan.org/#/blockchain/tran sactions	Transactions per day
Platform	Energy consumption	Throughput	Variable definition
Bitcoin	https://ccaf.io/cbeci/index	https://www.blockchain.com/explorer	Tps (last day) - Annual energy consumption in GJ
Visa	https://usa.visa.com/conte nt/dam/VCOM/regional/na/ us/about-visa/documents/2 021-environmental-social- and-report.pdf	https://usa.visa.com/run-your-busines s/small-business-tools/retail.html	Tps (not specified) - Annual energy consumption in TWh
		- // n/	

Table IV

Sources for the data used. Where unavailable, past snapshots from Wayback Machine were used.

¹⁹ We contacted the Solana Beach team for the source data used at Solana Foundation (2022c). As we did not obtain a response, we resorted to screen scraping techniques to obtain Solana's historical validator count.

Platform	Time Period		Annual Ene	ergy	Energy per second	Tx/s	Energy per tx
		Source	measure	kWh	kWh		kWh/tx
Visa	2021	646000	GJ	179,439,420.0 0	5.69	1736	0.00328
Bitcoin Iower	2022	50.41	TW/h	50,410,000,00 0.00	1598.49	2.56	624.0
Bitcoin upper	2022	134.24	TW/h	134,240,000,0 00.00	4256.72	2.56	1662.8

Table V

Estimation of energy consumption of Visa and Bitcoin (lower and upper bounds)

Tx/s observation	Date	Nonvote tx per day	Total tx per day	Average tx/s	Nonvote vs total tx ratio	Nonvote tx/s
1734	14/9/21	31,436,549	166,730,469	1,930	0.189	327
2227	30/3/22	26,040,310	179,416,101	2,077	0.145	323
2020	2/5/22	18,166,816	174,322,626	2,018	0.104	211
3363.	28/7/22	36,691,080	157,490,743	1,823	0.233	784
3338	9/26/22	35,338,176	185,904,800	2,152	0.190	635
3183	11/10/22	17,855,155	170,894,804	1,978	0.104	333
4123	11/12/22	172,633,381	309,222,640	3,579	0.056	230

Table VI

Calculation of past Solana nonvote throughput based on https://analytics.solscan.io/ and https://solana.fm/.

DLT	Source	Metric	Value
Algorand	https://metrics.algorand.org/#/protocol/	"Peak TPS:" Maximum number of transactions that occurred between two blocks over the past 60 days, divided by the block confirmation time.	6,192
Avalanche	https://support.avax.network/en/article s/5325146-what-is-transactional-throu ghput	Transactions per second	4,500
BNB Chain	https://bscscan.com/chart/tx	Maximum recorded transactions per second	188

Cardano	https://vacuumlabs.com/what-we-love- about-cardano-a-technical-analysis/	Transactions per second	257
Elrond/Multiv ersX	https://docs.elrond.com/welcome/welc ome-to-elrond/	Transactions per second	15,000
Ethereum	https://ethtps.info/	Maximum recorded transactions per second	115
Flow	https://developers.flow.com/flow/faq/o perators	Transactions per second	100
Hedera	https://hedera.com/hbar	Transactions per second	10,000
NEAR	https://near.org/papers/the-official-nea r-white-paper/	Transactions per second	2,000
Polkadot	https://twitter.com/gavofyork/status/12 55859146127179782	Transactions per second	1,000
Solana	https://twitter.com/solana/status/13345 65204449841153	Transactions per second * nonvote tx to total transaction ratio ²⁰	7,295
Tezos	https://forum.tezosagora.org/t/tezos-st orage-irmin-march-2022/4497	Transactions per second	1,048
Toncoin	https://coinmarketcap.com/currencies/ toncoin/	Maximum recorded transactions per second	65,000
Tron	https://tron.network/static/doc/white_p aper_v_2_0.pdf	Transactions per second	2,000

 Table VII

 Maximum throughput per DLT under study.

-

²⁰ Although there are claims of 710,000 tps (<u>https://solana.com/solana-whitepaper.pdf</u>), 400,000 tps (<u>https://solana.blog/seriously-how-fast-can-solana-blockchain-get</u>/), 100,000 tps (<u>https://twitter.com/solana/status/1156206130986536961</u>) and 65,000 tps (<u>https://twitter.com/solana/status/1242627295510056961</u>)</u>, we follow the claim of 50,000 tps, which appears to be most frequently (and recently) displayed in Solana's official social media.

DLT	period	date	validators	TPS	Global energy consumption lower bound	Global energy consumption upper bound	Average of global energy consumption bounds	Energy consumption per transaction lower bound	Energy consumption per transaction upper bound	Average of energy consumption per transaction bounds
Algorand	tO	-	0.00	0.00			-	0.000000	0.000000	
Algorand	t1	16/7/2021	1298.00	12.50	7.18	218.83	113.00	0.0002	0.004863	0.002512
Algorand	t2	12/8/2021	1126.00	9.84	6.23	189.83	98.03	0.0002	0.005359	0.002768
Algorand	t3	30/3/2022	1695.00	17.42	9.37	285.76	147.57	0.0001	0.004557	0.002353
Algorand	t4	22/12/2022	1613.00	11.07	8.92	271.94	140.43	0.0002	0.006824	0.003524
Algorand	t5	13/1/2023	1227.00	8.70	6.79	206.86	106.82	0.0002	0.006605	0.003411
Avalanche	t0	-	0.00	0.00			-	0.0000	0.000000	
Avalanche	t1	19/5/2021	888.00	6.21	20.81	128.47	74.64	0.0009	0.005746	0.003339
Avalanche	t2	30/3/2022	1389.00	10.18	32.56	200.95	116.75	0.0009	0.005483	0.003186
Avalanche	t3	2/5/2022	1564.00	9.04	36.66	226.26	131.46	0.0011	0.006953	0.004040
Avalanche	t4	8/12/2022	1197.00	23.44	28.06	173.17	100.61	0.0003	0.002052	0.001193
Avalanche	t5	13/1/2023	1209.00	11.79	28.34	174.91	101.62	0.0007	0.004121	0.002395
BNB Chain	tO	-	0.0	0.00			-	0.0000	0.000000	0.000000
BNB Chain	t1	24/12/2022	52.0	26.00	1.52	11.51	6.52	0.0000	0.000123	0.000070
BNB Chain	t2	24/12/2022	53.0	27.70	1.55	11.73	6.64	0.0000	0.000118	0.000067
BNB Chain	t3	3/1/2023	56.0	34.20	1.64	12.39	7.02	0.0000	0.000101	0.000057
BNB Chain	t4	11/1/2023	56.0	33.40	1.64	12.39	7.02	0.0000	0.000103	0.000059
Cardano	t0	-	0.0	0.00			-	0.0000	0.000000	0.000000

Cardano	t1	11/8/2021	2958.0	0.36	11.54	249.86	130.70	0.0089	0.192795	0.100848
Cardano	t2	30/3/2022	3218.0	1.40	12.55	271.82	142.19	0.0025	0.053933	0.028212
Cardano	t3	2/5/2022	3205.0	1.30	12.50	270.73	141.61	0.0027	0.057848	0.030260
Cardano	t4	7/12/2022	3232.0	0.88	12.60	273.01	142.81	0.0040	0.086176	0.045078
Cardano	t5	13/1/2023	3228.0	0.96	12.59	272.67	142.63	0.0036	0.078897	0.041270
Elrond/MultiversX	tO	-	0.0	0.00			-	0.0000	0.000000	0.000000
Elrond/MultiversX	t1	14/11/2022	3200.0	0.98	17.60	537.92	277.76	0.0050	0.152472	0.078731
Elrond/MultiversX	t2	21/12/2022	3200.0	0.96	17.60	537.92	277.76	0.0051	0.155648	0.080371
Elrond/MultiversX	t3	3/1/2023	3200.0	0.88	17.60	537.92	277.76	0.0056	0.169798	0.087677
Elrond/MultiversX	t4	11/1/2023	3200.0	0.75	17.60	537.92	277.76	0.0065	0.199230	0.102875
Ethereum	tO	-	0.0	0.00			-	0.0000	0.000000	0.000000
Ethereum	t1	4/10/2022	8307.0	13.72	166.14	1246.55	706.34	0.0034	0.025238	0.014301
Ethereum	t2	23/10/2022	7998.0	11.69	159.96	1200.18	680.07	0.0038	0.028519	0.016160
Ethereum	t3	16/11/2022	7845.0	12.54	156.90	1177.22	667.06	0.0035	0.026077	0.014777
Ethereum	t4	10/12/2022	6800.0	12.77	136.00	1020.41	578.20	0.0030	0.022196	0.012577
Ethereum	t5	13/1/2023	5294.0	12.56	105.88	794.42	450.15	0.0023	0.017569	0.009956
Flow	tO	-	0.0	0.00			-	0.0000	0.000000	0.000000
Flow	t2	21/12/2022	429.0	3.45	2.36	72.11	37.24	0.0002	0.005806	0.002998
Flow	t3	3/1/2023	428.0	3.11	2.35	71.95	37.15	0.0002	0.006426	0.003318
Flow	t4	11/1/2023	428.0	3.11	2.35	71.95	37.15	0.0002	0.006426	0.003318
Hedera	t0	-	0.0	0.00			-	0.0000	0.000000	0.000000
Hedera	t1	13/8/2021	20.0	44.60	3.36	6.56	4.96	0.0000	0.000041	0.000031

Hedera	t2	3/5/2022	25.0	38.00	4.20	8.20	6.20	0.0000	0.000060	0.000046
Hedera	t3	30/3/2022	25.0	29.70	4.20	8.20	6.20	0.0000	0.000077	0.000058
Hedera	t4	2/5/2022	25.0	19.90	4.20	8.20	6.20	0.0001	0.000114	0.000087
Hedera	t5	8/12/2022	23.0	7.48	3.87	7.54	5.71	0.0001	0.000280	0.000212
Hedera	t6	13/1/2023	26.0	568.45	4.37	8.53	6.45	0.0000	0.000004	0.000003
Near	tO	-	0.0	0.00			-	0.0000	0.000000	0.000000
Near	t1	14/11/2022	127.0	5.86	0.70	21.35	11.02	0.0000	0.001012	0.000523
Near	t2	21/12/2022	130.0	3.76	0.72	21.85	11.28	0.0001	0.001614	0.000834
Near	t3	3/1/2023	153.0	3.51	0.84	25.72	13.28	0.0001	0.002035	0.001051
Near	t4	11/1/2023	158.0	6.33	0.87	26.56	13.71	0.0000	0.001166	0.000602
Polkadot	tO	-	0.0	0.00	0.00		-	0.0000	0.000000	0.000000
Polkadot	t1	5/7/2021	297.0	0.12	1.28	32.03	16.66	0.0030	0.074154	0.038559
Polkadot	t2	30/3/2022	297.0	0.09	1.28	32.03	16.66	0.0040	0.098872	0.051412
Polkadot	t3	2/5/2022	297.0	0.07	1.28	32.03	16.66	0.0051	0.127121	0.066101
Polkadot	t4	8/12/2022	297.0	0.08	1.28	32.03	16.66	0.0044	0.111231	0.057838
Polkadot	t5	21/12/2022	297.0	0.06	1.28	32.03	16.66	0.0059	0.148307	0.077117
Polkadot	t6	13/1/2023	297.0	0.13	1.28	32.03	16.66	0.0027	0.068450	0.035593
Solana	tO	-	0.0	0.00			-	0.0000	0.000000	0.000000
Solana	t1	14/9/2021	1294.0	326.94	286.40	658.65	472.52	0.0002	0.000560	0.000402
Solana	t2	30/3/2022	1641.0	323.23	363.20	835.27	599.24	0.0003	0.000718	0.000515
Solana	t3	2/5/2022	1732.0	210.51	383.34	881.59	632.47	0.0005	0.001163	0.000835
Solana	t4	28/7/2022	3450.0	783.65	763.59	1756.05	1259.82	0.0003	0.000622	0.000447

Solana	t5	11/12/2022	1906.0	230.18	421.85	970.15	696.00	0.0005	0.001171	0.000840
Solana	t6	13/1/2023	2512.0	493.00	555.98	1278.61	917.29	0.0003	0.000720	0.000517
Tezos	tO	-	0.00	0.00			-	0.0000	0.000000	0.000000
Tezos	t1	5/2/2021	430.00	0.40	2.09	60.91	31.50	0.0015	0.042298	0.021875
Tezos	t2	12/8/2021	399.00	1.70	1.94	56.52	29.23	0.0003	0.009235	0.004776
Tezos	t3	30/3/2022	384.00	2.60	1.87	54.39	28.13	0.0002	0.005811	0.003005
Tezos	t4	2/5/2022	421.00	1.61	2.05	59.63	30.84	0.0004	0.010289	0.005321
Tezos	t5	8/12/2022	406.00	1.76	1.97	57.51	29.74	0.0003	0.009077	0.004694
Tezos	t6	13/1/2023	407.00	0.90	1.98	57.65	29.81	0.0006	0.017794	0.009203
Toncoin	tO	-	0	0	0	0	0	0	0	0
Toncoin	t2	44916	236	3.03	1.298	39.6716	0.649	20.4848	0.003637	0.001878
Toncoin	t3	44929	227	2.17	1.2485	38.1587	0.62425	19.7036	0.004885	0.0025225
Toncoin	t4	44937	244	3.02	1.342	41.0164	0.671	21.1792	0.003773	0.001948
Tron	t0	-	0	0	0	0	0	0	0	0
Tron	t2	44916	5420	86.1	91.056	669.37	45.528	380.213	0.00216	0.001227
Tron	t3	44929	5469	81.03	91.8792	675.4215	45.9396	383.65035	0.002315	0.001315
Tron	t4	44937	5587	90.52	93.8616	689.9945	46.9308	391.92805	0.002117	0.0012025

 Table VIII

 Set of observations and estimations derived therefrom on which this paper is based.

Online Appendix

Reader may verify and expand the model and observations by consulting the online appendix on Github.