Dynamic Regret of Distributed Online Frank-Wolfe Convex Optimization*

Wentao Zhang^a, Yang Shi^b, Baoyong Zhang^{a,*}, Deming Yuan^a

^aSchool of Automation, Nanjing University of Science and Technology, Nanjing 210094, Jiangsu, P. R. China ^bDepartment of Mechanical Engineering, University of Victoria, Victoria, BC, Canada, V8W 3P6

Abstract

This paper considers distributed online convex constrained optimization, in which various agents in a multi-agent system cooperate to minimize a global cost function through communicating with neighbors over a time-varying network. When the constraint set of optimization problem is high-dimensional and complicated, the computational cost of the projection operation often becomes prohibitive. To handle this problem, we develop a distributed online Frank-Wolfe optimization algorithm combining with gradient tracking technique. We rigorously establish the dynamic regret bound of the proposed optimization algorithm as $\mathcal{O}(\sqrt{T(1 + H_T)} + D_T)$, which explicitly depends on the iteration round T, function variation H_T , and gradient variation D_T . Finally, the theoretical results are verified and compared in the case of distributed online ridge regression problems.

Keywords: Distributed online convex optimization; Frank-Wolfe algorithm; dynamic regret; gradient tracking method.

1. Introduction

Recently, distributed optimization over multi-agent network has attracted much attention due to its wide applications, such as power systems, sensor networks, machine learning, etc (see, e.g., Nedić & Liu (2018), Yang et al. (2019), Li et al. (2022), Liu et al. (2020), Li et al. (2021), Xu & Soh (2016), Yuan et al. (2022), Xu et al. (2022)). In such an optimization problem, distributed online optimization can be described as a repeated game as follows:

- 1. At every round t, agent i first generates a decision $x_{i,t} \in X$.
- 2. Agent *i* suffers a loss $f_{i,t}(\boldsymbol{x}_{i,t})$ and the adversary reveals the information about loss function $f_{i,t}$.
- 3. Then, agent *i* uses the information about loss function $f_{i,t}$ to construct the next decision $x_{i,t+1}$.

The main task of the network is to minimize the sum of local objective function in problem (1) by mean of information exchange among all agents and local computation, where every agent only knows the information about itself and its neighbors at each round.

$$\min_{\boldsymbol{x} \in \boldsymbol{X}} \sum_{t=1}^{T} F_t(\boldsymbol{x}) \tag{1}$$

where $F_t(\boldsymbol{x}) = \sum_{i=1}^n f_{i,t}(\boldsymbol{x})$, \boldsymbol{X} is convex and compact set in \mathbb{R}^d , and the function $f_{i,t}$ is convex in \boldsymbol{X} . To measure the performance of the proposed algorithm, the dynamic regret $\mathbf{Regret}_d^j(T)$ is defined, which represents the total sum over time T of the difference between the cumulative cost $F_t(\boldsymbol{x}_{j,t})$ of the agent j and the cumulative cost at the optima \boldsymbol{x}_t^* .

$$\mathbf{Regret}_{d}^{j}(T) = \sum_{t=1}^{T} F_{t}(\boldsymbol{x}_{j,t}) - \sum_{t=1}^{T} F_{t}(\boldsymbol{x}_{t}^{*})$$
(2)

where $\boldsymbol{x}_t^* \in \operatorname{arg\,min}_{\boldsymbol{x} \in \boldsymbol{X}} F_t(\boldsymbol{x})$.

In such distributed online (off-line) optimization problems with constraint sets, projection operations are usually used as a fundamental technique to deal with constraints, such as distributed online gradient descent in Sundhar Ram et al. (2010). In general, the projection step is equivalent to solving a convex quadratic problem Hazan & Kale (2012). However, in high-dimensional and complex constrained optimization problems such as multiclass classification in Zhang et al. (2017b), optimal control in Wu & Teo (1983), matrix completion in Hazan & Kale (2012); Wai et al. (2017), electric vehicle charging in Zhang et al. (2017a), and semidefinite programs in Hazan (2008), projection operations cause a heavy computational burden. In contrast, Frank-Wolfe (FW) method avoids such operations with expensive computational cost through solving a linear minimization oracle. Because of its low computational cost, FW method has been widely utilized in distributed online (off-line) optimization in recent years. In Zhang et al. (2017b), the authors earlier proposed an online distributed FW algorithm by extending online centralized FW algorithm in

^{*}This paper was not presented at any conference.

^{*}Corresponding author.

Email addresses: iswt.zhang@gmail.com (Wentao Zhang), yshi@uvic.ca (Yang Shi), baoyongzhang@njust.edu.cn (Baoyong Zhang), dmyuan1012@gmail.com (Deming Yuan)

Table 1: The comparison among relevant works on online FW convex optimization.

Reference	Loss function	Distributed	Dynamic regret	Dynamic network	Linear oracle	Regret bound
Zhang et al. (2017b)	Convex and continuous	1	×	X	$\mathcal{O}(T)$	$\mathcal{O}(T^{3/4})$
Wan et al. (2020)	Convex and continuous	1	×	×	$\mathcal{O}(\sqrt{T})$	$\mathcal{O}(T^{3/4})$
Wan et al. (2021a)	Strongly convex and continuous	1	×	×	$\mathcal{O}(T^{1/3})$	$\mathcal{O}(T^{2/3}\log T)$
Thang et al. (2022)	Convex and smooth	1	×	×	$\mathcal{O}(T^{3/2})$	$\mathcal{O}(\sqrt{T})$
Kalhan et al. (2021)	Convex and smooth	×	1	/	$\mathcal{O}(T)$	$\mathcal{O}\left(\sqrt{T}\left(1+H_T+\sqrt{D_T}\right)\right)$
					$\mathcal{O}(T^{3/2})$	$\mathcal{O}\left(1+H_T+\sqrt{T}\right)$
Wan et al. $(2021b)$	Convex and continuous	×	\checkmark	/	$\mathcal{O}(T \log_2 T)$	$\mathcal{O}\left(\max\left\{\sqrt{T}, T^{2/3}H_T^{1/3}\right\}\right)$
	Strongly convex and continuous	×	1	/	$\mathcal{O}(T \log_2 T)$	$\mathcal{O}\left(\max\left\{\sqrt{TH_T \log T}, \log T\right\}\right)$
This work	Convex and smooth	\checkmark	\checkmark	\checkmark	$\mathcal{O}(T)$	$\mathcal{O}\left(\sqrt{T(1+H_T)} + D_T\right)$

Hazan & Kale (2012) and obtained the static regret bound $\mathcal{O}(T^{3/4})$. Wan et al. (2020) considered an improved variant under full-information feedback and bandit feedback. Based on the idea of dividing time T into \sqrt{T} equally-sized blocks, the frequency of communication between agents was reduced and the related regret upper bounds $\mathcal{O}(T^{3/4})$ and $\tilde{\mathcal{O}}(T^{3/4})$ were established, respectively. The paper (Wan et al., 2021a) further exploited the improved convergence results under the condition of strong convexity on the basis of Wan et al. (2020). Thang et al. (2022) analyzed two algorithm versions of exact and stochastic gradient under smooth loss function and showed the regret upper bound $\mathcal{O}(\sqrt{T})$. However, in both algorithms, the extra step size loop for each agent slows down the computation at time t.

Up to now, there is few research work on dynamic regret of online FW algorithms, especially in distributed scenarios. Dynamic regret is a more stringent and effective performance metric than static regret because of its dynamic rather than fixed benchmark, whose bound is generally related with the regularity of the optimization problem. From Besbes et al. (2015), it is well known that dynamic regret can not achieve sublinear convergence unless the variation budget satisfies sublinear in T. With that in mind, the function variation H_T and gradient variation D_T related to the bound of **Regret** $_d^{i}(T)$ are defined as

$$H_T = \sum_{t=1}^T \max_{i \in \mathcal{V}} \max_{\boldsymbol{x} \in \boldsymbol{X}} |f_{i,t+1}(\boldsymbol{x}) - f_{i,t}(\boldsymbol{x})|, \qquad (3)$$

$$D_T = \sum_{t=1}^{I} \max_{i \in \mathcal{V}} \max_{\boldsymbol{x} \in \boldsymbol{X}} \|\nabla f_{i,t+1}(\boldsymbol{x}) - \nabla f_{i,t}(\boldsymbol{x})\|.$$
(4)

In Kalhan et al. (2021), the authors analyzed the dynamic regret bounds of several centralized online FW algorithms, in which H_T has a limitation about application range. In this paper, we aim to further improve the range under the same conditions, thus the proposed algorithm has stronger applicability. Wan et al. (2021b) considered a novel centralized online FW algorithm using a restarting strategy. In detail, the comparisons among relevant works on online FW convex optimization are summarized in Table 1.

It's not hard to notice that the works in Kalhan et al. (2021) and Wan et al. (2021b) only analyze the dynamic

regret for centralized online optimization. It is well known that the large-scale optimization problems are difficult to be addressed by the centralized online algorithms due to the computational bottleneck of single machine. From the comparisons and analysis in Table 1, the dynamic regret of online FW algorithm under distributed scenarios needs to be developed. Hence, the <u>distributed online Frank-Wolfe</u> <u>convex optimization algorithm (DOFW-CO)</u> is designed to fill this gap in this paper. This paper makes the following contributions.

Firstly, we develop a distributed online Frank-Wolfe convex optimization algorithm that can efficiently deal with the high-dimensional and complicated constraint set, which alleviates the high computational burden imposed by the projection operator. Meanwhile, the gradient tracking technique is utilized in Algorithm DOFW-CO to update the gradient change of loss function by using history information. Moreover, different from the previous communication topology in Zhang et al. (2017b), Wan et al. (2021a), Wan et al. (2020), Thang et al. (2022), the distributed optimization algorithm over a time-varying network topology is developed, which is more practical and general than static network.

Secondly, inspired by Kalhan et al. (2021), the dynamic regret bound $\mathcal{O}(\sqrt{T(1+H_T)} + D_T)$ for the proposed algorithm is established, which can recover the centralized result and further broaden the range of H_T compared to Kalhan et al. (2021) under the same complexity of linear oracle. The dynamic regret analysis of the FW method in a distributed scenario, for the first time, is developed in this work. Finally, the case of distributed online ridge regression problems is simulated to verify the performance of the proposed algorithm.

Notation: \mathbb{R}^n represents the Euclidean space with n dimensions. $\mathbb{Z}(\mathbb{Z}_+)$ represents the (positive) integers set. The Euclidean norm of a vector \boldsymbol{z} is denoted as $\|\boldsymbol{z}\|$. $[A_t]_{ij}$ signifies the element in the *i*-th row and *j*-th column of matrix A_t and $[\boldsymbol{w}]_i$ denotes the *i*-th element of vector \boldsymbol{w} .

2. Problem Formulation

2.1. The Optimization Problem

Let $\mathcal{G}_t = {\mathcal{V}, \mathcal{E}_t, A_t}$ represent a directed time-varying network with the set $\mathcal{V} := {1, ..., n}$ of agents, the edge set

 $\mathcal{E}_t \subseteq \mathcal{V} \times \mathcal{V}$ and the weighted adjacency matrix $A_t \in \mathbb{R}^{n \times n}$ In the network, agent i has permission to communicate with the agents on inner neighbor sets $\mathcal{N}_i^{\text{in}}(t) = \{j \mid i \}$ $(j,i) \in \mathcal{E}_t \cup \{i\}$ of agent *i*. Further, $[A_t]_{ij} > 0$ holds when $j \in \mathcal{N}_i^{\text{in}}(t)$, and $[A_t]_{ij} = 0$ holds otherwise.

The objective of this paper is to design a distributed online algorithm for problem (1) to ensure that the dynamic regret of every agent $j \in \mathcal{V}$ grows sublinearly, i.e., $\lim_{T\to\infty}(\mathbf{Regret}^{\mathcal{I}}_d(T)/T) = 0, \forall j \in \mathcal{V}.$ Around the network \mathcal{G}_t , the constraint set and loss function in problem 1, the following assumptions are made.

Assumption 1. (a) There exists a positive scalar ζ such

that $[A_t]_{ij} > \zeta, t \in \{1, \dots, T\}$ when $[A_t]_{ij} > 0$. (b) A_t satisfies $\sum_{j=1}^n [A_t]_{ij} = \sum_{i=1}^n [A_t]_{ij} = 1$ for any $t \in \{1, \dots, T\}$ and all $i, j \in \mathcal{V}$.

(c) With some $Q \in \mathbb{Z}_+$, the graph's union $\bigcup_{i=kQ+1}^{(k+1)Q} \mathcal{G}_i$ is strongly connected for every integer $k \ge 0$.

Assumption 2. The constraint set X has a finite diameter M, i.e., for $\forall \boldsymbol{x}_1, \boldsymbol{x}_2 \in \boldsymbol{X}, \max_{\boldsymbol{x}_1, \boldsymbol{x}_2 \in \boldsymbol{X}} \| \boldsymbol{x}_1 - \boldsymbol{x}_2 \| \leq M$.

Assumption 3. (Lipschitz Function) The function $f_{i,t}$ is L_X -Lipschitz, i.e., for $\forall \boldsymbol{x}_1, \boldsymbol{x}_2 \in \boldsymbol{X}, |f_{i,t}(\boldsymbol{x}_1) - f_{i,t}(\boldsymbol{x}_2)| \leq 1$ $L_X \| \boldsymbol{x}_1 - \boldsymbol{x}_2 \|$, where L_X is known positive constant.

Assumption 4. (Lipschitz Gradient) The gradient $\nabla f_{i,t}(\boldsymbol{x})$ is G_X -Lipschitz, i.e., $\|\nabla f_{i,t}(\boldsymbol{x}_1) - \nabla f_{i,t}(\boldsymbol{x}_2)\| \leq 1$ $G_X \| \boldsymbol{x}_1 - \boldsymbol{x}_2 \|, \forall \boldsymbol{x}_1, \boldsymbol{x}_2 \in \boldsymbol{X}.$

Remark 1. In centralized and distributed optimization, Assumptions 1, 2, 3 are standard and similar settings can be seen in Nedić et al. (2008); Yi et al. (2021), Besbes et al. (2015); Wai et al. (2017). According to Lemma 2.6 in Shalev-Shwartz et al. (2011), Assumption 3 implies $\|\nabla f_{i,t}(\boldsymbol{x})\| \leq L_X$. Assumption 4 is equivalent to the fact

$$f_{i,t}(\boldsymbol{x}_1) - f_{i,t}(\boldsymbol{x}_2) \leq \langle \nabla f_{i,t}(\boldsymbol{x}_2), \boldsymbol{x}_1 - \boldsymbol{x}_2 \rangle + \frac{G_X}{2} \|\boldsymbol{x}_1 - \boldsymbol{x}_2\|^2, \forall \boldsymbol{x}_1, \boldsymbol{x}_2 \in \boldsymbol{X}.$$
(5)

3. Algorithm Design and Convergence Analysis

3.1. Algorithm DOFW-CO

In this section, we first develop Algorithm DOFW-CO. The algorithm description is presented in Algorithm 1. Specifically, the key ingredients include: 1) the gradient tracking and Frank-Wolfe methods are utilized; 2) the gradient $\widehat{\nabla} f_{i,t}$ after the gradient tracking step replaces the traditional gradient $abla f_{i,t}(\hat{x}_{i,t})$ in the linear oracle of Frank-Wolfe step.

Algorithm 1 (DOFW-CO) Distributed Online Frank-Wolfe Convex Optimization

- **Initialize:** Initial variables $x_{i,1} \in X$ and parameter 0 < $\alpha \leq 1.$
- 1: for $t = 1, 2, \dots, T$ do
- 2: for Each agent $i \in \mathcal{V}$ do
- Agent *i* receives $x_{j,t}$ from $j \in \mathcal{N}_i^{\text{in}}(t)$, and up-3: dates

$$\hat{x}_{i,t} = \sum_{j \in \mathcal{N}_i^{in}(t)} [A_t]_{ij} x_{j,t}$$

The gradient value $\nabla f_{i,t}(\hat{x}_{i,t})$ is revealed and 4: agent i executes gradient tracking steps:

if t = 1 then 5: $\overline{\nabla}f_{i,1} = \nabla f_{i,1}(\hat{\boldsymbol{x}}_{i,1}),$ 6:

7: else $\overline{\nabla}f_{i,t} = \widehat{\nabla}f_{i,t-1} + \nabla f_{i,t}(\hat{x}_{i,t}) - \nabla f_{i,t-1}(\hat{x}_{i,t-1}).$ 8: end if 9:
$$\label{eq:fisher} \begin{split} \widehat{\nabla} f_{i,t} &= \sum_{j \in \mathcal{N}_i^{in}(t)} \, [A_t]_{ij} \overline{\nabla} f_{j,t}, \\ \text{Frank-Wolfe step: update} \end{split}$$
10: $\boldsymbol{v}_{i,t} = \operatorname*{arg\,min}_{\boldsymbol{x} \in \boldsymbol{X}} \left\langle \boldsymbol{x}, \widehat{\nabla} f_{i,t} \right\rangle, \\ \boldsymbol{x}_{i,t+1} = \hat{\boldsymbol{x}}_{i,t} + \alpha(\boldsymbol{v}_{i,t} - \hat{\boldsymbol{x}}_{i,t}).$

end for 11: 12: **end for**

3.2. Main Convergence Results

In this section, the upper bound of dynamic regret defined in (2) for Algorithm 1 is analyzed in detail. In order to facilitate the proof and analysis, we define the running average vectors $\boldsymbol{x}_{avg,t}$ and $\boldsymbol{v}_{avg,t}$, the max function variation $f_{t,sup}$ at time t, the max gradient variation $g_{t,sup}$ at time t and gradient difference $\delta_{i,t}$ of agent i as follows:

$$\begin{cases} \boldsymbol{x}_{avg,t} = \frac{1}{n} \sum_{i=1}^{n} \boldsymbol{x}_{i,t}, \boldsymbol{v}_{avg,t} = \frac{1}{n} \sum_{i=1}^{n} \boldsymbol{v}_{i,t} \\ f_{t,sup} = \max_{i \in \mathcal{V}} \max_{\boldsymbol{x} \in \boldsymbol{X}} |f_{i,t+1}(\boldsymbol{x}) - f_{i,t}(\boldsymbol{x})| \\ g_{t,sup} = \max_{i \in \mathcal{V}} \max_{\boldsymbol{x} \in \boldsymbol{X}} ||\nabla f_{i,t+1}(\boldsymbol{x}) - \nabla f_{i,t}(\boldsymbol{x})|| \\ \boldsymbol{\delta}_{i,t} = \nabla f_{i,t}(\hat{\boldsymbol{x}}_{i,t}) - \nabla f_{i,t-1}(\hat{\boldsymbol{x}}_{i,t-1}) \end{cases}$$
(6)

Theorem 1. Let the decision sequence $\{x_{i,t}\}$ be generated by Algorithm 1 and suppose Assumptions 1-4 hold. Then, for $T \geq 2$ and $j \in \mathcal{V}$, the regret is bounded as follows:

$$\mathbf{Regret}_{d}^{j}(T) \le C_1 + C_2 \alpha T + \frac{2n}{\alpha} H_T + \frac{C_3}{\alpha} + C_4 D_T \quad (7)$$

where

$$C_{1} = nL_{X} \sum_{i=1}^{n} \|\boldsymbol{x}_{i,1} - \boldsymbol{x}_{avg,1}\| + \frac{2Mn\Gamma}{1-\sigma} \sum_{i=1}^{n} \|\nabla f_{i,1}(\hat{\boldsymbol{x}}_{i,1})\| \\ + \left(nL_{X} + 2MG_{X} + \frac{4Mn\Gamma G_{X}}{1-\sigma}\right) \frac{n\Gamma}{1-\sigma} \sum_{i=1}^{n} \|\boldsymbol{x}_{i,1}\|, \\ C_{2} = 2n^{2}L_{X}M + \left(4MG_{X} + nL_{X} + \frac{4Mn\Gamma G_{X}}{1-\sigma}\right) \frac{n^{2}M\Gamma}{1-\sigma} \\ + \frac{nG_{X}M^{2}}{2}, C_{3} = nL_{X}M, C_{4} = \frac{2Mn^{2}\Gamma}{1-\sigma} + nM, \end{cases}$$

$$\sigma = (1 - \zeta/4n^2)^{1/Q}, \quad \Gamma = (1 - \zeta//4n^2)^{(1-2Q)/Q}$$

Proof. According to Assumption 3, we have that

$$F_{t}(\boldsymbol{x}_{j,t}) - F_{t}(\boldsymbol{x}_{t}^{*}) = F_{t}(\boldsymbol{x}_{j,t}) - F_{t}(\boldsymbol{x}_{avg,t}) + F_{t}(\boldsymbol{x}_{avg,t}) - F_{t}(\boldsymbol{x}_{t}^{*}) \\ \leq nL_{X} \|\boldsymbol{x}_{j,t} - \boldsymbol{x}_{avg,t}\| + F_{t}(\boldsymbol{x}_{avg,t}) - F_{t}(\boldsymbol{x}_{t}^{*}) \\ \leq nL_{X} \sum_{i=1}^{n} \|\boldsymbol{x}_{i,t} - \boldsymbol{x}_{avg,t}\| + F_{t}(\boldsymbol{x}_{avg,t}) - F_{t}(\boldsymbol{x}_{t}^{*}).$$
(8)

Based on Algorithm 1 and double stochasticity of A_{t-1} , we obtain that $\boldsymbol{x}_{avg,t} = \frac{1}{n} \sum_{i=1}^{n} [\hat{\boldsymbol{x}}_{i,t-1} + \alpha(\boldsymbol{v}_{i,t-1} - \hat{\boldsymbol{x}}_{i,t-1})] = \boldsymbol{x}_{avg,t-1} + \alpha(\boldsymbol{v}_{avg,t-1} - \boldsymbol{x}_{avg,t-1})$. Thus, by considering Assumption 2, we have for any $t \geq 2$ that

$$\|\boldsymbol{x}_{i,t} - \boldsymbol{x}_{avg,t}\| = \|\hat{\boldsymbol{x}}_{i,t-1} - \boldsymbol{x}_{avg,t-1} + \alpha(\boldsymbol{v}_{i,t-1} - \hat{\boldsymbol{x}}_{i,t-1}) - \alpha(\boldsymbol{v}_{avg,t-1} - \boldsymbol{x}_{avg,t-1})\| \\ \leq \|\hat{\boldsymbol{x}}_{i,t-1} - \boldsymbol{x}_{avg,t-1}\| + 2\alpha M.$$
(9)

With this condition and recalling the regret notion defined in (2), we obtain from (8) that

 $\mathbf{Regret}_d^{\mathcal{I}}(T)$

$$\leq nL_X \sum_{i=1}^{n} \|\boldsymbol{x}_{i,1} - \boldsymbol{x}_{avg,1}\| + nL_X \sum_{t=1}^{T-1} \sum_{i=1}^{n} \|\hat{\boldsymbol{x}}_{i,t} - \boldsymbol{x}_{avg,t}\| \\ + 2\alpha T n^2 L_X M + \sum_{t=1}^{T} \left[F_t(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_t^*) \right].$$
(10)

Based on this inequality together with the use of Lemma 1, Lemma 3 and Lemma 4 in Appendix, we can readily obtain the condition (7) in Theorem 1. The proof is completed.

Theorem 1 shows the main results of dynamic regret. It is easy to note that the regret bound of Algorithm 1 depends on the choice of α . Hence, we have the following corollary by choosing suitable step sizes.

Corollary 1. Suppose that the conditions in Theorem 1 hold. Then, if $H_T = o(T), D_T = o(T)$ holds, taking $\alpha = \gamma \sqrt{\frac{H_T+1}{T}}$, we have

$$\operatorname{\mathbf{Regret}}_{d}^{j}(T) \leq \mathcal{O}\left(\sqrt{T(1+H_{T})} + D_{T}\right)$$
(11)

where γ is a positive adjustment constant guaranteeing $\alpha \leq 1$.

Proof. According to (7), we obtain $\operatorname{\mathbf{Regret}}_{d}^{j}(T) \leq \mathcal{O}\left(\alpha T + \frac{1}{\alpha}(1 + H_{T}) + D_{T}\right)$. Then, (11) is easily obtained by taking $\alpha T = \frac{1}{\alpha}(1 + H_{T})$. The proof is complete. \Box

Remark 2. In particular, this result shown in Corollary 1 matches the centralized result in Kalhan et al. (2021) and is less conservative and tighter than its upper bound $\mathcal{O}(\sqrt{T}(1 + H_T + \sqrt{D_T}))$ under the same complexity of linear oracle. Further, the range of H_T in Kalhan et al. (2021) is improved from $\mathcal{O}(\sqrt{T})$ to $\mathcal{O}(T)$ when a sublinear regret bound is expected, which effectively expands the application field of optimization problems.

Remark 3. Note that H_T as a prior knowledge is difficult to be obtained accurately in practical applications. Two discussions are shown as follows:

- i) if an estimated upper bound satisfying $H_T \leq \hat{H}_T = \mathcal{O}(T^{\theta}), 0 < \theta < 1$ can be known in advance, the sublinear dynamic regret is obtained by setting step size $\alpha = \gamma \sqrt{(T^{\theta} + 1)/T}$.
- ii) when the loss function $F_t(x) = F(x)$ is time-invariant, $H_T = 0, D_T = 0$ hold and the dynamic regret bound $\mathcal{O}(\sqrt{T})$ is established, which matches the results in distributed off-line scenario, such as Hou et al. (2022).

4. Simulation

In this section, several numerical simulations are conducted for ridge regression problem to verify the algorithms we proposed. The problem of ridge regression is formulated as

$$\min_{\boldsymbol{x} \in \boldsymbol{X}} \sum_{t=1}^{T} \sum_{i=1}^{n} \left[\frac{1}{2} \left(\boldsymbol{a}_{i,t}^{\top} \boldsymbol{x} - \boldsymbol{l}_{i,t} \right)^2 + \lambda_1 \|\boldsymbol{x}\|_2^2 \right]$$
(12)

where $\mathbf{X} := \{\mathbf{x} \mid \mathbf{1}^T \mathbf{x} = 1\}, \lambda_1 = 5 \times 10^{-6}$ is a regular parameter and the pair $(\mathbf{a}_{i,t}, l_{i,t}) \in \mathbb{R}^d \times \mathbb{R}$ represents the feature and label information only known by agent i at time t. The feature vector $\mathbf{a}_{i,t}$ is generated randomly and its entries are distributed uniformly from -5 to 5 and the label $l_{i,t}$ satisfies $l_{i,t} = \mathbf{a}_{i,t}^\top \mathbf{x}_0 + \frac{2\xi_{i,t}}{d\sqrt{t}}$ where $[\mathbf{x}_0]_i = 1/d$ and $\xi_{i,t}$ is generated uniformly in the interval [0, 1]. We execute the algorithm over the network of n = 20 and d = 8 in this simulation. In the following cases, the global average dynamic regret, the upper envelope and the lower envelope of $\mathbf{Regret}_d^j(T)/T$ are denoted as $\frac{1}{n} \sum_{j=1}^n [\mathbf{Regret}_d^j(T)/T]$, $\sup_j \{\mathbf{Regret}_d^j(T)/T\}$ and $\inf_j \{\mathbf{Regret}_d^j(T)/T\}$ to measure the performance of the algorithm, respectively. From Fig. 1, it is clearly seen that the three average dynamic regrets are convergent for Algorithm 1 under the condition $\alpha = 1/(4T^{0.4})$, which corresponds to the theoretical result.

To study the level of computational cost savings of Algorithm 1, we compare the global average dynamic regret and computational time of Algorithm 1 with distributed online gradient descent (DOGD) algorithm Yan et al. (2013) under two dimensions d = 8 and 160, where the dynamic regret analysis of Algorithm DOGD can be regarded as a special case satisfying that distancemeasuring function $\mathcal{R}(\mathbf{x}) = \|\mathbf{x}\|^2$ and the mapping A =I in Shahrampour & Jadbabaie (2017). The step sizes $\alpha_1 = 1/(4T^{0.4}), \alpha_2 = 1/(2T^{0.4})$ and $\alpha_3 = 1/(T^{0.4}), \alpha_4 =$ $1/(4T^{0.4})$ are set for Algorithms 1 and DOGD, respectively. From Figs. 2 and 3, we obtain that Algorithm 1 is able to achieve similar convergence performance to Algorithm DOGD but using less computation time, which convincingly reflects the advantages of the linear oracle. In particular, when the dimension d is increased from 8 to 160, Algorithm 1 only has a slightly increase in computation cost compared to the significant increase of Algorithm



Fig. 1: The convergence performance for Algorithm 1.



Fig. 2: The comparison results of regret between Algorithms 1 and DOGD under d = 8 and 160.

DOGD. In term of this point, the higher the dimension of the constrained optimization problem is, the more prominent and important the advantage of Algorithm 1 in saving computational costs is.

5. Conclusions

For the distributed online convex optimization problem, this paper has developed Algorithm DOFW-CO to reduce the expensive computational cost of the projection step for the high-dimensional and complicated constraint set. In this problem, each agent cooperates to minimize a global cost function through local calculation and information exchange with neighbors over a direct time-varying network. We have rigorously established the dynamic regret upper bound of the proposed optimization algorithm as $\mathcal{O}(\sqrt{T(1+H_T)}+D_T)$. Finally, the performance of our algorithm has been verified and compared by the simulation of distributed online ridge regression problems. In the future, a promising direction is to explore an improved



Fig. 3: The comparison of the computation time between Algorithms 1 and DOGD under d = 8 and 160.

version of Algorithm DOFW-CO from the perspective of convergence speed or saving computing resources.

Appendix A. Some key lemmas

For the convergence analysis of Algorithm 1, the following lemmas are essential. Define $\Phi(t, s) = A_t A_{t-1} \dots A_s$ as the transition matrix of A_t for all t, s with $t \ge s \ge 1$.

Lemma 1. Let the decision sequence $\{x_{i,t}\}$ be generated by Algorithm 1. Then, under Assumptions 1 and 2, we have for $T \ge 2$ that

$$\sum_{t=1}^{T} \sum_{i=1}^{n} \|\hat{\boldsymbol{x}}_{i,t} - \boldsymbol{x}_{avg,t}\| \le \frac{n\Gamma}{1-\sigma} \sum_{j=1}^{n} \|\boldsymbol{x}_{j,1}\| + \alpha T \frac{n^2 M\Gamma}{1-\sigma}.$$

Proof. According to Algorithm 1, we get

$$\hat{\boldsymbol{x}}_{i,t} = \sum_{j=1}^{n} [A_t]_{ij} \boldsymbol{x}_{j,t}$$

$$= \sum_{j=1}^{n} [A_t]_{ij} \hat{\boldsymbol{x}}_{j,t-1} + \alpha \sum_{j=1}^{n} [A_t]_{ij} (\boldsymbol{v}_{j,t-1} - \hat{\boldsymbol{x}}_{j,t-1})$$

$$= \sum_{j=1}^{n} [\Phi(t,1)]_{ij} \boldsymbol{x}_{j,1} + \alpha \sum_{l=1}^{t-1} \sum_{j=1}^{n} [\Phi(t,l+1)]_{ij} (\boldsymbol{v}_{j,l} - \hat{\boldsymbol{x}}_{j,l})$$
(A.1)

According to Algorithm 1, the term $x_{avg,t}$ can be further simplified as follows:

$$\begin{aligned} \boldsymbol{x}_{avg,t} &= \frac{1}{n} \sum_{i=1}^{n} \sum_{j=1}^{n} [A_{t-1}]_{ij} \boldsymbol{x}_{i,t-1} + \frac{\alpha}{n} \sum_{i=1}^{n} (\boldsymbol{v}_{i,t-1} - \hat{\boldsymbol{x}}_{j,t-1}) \\ &= \boldsymbol{x}_{avg,t-1} + \frac{\alpha}{n} \sum_{i=1}^{n} (\boldsymbol{v}_{i,t-1} - \hat{\boldsymbol{x}}_{j,t-1}) \\ &= \frac{1}{n} \sum_{j=1}^{n} \boldsymbol{x}_{j,1} + \frac{\alpha}{n} \sum_{l=1}^{t-1} \sum_{j=1}^{n} (\boldsymbol{v}_{j,l} - \hat{\boldsymbol{x}}_{j,l}) \end{aligned}$$
(A.2)

where the third equality combines the double stochasticity of adjacent weight matrix A_{t-1} .

Combining (A.1) and (A.2), for $t \ge 2$, we achieve

$$\begin{aligned} \|\hat{\boldsymbol{x}}_{i,t} - \boldsymbol{x}_{avg,t}\| \\ &\leq \left\| \sum_{j=1}^{n} [\Phi(t,1)]_{ij} \boldsymbol{x}_{j,1} - \frac{1}{n} \sum_{j=1}^{n} \boldsymbol{x}_{j,1} \right\| + \\ \left\| \alpha \sum_{l=1}^{t-1} \sum_{j=1}^{n} [\Phi(t,l+1)]_{ij} (\boldsymbol{v}_{j,l} - \hat{\boldsymbol{x}}_{j,l}) - \frac{\alpha}{n} \sum_{l=1}^{t-1} \sum_{j=1}^{n} (\boldsymbol{v}_{j,l} - \hat{\boldsymbol{x}}_{j,l}) \right\| \\ &\leq \sum_{j=1}^{n} \left| [\Phi(t,1)]_{ij} - \frac{1}{n} \right| \|\boldsymbol{x}_{j,1}\| \\ &+ \alpha \sum_{l=1}^{t-1} \sum_{j=1}^{n} \left| [\Phi(t,l+1)]_{ij} - \frac{1}{n} \right| \|\boldsymbol{v}_{j,l} - \hat{\boldsymbol{x}}_{j,l}\| \\ &\leq \Gamma \sigma^{t-1} \sum_{j=1}^{n} \|\boldsymbol{x}_{j,1}\| + \alpha n M \Gamma \sum_{l=1}^{t-1} \sigma^{t-l-1} \\ &\leq \Gamma \sigma^{t-1} \sum_{i=1}^{n} \|\boldsymbol{x}_{j,1}\| + \alpha \frac{n M \Gamma}{1 - \sigma} \end{aligned}$$
(A.3)

where the third inequality follows the property of $\Phi(t, s)^{-1}$ and the fact $v_{j,l}, \hat{x}_{j,l} \in X$. Summing from i = 1 to n and t = 1 to T on both sides of (A.3), we get

$$\sum_{t=1}^{T} \sum_{i=1}^{n} \|\hat{\boldsymbol{x}}_{i,t} - \boldsymbol{x}_{avg,t}\| \\ \leq \sum_{i=1}^{n} \|\hat{\boldsymbol{x}}_{i,1} - \boldsymbol{x}_{avg,1}\| + n\Gamma \sum_{t=2}^{T} \sigma^{t-1} \sum_{j=1}^{n} \|\boldsymbol{x}_{j,1}\| + \alpha T \frac{n^2 M\Gamma}{1 - \sigma} \\ \leq \frac{n\Gamma}{1 - \sigma} \sum_{j=1}^{n} \|\boldsymbol{x}_{j,1}\| + \alpha T \frac{n^2 M\Gamma}{1 - \sigma}$$
(A.4)

where the second inequality follows the fact $\sum_{i=1}^{n} \|\hat{x}_{i,1} - x_{avg,1}\| \leq \sum_{i=1}^{n} \|\sum_{j=1}^{n} [A_1]_{ij} x_{j,1} - \frac{1}{n} \sum_{j=1}^{n} x_{j,1}\| \leq \sum_{i=1}^{n} \sum_{j=1}^{n} |[A_1]_{ij} - \frac{1}{n}| \|x_{j,1}\| \leq n \sum_{j=1}^{n} \|x_{j,1}\|.$ The proof is complete.

Lemma 2. Let the decision sequence $\{x_{i,t}\}$ be generated by Algorithm 1. Then, under Assumptions 2 and 4, we have for any $T \ge 2$ that

(a)
$$\sum_{i=1}^{n} \overline{\nabla} f_{i,t} = \sum_{i=1}^{n} \nabla f_{i,t}(\hat{x}_{i,t}), \ \forall t \ge 1.$$
 (A.5)
(b) $\sum_{t=2}^{T} \sum_{i=1}^{n} \|\delta_{i,t}\| \le 2G_X \sum_{t=2}^{T} \sum_{i=1}^{n} \|\hat{x}_{i,t-1} - x_{avg,t-1}\| + nD_T + nMG_X \alpha T.$ (A.6)

Proof. (a) We utilize the mathematical induction method to prove this part. Note that $\overline{\nabla}f_{i,1} = \nabla f_{i,1}(\hat{x}_{i,1})$ according to Algorithm 1. Thus, the equality in (A.5) holds when t = 1. Now we assume that $\sum_{i=1}^{n} \overline{\nabla}f_{i,t} = \sum_{i=1}^{n} \nabla f_{i,t}(\hat{x}_{i,t})$ holds at some t, and we are going to show this equality also holds at t + 1. Actually,

$$\sum_{i=1}^{n} \overline{\nabla} f_{i,t+1}$$

$$= \sum_{i=1}^{n} \widehat{\nabla} f_{i,t} + \sum_{i=1}^{n} \nabla f_{i,t+1}(\hat{x}_{i,t+1}) - \sum_{i=1}^{n} \nabla f_{i,t}(\hat{x}_{i,t})$$

$$= \sum_{i=1}^{n} \sum_{j=1}^{n} [A_t]_{ij} \overline{\nabla} f_{j,t} + \sum_{i=1}^{n} \nabla f_{i,t+1}(\hat{x}_{i,t+1}) - \sum_{i=1}^{n} \overline{\nabla} f_{i,t}$$

$$= \sum_{i=1}^{n} \nabla f_{i,t+1}(\hat{x}_{i,t+1})$$
(A.7)

where the last equality follows from the double stochasticity of A_t .

(b) By using (6), we obtain for any $t \ge 2$ that

$$\sum_{i=1}^{n} \|\boldsymbol{\delta}_{i,t}\| \leq \sum_{i=1}^{n} \|\nabla f_{i,t}(\hat{\boldsymbol{x}}_{i,t}) - \nabla f_{i,t-1}(\hat{\boldsymbol{x}}_{i,t})\| \\ + \sum_{i=1}^{n} \|\nabla f_{i,t-1}(\hat{\boldsymbol{x}}_{i,t}) - \nabla f_{i,t-1}(\hat{\boldsymbol{x}}_{i,t-1})\| \\ \leq ng_{t-1,sup} + \sum_{i=1}^{n} (G_X \|\hat{\boldsymbol{x}}_{i,t} - \hat{\boldsymbol{x}}_{i,t-1}\|) \\ \leq ng_{t-1,sup} + G_X \sum_{i=1}^{n} (\|\hat{\boldsymbol{x}}_{i,t} - \boldsymbol{x}_{avg,t-1}\| \\ + \|\hat{\boldsymbol{x}}_{i,t-1} - \boldsymbol{x}_{avt,t-1}\|) \\ \leq ng_{t-1,sup} + 2G_X \sum_{i=1}^{n} \|\hat{\boldsymbol{x}}_{i,t-1} - \boldsymbol{x}_{avg,t-1}\| \\ + nMG_X \alpha$$
(A.8)

where the last inequality is obtained based on the fact: $\sum_{i=1}^{n} \|\hat{x}_{i,t} - x_{avg,t-1}\| \leq \sum_{i=1}^{n} \sum_{j=1}^{n} [A_t]_{ij} \|x_{j,t} - x_{avg,t-1}\| \leq \sum_{i=1}^{n} \|\hat{x}_{i,t-1} - x_{avg,t-1} + \alpha(v_{i,t-1} - \hat{x}_{i,t-1})\| \leq \sum_{i=1}^{n} \|\hat{x}_{i,t-1} - x_{avg,t-1}\| + \alpha n M.$

Then, by summing the both sides of (A.8) from t = 2 to T, we can readily obtain the inequality in (A.6). The proof is complete.

Lemma 3. Let the sequence $\{\widehat{\nabla}f_{i,t}, \nabla f_{i,t}(\hat{x}_{i,t})\}$ be generated by Algorithm 1. Then, under Assumptions 1 and 4, we have for any $T \geq 2$ that

$$\sum_{t=1}^{T} \sum_{i=1}^{n} \left\| \widehat{\nabla} f_{i,t} - \frac{1}{n} \sum_{j=1}^{n} \nabla f_{j,t}(\hat{x}_{j,t}) \right\| \\ \leq \frac{n\Gamma}{1 - \sigma} \sum_{j=1}^{n} \| \nabla f_{j,1}(\hat{x}_{j,1}) \| + \frac{n\Gamma}{1 - \sigma} \sum_{t=2}^{T} \sum_{i=1}^{n} \| \boldsymbol{\delta}_{i,t} \|.$$
(A.9)

¹Lemma (Nedić et al. (2008)) Let Assumption 1 hold. Then, for all $i, j \in \mathcal{V}$, we have $|[\Phi(t,s)]_{ij} - \frac{1}{n}| \leq \Gamma \sigma^{(t-s)}$ where $\sigma = (1 - \zeta/4n^2)^{1/Q}$ and $\Gamma = (1 - \zeta/4n^2)^{(1-2Q)/Q}$.

Proof. Similar to the proof of Lemma 1 and combining Algorithm 1, (A.5), for any $t \ge 2$ it can be verified that

$$\widehat{\nabla}f_{i,t} = \sum_{j=1}^{n} [\Phi(t,2)]_{ij} \widehat{\nabla}f_{j,1} + \sum_{l=2}^{t} \sum_{j=1}^{n} [\Phi(t,l)]_{ij} \delta_{j,l}, \quad (A.10)$$
$$\frac{1}{n} \sum_{i=1}^{n} \nabla f_{i,t}(\hat{x}_{i,t}) = \frac{1}{n} \sum_{i=1}^{n} \overline{\nabla}f_{i,1} + \frac{1}{n} \sum_{l=2}^{t} \sum_{i=1}^{n} \delta_{i,l}. \quad (A.11)$$

Similar to (A.3), combining the fact $\widehat{\nabla} f_{i,1} = \sum_{j=1}^{n} [A_1]_{ij} \overline{\nabla} f_{j,1}, \overline{\nabla} f_{i,1} = \nabla f_{i,1}(\hat{x}_{i,1})$, it follows from (A.10) and (A.11) that $\|\widehat{\nabla} f_{i,t} - \frac{1}{n} \sum_{j=1}^{n} \nabla f_{j,t}(\hat{x}_{j,t})\| \leq \sum_{j=1}^{n} \Gamma \sigma^{t-1} \|\nabla f_{j,1}(\hat{x}_{j,1})\| + \sum_{l=2}^{t} \sum_{j=1}^{n} \Gamma \sigma^{t-l} \|\delta_{j,l}\|$. This implies that

$$\begin{split} &\sum_{t=1}^{T} \sum_{i=1}^{n} \left\| \widehat{\nabla} f_{i,t} - \frac{1}{n} \sum_{j=1}^{n} \nabla f_{j,t}(\hat{x}_{j,t}) \right\| \\ &\leq \sum_{i=1}^{n} \left\| \widehat{\nabla} f_{i,1} - \frac{1}{n} \sum_{j=1}^{n} \nabla f_{j,1}(\hat{x}_{j,1}) \right\| \\ &+ \sum_{t=2}^{T} \sum_{j=1}^{n} n \Gamma \sigma^{t-1} \left\| \nabla f_{j,1}(\hat{x}_{j,1}) \right\| + \sum_{t=2}^{T} \sum_{l=2}^{t} \sum_{j=1}^{n} n \Gamma \sigma^{t-l} \left\| \delta_{j,l} \right\| \\ &\leq \sum_{i=1}^{n} \sum_{j=1}^{n} \left| [A_1]_{ij} - \frac{1}{n} \right| \left\| \nabla f_{j,1}(\hat{x}_{j,1}) \right\| \\ &+ \frac{\sigma n \Gamma}{1 - \sigma} \sum_{j=1}^{n} \left\| \nabla f_{j,1}(\hat{x}_{j,1}) \right\| + n \Gamma \left(\sum_{l=0}^{T-2} \sigma^{l} \right) \left(\sum_{t=2}^{T} \sum_{i=1}^{n} \left\| \delta_{i,t} \right\| \right) \\ &\leq \frac{n \Gamma}{1 - \sigma} \sum_{j=1}^{n} \left\| \nabla f_{j,1}(\hat{x}_{j,1}) \right\| + \frac{n \Gamma}{1 - \sigma} \sum_{t=2}^{T} \sum_{i=1}^{n} \left\| \delta_{i,t} \right\| \quad (A.12) \end{split}$$

Substituting the above inequalities into (A.12), we can readily obtain (A.9). The proof is complete. \Box

Lemma 4. Let the decision sequence $\{x_{i,t}\}$ be generated by Algorithm 1. Then, under Assumptions 2, 3 and 4, we have for any $T \ge 2$ that

$$\sum_{t=1}^{T} F_t(\boldsymbol{x}_{avg,t}) - \sum_{t=1}^{T} F_t(\boldsymbol{x}_t^*)$$

$$\leq \frac{2n}{\alpha} H_T + \frac{nL_X M}{\alpha} + 2M \sum_{t=1}^{T-1} \sum_{i=1}^{n} \left\| \sum_{j=1}^{n} \nabla f_{j,t}(\hat{\boldsymbol{x}}_{j,t}) - \widehat{\nabla} f_{i,t} \right\|$$

$$+ 2M G_X \sum_{t=1}^{T-1} \sum_{i=1}^{n} \left\| \hat{\boldsymbol{x}}_{i,t} - \boldsymbol{x}_{avg,t} \right\| + \frac{nG_X M^2}{2} \alpha T + nM D_T$$
(A.13)

Proof. By using the smooth property in Assumption 4, we have

$$F_{t+1}(\boldsymbol{x}_{avg,t+1}) - F_{t+1}(\boldsymbol{x}_{avg,t})$$

$$\leq \langle \nabla F_{t+1}(\boldsymbol{x}_{avg,t}), \boldsymbol{x}_{avg,t+1} - \boldsymbol{x}_{avg,t} \rangle$$
(A.14)

$$+ \frac{nG_X}{2} \|\boldsymbol{x}_{avg,t+1} - \boldsymbol{x}_{avg,t}\|^2$$

$$\leq \alpha \sum_{i=1}^n \left\langle \frac{1}{n} \nabla F_{t+1}(\boldsymbol{x}_{avg,t}), \boldsymbol{v}_{i,t} - \boldsymbol{x}_{avg,t} \right\rangle + \frac{nG_X M^2 \alpha^2}{2}$$

It can be further verified that

$$\left\langle \frac{1}{n} \nabla F_{t+1}(\boldsymbol{x}_{avg,t}), \boldsymbol{v}_{i,t} - \boldsymbol{x}_{avg,t} \right\rangle$$

$$\leq \left\langle \frac{1}{n} \nabla F_{t+1}(\boldsymbol{x}_{avg,t}) - \widehat{\nabla} f_{i,t}, \boldsymbol{v}_{i,t} - \boldsymbol{x}_{avg,t} \right\rangle$$

$$+ \left\langle \widehat{\nabla} f_{i,t}, \boldsymbol{x}_{t}^{*} - \boldsymbol{x}_{avg,t} \right\rangle$$

$$\leq \frac{M}{n} \| \nabla F_{t+1}(\boldsymbol{x}_{avg,t}) - \nabla F_{t}(\boldsymbol{x}_{avg,t}) \| + 2M \left\| \frac{1}{n} \nabla F_{t}(\boldsymbol{x}_{avg,t}) \right\|$$

$$- \frac{1}{n} \sum_{j=1}^{n} \nabla f_{j,t}(\hat{\boldsymbol{x}}_{j,t}) + \frac{1}{n} \sum_{j=1}^{n} \nabla f_{j,t}(\hat{\boldsymbol{x}}_{j,t}) - \widehat{\nabla} f_{i,t} \right\|$$

$$+ \frac{1}{n} \left\langle \nabla F_{t}(\boldsymbol{x}_{avg,t}), \boldsymbol{x}_{t}^{*} - \boldsymbol{x}_{avg,t} \right\rangle$$

$$\leq M g_{t,sup} + 2M \left\| \frac{1}{n} \sum_{j=1}^{n} \nabla f_{j,t}(\hat{\boldsymbol{x}}_{j,t}) - \widehat{\nabla} f_{i,t} \right\|$$

$$+ \frac{2MG_{X}}{n} \sum_{j=1}^{n} \| \hat{\boldsymbol{x}}_{j,t} - \boldsymbol{x}_{avg,t} \| + \frac{1}{n} [F_{t}(\boldsymbol{x}_{t}^{*}) - F_{t}(\boldsymbol{x}_{avg,t})]$$

where the first inequality is obtained by utilizing the following optimality condition:

$$\left\langle \widehat{\nabla} f_{i,t}, \boldsymbol{x}_{t}^{*} \right\rangle \geq \min_{\boldsymbol{x} \in \boldsymbol{X}} \left\langle \widehat{\nabla} f_{i,t}, \boldsymbol{x} \right\rangle = \left\langle \widehat{\nabla} f_{i,t}, \boldsymbol{v}_{i,t} \right\rangle \quad (A.16)$$

and the last inequality is derived based on the convexity condition of $F_t(\boldsymbol{x})$ together with Assumption 4. Then, it follows from (A.14) and (A.15) that

$$F_{t+1}(\boldsymbol{x}_{avg,t+1}) - F_{t+1}(\boldsymbol{x}_{avg,t})$$

$$\leq \alpha n M g_{t,sup} + \alpha \left[F_t(\boldsymbol{x}_t^*) - F_t(\boldsymbol{x}_{avg,t}) \right] + \Psi_t. \quad (A.17)$$

where $\Psi_t = 2\alpha M \sum_{i=1}^n \left\| \frac{1}{n} \sum_{j=1}^n \nabla f_{j,t}(\hat{x}_{j,t}) - \widehat{\nabla} f_{i,t} \right\| + 2\alpha M G_X \sum_{j=1}^n \|\hat{x}_{j,t} - x_{avg,t}\| + \frac{n G_X M^2 \alpha^2}{2}$. Based on this inequality, we can further obtain that

$$F_{t+1}(\boldsymbol{x}_{avg,t+1}) - F_{t+1}(\boldsymbol{x}_{t+1}^{*}) \\ \leq F_{t+1}(\boldsymbol{x}_{avg,t}) - F_{t+1}(\boldsymbol{x}_{t+1}^{*}) + \alpha n M g_{t,sup} + \Psi_{t} \\ + \alpha \left[F_{t}(\boldsymbol{x}_{t}^{*}) - F_{t}(\boldsymbol{x}_{avg,t})\right] \\ \leq n f_{t,sup} + F_{t}(\boldsymbol{x}_{avg,t}) - F_{t}(\boldsymbol{x}_{t}^{*}) + F_{t}(\boldsymbol{x}_{t}^{*}) - F_{t+1}(\boldsymbol{x}_{t+1}^{*}) \\ + \alpha n M g_{t,sup} + \alpha \left[F_{t}(\boldsymbol{x}_{t}^{*}) - F_{t}(\boldsymbol{x}_{avg,t})\right] + \Psi_{t} \quad (A.18)$$

where the last inequality is established by using the following fact:

$$F_{t+1}(\boldsymbol{x}_{avg,t}) - F_{t+1}(\boldsymbol{x}_{t+1}^*) \\ = F_{t+1}(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_{avg,t}) + F_t(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_t^*) \\ + F_t(\boldsymbol{x}_t^*) - F_{t+1}(\boldsymbol{x}_{t+1}^*)$$

$$\leq nf_{t,sup} + F_t(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_t^*) + F_t(\boldsymbol{x}_t^*) - F_{t+1}(\boldsymbol{x}_{t+1}^*).$$

By summing the both sides of (A.18), we get

$$\sum_{t=1}^{T-1} \left\{ F_{t+1}(\boldsymbol{x}_{avg,t+1}) - F_{t+1}(\boldsymbol{x}_{t+1}^*) - [F_t(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_t^*)] \right\} + \alpha \sum_{t=1}^{T-1} [F_t(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_t^*)] \leq nH_T + F_1(\boldsymbol{x}_1^*) - F_T(\boldsymbol{x}_T^*) + \alpha nMD_T + \sum_{t=1}^{T-1} \Psi_t \quad (A.19)$$

By recalling the facts that $0 < \alpha \leq 1$ and $F_T(\boldsymbol{x}_{avg,T}) - F_T(\boldsymbol{x}_T^*) \geq 0$, we have that

$$\alpha \sum_{t=1}^{T} \left[F_t(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_t^*) \right]$$
(A.20)

$$\leq [F_T(\boldsymbol{x}_{avg,T}) - F_T(\boldsymbol{x}_T^*)] + \alpha \sum_{t=1}^{T-1} [F_t(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_t^*)]$$

$$\leq nH_T + [F_1(\boldsymbol{x}_{avg,1}) - F_T(\boldsymbol{x}_T^*)] + \alpha nMD_T + \sum_{t=1}^{T-1} \Psi_t.$$

In addition, it can be obtained under Assumption 2 and Assumption 3 that $F_1(\boldsymbol{x}_{avg,1}) - F_T(\boldsymbol{x}_T^*) = F_1(\boldsymbol{x}_{avg,1}) - F_1(\boldsymbol{x}_T^*) + \sum_{t=1}^{T-1} [F_t(\boldsymbol{x}_T^*) - F_{t+1}(\boldsymbol{x}_T^*)] \le nL_X \|\boldsymbol{x}_{avg,1} - \boldsymbol{x}_T^*\| + \sum_{t=1}^{T-1} \sum_{i=1}^n |f_{i,t}(\boldsymbol{x}_T^*) - f_{i,t+1}(\boldsymbol{x}_T^*)| \le nL_X M + nH_T.$ This, together with (A.20), yields that

$$\alpha \sum_{t=1}^{T} \left[F_t(\boldsymbol{x}_{avg,t}) - F_t(\boldsymbol{x}_t^*) \right]$$

$$\leq 2nH_T + nL_X M + \alpha nMD_T + \sum_{t=1}^{T-1} \Psi_t. \quad (A.21)$$

This further implies the result in (A.13) through recalling the definition of Ψ_t . The proof is complete.

References

- Besbes, O., Gur, Y., & Zeevi, A. (2015). Non-stationary stochastic optimization. Operations Research, 63, 1227–1244.
- Hazan, E. (2008). Sparse approximate solutions to semidefinite programs. In Latin American Symposium on Theoretical Informatics (pp. 306–316).
- Hazan, E., & Kale, S. (2012). Projection-free online learning. In Proceedings of the 29th International Coference on International Conference on Machine Learning (pp. 1843–1850).
- Hou, J., Zeng, X., Wang, G., Sun, J., & Chen, J. (2022). Distributed momentum-based Frank-Wolfe algorithm for stochastic optimization. *IEEE/CAA Journal of Automatica Sinica*, . Doi:10.1109/JAS.2022.105923.
- Kalhan, D. S., Bedi, A. S., Koppel, A., Rajawat, K., Hassani, H., Gupta, A. K., & Banerjee, A. (2021). Dynamic online learning via Frank-Wolfe algorithm. *IEEE Transactions on Signal Processing*, 69, 932–947.
- Li, W., Zeng, X., Hong, Y., & Ji, H. (2021). Distributed consensusbased solver for semi-definite programming: An optimization viewpoint. Automatica, 131, 109737.

- Li, X., Xie, L., & Li, N. (2022). A survey of decentralized online learning. arXiv preprint, arXiv:2205.00473.
- Liu, C., Li, H., & Shi, Y. (2020). A unitary distributed subgradient method for multi-agent optimization with different coupling sources. *Automatica*, 114, 108834.
- Nedić, A., & Liu, J. (2018). Distributed optimization for control. Annual Review of Control, Robotics, and Autonomous Systems, 1, 77–103.
- Nedić, A., Olshevsky, A., Ozdaglar, A., & Tsitsiklis, J. N. (2008). Distributed subgradient methods and quantization effects. In 2008 47th IEEE Conference on Decision and Control (pp. 4177–4184).
- Shahrampour, S., & Jadbabaie, A. (2017). Distributed online optimization in dynamic environments using mirror descent. *IEEE Transactions on Automatic Control*, 63, 714–725.
- Shalev-Shwartz, S. et al. (2011). Online learning and online convex optimization. Foundations and Trends in Machine Learning, 4, 107–194.
- Sundhar Ram, S., Nedić, A., & Veeravalli, V. V. (2010). Distributed stochastic subgradient projection algorithms for convex optimization. Journal of Optimization Theory and Applications, 147, 516– 545.
- Thang, N. K., Srivastav, A., Trystram, D., & Youssef, P. (2022). A stochastic conditional gradient algorithm for decentralized online convex optimization. *Journal of Parallel and Distributed Computing*, 169, 334–351.
- Wai, H.-T., Lafond, J., Scaglione, A., & Moulines, E. (2017). Decentralized Frank-Wolfe algorithm for convex and nonconvex problems. *IEEE Transactions on Automatic Control*, 62, 5522–5537.
- Wan, Y., Tu, W.-W., & Zhang, L. (2020). Projection-free distributed online convex optimization with $o(\sqrt{T})$ communication complexity. In *Proceedings of the 37th International Conference on Machine Learning* (pp. 9818–9828).
- Wan, Y., Wang, G., & Zhang, L. (2021a). Projection-free distributed online learning with strongly convex losses. arXiv preprint, arXiv:2103.11102.
- Wan, Y., Xue, B., & Zhang, L. (2021b). Projection-free online learning in dynamic environments. *Proceedings of the AAAI Confer*ence on Artificial Intelligence, (pp. 10067–10075).
- Wu, Z., & Teo, K. (1983). A conditional gradient method for an optimal control problem involving a class of nonlinear second-order hyperbolic partial differential equations. *Journal of Mathematical Analysis and Applications*, 91, 376–393.
- Xu, J.-M., & Soh, Y. C. (2016). A distributed simultaneous perturbation approach for large-scale dynamic optimization problems. *Automatica*, 72, 194–204.
- Xu, L., Yi, X., Sun, J., Shi, Y., Johansson, K. H., & Yang, T. (2022). Quantized distributed nonconvex optimization with linear convergence. In 2022 IEEE 61st Conference on Decision and Control (CDC) (pp. 5837–5842).
- Yan, F., Sundaram, S., Vishwanathan, S., & Qi, Y. (2013). Distributed autonomous online learning: Regrets and intrinsic privacy-preserving properties. *IEEE Transactions on Knowledge* and Data Engineering, 25, 2483–2493.
- Yang, T., Yi, X., Wu, J., Yuan, Y., Wu, D., Meng, Z., Hong, Y., Wang, H., Lin, Z., & Johansson, K. H. (2019). A survey of distributed optimization. Annual Reviews in Control, 47, 278–305.
- Yi, X., Li, X., Yang, T., Xie, L., Chai, T., & Johansson, K. H. (2021). Distributed bandit online convex optimization with time-varying coupled inequality constraints. *IEEE Transactions on Automatic Control*, 66, 4620–4635.
- Yuan, D., Zhang, B., Ho, D. W., Zheng, W. X., & Xu, S. (2022). Distributed online bandit optimization under random quantization. *Automatica*, 146, 110590.
- Zhang, L., Kekatos, V., & Giannakis, G. B. (2017a). Scalable electric vehicle charging protocols. *IEEE Transactions on Power Systems*, 32, 1451–1462.
- Zhang, W., Zhao, P., Zhu, W., Hoi, S. C. H., & Zhang, T. (2017b). Projection-free distributed online learning in networks. In Proceedings of the 34th International Conference on Machine Learning (pp. 4054–4062).