

SPECWANDS: An Efficient Priority-based Scheduler Against Speculation Contention Attacks

Bowen Tang[✉], Chenggang Wu[✉], Pen-Chung Yew[✉], *Fellow, IEEE*, Yinqian Zhang[✉], Mengyao Xie[✉],
Yuanming Lai[✉], Yan Kang[✉], Wei Wang[✉], Qiang Wei[✉], Zhe Wang[✉]

Abstract—Transient Execution Attacks (TEAs) have gradually become a major security threat to modern high-performance processors. They exploit the vulnerability of speculative execution to illegally access private data, and transmit them through timing-based covert channels. While new vulnerabilities are discovered continuously, the covert channels can be categorised to two types: 1) *Persistent Type*, in which covert channels are based on the layout changes of buffering, e.g. through caches or TLBs; 2) *Volatile Type*, in which covert channels are based on the contention of sharing resources, e.g. through execution units or issuing ports. The defenses against the persistent-type covert channels have been well addressed, while those for the volatile-type are still rather inadequate. Existing mitigation schemes for the volatile type such as *Speculative Compression* and *Time-Division-Multiplexing* will introduce significant overhead due to the need to stall the pipeline or to disallow resource sharing. In this paper, we look into such attacks and defenses with a new perspective, and propose a scheduling-based mitigation scheme, called SPECWANDS. It consists of three priority-based scheduling policies to prevent an attacker from transmitting the secret in different contention situations. SPECWANDS not only can defend against both inter-thread and intra-thread based attacks, but also can keep most of the performance benefit from speculative execution and resource-sharing. We evaluate its runtime overhead on SPEC 2006/2017 benchmarks. The experimental results show that SPECWANDS has a significant performance advantage (3%-5%) over the other two representative schemes.

Index Terms—Transient Execution Attack, Simultaneous Multi-Threading, Resource Contention, Scheduling Strategy.

I. INTRODUCTION

SIMULTANEOUS multi-threading (SMT), also known as hyper-threading, has become an important feature on modern high-performance processors. It allows multiple threads to run simultaneously on a physical core and share the resources in the instruction pipeline to cover the slack caused by the

stalled threads, thereby improving the efficiency and throughput of the pipeline. However, due to the resource sharing on the pipeline, SMT can introduce new security vulnerabilities. Multiple threads may compete for shared resources and interfere with each other's execution under the common *first-come-first-served* (FCFS) policy. If an attacker can control one thread, he/she can figure out the execution state of other threads according to the difference in its execution time and then infer some private information, which is the so-called SMT contention-based side channel [1]–[3].

Such attacks can be mitigated by scheduling mutually distrusting threads on different physical cores. However, the recent *transient execution attacks* (TEAs) [4]–[19], such as the well-known Meltdown and Spectre, cannot be defended using such an approach. It is because an attacker can spawn and control multiple threads in some attack scenarios. The system cannot distinguish which ones are malicious when resource contention occurs.

Take an example from the work in [20]. It installs a malicious plug-in running on a sandboxed browser to launch such an attack. Assume two threads are both created by the plug-in and run on a physical core with SMT. One of them, called *Trojan*, leverages speculative execution to access a secret outside the sandbox. Trojan thread then issues a burst of requests to keep the resource busy if the bit to be transmitted is "1", and leaves the resource idle if it is "0" instead. The other thread, called *Spy*, then attempts to acquire the same resource and infer the secret value based on whether the resource is busy or not by measuring its acquisition time. In such an attack scenario, the resource contention is used as a covert channel to transmit the illegally obtained data from speculative accesses.

To block such covert channels, researchers have proposed a variety of defenses. One well-known approach is *Speculation Compression* [21]–[24], which delays the speculative data to be propagated in the pipeline. That is, if an operand of an instruction comes from a speculative instruction, it will not be issued until the speculative instruction it depends on has become non-speculative. This approach prevents the data of a speculative instruction from being transmitted via the covert channel. However, it will obstruct the speculative execution (e.g. from branch prediction) that has been the cornerstone of a modern CPU to improve its performance. Based on our own simulation results, its performance hit can be as high as 15% on a typical CPU with SMT. The other approach is to partition the resources in the spacial or temporal dimensions, such as *Time-Division-Multiplexing* (TDM), to avert inter-thread interference [25]–[27]. Although this approach doesn't obstruct

This research was supported by the National Natural Science Foundation of China (NSFC) under Grant 61902374 and U1736208, and Innovation Funding of ICT, CAS under Grant No.E161040. (*Corresponding Author: Zhe Wang.*)

Bowen Tang, Chenggang Wu, Mengyao Xie, Yuanming Lai, Yan Kang, Wei Wang, Zhe Wang are with SKLP, Institute of Computing Technology, CAS, Beijing 100190, China, and also with University of Chinese Academy of Sciences, Beijing 100049, China. Chenggang Wu and Zhe Wang are also with Zhongguancun Laboratory, Beijing, China. Email: {tangbowen, wucg, xiemengyao, laiyuanming, kangyan, wangwei2021, wangzhe12}@ict.ac.cn

Pen-Chuang Yew is with Computer Science & Engineering Department of the University of Minnesota-Twin Cities, MN 55455, USA. Email: yew@umn.edu

Yinqian Zhang is with Department of Computer Science and Engineering of the Southern University of Science and Technology, Shenzhen 518055, China. Email: yinqianz@acm.org

Qiang Wei is with State Key Laboratory of Mathematical Engineering and Advanced Computing, ZhengZhou 450000, China. Email: prof_weiqiang@163.com

the speculative execution, it contradicts the original intention of resource sharing using SMT, and will also incur non-negligible performance overhead (e.g. more than 12% overhead according to our evaluation).

Besides the well-known resource contention in SMT, researchers have found the resource contention also exists in the single thread scenario, and it can be abused as a new covert channel [28], [29]. Such attacks exploit the contention caused by multiple instructions scheduled in the same scheduling window within a thread. These instructions have no dependence among them, and can be issued simultaneously in the pipeline that supports *multi-issuing* and *out-of-order* execution. The attacker can use the contention at the issuing port as a covert channel. Moreover, he/she only needs to launch one single thread without the need for inter-thread synchronization. This kind of attacks, which leverage intra-thread covert channels, thus have a higher probability of success. TDM-based defense approaches are basically ineffective and are difficult to harden for this scenario.

In order to defend against the TEAs that exploit resource contention as a covert channel, which we call *speculative contention attacks* (SCAs), while minimizing the performance overhead, we proposed a secure scheduling scheme for shared resources, called SPECWANDS. The main idea behind SPECWANDS is to batching multiple operations into groups, and ensure that each group can share a resource without any interference from other groups in the same or different threads. To apply such an idea to different scenarios, we use the following three priority-based scheduling policies.

- **NOP: Non-speculative Operations have a higher Priority.** SPECWANDS assigns a higher priority to non-speculative operations. They not only can be scheduled ahead of all other speculative operations, but also allowed to preempt the speculative operations already occupying the resource. This policy can be used as a guideline for delimit the boundaries of each group, i.e. each non-speculative operation is the header of each group.
- **LOP: Last-owner-thread's Operations have a higher Priority.** When there are multiple speculative operations from different threads, SPECWANDS assigns a higher priority to the speculative operations whose owner thread used the resource most recently. This policy further clusters the speculative operations into groups based on their owner threads, i.e. their group header non-speculative operations.
- **EOP: Earlier Operations have a higher Priority.** Within the same SMT thread, when the operations that request a resource are all speculative, SPECWANDS assigns a higher and preemptive priority (similar to the NOP policy) to the operations that are issued earlier in program order. Different from NOP and LOP policies, its purpose is to prevent the backward contention within a group, i.e., to prevent a later operation from blocking an earlier operation in the group due to multi-issuing and out-of-order execution.

The above policies not only maintain the security principle of *Speculative Non-Interference* (SNI) [30], but also facilitate the temporal locality of the shared resource usage. From




Fig. 1: The microarchitecture of a typical high performance CPU that supports *speculative, out-of-order* execution with a 2-context SMT.

our simulation results, SPECWANDS only introduces 3% and 5% performance overhead on SPEC 2006 and SPEC 2017 benchmarks, respectively, which are much lower than those in STT [21] and SMT-COP [25], the representative work of the other two defenses.

To summarize, this paper makes the following contributions.

- 1) We examine the deficiencies in existing defense approaches against SCAs, such as speculation compression and TDM, and propose a novel grouping-based mitigation scheme to reduce most delay between operations within the group, while blocking potential cover channels created in both inter-thread and intra-thread modes.
- 2) We present a hardened instruction scheduler practicing above scheme, called SPECWANDS. It consists of three priority-based scheduling policies for different contention situations to divide the instructions into groups and ensure their security. Moreover, we analyze the performance impact of each policy based on the distribution of different contention situations.
- 3) We evaluate the performance overhead and power consumption of SPECWANDS via detailed simulations. Compared with the other two representative defenses [21], [25], SPECWANDS has lower overheads and power consumption for SPEC 2006/2017 benchmarks.

II. BACKGROUND

A. Modern CPU Pipeline and SMT

Figure 1 shows a typical microarchitecture of a modern high performance CPU. The branch prediction unit, which consists of PHT/BTB/RSB, facilitates the control-flow speculation, while renaming-based instruction scheduling and a ROB with a squashing mechanism support the out-of-order program execution. These techniques optimize the use of instruction level parallelism (ILP) and can improve the processor performance quite substantially. To further improve the throughput of an instruction pipeline, switching from a thread that encounters a long-delay cache miss to another thread ready for execution can hide the memory latency and improve resource utilization from another view. This approach eventually led to the design of *simultaneous multi-threading* (SMT) [31].

In an SMT processor, multiple *hardware-supported threads* (denoted as HTs in the rest of the paper) are running on the




Fig. 2: The PoC of an inter-thread SCA that exploits Spectre-V1 vulnerability. The "index" can be steered by an attacker, and the "secret" is the target to be leaked. The highlighted code can occupy an integer division unit and its corresponding issuing port.

pipeline concurrently and share most of its critical resources. The storage resources, such as physical register file (PRF), ROB and PHT/BTB/RSB are shared among HTs by physical partitioning them or using tag-based partitioning schemes. It allows the states of multiple HTs to be maintained simultaneously without using context switching. Some computational components, such as the instruction fetcher, decoder and register-renaming unit, are shared among HTs using a time-division-multiplexing (TDM) scheme. For L1-cache/TLBs, execution units and issuing ports, they are fully shared by all HTs to maximize their utilization. Earlier studies have shown that, compared with a single-threaded processor, the performance improvement brought on by a 2-context SMT processor can be up to 30% with negligible hardware cost [31]. Hence, SMT has been widely used in PCs and servers.

B. Side Channel Attacks on SMT Processors

While resources sharing can bring performance benefits, it also exposes the SMT processors to potential side channel attacks. For the shared storage components, such as L1-caches/TLBs, the interference among sharing HTs can cause a subsequent access to be a hit or a miss. An attacker can exploit this side effect by measuring the difference in its access time, and infer some private information such as the encryption key or keyboard strokes through the access traces [32]. Because the placement and the measurement of the data layout in the side channel can be done asynchronously, such channels are called *persistent* channels. For shared computational components, such as issuing ports [3] and execution units [1], [2], the contention among threads can prolong the execution time of each HT, which can also be perceived by the attacker to reason about the private information related to the execution flow. Such side channels are referred to as *volatile* channels.

C. Transient Execution Attacks and Covert Channels

Side channel attacks have not attracted attention of processor designers until the emergence of *transient execution attacks* (TEAs). The core logic of a TEA has three main steps: *Accessor*, *Sender* and *Receiver* [4], [33]. In the accessor step, the attacker illegally accesses the secret data through a staged speculative execution. There are two ways the attacker can set up the speculative attacks. In *Spectre-type* attacks, the attacker exploits hardware branch predictors on control flow transfer or memory




Fig. 3: The PoC of an intra-thread SCA, also called *SpecRewind* Attack, which also exploits Spectre-V1 vulnerability and leverages the intra-thread contention as covert channel.

disambiguation to bypass intended software defense codes, such as bound checking [19], data cleaning [13] or stack pivoting [14]. While in *Meltdown-type* attacks, the attacker exploits the bugs of access permission protection to break hardware isolation between domains, such as User_Space and Kernel_Space [18], GuestVM and Hypervisor [5], or SGX_Enclave and Untrusted_Software_Stack [7].

The attacker can then use the *sender* step and the *receiver* step to transmit the illegally accessed data through a covert channel. A covert channel works very similarly to that of a side channel. The only difference is that the sender and the receiver in a covert channel are both manipulated by the attacker. While in a side channel, the victim process is the sender and the receiver are controlled by the attacker. In this paper, we use the term *Speculative Contention Attacks* (SCAs) to describe the TEAs that are based on resource contention, i.e. the attacks that use *volatile covert channels*. Furthermore, we classify the existing SCAs into two categories.

Inter-thread SCAs. Figure 2 shows a PoC code of the Spectre-V1 attack that exploits the resource contention on the issuing port and the execution unit on an SMT processor. In this attack, HT_{Trojan} and HT_{Spy} are both controlled by the attacker, with HT_{Trojan} acting as both the accessor and the sender, and HT_{Spy} acting as the receiver. Firstly, HT_{Trojan} bypasses the bound check by manipulating the branch predictor at line 2, and reads the secret by out-of-bounds access at line 4 during the speculative execution. Then, HT_{Trojan} controls the execution of the subsequent division instructions according to the value of secret. Assume the secret has only one bit. If it is 1, the division will be executed. Meanwhile, HT_{Spy} will also perform division operations and measuring the time. If the time is shorter, it can infer that no contention has occurred and the secret is 0; Otherwise, the secret is 1.

Intra-thread SCAs. The above *inter-thread* SCAs can be extended and carried out in the same HT, i.e. an *intra-thread* SCA. Some researchers have shown that, on a superscalar processor, multiple independent instructions in the same scheduling window can compete for the resources and thus

can be used to form a covert channel [28], [29]. As Figure 3 shows, the attacker combines the three steps in the same HT, and delays the receiver step (via line 2) to make it executed simultaneously with the sender step. This attack is also known as *SpecRewind* Attack [28].

D. Existing Mitigations

In most cases, mitigations for the side channel attacks via persistent channels have been well established. They include domain partitioning [34]–[36], index/replacement randomization [37]–[39], and footprint-based detection [40], [41]. In particular, for TEAs through persistent covert channels, schemes that use *Invisible Speculation* [42]–[46] extends the squashing mechanism in the pipeline to cleanup and rollback the side effects in the cache memory for the mis-predicted speculative execution with modest performance and hardware overhead.

However, these methods cannot be generalized and applied to volatile channels. Currently, the only secure solution is to disable SMT for security-sensitive HTs [47], or scheduling mutually untrusted threads on different physical cores [48], [49]. However, this approach only works against traditional side-channel attacks when the protected target, such as the thread executing a cryptographic computation or code inside a secure enclave, can be identified by the programmer before running. But for SCAs, any thread with vulnerable speculative code can be exploited by an attacker. It's hard to distinguish an HT_{Trojan} from an HT_{Spy} as they are often from the same user group and supposed to be trustworthy.

Another solution is to use *Timing-Division-Multiplexing* (TDM) scheme on the shared resources [25]. It allocates time slices for each HT to avoid resource contention. However, this approach violates the original intent of SMT to share unused resources when available. It can incur significant performance overhead due to its rigidity in resource sharing (more than 12% in our evaluation). Although, some approaches try to adaptively allocate time slices to improve resource utilization [26], the adaptive measure can inevitably be used to become another potential covert channel. Other schemes [27], [50] adopt asymmetric allocation strategies for threads with different trust levels to ensure that highly trusted threads can obtain more time slices. However, the trust level needs to be specified by the programmer through some annotations. So, it comes back to the earlier question of "which threads can we trust?".

Another type of defenses against SCAs is *Speculation Compression* [21]–[24]. Instead of blocking covert channels, it disallows data or other potential microarchitectural side effects from propagating to the downstream instructions by stalling/blocking some dependent instructions during the speculative execution until the execution has reached some safe points. The advantage of such schemes is that they can block both persistent and volatile covert channels of TEAs comprehensively. But, due to the use of stalling and blocking of the dependent instructions, they often incur a significant performance overhead (up to 15% according to our evaluation).

III. THREAT MODEL

Table I lists the vulnerabilities exploited by existing SCAs, as well as the capabilities for their illegal accesses. We assume

TABLE I: The vulnerability and access capability of existing SCAs. AC: whether it can access the data cross hardware protection domains.

Attack	Vulnerability	AC
Spectre-PHT/BTB/RSB [12], [17], [19]	Control Flow Prediction	✗
Speculative Store Bypass [13]	Memory Disambiguation	✗
Speculative Load Disorder [51]	Memory Order Speculation	✗
SWAPGS [14]	Out-of-Order Execution	✓
Rogue System Register Read [6], [52]	Buggy #NM Exception Handler	✓
Meltdown [4], [5], [18]	Buggy #GP Exception Handler	✓
L1TF (Foreshadow) [4], [7]	Buggy Terminate Fault Handler	✓
MDS [8]–[10], LVI [11]	Buggy Assist/Abort Data Forward	✓

a powerful attacker can launch any SCA listed in Table I within or across domains. For example, the attacker can inject an attack code through malicious Javascript scripts, or malicious browser plug-ins. The code can exploit Spectre-PHT vulnerability [19] to bypass the bound check of browser's sandbox and access some private keys and cookies. Or, the attacker can exploit Meltdown vulnerability [18] by crossing the hardware domain of the kernel and accessing some critical data structures. The attacker can then transmit the stolen secrets through a covert channel based on resource contention as shown in Figure 2 and Figure 3. Furthermore, the attacker can launch a malicious virtual machine (VM) in the cloud and exploit Foreshadow vulnerability [7] to access the data in other victim VMs residing on the same physical core. The malicious VM can also transfer the stolen data through the fabricated contention covert channel.

Out-of-Scope. We do not consider TEAs through persistent covert channels, e.g. cache or TLB. As explained in section II-D, existing defenses are effective and efficient to cover these attacks, and they are orthogonal to our scheme. We also exclude non-transient side channel attacks because of their limited threat. But in subsection II-D, we still introduce some effective defenses against those attacks.

IV. DESIGN OF SPECWANDS

A. Overview

We first revisit the handicaps of two existing defense approaches, i.e. Time-Division-Multiplexing (TDM) and Speculation Compression. For TDM, the strict partitioning of time slices is too rigid for most workloads that may have unbalanced resource requirements. For example, if we have two active HTs in the system, with one being more computation-intensive and the other more memory-intensive. Using TDM, almost half of the computation and memory resources may be wasted. For speculation compression, when branch instructions are issued frequently and the average branch resolution time is long (nearly 20 cycles for SPEC benchmarks according to our evaluation), the aggregated issuing delay will incur a significant performance overhead. Figure 4(a) shows the timelines of two HTs that execute the code snippet shown in the box. In each iteration, the division operation within the loop body need to be delayed until the guarding branch is resolved, i.e. until the operation becomes non-speculative. If the loop iterates more than 8 times, the overhead can reach 8X as long for SC policy.

Our Insight. The above observation leads us to conclude that *if the scheduler can batch multiple speculative operations from the same HT into a group and allow them to exclusively*




Fig. 4: The timelines of loop iterations in the code snippet shown in the figure under Speculative Compression (SC), Grouping (i.e. the policy of SPECWANDS), and native FCFS policies, respectively.

occupy the resource for a short period of time (as most of the speculative execution windows are relatively short), then it can avoid the delay on each group member to improve performance. As shown in Figure 4, compared to the timeline under SC policy in (a), the timeline of grouping-based policy in (b) greatly reduces the number of delays and is close to the timeline under the native FCFS policy in (c). However, to make such grouping secure against both inter-/intra-thread SCAs, we must overcome the following two challenges: 1) We must be able to form groups within an HT, and schedule the groups from different HTs to prevent group interference from being exploited by attackers who may launch inter-thread SCAs; 2) We must be able to eliminate backward contention among speculative operations within a group to defend against intra-thread SCAs.

To address these challenges, we propose a priority-based scheduler, called SPECWANDS. It consists of three scheduling policies: a) Non-speculative Operations have higher Priority over speculative operations (denoted as NOP); b) Last-owner-thread's Operations have higher Priority among speculative operations from different HTs (denoted as LOP); c) Earlier Operations have higher Priority within the same HT (denoted as EOP).

Among them, the NOP and LOP policies guide the group formation and regulate inter-thread scheduling among the groups, and the EOP policy resolves the backward resource contention within a group. As shown in Figure 4(b), the NOP policy enforces each group header operation to wait until it becomes non-speculative; LOP policy allows inner speculative operations within a group to inherit resource until another group header operation (from the other HT) becomes non-speculative; EOP policy inhibits the disorder of inner speculative operations within a group.

The security concept behind them is the principle of *Speculative Non-Interference (SNI)* [30], i.e. the observable states of a speculative execution should be indistinguishable from those




Fig. 5: The workflow of the NOP policy and its defense mechanism in an inter-thread scenario. It is also the same in an intra-thread scenario.

when the same code sequence is executed non-speculatively. Focusing on resource contention-based covert channels, the SNI principle means that the machine states as the result of the resource allocation policies should be independent of whether the code sequence is executed speculatively or not. We will detail the workflow, defense mechanism and performance impact of these policies in the following subsections.

B. NOP: Non-speculative Operations have higher Priority

In SPECWANDS, each non-speculative operation is treated as the header of a group. When a group header operation competes for resources together with another group inner speculative operations, it should be assigned higher and preemptive priority.

This policy ensures that non-speculative operations from a potential receiver can access the shared resource immediately, and will not observe the interference caused by speculative operations staged by a potential sender. Figure 5 shows such an example with two instructions from two HTs, one as a sender and the other as a receiver, competing for an issuing port. The policy takes effect in the following two scenarios.

If the port is free when the contention occurs, the non-speculative instruction will access the port immediately. As Figure 5(a) shows, instruction I_X from HT₀ and instruction I_Y from HT₁ compete for the port at t_0 . The status of I_X is speculative, and I_Y is not. According to the NOP policy, I_Y can occupy the port immediately, and I_X needs to wait until the port is free. In this scenario, if HT₀ acts as the sender and HT₁ as the receiver, owing to the NOP policy on HT₁, no information can be transmitted.

If the port is currently occupied by a speculative instruction, the non-speculative instruction can preempt it immediately. As shown in Figure 5(b), speculative instruction I_X from HT₀ (acting as the sender) is occupying the port exclusively at t_0 . At t_1 , instruction I_Y (acting as the receiver) is ready and becomes non-speculative. According to the NOP policy, it can preempt the port, and I_X needs to wait for being re-issued until the completion of I_Y at t_2 . In this case, the sender cannot interfere with the receiver, thus no information can be transmitted either.




Fig. 6: The workflow of the LOP policy and its defense mechanism.

C. LOP: Last-owner-thread's Operations have higher Priority

If the group header operation has occupy a resource, the rest of inner speculative operations within the group can inherit the ownership without waiting for becoming non-speculative, until it is preempted by another group header operation. In other words, when multiple speculative operations from different HTs compete for a resource, SPECWANDS will give a higher priority to the competitor whose HT is the most recent non-speculative owner of the resource.

Note that this policy is *non-preemptive*, which means the owner HT can exclusively occupy the resource during the current period, regardless of whether it needs it or not, until the other HT preempts the resource, i.e. switches the ownership, via the NOP policy.

Combined with the NOP policy, this policy guarantees that the resource allocation across multiple HTs is independent of any speculative operation. It prevents the accessor of an SCA from modulating the resource to setup a covert channel. Figure 6 shows the workflow of the LOP policy in more details and discuss how it can defeat inter-thread SCAs.

In Figure 6(a), we assume HT_1 is a more recent non-speculative owner of the port. At t_2 , the instruction I_X of HT_0 is ready, but according to the LOP policy, it still cannot occupy the port even though the port is free. At t_3 , when the instruction I_Y of HT_1 is ready, it can be issued immediately. If HT_0 acts as the sender and HT_1 as the receiver, nothing can be transmitted because HT_1 observes no delay.

On the contrary, in Figure 6(b), HT_0 is the most recent non-speculative owner and its subsequent instruction I_X (acting as the sender) can occupy the port immediately at t_2 . Thus, the instructions I_Y from HT_1 (acting as the receiver) needs to wait until it becomes non-speculative at t_4 . In this case, although a delay occurs, the receiver cannot attribute it to the contention created by the sender, because no matter I_X exists or not, HT_1 still needs to wait as it is not the most recent non-speculative owner. The delay only depends on the previous non-speculative instructions of HT_0 , which cannot




Fig. 7: The workflow of the EOP policy and its defense mechanism.

be dependent to the speculative accessor of any SCA.

D. EOP: Earlier Operations have higher Priority

The above policies does not aim at intra-thread SCAs, i.e. the contention of speculative operations within the group, due to multi-issuing and out-of-order execution. Therefore, we need more information to identify potential receivers and senders and keep a receiver from observing the interference created by a sender within the same HT.

With a closer look at the PoC in Figure 3, we can notice that the receiver must be earlier than the sender in the program order. Otherwise, the completion time of the receiver will depend on the resolution time of the branch instruction at Line-8, instead of its own execution time. That is why intra-thread SCAs are called *SpecRewind Attacks* [28]. Based on this observation, SPECWANDS assigns a higher and preemptive priority to the earlier speculative operations than other speculative operations within the same HT.

Figure 7 shows the EOP workflow using an example with two speculative instructions from HT_0 . We assume the earlier one (I_X) serves as the receiver and the later one (I_Y) as the sender. There is no data dependence between them, and the issuing of receiver is delayed because its operands are not available until it encounters the sender within the scheduling window. As shown in Figure 7(a), if the port is idle at t_0 and two instructions are both ready to be issued, the earlier receiver will be scheduled first. However, as shown in Figure 7(b), if the sender is issued at t_0 and the receiver becomes ready at t_1 , it will immediately preempt the issuing port.

E. The Analysis on Performance Impact

We collect some statistics on various contention scenarios on an insecure native SMT system to estimate the performance impact of those three policies. The configuration and the methodology of the experiments are the same as those described in subsection VI-A, and the results are presented in Figure 8.

For NOP. The NOP policy can affect the performance in two ways. It can positively eliminate the contention caused by the wrong-path speculation. Also, it can negatively preempt




Fig. 8: The distribution of various contention scenarios on a "vanilla" SMT processor. **S1:** one competitor is non-speculative and the other is speculative; **S2:** both competitors from different HTs are speculative, and the competitor from the most recent owner HT is the first to occupy the resource; **S3:** same as S2, except the competitor is not from the most recent owner HT that occupies the source first; **S4:** both competitors are speculative and from the same HT.

the speculative execution on the correct path by some non-speculative operations, and force some of its operations to be re-executed. However, as shown in Figure 13, almost 50% of instructions are not issued (3%) or issued without contention (47%). For these two situations, SPECWANDS will not incur any overhead. Only about 1% of the issued instructions encounter a contention with one non-speculative and the other speculative competitor. This situation can lead to preemption under the NOP policy. Thus, we believe that the NOP policy will incur only modest overhead.

For LOP. The LOP policy is designed not only to break the *speculative dependence* required by all SCAs, but also to utilize the temporal locality of resource occupancy to minimize the performance impact. As shown in Figure 8, scenarios S2 and S3, i.e. both competitors are speculative and from different HTs, constitute 46% of total cases. Among them, 42% are in scenario S2, i.e. the first arriving request are from the last owner HT; While only 4% cases are in scenario S3, i.e. the first arriving request is not from the last owner HT. The results show that the efficiency of the LOP policy used in SPECWANDS approximates to the FCFS policy used in the insecure native SMT processor.

For EOP. From Figure 8, we can see that only about 1% of the cases are in scenario S4, i.e. both competitors are speculative and from the same HT, which may violate the EOP policy and cause preemption and re-execution with a negative impact on performance. This result indicates that the EOP policy will also have a minimal impact on the overall performance.

Overall, the performance impact of all three scheduling policies are quite small. And subsequent performance evaluation on a simulated system, as described in subsection VI-C and subsection VI-D, also confirm our assertions.

V. KEY IMPLEMENTATION ASPECTS

Figure 9 presents the framework of SPECWANDS on a typical SMT microarchitecture. Before introducing its implementation, we need to clarify the definition on when a speculative instruction becomes "non-speculative". It can determine the defense capability and the impact on performance. Similar to earlier work such as [21], [42], [43], SPECWANDS has two operating modes that correspond to two variants of definition on when an instruction has become "non-speculative".




Fig. 9: The framework of SPECWANDS. The shaded boxes are those introduced by SPECWANDS.

- **SPECWANDS-Spectre.** This operating mode only defends against SCAs that exploit vulnerabilities from branches, e.g. Spectre-PHT/BTB/RSB. Here, a speculative instruction is considered to have become *non-speculative* when all its previous branch instructions have been resolved and predicted correctly. This mode has a small performance overhead because the speculative instructions from the correctly-predicted path can become non-speculative quickly and free to compete for resources as the instructions in the unsecured native processor. But its defense scope is more restrictive, and should be deployed with other mitigation schemes to form a more comprehensive defense system.
- **SPECWANDS-All.** This variant can defend against all SCAs that include existing SCAs and any future SCA. Here, an instruction is considered to be non-speculative only when it reaches the head of ROB without triggering an exception. This variant has a relatively higher performance overhead due to longer waiting time for becoming non-speculative. But it has a much wider defense scope so that it does not rely on any other mitigation schemes.

Based on the above definition, we can also give two variants of the definition on the instruction ordering in the EOP policy. In the SPECWANDS-ALL mode, we adhere to the conventional definition of instruction ordering, i.e. an "earlier" instruction means an "older" instruction in the original program order. In the SPECWANDS-Spectre mode, we define instruction ordering between two instructions using their relative *speculative degree*, which means the number of control flow predictions (branches) exercised by the instruction. From the view of dynamic control flow graph, the instruction in the deeper basic block (dominated by more branches) has larger speculative degree. Taking the PoC in Figure 3 as an example, the division instruction at Line-13 has 2-more speculative degree than the division instruction at Line-4, since before Line-13 enters the pipeline, the speculation of previous branches at Line-8 and Line-11 must have been exercised. This variant further reduces the performance overhead of the EOP in the SPECWANDS-Spectre mode, because instructions within the same basic block have

the same speculative degree, and thus no preemption and re-execution occurs.

A. Speculative Status Checker (SSC)

SSC plays the role to check whether an instruction is speculative or not, and compute its speculative degree if it is. Such information is needed in the NOP and EOP policies. SSC is associated with ROB, which provides a global program ordering and execution status of each HT. When instructions are inserted/removed in/from ROB, or ROB receives updated speculation information, SSC will be activated to check and update the speculation status of each ROB entry, and then notify the instruction scheduler. The speculation status is recorded in the following two fields in each ROB entry.

- **Spec_Flag**: 1-bit tag indicating whether the instruction is speculative or not.
- **Spec_Degree**: 7-bit tag specifying the *speculative degree* of the instruction.

In a simple implementation, SSC can scan from the header of ROB, setting the *Spec_Flag* of each instruction to non-speculative and the *Spec_Degree* to zero, until it encounters an unresolved branch. The *Spec_Flag* of the subsequent instructions are all set to speculative, and the *Spec_Degree* will be incremented with the number of scanned unsolved branches. However, such an implementation may incur significant overhead and power consumption when ROB is large as in modern CPUs (more than 200). In SPECWANDS, we limit the width of each scan and adopt a progressive scanning strategy. In each round, SSC only scans a fixed number of instructions (usually the same as the issue width), and records the results in three intrinsic registers for next scan.

- **Last_Pos**: 8-bit field pointing to the ending entry of this scan.
- **Last_NS**: 8-bit field pointing to the entry of the last non-speculative instruction in this scan.
- **Spec_Degree_Counter**: 8-bit field accumulating the number of unresolved branches encountered.

When a ROB squash occurs due to a mispeculation, SSC can quickly reset the *Last_Pos* to the position of the youngest unsquashed instruction, and recover the *Last_NS* and *Spec_Degree_Counter* from the *Spec_Flag* and *Spec_Degree* fields of that instruction.

B. Enhanced SMT Instruction Scheduler

Each reservation station (RS) entries needs to be tagged with two fields: *Spec_Flag* and *Spec_Degree*, which will be updated by SSC and used by the SMT instruction scheduler. The scheduler also need to add a *Victim_Slot* for each issuing port to temporarily store each preempted instruction. The instruction in *Victim_Slot* will be re-inserted into the RS. It also needs an intrinsic control register for scheduling, which includes the following four fields:

- **Free_Flag**: 1-bit field indicating whether the port is free or not. Only when it is cleared (i.e. free), the following four fields can be valid.
- **Owner_TID**: 1-bit field indicating which HT is occupying the port.




Fig. 10: The workflow of the instruction issuing logic in the SPECWANDS scheduler.

- **Owner_Spec_Flag**: 1-bit field recording whether the occupying instruction is speculative.
- **Owner_Spec_Degree**: 7-bit field recording the speculative degree of the occupying instruction

Figure 10 shows the workflow of the enhanced SMT instruction scheduler. **Step-1:** Select a ready instruction from RS as the candidate. **Step-2:** Determine whether the candidate's thread ID (TID) matches the port's *Owner_TID*. If they match, go to Step-3; Otherwise, go to Step-7. **Step-3:** Check the port's *Free_Flag* to determine whether it is free or not. If it is free, go to Step-7; Otherwise, go to Step-4. **Step-4:** If the candidate's TID matches the port's *Owner_TID*, but the port is not free, it means the port is being occupied by another instruction from the same HT. In this case, according to the EOP policy, we can just compare their speculative degrees. If the candidate wins, go to Step-6 for preemption; Otherwise, go to Step-8. **Step-5:** If the candidate does not match the port's *Owner_TID*, it means the port is occupied by another HT. According to the NOP policy, we need to check whether the candidate is non-speculative and the owner instruction is speculative or not. If so, go to Step-6; Otherwise, go to Step-8. **Step-6:** According to the NOP or EOP policy, preempt the occupying instruction and put it in the port's *Victim_Slot*. **Step-7:** Issue the candidate, update the port's control register. **Step-8:** When this step is reached, it means issuing of this candidate has failed. So, just skip it and schedule the next instruction.

VI. EVALUATION

A. Experiment Setup and Methodology

We implemented a prototype of SPECWANDS on Gem5 simulator [53] (version *fe187de9bd*) with the O3 CPU model. The parameters of main components are shown in Table II. We add issuing ports and configure the grouping of execution units similar to Intel Skylake microarchitecture [54]. SPEC CPU 2006 and 2017 (rate) benchmarks are used with *ref* input data. To evaluate the impact of SMT, we pair the benchmarks according to their types (integer or floating-point) and program characteristics (number of branches or L2 Cache misses). For SPEC 2006, we use a pairing scheme similar to the one used in [25], which divides them into three groups: INT-INT, FP-FP, and INT-MIX; For SPEC 2017, based on their

TABLE II: Parameters used in the simulated micro-architecture for the baseline data. The label shown after each component indicates its sharing strategy among multiple HTs, where "S" means total sharing, "P" means fair partition, "M" means multiplexing with yield scheme.

Component	Parameter Value
Core Overview	8-issue, out-of-order, 2-context SMT, 2Ghz
Pipeline	Fetcher/Decoder/Register Renamer (M), 64-entry RS (P), 256 Int / 256 FP Physical Registers (P), 8 Issue Ports (S), 92-entry ROB (P), 32-entry LQ (P), 32-entry SQ (P)
BPU	Tournament branch predictor(S), 4096 BTB (S), 16 RSB (S)
Private L1-I Cache	32KB 64B line, 4-way, 1 cycle RT latency, 8 MSHRs (S)
Private L1-D Cache	64KB, 64B line, 8-way, 1 cycle RT latency, 8 MSHRs (S)
Shared L2 Cache	2MB bank, 64B line, 16-way, 8 cycles RT local latency, 16 cycles RT remote latency, 16 MSHRs (S)
Coherence Protocol	inclusive, Directory-based MESI protocol
Network	4×2 mesh, 128b link width, 1 cycle latency per hop
DRAM	2GB, 50 ns RT latency after L2

characteristics [55], we select the pairs and also divide them into three groups. Similar to other work in this area [25], [42], we first run each pair with the O3 CPU model and skip 10 billion instructions of each benchmark, and then obtain the statistics on the next 1 billion of each benchmark for analysis¹.

B. Security Evaluation

To evaluate the effectiveness of SPECWANDS, we construct two PoCs of inter/intra-thread SCAs as shown in Figure 2 and Figure 3. We choose the integer division unit as the covert channel because it takes 12 cycles to complete the computation, which will create a larger window for contention compared to other single-cycle and pipelined functional units. In PoCs, 1 bit value can be transmitted per iteration. We repeat it 100 times to reduce the statistical error. For the inter-thread PoC, considering that GEM5 does not support full-system simulation in the SMT mode, and the memory space of each HT is completely isolated, it is quite challenging to synchronize the HT_{sender} and $HT_{receiver}$ in each iteration. Thus, we add an instruction in the ISA dedicated to synchronize HTs on SMT, whose function is similar to *pthread_barrier_wait()*. The simulation results of the SPECWANDS-hardened system compared to the native system are presented in Figure 11. It shows that the attacker can accurately leak each bit in the native system, while unable to do so in the SPECWANDS-hardened system.




Fig. 11: Latency (of four integer division instructions) measured by the receiver of inter/intra-thread SCA running on the native system and the SPECWANDS-hardened system. The figure only shows the first 16 transmitted bits (bitstream is "01001001,01101110", which represents the ASCII code of "It"). Due to the limited space in the figure, we superimpose the two lines for the inter-thread latency above those for the intra-thread latency, and shift them upward along the y-axis by a constant value of 9 to make them easy to read.

¹We do not use *Simpont* evaluating method, before it needs atomic simulation to fast forward non-sampling codes, but Gem5's atomic CPU does not support SMT.

TABLE III: Mean statistic of running SPEC 2006/2017 on each system. "SW": SPECWANDS, "-Sp": Spectre-Mode, "-All": All-Mode. "LW": Latency of operand-ready instruction waiting for issuing; "LT": Latency of issue-Trying, which equals the latency between the moment of instruction being issued first time and the moment being issued successfully (last time); "LX": Latency of instruction execution. "BR": Busy rate of issuing ports; "UR": Utilization rate of issuing width. "FR": Full-event occurrence rate of reservation station.

	LW (c)	LT (c)	LX (c)	BR (%)	UR (%)	FR (%)
SMT-COP	15.6/14.8	0.9/0.8	3.9/3.9	24.4/24.1	43.6/51.4	19.8/20.5
STT-Sp	19.2/19.1	0.3/0.3	3.5/3.7	22.0/22.8	88.3/91.4	19.5/18.4
STT-All	30.1/33.3	0.2/0.2	3.2/3.5	21.1/19.9	94.3/94.6	38.7/37.7
SW-Sp	13.2/11.5	0.6/0.5	3.7/3.8	26.3/29.1	80.1/82.7	12.9/14.2
SW-All	15.5/13.2	0.5/0.4	3.6/3.6	22.4/22.6	74.6/77.8	16.6/18.2

C. Performance Evaluation

We compare the performance of SPECWANDS with two other schemes, where SMT-COP [25] represents time-division-multiplexing (TDM) scheme and STT [21] represents the speculative compression scheme. Since SMT-COP is not open-sourced, we re-implement its scheme on Gem5. To give a fair comparison, for SMT-COP, we do not implement other adaptive strategies that may sacrifice its security; For STT, we lift the protection for the persistent-channel components, such as cache/TLB and PHT/BTB/RSB. Similar to SPECWANDS, STT also has two defense modes, i.e. Spectre-Mode and All-Mode (called Futuristic-Mode in their paper).

Figure 12 (a) and (b) show the performance overhead of the three defenses using SPEC CPU 2006 and 2017 (rate), respectively. Moreover, to give a more detailed analysis on the performance among these schemes, we record other statistics such as the latency of operand-ready instructions waiting for issuing, the busy rate of issuing port, etc., as shown in Table III.

From the figure, we can see that the overall performance overhead of SPECWANDS-Spectre-/All on SPEC 2006 and SPEC 2017 are 2.94%/6.01% and 5.83%/10.56%, which are much lower than 15.58%/63.57% and 14.04%/67.47% of STT, and also much lower than 12.04% and 17.29% of SMT-COP. For each benchmark pair, SPECWANDS significantly outperforms STT in both defense modes. And this advantage also shows in comparison between SPECWANDS and SMT-COP, except for a few cases such as *povray-calculix* and *x264_r-leela_r*. We will give a more detailed analysis in the subsequent subsections.

Versus STT. The main overhead of STT comes from the need to wait for the dependant instructions to become non-speculative, which may cause the pipeline to stall. Table III indeed shows the system hardened by STT has a much larger issuing waiting latency than the other two (almost by 20 to 30 cycles). The trend is even more pronounced when the program has a larger branch resolution time or a longer dependency chain, such as the pairs containing *gcc*, *povray*, *libquantum*, *omnetpp* in SPEC 2006, and *perlbench_r*, *mcf_r*, *parest_r* in SPEC 2017. But, once the instructions are allowed to be issued in STT, HTs are free to compete for the resources as in an unprotected system. So, its utilization of issuing bandwidth is the most efficient among the three.

Versus SMT-COP. The main overhead of SMT-COP is the time waiting for an HT's own time slice, which often leads to longer issuing waiting latency and much lower issuing




Fig. 12: The performance overhead of SMT-COP, STT-Spectre, STT-All, SPECWANDS-Spectre and SPECWANDS-All on SPEC CPU 2006 and 2017 (rate) benchmarks. The bars taller than 80% are truncated, whose maximum values are marked in red. The geomean of the overhead for each group is also labeled in black. The benchmarks with a relative high overhead for SPECWANDS are highlighted in boxes.

port utilization (below 50%) as Table III shows. For memory intensive programs, such as *bzip2*, *gobmk*, *leslie3d* in SPEC 2006, and *x264_r*, *wrf_r*, and *exchange2_r* in SPEC 2017, such low utilization rates become more serious. The advantage of SMT-COP is its simplicity to implement, but its scalability is the worst among three schemes. The length of the time slice depends on the longest completion time of any unpipelined execution unit, and the waiting time is proportionate to the number of HTs supported on the CPU.

Compared to STT and SMT-COP, the main overhead of SPECWANDS is from the issuing waiting latency induced by the LOP policy, and the preemption/re-execution overhead induced by the NOP and EOP policies. However, its overall overhead is still among the lowest. Furthermore, the longer issue delay in STT and SMT-COP may cause a reservation station to become full more frequently, which will stall the pipeline and drag down the overall performance.

D. More Detailed Analysis on Performance Overhead

First, we analyze the impact of different scheduling policies on the overall performance. Based on their defense scopes, we separate the policies into two groups: 1) enabling NOP and EOP policies only for intra-thread SCAs; 2) enabling NOP and LOP policies only for intra-thread SCAs. The results are shown in Figure 13. The performance overhead of the NOP+EOP is around 0.1% to 0.3%. This is because most of the issuing port contention comes from speculative instructions. Thus, the preemption caused by NOP occurs only very infrequently. And since the native scheduler (using FCFS policy) tends to issue older operands-ready instructions, the preemption caused by EOP also occurs infrequently. In contrast, the overhead of the

NOP+LOP is relatively high at around 5%-8%, which basically constitutes most of the overall overhead. It shows that, although we try to exploit the temporal locality of the issuing port using LOP, it still cannot satisfy the bandwidth demand of all HTs.

Next, we analyze the benchmark pairs that have a high performance overhead under the NOP+LOP policies. We sample the number of issuing ports occupied by each HT and calculate the ratio of that number for HT_0 and HT_1 under native FCFS policy (as baseline) and SPECWANDS, respectively. The results are shown in Figure 14. We find that, for those program pairs that have a high overhead under LOP, one of them must be a dominant program that has a higher occupancy rate under the native policy. They are usually data-intensive programs such as *hmmer*, *calculix* and *x264_r*. When using the LOP policy, the non-dominant HT can have a larger share of the issuing port, which can slow down the dominant HT as a result. For this situation, one workaround is to referring more non-speculative access history of each HT for resource allocation instead of direct ownership inheriting. Such revised policy may give more opportunities to the HT that exactly needs the resource more eagerly. We will further evaluate more improvement solutions in the future works.

E. Power Consumption Evaluation

We applied McPAT [56] (version 1.3) to model the power consumption of SMT-COP, STT, and SPECWANDS. The results are shown in Table IV. We only modify the scheduler instead of introducing new RAM components, thus the incurred hardware cost and static power consumption (such as gate leakage, sub-threshold leakage) are negligible. Here we only measure dynamic power when running SPEC 2006/2017 benchmark




Fig. 13: The performance overhead of SPECWANDS using different combinations of policies on SPEC 2006 and 2017 benchmarks.

suites. To ensure a more accurate measurement, we patch the code of *Speculative Status Checker* and *Enhanced Scheduler* in SPECWANDS, as well as the code of *Data Flow Tracking* and *Tainting/Untainting* in STT, so that these actions can be reflected in the statistics of relevant pipeline components, i.e. execution units (EUs), reservation station (RS), and ROB.

As we can see from Table IV, SPECWANDS has a slightly higher power overhead on Execution Units compared to SMT-COP and STT, which mainly comes from the preemption and the re-execution required in the NOP and EOP policies. STT also consumes more power than SPECWANDS on RS and ROB accesses because both *Taint* and *Untaint* operations in STT require frequent accesses to these two components.

TABLE IV: The overhead of dynamic power consumption running SPEC 2006/2017 on each system. Because the running time and executed instructions of each benchmarks pairs differ under different systems, we calculate the average power consumption per nanosecond.

	EUs (%)	RS (%)	ROB (%)
SMT-COP	1.74/2.50	2.85/4.32	2.33/2.78
STT-Sp	1.52/2.89	7.99/9.12	10.86/12.03
STT-All	2.13/2.99	9.67/12.92	15.35/17.21
SPECWANDS-Sp	4.78/5.01	4.26/6.75	8.17/10.09
SPECWANDS-All	4.96/6.59	6.14/9.26	8.61/10.92

VII. DISCUSSION

In addition to issuing ports and execution units, recent research [27] has shown that other micro-architectural components that can incur inter-thread contention, such as Instruction Fetcher, Decoder, Reservation Stations, and Load Queue, also require similar attention. Here, we discuss the extension of SPECWANDS to those components.

Instruction Fetcher & Decoder. These components are usually shared among multiple HTs using a round-robin policy. However, when one HT is stalled due to an I-cache miss or pipeline stall, its time slice will be borrowed by the other HT, which can affect its execution time. Such optimization can thus be exploited as a covert channel. Specifically, fetching/decoding operations can be divided into two categories: *prediction-based* and *resolving-based*. Prediction-based operations are controlled by the prediction units. The attacker can encode them by manipulating the prediction history via speculative branch instructions. To block this path, we can just prohibit speculative branch instructions from polluting the prediction units until they




Fig. 14: The ratios of issue ports owned by two HTs (HT_0/HT_1). Under the LOP policy, the number of issue ports owned by each HT are sampled per 10,000 cycles, and then their arithmetic average is calculated.

are committed. Resolving-based operations are triggered when the execution of corresponding branch instructions completes and the mispredictions are detected. If these branch instructions are also dominated by other earlier speculative branches, these operations can also be modulated to transmit the secret. For this situation, we can apply the NOP+LOP policies of SPECWANDS to determine whether the time slice borrowing will be approved. The speculative status of operation-based fetching/decoding operations can also be checked with its corresponding branch instructions by the SSC module as section V describe.

Reservation Station (LS) & Load Queue (LQ). In some aggressive CPU, both RS and LQ adopt a constrained sharing strategy that sets a threshold of occupying entry number for each HT (usually larger than half). If one HT occupies most of entries and does not release them (achieved by manufacturing multiple cache misses), the number of available entries for the other HT will be suppressed, and thus can be exploited as a covert channel. To harden these components, we can adopt a hybrid strategy where half of the entries are set aside for fair partition between two HTs to avoid starvation, and then apply the NOP+LOP policies to the remaining half of the entries to maintain the performance benefit of temporal locality.

VIII. RELATED WORK

In addition to *speculation compression* and *time-division-multiplexing* (TDM), there are other approaches that can mitigate SCAs. Depending on their blocking schemes, we classify them into the following three categories.

Prediction Manipulation Prevention. This type of mitigations only targets Spectre-type SCAs. They work by isolating/flushing/bypassing the control prediction units, which prevent them from being trained by attackers to launch illegal speculative accesses. When Spectre-V1/V2 attacks were disclosed, Intel added the *Indirect Branch Control Mitigation* features (including IBRS/STIBP/IBPB) to its new processors [57]. It prevents the states of prediction units from being transferred between user/kernel modes, non-root/root modes, and across different HTs. For Spectre-V3 attacks, Intel recommended inserting an *lfence* instruction or enable *Speculative Store Bypass Disable* (SSBD) mitigation before a critical *store* instruction [58], which is similar to the ARM's recommendation [59]. Some software mitigations are also proposed. For example, *SLH* [5] tries

to replace branch instructions with *cmov* instructions, and *Retpoline* [60] converts all indirect *jmp* instructions to *call-ret* gadgets, which can bypass poisoned PHT and BTB. Compare with SPECWANDS, the above schemes can defend against SCAs for certain types of Spectre vulnerabilities only. Also, due to the lack of prediction accuracy, they will incur a higher performance overhead than SPECWANDS.

Domain Access Isolation. This type of mitigations is proposed for Meltdown-type TEAs. The core idea of their defense is to enforce the isolation between different domains, which prevents the secret data from being accessed by illegal cross-domain speculation. As a typical example, *KPTI* [61] and *USC* [62] unmap the critical entries of kernel page table from the user page table, which can foil a speculative access from the user space to the kernel space during its address translation. *SF-Xen* [63] introduces a similar scheme to isolate the hypervisor from untrusted guest VMs. Meanwhile, Chrome and Webkit browsers [64] leverage index masking and pointer poisoning to eliminate the overlap between the address spaces of different websites. At the hardware level, *OISA* [65] extends the RISC-V ISA to add dedicated memory access instructions for the secret domain, which ensure normal memory access cannot touch the secret domain speculatively. *ConTeXt* [66] modifies speculative data forwarding of cross-domain accesses to fill nonsense values for subsequent dependant instructions. In contrast to SPECWANDS, these schemes all require the assistance of upper-layer software, and can only protect data in a specified domain against illegal speculative accesses from other domains. They cannot alleviate various SCAs based on Spectre-like vulnerabilities within the domain.

Resource Contention Elimination. The original intent of such approaches is to defeat traditional side channel attacks based on resource contention. In some scenarios, they can also be used to defend against SCAs. Since a native X86 processor does not support turning on/off SMT dynamically at runtime, *DDM* [47] emulates this function through the *HLT* instruction and abstracts it into a user-friendly OS interface. *Partial-SMT* [48] first redesigns the user-level thread library so that users can define different thread groups according to their trust level, then it leverages affinity-scheduling features in the Linux kernel to make sure that different groups are scheduled to different physical cores. *Hyperspace* [67] modifies the compiler for Intel SGX development to instrument an enclave program and allows it to launch a shadow thread located on the same physical core. It thus prevents the contention from being tampered by an attacker. Same as *domain access isolation*, these methods still need software support to specify the protected threads. But from the perspective of TEAs, any thread or gadget can be compromised as the sender of a covert channel. It may not be practical to manually specify all of the protected objects. In addition, these methods only consider inter-thread contention and cannot be applied to intra-thread contention.

IX. CONCLUSION

In this paper, we propose a priority-based scheduler, called SPECWANDS, to defend against *transient execution attacks* (TEAs) that exploit inter-/intra-thread contention on a system

component as a covert channel. SPECWANDS contains three scheduling policies: a) Non-speculative Operations have higher Priority (NOP). It allows non-speculative operations to preempt speculative operations at any time; b) Last-owner-thread's Operations have higher Priority (LOP). It allocates the resource to the speculative operations which belong to the thread occupying the resource most recently. c) Earlier Operations have higher Priority (EOP). It gives the earlier speculative operations in a thread higher and preemptive priority over the later speculative operation within the same thread. These three policies batch multiple continuous speculative operations into a group, which can exclusively occupy the resource for a certain period of time without any delay. The performance evaluation shows that SPECWANDS has a significant performance advantage over other state-of-the-art approaches such as speculative compression and time-division-multiplexing.

REFERENCES

- [1] W.-M. Hu, "Lattice scheduling and covert channels," in *Proceedings 1992 IEEE Computer Society Symposium on Research in Security and Privacy*. IEEE Computer Society, 1992, pp. 52–52.
- [2] M. Andryscio, D. Kohlbrenner, K. Mowery, R. Jhala, S. Lerner, and H. Shacham, "On subnormal floating point and abnormal timing," in *2015 IEEE Symposium on Security and Privacy*. IEEE, 2015, pp. 623–639.
- [3] A. C. Aldaya, B. B. Brumley, S. ul Hassan, C. P. García, and N. Tuveri, "Port contention for fun and profit," in *2019 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2019, pp. 870–887.
- [4] C. Canella, J. Van Bulck, M. Schwarz, M. Lipp, B. Von Berg, P. Ortner, F. Piessens, D. Evtushkin, and D. Gruss, "A systematic evaluation of transient execution attacks and defenses," in *28th USENIX Security Symposium*, 2019, pp. 249–266.
- [5] V. Kiriansky and C. Waldspurger, "Speculative buffer overflows: Attacks and defenses," *arXiv preprint arXiv:1807.03757*, 2018.
- [6] J. Stecklina and T. Prescher, "Lazyfp: Leaking fpu register state using microarchitectural side-channels," *arXiv preprint arXiv:1806.07480*, 2018.
- [7] J. Van Bulck, M. Minkin, O. Weisse, D. Genkin, B. Kasikci, F. Piessens, M. Silberstein, T. F. Wenisch, Y. Yarom, and R. Strackx, "Foreshadow: Extracting the keys to the intel {SGX} kingdom with transient out-of-order execution," in *27th USENIX Security Symposium*, 2018, pp. 991–1008.
- [8] S. Van Schaik, A. Milburn, S. Österlund, P. Frigo, G. Maisuradze, K. Razavi, H. Bos, and C. Giuffrida, "Rid! Rogue in-flight data load," in *2019 IEEE Symposium on Security and Privacy (SP)*, 2019, pp. 88–105.
- [9] M. Schwarz, M. Lipp, D. Moghimi, J. Van Bulck, J. Stecklina, T. Prescher, and D. Gruss, "Zombieload: Cross-privilege-boundary data sampling," in *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, 2019, pp. 753–768.
- [10] C. Canella, D. Genkin, L. Giner, D. Gruss, M. Lipp, M. Minkin, D. Moghimi, F. Piessens, M. Schwarz, B. Sunar *et al.*, "Fallout: Leaking data on meltdown-resistant cpus," in *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, 2019, pp. 769–784.
- [11] J. Van Bulck, D. Moghimi, M. Schwarz, M. Lippi, M. Minkin, D. Genkin, Y. Yarom, B. Sunar, D. Gruss, and F. Piessens, "Lvi: Hijacking transient execution through microarchitectural load value injection," in *2020 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2020, pp. 54–72.
- [12] E. M. Koruyeh, K. N. Khasawneh, C. Song, and N. Abu-Ghazaleh, "Spectre returns! speculation attacks using the return stack buffer," in *Proceedings of the 12th USENIX Conference on Offensive Technologies*, ser. WOOT'18. USA: USENIX Association, 2018, p. 3.
- [13] M. Schwarz, C. Canella, L. Giner, and D. Gruss, "Store-to-heap forwarding: Leaking data on meltdown-resistant cpus (updated and extended version)," *arXiv preprint arXiv:1905.05725*, 2019.
- [14] A. LUȚAȘ and D. LUȚAȘ, "Bypassing kpti using the speculative behavior of the swaps instruction, <https://i.blackhat.com/eu-19/thursday/eu-19-lutas-bypassing-kpti-using-the-speculative-behavior-of-the-swaps-instruction-wp.pdf>," in *2019 BlackHat Europe Conference*, 2019.


- [15] M. Schwarz, M. Schwarzl, M. Lipp, J. Masters, and D. Gruss, "Netspectre: Read arbitrary memory over network," in *European Symposium on Research in Computer Security*, 2019, pp. 279–299.
- [16] M. Behnia, P. Sahu, R. Paccagnella, J. Yu, Z. Zhao, X. Zou, T. Unterluggauer, J. Torrellas, C. Rozas, A. Morrison *et al.*, "Speculative interference attacks: Breaking invisible speculation schemes," *arXiv preprint arXiv:2007.11818*, 2020.
- [17] G. Chen, S. Chen, Y. Xiao, Y. Zhang, Z. Lin, and T. H. Lai, "Sgxpectre: Stealing intel secrets from sgx enclaves via speculative execution," in *2019 IEEE European Symposium on Security and Privacy (EuroS&P)*, 2019, pp. 142–157.
- [18] M. Lipp, M. Schwarz, D. Gruss, T. Prescher, W. Haas, A. Fogh, J. Horn, S. Mangard, P. Kocher, D. Genkin *et al.*, "Meltdown: Reading kernel memory from user space," in *27th USENIX Security Symposium*, 2018, pp. 973–990.
- [19] P. Kocher, J. Horn, A. Fogh, D. Genkin, D. Gruss, W. Haas, M. Hamburg, M. Lipp, S. Mangard, T. Prescher, M. Schwarz, and Y. Yarom, "Spectre attacks: Exploiting speculative execution," in *40th IEEE Symposium on Security and Privacy (S&P'19)*, 2019.
- [20] A. Bhattacharyya, A. Sandulescu, M. Neugschwandtner, A. Sorniotti, B. Falsafi, M. Payer, and A. Kurmus, "Smotherspectre: exploiting speculative execution through port contention," in *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, 2019, pp. 785–800.
- [21] J. Yu, M. Yan, A. Khyzha, A. Morrison, J. Torrellas, and C. W. Fletcher, "Speculative taint tracking (stt): A comprehensive protection for speculatively accessed data," in *Proceedings of the 52nd Annual IEEE/ACM International Symposium on Microarchitecture*, 2019.
- [22] O. Weisse, I. Neal, K. Loughlin, T. F. Wenisch, and B. Kasikci, "Nda: Preventing speculative execution attacks at their source," in *Proceedings of the 52nd Annual IEEE/ACM International Symposium on Microarchitecture*, 2019, pp. 572–586.
- [23] K. Barber, A. Bacha, L. Zhou, Y. Zhang, and R. Teodorescu, "Specshield: Shielding speculative data from microarchitectural covert channels," in *2019 28th International Conference on Parallel Architectures and Compilation Techniques (PACT)*. IEEE, 2019, pp. 151–164.
- [24] P. Li, L. Zhao, R. Hou, L. Zhang, and D. Meng, "Conditional speculation: An effective approach to safeguard out-of-order execution against spectre attacks," in *2019 IEEE International Symposium on High Performance Computer Architecture (HPCA)*. IEEE, 2019, pp. 264–276.
- [25] D. Townley and D. Ponomarev, "Smt-cop: Defeating side-channel attacks on execution units in smt processors," in *2019 28th International Conference on Parallel Architectures and Compilation Techniques (PACT)*, 2019, pp. 43–54.
- [26] U. Nezir, B. Lus, and G. Kucuk, "Improved resource scheduling for lightweight smt-cop," in *2021 6th International Conference on Computer Science and Engineering (UBMK)*. IEEE, 2021, pp. 575–580.
- [27] M. Taram, X. Ren, A. Venkat, and D. Tullsen, "Secsmt: Securing smt processors against contention-based covert channels," in *USENIX Security Symposium*, 2022.
- [28] J. Fustos, M. Bechtel, and H. Yun, "Spectrerewind: Leaking secrets to past instructions," in *Proceedings of the 4th ACM Workshop on Attacks and Solutions in Hardware Security*, 2020, pp. 117–126.
- [29] T. Rokicki, C. Maurice, and M. Schwarz, "Cpu port contention without smt," in *European Symposium on Research in Computer Security*. Springer, 2022, pp. 209–228.
- [30] M. Guarnieri, B. Köpf, J. F. Morales, J. Reineke, and A. Sánchez, "Spectector: Principled detection of speculative information flows," in *2020 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2020, pp. 1–19.
- [31] D. M. Tullsen, S. J. Eggers, and H. M. Levy, "Simultaneous multithreading: Maximizing on-chip parallelism," in *Proceedings of the 22nd annual international symposium on Computer architecture*, 1995, pp. 392–403.
- [32] Q. Ge, Y. Yarom, D. Cock, and G. Heiser, "A survey of microarchitectural timing attacks and countermeasures on contemporary hardware," *J. Cryptogr. Eng.*, vol. 8, no. 1, pp. 1–27, 2018.
- [33] W. Xiong and J. Szefer, "Survey of transient execution attacks," *arXiv preprint arXiv:2005.13435*, 2020.
- [34] T. Kim, M. Peinado, and G. Mainar-Ruiz, "Stealthmem: System-level protection against cache-based side channel attacks in the cloud," in *21th USENIX Security Symposium*, 2012, pp. 189–204.
- [35] N. El-Sayed, A. Mukkara, P.-A. Tsai, H. Kasture, X. Ma, and D. Sanchez, "Kpart: A hybrid cache partitioning-sharing technique for commodity multicores," in *2018 IEEE International Symposium on High Performance Computer Architecture (HPCA)*, 2018, pp. 104–117.
- [36] V. Kiriansky, I. Lebedev, S. Amarasinghe, S. Devadas, and J. Emer, "Dawg: A defense against cache timing attacks in speculative execution processors," in *2018 51st Annual IEEE/ACM International Symposium on Microarchitecture (MICRO)*, 2018, pp. 974–987.
- [37] F. Liu and R. B. Lee, "Random fill cache architecture," in *2014 47th Annual IEEE/ACM International Symposium on Microarchitecture*, 2014, pp. 203–215.
- [38] Z. Wang and R. B. Lee, "New cache designs for thwarting software cache-based side channel attacks," pp. 494–505, 2007.
- [39] M. Werner, T. Unterluggauer, L. Giner, M. Schwarz, D. Gruss, and S. Mangard, "{ScatterCache}: Thwarting cache attacks via cache set randomization," in *28th USENIX Security Symposium (USENIX Security 19)*, 2019, pp. 675–692.
- [40] J. Cho, T. Kim, S. Kim, M. Im, T. Kim, and Y. Shin, "Real-time detection for cache side channel attack using performance counter monitor," *Applied Sciences*, vol. 10, no. 3, p. 984, 2020.
- [41] J. Depoix and P. Altmeyer, "Detecting spectre attacks by identifying cache side-channel attacks using machine learning," *Advanced Microkernel Operating Systems*, vol. 75, 2018.
- [42] M. Yan, J. Choi, D. Skarlatos, A. Morrison, C. Fletcher, and J. Torrellas, "Invisispec: Making speculative execution invisible in the cache hierarchy," in *2018 51st Annual IEEE/ACM International Symposium on Microarchitecture (MICRO)*. IEEE, 2018, pp. 428–441.
- [43] G. Saileshwar and M. K. Qureshi, "Cleanupspec: An" undo" approach to safe speculation," in *Proceedings of the 52nd Annual IEEE/ACM International Symposium on Microarchitecture*, 2019, pp. 73–86.
- [44] K. N. Khasawneh, E. M. Koruyeh, C. Song, D. Evtushkin, D. Ponomarev, and N. Abu-Ghazaleh, "Safespec: Banishing the spectre of a meltdown with leakage-free speculation," in *2019 56th ACM/IEEE Design Automation Conference (DAC)*. IEEE, 2019, pp. 1–6.
- [45] S. Ainsworth and T. M. Jones, "Muontrap: Preventing cross-domain spectre-like attacks by capturing speculative state," in *2020 ACM/IEEE 47th Annual International Symposium on Computer Architecture (ISCA)*. IEEE, 2020, pp. 132–144.
- [46] B. Tang, C. Wu, Z. Wang, L. Jia, P.-C. Yew, Y. Cheng, Y. Zhang, C. Wang, and G. Xu, "Specbox: A label-based transparent speculation scheme against transient execution attacks," *IEEE Transactions on Dependable and Secure Computing*, 2022.
- [47] Y. Zhang, Z. Zhu, and D. Meng, "Ddm: A demand-based dynamic mitigation for smt transient channels," in *2019 IEEE Intl Conf on Parallel & Distributed Processing with Applications, Big Data & Cloud Computing, Sustainable Computing & Communications, Social Computing & Networking (ISPA/BDCLOUD/SocialCom/SustainCom)*. IEEE, 2019, pp. 614–621.
- [48] X. Wu, Y. He, Q. Zhou, H. Ma, L. He, W. Wang, and L. Chen, "Partial-smt: Core-scheduling protection against smt contention-based attacks," in *2020 IEEE 19th International Conference on Trust, Security and Privacy in Computing and Communications (TrustCom)*. IEEE, 2020, pp. 378–385.
- [49] S. Blagodurov, S. Zhuravlev, and A. Fedorova, "Contention-aware scheduling on multicore systems," *ACM Transactions on Computer Systems (TOCS)*, vol. 28, no. 4, pp. 1–45, 2010.
- [50] M. Escouteloup, R. Lashermes, J. Fournier, and J.-L. Lanet, "Under the dome: preventing hardware timing information leakage," in *International Conference on Smart Card Research and Advanced Applications*. Springer, 2021, pp. 233–253.
- [51] Intel. (2021) Speculative load disordering / cve-2021-33149. [Online]. Available: <https://www.intel.com/content/www/us/en/developer/articles/technical/software-security-guidance/advisory-guidance/speculative-load-disordering.html>
- [52] —, "Rogue system register read / cve-2018-3640 / intel-sa-00115," 2018. [Online]. Available: <https://www.intel.com/content/www/us/en/developer/articles/technical/software-security-guidance/advisory-guidance/rogue-system-register-read.html>
- [53] N. Binkert, B. Beckmann, G. Black, S. K. Reinhardt, A. Saidi, A. Basu, J. Hestness, D. R. Hower, T. Krishna, S. Sardashti *et al.*, "The gem5 simulator," *ACM SIGARCH computer architecture news*, vol. 39, no. 2, pp. 1–7, 2011.
- [54] J. Doweck, W.-F. Kao, A. K.-y. Lu, J. Mandelblat, A. Rahatekar, L. Rappoport, E. Rotem, A. Yasin, and A. Yoaz, "Inside 6th-generation intel core: New microarchitecture code-named skylake," *IEEE Micro*, vol. 37, no. 2, pp. 52–62, 2017.
- [55] A. Limaye and T. Adegija, "A workload characterization of the spec cpu2017 benchmark suite," in *2018 IEEE International Symposium on Performance Analysis of Systems and Software (ISPASS)*. IEEE, 2018, pp. 149–158.
- [56] S. Li, J. H. Ahn, R. D. Strong, J. B. Brockman, D. M. Tullsen, and N. P. Jouppi, "Mcpat: An integrated power, area, and timing modeling framework for multicore and manycore architectures," in *Proceedings of*

the 42nd annual ieee/acm international symposium on microarchitecture, 2009, pp. 469–480.

- [57] Intel, “Speculative execution side channel mitigations,” pp. 2–7, 2018. [Online]. Available: <https://www.intel.com/content/dam/develop/external/us/en/documents/336996-speculative-execution-side-channel-mitigations.pdf>
- [58] —, “Speculative execution side channel mitigations,” pp. 10–11, 2018. [Online]. Available: <https://www.intel.com/content/dam/develop/external/us/en/documents/336996-speculative-execution-side-channel-mitigations.pdf>
- [59] ARM, “Arm® instruction set architecture: for armv8-a architecture,” 2022. [Online]. Available: <https://developer.arm.com/docs/ddi0597/h/base-instructions-alphabetic-order/ssbb-speculative-store-bypass-barrier>
- [60] M. F. A. Kadir, J. K. Wong, F. Ab Wahab, A. F. A. A. Bharun, M. A. Mohamed, and A. H. Zakaria, “Retpoline technique for mitigating spectre attack,” in *2019 6th International Conference on Electrical and Electronics Engineering (ICEEE)*, 2019, pp. 96–101.
- [61] Linux, “The current state of kernel page-table isolation, <https://lwn.net/articles/741878/>.”
- [62] J. Behrens, A. Cao, C. Skeggs, A. Belay, M. F. Kaashoek, and N. Zeldovich, “Efficiently mitigating transient execution attacks using the unmapped speculation contract,” in *14th USENIX Symposium on Operating Systems Design and Implementation (OSDI 20)*, 2020, pp. 1139–1154.
- [63] H. Xia, D. Zhang, W. Liu, I. Haller, B. Sherwin, and D. Chisnall, “A secret-free hypervisor: Rethinking isolation in the age of speculative vulnerabilities,” in *2022 IEEE Symposium on Security and Privacy (SP)*. IEEE Computer Society, 2022, pp. 1544–1544.
- [64] C. Reis, A. Moshchuk, and N. Oskov, “Site isolation: Process separation for web sites within the browser,” in *28th USENIX Security Symposium*, 2019, pp. 1661–1678.
- [65] J. Yu, L. Hsiung, M. El’Hajj, and C. W. Fletcher, “Data oblivious isa extensions for side channel-resistant and high performance computing,” in *The Network and Distributed System Security Symposium (NDSS)*, 2019.
- [66] M. Schwarz, M. Lipp, C. Canella, R. Schilling, F. Kargl, and D. Gruss, “Context: A generic approach for mitigating spectre,” in *NDSS*, 2020.
- [67] G. Chen, W. Wang, T. Chen, S. Chen, Y. Zhang, X. Wang, T.-H. Lai, and D. Lin, “Racing in hyperspace: Closing hyper-threading side channels on sgx with contrived data races,” in *2018 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2018, pp. 178–194.



Bowen Tang is currently working toward the PhD degree in the Institute of Computing Technology, Chinese Academy of Sciences. His research interests include computer architecture, system security, bug detection and virtualization.




Chenggang Wu is a professor at Institute of Computing Technology, Chinese Academy of Sciences. His research was supported by National Science Foundation of China (NSF), the National High Technology Research and Development Program of China, and the National Science and Technology Major Project of China. His research interests include the dynamic compilation, virtualization, bug detection on concurrent program, and system security.




Pen-Chung Yew has been a professor in the Department of Computer Science and Engineering, University of Minnesota since 1994, and was the head of the department and the holder of the William-Norris Land-Grant chair professor between 2000 and 2005. He has also served on the organizing and program committees of many major conferences. His current research interests include system virtualization, compilers and architectural issues related multi-core/many-core systems. He is a IEEE fellow.



Yingqian Zhang is an professor of Department of Computer Science and Engineering Southern University of Science and Technology (SUSTech). Before joining SUSTech in 2021, he was an associate professor at Department of Computer Science and Engineering of The Ohio State University. His research interest is computer system security, with particular emphasis on cloud computing security, OS security and side-channel security.



Mengyao Xie received her PhD degree in the Institute of Computing Technology, Chinese Academy of Sciences in 2022, and then has been working there until now. Her research interests include system security and virtualization.



Yuanming Lai received the BS degree in Digital Media Technology from Central China Normal University in 2013, and the Master degree in Pattern Recognition and Intelligence System from Huazhong University of Science and Technology, in 2016. Now he is in Institute of Computing Technology, Chinese Academy of Sciences. His research interests include information security and machine learning.



Yan Kang received the BS degree and the Master degree in Software Engineering from Beijing University of Aeronautics and Astronautics (BUAA) in 2014 and 2017. Now she is currently working in Institute of Computing Technology, Chinese Academy of Sciences. Her research interests include software and system security.



Wei Wang received his M.S. degree in Computer Science and Technology from Capital Normal University in 2021. He is currently working in the Institute of Computing Technology, Chinese Academy of Sciences, Beijing, China. His research interests include software security, speech recognition, adversarial attack and robustness.



Qiang Wei is a professor at State Key Laboratory of Mathematical Engineering and Advanced Computing of China. His main research interests are network and information system security, including software vulnerability analysis, cloud computing security, industrial control system security, intelligent terminal security, software-defined networks, etc.



Zhe Wang is currently an associate professor at Institute of Computing Technology, Chinese Academy of Sciences. His research interests are in dynamic binary translation, multi-threaded program record-and-replay, operating systems, system virtualization, and memory corruption attacks and defenses.