

Exploring ChatGPT’s Ability to Rank Content: A Preliminary Study on Consistency with Human Preferences

Yunjie Ji, Yan Gong, Yiping Peng, Chao Ni, Peiyan Sun, Dongyu Pan, Baochang Ma*, Xiangang Li
Beike Inc., Beijing, China

{jiyunjie001, gongyan013, pengyiping001, nichao007, sunpeiyan001,
pandongyu002, mabaochang001, lixiangang002}@ke.com

Abstract

As a natural language assistant, ChatGPT is capable of performing various tasks, including but not limited to article generation, code completion, and data analysis. Furthermore, ChatGPT has consistently demonstrated a remarkable level of accuracy and reliability in terms of content evaluation, exhibiting the capability of mimicking human preferences. To further explore ChatGPT’s potential in this regard, a study is conducted to assess its ability to rank content. In order to do so, a test set consisting of prompts is created, covering a wide range of use cases, and five models are utilized to generate corresponding responses. ChatGPT is then instructed to rank the responses generated by these models. The results on the test set show that ChatGPT’s ranking preferences are consistent with human to a certain extent. This preliminary experimental finding implies that ChatGPT’s zero-shot ranking capability could be used to reduce annotation pressure in a number of ranking tasks.

1 Introduction

Large Language Models (LLMs) Brown et al. (2020); Zhang et al. (2022); Chowdhery et al. (2022); Workshop et al. (2022); Black et al. (2022); Hoffmann et al. (2022) have made significant contributions to the development of natural language processing (NLP), especially in the performance of zero-shot and few-shot tasks. Through instruction tuning Wei et al. (2021); Sanh et al. (2021); Muenighoff et al. (2022); Chung et al. (2022) and alignment training Bai et al. (2022a); Ouyang et al. (2022), LLMs have become more than just general-purpose NLP task solvers Liang et al. (2022); Qin et al. (2023), but also natural language assistants capable of performing various text-related tasks, such as writing articles, completing code Chen et al. (2021); Nijkamp et al. (2023), and analyzing structural data.

*Corresponding author.

Recent studies have shown that ChatGPT is not only capable of generating high-quality content as requested by users, but also capable of providing effective evaluations of content Kocmi and Federmann (2023); Wang et al. (2023). By using carefully designed prompts, ChatGPT can provide reasonable evaluations of given content from different perspectives. Currently, most research has focused on using ChatGPT to evaluate a single sample, and its ability to rank multiple samples has not been well explored.

In this paper, we explore this question and construct a set of prompts covering typical NLP tasks, brainstorming, article generation, and other open-ended tasks. For each prompt, five models are adopted to generate responses. By comparing ChatGPT’s ranking results to human preference annotations, we find that ChatGPT’s ranking preferences had a certain level of consistency with humans. Based on this finding, ChatGPT’s zero-shot ranking capabilities can be leveraged to obtain more annotation data and improve the performance of the model on ranking tasks. For example, in RLHF Ouyang et al. (2022); Bai et al. (2022a), ChatGPT can be used to construct a set of initial preference annotation data for bootstrapping the reward model.

2 Related Work

The models based on transformer Vaswani et al. (2017); Devlin et al. (2018); Lan et al. (2019); Yang et al. (2019); Dong et al. (2019); Clark et al. (2020); Raffel et al. (2020) have greatly promoted the development of NLP, and recently the generative large language models Brown et al. (2020); Zhang et al. (2022); Chowdhery et al. (2022); Black et al. (2022); Hoffmann et al. (2022); Glaese et al. (2022); Srivastava et al. (2022) have made further progress. One notable example is the GPT (Generative Pre-trained Transformer) family of models, ChatGPT has further improved its ability to understand and follow human instructions by RLHF Ouyang et al. (2022); Bai et al. (2022b); Ziegler et al. (2020); Stiennon et al. (2022); Ganguli et al.; Nakano et al.




Figure 1. The illustration of our evaluation process.

(2022); Korbak et al. (2023). This has transformed ChatGPT from a simple NLP task solver to a comprehensive natural language assistant capable of tasks such as writing articles, analyzing structural data.

Using pre-trained language models as the evaluation metric (e.g., BERTScore Zhang et al. (2019), MoverScoreZhao et al. (2019), COMETRei et al. (2020), BLEURTSELLAM et al. (2020), MAUVEPillutla et al. (2022) and BARTScoreYuan et al. (2021) receives increasing attention. Considering ChatGPT’s impressive capability as an intelligent conversational language model, there are works studying ChatGPT from various perspectives. Dai et al. (2023) uses ChatGPT to generate augmented data to further improve the performance of the model. Kuzman et al. (2023) found that ChatGPT’s zero-shot ability in genre classification tasks exceeded that of the multilingual XLM-RoBERTa language model, which was fine-tuned on training data. Similarly, Tang et al. utilized ChatGPT to generate high-quality synthetic data, reducing the time and effort required for data collection and labeling, while also addressing data privacy concerns and enhancing the ability to perform clinical text mining. This demonstrates ChatGPT’s strength as a data annotator. In addition to generating and annotating data, ChatGPT is also a great evaluator of texts. For example, Kocmi and Federmann (2023) used ChatGPT to evaluate translation model results and found that its accuracy reached SOTA in WMT22’s Metrics shared task. Wang et al. (2023) evaluated ChatGPT’s performance on NLG tasks and found that it surpassed previously widely-used automatic NLG metrics, achieving the highest consistency with human-annotated results.

Our work is similar to Kocmi and Federmann (2023) and Wang et al. (2023), but we focus on ChatGPT’s ability to rank the generated contents of different models.

3 Method

In order to enable ChatGPT to accomplish ranking tasks, two types of prompts are designed: one-by-one ranking prompt and one-for-all ranking prompt. The first prompt is as follows:

Please give a score to the answer, ranging from 1 to 5. If the response does not meet the requirements of the instruction, the score is 1. Only give a score, no additional explanation is needed. “Instruction”: “...”, “Response”: “...”

In this prompt, “Instruction” is from our test set and “Response” is generated by one of our models. Therefore ChatGPT is actually required to assess the model against following user instructions. The second prompt is as follows:

Given a JSON file that contains an instruction and five potential responses, please rank the quality of these responses, and return the index of the ranked responses, no additional explanation is needed, {“Instruction”: “...”, “Response 1”: “...”, “Response 2”: “...”, “Response 3”: “...”, “Response 4”: “...”, “Response 5”: “...” }

In this case, the prompt includes an instruction and five responses, and ChatGPT is asked to rank these responses at once.

4 Experiments

4.1 Datasets

In this subsection, we introduce the test prompts in our experiment. The primary objective of our study is to evaluate the ability of ChatGPT as a comprehensive content

Table 1. Statistics of test prompts.

Use case	#Nums	Ave prompt length	Prompt example
NLP tasks	600	64.79	我想知道下面两句话的意思是否相同。“花呗分期了会影响芝麻分吗”，“花呗被限额了会不会有什么影响”。选项：是的,不是
Brainstorming	611	20.44	如何克服焦虑？
Generation	605	37.14	以成功为主题，撰写一篇商业风格的人物访谈，探讨如何将某种难题或挑战转化为商业机会。
Open QA	584	15.68	鸡蛋的蛋黄中含有增强人脑记忆不可缺少的哪种物质？
Math	106	68.41	红，黄，蓝气球共有62只，其中红气球的五分之三等于黄气球的三分之二，蓝气球有24只，红气球和黄气球各有多少只？
Code	494	65.59	请用Python语言完成如下题目解答。有四个数字：1、2、3、4，能组成多少个互不相同且无重复数字的三位数？各是多少？

Table 2. Main results.

	Spearman correlation coefficient		Top 1 consistency rate	
	one-by-one	one-for-all	one-by-one	one-for-all
NLP tasks	0.3030	0.3528	0.6050	0.4533
Brainstorming	0.6267	0.6135	0.8216	0.3797
Generation	0.8014	0.6244	0.7454	0.2611
OpenQA	0.4339	0.3781	0.5547	0.2688
Math	0.3493	0.5134	0.5943	0.4339
Code	0.4847	0.5321	0.7044	0.3643
Overall	0.5321	0.5006	0.6836	0.3483

preference annotator. So our dataset encompasses a diverse range of NLP tasks, along with open-ended instructions such as brainstorming and open QA, which are common online use cases as described in Ouyang et al. (2022). Table 1 shows details.

4.2 Models

In this paper, we focus on Chinese text. Models such as LLAMA Touvron et al. (2023), OPT Zhang et al. (2022) and GPT-J Wang and Komatsuzaki (2021) have not been particularly optimized in Chinese, so we choose Bloomz Muennighoff et al. (2022) series models as one of the baseline models. Their pre-training data include more Chinese text, and a further multi-task fine-tuning on Chinese corpus was conducted. The following models are used to generate responses to each prompt:

Bloomz-176b-mt Workshop et al. (2022); Muennighoff et al. (2022), which was further instruction-finetuned on the xP3mt dataset based on Bloom-176b and acquired general prompt understanding abilities to some degree.

Bloomz-7b1-mt Workshop et al. (2022); Muennighoff et al. (2022), which is the same as Bloomz-176b-mt but with 7.1 billion parameters.

Text-davinci-003, which is developed by OpenAI and

trained to generate high-quality natural language text in a variety of formats through RLHF Ouyang et al. (2022); Bai et al. (2022a).

ChatGPT, which is similar to Text-davinci-003 but particularly optimized to generate human-like responses to human prompts.

InstrLLM, which is our own model. InstrLLM has 7 billion parameters and is finetuned on a collection of diversified prompt-response pairs.

4.3 Human preference labeling

To obtain the human preference annotations of the generated responses from models, we distribute these data for labeling to 129 colleagues, 90% of whom had a bachelor’s degree or higher. For each prompt and its corresponding model responses, three annotators independently rank them, and the final ranking is the average of the three. We have 30 experienced software developers annotate code-related prompts.

4.4 Metric

Spearman correlation coefficient is used to evaluate the consistency between human preferences and ChatGPT pref-




Figure 2. ChatGPT preference scores of different models.




Figure 3. Human preference scores of different models.

erences among models’ responses. Additionally, we calculate the top 1 human preference consistency rate to assess the consistency of the first rank model between human and ChatGPT.

4.5 Main results

According to Table 2, ChatGPT shows an impressive level of consistency with human preference. Overall one-by-one prompting is more consistent with human than one-for-all prompting, especially on brainstorming, generation, and open QA prompts, this is mainly because responses are truncated due to the length limitation while performing one-for-all prompting. Meanwhile, one-by-one prompting outperforms one-for-all prompting at all types of prompts according to top 1 consistency rate. ChatGPT is more consistent with human on brainstorming and generation prompts, and there is still room for improvement for other use cases. There are two main reasons. The first one is that these prompts are all relatively difficult for the five models, so the quality of the generated responses is relatively low, making it difficult to determine which one is better. The second one is that to evaluate the responses of these prompts, ChatGPT needs to have strong knowledge and reasoning capabilities.

4.6 Model Comparison

A comparison of five models is conducted in six different use cases, as depicted in Figure 3 and 2. From both Figure 3 and 2, we can see that among all models, ChatGPT demonstrates the best performance, with scores exceeding four points across all use cases. Following behind is Text-davinci-003, the gap between ChatGPT and Text-davinci-003 is large from human’s perspective but small from ChatGPT’s perspective. It is worth noting that our InstrLLM outperforms bloomz-176b-mt overall, especially in brainstorming, generation, and math. InstrLLM is adept at brainstorming and generation tasks, which may be because there is a large number of open-ended prompts in its training dataset. In Figure 3, our model performs worst on NLP tasks, which is primarily due to the overfitting to following human instructions. Interestingly, from ChatGPT’s perspective, our model is comparable with Text-davinci-003, but bloomz-176b-mt, bloomz-7b1-mt are still much worse than Text-davinci-003. This indicates that ChatGPT is still not meticulous enough when evaluating contents, and cannot pay attention to many details, such as factualness and ethics. When it comes to Code and Math-related prompts, ChatGPT may not be able to check the correctness of code execution and mathematical calculation.

5 Discussion and Conclusion

Given the consistency of ChatGPT with human preferences, we discuss the possibilities of using ChatGPT to help us train models, especially in RLHF.

- ChatGPT can be used to construct a set of initial preference annotations to bootstrap reward models.
- ChatGPT can also be considered as a reward model to evaluate the quality of the responses generated by our SFT model. Of course, there is the issue that the SFT model trained this way may never be able to surpass ChatGPT, as it is constantly fitting to the preference of ChatGPT.

- Based on the zero-shot annotation capability of ChatGPT, we can find out in which use cases the existing models perform poorly, so that we can further optimize our models for these use cases particularly

In this paper, we explore the ability of ChatGPT in content ranking. On the diversified test prompts we built, ChatGPT shows a certain consistency with human preference for model responses ranking. Based on this discovery, we discuss the possibilities of leveraging ChatGPT to help us train and optimize our own model.

6 Acknowledgements

We want to express our gratitude to our colleagues for their professional and efficient data labeling, which has greatly helped us complete the experiment.

References

- Tom B. Brown, Benjamin Mann, Nick Ryder, et al. Language models are few-shot learners, July 2020.
- Susan Zhang, Stephen Roller, Naman Goyal, et al. Opt: Open pre-trained transformer language models, June 2022.
- Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, et al. Palm: Scaling language modeling with pathways, October 2022.
- BigScience Workshop, Teven Le Scao, Angela Fan, et al. Bloom: A 176b-parameter open-access multilingual language model, December 2022.
- Sid Black, Stella Biderman, Eric Hallahan, et al. Gpt-neox-20b: An open-source autoregressive language model, April 2022.
- Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, et al. Training compute-optimal large language models, March 2022.
- Jason Wei, Maarten Bosma, Vincent Y. Zhao, et al. Finetuned language models are zero-shot learners. *arXiv:2109.01652 [cs]*, September 2021.
- Victor Sanh, Albert Webson, Colin Raffel, et al. Multitask prompted training enables zero-shot task generalization. *arXiv:2110.08207 [cs]*, October 2021.
- Niklas Muennighoff, Thomas Wang, Lintang Sutawika, et al. Crosslingual generalization through multitask finetuning, November 2022.
- Hyung Won Chung, Le Hou, Shayne Longpre, et al. Scaling instruction-finetuned language models, October 2022.
- Yuntao Bai, Andy Jones, Kamal Ndousse, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback, April 2022a.
- Long Ouyang, Jeff Wu, Xu Jiang, et al. Training language models to follow instructions with human feedback, March 2022.
- Percy Liang, Rishi Bommasani, Tony Lee, et al. Holistic evaluation of language models, November 2022.
- Chengwei Qin, Aston Zhang, Zhuosheng Zhang, et al. Is chatgpt a general-purpose natural language processing task solver?, February 2023.
- Mark Chen, Jerry Tworek, Heewoo Jun, et al. Evaluating large language models trained on code, July 2021.
- Erik Nijkamp, Bo Pang, Hiroaki Hayashi, et al. Codegen: An open large language model for code with multi-turn program synthesis, February 2023.
- Tom Kocmi and Christian Federmann. Large language models are state-of-the-art evaluators of translation quality, February 2023.
- Jiaan Wang, Yunlong Liang, Fandong Meng, et al. Is chatgpt a good nlg evaluator? a preliminary study, March 2023.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. *arXiv preprint arXiv:1909.11942*, 2019.
- Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *Advances in neural information processing systems*, 32, 2019.
- Li Dong, Nan Yang, Wenhui Wang, Furu Wei, Xiaodong Liu, Yu Wang, Jianfeng Gao, Ming Zhou, and Hsiao-Wuen Hon. Unified language model pre-training for natural language understanding and generation. *Advances in neural information processing systems*, 32, 2019.

- Kevin Clark, Minh-Thang Luong, Quoc V Le, and Christopher D Manning. Electra: Pre-training text encoders as discriminators rather than generators. *arXiv preprint arXiv:2003.10555*, 2020.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *The Journal of Machine Learning Research*, 21(1):5485–5551, 2020.
- Amelia Glaese, Nat McAleese, Maja Trębacz, John Aslanides, Vlad Firoiu, Timo Ewalds, Maribeth Rauh, Laura Weidinger, Martin Chadwick, Phoebe Thacker, et al. Improving alignment of dialogue agents via targeted human judgements. *arXiv preprint arXiv:2209.14375*, 2022.
- Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *arXiv preprint arXiv:2206.04615*, 2022.
- Yuntao Bai, Saurav Kadavath, Sandipan Kundu, et al. Constitutional ai: Harmlessness from ai feedback, December 2022b.
- Daniel M. Ziegler, Nisan Stiennon, Jeffrey Wu, et al. Fine-tuning language models from human preferences, January 2020.
- Nisan Stiennon, Long Ouyang, Jeff Wu, et al. Learning to summarize from human feedback, February 2022.
- Deep Ganguli, Liane Lovitt, Jackson Kernion, et al. Red teaming language models to reduce harms: Methods, scaling behaviors, and lessons learned.
- Reiichiro Nakano, Jacob Hilton, Suchir Balaji, et al. Webgpt: Browser-assisted question-answering with human feedback, June 2022.
- Tomasz Korbak, Kejian Shi, Angelica Chen, et al. Pretraining language models with human preferences, February 2023.
- Tianyi Zhang, Varsha Kishore, Felix Wu, et al. Bertscore: Evaluating text generation with bert. *arXiv preprint arXiv:1904.09675*, 2019.
- Wei Zhao, Maxime Peyrard, Fei Liu, et al. Mover-score: Text generation evaluating with contextualized embeddings and earth mover distance. *arXiv preprint arXiv:1909.02622*, 2019.
- Ricardo Rei, Craig Stewart, Ana C Farinha, and Alon Lavie. Comet: A neural framework for mt evaluation. *arXiv preprint arXiv:2009.09025*, 2020.
- Thibault Sellam, Dipanjan Das, and Ankur P Parikh. Bleurt: Learning robust metrics for text generation. *arXiv preprint arXiv:2004.04696*, 2020.
- Krishna Pillutla, Lang Liu, John Thickstun, et al. Mauve scores for generative models: Theory and practice. *arXiv preprint arXiv:2212.14578*, 2022.
- Weizhe Yuan, Graham Neubig, and Pengfei Liu. Bartscore: Evaluating generated text as text generation. *Advances in Neural Information Processing Systems*, 34:27263–27277, 2021.
- Haixing Dai, Zhengliang Liu, Wenxiong Liao, et al. Chataug: Leveraging chatgpt for text data augmentation, February 2023.
- Taja Kuzman, Nikola Ljubešić, and Igor Mozetič. Chatgpt: Beginning of an end of manual annotation? use case of automatic genre identification, March 2023.
- Ruixiang Tang, Xiaotian Han, Xiaoqian Jiang, and Xia Hu. Does synthetic data generation of llms help clinical text mining?
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.
- Ben Wang and Aran Komatsuzaki. GPT-J-6B: A 6 Billion Parameter Autoregressive Language Model. <https://github.com/kingoflolz/mesh-transformer-jax>, May 2021.