
LLaVA-Med: Training a Large Language-and-Vision Assistant for Biomedicine in One Day

Chunyuan Li*, Cliff Wong*, Sheng Zhang*, Naoto Usuyama, Haotian Liu, Jianwei Yang
Tristan Naumann, Hoifung Poon, Jianfeng Gao

Microsoft

<https://aka.ms/llava-med>

Abstract

Conversational generative AI has demonstrated remarkable promise for empowering biomedical practitioners, but current investigations focus on unimodal text. Multimodal conversational AI has seen rapid progress by leveraging billions of image-text pairs from the public web, but such general-domain vision-language models still lack sophistication in understanding and conversing about biomedical images. In this paper, we propose a cost-efficient approach for training a vision-language conversational assistant that can answer open-ended research questions of biomedical images. The key idea is to leverage a large-scale, broad-coverage biomedical figure-caption dataset extracted from PubMed Central, use GPT-4 to self-instruct open-ended instruction-following data from the captions, and then fine-tune a large general-domain vision-language model using a novel curriculum learning method. Specifically, the model first learns to align biomedical vocabulary using the figure-caption pairs as is, then learns to master open-ended conversational semantics using GPT-4 generated instruction-following data, broadly mimicking how a layperson gradually acquires biomedical knowledge. This enables us to train a **Large Language and Vision Assistant for BioMedicine** (LLaVA-Med) in less than 15 hours (with eight A100s). LLaVA-Med exhibits excellent multimodal conversational capability and can follow open-ended instruction to assist with inquiries about a biomedical image. On three standard biomedical visual question answering datasets, fine-tuning LLaVA-Med outperforms previous supervised state-of-the-art on certain metrics. To facilitate biomedical multimodal research, we will release our instruction-following data and the LLaVA-Med model.

1 Introduction

Parallel image-text data is abundantly available in the general domain, such as web images and their associated captions. Generative pretraining has proven effective to leverage this parallel data for self-supervised vision-language modeling, as demonstrated by multimodal GPT-4 [32] and open-sourced efforts such as LLaVA [24]. By instruction-tuning models to align with human intents based on multimodal inputs, the resulting large multimodal models (LMMs) exhibit strong zero-shot task completion performance on a variety of user-oriented vision-language tasks such as image understanding and reasoning, paving the way to develop general-purpose multimodal conversational assistants [2, 21, 9].

While successful in the general domains, such LMMs are less effective for biomedical scenarios because biomedical image-text pairs are drastically different from general web content. As a result, general-domain visual assistants may behave like a layperson, who would refrain from answering

*Equal Contribution

biomedical questions, or worse, produce incorrect responses or complete hallucinations. Much progress has been made in biomedical visual question answering (VQA), but prior methods typically formulate the problem as classification (*e.g.*, among distinct answers observed in the training set) and are not well equipped for open-ended instruction-following. Consequently, although conversational generative AI has demonstrated great potential for biomedical applications [19, 30, 18], current investigations are often limited to unimodal text.

In this paper, we present **Large Language and Vision Assistant for BioMedicine (LLaVA-Med)**, a first attempt to extend multimodal instruction-tuning to the biomedical domain for end-to-end training of a biomedical multimodal conversational assistant. Domain-specific pretraining has been shown to be effective for biomedical natural language processing (NLP) applications [17, 14, 10, 28] and biomedical vision-language (VL) tasks [15, 7, 38, 49, 8]. Most recently, large-scale biomedical VL learning has been made possible by the creation of PMC-15M [49], a broad-coverage dataset with 15 million biomedical image-text pairs extracted from PubMed Central¹. This dataset is two orders of magnitude larger than the next largest public dataset, MIMIC-CXR [15], and covers a diverse image types. Inspired by recent work in instruction-tuning [34, 24], LLaVA-Med uses GPT-4 to generate diverse biomedical multimodal instruction-following data using image-text pairs from PMC-15M, and fine-tune a large biomedical-domain VL model [24] using a novel curriculum learning method.

Specifically, our paper makes the following contributions:

- *Biomedical multimodal instruction-following data.* We present a novel data generation pipeline to create diverse (image, instruction, output) instances, by sampling biomedical image-text pairs from PMC-15M and using GPT-4 to create instructions from the text alone (which becomes the intended output). This requires zero manual annotations and creates an extremely diverse visual instruction-following dataset by piggybacking on PMC-15 that covers the full spectrum of research findings over biomedical images.
- *LLaVA-Med.* We propose a novel curriculum learning method for adapting LLaVA [24] to the biomedical domain using our self-generated biomedical multi-modal instruction-following dataset. Specifically, we first fine-tune LLaVA to align biomedical vocabulary using the image-text pairs as is (with the generic instruction that simply asks for a description of the image). We then continue training the model using our self-generated instruction-following data to learn open-ended conversational semantics. In this way, we were able to train LLaVA-Med in less than 15 hours with eight A100s. Our empirical study validates the effectiveness of domain-specific instruction-tuning, and reveals best practice and interesting findings for adapting multimodal conversational assistant to high-value verticals. On well-established biomedical VQA datasets, fine-tuning LLaVA-Med often outperforms supervised state-of-the-art (SoTA).
- *Open-source.* To facilitate research in biomedical multimodal learning, we will release the following assets to the public: the biomedical multimodal instruction-following dataset and the codebase for data generation and model training.

2 Related Work

Biomedical Chatbots. Inspired by ChatGPT [31]/GPT-4 [32] and the success of open-sourced instruction-tuned large language models (LLMs) in the general domain, several biomedical LLM chatbots have been developed, including ChatDoctor [47], Med-Alpaca [12], PMC-LLaMA [45], Clinical Camel [1], DoctorGLM [46], and Huatuo [44]. They are initialized with open-sourced LLM and fine-tuned on customized sets of biomedical instruction-following data. The resulting LLMs emerge with great potential to offer assistance in a variety of biomedical-related fields/settings, such as understanding patients’ needs and providing informed advice.

To our knowledge, Visual Med-Alpaca [39] is the only existing multimodal biomedical chatbot that accepts image inputs. Though Visual Med-Alpaca and the proposed LLaVA-Med share a similar input-output data format, they differ in key aspects: (i) *Model architectures.* LLaVA-Med is an end-to-end neural model and Visual Med-Alpaca is a system that connect multiple image captioning models with a LLM, using a classifier to determine if or which biomedical captioning model is responsible for the image. The text prompt subsequently merges the converted visual information with the textual query, enabling Med-Alpaca to generate an appropriate response. (ii) *Biomedical instruction-following data.* While Visual Med-Alpaca is trained on 54K samples from limited biomedical subject domains, LLaVA-Med is trained a more diverse set.

¹<https://www.ncbi.nlm.nih.gov/pmc/>

Biomedical Visual Question Answering. An automated approach to building models that can answer questions based on biomedical images stands to support clinicians and patients. To describe existing biomedical VQA methods, we make a distinction between discriminative and generative methods. For discriminative methods, VQA is treated as a classification problem: models make predictions from a predefined set of answers. While discriminative methods yield good performance, they deal with closed-set predictions [13], and require mitigation when a customized answer set is provided in at inference [22, 49, 8]. The discriminative formulation is suboptimal towards the goal of developing a general-purpose biomedical assistant that can answer open questions in the wild. To this end, generative methods have been developed to predict answers as a free-form text sequence [5, 26, 41]. Generative methods are more versatile because they naturally cast the close-set questions as a special case where candidate answers are in language instructions.

Model Architecture. LLaVA-Med is similar to prefix tuning of language models (LMs) in [41] in that a new trainable module connects frozen image encoder and causal LM. In [41], a three-layer MLP network is used to map the visual features into a visual prefix, and the pre-trained LM are GPT2-XL [37], BioMedLM [42] and BioGPT [28], with size varying from 1.5B to 2.7B. By contrast, LLaVA-Med uses a linear projection and a 7B LM [43, 40]. Most importantly, [41] only considers standard supervised fine-tuning and focuses efforts on exploring various modeling choices. Our main contributions instead comprise proposing a novel data generation method that uses GPT-4 to self-instruct biomedical multimodal instruction-following data using freely-available broad-coverage biomedical image-text pairs extracted from PubMed Central [49].

3 Biomedical Visual Instruction-Following Data

There are a lack of multimodal biomedical datasets to train an instruction-following assistant. To fill this gap, we create the first dataset of its kind from widely existing biomedical image-text pairs, through a machine-human co-curation procedure. It consists of two sets, concept alignment and instruction-following, which are used at different training stages, described in Section 4.

Biomedical Concept Alignment Data. For a biomedical image $\mathbf{X}_v$ and its associated caption $\mathbf{X}_c$, we sample a question $\mathbf{X}_q$, which asks to describe the biomedical image. With $(\mathbf{X}_v, \mathbf{X}_c, \mathbf{X}_q)$, we create a single-round instruction-following example:

Human : $\mathbf{X}_q \mathbf{X}_v$ <STOP>\n Assistant : $\mathbf{X}_c$ <STOP>\n

Depending on the length of caption, the question that is sampled either asks to describe the image *concisely* or *in detail*. Two lists of questions are provided in Appendix A. In practice, 25% of captions have length less than 30 words in PMC-15M [49], and thus 30 words is used as the cutoff point to determine which list to choose. We sample 600K image-text pairs from PMC-15M. Though this dataset only presents one-single task instructions, *i.e.*, image captioning, it contains a diverse and representative set of biomedical concept samples from the original PMC-15M [49].

Biomedical Instruction-Tuning Data. To align the model to follow a variety of instructions, we present and curate diverse instruction-following data with multi-round conversations about the provided biomedical images, by prompting language-only GPT-4. Specifically, given an image caption, we design instructions in a prompt that asks GPT-4 to generate multi-round questions and answers in a tone as if it could see the image (even though it only has access to the text). Sometimes the image caption is too short for GPT-4 to generate meaningful questions and answers. To provide more context regarding the image, we also create a prompt that includes not only captions but also sentences from the original PubMed paper that mentions the image. We also manually curate few-shot examples in the prompt to demonstrate how to generate high-quality conversations based on the provided caption and context. See Appendix B for the prompt and few-shot examples. To collect image captions and their context, we filter PMC-15M to retain the images that only contain a single plot. From them, we sample 60K image-text pairs from the five most common imaging modalities: CXR (chest X-ray), CT (computed tomography), MRI (magnetic resonance imaging), histopathology, and gross (*i.e.*, macroscopic) pathology. We then extract sentences that mention the image from the original PubMed paper as additional context to the caption, inspired by the observations that external knowledge helps generalization [20, 25].

An example of instruction-following data is shown in Figure 1 shows, and the data statistics is shown Figure 2. We have produced three versions of instruct data when iteratively improving the data

Biomedical Visual Instruction-Following Example

Caption:

Figure 4: Contrast-enhanced CT scan of the chest for patient #1. A large cavitating lesion was identified in the right upper lobe with pleural involvement and likely extension into the chest wall. In addition, right hilar lymphadenopathy was suspected. This was the primary malignant lesion in this patient.



Sentences with in-line figure mentions:

- Computerized tomography (CT) scans of the chest (Figure 4) were obtained.
- (Figure 4) and demonstrated a large cavitating lesion in the posterior aspect of the right upper lobe with probable pleural involvement likely representing the primary lesion.

Conversation:

User: Where is the lesion located?

Assistant: The lesion is located in the posterior aspect of the right upper lobe of the lung.

User: Is it extending into the chest wall?

Assistant: Yes, the CT scan suggests that the large cavitating lesion in the right upper lobe is likely extending into the chest wall.

User: Can you explain more about the cavitating lesion?

Assistant: Certainly. A cavitating lesion refers to an abnormal mass or growth within the lung tissue that has a cavity or hollow space inside it. This cavity can be formed due to the necrosis (death) of the tissue inside the lesion, leading to the breakdown and disintegration of the affected tissue. Cavitating lesions can be caused by various factors, such as infections (like tuberculosis or fungal infections), autoimmune diseases, or malignancies (cancer). In the context of the CT scan provided, the large cavitating lesion in the right upper lobe of the lung is suggestive of a malignant (cancerous) growth. The cavity within the lesion may be a result of the rapid and uncontrolled growth of cancer cells, which can lead to the destruction of surrounding healthy tissue. It's important to note that further diagnostic tests, such as a biopsy, would be required to confirm the malignancy and determine the specific type of cancer involved.

Figure 1: An instance of our GPT-4 generated instruction-following data. Top: The figure and caption were extracted from a PubMed Central full-text article [35], along with the corresponding citances (mentions of the given figure in the article). Bottom: The instruction-following data generated by GPT-4 using the text only (caption and citances). Note that the image is not used to prompt GPT-4; we only show it here as a reference.

quality: (i) *60K-IM*. The aforementioned dataset that considers inline mentions (IM) as the context. (ii) *60K*. A dataset of similar size (60K samples) without IM in self-instruct generation. (iii) *10K*. A smaller dataset (10 samples) without IM. They are used to ablate our data generation strategies and their impact on trained LLaVA-Med in experiments.

4 Adapting Multimodal Conversational Models to the Biomedical Domain

We employ LLaVA, a general-domain multimodal conversation model [24], as the initial general-domain LM, and continuously train the model to the biomedical domain. The same network architecture is utilized, where a linear projection layer connects the vision encoder and the language model. For LLaVA-Med model training, we use a two-stage procedure, illustrated in Figure 3.

Stage 1: Biomedical Concept Feature Alignment. To balance between concept coverage and training efficiency, we filter PMC-15M to 600K image-text pairs. These pairs are converted to instruction-following data using a naive expansion method: instructions simply presents the task of describing the image. For each sample, given the language instruction and image input, we ask the model to predict the original caption. In training, we keep both the visual encoder and LM weights frozen, and only update the projection matrix. In this way, the image features of vast novel biomedical




Figure 2: The data statistics of biomedical multimodal instruction-following data: (a,b) The root verb-noun pairs of instruction and responses, where the inner circle of the plot represents the root verb of the output response, and the outer circle represents the direct nouns. (c) The distribution of images and QA pairs on the five domains, one image is shown per domain. The domain example images are from [3, 33, 4, 29, 48].




Figure 3: LLaVA-Med was initialized with the general-domain LLaVA and then continuously trained in a curriculum learning fashion (first biomedical concept alignment then full-blown instruction-tuning). We evaluated LLaVA-Med on standard visual conversation and question answering tasks.

visual concepts can be aligned to their textual word embeddings in the pre-trained LM. This stage can be understood as expanding the vocabulary of aligned image-text tokens to the biomedical domain.

Stage 2: End-to-End Instruction-Tuning. We only keep the visual encoder weights frozen, and continue to update both the pre-trained weights of the projection layer and LM. To train the model to follow various instructions and complete tasks in a conversational manner, we develop a biomedical chatbot by fine-tuning our model on the biomedical language-image instruction-following data collected in Section 3. As demonstrated in the experiments to be described later, the LLaVA-Med model at this stage is able to not only be served as a biomedical visual assistant to interact with users, but also achieve good zero-shot task transfer performance when evaluated on well-established biomedical VQA datasets.

Fine-tuning to Downstream Datasets. For some specific biomedical scenarios, there is a need of developing highly accurate and dataset-specific models to improve the service quality of the assistant. We fine-tune LLaVA-Med after the two-stage training on three biomedical VQA datasets [27], covering varied dataset sizes and diverse biomedical subjects. Given a biomedical image as context,

multiple natural language questions are provided, the assistant responds in free-form text for both the close-set and open-set questions, with a list of candidate answers constructed in the prompt for each close-set question.

Discussion. We discuss three favorable properties/implications of LLaVA-Med: (i) *Affordable development cost.* Instead of scaling up data/model for the best performance, we aim to provide affordable and reasonable solutions with low development cost: it takes 7 and 8 hours for stage 1 and 2 on 8 40G A100 GPUs, respectively (see Table 5 for detailed numbers). (ii) *A recipe for many domains.* Though this paper focuses on biomedical domains, the proposed adaptation procedure is generalizable to other vertical domains such as gaming and education, where novel concepts and domain knowledge are needed to build a helpful assistant. Similar to the *don’t stop pre-training* argument in [11], we consider a scalable pipeline to create domain-specific instruct data from large unlabelled data, and advocate *don’t stop instruction-tuning* to build customized LMM. (iii) *Low serving cost.* While the model size of general LMM can be giant and serving cost can be prohibitively high, customized LMM has its unique advantages in low serving cost. (iv) *Smooth Model Adaptation.* Alternatively, the network architecture allows us to initialize the vision encoder from BioMedCLIP [49], or initialize the language model from Vicuna [43], which may lead to higher performance. However, adapting from LLaVA smooth adaptation as a chatbot, where model’s behaviors transit from layperson to a professional assistant that is able to provide helpful domain-specific response.

5 Experiments

We conduct experiments to study two key components, the quality of the produced multimodal biomedical instruction-following data, and performance of LLaVA-Med. We consider two research evaluation settings: (1) What is the performance of LLaVA-Med as an open-ended biomedical visual chatbot? (2) How does LLaVA-Med compare to existing methods on standard benchmarks? To clarify, throughout the entire experiments, we only utilize the language-only GPT-4.

5.1 Biomedical Visual Chatbot


To evaluate the performance of LLaVA-Med on biomedical multimodal conversation, we construct an evaluation dataset with 193 novel questions. For this test dataset, we randomly selected 50 *unseen* image and caption pairs from PMC-15M, and generate two types of questions: conversation and detailed description. The conversation data is collected using the same self-instruct data generation pipeline as for the 2nd stage. Detailed description questions were randomly selected from a fixed set [24] of questions to elicit detailed description responses.

We leverage GPT-4 to quantify the correctness of the model answer to a question when given the image context and caption. GPT-4 makes a reference prediction, setting the upper bound answer for the teacher model. We then generate response to the same question from another LMM. Given responses from the two assistants (the candidate LMM and GPT-4), the question, figure caption, and figure context, we ask GPT-4 to score the helpfulness, relevance, accuracy, and level of details of the responses from the two assistants, and give an overall score on a scale of 1 to 10, where a higher score indicates better overall performance. GPT-4 is also asked to provide a comprehensive explanation the evaluation, for us to better understand the models. We then compute the relative score using GPT-4 reference score for normalization.

(Question Count)	Question Types		Domains					Overall
	Conversation (143)	Description (50)	CXR (37)	MRI (38)	Histology (44)	Gross (34)	CT (40)	
LLaVA	39.4	26.2	41.6	33.4	38.4	32.9	33.4	36.1
LLaVA-Med								
Stage 1	22.6	25.2	25.8	19.0	24.8	24.7	22.2	23.3
10K	42.4	32.5	46.1	36.7	43.5	34.7	37.5	39.9
60K	53.7	36.9	57.3	39.8	49.8	47.4	52.4	49.4
60K-IM	55.1	36.4	56.2	40.4	52.7	51.8	50.1	50.2

Table 1: Performance comparison of mulitmodal chat instruction-following abilities, measured by the relative score via language GPT-4 evaluation.

Visual input example, Biomedical image from [6]



Caption: Chest x-ray (CXR) on Day 2 of admission post-intubation (yellow line showing the level of the endotracheal tube). Rapidly worsening ground-glass opacities are seen throughout the lungs with relative subpleural sparing (red arrows)

User	Source: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7398722/ What is shown in this image?
LLaVA-Med	The image is a chest X-ray (CXR) that shows bilateral patchy infiltrates, which are areas of increased opacity in the lungs. These infiltrates can be indicative of various lung conditions, such as infections, inflammation, or other lung diseases.
User	Are there any devices implanted in this patient?
LLaVA-Med	Yes, it appears that the patient has several devices implanted. These devices may include endotracheal tubes, central venous catheters, and/or pulmonary artery catheters. These devices are typically used for monitoring and managing various medical conditions, as well as for providing support during surgical procedures.
User	What is shown in this image?
LLaVA	The image shows a ribcage with wires coming out of it, indicating that it is likely a medical illustration or diagram.
User	Are there any devices implanted in this patient?
LLaVA	Yes, there are several devices protruding from the patient's chest, which are likely medical devices used for treatment or monitoring.
User	What is shown in this image?
Language GPT-4	The image shows a chest x-ray taken on Day 2 of a patient's admission after intubation. You can see the endotracheal tube marked by a yellow line, and rapidly worsening ground-glass opacities throughout the lungs. There is also relative subpleural sparing, which is indicated by red arrows.
User	Are there any devices implanted in this patient?
Language GPT-4	Yes, there is an endotracheal tube implanted in the patient, as indicated by the yellow line in the image.

Table 2: Example comparison of medical visual chat and reasoning capabilities. The language-only GPT-4 is considered as the performance upper bound, as the golden captions and inline mentions are fed into GPT-4 as the context, without requiring the model to understand the raw image.

The results are reported in Table 1. LLaVA-Med with Stage-1 training alone is insufficient as a chatbot, as it loses its ability to follow diverse instructions, though biomedical concept coverage is improved. LLaVA-Med with the full two-stage training consistently outperforms the general domain LLaVA, and training with larger instruct data (from 10K to 60K samples) leads to higher performance. When inline mentions are considered in self-instruct, the generated data 60K-IM slightly improves the chat ability. The results demonstrate the effectiveness of the strategies in biomedical instruction-following data collection as well as the value of dataset assets. Overall, for the best LLaVA-Med, it matches the 50.2% performance of GPT-4. Note that GPT-4 generates response by considering ground-truth caption and golden inline mentions, without understanding the images. Though not a fair comparison between LMMs and GPT-4, GPT-4 is a consistent and reliable evaluation tool.

In Table 2, we provide examples on the biomed visual conversations of different chatbots. LLaVA-Med precisely answers the questions with biomedical knowledge, while LLaVA behaves like a layperson, who hallucinate based on commonsense. Since the multimodal GPT-4 is not publicly available, we resort to language-only GPT-4 for comparison. We feed golden captions and inline mentions into GPT-4 as the context, it generates knowledgeable response through re-organizing the information in the conversational manner.

5.2 Performance on Established Benchmarks

Dataset Description. We train and evaluate LLaVA-Med on three biomedical VQA datasets. The detailed data statistics are summarized in Table 3.

- **VQA-RAD [16]** contains 3515 QA pairs generated by clinicians and 315 radiology images that are evenly distributed over the head, chest, and abdomen. Each image is associated with multiple questions. Questions are categorized into 11 categories: abnormality, attribute, modality, organ system, color, counting, object/condition presence, size, plane, positional reasoning, and other. Half of the answers are closed-ended (*i.e.*, yes/no type), while the rest are open-ended with either one-word or short phrase answers.

Dataset	VQA-RAD		SLAKE			PathVQA		
	Train	Test	Train	Val	Test	Train	Val	Test
# Images	313	203	450	96	96	2599	858	858
# QA Pairs	1797	451	4919	1053	1061	19,755	6279	6761
# Open	770	179	2976	631	645	9949	3144	3370
# Closed	1027	272	1943	422	416	9806	3135	3391

Table 3: Dataset statistics. For SLAKE, only the English subset is considered for head-to-head comparison with existing methods.

- *SLAKE* [23] is a Semantically-Labeled Knowledge-Enhanced dataset for medical VQA. It consists of 642 radiology images and over 7000 diverse QA pairs annotated by experienced physicians, where the questions may involve external medical knowledge (solved by provided medical knowledge graph), and the images are associated with rich visual annotations, including semantic segmentation masks and object detection bounding boxes. Besides, SLAKE includes richer modalities and covers more human body parts than the currently available dataset, including brain, neck, chest, abdomen, and pelvic cavity. Note SLAKE is bilingual dataset with English and Chinese. When compared with existing methods, we only consider the English subset.
- *PathVQA* [13] is a dataset of pathology images. It contains a total of 4998 pathology images with 32,799 QA pairs. Every image has several questions that relate to multiple aspects such as location, shape, color, appearance, etc. The questions are categorized into two types, with several varieties: open-ended questions such as why, what, how, where, *etc.*, and closed-ended questions.

Evaluation Metrics. For the closed-set questions, we report the accuracy. For open-set questions, we use recall to evaluate the ratio that ground-truth tokens appear in the generated sequences. In the literature, the unique answers in the training set are considered as the answer candidates, from which the models can select to predict answers for testing questions. Since we do not provide any constraint for the responses to open-set questions, our formulation is closer to open-set nature, but is intrinsically harder.

Comparisons with SoTA. We compare LLaVA-Med with the general domain LLaVA and existing representative methods in Table 4 (a). First, All LLaVA-Med variants outperform LLaVA. While the difference of language model initialization from LLaVA or Vicuna is minor, the initialization of vision encoder from BioMed CLIP is slightly better than from general-domain CLIP. Second, the fine-tuning performance of LLaVA-Med is higher than supervised SoTA on the closed-set questions on VQA-RAD and PathVQA. This validates LLaVA-Med’s strong ability in following instruction to complete biomedical tasks, when clear instructions are provided (*e.g.*, , yes or no). Third, for open-set questions, LLaVA-Med achieves SoTA on SLAKE, while its performance is limited on other datasets, especially compared with existing methods. This is perhaps because the open-set biomedical questions can be ambiguous without constraining their expected answer options.

Ablation Studies. To study the impact of our curated instruction data and hyper-parameters in the training pipeline, we report the performance of different model variants in Table 4 (b). Several findings are confirmed: (i) LLaVA-Med consistently outperforms LLaVA by a large margin, indicating the effectiveness of our biomedical domain-specific adaptation. The performance gaps on zero-shot are larger than that in fine-tuned settings, showing that LLaVA-Med is clearly a better option than LLaVA when deploying one model for various scenarios in the wild. (ii) Training longer in Stage 1 improves zero-shot transfer, but Stage 1 alone is not sufficient, because the single image captioning instruction in Stage 1 may encourage the model to lose its ability in follow diverse instructions. (iii) Instruction-following data in Stage 2 is critical, and the performance is generally improved, when the instruct data amount increases from 10K to 60K. The 60K-IM data provides the best averaged zero-shot and fine-tuned performance, respectively, validating the effectiveness of considering inline mention as external knowledge in data creation. (iv) Fine-tuning longer on downstream datasets till 9 epochs benefits the performance, especially on checkpoints with 3-epoch training in Stage 2. Increasing language model size from 7B to 13B improves the overall zero-shot performance and fine-tuned performance. We suggest practitioners to choose the appropriate quality-cost trade-off, by referring to the running time in Table 5.

Method	VQA-RAD			SLAKE			PathVQA		
	Ref	Open	Closed	Ref	Open	Closed	Ref	Open	Closed
<i>Supervised finet-tuning results with our own experiment runs</i>									
LLaVA		50.00	65.07		78.18	63.22		7.74	63.20
LLaVA-Med (From LLaVA)		61.52	84.19		83.08	85.34		37.95	91.21
LLaVA-Med (From Vicuna)		64.39	81.98		84.71	83.17		38.87	91.65
LLaVA-Med (BioMed CLIP)		64.75	83.09		87.11	86.78		39.60	91.09
<i>Representative & SoTA methods with numbers reported in the literature</i>									
VL Encoder-Decoder [5]	71.49		82.47				71.49		85.61
Q2ATransformer [26]	79.19		81.20				54.85		88.85
Prefix T. Medical LM [41]				84.30		82.01	40.00		87.00
PubMedCLIP [8]	60.10		80.00	78.40		82.50			
BiomedCLIP [49]	67.60		79.80	82.05		89.70			
M2I2 [22]	66.50		83.50	74.70		91.10	36.30		88.00

(a) Comparison with prior state-of-the-art supervised methods. For open-ended questions, prior methods still formulate the problem as classification among distinct answers in the training set, which may overestimate their generalizability as these datasets are unusual in that the test answers are almost always present in training.

LLaVA-Med Model Variants				VQA-RAD		SLAKE		PathVQA		Average
Instruct	Stage 1	Stage 2	FT	Open	Closed	Open	Closed	Open	Closed	
CLIP Vision Encoder [36], 7B Language Model										
0	1	0	0	15.27	12.50	18.55	13.46	6.26	13.51	13.26
0	3	0	0	15.33	15.44	23.61	15.38	6.35	14.74	15.14
10K	1	3	0	25.79	57.35	31.50	51.68	8.49	59.66	39.08
10K	3	3	0	28.44	59.56	22.63	43.99	5.40	52.67	35.45
10K	1	3	1	36.39	55.88	71.64	56.49	25.50	82.87	54.79
10K	1	3	3	18.59	55.51	78.60	63.46	34.02	86.94	56.19
60K	1	1	0	29.80	55.15	38.08	50.00	11.70	59.66	40.73
60K	1	3	0	29.67	60.29	35.53	53.85	11.76	53.20	40.72
60K	1	3	1	22.63	58.09	72.75	54.33	24.19	71.60	50.60
60K	1	3	3	54.12	64.71	79.33	64.90	17.18	71.37	58.60
60K-IM	1	1	0	29.67	61.40	38.44	52.40	11.41	56.24	41.59
60K-IM	1	3	0	28.23	61.40	39.17	52.16	12.30	54.05	41.22
60K-IM	1	3	1	28.61	56.25	70.58	54.57	11.17	59.19	46.73
60K-IM	1	3	3	55.50	66.54	80.57	64.18	35.88	89.15	65.30
60K-IM	1	3	9	66.26	80.88	82.30	84.86	37.59	91.54	73.90
60K-IM	1	3	15	61.53	84.19	83.08	85.34	37.95	91.21	73.88
60K-IM	1	3	18	61.37	81.25	84.24	83.17	37.88	91.39	73.22
CLIP Vision Encoder [36], 13B Language Model										
60K-IM	1	3	0	31.66	61.40	37.71	49.76	11.34	49.63	40.25
60K-IM	1	3	9	64.58	77.94	84.97	85.58	38.82	92.39	74.05
BioMed CLIP Vision Encoder [49], 7B Language Model										
60K-IM	1	3	0	37.84	60.66	39.73	54.33	11.65	49.07	42.21
60K-IM	1	3	9	64.75	83.09	87.11	86.78	39.60	91.09	75.40
LLaVA	0	0	0	20.74	59.19	26.82	50.24	8.74	45.65	35.23

(b) Ablation studies with varying number of training epochs at different stages. “FT” is Fine-Tuning. 60K-IM indicates the instruct data generated with inline mentions. The gray rows are zero-shot performance of LLaVA-Med trained with different instruct data, they are selected to show in subtable (a).

Table 4: Quantitative results on three established biomedical VQA datasets. For open-set questions, we report the recall for our free-form text generation method in column *Open*. For closed-set questions, we report the accuracy in column *Closed*. Bold indicates LLaVA-Med achieves new SoTA.

Stage 1		Stage 2			VQA-RAD		SLAKE		PathVQA	
1	3	Instruct	1	3	1	3	1	3	1	3
6.8	19.4	10K	0.6	1.8	0.3	0.6	0.6	1.0	1.0	2.5
		60K	2.6	8.0						

Table 5: Running time (hours) for 1 and 3-epoch training at each stage, with batch size 128 on eight A100 GPUs.



Biomedical image from the SLAKE Bilingual dataset. [23]		
	User	这张图片的成像方式是什么?
	LLaVA-Med	The image is an abdominal computed tomography (CT) scan, which is a cross-sectional view of the patient's abdomen. The image is taken in the portal phase, which means it is captured after the administration of contrast material to enhance the visibility of certain structures within the abdomen.
	Answer	CT
	User	这张图片展示的是核磁共振的哪种类型?
	LLaVA	The image shows a typical appearance of a nodular lesion on T1-weighted MR images. The lesion appears hyperintense, which means it is brighter than the surrounding tissue. This can be indicative of various types of lesions, and further evaluation would be needed to determine the specific nature and cause of the lesion.
	Answer	T1

Table 6: Examples on zero-shot on Chinese questions. Though LLaVA-Med training data itself does not include Chinese, it is able to correctly understand the Chinese questions.

Case Study I: Zero-shot on Chinese Questions. For the LLaVA-Med trained on 60K-IM data, we provide Chinese questions on SLAKE dataset. Though LLaVA-Med training does not include Chinese instruction-following data, we show in Table 6 that LLaVA-Med is able to correctly understand the Chinese questions and respond the correct answers, probably due to the multilingual knowledge learned in LLaMA/Vicuna. Existing models will fail when zero-shot transfer cross languages.

6 Conclusions

We present LLaVA-Med, a large language-and-vision model for the biomedical domain. To create this model, we create high-quality biomedical language-image instruction-following dataset using a self-instruct approach to build a data curation pipeline using language-only GPT-4 and external knowledge. LLaVA-Med demonstrates strong excellent chat abilities with domain knowledge, and outperforms previous supervised SoTA on three VQA datasets on certain metrics with subsequent fine-tuning.

While we believe that LLaVA-Med represents a significant step towards building a useful biomedical visual assistant, we note that LLaVA-Med is limited by hallucinations and weak in-depth reasoning common to many LMMs. Future work is directed toward improving quality and reliability.

References

- [1] Clinical Camel. https://wanglab.ml/clinical_camel.html, 2023. 2
- [2] Amanda Askeel, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Ben Mann, Nova DasSarma, et al. A general language assistant as a laboratory for alignment. *arXiv preprint arXiv:2112.00861*, 2021. 1
- [3] Malek Ayoub, Megan Quamme, Abdul-Rahman K Abdel-Reheem, Poe Lwin, and Megan K Quamme. Covid or not covid? a great mimicker behind the smoke screen. *Cureus*, 13(11), 2021. 5
- [4] Bappy Basak, Alexander Haragan, Michael Shackcloth, and Joyce Thekkudan. Chondromyxoid fibroma of the rib: A rare benign tumor with potential for local recurrence. *Cureus*, 13(10), 2021. 5

- [5] Yakoub Bazi, Mohamad Mahmoud Al Rahhal, Laila Bashmal, and Mansour Zuair. Vision–language model for visual question answering in medical imagery. *Bioengineering*, 2023. 3, 9
- [6] Anchit Bharat, Nikita Jain, Belaal Sheikh, Hafiz Jeelani, and Maryna Shayuk. Vaping-induced lung injury: An uncharted territory. *Cureus*, 12, 07 2020. 7
- [7] Benedikt Boecking, Naoto Usuyama, Shruthi Bannur, Daniel C Castro, Anton Schwaighofer, Stephanie Hyland, Maria Wetscherek, Tristan Naumann, Aditya Nori, Javier Alvarez-Valle, et al. Making the most of text semantics to improve biomedical vision–language processing. In *ECCV*. Springer, 2022. 2
- [8] Sedigheh Eslami, Christoph Meinel, and Gerard De Melo. Pubmedclip: How much does clip benefit visual question answering in the medical domain? In *Findings of the Association for Computational Linguistics: EACL 2023*, pages 1151–1163, 2023. 2, 3, 9
- [9] Zhe Gan, Linjie Li, Chunyuan Li, Lijuan Wang, Zicheng Liu, Jianfeng Gao, et al. Vision–language pre-training: Basics, recent advances, and future trends. *Foundations and Trends® in Computer Graphics and Vision*, 2022. 1
- [10] Yu Gu, Robert Tinn, Hao Cheng, Michael Lucas, Naoto Usuyama, Xiaodong Liu, Tristan Naumann, Jianfeng Gao, and Hoifung Poon. Domain-specific language model pretraining for biomedical natural language processing. *ACM Transactions on Computing for Healthcare (HEALTH)*, 3(1):1–23, 2021. 2
- [11] Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A Smith. Don’t stop pretraining: Adapt language models to domains and tasks. *arXiv preprint arXiv:2004.10964*, 2020. 6
- [12] Tianyu Han, Lisa C Adams, Jens-Michalis Papaioannou, Paul Grundmann, Tom Oberhauser, Alexander Löser, Daniel Truhn, and Keno K Bressen. Medalpaca—an open-source collection of medical conversational ai models and training data. *arXiv preprint arXiv:2304.08247*, 2023. 2
- [13] Xuehai He, Yichen Zhang, Luntian Mou, Eric Xing, and Pengtao Xie. Pathvqa: 30000+ questions for medical visual question answering. *arXiv preprint arXiv:2003.10286*, 2020. 3, 8
- [14] Kexin Huang, Jaan Altosaar, and Rajesh Ranganath. Clinicalbert: Modeling clinical notes and predicting hospital readmission. *arXiv preprint arXiv:1904.05342*, 2019. 2
- [15] Alistair EW Johnson, Tom J Pollard, Seth J Berkowitz, Nathaniel R Greenbaum, Matthew P Lungren, Chih-ying Deng, Roger G Mark, and Steven Horng. Mimic-cxr, a de-identified publicly available database of chest radiographs with free-text reports. *Scientific data*, page 317, 2019. 2
- [16] Jason J Lau, Soumya Gayen, Asma Ben Abacha, and Dina Demner-Fushman. A dataset of clinically generated visual questions and answers about radiology images. *Scientific data*, 2018. 7
- [17] Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. Biobert: a pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240, 2020. 2
- [18] Peter Lee, Sebastien Bubeck, and Joseph Petro. Benefits, limits, and risks of gpt-4 as an ai chatbot for medicine. *New England Journal of Medicine*, 388(13):1233–1239, 2023. 2
- [19] Peter Lee, Carey Goldberg, and Isaac Kohane. The ai revolution in medicine: Gpt-4 and beyond. 2023. 2
- [20] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive NLP tasks. *NeurIPS*, 2020. 3

- [21] Chunyuan Li, Haotian Liu, Liunian Harold Li, Pengchuan Zhang, Jyoti Aneja, Jianwei Yang, Ping Jin, Houdong Hu, Zicheng Liu, Yong Jae Lee, and Jianfeng Gao. ELEVATER: A benchmark and toolkit for evaluating language-augmented visual models. In *NeurIPS Track on Datasets and Benchmarks*, 2022. 1
- [22] Pengfei Li, Gang Liu, Lin Tan, Jinying Liao, and Shenjun Zhong. Self-supervised vision-language pretraining for medical visual question answering. *arXiv preprint arXiv:2211.13594*, 2022. 3, 9
- [23] Bo Liu, Li-Ming Zhan, Li Xu, Lin Ma, Yan Yang, and Xiao-Ming Wu. Slake: A semantically-labeled knowledge-enhanced dataset for medical visual question answering. In *International Symposium on Biomedical Imaging (ISBI)*. IEEE, 2021. 8, 10
- [24] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *arXiv preprint arXiv:2304.08485*, 2023. 1, 2, 4, 6
- [25] Haotian Liu, Kilho Son, Jianwei Yang, Ce Liu, Jianfeng Gao, Yong Jae Lee, and Chunyuan Li. Learning customized visual models with retrieval-augmented knowledge. *arXiv preprint arXiv:2301.07094*, 2023. 3
- [26] Yunyi Liu, Zhanyu Wang, Dong Xu, and Luping Zhou. Q2atransformer: Improving medical vqa via an answer querying decoder. *arXiv preprint arXiv:2304.01611*, 2023. 3, 9
- [27] Pan Lu, Swaroop Mishra, Tanglin Xia, Liang Qiu, Kai-Wei Chang, Song-Chun Zhu, Oyvind Tafjord, Peter Clark, and Ashwin Kalyan. Learn to explain: Multimodal reasoning via thought chains for science question answering. *Advances in Neural Information Processing Systems*, 2022. 5
- [28] Renqian Luo, Liai Sun, Yingce Xia, Tao Qin, Sheng Zhang, Hoifung Poon, and Tie-Yan Liu. Biogpt: generative pre-trained transformer for biomedical text generation and mining. *Briefings in Bioinformatics*, 2022. 2, 3
- [29] Hassan Mirmohammad Sadeghi, Abbas Karimi, Samira Derakhshan, Pouyan Aminishakib, and Kiarash Parchami. Conventional osteosarcoma of the mandible: Report of a rare case. *Clinical Case Reports*, 9(9):e04843, 2021. 5
- [30] Harsha Nori, Nicholas King, Scott Mayer McKinney, Dean Carignan, and Eric Horvitz. Capabilities of gpt-4 on medical challenge problems. *arXiv preprint arXiv:2303.13375*, 2023. 2
- [31] OpenAI. ChatGPT. <https://openai.com/blog/chatgpt/>, 2022. 2
- [32] OpenAI. GPT-4 technical report. <https://arxiv.org/abs/2303.08774>, 2023. 1, 2
- [33] Kyriakos A Papavasiliou, Dimitrios Stamiris, Stavros Stamiris, Antonia Bintoudi, and Eleftherios Tsiridis. Quadratus femoris partial tear secondary to occult ischiofemoral impingement. *Journal of Orthopaedic Case Reports*, 11(9):7, 2021. 5
- [34] Baolin Peng, Chunyuan Li, Pengcheng He, Michel Galley, and Jianfeng Gao. Instruction tuning with GPT-4. *arXiv preprint arXiv:2304.03277*, 2023. 2
- [35] Roger Kevin Pringle and Lawrence H Wyatt. The appropriate use of radiography in clinical practice: a report of two cases of biomechanical versus malignant spine pain. *Chiropractic & Osteopathy*, 14(1):1–8, 2006. 4
- [36] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. *arXiv preprint arXiv:2103.00020*, 2021. 9
- [37] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 2019. 3

- [38] George Shih, Carol C Wu, Safwan S Halabi, Marc D Kohli, Luciano M Prevedello, Tessa S Cook, Arjun Sharma, Judith K Amorosa, Veronica Arteaga, Maya Galperin-Aizenberg, et al. Augmenting the national institutes of health chest radiograph dataset with expert annotations of possible pneumonia. *Radiology: Artificial Intelligence*, 2019. 2
- [39] Chang Shu, Baian Chen, Fangyu Liu, Zihao Fu, Ehsan Shareghi, and Nigel Collier. Visual med-alpaca: A parameter-efficient biomedical llm with visual capabilities. 2023. 2
- [40] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023. 3
- [41] Tom van Sonsbeek, Mohammad Mahdi Derakhshani, Ivona Najdenkoska, Cees GM Snoek, and Marcel Worring. Open-ended medical visual question answering through prefix tuning of language models. *arXiv preprint arXiv:2303.05977*, 2023. 3, 9
- [42] A Venigalla, J Frankle, and M Carbin. BiomedLM: a domain-specific large language model for biomedical text. *MosaicML*. Accessed: Dec, 23, 2022. 3
- [43] Vicuna. Vicuna: An open-source chatbot impressing GPT-4 with 90%* chatgpt quality. <https://vicuna.lmsys.org/>, 2023. 3, 6
- [44] Haochun Wang, Chi Liu, Nuwa Xi, Zewen Qiang, Sendong Zhao, Bing Qin, and Ting Liu. Huatuo: Tuning llama model with chinese medical knowledge, 2023. 2
- [45] Chaoyi Wu, Xiaoman Zhang, Ya Zhang, Yanfeng Wang, and Weidi Xie. Pmc-llama: Further finetuning llama on medical papers. *arXiv preprint arXiv:2304.14454*, 2023. 2
- [46] Honglin Xiong, Sheng Wang, Yitao Zhu, Zihao Zhao, Yuxiao Liu, Qian Wang, and Dinggang Shen. Doctorglm: Fine-tuning your chinese doctor is not a herculean task. *arXiv preprint arXiv:2304.01097*, 2023. 2
- [47] Li Yunxiang, Li Zihan, Zhang Kai, Dan Ruilong, and Zhang You. Chatdoctor: A medical chat model fine-tuned on llama model using medical domain knowledge. *arXiv preprint arXiv:2303.14070*, 2023. 2
- [48] Mansoor Zafar, Abdul Wahab Paracha, Muteeb Ashraf, Tila Muhammad, Mark Whitehead, Muhammad Toqeer, and Abdul Paracha. Delayed spontaneous regression of metastatic gastric cancer: A case report of a rare finding. *Cureus*, 13(12), 2021. 5
- [49] Sheng Zhang, Yanbo Xu, Naoto Usuyama, Jaspreet Bagga, Robert Tinn, Sam Preston, Rajesh Rao, Mu Wei, Naveen Valluri, Cliff Wong, et al. Large-scale domain-specific pretraining for biomedical vision-language processing. *arXiv preprint arXiv:2303.00915*, 2023. 2, 3, 6, 9

A Data

Instructions for brief image description. The list of instructions used to briefly describe the image content are shown in Table 7. They present the same meaning with natural language variance.

- "Describe the image concisely."
- "Provide a brief description of the given image."
- "Offer a succinct explanation of the picture presented."
- "Summarize the visual content of the image."
- "Give a short and clear explanation of the subsequent image."
- "Share a concise interpretation of the image provided."
- "Present a compact description of the photo's key features."
- "Relay a brief, clear account of the picture shown."
- "Render a clear and concise summary of the photo."
- "Write a terse but informative summary of the picture."
- "Create a compact narrative representing the image presented."

Table 7: The list of instructions for brief image description.

Instructions for detailed image description. The list of instructions used to describe the image content in detail are shown in Table 8. They present the same meaning with natural language variance.

- "Describe the following image in detail"
- "Provide a detailed description of the given image"
- "Give an elaborate explanation of the image you see"
- "Share a comprehensive rundown of the presented image"
- "Offer a thorough analysis of the image"
- "Explain the various aspects of the image before you"
- "Clarify the contents of the displayed image with great detail"
- "Characterize the image using a well-detailed description"
- "Break down the elements of the image in a detailed manner"
- "Walk through the important details of the image"
- "Portray the image with a rich, descriptive narrative"
- "Narrate the contents of the image with precision"
- "Analyze the image in a comprehensive and detailed manner"
- "Illustrate the image through a descriptive explanation"
- "Examine the image closely and share its details"
- "Write an exhaustive depiction of the given image"

Table 8: The list of instructions for detailed image description.

B Prompts

Prompting GPT-4 to generate medical visual instruction-following data

```
messages = [ {"role": "system", "content": """"You are an AI assistant specialized in biomedical topics.
```

You are provided with a text description (Figure Caption) of a figure image from a biomedical research paper. In some cases, you may have additional text (Figure Context) that mentions the image. Unfortunately, you don't have access to the actual image.

Below are requirements for generating the questions and answers in the conversation:

- Avoid quoting or referring to specific facts, terms, abbreviations, dates, numbers, or names, as these may reveal the conversation is based on the text information, rather than the image itself. Focus on the visual aspects of the image that can be inferred without the text information.
- Do not use phrases like "mentioned", "caption", "context" in the conversation. Instead, refer to the information as being "in the image."
- Ensure that questions are diverse and cover a range of visual aspects of the image.
- The conversation should include at least 2-3 turns of questions and answers about the visual aspects of the image.
- Answer responsibly, avoiding overconfidence, and do not provide medical advice or diagnostic information. Encourage the user to consult a healthcare professional for advice."""}

```
]
for sample in fewshot_samples:
    messages.append({"role": "user", "content": sample['context']})
    messages.append({"role": "assistant", "content": sample['response']})
    )
messages.append({"role": "user", "content": query})
```

Figure 4: `messages` we use to prompt GPT-4 to generate medical visual instruction-following data. Manually curated few-shot examples are included in the prompt, where each example has input `sample['context']` and output `sample['response']`. Please see Figure 5 for one of the few-shot examples.

One of the few-shot examples used in the prompt

Example input:

Figure Caption:

Figure 2: Chest X-ray. Cardiomegaly with diffuse bilateral interstitial infiltrates and a right-sided pleural effusion.

Figure Context:

- His respiratory status continued to worsen and on hospital day number 14 , he required intubation and mechanical ventilation for hypoxemic respiratory failure (Figure 2) .

Example output:

User: Which side of the lung has a pleural effusion?

Assistant: The right side of the lung has a pleural effusion.

User: According to the CT image, does the patient has cardiomegaly?

Assistant: The image appears to be a chest x-ray. However, it indicates that the patient has cardiomegaly, which means an enlarged heart. Additionally, there are diffuse bilateral interstitial infiltrates and a right-sided pleural effusion present in the image.

User: Additional Info: The patient's respiratory status continued to worsen and on hospital day number 14, requiring intubation and mechanical ventilation for hypoxemic respiratory failure.

Assistant: Thank you for providing additional information about the patient's condition. Based on the information you provided, it appears that the patient's respiratory status continued to worsen and on hospital day number 14, they required intubation and mechanical ventilation for hypoxemic respiratory failure. This suggests that the patient's lung function has significantly declined, and they may be experiencing respiratory distress. It is important for the medical team to closely monitor the patient's condition and provide appropriate treatment to manage their symptoms and improve their lung function.

Figure 5: One of the few-shot examples used in our prompt to construct medical visual instruction-following data. "Figure Context" in the input provides additional context by including sentences from the corresponding PubMed paper that mention the figure.

Visual input example, Biomedical image:	
	
User	What is this image about?
LLaVA-Med	The image is a coronal view of a computed tomography (CT) scan of the abdomen and pelvis. It provides a detailed view of the internal organs and structures within the abdominal and pelvic cavities.
User	What is abnormal about this image?
LLaVA-Med	The abnormality in this image is the presence of a large left-sided pelvic mass. This mass could be due to various reasons, such as a tumor, cyst, or other growth. Further evaluation and tests would be needed to determine the exact cause and appropriate treatment for this abnormality.
User	What is this image about?
LLaVA	The image is a medical illustration showing a person's internal anatomy, especially focusing on their large and small intestines, stomach, liver and kidneys. The organs are highlighted in different colors, making it easy to identify each organ
User	What is abnormal about this image?
LLaVA	As a visual AI assistant, I cannot determine the specific abnormality on the chest X-ray based on the provided image description. The image description mainly focuses on the organs and their colors...

Table 9: Example comparison of medical visual chat and reasoning capabilities.