

ABUGIDA NORMALIZER AND PARSER FOR UNICODE TEXTS

Nazmuddoha Ansary^a, Quazi Adibur Rahman Adib^b, Tahsin Reasat^c, Sazia Mehnaz^d,
Asif Shahriyar Sushmit^d, Ahmed Imtiaz Humayun^e, Mohammad Mamun Or Rashid^f, Farig Sadeque^b

^a Bangladesh University of Engineering and Technology, Dhaka - 1000, Bangladesh

^b BRAC University, Dhaka - 1212, Bangladesh

^c Vanderbilt University, TN 37235, USA

^d Bengali.Ai, Bangladesh

^e Rice University, TX 77005, USA

^f Jahangirnagar University, Bangladesh

ABSTRACT

This paper proposes two libraries to address common and uncommon issues with Unicode-based writing schemes for Indic languages. The first is a normalizer that corrects inconsistencies caused by the encoding scheme¹. The second is a grapheme parser for Abugida text². Both tools are more efficient and effective than previously used tools. We report 400% increase in speed and ensure significantly better performance for different language model based downstream tasks.

1 Introduction

Unicode Normalization is a procedure for transforming Unicode text into different levels of equivalence, based on rules outlined by the Unicode Standard [1]. The goal is to ensure consistent treatment of certain types of text across applications and systems.

Graphemes are the basic units of writing and include individual letters, symbols, or glyphs that convey meaning within a language system [2]. Each grapheme typically represents at least one phoneme or sound component of spoken language.

Many speakers of Indian, Bangladeshi, and Thai languages utilize abugidas, also referred to as alphasyllabaries, consisting of over 1.3 billion individuals. Unfortunately, despite the large number of users, these languages encounter obstacles when it comes to natural language processing due to scarce resources and constraints in technology. Nevertheless, there exists vast academic and industrial interest in devising novel NLP techniques for these languages.

Our group has developed a novel Indic Unicode Normalizer designed to overcome typical problems encountered in online Indic Abugida language datasets. Our solution surpasses current alternatives, delivering superior accuracy and efficiency. Moreover, we have fashioned an innovative grapheme dissectioner that markedly boosts orthographic syllabification exactness and speed relative to conventional approaches. These pioneering instruments enable us to supply upgraded NLP services for abugidas, fostering trailblazing research and propelling advancement in the wider domain of natural language processing.

2 Complexities and Challenges of Abugida Orthography

Words using Abugidas consist of independent, visual segments known as Orthographic Syllables or Graphemes. An Abugida word contains various components, such as Vowel Letters, Consonant Letters, Vowel Diacritics, and Consonant Diacritics arranged above, below, around, or on top of each other [3, 4]. In many Abugida languages, vowels possess unique diacritics that are easily recognizable. Some consonant diacritics are also distinguishable from the corresponding character they modify. Additionally, several ligatures exist which either display remarkable characteristics unlike the

¹<https://pypi.org/project/bnunicodenormalizer/>

²<https://pypi.org/project/indicparser/>

participating consonants or exhibit new composite forms. Some graphemes are extremely popular while others remain less preferred among users.




Figure 1: Orthographic components in Bengali word 'Borendro'. Equivalent grapheme constituents are color-coded according to phonemic correspondence. Alpha-syllabary grapheme segments and corresponding characters from the different languages are segregated with the markers. While characters in English are arranged horizontally according to phonemic sequence, the order is not maintained in the Abugida languages.

- Grapheme Roots and Diacritics
- Consonant Conjunct or Ligatures
- Unique Grapheme Combinations

Abugida Unicode Blocks In contrast to other writing systems like Latin, Han, or Kanji, Abugidas employ thousands of distinct characters. Unicode considers these characters as smaller parts which can be grouped together to form one complete symbol. This allows multiple ways to write the same term. When font rendering software fails to support a particular arrangement, this may lead to incorrect displays. As different keyboard layouts and personal preferences create additional variants, text analyses must ensure thorough normalisation prior to examination. These factors highlight the importance of correct input formatting for effective text exploration.

In the next section we categorically discuss the issues with the Bengali Unicode block in detail to demonstrate the issues with Bengali unicode based encoding system and our proposed pipeline to correct the non-normalized text.

3 Unicode Normalization

Our proposed algorithm takes into account the word formation rules using Unicode schemes and fixes seven types of different errors and issues that lead to major non-normalized text formations in Abugida texts. A previous attempt was made by [5] in making an indic nlp normalizer; however many of the crucial issues remained unaddressed. Our normalization policy is minimal: going with the less number of unicode codes to represent a glyph when possible while being consistent. We override the suggestions from the unicode consortium in cases when this normalization philosophy contradicts with them. Our proposed normalizer can be found here ³. The issues that are solved by our proposed algorithm are as follows:

- Legacy Symbols Handling
- Broken Diacritics Fixing
- Broken Nukta Resolution
- Invalid Unicode Handling
- Invalid Connector Handling
- Diacritic Form Correction
- Vowel-Vowel Diacritic Removal
- Language Specific Treatment (Bengali)
 - Unwanted doubles
 - Complex root normalization
 - Assamese replacement for Bengali
 - To-hoshonto normalization

³<https://github.com/mnansary/bnUnicodeNormalizer>

4 Proposed Grapheme Parser

To parse graphemes in an Indic language, we require three components: a set of vowel diacritics, a connector and a set of consonant diacritics. A **Connector** is a specific Unicode character that joins two consonants to form consonant conjuncts in a given Indic language. Our GitHub repository contains the algorithm we propose⁴. Our grapheme parser stands out for its efficiency. We test its runtime by applying it to the unique words in the OSCAR corpus[6] and achieve superior performance. We also check the accuracy of the parser by reassembling the words from the parsed components and find no errors.

5 Conclusion

Our team has developed a state-of-the-art Indic Unicode normalizer that addresses common issues found in online Indic Abugida language corpora. This normalizer offers superior performance compared to other available solutions. Additionally, we have designed an advanced grapheme parser that significantly improves upon traditional orthographic syllabifiers in terms of both accuracy and speed. By creating reliable NLP tools for Abugida languages, we aim to enable and inspire future researchers in this field to achieve breakthrough results, ultimately driving innovation in natural language processing as a whole.

References

- [1] Mark Davis and Martin Dürst. Unicode normalization forms, 2001.
- [2] Liudmila Fedorova. The development of graphic representation in abugida writing: The akshara’s grammar. *Lingua Posnaniensis*, 55(2):49–66, 2014.
- [3] Padmapriya Kandhadai and Richard Sproat. Impact of spatial ordering of graphemes in alphasyllabic scripts on phonemic awareness in indic languages. *Writing Systems Research*, 2(2):105–116, 2010.
- [4] Dimitrios Meletis. The grapheme as a universal basic unit of writing. *Writing Systems Research*, 11(1):26–49, 2019.
- [5] Anoop Kunchukuttan. The IndicNLP Library. https://github.com/anoopkunchukuttan/indic_nlp_library/blob/master/docs/indicnlp.pdf, 2020.
- [6] Julien Abadji, Pedro Ortiz Suarez, Laurent Romary, and Benoît Sagot. Towards a Cleaner Document-Oriented Multilingual Crawled Corpus. *arXiv e-prints*, page arXiv:2201.06642, January 2022.

⁴<https://github.com/mnansary/indicparser>