

# How good are Large Language Models for African Languages?

Jessica Ojo<sup>\*†</sup> Kelechi Ogueji<sup>\*</sup> Pontus Stenetorp<sup>‡</sup> David Ifeoluwa Adelani<sup>‡,\*</sup>

<sup>\*</sup>Masakhane, <sup>†</sup>Lelapa AI, South Africa, and <sup>‡</sup>University College London, United Kingdom  
jessica.ojo@lelapa.ai, d.adelani@ucl.ac.uk

## Abstract

Recent advancements in natural language processing have led to the proliferation of large language models (LLMs). These models have been shown to yield good performance, using in-context learning, even on tasks and languages they are not trained on. However, their performance on African languages is largely understudied relative to high-resource languages. We present an analysis of four popular large language models (mT0, Aya, LLaMa 2, and GPT-4) on six tasks (topic classification, sentiment classification, machine translation, summarization, question answering, and named entity recognition) across 60 African languages, spanning different language families and geographical regions. Our results suggest that all LLMs produce lower performance for African languages, and there is a large gap in performance compared to high-resource languages (such as English) for most tasks. We find that GPT-4 has an average to good performance on classification tasks, yet its performance on generative tasks such as machine translation and summarization is significantly lacking. Surprisingly, we find that mT0 had the best overall performance for cross-lingual QA, better than the state-of-the-art supervised model (i.e. fine-tuned mT5) and GPT-4 on African languages. Similarly, we find the recent Aya model to have comparable result to mT0 in almost all tasks except for topic classification where it outperform mT0. Overall, LLaMa 2 showed the worst performance, which we believe is due to its English and code-centric (around 98%) pre-training corpus. Our findings confirms that performance on African languages continues to remain a hurdle for the current LLMs, underscoring the need for additional efforts to close this gap.

## 1 Introduction

Large language models (LLMs) have risen to the fore of natural language processing and also become increasingly commercially viable. These models have empirically demonstrated strong performance across a variety of natural language processing (NLP) tasks and languages (Brown et al., 2020; Lin et al., 2021; Chowdhery et al., 2022; Chung et al., 2022b). However, their performance on low-resources languages, such as African languages, is largely understudied. This is problematic for two primary reasons: ideally our approaches to language understanding should be applicable to all languages and technological advances should be ensured to benefit all language users.

While there are some recent evaluation of the performance of LLMs on several languages (Ahuja et al., 2023a; Lai et al., 2023; Robinson et al., 2023), the evaluation is focused on *closed models* like ChatGPT. Ahuja et al. (2023c) extended the evaluation to PaLM 2 (Anil et al., 2023) and LLaMa 2 (Touvron et al., 2023). The former is a closed model while the latter has publicly available open weights but it is English-centric since about 90% pre-training corpus is based English data. Our evaluation compares GPT-4, LLaMa 2, and extends to two additional *open multilingual LLMs* that have been pre-trained on over 100 languages and publicly available instruction data. The advantage of the open models is that results are fully reproducible unlike closed models whose version changes.

In this paper, we conduct an extensive analysis of large language models for 60 African languages from different language families and geographical locations. Our evaluation covers four popular LLMs: mT0 (Muennighoff et al., 2023) (derived from mT5 (Xue et al., 2021) through multitask prompted fine-tuning), LLaMa 2 (Touvron et al., 2023), Aya (Üstün et al., 2024), and GPT-4. We evaluate the models on six tasks: topic classification (two datasets), sentiment classification, machine translation, named entity recognition, question answering, and summarization.

Our results indicates that large language models do not perform well on African languages. In particular, we note a large disparity in performance depending on the task: models perform better for classification tasks than generative tasks, such as machine translation. We find performance to be worse for low-resource languages compared to high-resources ones. Our evaluation shows that GPT-4 achieves more than 80% of the performance of fully-supervised fine-tuning on news topic classification and sentiment classification, but a bit lower performance—62% of full-supervised fine-tuning on named entity recognition respectively. On the other hand, performance of generative tasks like machine translation (MT) was significantly poor. In comparison to MT evaluation on high-resource languages (e.g. English-German and French-German), our evaluation shows the gap in performance between LLM and full-supervised fine-tuning is wider for African languages.

In general, other LLMs have worse results than GPT-4 on most tasks. However, for cross-lingual QA, mT0 and Aya had the best overall performance, even exceeding the state-of-the-art supervised model (i.e. fine-tuned mT5). Overall, LLaMa 2 records the worst performance due to its limited multilingual capabilities. Our work sheds light on the need to ensure the inclusion of African languages in the development of large language models, given their inevitable adoption in our daily lives.

## 2 Related Work

**Instruction Fine-tuning** Growing the size of language models does not inherently make them better at following a user’s intent (Ouyang et al., 2022), fine-tuning language models on a collection of tasks described via instructions substantially improves zero-shot performance on unseen tasks (Wei et al., 2022). This method involves further training the large language model on a dataset consisting of instruction-output pairs in a supervised fashion enabling the LLMs to adhere to human instructions. Several recent work agrees that instruction fine-tuning generally improves the usability of pretrained large language models (Chung et al., 2022c; Ouyang et al., 2022; Zhang et al., 2023; Jiang et al., 2023). This has also been adopted in multilingual settings (Holmström & Doostmohammadi, 2023)

**Multitask prompted fine-tuning (MTF)** While instruction fine-tuning is useful for understanding the user intents and teaching the models to respond to instructions, multitask prompted fine-tuning aims at making the model generalize to new tasks in a zero-shot setting (Sanh et al., 2022). Typically, many supervised NLP tasks are constructed in a question-answer format, and jointly fine-tuned, hoping this will easily generalize to new tasks. Muennighoff et al. (2023) created mT0 by applying MTF in multilingual settings, and find that fine-tuning large multilingual language models on English tasks with English prompts allows for task generalization to non-English languages. Another model that incorporate this is the Aya model (Üstün et al., 2024).

**Multilingual in-context Learning** LLMs have proven successful in multilingual settings. Lin et al. (2021) trained a multilingual generative language models on datasets covering diverse set of languages studying their few and zero shot learning capabilities on a wide range of tasks. Their model outperforms GPT3 on several multilingual tasks. Muennighoff et al. (2022a) perform multitask prompted fine-tuning on multilingual pretrained language models and observe impressive zero-shot generalization to tasks in unseen languages. Following findings from Blevins & Zettlemoyer (2022) that non-English dataset present in the pretraining corpora of English language models explains their surprising cross-lingual ability, Chowdhery et al. (2022) deliberately introduce non-English corpora ( $\approx 22\%$ ) into the pretraining corpora of their PaLM model and achieve impressive few-shot multilingual performance. Shi et al. (2022) evaluate GPT3 and PaLM on a newly introduced grade school mathematics multilingual benchmark. They find that using prompts with intermediate reasoning steps in English consistently led to competitive or better results than those written in the native language of the question.

**Multilingual LLM evaluation** Ahuja et al. (2023b) performs a comprehensive evaluation of the ChatGPT models on standard NLP benchmarks, covering 16 NLP datasets across 70 typologically diverse languages. However, the evaluation of African languages are limited to part-of-speech tagging, named entity recognition, and summarization. Zhu et al. (2023) finds that performing crosslingual instruction fine-tuning and multilingual instruction fine-tuning on LLaMA outperforms the non multilingual LLaMA base models on translation dataset Flores-101. Similarly, Robinson

et al. (2023) and Adelani et al. (2024) conducted a large scale evaluation of ChatGPT on machine translation and topic classification respectively, covering 204 languages, however, all these evaluation are focused on closed models. Ahuja et al. (2023c) expanded the initial evaluation of Ahuja et al. (2023b) using other closed models like PaLM 2, ChatGPT and LLaMa open model, they also cover more tasks and languages, their evaluation expanded to QA datasets for African languages. However, a comprehensive evaluation on several tasks covering classification and generation tasks are missing for African languages. Our paper expanded the evaluation to include two open-sourced multilingual LLMs (mT0 and Aya). These two LLMs have not been covered by the last scale multilingual evaluation by Ahuja et al. (2023a;c) since they only focus on Decoder-only models. Our evaluation extends to Encoder-Decoder models like mT5 which is missing in previous research.

### 3 Languages and evaluation tasks

We cover 60 African languages from seven language families (Afro-Asiatic, Atlantic-Congo, Austronesian, Indo-European, Mande, Nilotic, and English-Creole). 35 languages are from the Atlantic-Congo family, 14 from the Afro-Asiatic family, five from Nilotic family, three from Manda family, and one language each from Austronesian (Malagasy), Indo-European (Afrikaans) and English-Creole (Naija) Appendix A shows the languages and tasks we evaluated on.

#### 3.1 Evaluation tasks and datasets

We cover the following seven datasets and six tasks, three classification tasks (topic classification, sentiment classification and named entity recognition) and three generative tasks (question answering, machine translation, and summarization)

**News Classification:** We make use of MASAKHANEWS (Adelani et al., 2023), a multilingual news classification dataset covering 16 typologically-diverse languages spoken in Africa, including English and French. The task is to classify a news article into one of these seven categories: *business*, *entertainment*, *health*, *politics*, *religion*, *sports*, or *technology*.

**Topic Classification:** SIB-200 (Adelani et al., 2024) is a large-scale multilingual topic classification dataset covering 205 languages and dialects based on the Flores-200 corpus NLLB Team et al. (2022) which is parallel across all languages. This dataset covers 57 (out of the 60) African languages we evaluated on. Only three languages are missing: Algerian Arabic, Ghomálá’, and Nigerian-Pidgin. The task is to classify a news articles into one of these seven categories: *science/technology*, *travel*, *politics*, *sports*, *health*, *entertainment*, or *geography*.

**Sentiment Classification:** AFRISENTI (Muhammad et al., 2023) is a multilingual sentiment classification dataset for 14 languages spoken in Africa. The goal of the task is to classify tweets as positive, negative, or neutral.

**Named Entity Recognition (NER):** For NER, we make use MASAKHANER-X (Ruder et al., 2023)—a subset of MASAKHANER (Adelani et al., 2021; 2022b) that has been converted to be suitable for evaluating generative models (i.e. the input “*Jens is an employee of Amazon*” should produce “*PERSON: Jens & ORG: Amazon*” as an output) and covers 20 African languages.

**Question Answering (QA):** AFRIQA (Ogundepo et al., 2023) is a cross-lingual, open-retrieval, question answering (XOR QA) dataset, which consists of more than 12,000 examples across 10 African languages. In this setting, the answer and context are provided in a high resource language, while the question is either in an African language or a high-resource language.

**Machine Translation (MT):** MAFAND-MT Adelani et al. (2022a)<sup>1</sup> is a professionally translated, news domain dataset which covers 16 African languages. Here, we compare the performance of fine-tuning M2M-100 on few thousand parallel sentences to the performance of GPT-4. The reason

<sup>1</sup>While Flores-200 is a larger benchmark, it was used for instructing fine-tuning of mT0 model, so, it is no longer suitable as an evaluation set.

LLM	size	# Pre-training African Languages	# SFT African Languages	African Languages in pre-training	African Languages covered in SFT
LLaMa 2	13B	> 27	unknown	unknown	unknown
mT0/mT0-MT	13B	13	22	afr, amh, hau, ibo, plt, nya, sna, som, sot, swl, xho, yor, zul	aka, bam, fon, ibo, kik, lug, lin, nso, nya, run, kin, sna, sot, swl, tsn, tso, tum, twi, wol, xho, yor, zul
Aya	13B	13	29	afr, amh, hau, ibo, plt, nya, sna, som, sot, swl, xho, yor, zul	afr, arq, amh, bem, knk, eng, arz, fon, fra, hau, ibo, kin, ary, por, nso, nya, plt, sna, som, sot, arb, swl, taq, aeb, twi, wol, xho, yor, zul
GPT-4	unknown	unknown	unknown	unknown	unknown

Table 1: Languages covered by different LLMs, their sizes, African languages covered during pre-training of the LLM, and African languages in supervised fine-tuning.

we compared to this setting is because pre-trained M2M-100 was trained on few African languages, only 8 out of 16 languages are covered by the model. An effective way to add a new language to the model is to fine-tune a pre-trained MT model on few high-quality parallel data.

**Summarization:** XL-SUM (Hasan et al., 2021) is a multilingual summarization dataset curated automatically from BBC news articles. The dataset covers 10 African languages that the BBC is publishing in. The goal of the task is that given an article, generate a short summary of the articles, typically one to two sentences.

## 4 Experimental Setup

We focus our evaluations on the following LLMs: mT0-13B (-MT), Aya, LLaMa 2 13B, and GPT-4.<sup>2</sup> mT0-13B (Muennighoff et al., 2023) is an LLM obtained by fine-tuning mT5-XXL (a 13B parameter size text-to-text model and also the largest) on a collection of multitask prompted datasets known as xP3 (Crosslingual Public Pool of Prompts) while mT0-13B-MT was fine-tuned on xP3<sub>mt</sub> where prompts are provided in 20 languages (machine-translated from English).<sup>3</sup> Aya is a more recent LLM developed very similar to mT0, with a carefully curated multi-task prompted dataset and heavy translation of datasets from English to over 100 languages (Singh et al., 2024), similar to xP3. LLaMa 2 (Touvron et al., 2023) is a popular, publicly available LLM with chat functionality, the number of parameters ranges from 7B to 70B; we make use of the 13B chat model since it is the largest model that can fit a single A100 GPU. GPT-4 is a transformer-style model pre-trained to predict the next token followed by a set of instructions in a prompt based on human feedback. Table 1 provides an overview of the LLMs in our study, their sizes, languages covered during pre-training and supervised fine-tuning.

We did some early exploration of other models like FlanT5-XXL (Chung et al., 2022a), Flan-UL2<sup>4</sup>, Bactrian-X (Li et al., 2023), and BLOOMZ-7B (Muennighoff et al., 2022b), they tend to give worse result especially for generative tasks to the models we evaluated, and do not follow very well the instructions provided in the prompt templates. The Flan-T5 gave comparable results to mT0-MT on classification tasks and QA but worse results on generative tasks for African languages. Similarly, BLOOMZ-7B and Bactrian-X, are worse than LLaMa 2 in our evaluation, and they do not seem to follow instructions. We provide some qualitative analysis in section 6.

### 4.1 Prompt Templates

We designed our prompts in a zero-shot cross lingual manner, that is, the prompt context and query is designed in English, while the text to be analyzed is provided in the target African language. For each task, we designed simple prompts that tend to reasonable results on few examples of the training set. We prompt the LLMs using only English since it has been shown that English prompts perform better, on average, than in-language prompts (Lin et al., 2021; Shi et al., 2022). As such, we do not explore

<sup>2</sup>We specifically use gpt-4-0613.

<sup>3</sup><https://huggingface.co/datasets/bigscience/xP3mt>

<sup>4</sup><https://huggingface.co/google/flan-ul2>

Task/Dataset	Prompt
MASAKHANEWS	Labels only. Is this a piece of news regarding {business, entertainment, health, politics, religion, sports or technology}? {headline} {article body}
SIB-200	Labels only. Is this a piece of news regarding {science/techonology, travel, politics, sports, health, entertainment or geography}? {text}
AFRISENTI	Does this {language} statement; "{text}" have a {positive neutral or negative} sentiment? Labels only
MASAKHANER -X	{Text} Named entities refers to names of location, organisation and personal name. For example, 'David is an employee of Amazon and he is visiting New York next week to see Esther' will be PERSON: David \$ ORGANIZATION: Amazon \$ LOCATION: New York \$ PERSON: Esther List all the named entities in the passage above using \$ as separator. Return only the output
AFRIQA	Use the following pieces of context to answer the provided question. If you don't know the answer, just say that you don't know, don't try to make up an answer. Provide the answer with the least number of words possible. Provide the answer only. Provide answer in {pivot language}. Do not repeat the question {Context} {Question}
MAFAND-MT	Translate the {source language} sentence below to {target language}. Return the translated sentence only. If you cannot translate the sentence simply say you don't know {Text}
XL-SUM	Summarize this article in {language} language concisely with all important information and in the same language {article body} write a summary for the text

Table 2: **Prompt templates used for different tasks and datasets.** We make use of some templates from Sanh et al. (2022) with the addition of the prefix *labels only*.

prompting in the target language for both tasks. Table 2 provides the prompt template we used for each task. Appendix B provides details on the verbalizer employed for the news classification task.

#### 4.2 State-of-the-art (SotA) models

Here, we compare the performance GPT-4 on African languages with:

1. **State-of-the-art:** fully-supervised setting results i.e. pre-trained language models fine-tuned on labelled training data.
2. **High-resource languages (HRL) (e.g. English or French):** evaluation results available for the task, whenever it is available.

By comparing with high-resource languages, we can **compare the gap in performance with SotA** for low-resource African languages. We provide details of the SotA models in below:

#### 4.3 SotA models per task

**Classification/Tagging tasks** For news classification, topic classification sentiment classification, named entity recognition, the SotA was obtained by fine-tuning AfroXLMR-large model (Alabi et al., 2022) as reported in their respective benchmark datasets papers: MASAKHANEWS (Adelani et al., 2023), AFRISENTI (Muhammad et al., 2023) and MASAKHANER (Adelani et al., 2022b). However, for SIB-200 topic classification, we make use of AfroXLMR-large-76 (Adelani et al., 2024), covering 76 African languages. It is an adaptation of XLM-R (Conneau et al., 2020) to 76 languages, trained on on a mix of real data and synthetic data generated from NLLB-200.

**Question answering** The baseline was obtained by fine-tuning MT5-BASE (Xue et al., 2021) on SQuAD2.0 dataset (Rajpurkar et al., 2016) and evaluating it on African languages as reported in the AFRIQA paper (Ogundepo et al., 2023). For the high-resource languages evaluation, we perform the evaluation by providing the questions in English or French instead of the African language. This is possible since AFRIQA dataset provides the question and their human translation in the pivot language which is either English or French.

Question human-translated to EN/FR												Question in an African languages									
Model	Size	bem	fon	hau	ibo	kin	swa	twi	yor	zul	avg	bem	fon	hau	ibo	kin	swa	twi	yor	zul	avg
Fine-tune: SotA																					
mT5-base	580M	48.8	41.4	58.5	66.6	60.8	52.3	55.4	44.6	54.9	60.2	2.9	5.1	25.8	41.7	25.5	29.4	5.2	11.9	24.7	19.1
Prompting of LLMs																					
GPT-4	-	60.2	56.4	65.9	78.1	41.6	66.5	62.7	74.1	68.7	66.1	18.4	22.8	17.0	25.0	23.7	22.2	21.2	19.0	19.2	20.9
Aya	13B	73.9	70.6	76.9	<b>85.8</b>	<b>76.5</b>	<b>72.5</b>	74.1	76.1	82.2	76.5	43.9	32.8	<b>74.6</b>	<b>83.4</b>	<b>71.5</b>	71.4	43.4	68.5	<b>77.9</b>	63.0
mT0	13B	74.4	70.7	78.8	84.4	72.3	72.1	<b>75.6</b>	<b>79.3</b>	79.4	76.1	45.8	44.0	70.7	79.5	70.2	<b>71.8</b>	<b>52.7</b>	<b>72.6</b>	74.3	<b>64.6</b>
mT0-MT	13B	<b>76.1</b>	<b>73.9</b>	<b>80.3</b>	83.7	74.8	70.7	73.8	77.9	<b>80.3</b>	<b>76.8</b>	<b>46.9</b>	<b>46.4</b>	68.3	81.7	71.3	69.9	47.6	69.5	74.4	64.0
LLaMa 2	13B	63.5	55.6	70.5	75.5	63.5	65.4	62.6	74.6	63.1	66.0	27.7	35.6	25.5	37.2	22.6	42.9	23.7	24.9	24.1	29.6

Table 3: **Cross-lingual Question Answering Results:** We compare the SQuAD F1-score of various LLMs’ results (both target and high resource) with that of the current state of the art result obtained from Ogundepo et al. (2023).

French Centric									English Centric											
Model	Size	deu	bam	bbj	ewe	fon	mos	wol	deu	hau	ibo	lug	pcm	swa	tsn	twi	yor	zul	avg	
xx-fr/en																				
M2M-100	418M	51.9	45.6	26.5	30.9	27.5	17.0	33.8	57.6	35.1	46.1	46.4	36.7	68.6	55.8	45.2	35.1	35.2	39.0	
GPT-4	-	66.7	10.8	7.3	15.5	6.1	11.0	14.7	66.3	14.7	21.8	23.2	58.8	19.8	21.7	21.1	13.6	20.7	18.7	
Aya	13B	64.0	21.0	15.0	30.8	17.4	14.7	13.5	68.6	36.1	45.9	45.6	59.4	58	52.1	17.6	39.4	54.7	34.7	
mT0	13B	27.2	27.2	16.2	26.3	24.7	16.1	23.1	28.9	32.0	31.2	36.9	44.9	25.4	28.4	26.1	35.7	34.8	28.6	
mT0-MT	13B	63.1	32.9	13.9	33.1	27.9	16.3	27.7	68.2	38.1	46.8	48.7	56.9	57.1	53.5	38.2	40.8	54.4	39.1	
LLaMa 2	13B	45.0	17.8	15.3	21.2	18.2	17.1	18.0	53.2	17.4	23.1	29.2	54.8	32.9	24.0	24.4	20.8	22.6	23.8	
fr/en-xx																				
M2M-100	418M	59.0	48.2	23.1	30.9	27.6	16.7	35.7	53.4	43.3	50.0	39.0	64.0	56.4	52.0	38.2	35.9	51.2	40.8	
GPT-4	-	57.4	4.9	5.2	5.9	3.3	5.7	5.3	60.3	36.1	35.7	38.6	53.4	59.0	43.6	32.0	18.1	45.1	18.7	
Aya	13B	30.8	8.8	9.3	9.8	10.8	15.1	5.8	63.8	35.0	39.6	14.4	24.4	51.6	33.9	19.1	17.4	41.4	22.4	
mT0	13B	15.4	8.6	8.7	11.8	6.9	12.3	11.0	16.1	15.4	23.5	21.5	34.2	23.1	17.3	12.1	6.3	19.6	15.5	
mT0-MT	13B	24.9	17.7	11.5	20.1	9.1	14.6	16.5	25.0	23.11	38.5	28.6	48.3	48.3	34.3	29.9	15.2	38.1	26.2	
LLaMa 2	13B	22.4	13.2	6.5	16.8	11.0	10.9	15.1	22.4	14.7	16.3	14.1	21.4	41.3	24.4	19.5	10.4	20.3	17.1	

Table 4: **Machine Translation Results:** We compare the ChrF scores of various LLMs’ results with that of the current state of the art result obtained from Adelani et al. (2022a). Best results per language are in bold.

**Machine translation** The baseline was obtained by fine-tuning M2M-100 (Fan et al., 2021) on few thousands parallel sentences from the news domain. The high-resource languages evaluation is obtained by running predictions on pre-trained M2M-100, because they high-resource languages have been trained on very diverse domains (including news domain) unlike low-resource African languages that are mostly trained on the religious domain (Gowda et al., 2021; Nekoto et al., 2020; Adelani et al., 2022a).

**Summarization** The baseline was obtained by fine-tuning mT5-base model on the TRAIN split of XL-SUM as reported by (Hasan et al., 2021).

## 5 Results

Here, we discuss the key findings in comparing LLMs performance on African languages with SotA models across the five different tasks. We further report the gap in performance when compared to HRLs.

**Large gap persists between the performance of HRLs and African languages** Table 3 shows the QA results, which clearly demonstrates that providing questions in English/French which is also the language of the context passage achieves significantly better performance than providing questions in an African language both for the fully-supervised setting and prompting setup. The performance gap is as wide as  $-45.2$  and  $-36.4$  for GPT-4 and LLaMa 2 but smaller ( $-12.5$  to  $-11.5$ ) for Aya, mT0-13B and mT0-13B-MT. Similarly, for machine translation (Table 4), GPT-4 gave better performance than the baseline M2M-100 model in the high-resource directions like *fr-deu*, *en-deu*, however for the translation into African languages, the ChrF score is  $< 50$  score except for Nigerian-Pidgin (pcm) which is an English-based creole, and Swahili (a mid-resource language). Generating in English (i.e *xx-en*) is much better for GPT-4 overall. Other LLMs also have the same trend as GPT-4. For summarization task, news classification, and sentiment analysis, we also observe this trend, however, some African languages also have similar performance.

**Aya and mT0 are better on generative tasks than GPT-4 and LLaMa 2** Table 3 shows that Aya, mT0 and mT0-MT have compared performance on the QA task reaching F1-score of 75.0 or above

High-resource			African languages										
Model	Size	eng	amh	hau	ibo	orm	pcm	run	som	swa	tir	yor	avg
Fine-tune: SotA													
mT5	580M	29.9	18.0	31.7	24.5	16.2	29.9	25.8	24.2	30.9	21.2	25.1	25.2
Prompting of LLMs													
GPT-4	-	9.0	3.1	11.7	12.8	7.0	11.7	11.9	11.6	13.5	14.1	3.3	11.5
Aya	13B	25.1	3.2	29.2	26.0	13.4	21.1	25.6	24.6	30.9	3.7	26.8	20.9
LLaMa 2	13B	9.4	0.1	7.1	4.1	1.9	10.3	4.1	5.8	7.4	0.3	8.4	5.4

Table 5: **Summarization Results:** We compare the rougeL score of various LLMs’ results with that of the current state of the art result obtained from Muhammad et al. (2023). Best results per language are in bold.

		High-resource		African languages																	
Model	Size	eng	fra	amh	hau	ibo	lin	lug	pcm	orm	run	sna	som	swa	tir	xho	yor	avg			
Fine-tune: SotA																					
AfroXLMR-large	550M	93.1	91.1	94.4	92.2	93.4	93.7	89.9	92.1	98.8	92.7	95.4	86.9	87.7	89.5	97.3	94.0	92.7			
Prompting of LLMs																					
GPT-4	-	84.7	82.6	91.1	74.4	82.2	82.4	84.1	78.8	94.7	88.5	78.1	79.7	79.2	75.7	87.5	93.7	85.6			
Aya	13B	81.0	83.3	88.5	82.6	84.5	88.4	90.1	87.5	96.1	93.0	78.5	78.3	78.6	79.6	87.6	92.1	86.1			
mT0	13B	64.7	58.3	64.8	65.6	63.6	62.3	56.7	57.4	74.4	58.8	82.6	52.3	57.8	52.0	69.7	61.7	62.8			
mT0-MT	13B	68.7	58.0	63.5	72.1	70.5	63.4	74.1	56.3	81.8	61.4	72.1	56.0	58.1	55.2	84.6	74.0	67.4			
LLaMa 2	13B	61.0	45.1	7.1	37.2	60.7	66.1	63.2	22.6	70.4	63.4	69.6	48.8	50.5	3.9	61.3	41.1	47.6			

Table 6: **News Classification Results:** We compare the F1-score of various LLMs’ results with that of the current state of the art result obtained from Adelani et al. (2023). Best results per language are in bold.

when questions are translated to English/French, and 63.0 – 64.6 for questions asked in an African language. LLaMa 2 and GPT-4 generally performs worse with over –30 F1 drop in performance when questions are asked in an African language. Similarly, for machine translation, mT0-MT and Aya are better than GPT-4 and LLaMa 2 on average, with mT0-MT having the overall best result. However, in the high-resource language direction, GPT-4 and Aya performance are comparable reaching 60.3 – 63.8 ChrF in *en-deu*, and better than mT0-MT with 25.0 ChrF. We hypothesize that one of the reasons for Aya and mT0 to be superior in generative tasks is that many of the languages we evaluated are covered during the pre-training of the base model (i.e. mT5) and supervised fine-tuning as shown in Table 1. This clearly shows when they are better than LLaMa 2. It is very likely that GPT-4 also covers fewer African languages.

**Fine-tuning with multilingual prompts helps mT0-13B-MT to be competitive on MT** Our evaluation shows that mT0-13B-MT significantly perform better than mT0-13B, the performance gap is wider for MT ( $\sim +10$  ChrF) than any other tasks we evaluated on ( $< 5.0$ ). The effective performance is due to the multilingual prompts used in developing the mT0-13B-MT instead of the English-only prompt as shown in Muennighoff et al. (2022a). mT0 generally outperforms other LLMs on MT because the multitask prompted datasets used in creating mT0 includes several MT datasets for African languages like WMT African dataset<sup>5</sup> and Flores-101 (Goyal et al., 2022).

**mT0 and Aya achieves better performance than SotA on cross-lingual QA** Surprisingly, we find mT0 and Aya achieved the best performance (see Table 3) even when the questions are provided in an African language. We hypothesize that this performance is probably due to the large number of QA datasets in xP3 and Aya dataset, which was used for creating the models.

**is Aya better than mT0-MT?** Both models are based on the same architecture and base model i.e. mT5-XXL, but they have been fine-tuned on different multi-task prompted dataset. Our evaluation on cross-lingual QA shows that mT0-MT (64.6) is still slightly better than Aya (63.0 F1) on average when the question is in an African language. For machine translation mT0-MT is better than Aya for low-resource translation directions but for high-resource languages like German, Aya is better. For classification tasks, the result are somewhat mixed, Aya is better than mT0 on news classification, but on SIB-200 topic classification and sentiment, the performance is comparable.<sup>6</sup> Our conclusion

<sup>5</sup>[https://huggingface.co/datasets/allenai/wmt22\\_african](https://huggingface.co/datasets/allenai/wmt22_african)

<sup>6</sup>Aya performed SFT on AFRISENTI training data but does not seem to improve performance.

HRL			African Language Family							
Model	Size	English	Afro-Asiatic (12)	Atlantic-Congo (34)	Austronesian (1)	Indo-European (1)	Mande (5)	Nilotic (3)	avg (56)	
Fine-tune: SotA										
AfroXLMR76L	550M	91.8	69.9	76.7	88.1	91.1	64.1	63.6	74.1	
Prompting of LLMs										
GPT-4	-	76.6	43.6	23.7	45.7	68.8	13.3	32.9	29.6	
Aya	13B	49.7	40.5	40.9	51.5	50.6	29.6	24.7	39.3	
mT0	13B	49.6	37.3	41.8	48.1	49.3	40.7	26.1	39.7	
mT0-MT	13B	33.4	28.8	31.8	39.2	40.8	31.4	18.3	30.3	

Table 7: **SIB News Topic Classification Results:** We compare the F1-score of various LLMs’ results with that of the current state of the art result obtained from Adelani et al. (2024). Best results per language are in bold. Appendix D provides full breakdown of results by languages.

High-resource			African languages												
Model	Size	eng	por-mz	amh	arq	ary	hau	ibo	kin	pcm	swa	tso	twi	yor	avg
Fine-tune: SotA															
AfroXLMR-large	550M	<b>68.1</b>	<b>71.6</b>	61.6	<b>68.3</b>	<b>56.6</b>	<b>80.7</b>	<b>79.5</b>	<b>70.6</b>	<b>68.7</b>	63.4	47.3	<b>64.3</b>	<b>74.1</b>	<b>66.8</b>
Prompting of LLMs															
GPT-4	-	66.1	60.4	72	63.2	56.4	41.9	65.1	57.3	64.1	<b>64.5</b>	22.3	51.9	53.9	55.7
Aya	13B	59.5	68.8	40.2	34.3	39.8	48.3	54.3	33.5	36.0	59.5	24.3	15.3	35.9	40.8
mT0	13B	41.2	16.0	67.2	50.4	37.0	40.5	26.7	36.3	63.6	20.9	<b>47.5</b>	43.5	35.6	42.6
mT0-MT	13B	37.2	16.5	<b>70.2</b>	58.5	34.6	36.1	27.2	39.5	50.7	18.7	42.1	35.9	23.7	39.7
LLaMa 2	13B	52.8	32.3	10.5	26.2	37.4	25.5	35.1	34.2	24.3	49.7	30.5	23.9	24.0	29.2

Table 8: **Sentiment Analysis Results:** We compare the F1-score of various LLMs’ results with that of the current state of the art result obtained from Muhammad et al. (2023). Best results per language are in bold.

is that, we have not made much progress with multilingual evaluation with the introduction of the recent Aya model.

**Aya excels on summarization task for Latin-based script** For the summarization evaluation, we did not include mT0 since xP3 multi-task prompted dataset it was trained on includes both XL-SUM and FLoRes-101. Table 5 shows the comparison of GPT-4, Aya and LLaMa 2. Aya’s performance is very similar to the baseline mT5-base model, and for some languages like *ibo*, *som* and *yor*, the performance over mT5-base is around +1.5, +0.6, +1.7 respectively. The only languages it struggles are the ones based on non-Latin script i.e. Amharic and Tigrinya that makes use of the Ge’ez script. Comparing with other LLMs, Aya performed better than GPT-4 and LLaMa 2 by +9.4 RougeL and +15.5 RougeL points respectively.

**GPT-4 achieves more than 92% of SotA’s performance on long context classification tasks** For news topic classification (Table 6), the performance on English (84.7) and French (82.6) is very similar to the average performance on African languages (85.6), possibly due to the simplicity of the task and the long context of the entire article provided for classification.

**LLMs achieves worse results on classification of short sentences** Unlike long context sentences like MASAKHANEWS, Table 7 and Table 8 shows the result for AFRISENTI and SIB-200 whose sentences are short like tweets or a single sentence from paragraph about a topic. The performance of LLMs on African languages are much worse than on English. For example, the performance gap of prompting GPT-4 to full-supervised setting for SIB-200 on English is −15.2 while on average for African language, it drops to −44.5. On sentiment classification, the performance for GPT-4 drops from −2 for English to −11.1 for African languages. Aya and mT0 are better than GPT-4 on SIB-200, but worse than GPT-4 on sentiment.

**LLaMa 2 often struggles due to limited multilingual abilities** In general LLaMa 2 achieves the worst performance compared to other models of similar sizes like mT0-13B and Aya, this is likely because of the pre-training corpus of LLaMa 2 that is mostly English and code.

**All models struggle with token classification** On average, all LLMs gave a poor result for NER (see Table 9), mT0 do not seem to follow the result template we provide with the “\$\$” as an entity separator. LLaMa 2 also often repeat the one-shot example we provided as the output. Only GPT-4 has an average performance on the task (55.6).



Model	Size	amh	bam	bbj	ewe	hau	ibo	kin	lug	luo	mos	nya	pcm	sna	swa	tsn	twi	wol	xho	yor	zul	avg
Fine-tune: SotA																						
AfroXLMR-large	550M	78.0	79.0	90.3	75.2	85.4	88.9	86.8	88.9	75.3	73.5	92.4	90.0	96.1	92.7	88.9	79.2	83.8	89.2	67.9	90.6	84.6
Prompting of LLMs																						
GPT-4	-	28.5	52.7	50.3	75.6	64.9	56.0	55.1	73.3	49.8	60.2	63.6	64.7	33.4	71.5	64.6	58.6	67.9	28.4	58.3	34.9	55.6
AYA	-	14.1	7.1	20.0	26.5	34.5	28.2	30.8	16.3	12.7	34.4	21.7	27.4	13.4	35.6	29.4	18.9	14.5	4.2	17.5	11.4	20.9
mT0	13B	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
mT0-MT	13B	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
LLaMa 2	13B	0.0	13.8	12.3	25.1	22.1	22.0	23.1	27.5	19.0	11.0	20.0	27.5	11.3	25.8	26.2	20.7	16.0	8.1	15.1	9.0	17.8

Table 9: **Named Entity Recognition Results:** We compare the F1-score of various LLMs with that of the current state of the art result obtained from Adelani et al. (2021) (amh, luo) and Adelani et al. (2022b) (others).

LLM	Output
machine translation	
source (en)	The disgusting note read: 'Put your dog on a lead, slag!
target (zul)	Umbhalo onyanyisayo ubufundeka kanje: 'Bekainja yakho phambili, slag!
FlanT5-XXL	Isiphelo esiphelo esiphelo esiphelo esiphelo esiphelo esiphelo esiphelo esiphelo esiphelo esiphelo ...
BLOOMZ-7B	The disgusting note read: 'Put your dog on a lead, slag!' The disgusting note read: 'Put your dog on a lead, slag!
Bactarian-X	Umuntu ngabantu ngabantu ngabantu ngabantu ngabantu ngabantu ngabantu ngabantu ngabantu ngabantu ...
LLaMa 2	I apologize, but I cannot provide a translation for that sentence as it contains derogatory language and is not appropriate to use in any context. It is important to treat all individuals with respect and kindness, regardless of their background or circumstances. Additionally, using offensive language or making threats is never an acceptable way to communicate. Is there something else I can assist you with?
mT0-MT	I-note ebuhlungu ifundeka: 'Beka i-dog yakho eqondile, scum!
Aya	I-note ecalulayo yathi: 'Hamba uthathe umqaphi wakho, i-sla!
sentiment classification	
Swahili	Umeondoka kimya kimya mzee wangu Sijapenda Time ingeruhusi ningetumia Usafiri Kutoka kwa Hawa
Label	neutral
FlanT5-XXL	positive
BLOOMZ-7B	Positive
Bactarian-X	The sentence is in Swahili and it translates to: "I am old enough that I do not like the chemical smell of my grandfather's medicine.
LLaMa 2	Sure! Here's my assessment of the sentiment of the given Swahili statement: Label: Neutral
mT0-MT	Negative
Aya	Negative

Table 10: Qualitative analysis of the predictions of the different open models

## 6 Discussion and Conclusion

**Qualitative analysis** We provide sample predictions of different models on sentiment classification and machine translation example from English to Zulu. Table 10 shows that for machine translation FlanT5, Bactarian-X, and BLOOMZ-7B often hallucinates in generation or does not translate, and it's one of the reasons we excluded them in our evaluation. LLaMa 2 13B sometimes refuses to generate texts if the sentiment of the texts is negative as shown in the machine translation generation, this is due to the safety alignment of the model. Similarly for sentiment classification of a Swahili sentence, Bactarian-X does not seem to follow instruction compared to other open models.

**Conclusion** we have presented an analysis of the performance of different language models on African languages. Our results shows that there is a large gap in performance between HRLs and African languages. Our result also shows that no single model is the best on all tasks, unlike previous large scale evaluation (Ahuja et al., 2023a;c) which claims ChatGPT is the best LLM on all tasks they evaluated on. We find mT0 and Aya to be better than GPT-4 on generative tasks such as cross-lingual QA, summarization and machine translation on African languages. One possible reason is that many of the languages we evaluated are covered during the pre-training of the base model (i.e. mT5) and supervised fine-tuning as shown in Table 1. Based on this findings, our goal is to create a leaderboard that can be continuously used to measure and evaluate the performance of newer multilingual LLMs. Leaderboards have helped the NLP field to advance the performance of multilingual pre-trained models over the years (Wang et al., 2018; Hu et al., 2020), and this provides an opportunity to create such a leaderboard.

**Future directions** There are several future directions to explore such as development of a high-quality supervised instruction data for adapting LLMs to African languages, developing instruct-style models leveraging open weights that are publicly available, and pre-training from scratch LLMs for African languages. Aside from building better models, newer evaluation datasets for reasoning tasks like mathematics reasoning Cobbe et al. (2021), Hellaswag (Zellers et al., 2019), MMLU (Hendrycks et al., 2021), ARC (Clark et al., 2018) are needed for African languages.

## References

- David Adelani, Jesujoba Alabi, Angela Fan, Julia Kreutzer, Xiaoyu Shen, Machel Reid, Dana Ruiter, Dietrich Klakow, Peter Nabende, Ernie Chang, Tajuddeen Gwadabe, Freshia Sackey, Bonaventure F. P. Dossou, Chris Emezue, Colin Leong, Michael Beukman, Shamsuddeen Muhammad, Guyo Jarso, Oreen Yousuf, Andre Niyongabo Rubungo, Gilles Hacheme, Eric Peter Wairagala, Muhammad Umair Nasir, Benjamin Ajibade, Tunde Ajayi, Yvonne Gitau, Jade Abbott, Mohamed Ahmed, Millicent Ochieng, Anuoluwapo Aremu, Perez Ogayo, Jonathan Mukiibi, Fatoumata Ouoba Kabore, Godson Kalipe, Derguene Mbaye, Allahsera Auguste Tapo, Victoire Memdjokam Koagne, Edwin Munkoh-Buabeng, Valencia Wagner, Idris Abdulmumin, Ayodele Awokoya, Happy Buzaaba, Blessing Sibanda, Andiswa Bukula, and Sam Manthalu. A few thousand translations go a long way! leveraging pre-trained models for African news translation. In Marine Carpuat, Marie-Catherine de Marneffe, and Ivan Vladimir Meza Ruiz (eds.), *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 3053–3070, Seattle, United States, July 2022a. Association for Computational Linguistics. doi: 10.18653/v1/2022.naacl-main.223. URL <https://aclanthology.org/2022.naacl-main.223>.
- David Adelani, Graham Neubig, Sebastian Ruder, Shruti Rijhwani, Michael Beukman, Chester Palen-Michel, Constantine Lignos, Jesujoba Alabi, Shamsuddeen Muhammad, Peter Nabende, Cheikh M. Bamba Dione, Andiswa Bukula, Rooweither Mabuya, Bonaventure F. P. Dossou, Blessing Sibanda, Happy Buzaaba, Jonathan Mukiibi, Godson Kalipe, Derguene Mbaye, Amelia Taylor, Fatoumata Kabore, Chris Chinenye Emezue, Anuoluwapo Aremu, Perez Ogayo, Catherine Gitau, Edwin Munkoh-Buabeng, Victoire Memdjokam Koagne, Allahsera Auguste Tapo, Tebogo Macucwa, Vukosi Marivate, Mboning Tchiase Elvis, Tajuddeen Gwadabe, Tosin Adewumi, Orevaoghene Ahia, Joyce Nakatumba-Nabende, Neo Lerato Mokono, Ignatius Ezeani, Chiamaka Chukwuneke, Mofetoluwa Oluwaseun Adeyemi, Gilles Quentin Hacheme, Idris Abdulmumin, Odunayo Ogundepo, Oreen Yousuf, Tatiana Moteu, and Dietrich Klakow. MasakhaNER 2.0: Africa-centric transfer learning for named entity recognition. In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 4488–4508, Abu Dhabi, United Arab Emirates, December 2022b. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.298. URL <https://aclanthology.org/2022.emnlp-main.298>.
- David Adelani, Hannah Liu, Xiaoyu Shen, Nikita Vassilyev, Jesujoba Alabi, Yanke Mao, Haonan Gao, and En-Shiun Lee. SIB-200: A simple, inclusive, and big evaluation dataset for topic classification in 200+ languages and dialects. In Yvette Graham and Matthew Purver (eds.), *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 226–245, St. Julian’s, Malta, March 2024. Association for Computational Linguistics. URL <https://aclanthology.org/2024.eacl-long.14>.
- David Ifeoluwa Adelani, Jade Abbott, Graham Neubig, Daniel D’souza, Julia Kreutzer, Constantine Lignos, Chester Palen-Michel, Happy Buzaaba, Shruti Rijhwani, Sebastian Ruder, Stephen Mayhew, Israel Abebe Azime, Shamsuddeen H. Muhammad, Chris Chinenye Emezue, Joyce Nakatumba-Nabende, Perez Ogayo, Aremu Anuoluwapo, Catherine Gitau, Derguene Mbaye, Jesujoba Alabi, Seid Muhie Yimam, Tajuddeen Rabiou Gwadabe, Ignatius Ezeani, Rubungo Andre Niyongabo, Jonathan Mukiibi, Verrah Otiende, Iroko Orife, Davis David, Samba Ngom, Tosin Adewumi, Paul Rayson, Mofetoluwa Adeyemi, Gerald Muriuki, Emmanuel Anebi, Chiamaka Chukwuneke, Nkiruka Odu, Eric Peter Wairagala, Samuel Oyerinde, Clemencia Siro, Tobius Saul Bateesa, Temilola Oloyede, Yvonne Wambui, Victor Akinode, Deborah Nabagereka, Maurice Katusiime, Ayodele Awokoya, Mouhamadane MBOUP, Dibora Gebreyohannes, Henok Tilaye, Kelechi Nwaike, Degaga Wolde, Abdoulaye Faye, Blessing Sibanda, Orevaoghene Ahia, Bonaventure F. P. Dossou, Kelechi Ogueji, Thierno Ibrahima DIOP, Abdoulaye Diallo, Adewale Akinfaderin, Tendai Marengereke, and Salomey Osei. MasakhaNER: Named entity recognition for African languages. *Transactions of the Association for Computational Linguistics*, 9:1116–1131, 2021. doi: 10.1162/tacl\_a\_00416. URL <https://aclanthology.org/2021.tacl-1.66>.
- David Ifeoluwa Adelani, Marek Masiak, Israel Abebe Azime, Jesujoba Alabi, Atnafu Lambebo Tonja, Christine Mwase, Odunayo Ogundepo, Bonaventure F. P. Dossou, Akintunde Oladipo, Doreen Nixdorf, Chris Chinenye Emezue, sana al azzawi, Blessing Sibanda, Davis David, Lolwethu Ndoleta, Jonathan Mukiibi, Tunde Ajayi, Tatiana Moteu, Brian Odhiambo, Abraham Owodunni, Nnaemeka

- Obiefuna, Muhidin Mohamed, Shamsuddeen Hassan Muhammad, Teshome Mulugeta Ababu, Saheed Abdullahi Salahudeen, Mesay Gemeda Yigezu, Tajuddeen Gwadabe, Idris Abdulmumin, Mahlet Taye, Oluwabusayo Awoyomi, Iyanuoluwa Shode, Tolulope Adelani, Habiba Abdulganiyu, Abdul-Hakeem Omotayo, Adetola Adeeko, Abeeb Afolabi, Anuoluwapo Aremu, Olanrewaju Samuel, Clemencia Siro, Wangari Kimotho, Onyekachi Ogbu, Chinedu Mbonu, Chiamaka Chukwuneke, Samuel Fanijo, Jessica Ojo, Oyinkansola Awosan, Tadesse Kebede, Toadoun Sari Sakayo, Pamela Nyatsine, Freedmore Sidume, Oreen Yousuf, Mardiyyah Oduwole, Tshinu Tshinu, Ussen Kimanuka, Thina Diko, Siyanda Nxakama, Sinodos Nigusse, Abdulmejid Johar, Shafie Mohamed, Fuad Mire Hassan, Moges Ahmed Mehamed, Evrard Ngabire, Jules Jules, Ivan Ssenkungu, and Pontus Stenertorp. Masakhanews: News topic classification for african languages, 2023.
- Kabir Ahuja, Harshita Diddee, Rishav Hada, Millicent Ochieng, Krithika Ramesh, Prachi Jain, Akshay Nambi, Tanuja Ganu, Sameer Segal, Mohamed Ahmed, Kalika Bali, and Sunayana Sitaram. MEGA: Multilingual evaluation of generative AI. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 4232–4267, Singapore, December 2023a. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.258. URL <https://aclanthology.org/2023.emnlp-main.258>.
- Kabir Ahuja, Harshita Diddee, Rishav Hada, Millicent Ochieng, Krithika Ramesh, Prachi Jain, Akshay Nambi, Tanuja Ganu, Sameer Segal, Maxamed Axmed, Kalika Bali, and Sunayana Sitaram. Mega: Multilingual evaluation of generative ai, 2023b.
- Sanchit Ahuja, Divyanshu Aggarwal, Varun Gumma, Ishaan Watts, Ashutosh Sathe, Millicent Ochieng, Rishav Hada, Prachi Jain, Maxamed Axmed, Kalika Bali, and Sunayana Sitaram. Mega-verse: Benchmarking large language models across languages, modalities, models and tasks, 2023c.
- Jesujoba O. Alabi, David Ifeoluwa Adelani, Marius Mosbach, and Dietrich Klakow. Adapting pre-trained language models to African languages via multilingual adaptive fine-tuning. In *Proceedings of the 29th International Conference on Computational Linguistics*, pp. 4336–4349, Gyeongju, Republic of Korea, October 2022. International Committee on Computational Linguistics. URL <https://aclanthology.org/2022.coling-1.382>.
- Rohan Anil, Andrew M. Dai, Orhan Firat, Melvin Johnson, Dmitry Lepikhin, Alexandre Passos, Siamak Shakeri, Emanuel Taropa, Paige Bailey, Zhifeng Chen, Eric Chu, Jonathan H. Clark, Laurent El Shafey, Yanping Huang, Kathy Meier-Hellstern, Gaurav Mishra, Erica Moreira, Mark Omernick, Kevin Robinson, Sebastian Ruder, Yi Tay, Kefan Xiao, Yuanzhong Xu, Yujing Zhang, Gustavo Hernandez Abrego, Junwhan Ahn, Jacob Austin, Paul Barham, Jan Botha, James Bradbury, Siddhartha Brahma, Kevin Brooks, Michele Catasta, Yong Cheng, Colin Cherry, Christopher A. Choquette-Choo, Aakanksha Chowdhery, Clément Crepy, Shachi Dave, Mostafa Dehghani, Sunipa Dev, Jacob Devlin, Mark Díaz, Nan Du, Ethan Dyer, Vlad Feinberg, Fangxiaoyu Feng, Vlad Fienber, Markus Freitag, Xavier Garcia, Sebastian Gehrmann, Lucas Gonzalez, Guy Gur-Ari, Steven Hand, Hadi Hashemi, Le Hou, Joshua Howland, Andrea Hu, Jeffrey Hui, Jeremy Hurwitz, Michael Isard, Abe Ittycheriah, Matthew Jagielski, Wenhao Jia, Kathleen Kenealy, Maxim Krikun, Sneha Kudugunta, Chang Lan, Katherine Lee, Benjamin Lee, Eric Li, Music Li, Wei Li, YaGuang Li, Jian Li, Hyeontaek Lim, Hanzhao Lin, Zhongtao Liu, Frederick Liu, Marcello Maggioni, Aroma Mahendru, Joshua Maynez, Vedant Misra, Maysam Moussalem, Zachary Nado, John Nham, Eric Ni, Andrew Nystrom, Alicia Parrish, Marie Pellat, Martin Polacek, Alex Polozov, Reiner Pope, Siyuan Qiao, Emily Reif, Bryan Richter, Parker Riley, Alex Castro Ros, Aurko Roy, Brennan Saeta, Rajkumar Samuel, Renee Shelby, Ambrose Slone, Daniel Smilkov, David R. So, Daniel Sohn, Simon Tokumine, Dasha Valter, Vijay Vasudevan, Kiran Vodrahalli, Xuezhi Wang, Pidong Wang, Zirui Wang, Tao Wang, John Wieting, Yuhuai Wu, Kelvin Xu, Yunhan Xu, Linting Xue, Pengcheng Yin, Jiahui Yu, Qiao Zhang, Steven Zheng, Ce Zheng, Weikang Zhou, Denny Zhou, Slav Petrov, and Yonghui Wu. Palm 2 technical report, 2023.
- Terra Blevins and Luke Zettlemoyer. Language contamination helps explain the cross-lingual capabilities of english pretrained models, 2022. URL <https://arxiv.org/abs/2204.08110>.

- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL <https://proceedings.neurips.cc/paper/2020/file/1457c0d6bfc4967418bfb8ac142f64a-Paper.pdf>.
- Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.
- Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Eric Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Shane Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Sharan Narang, Gaurav Mishra, Adams Yu, Vincent Zhao, Yanping Huang, Andrew Dai, Hongkun Yu, Slav Petrov, Ed H. Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V. Le, and Jason Wei. Scaling instruction-finetuned language models, 2022a. URL <https://arxiv.org/abs/2210.11416>.
- Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Shane Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Alex Castro-Ros, Marie Pellat, Kevin Robinson, Dasha Valter, Sharan Narang, Gaurav Mishra, Adams Yu, Vincent Zhao, Yanping Huang, Andrew Dai, Hongkun Yu, Slav Petrov, Ed H. Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V. Le, and Jason Wei. Scaling instruction-finetuned language models, 2022b. URL <https://arxiv.org/abs/2210.11416>.
- Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Shane Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Alex Castro-Ros, Marie Pellat, Kevin Robinson, Dasha Valter, Sharan Narang, Gaurav Mishra, Adams Yu, Vincent Zhao, Yanping Huang, Andrew Dai, Hongkun Yu, Slav Petrov, Ed H. Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V. Le, and Jason Wei. Scaling instruction-finetuned language models, 2022c.
- Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv:1803.05457v1*, 2018.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 8440–8451, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.747. URL <https://aclanthology.org/2020.acl-main.747>.
- Angela Fan, Shruti Bhosale, Holger Schwenk, Zhiyi Ma, Ahmed El-Kishky, Siddharth Goyal, Mandeep Baines, Onur Celebi, Guillaume Wenzek, Vishrav Chaudhary, Naman Goyal, Tom Birch, Vitaliy Liptchinsky, Sergey Edunov, Edouard Grave, Michael Auli, and Armand Joulin. Beyond english-centric multilingual machine translation. *J. Mach. Learn. Res.*, 22(1), jan 2021. ISSN 1532-4435.
- Thamme Gowda, Zhao Zhang, Chris Mattmann, and Jonathan May. Many-to-English machine translation tools, data, and pretrained models. In Heng Ji, Jong C. Park, and Rui Xia (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the*

- 11th International Joint Conference on Natural Language Processing: System Demonstrations*, pp. 306–316, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-demo.37. URL <https://aclanthology.org/2021.acl-demo.37>.
- Naman Goyal, Cynthia Gao, Vishrav Chaudhary, Peng-Jen Chen, Guillaume Wenzek, Da Ju, Sanjana Krishnan, Marc’Aurelio Ranzato, Francisco Guzmán, and Angela Fan. The Flores-101 evaluation benchmark for low-resource and multilingual machine translation. *Transactions of the Association for Computational Linguistics*, 10:522–538, 2022. doi: 10.1162/tacl\_a\_00474. URL <https://aclanthology.org/2022.tacl-1.30>.
- Tahmid Hasan, Abhik Bhattacharjee, Md. Saiful Islam, Kazi Mubasshir, Yuan-Fang Li, Yong-Bin Kang, M. Sohel Rahman, and Rifat Shahriyar. XL-sum: Large-scale multilingual abstractive summarization for 44 languages. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 4693–4703, Online, August 2021. Association for Computational Linguistics. URL <https://aclanthology.org/2021.findings-acl.413>.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.
- Oskar Holmström and Ehsan Doostmohammadi. Making instruction finetuning accessible to non-English languages: A case study on Swedish models. In Tanel Alumäe and Mark Fishel (eds.), *Proceedings of the 24th Nordic Conference on Computational Linguistics (NoDaLiDa)*, pp. 634–642, Tórshavn, Faroe Islands, May 2023. University of Tartu Library. URL <https://aclanthology.org/2023.nodalida-1.62>.
- Junjie Hu, Sebastian Ruder, Aditya Siddhant, Graham Neubig, Orhan Firat, and Melvin Johnson. Xtreme: A massively multilingual multi-task benchmark for evaluating cross-lingual generalization. *CoRR*, abs/2003.11080, 2020.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Léo Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mistral 7b, 2023.
- Viet Lai, Nghia Ngo, Amir Pouran Ben Veyseh, Hieu Man, Franck Dernoncourt, Trung Bui, and Thien Nguyen. ChatGPT beyond English: Towards a comprehensive evaluation of large language models in multilingual learning. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 13171–13189, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.878. URL <https://aclanthology.org/2023.findings-emnlp.878>.
- Haonan Li, Fajri Koto, Minghao Wu, Alham Fikri Aji, and Timothy Baldwin. Bactrian-x : A multilingual replicable instruction-following model with low-rank adaptation, 2023.
- Xi Victoria Lin, Todor Mihaylov, Mikel Artetxe, Tianlu Wang, Shuohui Chen, Daniel Simig, Myle Ott, Naman Goyal, Shruti Bhosale, Jingfei Du, Ramakanth Pasunuru, Sam Shleifer, Punit Singh Koura, Vishrav Chaudhary, Brian O’Horo, Jeff Wang, Luke Zettlemoyer, Zornitsa Kozareva, Mona T. Diab, Veselin Stoyanov, and Xian Li. Few-shot learning with multilingual language models. *CoRR*, abs/2112.10668, 2021. URL <https://arxiv.org/abs/2112.10668>.
- Niklas Muennighoff, Thomas Wang, Lintang Sutawika, Adam Roberts, Stella Biderman, Teven Le Scao, M Saiful Bari, Sheng Shen, Zheng-Xin Yong, Hailey Schoelkopf, Xiangru Tang, Dragomir Radev, Alham Fikri Aji, Khalid Almubarak, Samuel Albanie, Zaid Alyafeai, Albert Webson, Edward Raff, and Colin Raffel. Crosslingual generalization through multitask finetuning, 2022a. URL <https://arxiv.org/abs/2211.01786>.
- Niklas Muennighoff, Thomas Wang, Lintang Sutawika, Adam Roberts, Stella Biderman, Teven Le Scao, M Saiful Bari, Sheng Shen, Zheng-Xin Yong, Hailey Schoelkopf, et al. Crosslingual generalization through multitask finetuning. *arXiv preprint arXiv:2211.01786*, 2022b.

- Niklas Muennighoff, Thomas Wang, Lintang Sutawika, Adam Roberts, Stella Biderman, Teven Le Scao, M Saiful Bari, Sheng Shen, Zheng Xin Yong, Hailey Schoelkopf, Xiangru Tang, Dragomir Radev, Alham Fikri Aji, Khalid Almubarak, Samuel Albanie, Zaid Alyafeai, Albert Webson, Edward Raff, and Colin Raffel. Crosslingual generalization through multitask finetuning. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (eds.), *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15991–16111, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.891. URL <https://aclanthology.org/2023.acl-long.891>.
- Shamsuddeen Hassan Muhammad, Idris Abdulmumin, Abinew Ali Ayele, Nedjma Ousidhoum, David Ifeoluwa Adelani, Seid Muhie Yimam, Ibrahim Sa’id Ahmad, Meriem Beloucif, Saif Mohammad, Sebastian Ruder, Oumaima Hourrane, Pavel Brazdil, Felermino Dário Mário António Ali, Davis Davis, Salomey Osei, Bello Shehu Bello, Falalu Ibrahim, Tajuddeen Gwadabe, Samuel Rutunda, Tadesse Belay, Wendimu Baye Messelle, Hailu Beshada Balcha, Sisay Adugna Chala, Hagos Tesfahun Gebremichael, Bernard Opoku, and Steven Arthur. AfriSenti: A Twitter Sentiment Analysis Benchmark for African Languages, 2023. URL <https://arxiv.org/abs/2302.08956>.
- Wilhelmina Nekoto, Vukosi Marivate, Tshinondiwa Matsila, Timi Fasubaa, Taiwo Fagbohunge, Solomon Oluwale Akinola, Shamsuddeen Muhammad, Salomon Kabongo Kabenamualu, Salomey Osei, Freshia Sackey, Rubungo Andre Niyongabo, Ricky Macharm, Perez Ogayo, Orevaoghene Ahia, Musie Meressa Berhe, Mofetoluwa Adeyemi, Masabata Mokgesi-Seling, Lawrence Okegbemi, Laura Martinus, Kolawole Tajudeen, Kevin Degila, Kelechi Ogueji, Kathleen Siminyu, Julia Kreutzer, Jason Webster, Jamiil Toure Ali, Jade Abbott, Iroro Orife, Ignatius Ezeani, Idris Abdulkadir Dangana, Herman Kamper, Hady Elsahar, Goodness Duru, Gholah Kioko, Murhabazi Espoir, Elan van Biljon, Daniel Whitenack, Christopher Onyefuluchi, Chris Chinenye Emezue, Bonaventure F. P. Dossou, Blessing Sibanda, Blessing Bassey, Ayodele Olabiyi, Arshath Ramkilowan, Alp Öktem, Adewale Akinfaderin, and Abdallah Bashir. Participatory research for low-resourced machine translation: A case study in African languages. In Trevor Cohn, Yulan He, and Yang Liu (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 2144–2160, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.findings-emnlp.195. URL <https://aclanthology.org/2020.findings-emnlp.195>.
- NLLB Team, Marta R. Costa-jussà, James Cross, Onur Çelebi, Maha Elbayad, Kenneth Heafield, Kevin Heffernan, Elahe Kalbassi, Janice Lam, Daniel Licht, Jean Maillard, Anna Sun, Skyler Wang, Guillaume Wenzek, Al Youngblood, Bapi Akula, Loic Barrault, Gabriel Mejia-Gonzalez, Prangthip Hansanti, John Hoffman, Semarley Jarrett, Kaushik Ram Sadagopan, Dirk Rowe, Shannon Spruit, Chau Tran, Pierre Andrews, Necip Fazil Ayan, Shruti Bhosale, Sergey Edunov, Angela Fan, Cynthia Gao, Vedanuj Goswami, Francisco Guzmán, Philipp Koehn, Alexandre Mourachko, Christophe Ropers, Safiyyah Saleem, Holger Schwenk, and Jeff Wang. No language left behind: Scaling human-centered machine translation, 2022.
- Ogunayo Ogundepo, Tajuddeen R. Gwadabe, Clara E. Rivera, Jonathan H. Clark, Sebastian Ruder, David Ifeoluwa Adelani, Bonaventure F. P. Dossou, Abdou Aziz DIOP, Claytone Sikasote, Gilles Hacheme, Happy Buzaaba, Ignatius Ezeani, Rooweither Mabuya, Salomey Osei, Chris Emezue, Albert Njoroge Kahira, Shamsuddeen H. Muhammad, Akintunde Oladipo, Abraham Toluwase Owodunni, Atnafu Lambebo Tonja, Iyanuoluwa Shode, Akari Asai, Tunde Oluwaseyi Ajayi, Clemencia Siro, Steven Arthur, Mofetoluwa Adeyemi, Orevaoghene Ahia, Aremu Anuoluwapo, Oyinkansola Awosan, Chiamaka Chukwuneke, Bernard Opoku, Awokoya Ayodele, Verrah Otiende, Christine Mwase, Boyd Sinkala, Andre Niyongabo Rubungo, Daniel A. Ajisafe, Emeka Felix Onwuegbuzia, Habib Mbow, Emile Niyomutabazi, Eunice Mukonde, Falalu Ibrahim Lawan, Ibrahim Said Ahmad, Jesujoba O. Alabi, Martin Namukombo, Mbonu Chinedu, Mofya Phiri, Neo Putini, Ndumiso Mngoma, Priscilla A. Amuok, Ruqayya Nasir Iro, and Sonia Adhiambo. Afriqa: Cross-lingual open-retrieval question answering for african languages, 2023.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Gray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In Alice H. Oh,

- Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL <https://openreview.net/forum?id=TG8KACxEON>.
- Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. SQuAD: 100,000+ questions for machine comprehension of text. In Jian Su, Kevin Duh, and Xavier Carreras (eds.), *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 2383–2392, Austin, Texas, November 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1264. URL <https://aclanthology.org/D16-1264>.
- Nathaniel Robinson, Perez Ogayo, David R. Mortensen, and Graham Neubig. ChatGPT MT: Competitive for high- (but not low-) resource languages. In Philipp Koehn, Barry Haddow, Tom Kocmi, and Christof Monz (eds.), *Proceedings of the Eighth Conference on Machine Translation*, pp. 392–418, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.wmt-1.40. URL <https://aclanthology.org/2023.wmt-1.40>.
- Sebastian Ruder, J. Clark, Alexander Gutkin, Mihir Kale, Min Ma, Massimo Nicosia, Shruti Rijhwani, Parker Riley, Jean Michel A. Sarr, Xinyi Wang, John Wieting, Nitish Gupta, Anna Katanova, Christo Kirov, Dana L. Dickinson, Brian Roark, Bidisha Samanta, Connie Tao, David Ifeoluwa Adelani, Vera Axelrod, Isaac Caswell, Colin Cherry, Dan Garrette, R. Reeve Ingle, Melvin Johnson, Dmitry Panteleev, and Partha Pratim Talukdar. Xtreme-up: A user-centric scarce-data benchmark for under-represented languages. *ArXiv*, abs/2305.11938, 2023. URL <https://api.semanticscholar.org/CorpusID:258833298>.
- Victor Sanh, Albert Webson, Colin Raffel, Stephen Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Arun Raja, Manan Dey, M Saiful Bari, Canwen Xu, Urmish Thakker, Shanya Sharma Sharma, Eliza Szczechla, Taewoon Kim, Gunjan Chhablani, Nihal Nayak, Debajyoti Datta, Jonathan Chang, Mike Tian-Jian Jiang, Han Wang, Matteo Manica, Sheng Shen, Zheng Xin Yong, Harshit Pandey, Rachel Bawden, Thomas Wang, Trishala Neeraj, Jos Rozen, Abheesht Sharma, Andrea Santilli, Thibault Fevry, Jason Alan Fries, Ryan Teehan, Teven Le Scao, Stella Biderman, Leo Gao, Thomas Wolf, and Alexander M Rush. Multitask prompted training enables zero-shot task generalization. In *International Conference on Learning Representations*, 2022. URL <https://openreview.net/forum?id=9Vrb9D0WI4>.
- Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, Dipanjan Das, and Jason Wei. Language models are multilingual chain-of-thought reasoners, 2022. URL <https://arxiv.org/abs/2210.03057>.
- Shivalika Singh, Freddie Vargus, Daniel Dsouza, Börje F. Karlsson, Abinaya Mahendiran, Wei-Yin Ko, Herumb Shandilya, Jay Patel, Deividas Mataciunas, Laura OMahony, Mike Zhang, Ramith Hettiarachchi, Joseph Wilson, Marina Machado, Luisa Souza Moura, Dominik Krzemiński, Hakimeh Fadaei, Irem Ergün, Ifeoma Okoh, Aisha Alaagib, Oshan Mudannayake, Zaid Alyafeai, Vu Minh Chien, Sebastian Ruder, Surya Guthikonda, Emad A. Alghamdi, Sebastian Gehrmann, Niklas Muennighoff, Max Bartolo, Julia Kreutzer, Ahmet Üstün, Marzieh Fadaee, and Sara Hooker. Aya dataset: An open-access collection for multilingual instruction tuning, 2024.
- Hugo Touvron, Louis Martin, Kevin R. Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Daniel M. Bikel, Lukas Blecher, Cristian Cantón Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony S. Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel M. Kloumann, A. V. Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, R. Subramanian, Xia Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zhengxu Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models. *ArXiv*, abs/2307.09288, 2023. URL <https://api.semanticscholar.org/CorpusID:259950998>.

- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In Tal Linzen, Grzegorz Chrupała, and Afra Alishahi (eds.), *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 353–355, Brussels, Belgium, November 2018. Association for Computational Linguistics. doi: 10.18653/v1/W18-5446. URL <https://aclanthology.org/W18-5446>.
- Jason Wei, Maarten Bosma, Vincent Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V Le. Finetuned language models are zero-shot learners. In *International Conference on Learning Representations*, 2022. URL <https://openreview.net/forum?id=gEZrGCozdqR>.
- Linting Xue, Noah Constant, Adam Roberts, Mihir Kale, Rami Al-Rfou, Aditya Siddhant, Aditya Barua, and Colin Raffel. mT5: A massively multilingual pre-trained text-to-text transformer. In Kristina Toutanova, Anna Rumshisky, Luke Zettlemoyer, Dilek Hakkani-Tur, Iz Beltagy, Steven Bethard, Ryan Cotterell, Tanmoy Chakraborty, and Yichao Zhou (eds.), *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 483–498, Online, June 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.naacl-main.41. URL <https://aclanthology.org/2021.naacl-main.41>.
- Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, 2019.
- Shengyu Zhang, Linfeng Dong, Xiaoya Li, Sen Zhang, Xiaofei Sun, Shuhe Wang, Jiwei Li, Runyi Hu, Tianwei Zhang, Fei Wu, and Guoyin Wang. Instruction tuning for large language models: A survey, 2023.
- Wenhao Zhu, Yunzhe Lv, Qingxiu Dong, Fei Yuan, Jingjing Xu, Shujian Huang, Lingpeng Kong, Jiajun Chen, and Lei Li. Extrapolating large language models to non-english by aligning languages, 2023.
- Ahmet Üstün, Viraat Aryabumi, Zheng-Xin Yong, Wei-Yin Ko, Daniel D’souza, Gbemileke Onilude, Neel Bhandari, Shivalika Singh, Hui-Lee Ooi, Amr Kayid, Freddie Vargus, Phil Blunsom, Shayne Longpre, Niklas Muennighoff, Marzieh Fadaee, Julia Kreutzer, and Sara Hooker. Aya model: An instruction finetuned open-access multilingual language model, 2024.

## A Languages covered in the evaluation

Table 11 shows the languages and tasks we evaluated on.

## B Verbalizer for Prompted response

For MASAKHANEWS , we concatenated the “news headline” and “article body” for prompting. We also make use of a simple **verbalizer** since GPT-4 can produce other words related to the categories as predictions. This only applies to two categories: “business” and “entertainment” as shown below:

```
business: [business, finance, economy, economics],
entertainment: [entertainment, music],
health: [health],
politics: [politics],
religion: [religion],
sports: [sports],
technology: [technology]
```

For SIB-200 , we design a simple prompt that instructs the model to select from a list of options which best describes the provided sentence. We also make use of a simple **verbalizer** since LLMs can produce other words related to the categories as predictions. This only applies to three categories: “entertainment”, “politics” and “science/technology” as shown below:



Language	Family/branch	Region	Script	No. of speakers	Evaluation tasks				Generation			No. of tasks	
					NewsClass	Sentiment	NER	TopicClass	QA	MT	Summ		
Hausa (hau)	Afro-Asiatic / Chadic	West Africa	Latin	77M	✓	✓	✓	✓	✓	✓	✓	7	
Amharic (amh)	Afro-Asiatic / Ethio-Semitic	East Africa	Ge'ez	57M	✓	✓	✓	✓	✓	✓	✓	6	
Oromo (orm)	Afro-Asiatic / Cushitic	East Africa	Latin	37M	✓	✓	✓	✓	✓	✓	✓	3	
Somali (som)	Afro-Asiatic / Cushitic	East Africa	Latin	22M	✓	✓	✓	✓	✓	✓	✓	3	
Tigrinya (tig)	Afro-Asiatic / Ethio-Semitic	East Africa	Ge'ez	9M	✓	✓	✓	✓	✓	✓	✓	3	
Moroccan Arabic (ary)	Afro-Asiatic / Semitic	North Africa	Arabic	29M	✓	✓	✓	✓	✓	✓	✓	2	
Tunisian Arabic (aeb)	Afro-Asiatic / Semitic	North Africa	Arabic	12M	✓	✓	✓	✓	✓	✓	✓	1	
Algerian Arabic (arq)	Afro-Asiatic / Semitic	North Africa	Arabic	36M	✓	✓	✓	✓	✓	✓	✓	1	
Egyptian Arabic (arz)	Afro-Asiatic / Semitic	North Africa	Arabic	41M	✓	✓	✓	✓	✓	✓	✓	1	
Kabyle (kab)	Afro-Asiatic / Berber	North Africa	Arabic	3M	✓	✓	✓	✓	✓	✓	✓	1	
Tamasheq (taq)	Afro-Asiatic / Berber	East Africa	Latin	1M	✓	✓	✓	✓	✓	✓	✓	1	
Tamazight (tzm)	Afro-Asiatic / Berber	East Africa	Latin	-	✓	✓	✓	✓	✓	✓	✓	1	
Kiswahili (swa)	Niger-Congo / Bantu	East & Central Africa	Latin	71M-106M	✓	✓	✓	✓	✓	✓	✓	7	
Yorubá (yor)	Niger-Congo / Volta-Niger	West Africa	Latin	46M	✓	✓	✓	✓	✓	✓	✓	7	
Igbo (ibo)	Niger-Congo / Volta-Niger	West Africa	Latin	31M	✓	✓	✓	✓	✓	✓	✓	7	
Kinyarwanda (kin)	Niger-Congo / Bantu	East Africa	Latin	10M	✓	✓	✓	✓	✓	✓	✓	5	
Twi (twi)	Niger-Congo / Kwa	West Africa	Latin	9M	✓	✓	✓	✓	✓	✓	✓	5	
chiShona (sna)	Atlantic-Congo / Bantu	Southern Africa	Latin	11M	✓	✓	✓	✓	✓	✓	✓	4	
isiXhosa (xho)	Atlantic-Congo / Bantu	Southern Africa	Latin	19M	✓	✓	✓	✓	✓	✓	✓	4	
isiZulu (zul)	Atlantic-Congo / Bantu	Southern Africa	Latin	27M	✓	✓	✓	✓	✓	✓	✓	4	
Wolof (wol)	Atlantic-Congo / Senegambia	West Africa	Latin	5M	✓	✓	✓	✓	✓	✓	✓	4	
Luganda (lug)	Atlantic-Congo / Bantu	Central Africa	Latin	11M	✓	✓	✓	✓	✓	✓	✓	4	
Setswana (tsn)	Atlantic-Congo / Bantu	Southern Africa	Latin	14M	✓	✓	✓	✓	✓	✓	✓	3	
Chichewa (nya)	Atlantic-Congo / Bantu	South-East Africa	Latin	14M	✓	✓	✓	✓	✓	✓	✓	3	
Fon (fon)	Atlantic-Congo / Volta-Niger	West Africa	Latin	14M	✓	✓	✓	✓	✓	✓	✓	3	
Mossi (mos)	Atlantic-Congo / Gur	West Africa	Latin	8M	✓	✓	✓	✓	✓	✓	✓	3	
Éwé (ewe)	Atlantic-Congo / Kwa	West Africa	Latin	7M	✓	✓	✓	✓	✓	✓	✓	3	
Rundi (run)	Atlantic-Congo / Bantu	East Africa	Latin	11M	✓	✓	✓	✓	✓	✓	✓	3	
Xitsonga (tso)	Atlantic-Congo / Bantu	Southern Africa	Latin	7M	✓	✓	✓	✓	✓	✓	✓	2	
Bemba (bem)	Atlantic-Congo / Bantu	South, East & Central	Latin	4M	✓	✓	✓	✓	✓	✓	✓	2	
Lingala (lin)	Atlantic-Congo / Bantu	Central Africa	Latin	40M	✓	✓	✓	✓	✓	✓	✓	2	
Ghomlá' (bbj)	Atlantic-Congo / Grassfields	Central Africa	Latin	1M	✓	✓	✓	✓	✓	✓	✓	2	
Swati (ssw)	Atlantic-Congo / Bantu	Southern Africa	Latin	1M	✓	✓	✓	✓	✓	✓	✓	1	
Umbundu (umb)	Atlantic-Congo / Bantu	Southern Africa	Latin	7M	✓	✓	✓	✓	✓	✓	✓	1	
Tumbuka (tum)	Atlantic-Congo / Bantu	South & East Africa	Latin	2M	✓	✓	✓	✓	✓	✓	✓	1	
Chokwe (ckj)	Atlantic-Congo / Bantu	South & Central	Latin	1M	✓	✓	✓	✓	✓	✓	✓	1	
Kikongo (kon)	Atlantic-Congo / Bantu	South & Central	Latin	5M	✓	✓	✓	✓	✓	✓	✓	1	
Kamba (kam)	Atlantic-Congo / Bantu	East Africa	Latin	5M	✓	✓	✓	✓	✓	✓	✓	1	
Kikuyu (kik)	Atlantic-Congo / Bantu	East Africa	Latin	8M	✓	✓	✓	✓	✓	✓	✓	1	
Luba-Kasai (lua)	Atlantic-Congo / Bantu	Central Africa	Latin	6M	✓	✓	✓	✓	✓	✓	✓	1	
Sango (sag)	Atlantic-Congo / Ubangian	Central Africa	Latin	5M	✓	✓	✓	✓	✓	✓	✓	1	
Akan (aka)	Atlantic-Congo / Tano	West Africa	Latin	10M	✓	✓	✓	✓	✓	✓	✓	1	
Kabiye (kbp)	Atlantic-Congo / Gur	West Africa	Latin	1M	✓	✓	✓	✓	✓	✓	✓	1	
Nigerian Fulfulde (fuv)	Atlantic-Congo / Senegambia	West Africa	Latin	15M	✓	✓	✓	✓	✓	✓	✓	1	
Kimbundu (kmb)	Atlantic-Congo / Bantu	Southern Africa	Latin	2M	✓	✓	✓	✓	✓	✓	✓	1	
Northern Sotho (nso)	Atlantic-Congo / Bantu	Southern Africa	Latin	4M	✓	✓	✓	✓	✓	✓	✓	1	
Southern Sotho (sot)	Atlantic-Congo / Bantu	Southern Africa	Latin	7M	✓	✓	✓	✓	✓	✓	✓	1	
Luo (luo)	Nilo-Saharan	East Africa	Latin	4M	✓	✓	✓	✓	✓	✓	✓	2	
Kanuri (knc)	Nilo-Saharan	West/Central Africa	Latin	10M	✓	✓	✓	✓	✓	✓	✓	1	
Kanuri (knc)	Nilo-Saharan	West/Central Africa	Arabic	10M	✓	✓	✓	✓	✓	✓	✓	1	
Dinka (dik)	Nilo-Saharan	Central Africa	Latin	4M	✓	✓	✓	✓	✓	✓	✓	1	
Neur (rus)	Nilo-Saharan	Central Africa	Latin	2M	✓	✓	✓	✓	✓	✓	✓	1	
Bambara (bam)	Mande	West Africa	Latin	14M	✓	✓	✓	✓	✓	✓	✓	3	
Dyula (dyu)	Mande	West Africa	Latin	3M	✓	✓	✓	✓	✓	✓	✓	1	
N'Ko (nqo)	Mande	West Africa	Latin	-	✓	✓	✓	✓	✓	✓	✓	1	
Malagasy (plt)	Austronesian	Southern Africa	Latin	25M	✓	✓	✓	✓	✓	✓	✓	1	
Afrikaans (afr)	Indo-European	Southern Africa	Latin	7M	✓	✓	✓	✓	✓	✓	✓	1	
Naija (pcm)	English Creole	West Africa	Latin	121M	✓	✓	✓	✓	✓	✓	✓	5	
Languages/task					16	13	20	56	10	20	10		

Table 11: **Languages covered in each of our evaluation tasks:** language family, region, script, number of L1 & L2 speakers, and check marks (✓) for the tasks evaluated on per language. The evaluation dataset are based on MASAKHANEWS , SIB-200 , AFRISENTI , MASAKHANER -X, AFRIQA , XL-SUM and MAFAND-MT .

```

entertainment: [entertainment, music],
health: [health],
politics: [politics, world politics],
travel: [travel],
sports: [sports],
geography: [geography],
science/technology: [technology, tech, science and
technology, science/technology, science technology]

```

For MASAKHANER , we first define what named entity entails in this context, then, we provide a *one shot example* that describes how the output should be presented and constrained the model to return only the output.

For AFRIQA , we designed a QA prompt inspired by Langchain prompts<sup>7</sup>. The prompt attempts to constrain the model responses to the least possible words, prevents it from returning responses not included in the context and from repeating the question. Additionally, we expect the answer to be in a *pivot language* which is either English or French depending on the language, *Context* is the passage from which the answer should be retrieved (in the pivot language) and *Question* is question intended to be answered by the model, the question is provided in the evaluated language.

<sup>7</sup><https://github.com/langchain-ai/langchain>

Dataset	No. of Sentences Evaluated	No. of Languages
MASAKHANEWS	6025	16
SIB-200	11628	56
AFRISENTI	34321	14
MASAKHANER -X	29901	20
AFRIQA	3560	9
MAFAND-MT	24201	16
XL-SUM	19410	10

Table 12: **Dataset Breakdown** We breakdown the total number of sentences we evaluated for each task and the number of languages covered.

For XL-SUM , the prompt designed simple instructs the model to summarize the provided article in the *pivot language*—the language the sentence is in.

For MAFAND-MT dataset for machine translation, the prompt designed simply instructs the model to translate the provided sentence to the target language. Similar to AFRIQA , we provide the *pivot language*—the language the sentence is in, *TGT*—the target language to be translated into, and *Sentence* is a sentence to be translated.

## C Dataset per task

We use the dataset in the split as provided by the authors. We provide the breakdown of number of sentences we perform evaluations on per task Table 12

## D SIB-200 results

Table 13 provides the breakdown of the topic classification results by languages for SIB-200 .

Language	Language code	Language Family	Script	AfroXLMR76L	GPT-4	Aya	mT0	mT0-MT
Tunisian Arabic	aeb_Arab	Afro-Asiatic	Arab	<b>86.8</b>	73.9	50.49	45.16	37.41
Afrikaans	afr_Latn	Indo-European	Latn	<b>91.1</b>	68.6	50.59	49.32	40.83
Akan	aka_Latn	Atlantic-Congo	Latn	<b>79.8</b>	35.0	41.84	46.38	36.21
Amharic	amh_Ethi	Afro-Asiatic	Ethi	<b>87.1</b>	58.8	51.66	48.21	38.15
Moroccan Arabic	ary_Arab	Afro-Asiatic	Arab	<b>88.0</b>	73.3	52.18	50.8	35.99
Egyptian Arabic	arz_Arab	Afro-Asiatic	Arab	<b>88.8</b>	81.1	51.83	48.74	34.51
Bambara	bam_Latn	Mande	Latn	<b>70.9</b>	17.2	30.92	46.22	37.83
Bemba	bem_Latn	Atlantic-Congo	Latn	<b>83.6</b>	25.6	42.78	39.46	27.19
Chokwe	cjk_Latn	Atlantic-Congo	Latn	<b>63.5</b>	8.2	33.47	32.03	23.46
Southwestern Dinka	dik_Latn	Nilotic	Latn	<b>66.4</b>	14.9	21.21	28.76	19.04
Dyula	dyu_Latn	Mande	Latn	<b>57.3</b>	9.3	28.26	35.15	24.89
Ewe	ewe_Latn	Atlantic-Congo	Latn	<b>78.7</b>	12.2	36.95	31.61	23.19
Fon	fon_Latn	Atlantic-Congo	Latn	<b>68.5</b>	10.8	27.81	43.06	31.87
Nigerian Fulfulde	fuv_Latn	Atlantic-Congo	Latn	<b>70.0</b>	13.4	30.88	31.95	24.12
West Central Oromo	gaz_Latn	Afro-Asiatic	Latn	<b>77.5</b>	18.4	44.09	38.29	28.15
Hausa	hau_Latn	Afro-Asiatic	Latn	<b>84.8</b>	45.1	50.23	49.7	39.11
Igbo	ibo_Latn	Atlantic-Congo	Latn	<b>82.5</b>	38.4	51.21	48.45	34.1
Kabyle	kab_Latn	Afro-Asiatic	Latn	<b>53.0</b>	8.0	16.42	17.32	14.98
Kamba	kam_Latn	Atlantic-Congo	Latn	<b>67.7</b>	18.7	35.04	35.2	23.43
Kabiye	kbp_Latn	Atlantic-Congo	Latn	<b>70.7</b>	9.3	26.45	26.67	20.31
Central Kanuri (Arabic script)	knc_Arab	Nilotic	Arab	46.4	<b>48.8</b>	19.68	14.57	11.08
Central Kanuri (Latin script)	knc_Latn	Nilotic	Latn	<b>63.0</b>	28.6	30.24	33.72	22.58
Kikuyu	kik_Latn	Atlantic-Congo	Latn	<b>80.3</b>	50.5	31.62	47.46	33.35
Kinyarwanda	kin_Latn	Atlantic-Congo	Latn	<b>86.6</b>	11.2	53.33	46.07	40.68
Kimbundu	kmb_Latn	Atlantic-Congo	Latn	<b>66.6</b>	1.8	31.21	31.53	23.94
Kikongo	kon_Latn	Atlantic-Congo	Latn	<b>82.0</b>	12.0	40.75	43.15	27.04
Lingala	lin_Latn	Atlantic-Congo	Latn	<b>86.4</b>	23.5	44.91	49.36	36.49
Luba-Kasai	lua_Latn	Atlantic-Congo	Latn	<b>73.1</b>	26.0	38.05	38.13	33.97
Ganda	lug_Latn	Atlantic-Congo	Latn	<b>73.8</b>	17.9	40.96	51.31	35.42
Luo	luo_Latn	Nilotic	Latn	<b>77.8</b>	29.6	33.2	34.27	23.18
Mossi	mos_Latn	Atlantic-Congo	Latn	<b>71.1</b>	14.4	23.9	29.59	22.86
Nko	nqo_Nkoo	Atlantic-Congo	Latn	<b>22.0</b>	7.5	6.0	6.45	2.71
Northern Sotho	nso_Latn	Atlantic-Congo	Latn	<b>83.3</b>	3.6	50.53	48.05	38.9
Nuer	nus_Latn	Nilotic	Latn	<b>64.5</b>	42.7	19.02	19.06	15.79
Nyanja	nya_Latn	Atlantic-Congo	Latn	<b>83.9</b>	7.2	48.48	48.26	37.07
Plateau Malagasy	plt_Latn	Austronesian	Latn	<b>88.1</b>	45.7	51.46	48.07	39.22
Rundi	run_Latn	Atlantic-Congo	Latn	<b>83.5</b>	46.1	49.96	47.1	39.88
Sango	sag_Latn	Atlantic-Congo	Latn	<b>66.5</b>	33.1	35.38	37.29	23.93
Shona	sna_Latn	Atlantic-Congo	Latn	<b>82.8</b>	9.4	53.26	50.45	38.01
Somali	som_Latn	Afro-Asiatic	Latn	<b>80.8</b>	37.2	56.0	48.25	35.15
Southern Sotho	sot_Latn	Atlantic-Congo	Latn	<b>83.5</b>	58.3	50.38	48.98	38.39
Swati	ssw_Latn	Atlantic-Congo	Latn	<b>81.3</b>	43.2	48.39	44.27	36.4
Swahili	swh_Latn	Atlantic-Congo	Latn	<b>88.5</b>	30.3	51.96	50.44	38.63
Tamasheq (Latin script)	taq_Latn	Afro-Asiatic	Latn	60.3	<b>71.6</b>	26.6	27.76	20.93
Tamasheq (Tifinagh script)	taq_Tfng	Afro-Asiatic	Tfng	<b>25.7</b>	17.7	16.22	10.18	8.21
Tigrinya	tir_Ethi	Afro-Asiatic	Ethi	<b>79.8</b>	3.3	51.42	45.81	38.0
Tswana	tsn_Latn	Atlantic-Congo	Latn	<b>81.9</b>	37.1	50.49	49.9	40.44
Tsonga	tso_Latn	Atlantic-Congo	Latn	<b>82.5</b>	42.8	42.53	45.39	38.81
Tumbuka	tum_Latn	Atlantic-Congo	Latn	<b>87.6</b>	29.4	49.44	48.51	39.96
Twi	twi_Latn	Atlantic-Congo	Latn	<b>80.2</b>	32.6	45.87	46.2	35.5
Central Atlas Tamazight	tzm_Tfng	Afro-Asiatic	Tfng	26.7	<b>34.6</b>	18.68	17.32	15.6
Umbundu	umb_Latn	Atlantic-Congo	Latn	<b>68.5</b>	1.1	30.06	32.58	23.88
Wolof	wol_Latn	Atlantic-Congo	Latn	<b>73.3</b>	7.7	32.74	44.36	34.9
Xhosa	xho_Latn	Atlantic-Congo	Latn	<b>84.0</b>	24.1	51.32	48.91	38.03
Yoruba	yor_Latn	Atlantic-Congo	Latn	<b>78.8</b>	48.2	50.8	47.94	32.62
Zulu	zul_Latn	Atlantic-Congo	Latn	<b>85.8</b>	40.5	51.42	48.09	38.53
<b>Average</b>				<b>74.1</b>	39.3	39.7	30.3	29.6

Table 13: **SIB-News Classification Results:** We compare the F1-score of various LLMs’ results with that of the current state of the art result obtained from Adelani et al. (2023). Best results per language are in bold.