HotStuff-2 vs. HotStuff: The Difference and Advantage

Siyuan Zhao, Yanqi Wu, Zheng Wang*

Shanghai Jiao Tong University

{zsy123,prphrl27,wzheng}@sjtu.edu.cn

Abstract

Byzantine consensus protocols are essential in blockchain technology. The widely recognized HotStuff protocol uses cryptographic measures for efficient view changes and reduced communication complexity. Recently, the main authors of HotStuff introduced an advanced iteration named HotStuff-2. This paper aims to compare the principles and analyze the effectiveness of both protocols, hoping to depict their key differences and assess the potential enhancements offered by HotStuff-2.

Keywords: HotStuff, Byzantine Consensus Protocol, Blockchain

1 Introduction: HotStuff and HotStuff-2

1.1 The HotStuff Consensus Protocol

The consensus process of HotStuff [1] protocol is illustrated in Figure 1, where the protocol segregates the entire consensus mechanism into four distinct phases: prepare, pre-commit, commit, and decide. In a network comprising n consensus nodes and f Byzantine nodes, with the condition that $n \ge 3f + 1$, the operational procedure for each phase in HotStuff adheres to a consistent pattern. The leader node aggregates n - f votes from the preceding round to create a Quorum Certificate (QC), then broadcasts this QC. Subsequently, each consensus node casts

^{*}Corresponding author



Figure 1: The Consensus Process of HotStuff

a vote on the received QC and forwards it to the leader node. The HotStuff consensus protocol ensures liveness through its Pacemaker mechanism, which facilitates automatic view changes via a timeout strategy, thus preventing any liveness impairment. Meanwhile, the safety of Hot-Stuff is secured by its SafeNode rule. When compared with the classical PBFT [2] protocol, HotStuff's principal enhancements are as follows:

1. Linear and Effortless View Changes. HotStuff distinguishes itself with a streamlined communication approach, where the interaction is primarily between the consensus nodes and the leader, rather than the all-to-all broadcast paradigm employed in PBFT. This modification curtails the communication complexity from $O(n^2)$, as seen in PBFT, to a generally linear scale. Additionally, HotStuff ingeniously treats messages pertaining to new-view changes as regular consensus messages. This means that, upon collecting n - f new-view messages, the leader will discontinue the current consensus and initiate the prepare phase of the subsequent round. This approach avoids the extra cost in PBFT, where each consensus node must send a new-view message containing n - f messages from the previous round to the leader, generating significant overhead.

2. Optimistic Responsiveness. Based on a partially synchronous network model, HotStuff incorporates a feature known as optimistic responsiveness. This characteristic implies that after Global Stabilization Time (GST) [3], any non-Byzantine leader node can effectively drive the consensus process forward simply by gathering n - f votes, without necessitating additional delays. This property is consistently maintained even in case of view changes. Such optimistic responsiveness sharply contrasts with the approach taken by the Tendermint [4] consensus pro-



Figure 2: The Consensus Process of HotStuff-2

tocol. In Tendermint, there is a compulsory waiting delay following a view change, which is implemented to safeguard the protocol's safety. However, this will influence the consensus process, because the protocol must pause for this fixed duration before proceeding. This makes HotStuff more effective during view change, without affecting its security.

1.2 The HotStuff-2 Consensus Protocol

HotStuff-2 [5], an advancement of the original HotStuff protocol, is visualized in Figure 2. This method streamlines the consensus process by reducing one voting round, thus cutting down cryptographic cost while preserving linear view changes and optimistic responsiveness. Introducing the happy-path concept, HotStuff-2 employs two-phase voting under favorable conditions with non-Byzantine sequential leader nodes. This innovation ensures efficiency and security across various network scenarios, optimizing performance in ideal conditions.

When faced with deteriorating network conditions or the emergence of Byzantine leader nodes, HotStuff-2 safeguards its safety and liveness via the Pacemaker mechanism. In these situations, frequent view change is common, leading to differences in view height of nodes. To address this, the Pacemaker activates a view synchronization waiting mechanism for all nonleader nodes that are lagging. This mechanism requires these nodes to pause and wait for the leader to broadcast the proposal carrying the latest view. Once received, the nodes update their local state and subsequently reboot the two-phase voting consensus process. This ensures that all nodes remain synchronized and actively participate in the consensus, preserving the security and liveness of the protocol.

In summary, HotStuff-2 demonstrates adaptive behavior contingent on network conditions

First Stage:	First Stage:
As leader:	As leader:
wait for new-view messages	wait for new-view messages
create proposal	create proposal
broadcast proposal	broadcast proposal
As replica:	As replica:
wait for proposal	wait for proposal
verify proposal	verify proposal
	check and update local view
send vote	send vote
Second Stage:	Second Stage:
As leader:	As leader:
wait for votes	wait for votes
create QC	create QC
update preparedQC	update preparedQC
broadcast QC	broadcast QC
As replica:	As replica:
wait for OC	wait for OC
verify OC	verify OC
	check and update local view
update preparedOC	update preparedOC
send vote	send vote
bond tooo	bona roco
Third Stage:	Third Stage:
As leader:	As leader:
wait for votes	wait for votes
create OC	create OC
update lockedOC	update lockedOC
broadcast OC	broadcast OC
As replica:	As replica:
wait for OC	wait for OC
verify OC	verify OC
VCIIIY QO	check and undate local view
update lockedOC	update lockedOC
send vote	
Fourth Stage:	
As leader:	
wait for votes	
create OC	
update commitoc	
broadcast OC	
As replice:	
wait for OC	
wart for QC	
verity QC	
apparte committyc	and wate
Sella Vole	Sella VOLE

Figure 3: Pseudo-code Comparison between HotStuff and HotStuff-2

and the characteristics of the leader nodes. It strategically incorporates a δ time delay in scenarios with malicious leaders to ensure protocol security. During happy-path states, characterized by favorable conditions and non-Byzantine leaders, HotStuff-2 efficiently executes two-phase voting. This nuanced approach greatly boosts HotStuff-2's performance, marking a substantial optimization compared to the original HotStuff protocol.

Consensus	Consensus	Byzantine	Communication	View Switch
Parameter	Nodes	Nodes	Delay	Delay
HotStuff	v	v	v	
HotStuff-2	✓	✓	✓	✓

Table 1: Consensus Parameters Comparison between HotStuff and HotStuff-2

2 Comparing HotStuff and HotStuff-2

Figure 3 provides a pseudo-code comparison between the HotStuff and HotStuff-2 protocols, offering a visual representation of the variations in code volume between them. This comparison effectively illustrates the streamlined approach of HotStuff-2. Furthermore, Table 1 presents a comparison of the consensus parameters for both protocols, highlighting various factors that contribute to the efficiency of the consensus process. Overall, HotStuff-2, in its evolution from the original HotStuff, incorporates key modifications, which primarily include:

- HotStuff-2 simplifies the consensus process. HotStuff-2 optimizes the consensus process by reducing one voting phase, enhancing efficiency compared to the original Hot-Stuff's three rounds.
- 2. HotStuff-2 introduces view synchronization waiting mechanism. This is activated when nodes are not in sync, employing a timeout feature to align their views, thereby ensuring cohesive progression in the consensus process.

Due to these modifications, theoretically, HotStuff-2 holds two potential advantages over the HotStuff protocol: 1) HotStuff-2 is simpler and easier to implement; and 2) In scenarios where view synchronization isn't necessary, HotStuff-2 exhibits superior operational efficiency.

3 Experiments

To investigate the distinctions in design and performance between HotStuff and HotStuff-2, we execute a series of experimental analyses. These experiments are conducted using Python 3.9.7 to implement both protocols, on a system equipped with Windows 11. In the experimental setup, we simulate multiple consensus nodes within a single process, utilizing a hash table to simulate the public key signing and verification process. In addition, we integrate a basic

Communication Delay	10s	1s	0.1s	0.01s	0.001s	0.0001s
HotStuff	400.37s	40.49s	4.33s	0.62s	0.61s	0.59s
HotStuff-2	300.25s	30.34s	3.26s	0.47s	0.45s	0.43s

Table 2: Influence of Communication Delay on Efficiency

Table 3: Influence of Consensus Node Numbers on Efficiency

Consensus Node	13	22	31	40	49	58	67	76	85	94	103
HotStuff	4.33s	4.38s	4.36s	4.37s	4.37s	4.38s	4.38s	4.40s	4.42s	4.43s	4.44s
HotStuff-2	3.25s	3.28s	3.28s	3.28s	3.29s	3.29s	3.29s	3.28s	3.30s	3.31s	3.31s

communication delay function to simulate the communication delay between nodes. We assess the efficiency of each consensus protocol by measuring the process run time over a consistent number of consensus rounds, specifically across 10 iterations. This methodical approach allows for a comparative analysis of the two protocols under controlled and replicable conditions, highlighting their respective efficiencies and operational differences.

3.1 Influence of Communication Delay

Initially, we fix the consensus node number n = 13 and the Byzantine node number f = 4, satisfying the $n \ge 3f + 1$ condition required for BFT consensus protocols. Moreover, we set the view switch delay for HotStuff-2 at 0.5 seconds and communication delays ranging from 10 to 0.0001 seconds.

As shown in Table 2, HotStuff-2 consistently surpasses HotStuff in efficiency across various communication delays. This may due to HotStuff-2's fewer voting rounds, which reduce communication and cryptographic cost, especially in scenarios with fewer Byzantine nodes.

3.2 Influence of Consensus Node Number

In this experiment, we configure the consensus nodes number n increasing from 13 to 103, in intervals of 9. Correspondingly, we maintain the number of Byzantine nodes at one-fourth of the total nodes, ensuring adherence to the $n \ge 3f + 1$ consensus condition. Furthermore, we establish the communication delay at 0.1 seconds and set the view switch delay specific to

Byzantine Node	4	9	14	19	24	29	34
HotStuff	4.42s	4.43s	4.43s	4.45s	4.45s	4.46s	4.48s
HotStuff-2	3.45s	3.63s	4.01s	4.39s	4.85s	5.21s	6.03s

Table 4: Influence of Byzantine Node Numbers on Efficiency (n = 103)

HotStuff-2 at 0.5 seconds.

As shown in Table 3, HotStuff-2 consistently surpasses HotStuff in efficiency, with increasing the consensus node number. This trend emphasizes the enhanced scalability of HotStuff-2 due to streamlined design and protocol optimizations, improving performance in larger network environments.

3.3 Influence of Byzantine Node Numbers

Initially, we fix the consensus nodes number n = 103 and set the Byzantine node number f increasing from 0 to 34 in increments of 5, thereby always satisfying the $n \ge 3f + 1$ consensus condition. Subsequently, we set the communication delay to 0.1 seconds and the HotStuff-2 view change delay to 0.5 seconds.

As shown in Table 4 and Figure 4, HotStuff-2 is more effective than HotStuff when the number of Byzantine nodes is low. However, as the number of Byzantine nodes approaches one-fifth of the total nodes, HotStuff shows higher efficiency. This suggests that the efficiency of HotStuff-2 is contingent upon the rate of Byzantine nodes in the network, as it is more stable and faster in scenarios with lower rate of Byzantine nodes. Conversely, with a larger rate of Byzantine nodes, the frequent need for view change incurs considerable additional cost.

4 Conclusion

This study presents a comparative analysis of two well-known Byzantine consensus protocol: HotStuff, and its enhanced iteration, HotStuff-2. To facilitate this comparison, we implement both protocols within the same framework and conduct a series of experimental evaluations. Our findings highlight two primary advantages of HotStuff-2 over the original HotStuff: 1) HotStuff-2 exhibits a more compact code, which translates to ease of implementation; and 2) HotStuff-2 shows superior operational efficiency, particularly in network environments with



Figure 4: Comparison of Consensus Efficiency Under Different Numbers of Byzantine Nodes

a lower rate of Byzantine nodes. These advantages underscore HotStuff-2's advancements in both usability and performance within the realm of Byzantine consensus protocols.

References

- Maofan Yin, Dahlia Malkhi, Michael K Reiter, Guy Golan Gueta, and Ittai Abraham. Hotstuff: Bft consensus with linearity and responsiveness. In *Proceedings of the 2019 ACM Symposium on Principles of Distributed Computing*, pages 347–356, 2019.
- [2] Miguel Castro, Barbara Liskov, et al. Practical byzantine fault tolerance. In *OsDI*, pages 173–186, 1999.
- [3] Cynthia Dwork, Nancy Lynch, and Larry Stockmeyer. Consensus in the presence of partial synchrony. *Journal of the ACM (JACM)*, 35(2):288–323, 1988.
- [4] Ethan Buchman. *Tendermint: Byzantine fault tolerance in the age of blockchains*. PhD thesis, University of Guelph, 2016.

[5] Dahlia Malkhi and Kartik Nayak. Hotstuff-2: Optimal two-phase responsive bft. *Cryptology ePrint Archive*, 2023.