

Opportunistic Sensor-Based Multi-Factor Authentication in and for the Internet of Things

Marc Saideh, Jean-Paul Jamont, Laurent Vercouter

Abstract—Communication between connected objects often requires secure and reliable authentication mechanisms. These mechanisms are essential for verifying the identities of objects and preventing unauthorized access. The IoT offers several advantages and opportunities that are not necessarily found in other domains. For instance, IoT sensors collect real-time data about their environment and other objects which contain valuable information that, if used, can reinforce authentication. In this paper, we propose a novel idea for building opportunistic sensor-based authentication factors between IoT objects by leveraging the sensors already present in the systems where they interact. We claim that sensors can be utilized to build factors that reinforce object-to-object authentication mechanisms. Through the integration of these opportunistic sensor-based authentication factors into multi-factor authentication mechanisms, authentication in IoT can achieve a higher level of security. We provide illustrative experiments on two types of vehicles : mobile robots and cars.

Index Terms—Internet of Things, Sensors, Security, Multi-Factor Authentication, Machine-to-Machine Authentication.

I. INTRODUCTION

THE Internet of Things (IoT) is a network of connected objects, such as devices, vehicles, and various other types of objects that are often embedded with sensors and actuators. This allows them to collect and exchange data with each other and with other systems. Communication between IoT objects requires strong security and privacy measures. Authentication, which is the process of verifying the identity of an entity, plays a crucial role in the secure interaction of IoT devices. Ensuring that communication occurs between the correct entities is essential, particularly in situations like object-to-object communication where it is often essential to confirm the identities of both objects before any exchange of information or interaction. This verification prevents unauthorized access to sensitive data and resources while ensuring the involved objects are who they claim to be.

Over the last decade, there has been a significant amount of research work conducted to identify security challenges within the IoT and exploring methods to protect against attacks [1], [2]. Authentication is then a well recognized issue that is given big importance to ensure the global security in the IoT domain. Without robust authentication mechanisms, there exists a significant risk of unauthorized access to IoT networks

[1], attackers could impersonate other objects, eavesdrop sensitive information and destroy trust relations between objects. Authentication protocols have evolved over time to reduce these risks, including mechanisms that are password-based and advanced biometrics. Multi-factor authentication, which includes the use of several factors in order to verify an entity, has been increasingly adopted [3]. However, despite these advancements, authentication continues to be a significant challenge in IoT. The distributed architecture of IoT systems and lightweight constraints make it difficult to implement traditional centralized authentication models effectively. Thus, new adaptable ways of authentication are needed to meet the needs of the constantly changing and varied IoT environment. This is crucial as attackers are constantly trying to find new ways to bypass authentication and gain unauthorized access to systems [1].

In this paper, we propose a novel idea to build opportunistic sensor-based authentication factors between IoT objects to be used in multi-factor authentication mechanisms. IoT provides us with various advantages that we can use to reinforce authentication. For example, data captured by sensors deployed within IoT systems can be used and analysed to help identify other IoT objects. These sensors, capturing different types of data, constantly collect valuable information about the surrounding environment and the behavior of other IoT objects. We propose utilizing the sensors already present in the systems where the IoT objects interact to build these authentication factors. Hence, the objective of this paper is to show the benefits of opportunistically leveraging sensor information for object-to-object authentication. Through the integration of these opportunistic sensor-based authentication factors into multi-factor authentication mechanisms, authentication in IoT can achieve a higher level of security.

The rest of this paper is organized as follows: Section II provides a background of relevant authentication methods in IoT that have been used so far, as well as different types of authentication factors, while section III explains the proposed idea and provides an illustrative scenario. Next, in section IV we present the illustrative experiments conducted to demonstrate the proposed idea. At the end, V provides a conclusion over the obtained results with some challenges and some hints for future work.

II. BACKGROUND AND RELATED WORK

For an entity (human or machine) to prove its identity, it must provide evidence showing that they are who they claim to be. These proofs are called authentication factors. They refer to the methods or characteristics used to verify the identity

This work is supported by the French National Research Agency (ANR) by the project MaestrIoT ANR-21-CE23-0016.

Marc Saideh is with Normandie Univ, INSA Rouen, LITIS, St Etienne Du Rouvray, France (email: marc.saideh@insa-rouen.fr).

Jean-Paul Jamont is with LCIS, Univ. Grenoble Alpes Valence, France (email: jean-paul.jamont@univ-grenoble-alpes.fr).

Laurent Vercouter is with Normandie Univ, INSA Rouen, LITIS, St Etienne Du Rouvray, France (email: laurent.vercouter@insa-rouen.fr).

of an entity. Authentication factors are usually categorized in three groups [3]: knowledge factor (something the user knows, such as a password), possession factor (something the user has, such as a security token) and inherent factor (something the user is, such as a fingerprint).

In addition to understanding the different types of authentication factors, several approaches have been proposed to reinforce authentication mechanisms, especially in the IoT. In [4], the authors proposed a methodology to choose the best authentication factors based on trustworthy values for factors, as well as the context, security and risk. In [5], an authentication method that takes into account the context of the environment in which the devices are being authenticated is proposed. Location-based authentication [6] involves using the entity's location, such as GPS coordinates, to verify their identity. Building a signature of entities involves using patterns about the entities to authenticate them. These patterns can be built based on behavioral or physical factors. The authors in [7] conducted a survey on behavioral biometrics for continuous user authentication in IoT and showed how biometric data such as touchscreen dynamics, eye movements, and others can help strengthen authentication mechanisms. While these studies focused on context-aware authentication and behavioral or physical signature authentication factors, the majority of them were conducted to user authentication. To our knowledge, there has been limited research conducted on behavioral or physical-based signatures for object-to-object authentication.

III. OPPORTUNISTIC SENSOR-BASED AUTHENTICATION IN THE IOT

A. Concept of opportunistic sensor-based authentication

Opportunistic sensor-based factors means taking advantage of the potential presented by the deployed sensors in an unplanned way. For example, consider an authentication system in an IoT environment that normally relies on two factors to validate identities. Building upon this idea, we can explore a novel approach that also opportunistically utilizes the available sensors within the environment to build additional authentication factors. This transformation of sensor-data into authentication factors enables a new level of authentication.

Existing systems in IoT environments offer us several valuable information that can be used to strengthen authentication mechanisms. By leveraging these systems in a System of Systems approach, we take advantage of their deployed sensors and the information they provide. These existing deployed sensors capture various types of data such as motion, color, noise or environmental conditions such as temperature and other types of data. By utilizing them and the information they collect, we get the opportunity to authenticate IoT objects with additional factors, making the authentication process more robust. This approach takes advantage of the available information collected by sensors opportunistically, without the need for additional dedicated setups. In addition, the use of this kind of information can often be done without the need of direct communication between objects. For example, analyzing the motion of an object to verify its identity does not require any additional communication between that object and the object

verifying its identity. On one hand, opportunistic sensor-based factors increases the flexibility of the authentication process, while also building a set of physical and behavioral factors associated with objects. On the other hand, this flexibility introduces an element of unpredictability, making it more challenging for attackers to predict the authentication factors that will be used.

B. Illustrative scenario

By illustrating this scenario, we aim to highlight the feasibility and effectiveness of leveraging existing systems and sensor data in the authentication process. The scenario is about a private parking with access control, where only authorized vehicles are allowed to enter. Thus, the verification process of a vehicle is done at the entry of the parking to decide whether the vehicle should be allowed to enter or not. In the parking, there are three systems that have been deployed, each for specific functionalities. The following provides a description of the three existing systems:

System 1: Barrier management system. The barrier of the parking is managed by using a Radio Frequency Identification (RFID) scanner. Each authorized vehicle is equipped with an RFID tag that is scanned at the entry to verify its identity.

System 2: Surveillance system. This system includes multiple features designed for effective monitoring and enhanced security measures. The most important part of the system is the strategically placed cameras that capture and record images and video footage of different areas of the parking, which enables real-time monitoring of the parking. This system ensures the overall security and safety of the parking.

System 3: Acoustic monitoring system. This system includes microphones that are placed in specific places of the parking, as well as techniques like signal processing to analyze the recorded sounds and identify specific types of sounds or frequencies associated with alarms or other events to ensure the security of the parking by analyzing abnormal patterns of sounds that may indicate an incident, aggression...

In this scenario, the objective of our proposed idea is to reinforce the security of the authentication of the vehicles by utilizing the existing systems and the perceived information through their embedded sensors. This can be done by building a new system while taking advantage of the existing ones, or by updating an existing system.

C. Utilizing existing systems

Acoustic monitoring system: Microphones. Beside the applications where the audio sounds might be used, we want to use them to reinforce the authentication process of vehicles at the parking entrance. The captured sounds by microphones include the engine noise of vehicles. For that, we use the microphones that are placed at the parking entrance to analyze the captured sound while the vehicle wait to enter the parking. The idea is to help in identifying the vehicles based on their engine sound without having a large trained data set of different engine sounds. For that, supposing that we already have at least one known engine sound of each authorized vehicle, each time an authorized vehicle requests

to enter the parking by scanning its RFID tag, its engine sound that will be recorded at the entrance will be compared with its known engine sound. If there is a similarity between both sounds, we consider that the sound factor is validated. In case the authentication is validated, the recorded sound can be added to the known sound to be used in comparison for next times. However, if there is a significant difference between the two sounds, we can use this as a relevant indicator that the vehicle at the parking entrance might be an attacker that is trying to access the parking.

Surveillance system: Cameras. As discussed previously, we want to use the data, initially captured for surveillance purposes, to reinforce the authentication process of the authorized vehicles at the parking entrance. There exists several information that we can capture about a vehicle from an image of it. However, for illustrating purposes and to show the significance of information and its potential in authentication, we have chosen to utilize the color histogram of the image captured when the vehicle is present as a feature for authentication. While color alone may not be an entirely distinct attribute, it can play an important role in detecting significant variations, especially if a potentially malicious vehicle differs significantly in color.

IV. EXPERIMENTS

Considering conditions similar to the described illustrative scenario, we evaluate here the capacity of these existing IoT systems to reinforce the authentication process by creating signatures of the vehicles entering the parking, even by using simple processing methods. We take advantage of, a camera from the surveillance system and a microphone from the acoustic monitoring system. We propose using the information perceived by these sensors to build signatures about the vehicles, that act as an additional authentication level.

A. Methods

1) *Measuring the similarity of engine sounds:* To do the comparison between two engine sounds, we were satisfied with employing a simple but effective signal processing method. However, our objective is not to propose the optimal signal processing method to our problem but rather to demonstrate the feasibility of the proposed mechanism, which means the capability of identifying vehicles based on their engine sound. We used the spectral centroid feature (equation 1) to determine if two engine sounds are similar or not. It provides the average frequency or the center of mass of a sound spectrum:

$$SpectralCentroid = \frac{\sum f(n)M(n)}{\sum M(n)} \quad (1)$$

where $M(n)$ represents the magnitude, or weighted frequency value of bin number n , and $f(n)$ represents the center frequency at bin n .

With this feature, to find the similarity or dissimilarity between two signals, we calculate the spectral centroid of each signal separately, then we calculate the mean of each spectral

centroid before calculating the Euclidean distance function between the two means (equation 2):

$$distance = \sqrt{\sum (\overline{SC1} - \overline{SC2})^2} \quad (2)$$

where $\overline{SC1}$ and $\overline{SC2}$ are respectively the mean of the first spectral centroid and the mean of the second spectral centroid. As the distance increases in significance, the dissimilarity between two signals grows, while a distance close to 0 indicates greater similarity.

2) *Measuring the similarity of vehicle pictures:* In our experiments, a series of vehicle images were captured against a consistent background, and the background was then removed to isolate the vehicles. To compare vehicles pictures, color histograms were generated from these isolated vehicle images, which represent the distribution of colors of each vehicle. This comparison allows us to determine whether or not the two pictures contain the same distribution of color data. The objective is to compare these color histograms to help in determining if two vehicle images represent the same vehicle or not. To do this, we calculate the Bhattacharyya distance between two normalized color histograms (equation 3 and 4):

$$D_B(P, Q) = -\ln(BC(P, Q)) \quad (3)$$

$$BC(P, Q) = \sum_x \sqrt{P(x)Q(x)} \quad (4)$$

where BC represents the Bhattacharyya coefficient, and P and Q are the normalized color histograms of the two vehicle images. BC measures the similarity between the two histograms. A coefficient of 0 indicates that the histograms are identical, while higher values indicate greater dissimilarity.

B. Environments

The experiments were done on two different types of vehicles : cars and mobile robots, and in two different environments : indoor environment for the mobile robots, where it is calm and there is not a lot of noise when recording the engines sounds, and outdoor environment for the cars, where there is much more noise. The engines sounds were recorded from several distances from the vehicles to get realistic data and to detect if small distances can make big difference in the comparison. Tests were repeated on several samples of different duration. For example, one test was done on samples of 5 seconds, another one was done on samples of 2 seconds and another one on 1 second samples. Regarding the second test, we captured multiple pictures of each vehicle, varying the camera angle slightly for each shot.

C. Results

	Robot 1	Robot 2	Car 1	Car 2	Car 3	Car 4
Robot 1	43.6	467.8	951.3	1078.4	980.5	720.8
Robot 2	467.8	38.5	514.3	635.5	422.8	290.5
Car 1	951.3	514.3	17.2	131.1	76.6	223.9
Car 2	1078.4	635.5	131.1	16.8	110.7	343.4
Car 3	980.5	422.8	76.6	110.7	72.3	280.4
Car 4	720.8	290.5	223.9	343.4	280.4	17.9

TABLE I: Average distance between all the spectral centroids

1) *Engine sounds*: The conducted experiments resulted a 100% accuracy between the robots (indoor), and a 89% accuracy between the cars (outdoor), utilizing a fixed similarity score threshold of 100. Noting that the outdoor environment contains a significant amount of noise. Table I represents a symmetric distance matrix that shows the average distance between all spectral centroids for all the tested vehicles (robots and cars). The diagonal elements of the matrix represent the average distances between different spectral centroid samples of the same vehicle, while the off-diagonal elements represent the distances between the other vehicles. From the table, we can observe one false positive in the average distance between samples from Car 1 and Car 3 is below 100, as indicated in bold and red. However, it is evident that the average distance between spectral centroids of different vehicles is significantly greater than that between multiple spectral centroid samples from the same vehicle. We can see that all the diagonal elements were under the fixed threshold, as indicated in bold and black. This helps explain the favorable results and demonstrates the potential for using such information to in authentication purposes.

	Robot 1	Robot 2	Car 1	Car 2	Car 3	Car 4
Robot 1	0.038	0.31	-	-	-	-
Robot 2	0.31	0.042	-	-	-	-
Car 1	-	-	0.069	0.222	0.382	0.376
Car 2	-	-	0.222	0.145	0.342	0.348
Car 3	-	-	0.382	0.342	0.224	0.382
Car 4	-	-	0.376	0.348	0.382	0.165

TABLE II: Average distance between the color histograms

2) *Color histograms*: The conducted experiments resulted a 93.7% accuracy when comparing color histograms of several samples for each car, utilizing a fixed similarity score threshold of 0.2. For the robots, a 100% accuracy was achieved. Three of the four chosen cars for this experiment were selected to have similar color characteristics, minimizing potential bias in the results. Similar to the previous table, Table II presents a symmetric distance matrix illustrating the average distance between all color histograms for all the tested vehicles. We can observe that the average distance between color histograms of different vehicles is significantly greater than the average distance between color histograms of different picture samples from the same vehicle, often exceeding twice the value. The only false negative result is observed in Car 3 in bold and red, where the average distance exceeds the fixed threshold. This can be explained due to the fact that several shots were taken of each vehicle while changing the angle slightly each time.

V. DISCUSSION AND CONCLUSION

This study presented a novel idea of building opportunistic authentication factors in the IoT domain. The conducted experiments show the potential of utilizing data from existing sensors to build new relevant authentication factors. Integrating these new factors into an authentication process increases its reliability. The results obtained from our illustrative experiments showed that with simple methods, we were able to illustrate the effectiveness of utilizing existing sensors, such as cameras and microphones, to build new factors in

authentication mechanisms. This validates the integration of these two new factors with the existing authentication factors (RFID in the scenario) to create a MFA system. In recent research in IoT authentication, various approaches explored the use of distinct factors to enhance security. For instance, some studies have explored the use of Physical Unclonable Functions (PUFs) [8] which rely on unique physical properties of hardware components to generate cryptographic keys. This suggests the potential for extending these findings to other types of sensors. Therefore, the development of an opportunistic authentication method is relevant and holds substantial potential. Moreover, our experiments with sensor data from two environments showed context-dependence, with indoor results outperforming outdoor ones. Hence, an authentication mechanism must take into account the evaluation of the relevance of each factor. Existing systems may not have been initially designed for authentication purposes, but they provide an opportunity for enhancement. Adapting them to various contexts is crucial, and it is important to evaluate their effectiveness. On the other hand, opportunistic sensor-based authentication would provide a large set of factors and thus increase flexibility and security which make it harder for attackers to predict which factors that will be used. For that, exploring power consumption linked to each authentication factor is crucial to help optimize the selection and usage of factors in the IoT. Future research can address several challenges such as extending the proposed approach to diverse sensor types, considering the cost of factors, the context of data gathering and the stake associated to an authentication. These studies will not only contribute to advancing authentication mechanisms in IoT systems but also provide a comprehensive and rigorous validation of the proposed idea presented in this paper.

REFERENCES

- [1] F. Meneghello, M. Calore, D. Zucchetto, M. Polese, and A. Zanella, "IoT: Internet of threats? a survey of practical security vulnerabilities in real iot devices," *IEEE IoT Journal*, vol. 6, no. 5, pp. 8182–8201, 2019.
- [2] L. Babun, K. Denney, Z. B. Celik, P. McDaniel, and A. S. Uluagac, "A survey on iot platforms: Communication, security, and privacy perspectives," *Computer Networks*, vol. 192, p. 108040, 2021.
- [3] A. Ometov, S. Bezzateev, N. Mäkitalo, S. Andreev, T. Mikkonen, and Y. Koucheryavy, "Multi-factor authentication: A survey," *Cryptography*, vol. 2, no. 1, p. 1, 2018.
- [4] D. Dasgupta, A. Roy, and A. Nag, "Toward the design of adaptive selection strategies for multi-factor authentication," *computers & security*, vol. 63, pp. 85–116, 2016.
- [5] M. Miettinen, T. D. Nguyen, A.-R. Sadeghi, and N. Asokan, "Revisiting context-based authentication in iot," in *Proceedings of the 55th Annual Design Automation Conference*, 2018, pp. 1–6.
- [6] F. Zhang, A. Kondoro, and S. Muftic, "Location-based authentication and authorization using smart phones," in *11th Int. Conf. on Trust, Security and Privacy in Computing and Communications*. IEEE, 2012, pp. 1285–1292.
- [7] Y. Liang, S. Samtani, B. Guo, and Z. Yu, "Behavioral biometrics for continuous authentication in the iot era: An artificial intelligence perspective," *IEEE IoT Journal*, vol. 7, no. 9, pp. 9128–9143, 2020.
- [8] P. Mall, R. Amin, A. K. Das, M. T. Leung, and K.-K. R. Choo, "Puf-based authentication and key agreement protocols for iot, wsns, and smart grids: a comprehensive survey," *IEEE IoT Journal*, vol. 9, no. 11, pp. 8205–8228, 2022.