Kaibo Liu liukb@pku.edu.cn Peking University Beijing, China

Jie M. Zhang jie.zhang@kcl.ac.uk King's College London London, United Kingdom

> Ge Li lige@pku.edu.cn Peking University Beijing, China

# ABSTRACT

Conventional automated test generation tools struggle to generate test oracles and tricky bug-revealing test inputs. Large Language Models (LLMs) can be prompted to produce test inputs and oracles for a program directly, but the precision of the tests can be very low for complex scenarios (only 6.3% based on our experiments). To fill this gap, this paper proposes AID, which combines LLMs with differential testing to generate fault-revealing test inputs and oracles targeting plausibly correct programs (i.e., programs that have passed all the existing tests). In particular, AID selects test inputs that yield diverse outputs on a set of program variants generated by LLMs, then constructs the test oracle based on the outputs. We evaluate AID on two large-scale datasets with tricky bugs: TrickyBugs and EvalPlus, and compare it with three state-of-the-art baselines. The evaluation results show that the recall, precision, and F1 score of AID outperform the state-of-the-art by up to 1.80×, 2.65×, and 1.66×, respectively.

## **CCS CONCEPTS**

- Software and its engineering  $\rightarrow$  Software testing and debugging.

## **KEYWORDS**

Test automation, Test oracle, Large Language Model

#### **ACM Reference Format:**

Kaibo Liu, Yiyang Liu, Zhenpeng Chen, Jie M. Zhang, Yudong Han, Yun Ma, Ge Li, and Gang Huang. 2024. LLM-Powered Test Case Generation for Detecting Tricky Bugs. In . ACM, New York, NY, USA, 11 pages. https: //doi.org/XXXXXXXXXXXXXXXXX

Conference'24, April 2024, Washington, DC, USA

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 978-1-4503-XXXX-X/18/06 https://doi.org/XXXXXXXXXXXXXXXX

Yiyang Liu ptr1479@stu.pku.edu.cn Peking University Beijing, China

Yudong Han hanyd@pku.edu.cn Peking University Beijing, China

> Gang Huang hg@pku.edu.cn Peking University Beijing, China

## **1 INTRODUCTION**

Bug detection in software systems has always been a challenging problem within software engineering, which is becoming more crucial with the prevalence of automatically generated code from generative AI. Software testing is a widely adopted method of detecting bugs in programs [23]. If a program fails on a test case, that test case explicitly identifies a defect within the program. If a program passes all existing test cases, the program is referred to as a *plausibly correct program*, which may still contain tricky bugs that are challenging to detect [18].

Zhenpeng Chen

zp.chen@ucl.ac.uk

Nanyang Technological University

Singapore

Yun Ma

mayun@pku.edu.cn

Peking University Beijing, China

Automated test generation techniques aim to generate test cases automatically [3, 7]. Nevertheless, conventional automated test generation methods struggle to generate test oracles (more details in Section 5). A primary challenge for these methods is that program specifications are typically expressed in natural languages, which can be ambiguous and complex to parse automatically to derive test oracles. Recent studies have revealed the potential of Large Language Models (LLMs) in the field of automated test generation [9, 15, 31, 35, 37], due to the strong natural language understanding capabilities of LLMs, offering hope for automating the generation of test oracles.

However, our preliminary experiments show that when we use the program under test (PUT) and corresponding specification as prompts to request ChatGPT (a state-of-the-art LLM) to generate defect-identifying test cases directly, *the precision can be as low as 6.3%*. In other words, if the PUT fails on a test case generated by ChatGPT, in 93.7% of the cases, it is due to errors of the test case itself (*e.g.*, either the test oracle is incorrect or the test input is illegal). Our further study reveals that 92.2% out of the 93.7% cases are due to incorrect test oracles. This is because although ChatGPT has powerful natural language understanding capabilities to capture the specification, it falls short in accurate reasoning and precise computation [11, 33], which are also crucial for test oracle generation.

**Approach:** In this paper, we propose AID, an **automated test case generation** method designed for tricky bug detection in plausibly correct programs. AID combines LLMs and differential testing to accurately accomplish the task of generating both test inputs and

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

test oracles. The basic framework of AID consists of three steps: *program variants generation, input generation,* and *differential testing*. In the first two steps, we use LLMs to generate a certain number of program variants and test inputs. In the third step, we continually attempt to feed a generated test input to both the PUT and program variants, searching for inconsistencies in program outputs.

Our preliminary experiments indicate that naive prompts with LLMs are not applicable due to : O Poor correctness of the generated program variants. LLMs can generate correct programs with simple tasks based solely on specifications [5], but when we request LLMs to generate more complex programs (e.g., competition programs), the correctness tends to be poor, with a large probability of introducing incorrect variants, affecting the effectiveness of differential testing. **2** Poor correctness of the generated test inputs. LLMs are able to generate legal test inputs with a simple format (e.g., the legal input may be specified as two integers), but can fail to generate inputs subjected to certain constraints (e.g., a square matrix with every row of the matrix being monotonically increasing). Our experiments show that if we request LLM to generate test inputs directly according to the specified input constraints, the average illegal test input ratio is 40.1%. An illegal test input makes no contribution to discovering bugs because the behavior of the program is undefined in such situations. Even worse, illegal test inputs could also lead to *false positives*, meaning that a test case with illegal input might cause a correctly functioning program to fail.

To tackle the challenges above, we propose the following three solutions in AID:

• PUT-guided program generation. AID provides not only the specification but also the program under test (PUT) in the prompt, and then requests LLMs to examine the PUT and generate a repaired program if necessary. AID then uses existing test cases to filter out program variants that do not pass these tests. In this way, AID makes full use of the effective information of the specification, the PUT, and the existing test cases.

**②** Generator-based input generation. AID does not use the LLMs to generate test inputs directly; instead, AID utilizes the LLMs to generate an input generator (*e.g.*, a Python script) based on the input constraints. This approach is inspired by the program-aided model method [11]. Generating code with LLMs separates logic and computation, thereby mitigating the limitations in LLM's reasoning and computational capabilities.

**③ Priority in diversity in differential testing.** The generated program variants by LLMs are likely to have similar defects as the PUT. To address this problem, we do not adopt the commonly used majority voting principle (*i.e.*, the most frequent output is considered correct) to determine the correctness of test outputs during the differential testing phase. Instead, we propose a counterintuitive approach that prioritizes the diversity of test outputs when determining test oracles.

**Evaluation:** We use Trickybugs [2, 18] and EvalPlus [16] to evaluate the effectiveness of AID. These two datasets contain humanwritten and AI-generated buggy programs that are failed to be detected by the default test suite (a.k.a. plausibly correct programs), respectively. For Trickybugs, we consider both C++ and Python programs, while EvalPlus comprises only Python programs.

We compare AID with three state-of-the-art baselines: CHAT, DPP [15], and APR. The evaluation results show that the test cases generated by AID achieve the best recall, precision, and F1 score, outperforming the best baseline by up to **1.80**×, **2.65**×, and **1.66**×, respectively. In particular, AID achieves F1 scores of 41.3%, 42.35%, and 51.34% for Trickbugs (C++), Trickybugs (Python), and EvalPlus, outperforming the state-of-the-art method, which achieves only 24.71%, 34.90%, and 35.76% for these datasets, respectively. With two program variants, AID's precision is 69.91%, 78.95%, and 85.09% respectively, while the state-of-the-art method's precision is only 26.37%, 40 79%, and 53.54%. Our ablation study also shows that each component of AID contributes to its final performance.

**Contribution:** To summarize, this paper makes the following contributions:

- A novel LLM-powered test oracle generation approach. We propose AID, combining LLM and differential testing for test case generation for detecting tricky bugs. AID includes three components: PUT-guided program generation, generator-based input generation, and diversity-first differential testing. AID fully utilizes the effective information of the specification, the PUT, and the existing test cases.
- An extensive evaluation. We use 366 plausible programs from competition-level coding tasks and 151 plausible programs from basic coding tasks for evaluation. To our knowledge, our evaluation is the most comprehensive in the literature to date. The evaluation results show that AID achieves the best recall, precision, and F1 score, outperforming the state-of-the-art by up to 1.80×, 2.65×, and 1.66×.
- A replication package. We have made our code and data publicly available<sup>1</sup> to facilitate replication and future improvement.

The remainder of this paper is organized as follows. Section 2 formally defines the targeted problem and defines a category of test cases. Section 3 describes each component of AID in detail. Section 4 proposes our research questions and conducts a comprehensive evaluation to answer them. Section 5 summarizes the relevant work. Section 6 discusses the threats to validity, followed by concluding remarks in Section 7.

#### 2 PRELIMINARIES

In this section, we formally define the problem of defect-finding test case generation and create a category for test cases.

## 2.1 **Problem Definition**

Here we present a formal definition of the problem of generating defect-identifying test cases for plausible programs. Given a program specification *S*, it corresponds to a mapping *f* from the input space *I* to the output space *O*. Given any input  $in \in I$ , the output (test oracle) of a correctly implemented program is out = f(in). For a program under test (PUT) intended to implement this specification, the task of defect-identifying test case generation is to discover a trigger input  $in_t$  along with its corresponding test oracle  $f(in_t)$ , forming the pair  $(in_t, f(in_t))$ , such that the program's output  $PUT(in_t) \neq f(in_t)$ .

<sup>&</sup>lt;sup>1</sup>https://anonymous.4open.science/r/AID/

Specification PROBLEM DESCRIPTION Give three numbers A, B and C, determine whether (A,B,C) is a permutation of (5,7,5). INPUT CONSTRAINTS: 1≤A,B,C≤10 Existing Test Suite Correct Program INPUT L = list(map(int,input().split())) 577 No PASS L.sort() 557 Yes mhers [5,5,7] PASS 567 No orint('YES 755 Yes Defect-identifying Buggy plausible Program Test Case L = list(map(int,input().split()))
print('YES' if L.sum()==17 else 'NO PASS 'NO') FAIL 548 No

Figure 1: A motivating example.

In particular, if there exists a set of test cases known as the existing test suite  $T_0$ , where  $T_0$  is composed of multiple input and output pairs  $(in_j, out_j)$ , and if there is a program  $P_0$  that passes all the test cases in this test suite  $T_0$  (*i.e.*,  $\forall j, P_0(in_j) = out_j$ ),  $P_0$  is referred to as a **plausibly correct program** (a.k.a. **plausible program**) relative to  $T_0$ . Finding defects within such a plausible program  $P_0$  is often a more challenging task because they are non-trivial and tricky, most of which being logic corner cases [13, 18, 26, 36].

Two points need to be noted in our definition. First, specifications often exist in the form of natural language in practical software development, and the corresponding mapping f is often hard to define explicitly. Second, the definition is relatively simplified, focusing solely on the program's functional behavior, *i.e.*, its output under specified conditions, while overlooking non-functional behavior such as runtime efficiency and memory consumption. This simplification effectively emphasizes the functional correctness of the program, which is precisely the problem targeted in this paper.

Figure 1 shows an example. The specification requires a program that determines if the array formed by the three input integers is a permutation of (5,5,7). The logic of the first program is correct: directly sorting the array and then comparing it with (5,5,7). However, the logic of the second program is flawed. This program only checks if the sum of the three inputs equals 17, which is a necessary but not sufficient condition. Unfortunately, the logical error in the second program cannot be detected by the existing test suite. The second program passes all the test cases of the existing test suite but is still buggy, so we call it a **buggy plausible program**. The goal of our test generation method is to generate a test case that identifies the defects of such programs. As shown in the example in the bottom-left corner of the figure, such a defect-identifying test case must first be valid, meaning the test input is legal, the test oracle is correct, so any correct program should pass this test case. Secondly, this test case should cause the buggy program to fail, thereby successfully identifying the defect within the program.

## 2.2 Category of Test Cases

Based on the problem definition, we define a category of test cases: **①** Test cases that correctly identify a defect ( $T_c$ ). For any

 $t = (in, out) \in T_c$ , we have f(in) = out and  $PUT(in) \neq out$ . This is

exactly the test case we want, which effectively identifies a defect in PUT.

**②** Test cases with right test oracles but do not identify any **defect** ( $T_r$ ). For any  $t = (in, out) \in T_r$ , we have f(in) = out and PUT(in) = out. Test cases of this kind are trivial, neither positively nor negatively significant for defect identification.

**③** Test cases with wrong test oracles  $(T_w)$ . For any  $t = (in, out) \in T_w$ , we have  $f(in) \neq out$ . These test cases are erroneous. They may lead to *false negative*, where PUT(in) = out but  $PUT(in) \neq f(in)$ . They may also lead to *false positive*, where  $PUT(in) \neq out$  but PUT(in) = f(in). False positives are more detrimental than false negatives because false positives can undermine the credibility and practicality of the entire method.

**O** Test cases with illegal input  $(T_{ill})$ . For any  $t = (in, out) \in T_{ill}$ , we have  $in \notin input$  space *I*. These test cases are erroneous. For any illegal test input, no test oracle exists, and all program behaviors are undefined. These test cases might also lead to false positives.

Any test case should fall into one of the above four categories. Here, we have not taken into account other program behaviors outside of program output, such as timeouts or crashes, because we focus on identifying the functional defects within plausible programs, and other behaviors fall outside the scope of this work.

For convenience, we define two additional types of test cases: We define **passed test cases**  $(T_p)$ . For any  $t = (in, out) \in T_p$ , we have PUT(in) = out. A passed test case t could belong to  $T_r$ ,  $T_w$ , or  $T_{ill}$ . Then we define **failed test cases**  $(T_f)$ . For any  $t = (in, out) \in T_f$ , we have  $PUT(in) \neq out$ . A failed test case t could belong to  $T_c$ ,  $T_w$ , or  $T_{ill}$ .

#### 3 METHODOLOGY

The overall framework of AID is illustrated in Figure 2. AID takes the PUT, the existing test suite  $T_e$ , and the specification S as input, and the output is a test case (in, out).

The workflow of AID can be divided into three steps: program variants generation, test input generation, and differential testing. The following subsections will detail these steps respectively.

#### 3.1 **Program Variants Generation**

The first step of AID is generating program variants of the PUT, which are subsequently used in differential testing. AID employs **PUT-guided program generation** in this step. As illustrated in Figure 3, AID provides both the **program specification** and the **PUT** to the LLM, prompting it to determine if defects exist in the PUT according to the specification. If the LLM thinks a defect exists, then the LLM is requested to repair it and produce a repaired version of the program. This repaired version serves as our desired program variant.

The advantage of PUT-guided program generation lies in effectively utilizing the useful information in the program specification and the PUT. As the PUT is a plausible program, it inherently possesses a certain degree of correctness (at least, the behaviors of the plausible programs are correct across the input scope of all existing test cases). Generating program variants based on the PUT yields higher correctness compared to generating variants directly from Conference'24, April 2024, Washington, DC, USA



Specification

Figure 2: Overview of AID.

#### \*\*INSTRCUTION\*\*:

You are a professional coding competition participant, skilled at identifying bugs and logic flaws in code. You will receive a description of a coding problem, and a piece of code attempting to solve the problem. Your task is to find whether there is any bug or logic flaw in the code, if any, please repair the code. Please reply with ONLY the COMPLETE REPAIRED CODE (rather than code fragments) without any other content.

# \*\*PROBLEM DESCRIPTION\*\*: {The specification of the coding task}

# \*\*CODE\*\*: {Source code of PUT}

Figure 3: Prompt for generating program variants.

the specification, and this approach is less likely to introduce new defects. We will substantiate this viewpoint in Section 4.7

It is crucial to ensure that the program variants do not introduce new defects, as the correctness of these program variants during the subsequent differential testing process plays a pivotal role in constructing the test oracle. To achieve this goal, we also employ the existing test suite  $T_e$  to filter the generated program variants: only those program variants that have successfully passed all test cases of  $T_e$  are utilized in the subsequent step of differential testing. This filtering step effectively utilizes the useful information of existing test cases.

#### 3.2 Test Input Generation

The second step of AID involves the generation of test inputs, which are employed in the following differential testing step. The most significant challenge in this step is to ensure the legality of the generated test inputs. Only when the test input is legal can the discrepancy in the outputs of different program variants in the differential testing step identify a functional defect.

AID uses **generator-based input generation** in this step. AID requests LLM to create a random test input generator, then produces test inputs by executing the generator. In our approach, we specify the generator to be a Python script. The prompt used is shown in Figure 4. We can also provide a library for the LLM to use by

\*\*INSTRCUTION\*\*: The following is a description of a coding problem, please write an input generator for this problem (D0 NOT generate outputs). The generated inputs should meet the input constraints of the problem description. Please reply with ONLY the code without any other content. You can use the python library {library name} if necessary, here are some examples of how to use the library, which may be helpful: {Few-shot examples to use the library} \*\*PROBLEM DESCRIPTION\*\*: {The specification of the coding task}

#### Figure 4: Prompt for generating test input generator.

providing few-shot learning examples. LLM can efficiently learn the primary usage of these libraries. The chosen library can easily be adjusted by modifying the prompt.

The generator-based input generation is inspired by the programaided language model (PAL) [11]. LLM lacks coherent, logical reasoning abilities [11, 30, 33], so methods such as chain-of-thoughts [33] are required to guide LLM through multi-step logical thinking. In competition-level coding tasks, a legal input needs to satisfy several constraints, and it is challenging for LLM to solve and obtain a test input that meets all constraints. However, if we request the LLM to translate constraints into code one by one, the code can combine all constraints and produce legal test inputs. In Section 4.7 we will show the advantage of this technique.

Another benefit of employing generator-based input generation is the potential for cost savings. This approach is economical because a random input generator can be generated with minimal usage of tokens and can be reused. Conversely, the direct generation of test inputs by the LLM would result in a token consumption that increases proportionally with the quantity of test inputs generated.

#### 3.3 Differential Testing

The third step of AID is constructing a test oracle through differential testing. Differential testing is a classical and powerful approach employed to uncover semantic defects in programs [8]. Any inconsistency between the programs' behaviors (*e.g.*, the output of the program) based on the same situation (*e.g.*, the same input)

#### Algorithm 1 Diversity-first differential testing

**INPUT:** PUT, Set of program variants  $\mathcal{P}$ , Set of generated inputs  $\mathcal{I}$ **OUTPUT:** Test cases

1:  $testCases \leftarrow \emptyset$ 2: for  $input \in I$  do  $diff \leftarrow \emptyset$ 3:  $output_0 \leftarrow PUT(input)$ 4: for  $P \in \mathcal{P}$  do 5: output  $\leftarrow P(input)$ 6: if  $output \neq output_0$  then 7: Add output to diff 8: 9: end if end for 10: if  $diff \neq \emptyset$  then 11:  $oracle \leftarrow most frequent element in diff$ 12: *test*  $\leftarrow$  (*input*, *oracle*) 13: Add test to testCases 14: end if 15: 16: end for 17: return testCases

indicates a potential bug. It can be used only when multiple implementations with the same intent exist. AID method enables us to conduct differential testing based on a single PUT.

AID compares the outputs of different generated program variants when provided with the same generated test inputs, and any discrepancy indicates a potential defect. The detailed algorithm is shown in Algorithm 1. AID employs **diversity-first differential testing** in this step. If any program variant *P* produces a *output* that is different from the output of PUT *output*<sub>0</sub>, we consider that we identify a defect in PUT and take *output* as the test oracle. If multiple program variants produce outputs different from the *output*<sub>0</sub> with regard to the same input, AID will select the most frequent output as the test oracle.

The diversity-first differential testing algorithm is counterintuitive as developers generally follow the majority voting principle in differential testing. The insight behind this algorithm is that although the program variants obtained in the program generation step rarely introduce new defects, they are likely to suffer the same defect with PUT. Therefore, we place greater trust in program variants that exhibit different behavior from the PUT.

#### **4 EVALUATION**

#### 4.1 Research Questions

We aim to answer the following research questions to evaluate AID: **0** (Finding Defects) RQ1: How effective is AID in generating

defect-identifying test cases for plausible programs?

**②** (Parameter Analysis) RQ2: How does the number of program variants affect the effectiveness of AID?

**③** (Ablation Study) RQ3: How do different components contribute to the effectiveness of AID?

We select gpt-3.5-turbo as our language model for evaluation due to cost considerations. While GPT-4 may offer potentially improved performance, its usage can be prohibitively expensive for our evaluation purposes. By utilizing gpt-3.5-turbo, we strike a balance between performance and cost, allowing us to conduct our evaluation within budget constraints. All experiments are conducted on a Linux server with cores of Intel(R) Xeon(R) CPU E5-2650 2.3GHz and 256GB RAM.

### 4.2 Dataset

We use two datasets for evaluation: TrickyBugs [2, 17] and EvalPlus [16]. The two datasets are used to evaluate AID's ability to detect defects in **human-written** plausible programs and **AI-generated** plausible programs, respectively.

In total, we use 366 human-written competition-level plausible programs and 151 AI-generated basic plausible programs as PUTs for evaluation. *To the best of our knowledge, our experimental scale is the most comprehensive to date.* In comparison, a recent related work [15] uses 40 basic PUTs and 7 competition-level PUTs for evaluation, and they use only Python programs for evaluation, while we consider both C++ and Python, which are the most widely used programming languages in programming competitions [17].

4.2.1 TrickyBugs. The TrickyBugs dataset comprises hundreds of coding tasks sourced from a real coding competition platform, At-Coder, along with thousands of corresponding plausible programs submitted by real human coding competition participants. Despite passing the existing test suite, all these plausible programs contain defects, and the TrickyBugs dataset provides extra test cases that can discover the defects. We use 251 C++ plausible programs and 115 Python plausible programs from TrickyBugs as the PUTs. Each PUT is selected randomly from different coding tasks to avoid the impact of repetitive, similar defects on the evaluation.

4.2.2 EvalPlus. The EvalPlus Dataset is a rigorous evaluation framework for code generation. Similar to TrickyBugs, EvalPlus comprises 164 coding tasks with base test cases and extra test cases. We filtered out programs from the EvalPlus pre-generated LLM code samples [1] to get buggy plausible programs that pass the base test cases but fail the extra test cases. At last, the filtered plausible programs cover 151 coding tasks. Similarly, we randomly selected one plausible program from each coding task as the PUTs.

#### 4.3 Metrics

In this section, we describe the metrics we select. First, we do not care about the passed test cases because these test cases simply repeat the existing behavior of the PUT and almost make no contribution to identifying defects within the PUT.

Therefore, our evaluation focuses on those failed test cases, because only the failed test cases are possible to identify a defect. When a failed test case  $t \in T_f$  is generated, what concerns us is whether there is really a defect: If  $t \in T_c$ , it is good news, as the test case *t* has correctly identified a defect, and we call it a *true positive* (*TP*); However, if  $t \in T_w \cup T_{ill}$ , it is bad news, it is a false alarm due to the error of the test case, and we call it a *false positive* (*FP*).

To determine true positives and false positives, we need to know the corresponding test oracle and legality of a test input. For the former, both TrickyBugs and EvalPlus provide canonical programs for each coding task. We use the canonical programs *CP* as the ground truth mapping f defined in Section 2.1. *i.e.*, For any legal input *inp*  $\in I$ , the corresponding test oracle (test output) is defined

Table 1: (RQ1) The effectiveness of different methods in finding defects for TrickyBugs and EvalPlus. AID achieves the best
evaluation results in terms of recall, precision, and F1 score. Additionally, AID shows a significant improvement compared to
other methods.

	k	TrickyBugs (C++)			,	TrickyBugs (	(Python)		EvalPlus				
		Recall	Precision	F1 score	Recall	Precision	F1 score	Recall	Precision	F1 score			
CHAT	-	3.78	6.31	4.27	3.77	8.85	5.29	1.21	8.28	2.12			
APR	-	16.46	34.58	22.30	10.20	36.64	15.96	41.39	49.97	45.28			
DPP	2	20.96	26.37	23.35	32.54	40.79	36.20	23.36	53.54	32.52			
	4	19.46	32.22	24.27	28.72	46.32	35.46	23.01	61.16	33.45			
	6	17.68	41.60	24.81	26.17	53.03	35.05	22.80	72.71	34.71			
	8	16.31	53.09	24.95	24.41	62.02	35.03	22.55	80.51	35.23			
	10	15.50	60.80	24.71	23.22	70.26	34.90	22.29	90.36	35.76			
AID	2	25.06	69.91	36.90	23.74	78.95	36.51	32.78	85.09	47.33			
	4	27.74	69.69	39.68	27.17	77.81	40.28	35.35	84.41	49.83			
	6	28.65	69.45	40.57	28.69	77.81	41.92	36.32	83.85	50.69			
	8	29.19	69.34	41.09	29.09	77.81	42.35	36.90	83.38	51.16			
	10	29.38	69.57	41.31	29.09	77.81	42.35	37.14	83.14	51.34			
Improvement	Best	80.13% ↑	31.04% ↑	65.57% ↑	10.61%↓	90.76% ↑	16.99% ↑	66.62% ↑	7.99%↓	43.57% ↑			
	Worst	19.56% ↑	165.11% ↑	58.03% ↑	2.24% ↑	12.37% ↑	4.61% ↑	40.33% ↑	58.93% ↑	45.50% ↑			
	Average	55.73% ↑	62.54% ↑	63.44% ↑	2.01% ↑	43.23% ↑	15.16% ↑	56.56% ↑	17.19% ↑	45.83% ↑			

as *CP*(*inp*). For the latter, the legality of the generated inputs is checked manually.

**Precision.** What developers care most is *precision*, which is defined as #TP/(#TP + #FP). The lower the precision, the more false positive test cases a developer need to check before confirming a true defect. This checking process will be very time-consuming and labor-intensive, which goes against the original intention of using automated test generation tools. In summary, precision is the golden metric determining the practicality of test generation methods [19].

**Recall.** Recall is also an important metric for evaluation, which is defined as #TP/(#TP + #FN). Notice that all PUTs in our dataset contain defects, thus all negatives are false negatives, so the number of true positives largely determines the value of recall.

**F1 score.** F1 score is a metric that combines recall and precision, which is defined as  $(2 \times \#TP \times \#TP)/(\#TP + \#FP)$ . Since recall and precision tend to be inversely related, using just one of them does not provide a comprehensive evaluation. The F1 score balances recall and precision, making it a commonly used metric.

### 4.4 Baseline Methods

We choose the following end-to-end methods as baselines to compare the practical performance with AID.

**DirectChatGPT (CHAT).** Recent studies [25, 35, 37] have highlighted the competitive ability of ChatGPT in generating test cases. So this baseline is to prompt ChatGPT to generate a test case  $t_d = (in_d, out_d)$  directly. In this context, ChatGPT is provided with the PUT and specification *S*, then it is required to provide a test input *in<sub>d</sub>* along with its corresponding test oracle *out<sub>d</sub>*. **Differential Prompting Plus (DPP).** The most recent related work is Differential Prompting [15], it is an approach to generating failure-inducing test cases for PUT without specification. Differential Prompting first requests ChatGPT to a) infer a program intention  $S_{inf}$  from the provided PUT, and then b) generate failure-inducing test cases based on the  $S_{inf}$ . To ensure fairness, we omit the step of intention inference and use the original specification *S* as  $S_{inf}$ . In summary, this baseline is an augmented version of Differential Prompting, and hence is termed Differential Prompting Plus (DPP).

DPP also includes three steps: program generation, input generation, and differential testing. However, each step differs from AID. In the first two steps, DPP requires LLM to directly generate programs and inputs. In the third step, DPP employs majority voting to determine the test oracle.

Automated Program Repair (APR). We add an additional baseline, which is not a test generation method but an Automated Program Repair (APR) method. Recent works consider that the state-of-the-art APR methods are LLM-based APR [14, 34], so we use gpt-3.5-turbo to repair PUT by directly providing the LLM with the PUT and the specification, then asking the LLM to reply a repaired program.

In fact, this is the first step of AID. The reason for adding this baseline is to demonstrate that though AID indeed relies on the LLM's APR capability in the first step, the performance of AID does not solely derive from APR methods.

Automated program repair and test generation are both methods for addressing defects in programs. The former aims to directly fix erroneous parts of the code, while the latter seeks to uncover defects in programs through testing.



Figure 5: (RQ1) The distribution of the difficulty of coding tasks. AID is better than DPP in generating test cases for high-difficulty, logically complex programs.

A critical question for APR methods is that *how to discern the correctness of the plausible repair patches*? Actually, it often boils down to manual verification of the correctness of these plausible patches one by one, similar to how programmers manually verify the correctness of failed test cases. In fact, LLM claims that each repaired program is a successful fix, meaning every repaired plausible program is considered positive, but actually, not all are true positives. Some repaired programs may still contain the same defects as the PUT or introduce new defects, which are false positives. With the criteria of false positives and true positives established, we can calculate precision, thereby allowing the APR method to be compared with other test generation methods.

#### 4.5 RQ1: Finding Defects

The evaluation result we care about most is the effectiveness of AID in generating defect-identifying test cases and its comparison to other methods. We evaluate AID and all three baseline methods on both two datasets.

Table 1 shows the overall evaluation result. The second column is the parameter k that denotes the number of generated program variants, which is not applicable to CHAT and APR. The next nine columns are the evaluation results for datasets TrickyBugs (C++), TrickyBugs (Python), and EvalPlus, respectively.

The first two rows show the effectiveness of CHAT and APR. The next five rows show the effectiveness of DPP with k ranging from 2 to 10. Similarly, The next five rows show the effectiveness of AID with different k values.

The last three rows show the improvement of AID compared to DPP, as DPP is the recent state-of-the-art test generation method. We showcase three distinct comparison manners for comprehensive and fair comparison: Best, Worst, and Average. "Best" refers to we select the *k* value with highest F1 score for AID and *DPP*, and compare their recall, precision and F1 score under the selected *k* value. For example, DPP achieves the best F1 score (24.95) for TrickyBugs (C++) when k = 8, and AID achieves the best F1 score (41.31) for TrickyBugs (C++) when k = 10. So the "Best" row compares the recall, precision, and F1 score between DPP with k = 8 and AID with k = 10; Similarly, "Worst" refers to we select the *k* value resulting in the lowest F1 score for comparison. So in this case, we choose the performance of DPP with k = 2 and the performance of AID with

k = 2 to calculate the improvement; "Average" is a straightforward manner that just computes the average value of all k values and uses the average value for comparison.

We first look at the TrickyBugs (C++) dataset. AID (k=10) achieves the best F1 score among all the methods, significantly surpassing that of the second best method DPP. Specifically, regardless of recall, precision, or F1 score, even AID's worst performance exceeds DPP's best performance. Under the "Best", "Worst", and "Average" comparison manners, the F1 score of AID achieves improvements of 65.57%, 58.03%, and 63.44%, respectively. The precision of AID achieves an improvement up to 165.11%. The recall of AID achieves an improvement up to 80.13%.

Then we look at the TrickyBugs (Python) dataset. AID (k=10) still achieves the best F1 score, and the improvement over DPP is 4.61% to 16.99%. Despite the modest increases in F1 score and recall of AID on this dataset, the improvement in precision is still significant, reaching 12.36% to 90.76%.

Last is the EvalPlus dataset. AID (k=10) still achieves the best F1 score, and the improvement over DPP is 43.57% to 45.83%. The APR method shows a good performance, this may be because the defects in plausible programs within EvalPlus are more obvious and easier to fix. The recall of AID is lower than APR, but the precision of AID still shows a significant improvement of 55.29% over APR, and an improvement of -7.99% to 58.93% over DPP.

**Finding 1:** AID shows superior performance on both human-written and AI-generated plausible programs. The recall, precision, and F1 score of AID outperform the existing state-of-the-art test generation method DPP by up to 1.80×, 2.65×, and 1.66×, respectively.

To better understand why the improvement differs among the three datasets, we show the difficulty distribution of the coding tasks corresponding to the PUTs in Figure 5. On the X-axis, "ALL' represents the distribution of difficulty for the coding tasks corresponding to all PUTs in the dataset; "AID" represents the distribution of difficulty for the coding tasks corresponding to the PUTs that AID achieves an average precision more than 50% on, and "DPP" represents the same meaning for DPP. This figure shows that the overall difficulty of TrickyBugs (C++) is higher than that of TrickyBugs (Python). And for TrickyBugs (C++), the coding tasks that AID achieves a precision higher than 0.5 on is more difficult than that of DPP, which indicates that AID shows better performance for difficult, logic complex programs. For TrickyBugs (Python), the difficulty distribution of the coding tasks that AID and DPP achieve a precision higher than 0.5 on is similar, which is expected because most of the problems in the TrickyBugs (Python) are of low difficulty, hence the performance of the two methods are similar. We conducted a detailed examination of three datasets. Intuitively, TrickyBugs (C++) is more challenging than EvalPlus, and EvalPlus is more challenging than TrickyBugs (Python). This explains the varying degrees of improvement AID achieved on different datasets. We will show more evidence in Section 4.7.



(b) Impact of k on P and F

Figure 6: (RQ2) Impact of the number of generated program variants *k*. As the value of *k* changes, AID consistently maintains stable and excellent precision and F1 scores.

**Finding 2:** AID is more suitable for the PUTs with complex logic. AID achieves more significant improvement over DPP on the PUTs with more complex logic.

### 4.6 RQ2: Parameter Analysis

To better understand how k affects the effectiveness of AID and DPP, We show the number of false positives, the number of true positives, precision, and F1 score as line graphs with changes in k.

Figure 6a shows how the average number of true positives and false positives change with the increase of k. The blue lines belong to DPP and the red lines belong to AID. The lines with circle markers represent the number of true positives, the larger the better; The lines with triangle markers represent the number of false positives, the smaller the better. We can see that the number of true positives and false positives of DPP and AID follow two different paradigms with the change of k: For DPP, both the number of true positives and false positives decreases as k increases, and the magnitude of this change is relatively large; whereas for AID, the number of true positives and the magnitude of this change is relatively small.

Similarly, in Figure 6b blue lines represent DPP and red lines AID. Circle markers represent precision and triangle markers represent F1 score, both being the larger the better. We can see that AID consistently maintains a stable and excellent F1 score and precision, and performs better than DPP across any k values. On the other hand, the precision of DPP fluctuates significantly with changes in the k value, while the F1 score remains at a low value.

We can further understand AID's performance by referring to Table 1 again. It can be seen that **regardless of the dataset**, **AID consistently maintains stable and excellent precision**. In most cases, even AID's worst precision is higher than all other methods, and as the value of k changes, the precision of AID remains stable. For different datasets, AID's precision remains in a stable and excellent range of 69.3% to 85.1%, while DPP's precision is in an unstable range of 26.4% to 90.4%, with significant changes as the value of k varies. APR's precision is consistently lower, ranging from 34.6% to 50.0%. And CHAT's precision is unacceptably low, ranging from 6.3% to 8.9%.

As we mentioned in Section 4.3, precision is the golden metric for practicability, and AID's performance in precision shows significant potential for practical application.

**Finding 3:** As the number of generated program variants increases, the number of false positives and true positives of AID also increases, but AID's precision and F1 score always remain stable and excellent, which implies its significant potential for practical application.

### 4.7 RQ3: Ablation Study

In this section, we further explore the contributions of different components to the performance of AID. We take the evaluation results of TrickyBugs (C++) for the ablation study, as AID shows the most significant improvement in this dataset. Table 2 shows the result of the ablation study. "ProGen", "InpGen", and "DiffTest" represent patterns to perform program variants generation, input generation, and differential testing, respectively.

For program generation, "Basic" is the pattern of DPP, requesting the LLM to generate a correct program solely according to specification; "Filtered" represents retaining only those programs that passed the existing test cases from the program variants generated in "basic" pattern; "Ours" is our PUT-guided program generation (see Section 3.1). For input generation, "Basic" is the pattern of DPP, requesting the LLM to generate a test input directly according to specification and PUT; "Ours" is our generator-based input generation (see Section 3.2). For differential testing, "Basic" is the pattern of DPP, which follows the majority voting rule to determine the test oracle; "Ours" is our diversity-first differential testing (see Section 3.3). Pattern 1 is actually the result of DPP, and Pattern 6 is actually the result of AID.

By comparing Pattern 1 and Pattern 2, we find that there is not much difference in their performance. This indicates that using existing test cases to filter program variants is not a major reason why AID performs better than DPP.

By comparing Pattern 1 and Pattern 3, we find that diversityfirst differential testing can effectively improve performance. This

Table 2: (RQ3) Ablation study. "ProGen", "InpGen", and "DiffTest" represent the patterns to perform program variants generation, input generation, and differential testing, respectively. "R", "P", and "F" represent recall, precision, and F1 score, respectively. Each component contributes to the good performance of AID.

Pattern	ProGen	InpGen	DiffTest	k=2				k=4			k=6			k=8			k=10		
				R	Р	F	R	Р	F	R	Р	F	R	Р	F	R	Р	F	
1	Basic	Basic	Basic	.21	.26	.23	.19	.32	.24	.18	.42	.25	.16	.53	.25	.16	.61	.25	
2	Filtered	Basic	Basic	.20	.27	.23	.19	.34	.24	.17	.45	.25	.16	.50	.25	.16	.48	.24	
3	Filtered	Basic	Ours	.23	.60	.33	.22	.59	.32	.22	.59	.32	.22	.59	.32	.22	.59	.32	
4	Ours	Basic	Ours	.22	.48	.30	.24	.47	.32	.24	.47	.32	.25	.47	.32	.25	.47	.32	
5	Filtered	Ours	Ours	.26	.76	.38	.26	.76	.38	.26	.76	.38	.26	.76	.38	.26	.76	.38	
6	Ours	Ours	Ours	.25	.70	.37	.28	.70	.40	.29	.69	.41	.29	.69	.41	.29	.70	.41	

is expected because the filtered programs can efficiently capture valuable inputs using this method.

By comparing Pattern 3 and Pattern 5, we find that generatorbased input generation is crucial for improving recall and precision. This is reasonable because obtaining failure-triggering inputs is fundamental to generating defect-identifying test cases while producing inputs with a high validity rate is key to improving precision.

Finally, we explore Patterns 3, 4, and 6 together. It can be observed that when the value of k is small, using PUT-guided program generation without high-quality generated test inputs (Pattern 5) may somewhat diminish the effectiveness. This is because the program variants generated this way are more likely to share the same defects as the PUT, thereby reducing recall, and the proportion of false positives due to illegal test inputs increases, which in turn reduces precision. The larger the value of k, the less pronounced this negative impact is, as larger k values lead to more consistent quality in program variants. However, if PUT-guided program generation is combined with high-quality generated test inputs (Pattern 6), the performance can be further enhanced compared to Pattern 3 and Pattern 5. In this pattern, there will not be many false positives due to illegal test inputs, and compared to direct generation, PUT-guided program generation is more adept at generating useful program variants for logically complex PUTs, thereby improving both recall and precision.

To better understand how PUT-guided program generation influences the performance of AID, we show the problem-level average passing rate of the generated program variants on base test cases and extra test cases in Figure 7. Here low difficulty represents half of the PUTs that are of lower difficulty, while high difficulty represents another half of the PUTs that are of higher difficulty. Base tests represent the existing test suite, and if a program variant passes the base tests, we can say that it introduces no defect under the scope of the existing test suite; Extra tests represent the defect-identifying test cases for the PUTs, and if a program variant passes the extra tests, this program variant is actually one that free of the original defect within the PUT.

First, we look at the base tests. Although a program variant that passes the base test does not necessarily contribute to finding defects, a program variant that fails the base tests inevitably introduces new defects, which will significantly reduce the recall



Figure 7: (RQ3) The problem-level average passing rate of the generated program variants on base test cases and extra test cases, grouped by difficulty.

and precision of the final results. For the low-difficulty PUTs, the passing rate of AID's program variants is already much higher than that of DPP. For the high-difficulty PUTs, AID's program variants still maintain a relatively high passing rate, while almost all of DPP's program variants fail to pass the base tests. This result shows how PUT-guided program generation contributes to AID's precision.

Then, we look at extra tests. Program variants that pass the extra test are very valuable as they can produce correct test oracles for defect-triggering test inputs during the differential testing, thus providing an opportunity to obtain a true positive test case. For the low-difficulty PUTs, the passing rate of AID's program variants is a little lower than that of DPP. However, AID's diversity-first differential testing does not need many program variants that have passed extra tests; just one is likely enough to successfully find defects. For the high-difficulty PUTs, the passing rate of AID's program variants is higher than that of DPP, which aligns with the conclusion we obtain from Figure 5 that AID is better at finding defects for PUTs with complex logic than DPP. This result shows how PUT-guided program generation contributes to AID's recall. **Finding 4:** Each component of AID (PUT-guided program generation, generator-based test generation, and diversity-first differential testing) contributes to its performance.

#### **5 RELATED WORK**

We summarize related work from three aspects.

Search-based test generation. First we introduce search-based test generation methods [10, 20-22], which are popular traditional testing methods. There are many automated testing tools developed based on this method, such as EvoSuite [10] and Pynguin [20]. The methods target improving code coverage without adequately considering defect identification. Such methods often remain entirely unaware of program specifications throughout the entire search process, making it highly unlikely for them to actively discover inconsistencies between program behavior and specifications. These tools are primarily used to generate test inputs, but can also generate test cases. However, these test cases use a regression oracle [4, 6], (assuming the implementation of the PUT is correct), making it impossible to discover functional defects in the existing PUT. Fuzzers like AFL [38] can also be considered as search-based methods. However, in most cases, a fuzzer can only identify defects based on predefined oracles (such as crashes and efficiency issues) and is unable to detect specific functional defects in the PUT.

**Test oracle generation.** Early methods used specification mining [12, 27, 39] to complete test oracle generation, and their overall performance was mediocre. More recently, the academic community has shifted its focus toward using neural methods for oracle generation [6, 28, 29, 32]. TOGA [6] is the latest state-of-the-art method; however, TOGA's precision is very low, at only 0.38%, which is far from practical for real-world applications. Most of these methods are orthogonal to AID, as AID focuses on generating test inputs and test oracles with the specifications. Moreover, AID's precision ranges from 69.3% to 85.1%, making it practically valuable.

**LLMs for test generation.** In recent years, the application of LLMs in the field of software engineering has garnered significant attention, with many studies focusing on using LLMs for test generation [9, 31]. We dedicate a separate subsection to summarize these works.

Recently, there have been works related to LLMs for test generation such as ChatTester [37], TestPilot [25], ChatUnitTest [35], and SymPrompt [24]. Among these, only ChatTester involves generating test oracles for finding defects, adopting a strategy similar to Differential Prompting where it first summarizes the program's specification for test generation. The other works aim to generate test prefixes to increase coverage. It is important to note that although some works appear to generate test oracles, they actually only produce regression oracles, such as TestPilot and ChatUnitTest, because these methods use error messages from existing PUT runtime to fix the generated test oracles. These works are orthogonal to AID, as they do not consider the circumstances involving existing specifications and test suites.

Differential Prompting [15] is the most relevant recent work, and it is the state-of-the-art existing test generation method for finding functional defects. This paper has already devoted considerable content to comparing Differential Prompting (DPP) and AID, so we do not elaborate further here.

## 6 THREATS TO VALIDITY

This section discusses the threats to the validity of our results.

**External threats.** The external threats to validity mainly lie in the randomness of the LLM. This is inevitable, as we also rely on randomness to enhance the diversity of the generated program variants and inputs. We repeated the experiments multiple times to reduce the impact of randomness on the experimental results. For CHAT and APR, the randomness comes from the test cases and repaired programs generated by LLM. Our experiment involves repeatedly sampling responses from the LLM to reduce the randomness. For DPP and AID, the randomness also comes from program generation. We use a combinatorial approach to conduct repeated experiments. For example, we pre-generate 10 program variants for a PUT and set the parameter *k* (number of generated programs) as 4. Then, we will randomly select 4 out of the 10 program variants for the experiment, resulting in a total of  $C_{10}^4 = 210$  rounds of repeated experiments.

**Internal threats.** The internal threats to validity mainly lie in our manual checking of the legality of the test inputs. To determine a test case to be true positive and false positive, there are two problems. To mitigate the subjectivity, two authors independently carry out the checking work. Any discrepancies in our checking results are subjected to further checking to ensure the correctness of the manual checking. Furthermore, we also release an open-sourced replication package to enhance reproducibility.

## 7 CONCLUSION

We propose AID, an automated approach to generating defectidentifying test cases for plausible programs, with the power of LLM and differential testing. We evaluate AID on a large-scale dataset with 366 PUTs from competition-level coding tasks and 151 PUTs from basic coding tasks. The evaluation results show that AID achieves the best performance over all existing methods. The recall, precision, and F1 score of AID outperform the best existing method by up to 1.80×, 2.65×, and 1.66×. AID mainly consists of three components: PUT-guided program generation, generatorbased input generation, and diversity-first differential testing. Our ablation study shows each component contributes to the performance of AID. To the best of our knowledge, AID is the first method of generating defect-identifying test cases for plausible programs with practical performance.

#### DATA AVAILABILITY

We provide a replication package for reproducibility at https:// anonymous.4open.science/r/AID/. We plan to develop an opensource tool based on AID and extend the idea to more application scenarios in the future, contributing to the field of automated test generation.

Conference'24, April 2024, Washington, DC, USA

#### REFERENCES

- [1] [n. d.]. EvalPlus Pre-Generated LLM Code Samples. https://github.com/evalplus/ evalplus/releases/tag/v0.1.0
- [2] [n. d.]. TrickyBugs. https://github.com/RinCloud/TrickyBugs
- [3] Saswat Anand, Edmund K Burke, Tsong Yueh Chen, John Clark, Myra B Cohen, Wolfgang Grieskamp, Mark Harman, Mary Jean Harrold, Phil McMinn, Antonia Bertolino, et al. 2013. An orchestrated survey of methodologies for automated software test case generation. *Journal of systems and software* 86, 8 (2013), 1978– 2001.
- [4] Earl T Barr, Mark Harman, Phil McMinn, Muzammil Shahbaz, and Shin Yoo. 2014. The oracle problem in software testing: A survey. *IEEE transactions on software engineering* 41, 5 (2014), 507–525.
- [5] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. 2021. Evaluating large language models trained on code. arXiv preprint arXiv:2107.03374 (2021).
- [6] Elizabeth Dinella, Gabriel Ryan, Todd Mytkowicz, and Shuvendu K Lahiri. 2022. Toga: A neural method for test oracle generation. In Proceedings of the 44th International Conference on Software Engineering. 2130–2141.
- [7] Jon Edvardsson. 1999. A survey on automatic test data generation. In Proceedings of the 2nd Conference on Computer Science and Engineering. 21–28.
- [8] Robert B Evans and Alberto Savoia. 2007. Differential testing: a new approach to change detection. In The 6th Joint Meeting on European software engineering conference and the ACM SIGSOFT Symposium on the Foundations of Software Engineering: Companion Papers. 549–552.
- [9] Angela Fan, Beliz Gokkaya, Mark Harman, Mitya Lyubarskiy, Shubho Sengupta, Shin Yoo, and Jie M. Zhang. 2023. Large Language Models for Software Engineering: Survey and Open Problems. arXiv:2310.03533 [cs.SE]
- [10] Gordon Fraser and Andrea Arcuri. 2011. Evosuite: automatic test suite generation for object-oriented software. In Proceedings of the 19th ACM SIGSOFT symposium and the 13th European conference on Foundations of software engineering. 416–419.
- [11] Luyu Gao, Aman Madaan, Shuyan Zhou, Uri Alon, Pengfei Liu, Yiming Yang, Jamie Callan, and Graham Neubig. 2023. Pal: Program-aided language models. In International Conference on Machine Learning. PMLR, 10764–10799.
- [12] Alberto Goffi, Alessandra Gorla, Michael D Ernst, and Mauro Pezzè. 2016. Automatic generation of oracles for exceptional behaviors. In *Proceedings of the 25th international symposium on software testing and analysis.* 213–224.
- [13] Shuo Hong, Hailong Sun, Xiang Gao, and Shin Hwei Tan. [n. d.]. Investigating and Detecting Silent Bugs in PyTorch Programs. ([n. d.]).
- [14] Kai Huang, Xiangxin Meng, Jian Zhang, Yang Liu, Wenjie Wang, Shuhao Li, and Yuqing Zhang. 2023. An empirical study on fine-tuning large language models of code for automated program repair. In 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE, 1162–1174.
- [15] Tsz-On Li, Wenxi Zong, Yibo Wang, Haoye Tian, Ying Wang, Shing-Chi Cheung, and Jeff Kramer. 2023. Nuances are the Key: Unlocking ChatGPT to Find Failure-Inducing Tests with Differential Prompting. In 2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE). IEEE Computer Society, 14–26.
- [16] Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. 2023. Is Your Code Generated by ChatGPT Really Correct? Rigorous Evaluation of Large Language Models for Code Generation. In *Thirty-seventh Conference on Neural Information Processing Systems*. https://openreview.net/forum?id=1qvx610Cu7
- [17] Kaibo Liu, Yudong Han, , Yiyang Liu, Jie M. Zhang, Zhenpeng Chen, Federica Sarro, Gang Huang, and Yun Ma. 2024. TrickyBugs: A Dataset of Corner-case Bugs in Plausible Programs. In Proceedings of the 21st International Conference on Mining Software Repositories (MSR 2024). https://doi.org/10.1145/3643991.3644870
- [18] Kaibo Liu, Yudong Han, Jie M. Zhang, Zhenpeng Chen, Federica Sarro, Mark Harman, Gang Huang, and Yun Ma. 2023. Who Judges the Judge: An Empirical Study on Online Judge Tests. In Proceedings of the 32nd ACM SIGSOFT International Symposium on Software Testing and Analysis (ISSTA 2023). Association for Computing Machinery, New York, NY, USA, 334–346. https: //doi.org/10.1145/3597926.3598060
- [19] Zhongxin Liu, Kui Liu, Xin Xia, and Xiaohu Yang. 2023. Towards More Realistic Evaluation for Neural Test Oracle Generation. In Proceedings of the 32nd ACM SIGSOFT International Symposium on Software Testing and Analysis (ISSTA 2023). Association for Computing Machinery, New York, NY, USA, 589–600. https:

//doi.org/10.1145/3597926.3598080

- [20] Stephan Lukasczyk and Gordon Fraser. 2022. Pynguin: Automated unit test generation for python. In Proceedings of the ACM/IEEE 44th International Conference on Software Engineering: Companion Proceedings. 168–172.
- [21] Phil McMinn. 2004. Search-based software test data generation: a survey. Software testing, Verification and reliability 14, 2 (2004), 105–156.
- [22] Phil McMinn. 2011. Search-based software testing: Past, present and future. In 2011 IEEE Fourth International Conference on Software Testing, Verification and Validation Workshops. IEEE, 153–163.
- [23] Per Runeson, Carina Andersson, Thomas Thelin, Anneliese Andrews, and Tomas Berling. 2006. What do we know about defect detection methods?[software testing]. *IEEE software* 23, 3 (2006), 82–90.
- [24] Gabriel Ryan, Siddhartha Jain, Mingyue Shang, Shiqi Wang, Xiaofei Ma, Murali Krishna Ramanathan, and Baishakhi Ray. 2024. Code-Aware Prompting: A study of Coverage Guided Test Generation in Regression Setting using LLM. arXiv preprint arXiv:2402.00097 (2024).
- [25] Max Schäfer, Sarah Nadi, Aryaz Eghbali, and Frank Tip. 2024. An Empirical Evaluation of Using Large Language Models for Automated Unit Test Generation. *IEEE Transactions on Software Engineering* 50, 1 (2024), 85–105. https://doi.org/ 10.1109/TSE.2023.3334955
- [26] Florian Tambon, Amin Nikanjam, Le An, Foutse Khomh, and Giuliano Antoniol. 2024. Silent bugs in deep learning frameworks: An empirical study of Keras and TensorFlow. *Empirical Software Engineering* 29, 1 (2024), 10.
- [27] Shin Hwei Tan, Darko Marinov, Lin Tan, and Gary T Leavens. 2012. @ tcomment: Testing javadoc comments to detect comment-code inconsistencies. In 2012 IEEE Fifth International Conference on Software Testing, Verification and Validation. IEEE, 260–269.
- [28] Michele Tufano, Dawn Drain, Alexey Svyatkovskiy, Shao Kun Deng, and Neel Sundaresan. 2020. Unit test case generation with transformers and focal context. arXiv preprint arXiv:2009.05617 (2020).
- [29] Michele Tufano, Dawn Drain, Alexey Svyatkovskiy, and Neel Sundaresan. 2022. Generating accurate assert statements for unit test cases using pretrained transformers. In Proceedings of the 3rd ACM/IEEE International Conference on Automation of Software Test. 54–64.
- [30] Karthik Valmeekam, Alberto Olmo, Sarath Sreedharan, and Subbarao Kambhampati. 2022. Large language models still can't plan (a benchmark for llms on planning and reasoning about change). arXiv preprint arXiv:2206.10498 (2022).
- [31] Junjie Wang, Yuchao Huang, Chunyang Chen, Zhe Liu, Song Wang, and Qing Wang. 2024. Software testing with large language model: Survey, landscape, and vision. *IEEE Transactions on Software Engineering* (2024).
- [32] Cody Watson, Michele Tufano, Kevin Moran, Gabriele Bavota, and Denys Poshyvanyk. 2020. On learning meaningful assert statements for unit test cases. In Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering. 1398–1409.
- [33] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. Advances in neural information processing systems 35 (2022), 24824–24837.
- [34] Chunqiu Steven Xia, Yuxiang Wei, and Lingming Zhang. 2023. Automated program repair in the era of large pre-trained language models. In 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, 1482–1494.
- [35] Zhuokui Xie, Yinghao Chen, Chen Zhi, Shuiguang Deng, and Jianwei Yin. 2023. ChatUniTest: a ChatGPT-based automated unit test generation tool. arXiv preprint arXiv:2305.04764 (2023).
- [36] Guixin Ye, Zhanyong Tang, Shin Hwei Tan, Songfang Huang, Dingyi Fang, Xiaoyang Sun, Lizhong Bian, Haibo Wang, and Zheng Wang. 2021. Automated conformance testing for javascript engines via deep compiler fuzzing. In Proceedings of the 42nd ACM SIGPLAN international conference on programming language design and implementation. 435–450.
- [37] Zhiqiang Yuan, Yiling Lou, Mingwei Liu, Shiji Ding, Kaixin Wang, Yixuan Chen, and Xin Peng. 2023. arXiv:2305.04207 [cs.SE]
- [38] Michal Zalewski. 2015. American Fuzzy Lop (AFL). lcamtuf.coredump.cx/afl/
   [39] Juan Zhai, Yu Shi, Minxue Pan, Guian Zhou, Yongxiang Liu, Chunrong Fang, Shiqing Ma, Lin Tan, and Xiangyu Zhang. 2020. C2S: translating natural language comments to formal program specifications. In Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering. 25–37.