Exponential Quantum One-Wayness and EFI Pairs

Giulio Malavolta^{1,2}, Tomoyuki Morimae³, Michael Walter⁴, Takashi Yamakawa^{5,6,3}

¹Bocconi University, Milan, Italy giulio.malavolta@hotmail.it

²Max Planck Institute for Security and Privacy, Bochum, Germany ³Yukawa Institute for Theoretical Physics, Kyoto University, Kyoto, Japan

tomoyuki.morimae@yukawa.kyoto-u.ac.jp

⁴Faculty of Computer Science, Ruhr University Bochum, Bochum, Germany michael.walter@rub.de

 $^5\mathrm{NTT}$ Social Informatics Laboratories, Tokyo, Japan

takashi.yamakawa@ntt.com

⁶NTT Research Center for Theoretical Quantum Information, Atsugi, Japan

Abstract

In classical cryptography, one-way functions are widely considered to be the minimal computational assumption. However, when taking quantum information into account, the situation is more nuanced. There are currently two major candidates for the minimal assumption: the *search* quantum generalization of one-way functions are one-way state generators (OWSG), whereas the *decisional* variant are EFI pairs. A well-known open problem in quantum cryptography is to understand how these two primitives are related. A recent breakthrough result of Khurana and Tomer (STOC'24) shows that OWSGs imply EFI pairs, for the restricted case of pure states.

In this work, we make progress towards understanding the general case. To this end, we define the notion of *inefficiently-verifiable one-way state generators* (IV-OWSGs), where the verification algorithm is not required to be efficient, and show that these are precisely equivalent to EFI pairs, with an exponential loss in the reduction. Significantly, this equivalence holds also for *mixed* states. Thus our work establishes the following relations among these fundamental primitives of quantum cryptography:

(mixed) OWSGs \implies (mixed) IV-OWSGs \equiv_{exp} EFI pairs,

where \equiv_{exp} denotes equivalence up to exponential security of the primitives.

1 Introduction

The existence of one-way functions (OWFs) is widely regarded as the minimal assumption in classical cryptography. This is because almost all primitives imply OWFs and furthermore OWFs are in fact equivalent to many foundational primitives, such as secret-key encryption (SKE), commitments, zero-knowledge, pseudorandom generators (PRGs), pseudorandom functions (PRFs), and digital signatures [LR86, IL89, ILL89]. However, recent works have suggested that OWFs may not be the minimal assumption when bringing quantum information into the picture. Instead, several candidate "minimal" primitives have been proposed that are potentially weaker than OWFs [Kre21, KQST23, LMW23], yet still enable many useful applications, such as privatekey quantum money, SKE, commitments, multiparty computations, and digital signatures [JLS18, MY22b, AQY22, BCQ23, Yan22].

In this work, we consider two major candidates that have emerged in this recent line of research: one-way state generators (OWSGs) and EFI pairs. OWSGs were introduced in [MY22b, MY22a] as a search quantum generalization of OWFs. Formally, a OWSG consists of a triple (KeyGen, StateGen, Ver) of quantum polynomial-time (QPT) algorithms, where KeyGen $(1^{\lambda}) \rightarrow k$ is the key generation algorithm (keys are classical), StateGen $(k) \rightarrow \phi_k$ takes a key as input and generates a quantum state, and Ver $(k', \phi) \rightarrow \{\top, \bot\}$ is a verification algorithm that takes a bit string k' and a quantum state ϕ as input. The security of a OWSG requires that no QPT adversary \mathcal{A} can find a "preimage" of ϕ_k with non-negligible probability, that is,

$$\Pr\left[\top \leftarrow \mathsf{Ver}(k',\phi_k) : k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \phi_k \leftarrow \mathsf{StateGen}(k), k' \leftarrow \mathcal{A}(1^{\lambda},\phi_k^{\otimes t})\right] \approx 0$$

for any polynomial number $t = t(\lambda)$ of copies. This can be considered as a quantum analogue of the one-wayness of OWFs.

On the other hand, EFI pairs [BCQ23] are a *decisional* quantum generalization of OWFs. Formally, an EFI pair consists of a QPT algorithm that on input 1^{λ} generates two (mixed) quantum states ξ_0 and ξ_1 which are statistically far but computationally indistinguishable. As such, EFI pairs are a quantum generalization of EFIDs, which are pairs of efficiently samplable classical distributions that are statistically distinguishable but computationally indistinguishable, a primitive that is equivalent to OWFs [Gol90].

Given that both of these quantum primitives generalize the same object in classical cryptography, it is natural to ask about their relation. A recent breakthrough result [KT23] shows that OWSGs imply EFI pairs provided the outputs of StateGen are *pure* states. The general case where the outputs of StateGen are *mixed states*, as well as the reverse direction of the implication, remain open.

1.1 Our Results

In this work, we make progress towards understanding the relation between OWSGs and EFI pairs. First, we define a weaker notion of OWSGs, wherein the verification algorithm Ver is not required to be efficient. We refer to this primitive as *inefficiently-verifiable one-way state generators (IV-OWSGs)*. Then, as the main technical contribution of our work, we show that IV-OWSGs and EFI pairs are equivalent, but with an exponential loss in the reduction. That is, our work establishes the following relations amongst these fundamental primitives in quantum cryptography:

(mixed) OWSGs
$$\implies$$
 (mixed) IV-OWSGs \equiv_{exp} EFI pairs

where \equiv_{exp} means equivalence with an exponential loss for the implication from the left to right (but only with a polynomial loss for the other direction) and we write "(mixed)" to stress that all our results hold in the general case that the **StateGen** of OWSGs returns mixed states. The first implication is clear. That EFI pairs imply (mixed) IV-OWSGs follows using known facts in quantum cryptography (Theorem 4.3), and the reduction does not incur any loss. Our main technical contribution is to prove that IV-OWSGs imply EFI pairs with an exponential security loss (Theorem 5.2). Crucially, all our results hold in the general setting where the **StateGen** of OWSGs is allowed to generate mixed states. In contrast, the recent breakthrough [KT23] only considered *pure* states (but their reduction has a polynomial loss, so the results are incomparable). Our proof follows a different route, and makes crucial use of Aaronson's shadow tomography algorithm [Aar19].

Using known implications from the literature [BCQ23], a consequence of our work is that (mixed) OWSGs with exponential security imply a number of primitives in cryptography, such as non-interactive commitments, quantum computational zero knowledge, oblivious transfer, and general multiparty computation. At a more conceptual level, our work also sheds some light on the relation between OWSGs and EFI pairs: For instance, if one were able to show the outstanding implication that EFI pairs \implies OWSGs (with a polynomial reduction), one would automatically obtain a generic conversion that turns any exponentially secure OWSGs with *inefficient* verification into one with *efficient* verification, which would perhaps be surprising.

1.2 Proof Outline

We give here a brief overview of the proof of our main technical contribution, namely that IV-OWSGs imply EFI pairs. It is well-known that EFI pairs are equivalent to canonical quantum bit commitments [Yan22], and therefore our goal is to construct commitments from IV-OWSGs. Consider an arbitrary IV-OWSG (KeyGen, StateGen, Ver). We construct a non-interactive bit commitment scheme in the canonical form of [Yan22] as follows. A commitment to 0 is a state

$$|\psi_{0}\rangle_{\mathbf{R},\mathbf{C}} \coloneqq \sum_{k} \sum_{h \in \mathcal{H}} \sqrt{\frac{\Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})]}{|\mathcal{H}|}} |k, \mathrm{junk}_{k}, h\rangle_{\mathbf{C}_{1}} |h, h(k)\rangle_{\mathbf{R}_{1}} |\Phi_{k}^{\otimes t}\rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} |0...0\rangle_{\mathbf{R}_{3}}$$

whereas a commitment to 1 is a state

$$|\psi_1\rangle_{\mathbf{R},\mathbf{C}} \coloneqq \sum_k \sum_{h \in \mathcal{H}} \sqrt{\frac{\Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})]}{|\mathcal{H}|}} \, |k, \mathrm{jun}k_k, h\rangle_{\mathbf{C}_1} \, |h, h(k)\rangle_{\mathbf{R}_1} \, |\Phi_k^{\otimes t}\rangle_{\mathbf{C}_2, \mathbf{R}_2} \, |k\rangle_{\mathbf{R}_3}$$

where $t = t(\lambda)$ is a certain polynomial specified later, \mathcal{H} is a family of pairwise-independent hash functions, $|\text{junk}_k\rangle$ is the state of the non-output registers in a unitary realization of the KeyGen algorithm,¹ and $|\Phi_k\rangle$ is a purification of the output of the StateGen(k) algorithm.² One should think of $\mathbf{C} := (\mathbf{C}_1, \mathbf{C}_2)$ as the commitment register and of $\mathbf{R} := (\mathbf{R}_1, \mathbf{R}_2, \mathbf{R}_3)$ as the reveal register. It is clear that both $|\psi_0\rangle$ and $|\psi_1\rangle$ can be efficiently generated.

Computational binding is shown with a reduction to the exponential one-wayness of IV-OWSG: Assuming that there exists an efficient algorithm that converts $|\psi_0\rangle_{\mathbf{R},\mathbf{C}}$ into $|\psi_1\rangle_{\mathbf{R},\mathbf{C}}$ by acting only on \mathbf{R} , we can obtain an algorithm that computes k from h, h(k), and $\phi_k^{\otimes t} = \text{Tr}_{\mathbf{C}_2}(|\Phi_k^{\otimes t}\rangle\langle\Phi_k^{\otimes t}|)$. By randomly guessing h(k), we can use it to break the security of IV-OWSG with an exponential security loss of $2^{|h(k)|}$ where |h(k)| is the output length of h.

To show statistical hiding, it suffices to construct an (inefficient) unitary on **R** that turns $|\psi_0\rangle_{\mathbf{R},\mathbf{C}}$ into $|\psi_1\rangle_{\mathbf{R},\mathbf{C}}$ with a sufficiently good approximation. To this end consider the following procedure:

¹Without loss of generality, the KeyGen algorithm takes the following form: apply a QPT unitary to generate a superposition $\sum_{k} \sqrt{\Pr[k \leftarrow \text{KeyGen}(1^{\lambda})]} |k\rangle |\text{junk}_k\rangle$, measure the first register, and output the measurement result.

²Without loss of generality, StateGen takes the following form: on input k, apply a QPT unitary U_k on $|0...0\rangle$ to generate a pure state $|\Phi_k\rangle_{\mathbf{A},\mathbf{B}} = U_k|0...0\rangle$ and output the first register **A**, which is in state $\phi_k = \text{Tr}_{\mathbf{B}}(|\Phi_k\rangle\langle\Phi_k|)$. Then the **A** registers of $|\Phi_k^{\otimes t}\rangle$ make up **R**₂, while the **B** registers make up **C**₂.

- 1. Apply shadow tomography [Aar19] to list all k' that are accepted by $Ver(\cdot, \phi_k)$ with a sufficiently large probability.
- 2. In this list, find k^* such that $h(k) = h(k^*)$. If there is a single such k^* , output it. Otherwise, output \perp .

Intuitively, this algorithm outputs the true key k with probability at least $1/2 - \operatorname{negl}(\lambda)$, because the list obtained by the shadow tomography contains k except for a negligible probability and because we set the output length of h appropriately so that, with probability at least 1/2, $h^{-1}(h(k))$ intersects the list in a single element. By running this algorithm coherently, we get an (inefficient) unitary on **R** that maps $|\psi_0\rangle_{\mathbf{R},\mathbf{C}}$ close to $|\psi_1\rangle_{\mathbf{R},\mathbf{C}}$. Thus Uhlmann's theorem implies that the trace distance between $\operatorname{Tr}_{\mathbf{R}}(|\psi_0\rangle_{\mathbf{R},\mathbf{C}})$ and $\operatorname{Tr}_{\mathbf{R}}(|\psi_1\rangle_{\mathbf{R},\mathbf{C}})$ is small. This shows statistical hiding.

1.3 Paper Outline

Section 2 is for preliminaries where some notations and basic definitions are given. In Section 3, we define the new notion of IV-OWSGs. In Section 4, we show that EFI pairs imply IV-OWSGs, unconditionally and without any loss. In Section 5, we show that EFI pairs can be constructed from exponentially-secure IV-OWSGs, with an exponential loss.

2 Preliminaries

2.1 Basic Notations

We use notation that is standard in quantum computing and cryptography. We use λ as the security parameter. The notation [n] refers to the set $\{1, 2, ..., n\}$. For any set $S, x \leftarrow S$ means that an element x is sampled uniformly at random from the set S. For an algorithm $A, y \leftarrow A(x)$ means that the algorithm outputs y on input x. For a set S, |S| denotes its cardinality. We write negl to denote a negligible function and poly to mean a polynomial function. QPT stands for quantum polynomial-time. Any binary (2-outcome) quantum measurement can be described by a POVM element E, which is an operator such that both E and I - E are positive semidefinite. Quantum registers are denoted by bold font (e.g., \mathbf{A} and \mathbf{B}). We write $\mathrm{Tr}_{\mathbf{B}}(\rho_{\mathbf{A},\mathbf{B}})$ for the partial trace over the register \mathbf{B} of the bipartite state $\rho_{\mathbf{A},\mathbf{B}}$. The notation $I_{\mathbf{A}}$ denotes the identity operator on register \mathbf{A} . For any two quantum states ρ and σ , their fidelity is $F(\rho, \sigma) \coloneqq (\mathrm{Tr}\sqrt{\sqrt{\sigma}\rho\sqrt{\sigma}})^2$ and their trace distance is $\mathrm{TD}(\rho, \sigma) \coloneqq \frac{1}{2} \|\rho - \sigma\|_1$.

2.2 Computational Model for Adversaries

Throughout the paper, we treat adversaries as *non-uniform* QPT machine with *quantum* advice. However, all of our results extend to the uniform setting in a straightforward manner.

2.3 Pairwise-Independent Hash Family

We recall the definition of pairwise independence.

Definition 2.1 (Pairwise-Independent Hash Family). A family $\mathcal{H} = \{h : \mathcal{X} \to \mathcal{Y}\}$ of functions is called a pairwise-independent hash family if, for any two $x \neq x' \in \mathcal{X}$ and any two $y, y' \in \mathcal{Y}$,

$$\Pr_{h \leftarrow \mathcal{H}}[h(x) = y \land h(x') = y'] = \frac{1}{|\mathcal{Y}|^2}.$$

2.4 Shadow Tomography

The shadow tomography problem asks to predict a large number of measurement outcomes from copies of a quantum state. More formally:

Definition 2.2 (Shadow Tomography Problem [Aar19, Problem 1]). Given t copies of an unknown d-dimensional (possibly mixed) quantum state ρ , as well as known binary measurements given by POVM elements E_1, \ldots, E_M , output numbers $b_1, \ldots, b_M \in [0, 1]$ such that

$$|b_j - \operatorname{Tr}(E_j \rho)| \le \varepsilon$$

for all j, with success probability at least $1 - \omega$.

The following theorem from Aaronson provides a bound on the number of copies of the state needed to solve this problem.

Theorem 2.3 ([Aar19, Theorem 2]). The shadow tomography problem is solvable with

$$t = \tilde{O}\left(\frac{\log\frac{1}{\omega}}{\varepsilon^4} \cdot \log^4 M \cdot \log d\right),\,$$

where the \tilde{O} hides a poly $(\log \log M, \log \log d, \log \frac{1}{\epsilon})$ factor.

2.5 EFI Pairs and Quantum Bit Commitments

EFI pairs are pairs of efficiently generatable quantum states that are statistically \mathbf{f} ar, yet computationally indistinguishable. They were introduced in [BCQ23].

Definition 2.4 (EFI Pair [BCQ23]). An EFI pair is a family $\{\xi_{\lambda,b}\}_{\lambda \in \mathbb{N}, b \in \{0,1\}}$ of (mixed) quantum states that satisfies the following conditions:

- (Efficiently Generatable) There is a uniform QPT algorithm that generates $\xi_{\lambda,0}$ and $\xi_{\lambda,1}$ on input 1^{λ} .
- (Statistically Far) It holds that $\mathsf{TD}(\xi_{\lambda,0},\xi_{\lambda,1}) \ge 1/\mathsf{poly}(\lambda)$.
- (Computationally Indistinguishable) For any non-uniform QPT distinguisher A, there exists a negligible function negl such that

$$\left|\Pr[\mathcal{A}(1^{\lambda},\xi_{\lambda,0})=1]-\Pr[\mathcal{A}(1^{\lambda},\xi_{\lambda,1})=1]\right|\leq \mathsf{negl}(\lambda).$$

It is known that EFI pairs exist if and only if quantum bit commitments exist. We define canonical quantum bit commitments following [Yan22].

Definition 2.5 (Canonical Quantum Bit Commitments [Yan22]). A canonical quantum bit commitment scheme consists of a family $\{Q_0(\lambda), Q_1(\lambda)\}_{\lambda \in \mathbb{N}}$ of uniform QPT unitaries. Each acts on two registers **C** (called the commitment register) and **R** (called the reveal register). In the rest of the paper, we often omit λ and simply write Q_0 and Q_1 to mean $Q_0(\lambda)$ and $Q_1(\lambda)$. We define two properties that can be satisfied by canonical quantum bit commitments:

• (Hiding) The scheme is computationally (resp. statistically) ϵ -hiding if for any non-uniform QPT (resp. for any unbounded) adversary \mathcal{A} , it holds that

$$\left| \Pr\left[1 \leftarrow \mathcal{A}\left(1^{\lambda}, \operatorname{Tr}_{\mathbf{R}}\left((Q_0 | 0 \rangle \langle 0 | Q_0^{\dagger})_{\mathbf{C}, \mathbf{R}} \right) \right) \right] - \Pr\left[1 \leftarrow \mathcal{A}\left(1^{\lambda}, \operatorname{Tr}_{\mathbf{R}}\left((Q_1 | 0 \rangle \langle 0 | Q_1^{\dagger})_{\mathbf{C}, \mathbf{R}} \right) \right) \right] \right| \leq \epsilon(\lambda).$$

We say that the scheme is computationally (resp. statistically) hiding if ϵ is negligible.

• (Binding) The scheme is computationally (resp. statistically) δ -binding if for any polynomialsize register **Z** and for any non-uniform QPT (resp. for any unbounded) unitary $U_{\mathbf{R},\mathbf{Z}}$, it holds that

$$\left\| \left((\langle 0 | Q_1^{\dagger})_{\mathbf{C},\mathbf{R}} \otimes I_{\mathbf{Z}} \right) \left(I_{\mathbf{C}} \otimes U_{\mathbf{R},\mathbf{Z}} \right) \left((Q_0 | 0 \rangle)_{\mathbf{C},\mathbf{R}} \otimes I_{\mathbf{Z}} \right) \right\| \leq \delta(\lambda).$$

We say that the scheme is computationally (resp. statistically) binding if δ is negligible.

Note that *statistical* ϵ -hiding can also be defined in terms of the trace distance, as follows:

$$\mathsf{TD}\Big(\mathrm{Tr}_{\mathbf{R}}\big((Q_0|0\rangle\langle 0|Q_0^{\dagger})_{\mathbf{C},\mathbf{R}}\big), \mathrm{Tr}_{\mathbf{R}}\big((Q_1|0\rangle\langle 0|Q_1^{\dagger})_{\mathbf{C},\mathbf{R}}\big)\Big) \leq \epsilon(\lambda).$$
(2.1)

The following lemma is an immediate consequence of Uhlmann's theorem.

Lemma 2.6. EFI pairs exist if and only if there exists a canonical quantum bit commitment scheme that is computationally hiding and statistically $(1 - 1/\text{poly}(\lambda))$ -binding.³

It is known that binding and hiding of canonical quantum bit commitments can be traded for each other [CLS01, Yan22, HMY23, GJMZ23]. In particular, the following result was shown in [HMY23] (see also [HKNY23]).

Lemma 2.7 (Flavor Conversion for Quantum Bit Commitments [HMY23]). If there exists a canonical quantum bit commitment scheme that is statistically ϵ -hiding and computationally binding, then there also exists one that is computationally hiding and statistically $\sqrt{\epsilon}$ -binding.

Combining Lemmata 2.6 and 2.7, we obtain the following corollary.

Corollary 2.8. If there exists a canonical quantum bit commitment scheme that is statistically $(1 - 1/\text{poly}(\lambda))$ -hiding and computationally binding, then EFI pairs exist.

³A very recent work [BQSY23] shows that canonical quantum bit commitment schemes that satisfy computational hiding and *computational* $(1-1/\text{poly}(\lambda))$ -binding are sufficient for constructing EFI pairs. We do not need this result.

3 Inefficiently-Verifiable One-Way State Generators (IV-OWSGs)

In this section, we define IV-OWSGs and the notion of exponential security. We first recall the definition of $\rm OWSGs.^4$

Definition 3.1 (OWSGs [MY22b, MY22a]). A one-way state generator (OWSG) is a triple (KeyGen, StateGen, Ver) of uniform QPT algorithms with the following syntax:

- KeyGen $(1^{\lambda}) \rightarrow k$: On input the security parameter λ , this algorithm outputs a key $k \in \{0, 1\}^{\lambda}$.
- StateGen $(k) \rightarrow \phi_k$: On input k, this algorithm outputs the (possibly mixed) quantum state ϕ_k .
- Ver(k', φ) → {⊤, ⊥}: On input a bit string k' and a quantum state φ, this algorithm outputs ⊤ or ⊥.

We require the following two properties to hold.

• (Correctness) There exists a negligible function negl such that:

$$\Pr\left[\top \leftarrow \mathsf{Ver}(k, \phi_k) : k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \phi_k \leftarrow \mathsf{StateGen}(k)\right] \ge 1 - \mathsf{negl}(\lambda).$$

• (Security) For any non-uniform QPT adversary \mathcal{A} and any polynomial $t = t(\lambda)$, there exists a negligible function negl such that

$$\Pr\left[\top \leftarrow \mathsf{Ver}(k',\phi_k) : k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \phi_k \leftarrow \mathsf{StateGen}(k), k' \leftarrow \mathcal{A}(1^{\lambda},\phi_k^{\otimes t(\lambda)})\right] \le \mathsf{negl}(\lambda).$$

Now we introduce a new variant of OWSGs where we allow Ver to be inefficient.

Definition 3.2 (IV-OWSGs). An inefficiently-verifiable one-way state generator (IV-OWSG) is defined like a OWSG, except that the algorithm Ver is allowed to be inefficient (need not be QPT).

We will also consider exponential security as defined below. The definition applies to both OWSGs and IV-OWSGs.

Definition 3.3 (Exponential security of (IV-)OWSGs). For a function $\delta \colon \mathbb{N} \to \mathbb{R}$, we say that an OWSG or IV-OWSG is δ -exponentially secure if

$$\Pr\left[\top \leftarrow \mathsf{Ver}(k',\phi_k) : k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \phi_k \leftarrow \mathsf{StateGen}(k), k' \leftarrow \mathcal{A}(1^{\lambda},\phi_k^{\otimes t(\lambda)})\right] \le 2^{-\delta(\lambda)}$$

for any non-uniform QPT adversary \mathcal{A} , any polynomial $t = t(\lambda)$, and a large enough λ , possibly depending on the adversary.

⁴The original OWSGs introduced in [MY22b] were defined to have pure state outputs, but this was later generalized to allow for mixed state outputs [MY22a].

4 EFI Pairs Imply IV-OWSGs

In this section, we show that the existence of EFI pairs implies the existence of IV-OWSGs, unconditionally and without any loss. For our proof, it will be useful to recall the notion of secretly-verifiable and statistically-invertible one-way state generators (SV-SI-OWSGs) as introduced in [MY22a].

Definition 4.1 (SV-SI-OWSGs [MY22a]). A secretly-verifiable and statistically-invertible oneway state generator (SV-SI-OWSG) consists of a pair (KeyGen, StateGen) of uniform QPT algorithms with the following syntax.

- KeyGen $(1^{\lambda}) \rightarrow k$: On input the security parameter λ , this algorithm outputs a key $k \in \{0,1\}^{\lambda}$.
- StateGen $(k) \rightarrow \phi_k$: On input k, this algorithm outputs a (possibly mixed) quantum state ϕ_k .

We require the following two properties to hold:

- (Statistical Invertibility) There exists a (not necessarily efficient) POVM $\{\Pi_k\}_{k \in \{0,1\}^{\lambda}}$ such that $\operatorname{Tr}(\Pi_k \phi_k) \geq 1 \operatorname{negl}(\lambda)$ and $\operatorname{Tr}(\Pi_{k'} \phi_k) \leq \operatorname{negl}(\lambda)$ for any two keys $k \neq k'$.
- (Computational Non-Invertibility) For any non-uniform QPT adversary A and any polynomial t = t(λ), there exists a negligible function negl such that

 $\Pr[k \leftarrow \mathcal{A}(1^{\lambda}, \phi_k^{\otimes t(\lambda)}) : k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \phi_k \leftarrow \mathsf{StateGen}(k)] \le \mathsf{negl}(\lambda).$

The following result was proved in the same paper.

Lemma 4.2 ([MY22a, Theorem 7.8]). If EFI pairs exist, then SV-SI-OWSGs exist.

We are now ready to state and prove the main theorem of this section.

Theorem 4.3. If EFI pairs exist, then IV-OWSGs exist.

Proof. In view of Lemma 4.2 it suffices to show the existence of an IV-OWSG from a SV-SI-OWSG. Let us thus assume that a SV-SI-OWSG (SVSI.KeyGen, SVSI.StateGen) exists. We construct an IV-OWSG (KeyGen, StateGen, Ver) as follows:

- KeyGen $(1^{\lambda}) \rightarrow k$: Run $k \leftarrow$ SVSI.KeyGen (1^{λ}) and output k.
- StateGen $(k) \rightarrow \phi_k$: Run $\phi_k \leftarrow$ SVSI.StateGen(k) and output ϕ_k .
- Ver $(k', \phi) \to \top/\bot$: Measure ϕ with the POVM $\{\Pi_k\}_{k \in \{0,1\}^{\lambda}}$ that exists by the statistical invertibility. If the outcome is k' then output \top . Otherwise, output \bot .

Correctness follows as an immediate consequence of the statistical invertibility of the SV-SI-OWSG.

We now prove security. Let \mathcal{A} be an arbitrary non-uniform QPT algorithm and $t = t(\lambda)$ a polynomial. Then it holds that,

$$\begin{aligned} &\Pr[\top \leftarrow \mathsf{Ver}(k',\phi_k): k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \phi_k \leftarrow \mathsf{StateGen}(k), k' \leftarrow \mathcal{A}(1^{\lambda},\phi_k^{\otimes t})] \\ &= \sum_k \Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})] \sum_{k'} \Pr[k' \leftarrow \mathcal{A}(1^{\lambda},\phi_k^{\otimes t})] \cdot \operatorname{Tr}(\Pi_{k'}\phi_k) \end{aligned}$$

$$\begin{split} &= \sum_{k} \Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})] \Pr[k \leftarrow \mathcal{A}(1^{\lambda}, \phi_{k}^{\otimes t})] \cdot \operatorname{Tr}(\Pi_{k} \phi_{k}) \\ &+ \sum_{k} \Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})] \sum_{k' \neq k} \Pr[\alpha \leftarrow \mathcal{A}(1^{\lambda}, \phi_{k}^{\otimes t})] \cdot \operatorname{Tr}(\Pi_{k'} \phi_{k}) \\ &\leq \sum_{k} \Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})] \Pr[k \leftarrow \mathcal{A}(1^{\lambda}, \phi_{k}^{\otimes t})] \\ &+ \sum_{k} \Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})] \sum_{\alpha \neq k} \Pr[\alpha \leftarrow \mathcal{A}(1^{\lambda}, \phi_{k}^{\otimes t})] \cdot \operatorname{negl}(\lambda) \\ &\leq \operatorname{negl}(\lambda), \end{split}$$

where the first inequality follows by upper bounding $\text{Tr}(\Pi_k \phi_k) \leq 1$ and using the statistical invertibility of the SV-SI-OWSG, and the second inequality uses the computational non-invertibility of the SV-SI-OWSG.

5 Exponentially-Secure IV-OWSGs Imply EFI Pairs

In this section, we show our main result, namely, the construction of EFI pairs from exponentiallysecure IV-OWSGs. Before stating our main theorem, we first prove a useful lemma.

Lemma 5.1. Let (KeyGen, StateGen, Ver) be a δ -exponentially-secure IV-OWSG for some $\delta = \delta(\lambda)$. Let $p = p(\lambda)$ be an arbitrary polynomial, and define for any λ and for any $k \in \{0,1\}^{\lambda}$,

$$G_k := G_k(\lambda) := \left\{ k' \in \{0,1\}^{\lambda} : \Pr[\top \leftarrow \mathsf{Ver}(k',\phi_k)] \ge 1 - \frac{1}{p(\lambda)} \right\}.$$

Suppose that $r = r(\lambda)$ is a function that satisfies $\delta(\lambda) + r(\lambda) \ge C\lambda$ for some constant C > 1. Then there exists a negligible function $negl(\lambda)$ such that the following holds:

$$\Pr\left[1 \le |G_k| \le 2^r : k \leftarrow \mathsf{KeyGen}(1^{\lambda})\right] \ge \Pr\left[k \in G_k \land |G_k| \le 2^r : k \leftarrow \mathsf{KeyGen}(1^{\lambda})\right] \ge 1 - \mathsf{negl}(\lambda),$$

Proof. The correctness of the IV-OWSG implies that

$$\Pr\left[|G_k| < 1: k \leftarrow \mathsf{KeyGen}(1^{\lambda})\right] \le 1 - \Pr\left[k \in G_k: k \leftarrow \mathsf{KeyGen}(1^{\lambda})\right] \le \mathsf{negl}(\lambda).$$

It remains to show that the upper bound $|G_k| \leq 2^r$ holds for all but a negligible fraction of k as well. To this end we consider the following trivial attack against the IV-OWSG:⁵ On input $\phi_k^{\otimes t}$, ignore the state, sample $k' \leftarrow \{0, 1\}^{\lambda}$, and output k'. By the δ -exponential security of the IV-OWSG, the winning probability of this attack is at most

$$\Pr\left[\top \leftarrow \mathsf{Ver}(k',\phi_k) : k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \phi_k \leftarrow \mathsf{StateGen}(k), k' \leftarrow \{0,1\}^{\lambda}\right] \le 2^{-\delta(\lambda)}.$$

In other words:

$$\sum_{k,k'} \Pr[k] 2^{-\lambda} \Pr[\top \leftarrow \mathsf{Ver}(k', \phi_k)] \le 2^{-\delta(\lambda)}, \tag{5.1}$$

⁵It works even for t = 0.

where $\Pr[k] := \Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})]$. Let us define the set of keys for which the desired bound is not satisfied

$$T \coloneqq T(\lambda) \coloneqq \left\{ k \in \{0,1\}^{\lambda} : |G_k| > 2^{r(\lambda)} \right\}.$$

Then we can rewrite Equation (5.1) as follows:

$$\begin{split} 2^{-\delta(\lambda)} &\geq \sum_{k,k'} \Pr[k] 2^{-\lambda} \Pr[\top \leftarrow \mathsf{Ver}(k',\phi_k)] \\ &\geq \sum_{k \in T} \Pr[k] \sum_{k' \in G_k} 2^{-\lambda} \Pr[\top \leftarrow \mathsf{Ver}(k',\phi_k)] \\ &\geq \sum_{k \in T} \Pr[k] |G_k| \ 2^{-\lambda} \left(1 - \frac{1}{p(\lambda)}\right) \\ &\geq \sum_{k \in T} \Pr[k] \ 2^{r(\lambda)} \ 2^{-\lambda} \left(1 - \frac{1}{p(\lambda)}\right). \end{split}$$

Rearranging, we obtain that

$$\Pr\left[|G_k| > 2^{r(\lambda)} : k \leftarrow \mathsf{KeyGen}(1^{\lambda})\right] = \sum_{k \in T} \Pr[k],$$

which is negligible since $\delta(\lambda) + r(\lambda) \ge C\lambda$, for some C > 1.

We are now ready to show the main theorem of this section.

Theorem 5.2. For any constant D > 0 the following holds. If δ -exponentially secure IV-OWSGs exist with $\delta(\lambda) \ge (0.5 + D)\lambda$, then EFI pairs exist.

Proof. Assume that an IV-OWSG (KeyGen, StateGen, Ver) exists. By Corollary 2.8, it suffices to show that there exists a canonical quantum bit commitment scheme that is statistically $(1 - 1/\text{poly}(\lambda))$ -hiding and computationally binding. To prepare the construction of the bit commitment scheme, we make the following structural observations:

- Without loss of generality, we may assume that the KeyGen algorithm applies a QPT unitary to generate a superposition $\sum_k \sqrt{\Pr[k]} |k\rangle |\text{junk}_k\rangle$, measures the first register, and outputs the result.
- Similarly, we can assume that the StateGen(k) algorithm applies a QPT unitary to generate a pure state $|\Phi_k\rangle_{\mathbf{A},\mathbf{B}}$ and outputs the register \mathbf{A} , which is in state $\phi_k = \text{Tr}_{\mathbf{B}}(|\Phi_k\rangle\langle\Phi_k|_{\mathbf{A},\mathbf{B}})$.

Let $\mathcal{H} := \{h : \mathcal{X} \to \mathcal{Y}\}$ be a family of pairwise independent hash functions such that $\mathcal{X} := \{0, 1\}^{\lambda}$ and $\mathcal{Y} := \{1, \dots, 2\lfloor 2^{r(\lambda)} \rfloor\}$, where $r(\lambda) := (0.5 + \frac{D}{2})\lambda$. Let us also denote by $t(\lambda)$ a polynomial that will be chosen later in the proof. Then we can define the following two states, which we shall think of being the commitments of 0 and 1, respectively:

$$|\psi_{0}\rangle_{\mathbf{R},\mathbf{C}} \coloneqq \sum_{k} \sum_{h \in \mathcal{H}} \sqrt{\frac{\Pr[k]}{|\mathcal{H}|}} |k, \operatorname{junk}_{k}, h\rangle_{\mathbf{C}_{1}} |h, h(k)\rangle_{\mathbf{R}_{1}} |\Phi_{k}^{\otimes t(\lambda)}\rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} |0...0\rangle_{\mathbf{R}_{3}}$$

$$|\psi_1\rangle_{\mathbf{R},\mathbf{C}} \coloneqq \sum_k \sum_{h\in\mathcal{H}} \sqrt{\frac{\Pr[k]}{|\mathcal{H}|}} |k, \operatorname{junk}_k, h\rangle_{\mathbf{C}_1} |h, h(k)\rangle_{\mathbf{R}_1} |\Phi_k^{\otimes t(\lambda)}\rangle_{\mathbf{C}_2,\mathbf{R}_2} |k\rangle_{\mathbf{R}_3},$$

where $\Pr[k] \coloneqq \Pr[k \leftarrow \mathsf{KeyGen}(1^{\lambda})]$. We denote by $\mathbf{C} \coloneqq (\mathbf{C}_1, \mathbf{C}_2)$ the commitment register and by $\mathbf{R} \coloneqq (\mathbf{R}_1, \mathbf{R}_2, \mathbf{R}_3)$ the reveal register. Note that $\mathbf{C}_2 \coloneqq (\mathbf{B}_1, \dots, \mathbf{B}_t)$ and $\mathbf{R}_2 \coloneqq (\mathbf{A}_1, \dots, \mathbf{A}_t)$, where the *j*-th copy of $|\Phi_k\rangle$ lives on registers $\mathbf{A}_j, \mathbf{B}_j$. By construction, both $|\psi_0\rangle$ and $|\psi_1\rangle$ can be generated by QPT unitaries. In the following we show that the scheme is statistically $(1-1/\mathsf{poly}(\lambda))$ hiding and computationally binding.

Computational binding. Towards a contradiction, we assume that our construction is not computationally binding. This means that there exists a polynomial $q = q(\lambda)$, an advice quantum state $|\tau\rangle_{\mathbf{Z}}$ on a polynomially-sized register \mathbf{Z} , and a non-uniform QPT unitary U acting on \mathbf{R} and \mathbf{Z} such that

$$\|\langle \psi_1|_{\mathbf{C},\mathbf{R}} \left(I_{\mathbf{C}} \otimes U_{\mathbf{R},\mathbf{Z}}\right) \left(|\psi_0\rangle_{\mathbf{C},\mathbf{R}} \otimes |\tau\rangle_{\mathbf{Z}}\right)\|^2 \ge \frac{1}{q(\lambda)}$$

for infinitely many λ . This means that, abbreviating $t = t(\lambda)$,

$$\frac{1}{q(\lambda)} \leq \left\| \sum_{k,h} \frac{\Pr[k]}{|\mathcal{H}|} \langle h, h(k) |_{\mathbf{R}_{1}} \langle \Phi_{k}^{\otimes t} |_{\mathbf{C}_{2},\mathbf{R}_{2}} \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\|^{2} \\
\leq \left(\sum_{k,h} \frac{\Pr[k]}{|\mathcal{H}|} \left\| \langle h, h(k) |_{\mathbf{R}_{1}} \langle \Phi_{k}^{\otimes t} |_{\mathbf{C}_{2},\mathbf{R}_{2}} \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\| \right)^{2} \\
\leq \sum_{k,h} \frac{\Pr[k]}{|\mathcal{H}|} \left\| \langle h, h(k) |_{\mathbf{R}_{1}} \langle \Phi_{k}^{\otimes t} |_{\mathbf{C}_{2},\mathbf{R}_{2}} \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\|^{2} \\
\leq \sum_{k,h} \frac{\Pr[k]}{|\mathcal{H}|} \left\| \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\|^{2} \\
\leq \sum_{k \in G,h} \frac{\Pr[k]}{|\mathcal{H}|} \left\| \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\|^{2} \\
\leq \sum_{k \in G,h} \frac{\Pr[k]}{|\mathcal{H}|} \left\| \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\|^{2} \\
\leq \sum_{k \in G,h} \frac{\Pr[k]}{|\mathcal{H}|} \left\| \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\|^{2} \\
\leq \sum_{k \in G,h} \frac{\Pr[k]}{|\mathcal{H}|} \left\| \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\|^{2} \\
\leq \sum_{k \in G,h} \frac{\Pr[k]}{|\mathcal{H}|} \left\| \langle k |_{\mathbf{R}_{3}} (I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}}) | h, h(k) \rangle_{\mathbf{R}_{1}} | \Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} | 0...0 \rangle_{\mathbf{R}_{3}} | \tau \rangle_{\mathbf{Z}} \right\|^{2} + \operatorname{negl}(\lambda). \tag{5.2}$$

Here, in the second inequality we have used the triangle inequality, and in the third inequality we have used Jensen's inequality. G is a set defined as

$$G \coloneqq \left\{ k \in \{0,1\}^{\lambda} : \Pr[\top \leftarrow \operatorname{Ver}(k,\phi_k)] \ge \frac{1}{2} \right\}.$$
(5.3)

Due to the correctness of the IV-OWSG, we have $\sum_{k \notin G} \Pr[k] \leq \operatorname{\mathsf{negl}}(\lambda)$.

From such $|\tau\rangle$ and U, we can construct a non-uniform QPT adversary \mathcal{A} that breaks the security of the IV-OWSG as follows:

- 1. The algorithm gets as input the \mathbf{R}_2 register of $|\Phi_k^{\otimes t}\rangle_{\mathbf{C}_2,\mathbf{R}_2}$ and the \mathbf{Z} register containing the advice state $|\tau\rangle_{\mathbf{Z}}$.
- 2. Choose $h \leftarrow \mathcal{H}$. Choose $y \leftarrow \mathcal{Y}$.
- 3. Apply $(I_{\mathbf{C}_2} \otimes U_{\mathbf{R},\mathbf{Z}})$ on $|h,y\rangle_{\mathbf{R}_1} |\Phi_k^{\otimes t}\rangle_{\mathbf{C}_2,\mathbf{R}_2} |0...0\rangle_{\mathbf{R}_3} |\tau\rangle_{\mathbf{Z}}$.
- 4. Measure the register \mathbf{R}_3 in the computational basis, and output the result.

The probability that \mathcal{A} outputs k and $k \in G$ can then be lower bounded as

$$\begin{split} &\Pr\left[k \in G \land k \leftarrow \mathcal{A}(1^{\lambda}, \phi_{k}^{\otimes t(\lambda)}) \ : \ k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \ \phi_{k} \leftarrow \mathsf{StateGen}(k)\right] \\ &= \sum_{k \in G} \Pr[k] \sum_{h,y} \frac{1}{|\mathcal{H}| \cdot |\mathcal{Y}|} \left\| \langle k|_{\mathbf{R}_{3}} \left(I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}} \right) |h, y \rangle_{\mathbf{R}_{1}} |\Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} |0...0\rangle_{\mathbf{R}_{3}} |\tau \rangle_{\mathbf{Z}} \right\|^{2} \\ &= \sum_{k \in G, h} \frac{\Pr[k]}{|\mathcal{H}|} \sum_{y} \frac{1}{2\lfloor 2^{r(\lambda)} \rfloor} \left\| \langle k|_{\mathbf{R}_{3}} \left(I_{\mathbf{C}_{2}} \otimes U_{\mathbf{R},\mathbf{Z}} \right) |h, y \rangle_{\mathbf{R}_{1}} |\Phi_{k}^{\otimes t} \rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} |0...0\rangle_{\mathbf{R}_{3}} |\tau \rangle_{\mathbf{Z}} \right\|^{2} \\ &\geq \sum_{k \in G, h} \frac{\Pr[k]}{|\mathcal{H}|} \frac{1}{2\lfloor 2^{r(\lambda)} \rfloor} \left\| \langle k|_{\mathbf{R}_{3}} \left(I_{\mathbf{C}_{3}} \otimes U_{\mathbf{R},\mathbf{Z}} \right) |h, h(k)\rangle_{\mathbf{R}_{1}} |\Phi_{k}^{\otimes t}\rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} |0...0\rangle_{\mathbf{R}_{3}} |\tau \rangle_{\mathbf{Z}} \right\|^{2} \\ &\geq \frac{1}{4q(\lambda) \lfloor 2^{r(\lambda)} \rfloor}, \end{split}$$

where the first inequality is obtained by only keeping the term y = h(k), and the last inequality is from Equation (5.2). Hence, the probability that \mathcal{A} wins is lowerbounded by $\frac{1}{8q(\lambda)\lfloor 2^{r(\lambda)} \rfloor}$.

We claim that this is larger than $2^{-\delta(\lambda)}$, in contradiction to the δ -exponential security of the IV-OWSG. Indeed, we have

$$\frac{1}{8q(\lambda)\lfloor 2^{r(\lambda)}\rfloor} - \frac{1}{2^{\delta(\lambda)}} = \frac{2^{\delta(\lambda)} - 8q(\lambda)\lfloor 2^{r(\lambda)}\rfloor}{8q(\lambda)2^{\delta(\lambda)}\lfloor 2^{r(\lambda)}\rfloor} \ge \frac{2^{\delta(\lambda)} - 8q(\lambda)2^{r(\lambda)}}{8q(\lambda)2^{\delta(\lambda)}\lfloor 2^{r(\lambda)}\rfloor} \ge \frac{2^{(0.5+D)\lambda} - 8q(\lambda)2^{(0.5+\frac{D}{2})\lambda}}{8q(\lambda)2^{\delta(\lambda)}\lfloor 2^{r(\lambda)}\rfloor} > 0$$

for infinitely many λ . Thus we have obtained the desired contradiction, and we may conclude that our bit commitment scheme is computationally binding.

Statistical hiding. We first describe an (inefficient) algorithm that, given $|h, h(k)\rangle_{\mathbf{R}_1}$ and the \mathbf{R}_2 register of $|\Phi_k^{\otimes t(\lambda)}\rangle_{\mathbf{C}_2,\mathbf{R}_2}$, for $k \leftarrow \mathsf{KeyGen}(1^{\lambda})$ and $h \leftarrow \mathcal{H}$, outputs the key k with not too small probability:

- 1. Apply the shadow tomography procedure on the \mathbf{R}_2 register of $|\Phi_k^{\otimes t(\lambda)}\rangle_{\mathbf{C}_2,\mathbf{R}_2}$ to obtain an estimate $b_{k'}$ of $\Pr[\top \leftarrow \operatorname{Ver}(k',\phi_k)]$ with additive error $\varepsilon = 1/8$ for all $k' \in \{0,1\}^{\lambda}$, with failure probability at most $\omega = 2^{-\lambda}$. Compute the list $\mathcal{L} := \{k' \in \{0,1\}^{\lambda} : b_{k'} \geq 3/4\}$.
- 2. Read (h, h(k)) from \mathbf{R}_1 . Compute h(k') for each k' in the list \mathcal{L} . If there is only a single k^* in the list such that $h(k^*) = h(k)$, output k^* . Otherwise, output \perp .

By Theorem 2.3, the first step is possible if we choose $t(\lambda)$ to be a large enough polynomial. Then, with probability at least $1 - \omega = 1 - \operatorname{negl}(\lambda)$, the list \mathcal{L} computed in the first step satisfies

$$\left\{k' \in \{0,1\}^{\lambda} : \Pr[\top \leftarrow \operatorname{Ver}(k',\phi_k)] \ge \frac{7}{8}\right\} \subseteq \mathcal{L} \subseteq G_k,$$
(5.4)

where $G_k = \{k' \in \{0, 1\}^{\lambda} : \Pr[\top \leftarrow \mathsf{Ver}(k', \phi_k)] \ge \frac{1}{2}\}$ is the set defined in Lemma 5.1. By the correctness of the IV-OWSG, it holds that, except for a negligible fraction of k, $\Pr[\top \leftarrow \mathsf{Ver}(k, \phi_k)] \ge \frac{7}{8}$ holds for sufficiently large λ , in which case the first inclusion implies that $k \in \mathcal{L}$. This means that we have

$$\Pr\left[k \in \mathcal{L} \subseteq G_k : k \leftarrow \mathsf{KeyGen}(1^{\lambda})\right] \ge 1 - \mathsf{negl}(\lambda).$$
(5.5)

We claim that the second step will return k with not too small probability. To see this, we first note that for any fixed set $G \subseteq \{0,1\}^{\lambda}$ and for any fixed $x \in G$, it holds that

$$\Pr_{h \leftarrow \mathcal{H}} \left[|G \cap h^{-1}(h(x))| = 1 \right] = 1 - \Pr_{h \leftarrow \mathcal{H}} \left[\bigvee_{x' \in G, x' \neq x} h(x') = h(x) \right]$$
$$\geq 1 - \sum_{x' \in G, x' \neq x} \Pr_{h \leftarrow \mathcal{H}} \left[h(x') = h(x) \right] = 1 - \frac{|G| - 1}{|\mathcal{Y}|}$$

due to the pairwise independence of the family of hash functions and the union bound. Thus,

$$\begin{split} &\Pr\left[\mathcal{L} \cap h^{-1}(h(k)) = \{k\} : k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \ h \leftarrow \mathcal{H}\right] \\ &= \Pr\left[|\mathcal{L} \cap h^{-1}(h(k))| = 1, \ k \in \mathcal{L} : \ k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \ h \leftarrow \mathcal{H}\right] \\ &\geq \Pr\left[|G_k \cap h^{-1}(h(k))| = 1, \ k \in \mathcal{L} \subseteq G_k : \ k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \ h \leftarrow \mathcal{H}\right] \\ &\geq \Pr_{h \leftarrow \mathcal{H}}\left[|G_k \cap h^{-1}(h(k))| = 1, \ k \in G_k : \ k \leftarrow \mathsf{KeyGen}(1^{\lambda})\right] (1 - \mathsf{negl}(\lambda)) \\ &\geq \Pr_{h \leftarrow \mathcal{H}}\left[|G_k \cap h^{-1}(h(k))| = 1, \ k \in G_k, \ |G_k| \le 2^{r(\lambda)} : \ k \leftarrow \mathsf{KeyGen}(1^{\lambda})\right] (1 - \mathsf{negl}(\lambda)) \\ &\geq \Pr_{h \leftarrow \mathcal{H}}\left[|G_k \cap h^{-1}(h(k))| = 1 : \ k \leftarrow \mathsf{KeyGen}(1^{\lambda}), \ k \in G_k, \ |G_k| \le 2^{r(\lambda)}\right] (1 - \mathsf{negl}(\lambda))^2 \\ &\geq \left(1 - \frac{2^{r(\lambda)} - 1}{2\lfloor 2^{r(\lambda)}\rfloor}\right) (1 - \mathsf{negl}(\lambda)) \ge \frac{1}{2} - \mathsf{negl}(\lambda), \end{split}$$

where the second inequality uses Equation (5.5) and the fact that h and \mathcal{L} are independent conditioned on k, the fourth inequality uses Lemma 5.1, and the last line follows from the bound derived above. We conclude that the algorithm returns the correct key with probability at least $\frac{1}{2} - \operatorname{negl}(\lambda)$.

We may summarize the above as saying that there exists an (inefficient) POVM measurement $\{\Pi_{\mathbf{R}_1,\mathbf{R}_2}^{(\alpha)}\}_{\alpha\in\{0,1\}^{\lambda}\cup\{\perp\}}$ such that

$$\sum_{k}\sum_{h\in\mathcal{H}}\frac{\Pr[k]}{|\mathcal{H}|}\langle h,h(k)|_{\mathbf{R}_{1}}\langle\Phi_{k}^{\otimes t(\lambda)}|_{\mathbf{C}_{2},\mathbf{R}_{2}}\Pi_{\mathbf{R}_{1},\mathbf{R}_{2}}^{(k)}|h,h(k)\rangle_{\mathbf{R}_{1}}|\Phi_{k}^{\otimes t(\lambda)}\rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} \geq \frac{1}{2}-\operatorname{\mathsf{negl}}(\lambda).$$
(5.6)

This implies that there is an (inefficient) unitary $U_{\mathbf{G},\mathbf{Z}}$ that sends $|\psi_0\rangle_{\mathbf{R},\mathbf{C}} |0\rangle_{\mathbf{Z}}$ to a state with not too small overlap with $|\psi_1\rangle_{\mathbf{R},\mathbf{C}} |0\rangle_{\mathbf{Z}}$. To see this, choose a unitary $V_{\mathbf{R}_1,\mathbf{R}_2,\mathbf{Z}}$ that extends the Naimark dilation $V_{\mathbf{R}_1,\mathbf{R}_2,\mathbf{Z}} |0\rangle_{\mathbf{Z}} = \sum_{\alpha} (\Pi_{\mathbf{R}_1,\mathbf{R}_2}^{(\alpha)})^{1/2} \otimes |\alpha\rangle_{\mathbf{Z}}$ of the POVM measurement, and define $U_{\mathbf{G},\mathbf{Z}} \coloneqq V_{\mathbf{R}_1,\mathbf{R}_2,\mathbf{Z}}^{\dagger} CNOT_{\mathbf{Z}\to\mathbf{R}_3} V_{\mathbf{R}_1,\mathbf{R}_2,\mathbf{Z}}$. Then it holds that

$$\langle \psi_1 |_{\mathbf{R}, \mathbf{C}} \langle 0 |_{\mathbf{Z}} U_{\mathbf{R}, \mathbf{Z}} | \psi_0 \rangle_{\mathbf{R}, \mathbf{C}} | 0 \rangle_{\mathbf{Z}}$$

$$\begin{split} &= \sum_{k} \sum_{h \in \mathcal{H}} \frac{\Pr[k]}{|\mathcal{H}|} \left\langle h, h(k) \right|_{\mathbf{R}_{1}} \left\langle \Phi_{k}^{\otimes t(\lambda)} \right|_{\mathbf{C}_{2},\mathbf{R}_{2}} \left\langle k \right|_{\mathbf{R}_{3}} \left\langle 0 \right|_{\mathbf{Z}} U_{\mathbf{R},\mathbf{Z}} \left| h, h(k) \right\rangle_{\mathbf{R}_{1}} \left| \Phi_{k}^{\otimes t(\lambda)} \right\rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} \left| 0 \right\rangle_{\mathbf{R}_{3}} \left| 0 \right\rangle_{\mathbf{Z}} \\ &= \sum_{k} \sum_{h \in \mathcal{H}} \frac{\Pr[k]}{|\mathcal{H}|} \sum_{\alpha,\beta} \left\langle h, h(k) \right|_{\mathbf{R}_{1}} \left\langle \Phi_{k}^{\otimes t(\lambda)} \right|_{\mathbf{C}_{2},\mathbf{R}_{2}} \sqrt{\Pi_{\mathbf{R}_{1},\mathbf{R}_{2}}^{(\alpha)}} \left\langle \alpha, k \right|_{\mathbf{Z},\mathbf{R}_{3}} \operatorname{CNOT}_{\mathbf{Z} \to \mathbf{R}_{3}} \left| \beta, 0 \right\rangle_{\mathbf{Z},\mathbf{R}_{3}} \\ &\quad \sqrt{\Pi_{\mathbf{R}_{1},\mathbf{R}_{2}}^{(\beta)}} \left| h, h(k) \right\rangle_{\mathbf{R}_{1}} \left| \Phi_{k}^{\otimes t(\lambda)} \right\rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} \\ &= \sum_{k} \sum_{h \in \mathcal{H}} \frac{\Pr[k]}{|\mathcal{H}|} \left\langle h, h(k) \right|_{\mathbf{R}_{1}} \left\langle \Phi_{k}^{\otimes t(\lambda)} \right|_{\mathbf{C}_{2},\mathbf{R}_{2}} \Pi_{\mathbf{R}_{1},\mathbf{R}_{2}}^{(k)} \left| h, h(k) \right\rangle_{\mathbf{R}_{1}} \left| \Phi_{k}^{\otimes t(\lambda)} \right\rangle_{\mathbf{C}_{2},\mathbf{R}_{2}} \\ &\geq \frac{1}{2} - \operatorname{negl}(\lambda), \end{split}$$

where the last step is due to Equation (5.6). Hence

$$\left| \langle \psi_1 |_{\mathbf{R}, \mathbf{C}} \langle 0 |_{\mathbf{Z}} U_{\mathbf{R}, \mathbf{Z}} | \psi_1 \rangle_{\mathbf{R}, \mathbf{C}} | 0 \rangle_{\mathbf{Z}} \right|^2 \ge \frac{1}{4} - \mathsf{negl}(\lambda).$$

By Uhlmann's theorem, it follows that the reduced states $\rho_b \coloneqq \text{Tr}_{\mathbf{R}}(|\psi_b\rangle\langle\psi_b|_{\mathbf{R},\mathbf{C}})$ have fidelity

$$F(\rho_0,\rho_1) \ge \frac{1}{4} - \operatorname{negl}(\lambda),$$

and hence their trace distance is at most

$$\mathsf{TD}(\rho_0, \rho_1) \leq \sqrt{\frac{3}{4}} + \mathsf{negl}(\lambda).$$

In view of Equation (2.1) this implies that the scheme is statistically $(\sqrt{\frac{3}{4}} + \mathsf{negl}(\lambda))$ -hiding, which in particular means that it is statistically $(1 - 1/\mathsf{poly}(\lambda))$ -hiding. This completes the proof of Theorem 5.2.

Acknowledgements

GM was supported by the European Research Council through an ERC Starting Grant (Grant agreement No. 101077455, ObfusQation). GM and MW acknowledge support by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy - EXC 2092 CASA - 390781972. MW also acknowledges support by the European Research Council through an ERC Starting Grant (grant agreement No. 101040907, SYMOPTIC), by the NWO through grant OCENW.KLEIN.267, and by the BMBF through project Quantum Methods and Benchmarks for Resource Allocation (QuBRA). TM is supported by JST CREST JP-MJCR23I3, JST Moonshot JPMJMS2061-5-1-1, JST FOREST, MEXT QLEAP, the Grant-in Aid for Transformative Research Areas (A) 21H05183, and the Grant-in-Aid for Scientific Research (A) No.22H00522.

References

[Aar19] Scott Aaronson. Shadow tomography of quantum states. SIAM J. Comput., 49(5):STOC18-368, 2019. (Cited on page 3, 4, 5.)

- [AQY22] Prabhanjan Ananth, Luowen Qian, and Henry Yuen. Cryptography from pseudorandom quantum states. LNCS, pages 208–236. Springer, Heidelberg, 2022. (Cited on page 2.)
- [BCQ23] Zvika Brakerski, Ran Canetti, and Luowen Qian. On the computational hardness needed for quantum cryptography. ITCS 2023, 2023. (Cited on page 2, 3, 5.)
- [BQSY23] John Bostanci, Luowen Qian, Nicholas Spooner, and Henry Yuen. An efficient quantum parallel repetition theorem and applications, 2023. (Cited on page 6.)
- [CLS01] Claude Crépeau, Frédéric Légaré, and Louis Salvail. How to convert the flavor of a quantum bit commitment. In Birgit Pfitzmann, editor, *EUROCRYPT 2001*, volume 2045 of *LNCS*, pages 60–77. Springer, Heidelberg, May 2001. (Cited on page 6.)
- [GJMZ23] Sam Gunn, Nathan Ju, Fermi Ma, and Mark Zhandry. Commitments to quantum states. In Barna Saha and Rocco A. Servedio, editors, Proceedings of the 55th Annual ACM Symposium on Theory of Computing, STOC 2023, Orlando, FL, USA, June 20-23, 2023, pages 1579–1588. ACM, 2023. (Cited on page 6.)
- [Gol90] Oded Goldreich. A note on computational indistinguishability. Information Processing Letters 34.6 (1990), pp.277–281., 1990. (Cited on page 2.)
- [HKNY23] Taiga Hiroka, Fuyuki Kitagawa, Ryo Nishimaki, and Takashi Yamakawa. Robust combiners and universal constructions for quantum cryptography, 2023. (Cited on page 6.)
- [HMY23] Minki Hhan, Tomoyuki Morimae, and Takashi Yamakawa. From the hardness of detecting superpositions to cryptography: Quantum public key encryption and commitments. LNCS, pages 639–667. Springer, Heidelberg, 2023. (Cited on page 6.)
- [IL89] Russell Impagliazzo and Michael Luby. One-way functions are essential for complexity based cryptography (extended abstract). In 30th FOCS, pages 230–235. IEEE Computer Society Press, October / November 1989. (Cited on page 1.)
- [ILL89] Russell Impagliazzo, Leonid A. Levin, and Michael Luby. Pseudo-random generation from one-way functions (extended abstracts). In 21st ACM STOC, pages 12–24. ACM Press, May 1989. (Cited on page 1.)
- [JLS18] Zhengfeng Ji, Yi-Kai Liu, and Fang Song. Pseudorandom quantum states. In Hovav Shacham and Alexandra Boldyreva, editors, *CRYPTO 2018, Part III*, volume 10993 of *LNCS*, pages 126–152. Springer, Heidelberg, August 2018. (Cited on page 2.)
- [KQST23] William Kretschmer, Luowen Qian, Makrand Sinha, and Avishay Tal. Quantum cryptography in algorithmica. STOC, 2023. (Cited on page 2.)
- [Kre21] W. Kretschmer. Quantum pseudorandomness and classical complexity. *TQC 2021*, 2021. (Cited on page 2.)
- [KT23] Dakshita Khurana and Kabir Tomer. Commitments from quantum one-wayness. Cryptology ePrint Archive, Paper 2023/1620, 2023. https://eprint.iacr.org/2023/1620. (Cited on page 2, 3.)

- [LMW23] Alex Lombardi, Fermi Ma, and John Wright. A one-query lower bound for unitary synthesis and breaking quantum cryptography. Cryptology ePrint Archive, Paper 2023/1602, 2023. https://eprint.iacr.org/2023/1602. (Cited on page 2.)
- [LR86] Michael Luby and Charles Rackoff. Pseudo-random permutation generators and cryptographic composition. In 18th ACM STOC, pages 356–363. ACM Press, May 1986. (Cited on page 1.)
- Takashi [MY22a] Tomoyuki Morimae and Yamakawa. **One-wayness** in quantum cryptography. Cryptology ePrint Archive, Paper 2022/1336,2022.https://eprint.iacr.org/2022/1336. (Cited on page 2, 7, 8.)
- [MY22b] Tomoyuki Morimae and Takashi Yamakawa. Quantum commitments and signatures without one-way functions. LNCS, pages 269–295. Springer, Heidelberg, 2022. (Cited on page 2, 7.)
- [Yan22] Jun Yan. General properties of quantum bit commitments (extended abstract). LNCS, pages 628–657. Springer, Heidelberg, 2022. (Cited on page 2, 3, 5, 6.)