Three-Dimension Collision-Free Trajectory Planning of UAVs Based on ADS-B Information in Low-Altitude Urban Airspace

Chao Dong, Yifan Zhang, Ziye Jia, Yiyang Liao, Lei Zhang, and Qihui Wu

Abstract—The environment of low-altitude urban airspace is complex and variable due to numerous obstacles, non-cooperative aircrafts, and birds. Unmanned aerial vehicles (UAVs) leveraging environmental information to achieve three-dimension collisionfree trajectory planning is the prerequisite to ensure airspace security. However, the timely information of surrounding situation is difficult to acquire by UAVs, which further brings security risks. As a mature technology leveraged in traditional civil aviation, the automatic dependent surveillance-broadcast (ADS-B) realizes continuous surveillance of the information of aircrafts. Consequently, we leverage ADS-B for surveillance and information broadcasting, and divide the aerial airspace into multiple sub-airspaces to improve flight safety in UAV trajectory planning. In detail, we propose the secure sub-airspaces planning (SSP) algorithm and particle swarm optimization rapidly-exploring random trees (PSO-RRT) algorithm for the UAV trajectory planning in law-altitude airspace. The performance of the proposed algorithm is verified by simulations and the results show that SSP reduces both the maximum number of UAVs in the sub-airspace and the length of the trajectory, and PSO-RRT reduces the cost of UAV trajectory in the sub-airspace.

Index Terms—Three dimension trajectory planning of UAV, collision avoidance, sliding window, ADS-B, low-altitude urban airspace.

I. INTRODUCTION

W ITH the advantages of high mobility and low cost, unmanned aerial vehicles (UAVs) are capable of many tasks such as air surveillance [1]–[3], freight delivering [4], auxiliary communication [5], [6] and computation [7], and disaster rescue [8]. Compared with other ground vehicles, the trajectories of UAVs are more flexible [9]. Besides, UAVs are able to select efficient trajectories to complete required

Chao Dong, Yifan Zhang, Yiyang Liao, Lei Zhang and Qihui Wu are with the College of Electronic and Information Engineering, Nanjing University of Aeronautics and Astronautics, Nanjing 211106, China (e-mail: dch@nuaa.edu.cn; yi-fanzhang123@nuaa.edu.cn; liaoyiyang@nuaa.edu.cn; Zhang_lei@nuaa.edu.cn; wuqihui@nuaa.edu.cn;).

Ziye Jia is with the College of Electronic and Information Engineering, Nanjing University of Aeronautics and Astronautics, Nanjing 211106, China, and also with the National Mobile Communications Research Laboratory, Southeast University, Nanjing 211111, China (e-mail: jiaziye@nuaa.edu.cn).

Corresponding author: Ziye Jia.

tasks. UAVs are extensively utilized in low-altitude urban airspace owing to their cost-effectiveness, adaptability, and maneuverability. However, due to the limitation of endurance of UAVs, it is necessary to plan a collision-free trajectory within the energy constraints [10]. Furthermore, the incorrect acquisition of position information of UAVs may cause collisions with obstacles, which is unacceptable for low-altitude urban airspaces. The low-altitude urban airspace is characterized by a complex and variable environment [11], featuring unforeseen events such as birds and non-cooperative UAVs. Due to limited environment perception of UAVs, the groundassisted-airspace safety assessment becomes imperative, which requires swift information exchange among UAVs and ground surveillance agencies. Considering the above factors, the UAV must strategically plan a safe and viable trajectory within the energy constraints to fulfill the assigned task based on real-time airspace situational information during task execution.

A well-designed airspace division enhances the efficiency of UAV management systems. Drawing inspirations from the airspace corridors utilized by conventional civil aviation aircraft [12], [13], the airspace of UAV can also be divided into multiple designated tubes. By adhering to the pre-planned tubes, UAVs significantly reduce the probability of collision with obstacles. However, tubes lack flexibility and struggle to accommodate a large number of UAVs. An alternative approach to airspace division is stratification, which vertically segregates the airspace into distinct layers. This approach allows the airspace to accommodate more UAVs [14], but may compromise safety and operational efficiency [15]. Dividing the airspace into discrete grids is another commonly used method [16]. The grid approach allows for sequential traversal from initial to destination airspace, making it suitable for UAVs capable of vertical takeoff and landing. Compared with the tube method, the grid method leads to a higher collision probability, but this method effectively increases the number of UAVs that can be accommodated in the airspace. Additionally, it offers greater adaptability in UAV trajectory selection by refining airspace at the same altitude. In this paper, in order to make full use of the agility of UAVs, we divide the low-altitude urban airspace into multiple sub-airspaces.

As a mature technology employed in civil aviation surveillance, the automatic dependent surveillance broadcast (ADS-B) has the advantages of fast message update, low cost and rich

This work was supported in part by the National Key R&D Program of China 2022YFB3104502, in part by National Natural Science Foundation of China under Grant 62301251, in part by the Natural Science Foundation of Jiangsu Province of China under Project BK20220883, in part by the open research fund of National Mobile Communications Research Laboratory, Southeast University (No. 2024D04), and in part by the Young Elite Scientists Sponsorship Program by CAST 2023QNRC001.

information, the UAV enhances its airspace perception [31], enabling the acquisition of vital information and facilitating applications such as obstacle avoidance. In this paper, ADS-B device is equipped for UAVs to enhance the information acquisition and environmental perception capabilities.

A key prerequisite for UAVs to complete service tasks in low-altitude urban airspace is to plan a safe trajectory from the starting point to the endpoint without collisions [18]. Traditional trajectory planning methods include the artificial potential field (APF) [19], A^{*} [20] and Dijkstra [21], and these methods are widely used in the trajectory planning of UAV in urban airspace. APF is commonly used for aircraft trajectory planning. In [22], the area around the destination is set as the gravitational field, and various types of obstacles are set as the repulsive field to incite collision during UAVs flight. Both Dijkstra and A* are efficient in searching the trajectory between the start and the destination [47]. Intelligent algorithm is another way to find the trajectory in the airspace, such as genetic algorithm (GA), ant colony optimization (ACO) [24] and particle swarm optimization (PSO) [25]. GA simulates the genetic mechanism and natural evolution of organisms in nature. ACO and PSO simulate the process of ant colony and bird flock to obtain food, respectively. These algorithms use the bionic mechanism of biological individuals or clusters to find trajectories and avoid collisions, which are simple to be implemented and have better optimization effect. As a sampling-based trajectory planning method, rapidly-exploring random trees (RRT), bidirectional rapidly-exploring random trees (Bi-RRT) and RRT* are often used in trajectory planning [26], [27]. These algorithms find a collision-free trajectory by randomly generating trajectory points and performing the shortest trajectory update and timely collision detection. However, much of the existing research focuses on the two-dimensional trajectory planning of UAVs, which makes it difficult to fully leverage the high maneuverability advantage of UAVs. This paper considers the variation of the UAV in the vertical direction during trajectory planning, making it more closely aligned with real-world scenarios.

In this work, RRT and Bi-RRT are leveraged as the basic trajectory search algorithms, which are combined with the PSO algorithm to optimize the trajectory. The main contributions of this paper are summarized as follows:

- 1) We divide the airspace into grids and utilize ADS-B as information source for UAVs to obtain airspace status information. Meanwhile, ground stations broadcast information about sudden obstacles to UAVs via ADS-B, allowing for trajectory readjustment.
- 2) We propose a secure sub-airspaces planning (SSP) algorithm based on dynamic programming, sliding window, and attraction mechanism for trajectory planning among sub-airspaces for UAVs. The coarse-grained trajectory is dynamically adjusted based on the status of airspace, reducing the maximum number of UAVs in the subairspace.
- 3) We design the particle swarm optimization-rapidly random trees (PSO-RRT) algorithm for trajectory planning

2

within the sub-airspace, which considers both efficiency and cost to ensure safety and reduce energy consumption in UAV trajectories. The performance of PSO-RRT is sufficiently demonstrated via simulation results.

The organization of this paper is as follows: Section II introduces the related research works. In Section III, the problem expatiation and designed algorithms are presented. Section IV provides the simulation results. Finally, the conclusion is drawn in Section V.

II. RELATED WORKS

There exist a couple of researches focusing on UAV trajectory planning conducted by researchers. In this work, we primarily focus on three interconnected research fields: the integration of UAVs and ADS-B systems, airspace design for UAVs and UAV trajectory planning.

ADS-B enhances the situational awareness ability of UAVs in low-altitude airspace and the surveillance ability of ground stations. [28] studies the cooperative perception and avoidance among UAVs equipped with ADS-B, proposes a planning algorithm based on RRT, and the simulation results show that in frontal encounter conflict, the UAV equipped with the RRT based algorithm successfully realizes the conflict resolution by leveraging ADS-B. In the context of UAV trajectory prediction, [29] proposes a centralized UAV trajectory surveillance architecture with ADS-B in low-altitude airspace, and predicts the ADS-B trajectory. The long short-term memory (LSTM) is leveraged to train the UAV ADS-B information, and the simulation results reveal that the proposed algorithm has higher prediction accuracy by leveraging ADS-B information. In [30], the safety of utilizing ADS-B in UAVs is investigated, and an algorithm for distinguishing fake UAV ADS-B information is proposed, ensuring the data security of UAVs. The utilization of ADS-B for trajectory monitoring and planning on UAVs shows potential, but there exist limited researches specifically focusing on utilizing UAV ADS-B data for trajectory planning.

In the domain of civil aviation, the division of airspace holds the potential to augment both flight safety and airspace utilization for aircrafts. Hence, the airspace division can also enhance the efficiency and safety of UAVs. [33] proposes an airspace grid division model based on GPS signals and wind strength, which effectively enhances the utilization of airspace. [34] divides the urban airspace into multiple grids and adjusts their sizes based on the degree of danger, enabling risk avoidance in UAV trajectory planning. [35] subdivides the urban airspace into a series of grids and utilizes a designed cost function for UAV trajectory planning among grids. The results demonstrate that in various application scenarios, grids significantly enhance the airspace utilization of UAVs. [36] models the urban infrastructure in the three-dimensional airspace and conducts comparative experiments on trajectory planning using three methods: grid, tube, and trajectory points. The results demonstrated that compared with the other algorithms, the grid method has the highest UAV capacity and throughput. In conclusion, the grid method strikes a balance between efficiency and safety in UAV trajectory planning.

In the scenario of cargo transportation by UAVs in urban airspace, [37] redesigns the cost estimation function of A* to enable the planned trajectory to consider both the efficiency and cost of goods delivery, thus achieving rapid trajectory planning. In [38], according to the changes in the airspace, trajectory planning is performed using the A* and RRT* algorithms, respectively. When the airspace situation is stable, the UAV utilizes the A* algorithm. However, when the airspace changes and the original trajectory becomes invalid, the trajectory is optimized by adjusting the selection probability and range of trajectory points in the RRT* algorithm to adapt to the changing airspace. Although traditional methods are easy to implement, the planned trajectories tend to be rigid, making it difficult to fully leverage the advantages of agile flight for UAVs.

RRT and its variants efficiently compute collision-free trajectories within specified airspace. In the context of unknown environmental information and unavailable GPS signals, [42] explores the application of RRT* for small UAVs in locating the source of hazardous chemical leaks. By leveraging the utilization and exploration mechanism, RRT* generates candidate trajectories limited to the sensor's sensing range which optimizes computational resources and enables realtime trajectory planning. [43] aims to swiftly determine shorter UAV flight trajectories within the airspace, this study utilizes the RRT algorithm based on a greedy approach for trajectory planning to minimize unnecessary bends. The algorithm reduces search complexity and requires only a few trajectory points. In densely populated low-altitude airspace with static and dynamic obstacles, [44] models static threats and predicts dynamic threats using the RRT algorithm. By employing this model, the RRT* algorithm is utilized for trajectory planning in complex airspace. The algorithm exhibits a high obstacle penetration rate. However, the RRT algorithm and variants are known for randomness, making it challenging to find the optimal trajectory within the airspace for UAVs.

As an important part of intelligent algorithm, PSO has been applied in UAV trajectory planning. [39] combines simulated annealing and PSO to realize autonomous trajectory planning of UAVs. The random disturbance mechanism of simulated annealing algorithm is used to assist PSO to jump out of local minimum value and avoid falling into local optimum. The simulation results show that the algorithm has higher trajectory quality. [40] leverages PSO to generate the UAV trajectory in complex three-dimensional environment. The results show that the PSO algorithm satisfies the requirements of real-time trajectory planning for UAVs. Based on the above analysis, PSO demonstrates excellent performance in solving optimization problems related to UAV trajectories.

III. PROBLEM EXPATIATION AND ALGORITHM DESIGN

In this section, the low-altitude urban airspace is divided into multiple sub-airspaces, and the SSP algorithm is proposed to achieve trajectory planning among sub-airspaces. The PSO-



Fig. 1. Scenario and airspace division.

RRT algorithm is also designed to achieve trajectory planning within each sub-airspace.

A. Airspace division

Airspace division is beneficial for UAVs in low-altitude urban airspace. It enables better warning and avoidance of conflicts with obstacles. Additionally, when planning UAV trajectories, only obstacles within the current sub-airspace need to be considered, which reduces complexity compared to considering all obstacles in the entire airspace. On the left side of Fig. 1, the airspace where the UAV U_i works is designated as a large area A, which contains buildings of different heights and ADS-B ground stations. UAV U_i only provides services to users within airspace A, which means U_i will not fly out of the boundaries of A. On the right side of Fig. 1, A is divided into interconnected, independent, and equally sized multi-layer grid sub-airspace $SA = SA_1, SA_2, ..., SA_n, ..., SA_N, A_x$ is the number of sub-airspaces in the x direction, A_y is the number of sub-airspaces in the y direction, and A_z is the number of subairspaces in the z direction. The number of the grids is in the order of x direction first and then y direction layer by layer. In Fig. 1, the number of sub-airspaces in all three directions is 5, which means the airspace A is divided into 125 sub-airspaces.

B. Trajectory planning

The UAV trajectory planning consists of two main parts. Firstly, the UAV utilizes SSP for trajectory planning among subairspaces to find continuous coarse-grained trajectory CS = $\{CS_1, CS_2, ..., CS_m, ..., CS_M\}$, a coarse-grained trajectory consists of M continuous sub-airspaces. CS_1 and CS_M are respectively indicate the starting sub-airspace and the destination sub-airspace. Subsequently, a fine-grained trajectory planning is performed by PSO-RRT within each specific sub-airspace in CS. This paper assumes that the UAV possesses positional information of all buildings in A and can determine its current position coordinates P_i using an onboard positioning system, and the destination coordinates, P_e . UAVs in airspace A are equipped with ADS-B IN and ADS-B OUT devices, allowing for broadcasting and receiving ADS-B messages, respectively. Since ADS-B can periodically and automatically broadcast the current positioning information of UAVs, UAVs leverage the position information broadcasted by other UAVs within the airspace and sudden obstacle information broadcasted by ground surveillance agencies to conduct trajectory planning between sub-airspaces and trajectory re-planning in sub-airspace.

1) Trajectory planning among sub-airspaces: The UAV U_i utilizes the SSP algorithm to search for CS and executes two steps. Firstly, U_i determines the starting sub-airspace CS_1 and the destination sub-airspace CS_M based on coordinating P_i and P_e . Then, leveraging dynamic programming, U_i plans a coarsegrained trajectory CS composed of sub-airspace between CS_1 and CS_M . In Fig. 1, the CS_1 and CS_{11} of U_i are respectively SA_{102} and SA_{24} , and the continuous red sub-airspaces represent CS. CS can achieve a multitude of combination possibilities by utilizing different sub-airspaces. Therefore, it is necessary to establish evaluation criterias for comparisons. In formula (1), CT_n denotes the cost of U_i in sub-airspace SA_n , O_n denotes the number of static obstacles in SA_n , and AEC_n denotes the number of UAVs in SA_n . k1 and k2 are polynomials, in particular, k1 + k2 = 1, k1, k2 > 0, and $k1 \gg k2$:

$$CT_n = k1 \cdot O_n + k2 \cdot AEC_n. \tag{1}$$

The function expressed by formula (2) serves as a quantitative measure for evaluating the performance of different CSconfigurations:

$$CT_{sn} = \sum_{i=1}^{N} CT_i.$$
 (2)

Subsequently, the sub-airspaces in CS are optimized in problem $\mathcal{P}0$ to minimize the associated cost:

$$\mathscr{P}0: \min_{CS} CT_{sn} \tag{3}$$

To reduce the probability of collision, a sliding window is designed as a component in the SSP algorithm. In detail, the working process of the sliding window for trajectory planning among sub-airspaces is illustrated in Fig. 2. When U_i enters SA_{27} , formula (2) and dynamic programming algorithm are utilized to obtain the new CS. The sub-airspaces SA_{27} , SA_{32} , SA_{31} , and SA_6 within the blue dashed area are selected as the sliding window when U_i enters SA_{32} . When U_i moves from SA_{27} to SA_{32} , maintaining SA_{32} , SA_{31} , and SA_6 in the sliding window. formula (2) and dynamic programming algorithm are employed again to obtain the new CS. The subairspaces within the red solid box are selected as the sliding window when UAV U_i enters SA_{32} . This process of sliding the sub-airspace window is repeated when UAV U_i enters a new sub-airspace, until there are less than four sub-airspaces remained. The length for the sliding window needs to be carefully determined. When the length is too large, it will result in a delay in perceiving the overall spatial situation, which is not conducive to avoiding sub-airspaces with a large number of UAVs. Conversely, when the length is too small, in Fig. 2, the length of sliding window is 1. When UAV U_i enters SA_{32} ,



Fig. 2. The sliding window in SSP.

the endpoint will lie on the plane between SA_{32} and SA_{31} . the position could be P1 or P2. If the endpoint of U_i is P1, it leads to a long path in SA_{31} , which means more energy consumption and higher probability of conflicts. However, when the length of sliding window is 4, the endpoint P2 is determined by attraction mechanism. P2 shortens the trajectory in SA_{31} , which results in energy savings and lower probability of conflicts. Therefore, a window length of 4 is set for SSP to achieve a balance among computational power, energy consumption, and safety.

The endpoint position of a sub-airspace will affect the trajectory length of U_i . In order to shorten the trajectory length and save energy consumption, the SSP leverages an attraction mechanism which attracts the endpoint on the basis of sliding windows. The plane where the endpoint belongs is divided into different regions according to the direction of the sub-airspaces in sliding window. If two directions of the sub-airspace in the sliding window change, as shown in Fig. 3, the plane is divided into four areas. According to the change in the direction of the sub-airspaces, the endpoint can be limited to one area which shorten the length of trajectory in next sub-airspace. If only one direction of the sub-airspace in the sliding window changes, the plane will be divided into two parts, which still have certain performance improvement compared with completely randomly finding the endpoint. If the direction has no change, the selection of the endpoint is completely random, and the attraction mechanism will lose effect.

2) Trajectory planning in sub-airspace: After finding coarse grained trajectory CS for UAV U_i , more precise trajectory planning needs to be performed within the sub-airspace. In order to make full use of the advantages of PSO and Bi-RRT, PSO-RRT algorithm is formulated for U_i to achieve quickly locating the trajectory points of UAVs while keeping them away from obstacles.

The distance between UAV U_i and obstacles needs to keep a safe range to ensure safe flight. Therefore, it is necessary to model the obstacles to calculate the distance between them. The obstacles can be divided into the static obstacle and sudden



The direction changes only Once.





Fig. 4. Obstacle models in sub-airspace.

obstacle. The red cuboid in Fig. 4 represents a static obstacle, which mainly includes ground buildings. The space of static obstacle can be divided into two layers. The top layer consists of 9 sub-spaces, while the bottom layer, excluding the obstacle itself, has 8 sub-spaces, resulting in a total of 17 subspaces. UAV swarms, as typical multi-agent systems, rely on cooperation among individual agents for collision avoidance [49] and the implementation of optimal control [48] to effectively address UAV conflict avoidance. Another method to achieve collisionfree flights between UAVs is to define the flight range of the evading UAV as a sudden obstacle. Sudden obstacles appear within the same sub-airspace of UAVs, such as birds and noncooperative UAVs. In Fig. 4, different from the static obstacles, the sudden obstacles are divided into three layers, with each layer respectively containing 9, 8, and 9 subspaces, and in total 26 subspaces. The method for calculating the distance between the UAV and the sudden obstacle is the same as the static obstacle. The size and position of the sudden obstacle may change, and this model facilitates observation and dynamic adjustment of its range with flexibility.

In the trajectory planning process, obstacles are represented by their closest position to the airspace origin, with a length in the x-axis, y-axis, and z-axis. For example, ((2, 2, 0), 2, 3, 4) indicates that the obstacle's closest position to the airspace origin is (2, 2, 0), with a length of 2 meters in the x-axis, a length of 3 meters in the y-axis, and a length of 4 meters in the z-axis. The difference between sudden obstacles and static obstacles is that the coordinates of a sudden obstacle can have a z-value greater than 0, and the rest of the representation is



Fig. 5. Trajectory planning in sub-airspace.

the same as static obstacles.

The trajectory planning of UAV U_i in sub-airspace SA_n is shown in Fig. 5. The red cuboid $OBOB_n^1$, OB_n^2 and OB_n^3 represents static obstacle, while the yellow cuboid represents a sudden obstacle SO_n^1 , which is already appeared before U_i entering SA_n . The green points $P_n = p_1^n$, p_2^n , ..., p_j^n , ..., p_j^n are the planned trajectory points for U_i within the sub-airspace SA_n . Trajectory p_j^n point in p_n consists of three-dimensional coordinates $p_{j(x)}^n$, $p_{j(y)}^n$, and $p_{j(z)}^n$.

The vectors between two adjacent trajectory points in the x, y, and z directions are shown in formula (4) to formula (6). The horizontal vector and the distance between two adjacent trajectory points are represented by formula (7) and formula (8), respectively. The turning angle TA_n^i and the pitch angle PA_n^i of U_i in SA_n are obtained through formula (9) and formula (10).

$$TA_{n}^{i} = \arccos(\frac{\overrightarrow{p_{j+1(xy)}^{n}} \cdot \overrightarrow{p_{j(xy)}^{n}}}{|\overrightarrow{p_{j+1(xy)}^{n}}| \cdot |\overrightarrow{p_{j(xy)}^{n}}|}),$$
(4)

$$PA_n^i = \arcsin(\frac{q_{j+1(z)}^n}{L_j^{i+1}}),\tag{5}$$

$$\overrightarrow{p_{j(xy)}^{n}} = (q_{j(x)}^{n}, q_{j(y)}^{n}), \tag{6}$$

$$L_{j}^{j+1} = \sqrt{(q_{j+1(x)}^{n})^{2} + (q_{j+1(y)}^{n})^{2} + (q_{j+1(z)}^{n})^{2}}, \quad (7)$$

$$f_{j(x)}^{*} = p_{j(x)}^{*} - p_{j-1(x)}^{*},$$
(8)

$$p_{j(y)} = p_{j(y)} - p_{j-1(y)},$$
(9)

$$q_{j(z)}^{n} = p_{j(z)}^{n} - p_{j-1(z)}^{n}.$$
(10)

 U_i evaluates the cost of the planned trajectory in the subairspace through formula (11):

$$CSA_{n}^{i} = k3 \cdot \left(\frac{k5}{\sum_{j=1}^{O_{n}} lob_{n}^{j(e)}} + \frac{k6}{\sum_{j=1}^{M_{n}} lso_{n}^{j(e)}}\right) + k4 \cdot \sum_{j=1}^{q-1} L_{j}^{j+1},$$
(11)

where CSA_n^i is the cost function of U_i 's trajectory in SA_n . In formula (11), O_n denotes the number of static obstacles in SA_n , M_n denotes the number of sudden obstacles, $lob_n^{j(e)}$ indicates the distance between *j*th trajectory point of U_i and the *e*th static obstacle, and $lso_n^{j(e)}$ denotes the distance between *j*th trajectory point of U_i and the *e*th sudden obstacle. *J* is the number of trajectory points of U_i in SA_n . L_j^{j+1} denotes the distance between adjacent trajectory points p_j^n and p_j^{n+1} . k3, k4, k5, and k6 are coefficients, and if the number of static obstacles or sudden obstacles is 0, the parameters k5 or k6 are set as 0, respectively.

The positions of the trajectory points in P_n are optimized in problem $\mathscr{P}1$ to find a trajectory with the minimum cost:

$$\mathcal{P}1: \min_{P_{n}} CSA_{n}^{i}$$
(12)
s.t. $C1: L_{j}^{j+1} < l_{max},$
 $C2: \sum_{j=1}^{q-1} L_{j}^{j+1} < L_{max},$
 $C3: -TA_{max}^{i} < TA_{n}^{i} < TA_{max}^{i},$
 $C4: -PA_{max}^{i} < PA_{n}^{i} < PA_{max}^{i},$
 $C5: SA_{n(min)}^{x} < p_{j(x)}^{n} < SA_{n(max)}^{x},$
 $C6: SA_{n(min)}^{y} < p_{j(y)}^{n} < SA_{n(max)}^{y},$
 $C7: SA_{n(min)}^{z} < p_{j(z)}^{n} < SA_{n(max)}^{z}.$

In constraint C1, l_{max} denotes the maximum length between adjacent trajectory points, and in constraint C2, L_{max} denotes the maximum length of the trajectory in SA_n . In constraints C3 and C4, TA_{max} and PA_{max} denote the maximum turning angle and pitch angle between adjacent trajectory points, respectively, while TA_{min} and PA_{min} denote the minimum turning angle and pitch angle between adjacent trajectory points. Constraints C5, C6, and C7 denote the position range constraints that each trajectory point of the UAV needs to keep in safe ranges.

In the process of trajectory planning, it is necessary to consider both the distance between UAVs and obstacles and the length of the trajectory. The length of the trajectory indicates the energy consumption during UAV flight, while the distance between UAVs and obstacles represents the flight safety. PSO is an optimization algorithm inspired by the foraging behavior of birds. It has the fast convergence speed and simple implementation, which is effective in solving optimization problems. RRT is leveraged to find trajectories with no conflict within a specified range. It has fast computation speed and generates random trajectories. Bi-RRT is a variant of the RRT algorithm which adds a greedy mechanism in searching progress, enabling



Fig. 6. The process of PSO-RRT.

faster calculation of collision-free trajectories with shorter trajectory lengths. However, Bi-RRT makes the trajectory closer to the obstacles. In order to make full use of the advantages of PSO and Bi-RRT, we formulate PSO-RRT to achieve quickly locating the waypoints of UAVs while keeping them away from obstacles. Fig. 6 illustrates the proposed PSO-RRT algorithm for sub-airspace trajectory planning based on PSO, RRT, and Bi-RRT. Multiple RRT and Bi-RRT trajectories are planned within sub-airspace SA_n , which serve as input data for PSO. An additional trajectory connecting the starting point to the endpoint is added as another set of input data to prevent the RRT algorithm from missing the optimal obstacle-free trajectory. The input data is optimized employing the PSO, updating the individual best positions and global best positions of trajectory points in each UAV trajectory during each iteration. The iteration process continues until the entire optimization function converges or the maximum number of iterations is reached. PSO-RRT can make full use of the randomness of RRT, providing greater diversity in the input data. Bi-RRT provides trajectory data with shorter lengths for the optimization process. PSO quickly optimizes the input data, adjusts the position of trajectory points, and finds the UAV trajectory with the minimum cost within SA_n .

There are two situations in PSO-RRT when dealing with sudden obstacles. Firstly, when PSO-RRT is conducting trajectory planning, a sudden obstacle has already appeared. In such case, the treatment of sudden obstacles is the same as static obstacles. Secondly, while the UAV is flying within the sub-airspace, a sudden obstacle appears against the planned trajectory. In this



Fig. 7. Trajectory re-planning for sudden obstacles in SA_n . situation, it is necessary to re-plan the trajectory within the sub-airspace to avoid the conflict.

As shown in Fig. 7, when UAV U_i is flying within SA_n according to the pre-planned trajectory points, the surveillance center detects the occurrence of a sudden obstacle SO_n^q within SA_n . The surveillance center transmits the information of SO_n^q to the ground station and broadcasts it to airspace via ADS-B. Upon receiving this message, U_i in SA_n calculates whether there is a conflict with the planned trajectory of SO_n^q . If there is no conflict, U_i continues to fly according to the current trajectory. If there is a conflict with SO_n^q , a trajectory re-planning is required. In Fig. 7, the red trajectory points represent the points that U_i cannot reach due to conflicts, the yellow trajectory points are the two original trajectory points closest to the sudden obstacle SO_n^q , the green trajectory points are the original trajectory points planned before entering SA_n , and the blue trajectory points are the new trajectory points generated by re-planning. U_i leverages the two yellow trajectory points as the starting and ending points for trajectory re-planning in SA_n , and utilizes Bi-RRT to generate new blue trajectory points to avoid conflicts with SO_n^q .

IV. SIMULATION RESULTS

A. Trajectory planning in sub-airspace

The parameter settings in SA_n are shown in Table I, and the parameter settings of the PSO-RRT algorithm are shown in Table II.

The simulation results of cost function are shown in Fig. 8, in detail, there is at least one obstacle between the starting point and the endpoint of each esimulation. Each simulation leverages three algorithms to calculate their cost function values. The trajectories planned by RRT and Bi-RRT are the input data for PSO-RRT. It can be seen that the cost function value of the trajectory planned in each group of PSO-RRT is smaller than the cost function value of the trajectory planned by the trajectory planned by the trajectory planned by the trajectory planned by the two algorithms is leveraged as the input data and the PSO is leveraged to adjust the optimization result.

The top view and side view of the trajectory planned by the three algorithms in SA_n are respectively shown in Fig.

TABLE I PARAMETERS OF SUB-AIRSPACE.

Parameter	Value
$SA_{n(min)}^{x}, SA_{n(max)}^{x}$	0, 200
$SA_{n(min)}^{y}, SA_{n(max)}^{y}$	0, 200
$SA_{n(min)}^{z}, SA_{n(max)}^{z}$	0, 50
OB_n^1	((40, 50, 0), 50, 50, 100)
OB_n^2	((20, 120, 0), 30, 30, 100)
OB_n^3	((150, 125, 0), 30, 30, 100)
J	10
L_{max}	400m
l _{max}	40m
TA_{min}, TA_{max}	-60°, 60°
PA_{min}, PA_{max}	-45°, 45°

TABLE II PARAMETERS OF PSO-RRT.

Parameter	Value
Trajectory planned by RRT	15
Step size of RRT	10m
Trajectory planned by Bi-RRT	15
Step size of Bi-RRT	10m
Smooth points	5
Shortest straight trajectory	1
Maximum number of iterations	100
The weights of PSO	0.8
The coefficients $c1$ and $c2$ of PSO	1.4
The maximum velocity of particles	2.5
k3	0.8
k4	0.2
k5	100
k6	100

9a and Fig. 9b. The green trajectory in Fig. 9a is the smoothed trajectory planned by RRT. Since the algorithm planned by RRT has strong randomness, it may lead to a longer trajectory length. The yellow trajectory is planned by Bi-RRT. It is observed that due to its own unique trajectory length greedy mechanism, the trajectory is shorter than the other two algorithms. However, the shorter trajectory brings a more radical planning strategy, which means the trajectory is close to the obstacle, making U_i easy to collide with the obstacle if there exists an error in positioning. The blue trajectory is the trajectory planned by PSO-RRT for SA_n . Compared with the yellow and green trajectory, the blue one maintains a shorter trajectory length and avoids two obstacles between the second and sixth trajectory points, achieving a farther distance from the obstacle, which means that PSO-RRT considers the factors of security. Even if there is a deviation in positioning, it can still safely reach the endpoint through static obstacles.

Fig. 10 shows the relationship between cost function value and iterations in the planning process. At the beginning of the iteration, the minimum cost function value of all trajectories is 103.94. With the continuous increment of iterations, PSO constantly adjusts all trajectories until the final cost function value converges to 99.98, and the blue trajectory in Fig. 10 is obtained. Via the change process of fitness value, it is concluded that the trajectory obtained by final optimization must have a lower cost than the trajectory before optimization.

In Fig. 11, the UAV has planned the trajectory to be taken for



Fig. 8. Cost function values of simulation experiments.





Fig. 9. Trajectory planning in sub-airspace of simulation experiment 5.

the current sub-airspace, but the monitoring center observes that there exist sudden obstacles in the sub-airspace, and broadcasts the obstacle information to the airspace through the ADS-B ground station. After receiving the ADS-B information, the UAV in the sub-airspace detects that the fifth trajectory point is located in the sudden obstacle, resulting in the failure of the trajectory between the fourth trajectory point and the sixth



Fig. 10. Cost function value of PSO-RRT.



Fig. 11. Trajectory re-planning in sub-airspace.

trajectory point. Therefore, the sudden obstacle is added to the static obstacle list. Taking the coordinates of the fourth trajectory point as the starting point and the coordinates of the sixth trajectory point as the endpoint, Bi-RRT is leveraged to quickly re-plan the trajectory, and the re-planned trajectory is smoothed to replace the original conflict trajectory. When the UAV is located at the fourth trajectory point, the new trajectory is executed to avoid the yellow sudden obstacle.

B. Trajectory planning among sub-airspaces

After the whole airspace is divided, the trajectory planning is carried out to verify the effect of sliding window and attraction mechanism. The parameter settings of the experiment are shown in Table III.

The obstacle distribution of the whole airspace A in the experimental setting is shown in Fig. 12. SSP and three trajectory planning algorithms are employed with same environment settings. The sub-airspace in CS is: $(SA_1, SA_2, SA_{27}, SA_{32}, SA_{33}, SA_{34}, SA_{39}, SA_{44}, SA_{49})$. The black trajectory point is the trajectory planned by SSP and RRT, and the blue trajectory point is the trajectory planned by SSP and Bi-RRT. It is observed that the distance between the trajectory point and the obstacle is very close in the whole trajectory. The red point is the trajectory planned by SSP and PSO-RRT, and the trajectory point maintains a large distance from the obstacle.

parameter	value	
The lengths of A in Three dimensions	100,0m, 100,0m, 250m	
A_x, A_y, A_z	5, 5, 5	
Starting point	(0, 0, 0)	
endpoint	(750, 900, 80)	
Speed of UAVs	5m/s	
The number of obstacles	75	
Obstacle height range	[25, 240]	
k1	0.01	
k2	0.99	

TABLE III

PARAMETERS OF TRAJECTORY PLANNING IN AIRSPACE A.







In Fig. 13, we set the number of UAVs in airspace A as 50, and randomly generate 5 sets of starting points and endpoints for these UAVs. The trajectory between the starting point and the endpoint includes at least 5 sub-airspaces. Each set of simulations only leverages SSP and no sliding window method for UAVs. The trajectory of no sliding window is determined before take off. In the simulation, the maximum number of UAVs in the sub-airspace of the two trajectory planning methods during the entire UAV flight is recorded. It is observed that the maximum number of UAVs in the sub-





Fig. 14. The number of UAVs in each sub-airspace in simulation index 5.

space domain of SSP is smaller than that of trajectory planning without sliding window, which further guarantees the safety.

Fig. 14 is the distribution of the maximum number of UAVs in SA_1 to SA_{125} of the fifth index of simulations in Fig. 13, leveraging SSP and trajectory planning without sliding window. The maximum number of UAVs in the sub-airspace of SSP is 3, while the maximum number of UAVs in the sub-airspace without sliding window is 6, which are larger than the results of SSP. The reason is that the sliding window adjusts the subsequent sub-airspace trajectory according to the number of UAVs in the whole sub-airspace broadcast by ADS-B ground station when the UAV enters the new sub-airspace, which effectively reduces the maximum number of UAVs in each subairspace. The trajectory of no sliding window is fixed before the UAV takes off, so when the number of UAVs in the airspace is very large. The subsequent trajectory cannot be adjusted.

In Fig. 15, five sets of simulations are carried out and the first four are randomly generated. There are at least five subairspaces between the starting point and the endpoint. The fifth simulation is set specially, and its starting point and the endpoint are respectively SA_1 and SA_5 with no direction change. As shown in Fig. 15, in the first four groups of simulations, due to the change of direction among the sub-airspace trajectories, the attraction mechanism reduces the range of the sub-airspace endpoint in the trajectory planning process and reduces the total trajectory length. However, the trajectory planning without the attraction mechanism has a longer trajectory length because the endpoint in the sub-airspace is completely randomly selected.



Fig. 15. Trajectory lengths of different trajectory planning methods in airspace A.

In the fifth simulation, since there is no change in the direction of CS, the attraction mechanism fails, which is the same as the completely random search for the endpoint of the sub-airspace. Therefore, the length of the trajectory in the sub-airspace with the attraction mechanism is longer.

V. CONCLUSION AND FUTURE WORK

In this paper, in order to enhance the information acquisition and environmental perception capabilities, UAVs in low-altitude urban areas are equipped with ADS-B devices to achieve high-frequency information exchange. In order to enhance the safety and efficiency of UAVs, we divide the low-altitude urban airspace into multiple sub-airspaces, and leverage ADS-B to continuously monitor flight for each sub-airspace. On the basis of airspace division, we propose SSP algorithm based on dynamic programming, sliding window and attraction mechanism to conduct coarse-grained trajectory planning among sub-airspaces, and we propose the PSO-RRT algorithm for trajectory planning in sub-airspaces. The results of multiple simulations prove that the maximum number of UAVs in subairspaces and the total length of trajectory are both reduced by SSP. As for the trajectory planning in sub-airspace, the PSO-RRT algorithms reduce the cost of trajectory compared with the trajectory planned by RRT and Bi-RRT, which means the trajectory planned by PSO-RRT simultaneously considers both safety and efficiency. In conclusion, the collision-free trajectory planning for UAVs within the airspace has been successfully implemented by SSP and PSO-RRT with ADS-B information.

To further investigate the real-time performance, UAV peak values in airspace, and average computation time of the proposed algorithm, we just constructed a set of ADS-B OUT and ADS-B IN devices leveraging Raspberry Pi, positioning modules, and software-defined radio equipment to test the algorithm's performance. In addition, in future work, we will incorporate cooperation between UAVs into UAV conflict avoidance considerations, and consider the impact of NACv and NACp on ADS-B message reception, conducting more practical experiments for validation using the ADS-B devices we have constructed.

REFERENCES

- Y. Zhu, Z. Jia, Q. Wu, C. Dong, Z. Zhuang, H. Hu, and Q. Cai, "UAV trajectory tracking via RNN-enhanced IMM-KF with ADS-B data," *arXiv* preprint arXiv:2312.15721, 2023.
- [2] A. V. Savkin and H. Huang, "Bioinspired bearing only motion camouflage UAV guidance for covert video surveillance of a moving target," *IEEE Syst. J*, vol. 15, no. 4, pp. 5379–5382, 2021.
- [3] H. Huang, A. V. Savkin, and W. Ni, "Online UAV trajectory planning for covert video surveillance of mobile targets," *IEEE Trans. Autom. Sci. Eng*, vol. 19, no. 2, pp. 735–746, 2022.
- [4] W. Park, X. Wu, D. Lee, and S. J. Lee, "Design, modeling and control of a top-loading fully-actuated cargo transportation multirotor," *IEEE Rob. Autom. Lett*, vol. 8, no. 9, pp. 5807–5814, 2023.
- [5] Z. Jia, M. Sheng, J. Li, D. Niyato, and Z. Han, "LEO-satellite-assisted UAV: Joint trajectory and data collection for Internet of remote things in 6G aerial access networks," *IEEE Internet of Things Journal*, vol. 8, no. 12, pp. 9814–9826, 2021.
- [6] Z. Wang, J. Guo, Z. Chen, L. Yu, Y. Wang, and H. Rao, "Robust secure UAV relay-assisted cognitive communications with resource allocation and cooperative jamming," *J. Commun. Networks*, vol. 24, no. 2, pp. 139–153, 2022.
- [7] Z. Jia, Q. Wu, C. Dong, C. Yuen, and Z. Han, "Hierarchical aerial computing for Internet of things via cooperation of HAPs and UAVs," *IEEE Internet of Things Journal*, vol. 10, no. 7, pp. 5676–5688, 2023.
- [8] J. Xu, K. Ota, and M. Dong, "Big data on the fly: UAV-mounted mobile edge computing for disaster management," *IEEE Trans. Network Sci. Eng*, vol. 7, no. 4, pp. 2620–2630, 2020.
- [9] W. Kaifang, L. Bo, G. Xiaoguang, H. Zijian, and Y. Zhipeng, "A learningbased flexible autonomous motion control method for UAV in dynamic unknown environments," *J. Syst. Eng. Electron*, vol. 32, no. 6, pp. 1490– 1508, 2021.
- [10] H.-T. Ye, X. Kang, J. Joung, and Y.-C. Liang, "Optimization for wirelesspowered IoT networks enabled by an energy-limited UAV under practical energy consumption model," *IEEE Wireless Commun. Lett*, vol. 10, no. 3, pp. 567–571, 2021.
- [11] W. Yang, J. Tang, R. He, and Y. Chen, "A medium-term conflict detection and resolution method for open low-altitude city airspace based on temporally and spatially integrated strategies," *IEEE Trans. Control Syst. Technol*, vol. 28, no. 5, pp. 1817–1830, 2020.
- [12] M. Shanmugavel, A. Tsourdos, R. Zbikowski, and B. White, "3D path planning for multiple UAVs using pythagorean hodograph curves," in *AIAA Guidance, navigation and control conference and exhibit*, Hilton Head, South Carolina, USA, 2007.
- [13] R. Ehrmanntraut and S. McMillan, "Airspace design process for dynamic sectorisation," in 2007 IEEE/AIAA 26th Digital Avionics Systems Conference, Dallas, TX, USA, 2007.
- [14] J. M. Hoekstra, J. Maas, M. Tra, and E. Sunil, "How do layered airspace design parameters affect airspace capacity and safety?" in *7th international conference on research in air transportation*, Philadelphia, Pennsylvania, USA, 2016.
- [15] L. Sedov and V. Polishchuk, "Centralized and distributed UTM in layered airspace," in 8th International Conference on Research in Air Transportation, Castelldefels, Catalonia, Spain, 2018.
- [16] B. Pang, W. Dai, T. Ra, and K. H. Low, "A concept of airspace configuration and operational rules for UAS in current airspace," in 2020 AIAA/IEEE 39th Digital Avionics Systems Conference (DASC), San Antonio, TX, USA, 2020.
- [17] C. Wei and Y. Dai, "A design of communication interface of ADS-B for UAV," in 2014 Seventh International Symposium on Computational Intelligence and Design, vol. 1, Hangzhou, China, 2014.
- [18] J. Lee and V. Friderikos, "Interference-aware path planning optimization for multiple UAVs in beyond 5G networks," J. Commun. Networks, vol. 24, no. 2, pp. 125–138, 2022.
- [19] X. Yuan, Y. Hu, D. Li, and A. Schmeink, "Novel optimal trajectory design in UAV-assisted networks: A mechanical equivalence-based strategy," *IEEE J. Sel. Areas Commun*, vol. 39, no. 11, pp. 3524–3541, 2021.
- [20] Y. Cai, Q. Xi, X. Xing, H. Gui, and Q. Liu, "Path planning for UAV tracking target based on improved A-star algorithm," in 2019 1st International Conference on Industrial Artificial Intelligence (IAI), Shenyang, China, 2019.
- [21] M. T. S. Ibrahim, S. V. Ragavan, and S. Ponnambalam, "Way point based deliberative path planner for navigation," in 2009 IEEE/ASME In-

ternational Conference on Advanced Intelligent Mechatronics, Singapore, 2009.

- [22] M. Qian, Z. Wu, and B. Jiang, "Cerebellar model articulation neural network-based distributed fault tolerant tracking control with obstacle avoidance for fixed-wing UAVs," *IEEE Trans. Aerosp. Electron. Syst*, 2023.
- [23] Y. Pan, Y. Yang, and W. Li, "A deep learning trained by genetic algorithm to improve the efficiency of path planning for data collection with multi-UAV," *Ieee Access*, vol. 9, pp. 7994–8005, 2021.
- [24] J. Li, Y. Xiong, and J. She, "UAV path planning for target coverage task in dynamic environment," *IEEE Internet Things J*, 2023.
- [25] Y. Liu, H. Pan, G. Sun, A. Wang, J. Li, and S. Liang, "Joint scheduling and trajectory optimization of charging UAV in wireless rechargeable sensor networks," *IEEE Internet Things J*, vol. 9, no. 14, pp. 11796–11813, 2021.
- [26] L. Tan, Y. Zhang, J. Huo, and S. Song, "UAV path planning simulating drive's visual behavior with RRT algorithm," in 2019 Chinese Automation Congress (CAC), Hangzhou, China, 2019, pp. 219–223.
- [27] C. Jiang, Z. Hu, Z. P. Mourelatos, D. Gorsich, P. Jayakumar, Y. Fu, and M. Majcher, "R2-RRT*: Reliability-based robust mission planning of offroad autonomous ground vehicle under uncertain terrain environment," *IEEE Trans. Autom. Sci. Eng*, vol. 19, no. 2, pp. 1030–1046, 2021.
- [28] C. Zhao, J. Gu, J. Hu, Y. Lyu, and D. Wang, "Research on cooperative sense and avoid approaches based on ADS-B for unmanned aerial vehicle," in 2016 IEEE Chinese Guidance, Navigation and Control Conference (CGNCC), Nanjing, China, 2016.
- [29] Y. Zhang, Z. Jia, C. Dong, Y. Liu, L. Zhang, and Q. Wu, "Recurrent LSTM-based UAV trajectory prediction with ADS-B information," in *GLOBECOM 2022 - 2022 IEEE Global Communications Conference*, Rio de Janeiro, Brazil, 2022.
- [30] Z. P. Languell and Q. Gu, "Securing ADS-B with multi-point distancebounding for UAV collision avoidance," in 2019 IEEE 16th International Conference on Mobile Ad Hoc and Sensor Systems (MASS), Monterey, CA, USA, 2019.
- [31] Y. Liao, L. Zhang, Z. Jia, C. Dong, Y. Zhang, Q. Wu, H. Hu, and B. Wang, "Impact of UAVs equipped with ADS-B on the civil aviation monitoring system," in 2023 IEEE/CIC International Conference on Communications in China (ICCC), Dalian, China, 2023.
- [32] Z. Shen, X. Cheng, S. Zhou, X.-M. Tang, and H. Wang, "A dynamic airspace planning framework with ADS-B tracks for manned and unmanned aircraft at low-altitude sharing airspace," in 2017 IEEE/AIAA 36th Digital Avionics Systems Conference (DASC), St. Petersburg, FL, USA, 2017.
- [33] Q. Shao, R. Li, M. Dong, and C. Song, "An adaptive airspace model for quadcopters in urban air mobility," *IEEE Trans. Intell. Transp. Syst*, vol. 24, no. 2, pp. 1702–1711, 2023.
- [34] B. Pang, W. Dai, T. Ra, and K. H. Low, "A concept of airspace configuration and operational rules for UAS in current airspace," in 2020 AIAA/IEEE 39th Digital Avionics Systems Conference (DASC), San Antonio, TX, USA, 2020.
- [35] X. He, F. He, L. Li, L. Zhang, and G. Xiao, "A route network planning method for urban air delivery," *Transportation Research Part E: Logistics* and *Transportation Review*, vol. 166, p. 102872, 2022.
- [36] M. F. B. Mohamed Salleh, C. Wanchao, Z. Wang, S. Huang, D. Y. Tan, T. Huang, and K. H. Low, "Preliminary concept of adaptive urban airspace management for unmanned aircraft operations," in 2018 AIAA Information Systems-AIAA Infotech@ Aerospace, Kissimmee, Florida, USA, 2018.
- [37] B. Li, H. Zhang, L. Zhang, D. Feng, and Y. Fei, "Research on path planning and evaluation method of urban logistics UAV," in 2021 3rd International Academic Exchange Conference on Science and Technology Innovation (IAECST), Guangzhou, China, 2021.
- [38] Q. Zhou and G. Liu, "UAV path planning based on the combination of A-star algorithm and RRT-star algorithm," in 2022 IEEE International Conference on Unmanned Systems (ICUS), Guangzhou, China, 2022.
- [39] Z. Yu, Z. Si, X. Li, D. Wang, and H. Song, "A novel hybrid particle swarm optimization algorithm for path planning of UAVs," *IEEE Internet Things J*, vol. 9, no. 22, pp. 22547–22558, 2022.
- [40] V. Roberge, M. Tarbouchi, and G. Labonté, "Comparison of parallel genetic algorithm and particle swarm optimization for real-time UAV path planning," *IEEE Trans. Ind. Inf*, vol. 9, no. 1, pp. 132–141, 2012.
- [41] H. Zhang, X. Gan, S. Li, and Z. Chen, "UAV safe route planning based on PSO-BAS algorithm," J. Syst. Eng. Electron, vol. 33, no. 5, pp. 1151– 1160, 2022.

- [42] C. Rhodes, C. Liu, and W.-H. Chen, "Autonomous source term estimation in unknown environments: From a dual control concept to UAV deployment," *IEEE Rob. Autom. Lett*, vol. 7, no. 2, pp. 2274–2281, 2022.
- [43] J. Chang, N. Dong, D. Li, W. H. Ip, and K. L. Yung, "Skeleton extraction and greedy-algorithm-based path planning and its application in UAV trajectory tracking," *IEEE Trans. Aerosp. Electron. Syst*, vol. 58, no. 6, pp. 4953–4964, 2022.
- [44] N. Wen, L. Zhao, X. Su, and P. Ma, "UAV online path planning algorithm in a low altitude dangerous environment," *IEEE/CAA J. Autom. Sin*, vol. 2, no. 2, pp. 173–185, 2015.
- [45] R. Hoffman and J. Prete, "Principles of airspace tube design for dynamic airspace configuration," in *The 26th Congress of ICAS and 8th AIAA ATIO*, Anchorage, Alaska, USA, 2008.
- [46] E. Sunil, J. Hoekstra, J. Ellerbroek, F. Bussink, A. Vidosavljevic, D. Delahaye, and R. Aalmoes, "The influence of traffic structure on airspace capacity," in *7th International Conference on Research in Air Transportation*, vol. 4, Philadelphia, Pennsylvania, USA, 2016.
- [47] A. R. Soltani, H. Tawfik, J. Y. Goulermas, and T. Fernando, "Path planning in construction sites: performance evaluation of the Dijkstra, A, and GA search algorithms," *Adv. Eng. Inf*, vol. 16, no. 4, pp. 291–303, 2002.
- [48] J. Yu, X. Dong, Q. Li, J. Lü, and Z. Ren, "Adaptive practical optimal time-varying formation tracking control for disturbed high-order multiagent systems," *IEEE Trans. Circuits Syst. I Regul. Pap*, vol. 69, no. 6, pp. 2567–2578, 2022.
- [49] L. Dong, J. Yan, X. Yuan, H. He, and C. Sun, "Functional nonlinear model predictive control based on adaptive dynamic programming," *IEEE Trans. Cybern*, vol. 49, no. 12, pp. 4206–4218, 2019.