

Constructive Recognition of Special Linear Groups

Max Horn*

Alice C. Niemeyer[†]

Cheryl E. Praeger[‡]

Daniel Rademacher[§]

April 2023

Abstract

We introduce a new constructive recognition algorithm for finite special linear groups in their natural representation. Given a group G generated by a set of $d \times d$ matrices over a finite field $\mathbb{F}_q$, known to be isomorphic to the special linear group $\mathrm{SL}(d, q)$, the algorithm computes a special generating set S for G . These generators enable efficient computations with the input group, including solving the word problem. Implemented in the computer algebra system **GAP**, our algorithm outperforms existing state-of-the-art algorithms by a significant margin. A detailed complexity analysis of the algorithm will be presented in an upcoming publication.

1 Introduction

During the inaugural international conference “Computational Group Theory” held in Oberwolfach in 1988, Neubüser highlighted the necessity for efficient algorithms for working with matrix groups over finite fields. He challenged the audience to design an algorithm to determine whether a given finite set of $d \times d$ matrices over a finite field with q elements generates a group containing the special linear group $\mathrm{SL}(d, q)$.

Neubüser’s initial query was answered in 1992 by Peter Neumann and the third author [22]. During the three decades since, a research effort called *the Matrix Group Recognition Project* to design algorithms for matrix group computation has seen substantial progress, [28]. Numerous algorithms have been developed and implemented in computer algebra systems such as **GAP** [12] and **Magma** [4], enabling efficient manipulation of matrix groups of dimensions as large as several thousand.

The development of algorithms for matrix groups has followed two main approaches, often referred to as the soluble radical approach and the Composition Tree approach, the latter being the focus here. Both approaches have yielded significant breakthroughs, notably Babai, Beals and Seress [2] show that the soluble radical approach computes a data structure which allows to compute with a matrix group given abstractly as a black box group in randomized polynomial time, using oracles for factoring and discrete log. The Composition Tree method is described in [1, 23] and computes a data structure known as a *Composition Tree* for a given finite matrix group G . This composition tree serves as the fundamental tool for further computations with G , and exhibits a composition series of G . The complexity of this method has been shown to

*RPTU Kaiserslautern-Landau, Germany. email: mhorn@rptu.de

[†]RWTH Aachen University, Germany. email: alice.niemeyer@mathb.rwth-aachen.de

[‡]University of Western Australia, Australia. email: cheryl.praeger@uwa.edu.au

[§]RWTH Aachen University, Germany. email: rademacher@art.rwth-aachen.de

be polynomial the degree of the matrix group by Holt et al [18] if the composition tree avoids certain finite simple groups.

Given this remarkable progress the reader might wonder why we revisit a topic for which efficient algorithms already exist. Having efficient algorithms available is particularly crucial for groups closely related to the composition factors. As the classical groups yield infinite families of finite simple groups, improvements in algorithms for these groups cascade throughout the entire composition tree, amplifying their impact across the structure. Algorithms to compute a composition tree face two challenges when confronted with a matrix group: firstly, resolving the *naming problem*, which involves determining the finite simple group to which the given group is isomorphic, and secondly, tackling the *constructive recognition problem*. The constructive recognition problem takes as input a subgroup G of $\mathrm{GL}(d, q)$ known to be isomorphic to a particular almost simple group and aims to find an isomorphism to a standard copy of the almost simple group. Solutions to constructive recognition problems facilitate computations with the input group.

The constructive recognition problem we treat in this paper takes as input a subgroup G of $\mathrm{GL}(d, q)$ known to contain $\mathrm{SL}(d, q)$ and aims to find an isomorphism to a standard copy of $\mathrm{SL}(d, q)$. More precisely, we aim to compute a particular set of matrices, called *standard generators* in the standard copy of $\mathrm{SL}(d, q)$ as words in the generators of G .

Several algorithms have been developed to address the naming problem for classical groups, including [22, 26]. The initial algorithms devised to solve the constructive recognition problem for classical groups date back to 1995 [5]. Subsequently, numerous algorithms have been proposed [8, 11, 19, 20], with the current state-of-the-art algorithm being the one developed by Dietrich, Leedham-Green, Lübeck and O'Brien [10]. This algorithm descends recursively along a chain of subgroups, seeking at each step to construct a classical subgroup of roughly half the dimension.

Over a decade ago, our colleagues Ákos Seress and Max Neunhöffer proposed a novel approach to the constructive recognition problem for classical groups, based on the concept of elements that act irreducibly on a subspace of dimension roughly $\log(d)$ and fix pointwise a complementary subspace. We call such elements *stingray elements*. Ákos Seress asked the second and third authors to estimate the proportion of such elements in finite classical groups, see [25]. Moreover, he worked with Yalçinkaya and the third author on estimating the probability that a stingray element and its conjugate would generate a classical group of smaller dimension [29].

Despite their promising ideas, further development was halted following Seress's passing and Neunhöffer's departure from academia. We believed their ideas to be very promising and in a series of papers [13–17, 25] have paved the way for a complexity analysis of the algorithms presented here.

We present in this paper a new constructive recognition algorithm based on the theory of stingray elements tailored for the special linear groups in degree $d \geq 4$. Our algorithm demonstrates an unexpected speed and practical efficiency, outperforming the current state-of-the-art algorithm by a significant margin. In particular, we prove the following theorem.

Theorem 1.1. *Let $\langle X \rangle = G = \mathrm{SL}(d, q)$ and $\epsilon \in (0, 1)$. **StandardGenerators** is a one-sided Monte Carlo algorithm which given input G and ϵ outputs with probability at least $1 - \epsilon$ an MSLP $\mathfrak{S}$ and base change matrix $\mathcal{L}$ such that $\mathfrak{S}$ evaluates from $X^{\mathcal{L}}$ to the standard generators of $G^{\mathcal{L}}$.*

A detailed complexity analysis of our new algorithm is almost complete. We have also successfully adapted our method to the other families of classical groups. All of this will be presented in follow-up publications. In particular, we hope to establish the following result.

Conjecture 1.2. *The complexity of `StandardGenerators` as stated in [Theorem 4.5](#) is*

$$\mathcal{O}(d^3 \log(d) + d^2 \log(d) \log(\log(d)) \log(q) + \frac{\log(d)}{\log(\log(d))} \xi + \zeta(q))$$

where ξ denotes an upper bound on the number of field operations for computing a random element in $\text{SL}(d, q)$ and $\zeta(q)$ denotes an upper bound on the number of field operations for constructively recognising $\text{SL}(4, q)$.

Acknowledgements

The first, second and fourth authors acknowledge support by the German Research Foundation (DFG) – Project-ID 286237555 – within the SFB-TRR 195 “Symbolic Tools in Mathematics and their Applications”. The second and third author acknowledge the support of Australian Research Council Discovery program grant DP190100450 and the third author acknowledges the support of Australian Research Council Discovery program grant DP230101268.

Note that the content of this publication is a condensed version of some of the chapters in the fourth author’s Doctoral dissertation.

The fourth author thanks Eamonn O’Brien for his hospitality during a research stay at the University of Auckland, and many relevant discussions.

2 Preliminaries

Throughout this paper, we use the following notations:

- $q = p^f$ denotes a prime power.
- $\mathbb{F}_p$ and $\mathbb{F}_q$ are finite fields of order p resp. q .
- $(\omega_1, \dots, \omega_f)$ is an $\mathbb{F}_p$ -basis of $\mathbb{F}_q$.
- n and d are natural numbers satisfying $n \leq d$.
- By $E_{i,j}(\lambda)$ we denote an elementary matrix with entry (i, j) equal to λ .

Definition 2.1. Let V be a d -dimensional vector space with basis $\mathcal{B} = \{v_1, \dots, v_d\}$.

- $\langle \cdot | \cdot \rangle$ denotes the [standard scalar product](#) on V with respect to $\mathcal{B}$, i.e., $\langle \sum \lambda_i v_i, \sum \mu_i v_i \rangle = \sum \lambda_i \mu_i$.
- For $v, w \in V$ linearly independent, $T_{v,w}$ denotes the [transvection](#) $x \mapsto x + \langle x | v \rangle w$.

Note that the elementary matrix $E_{i,j}(\lambda)$ is equal to the matrix of the transvection $T_{\lambda v_i, v_j}$ with respect to $\mathcal{B}$.

Definition 2.2. Let k be a non-negative integer. The [iterated logarithm](#) $\log^*(k)$ is defined recursively as follows

$$\log^*(k) := \begin{cases} 0, & \text{if } k \leq 1 \text{ and} \\ 1 + \log^*(\log(k)), & \text{if } k > 1. \end{cases}$$

Definition 2.3. Let $S \subset \text{SL}(d, q)$. Then S is a set of [standard generators](#) for $\text{SL}(d, q)$ if S is conjugate to the following set consisting of $2f + 2$ elements:

- $E_{1,2}(\omega_i)$ for $1 \leq i \leq f$,
- $E_{2,1}(\omega_i)$ for $1 \leq i \leq f$,
- a permutation matrix z_1 corresponding to the permutation $(1, d, d-1, \dots, 2)$ with the entry $(z_1)_{1,d}$ changed to -1 if d is even and
- a permutation matrix z_2 corresponding to the permutation $(2, d, d-1, \dots, 3)$ with the entry $(z_2)_{2,d}$ changed to -1 if d is odd.

The (-1) -entries are introduced to ensure that the elements are contained in $\text{SL}(n, q)$.

A notation we use frequently throughout is the following.

Definition 2.4. Let $G \leq \text{GL}(d, q)$ and $U \leq G$. Then U is *stingray embedded of degree n in G* for $n \leq d$ if there exists a group $H \leq \text{GL}(n, q)$, a matrix $\mathcal{L} \in \text{GL}(d, q)$ and an isomorphism $\sigma_{\mathcal{L}}$ from H into $U^{\mathcal{L}}$ such that

$$\sigma_{\mathcal{L}}: H \rightarrow U^{\mathcal{L}}, \quad a \mapsto \text{diag}(a, I_{d-n}) = \begin{pmatrix} a & 0 \\ 0 & I_{d-n} \end{pmatrix}.$$

We denote a stingray embedding by

$$U^{\mathcal{L}} = \begin{pmatrix} H & 0 \\ 0 & I_{d-n} \end{pmatrix} \leq G^{\mathcal{L}}$$

where $G^{\mathcal{L}}$ is the conjugation by $\mathcal{L}$, i.e. $G^{\mathcal{L}} = \{\mathcal{L}^{-1}g\mathcal{L} \mid g \in G\}$.

Remark 2.5. A naming algorithm for a family of group (e.g. the family of all classical groups) takes as input a subset $X \subset \text{GL}(d, q)$ and decides whether the group $G = \langle X \rangle$ generated by X is isomorphic to a member of that family. This is also sometimes referred to as “non-constructive recognition”, as the group G is “recognized” to have a specific isomorphism type, but without actually constructing an isomorphism.

Some of the algorithms presented in this paper need to decide if G is equal (and not just isomorphic) to $\text{SL}(d, q)$. This can certainly be achieved using a naming algorithm for classical groups such as the ones presented in [22, 26].

Finally, we remark on some conventions we employ to enhance the readability of the algorithms we present.

Remark 2.6. The algorithms we present are randomised algorithms. They rely on a procedure to select elements from a group G which are nearly uniformly distributed and independent. Such an algorithm has been introduced by [3]. A practical version is presented in [6].

Remark 2.7. Some randomised algorithms described in this publication call other randomised algorithms. In order to bound the overall number of computed random elements, we use a “global” variable N . That means if a randomised algorithm A uses the variable N and calls a randomised algorithm B with input N , then A and B “share” the identical N , i.e. if N is decreased by B and B returns N , then the N of A is “updated” and thus also decreased. The variable N is very useful in this context to bound the maximal number of random elements computed by the input N .

Remark 2.8. Some algorithms of this publication call other randomised algorithms which can either return a valid output or **fail**. Whether an algorithm returns valid output or **fail** needs to be checked before the output is given as an argument to the next function. If a randomised algorithm A calls a randomised algorithm B and B returns **fail**, then A also terminates and returns **fail**. The check whether B returns **fail** requires an if statement in an implementation. To provide better readability of algorithms we sometimes omit this if-statement and refer to this remark instead.

Finally, we present proofs for the correctness of the algorithms we present. However, the complexity analysis of our algorithms will be published in a forthcoming paper. The reason for this is that many of the algorithms we present rely on various other results in the literature and drawing all of these together to present a complete complexity analysis would increase the length of this paper too much.

3 MSLP

Many of the algorithms in the literature store elements of a group as words in a given generating set in an efficient way, called a straight line program, namely as a word in certain subwords. In this section, we describe a modification to straight line programs, which also records the memory usage of a straight line program.

Definition 3.1. Let $G = \langle X \rangle$ be a group, $\mathfrak{b} \in \mathbb{N}_0$ and let $\mathcal{M} = [\mathfrak{m}_1, \dots, \mathfrak{m}_{\mathfrak{b}}]$ be an ordered list of $\mathfrak{b}$ elements of X such that $\langle \mathfrak{m}_1, \dots, \mathfrak{m}_{\mathfrak{b}} \rangle = G$. A *straight-line program with memory (MSLP)* is a sequence $\mathfrak{S} = [\mathcal{I}_1, \dots, \mathcal{I}_{\Upsilon}]$ of *instructions*, where for $1 \leq r \leq \Upsilon$ and $i, j, k \in \{1, \dots, \mathfrak{b}\}$

- (i) $\mathfrak{m}_k \leftarrow \mathfrak{m}_i$. This instruction stores $\mathfrak{m}_i$ in the list $\mathcal{M}$ in slot k .
- (ii) $\mathfrak{m}_k \leftarrow \mathfrak{m}_i \cdot \mathfrak{m}_j$. This instruction stores $\mathfrak{m}_i \cdot \mathfrak{m}_j$ in the list $\mathcal{M}$ in slot k .
- (iii) $\mathfrak{m}_k \leftarrow \mathfrak{m}_i^{-1}$. This instruction stores $\mathfrak{m}_i^{-1}$ in the list $\mathcal{M}$ in slot k .
- (iv) $\text{Show}(A)$ where $A \subseteq \{1, \dots, \mathfrak{b}\}$. The slots specified by A are displayed.

The number $\mathfrak{b} \in \mathbb{N}_0$ is the *memory quota* of $\mathfrak{S}$ and $\mathfrak{S}$ is a $\mathfrak{b}$ -MSLP. The number $\Upsilon \in \mathbb{N}_0$ is the length of $\mathfrak{S}$. The empty sequence is permitted with length 0.

The *evaluation of an MSLP* $\mathfrak{S}$ amounts to executing its instructions recursively. Suppose G is a group and X is a sequence of elements of G . If the memory $\mathcal{M}$ is initialised with the sequence X when $\mathfrak{S}$ is evaluated, then we say that $\mathfrak{S}$ is *evaluated in X* . The instruction $\text{Show}(A)$ can be employed to output multiple elements of G stored in one of the $\mathfrak{b}$ memory slots specified by A . For more details, see [24, Section 2].

In the evaluation process, $\mathcal{M}$ is used as memory for the elements that are needed. The instruction (i) of Definition 3.1 can be used to overwrite a slot and minimize the memory quota. The idea of an MSLP is to reduce the memory required for evaluating a particular word in a group by repeatedly overwriting memory slots which are no longer used. The length Υ of an MSLP describes the number of operations during the entire evaluation.

Remark 3.2. The instructions of Definition 3.1 use elements of $\{1, \dots, \mathfrak{b}\}$. The memory $\mathcal{M}$ is secondary in the description. This implies that an MSLP is independent of the group, i.e. $\text{Eval}_{\mathcal{M}}(\mathfrak{S})$ can be computed for every $\mathcal{M} \in G^{\mathfrak{b}}$ and every group G . Hence, it is possible to encode an element as a word in one group and to evaluate the constructed SLP in another group.

4 Outline of the algorithm

The goal of this section is to present an overview of the algorithm to recognise a special linear group constructively. The overarching algorithm is Algorithm **StandardGenerators**. This algorithm in turn relies on several subprocedures whose purpose is discussed here.

The input of Algorithm **StandardGenerators** is a set X with $X \subseteq \text{GL}(d, q)$ with $d > 4$ such that $G := \langle X \rangle = \text{SL}(d, q)$ is a special linear group in its natural representation. The output is

a matrix $\mathcal{L} \in \text{GL}(d, q)$ and an MSLP $\mathfrak{S}$ such that when $\mathfrak{S}$ is evaluated in $X^\mathcal{L}$, the output of $\mathfrak{S}$ is a particular generating set of $\text{SL}(d, q)^\mathcal{L}$, called the *standard generators* of $\text{SL}(d, q)^\mathcal{L}$. The definition of standard generators is given in [Definition 2.3](#).

Algorithm **StandardGenerators** calls three basic subalgorithms, namely:

- (1) Algorithm **GoingDown** is a one-sided Monte Carlo algorithm to construct a stingray embedded subgroup $\text{SL}(4, q)$ of G .
- (2) Algorithm **BaseCase** is a one-sided Monte Carlo algorithm to recognise $\text{SL}(4, q)$ constructively.
- (3) Algorithm **GoingUp** is a one-sided Monte Carlo algorithm to construct standard generators of G using the constructed standard generators of a stingray embedded subgroup $\text{SL}(4, q)$.

GoingDown algorithm

The input of Algorithm **GoingDown** is the set X described above. The output is a matrix $\mathcal{L} \in \text{GL}(d, q)$, an MSLP $\mathfrak{S}$ and a subgroup $\langle X_U \rangle = U \leq G$ with $U \cong \text{SL}(4, q)$ which is stingray embedded, that is

$$U^\mathcal{L} = \begin{pmatrix} \text{SL}(4, q) & 0 \\ 0 & I_{d-4} \end{pmatrix}.$$

Moreover, evaluating the MSLP $\mathfrak{S}$ in X yields the generators X_U of U .

Algorithm **GoingDown** is a randomised algorithm and relies on finding so-called *stingray elements* (see [Definition 5.2](#)) by random selection of elements of G . Therefore there is an additional input $N \in \mathbb{N}$ which is used as an upper bound for the maximal number of random selections. If the limit N is exceeded, then Algorithm **GoingDown** terminates returning **fail**. Moreover, Algorithm **GoingDown** is a one-sided Monte-Carlo algorithm, therefore we also discuss how to choose $N \in \mathbb{N}$ for a given $0 < \epsilon < 1$ such that the **GoingDown** algorithm succeeds with probability $1 - \epsilon$.

Algorithm **GoingDown** starts by setting $U_1 := G$, $d_1 := d$, $\mathcal{L}_1 := I_d$. then repeatedly calls the subroutine **GoingDownBasicStep** via

$$U_{i+1}, d_{i+1}, \mathcal{L}_{i+1}, \mathfrak{S}_{i+1}, N' := \text{GoingDownBasicStep}(U_i, d_i, \mathcal{L}_i, N),$$

where for $i > 1$ we assume that U_i is stingray embedded of degree d_i in U_{i-1} . The output satisfies that U_{i+1} is stingray embedded of degree d_{i+1} (and hence in G). Moreover, $d_{i+1} \leq 4\lceil \log(d_i) \rceil$. Next, $\mathcal{L}_{i+1} \in \text{GL}(d, q)$ is a base change matrix, and $\mathfrak{S}_{i+1}$ is an MSLP such that when $\mathfrak{S}_{i+1}$ is evaluated in the generators of U_i it returns generators of U_{i+1} . Finally, N' is equal to N minus the number of random selection performed by the subroutine, and is used as N for the next step. In summary, we have

$$U_{i+1}^{\mathcal{L}_{i+1}} = \begin{pmatrix} \text{SL}(d_{i+1}, q) & 0 \\ 0 & I_{d-d_{i+1}} \end{pmatrix} \leq G.$$

The subroutine **GoingDownBasicStep** is repeated until a group isomorphic to $\text{SL}(4, q)$ is reached. At this point we set $k := i + 1$ and return the descending chain

$$\text{SL}(4, q) \cong U_k \leq U_{k-1} \leq \dots \leq U_2 \leq U_1 = G = \text{SL}(d, q).$$

Since $d_{i+1} \leq 4\lceil \log(d_i) \rceil$ holds, k is roughly $\log^*(d)$, where $\log^*$ denotes the iterated logarithm, see [Definition 2.2](#). The descending chain thus computed is a *descending recognition chain* of G :

Definition 4.1. Let $\text{SL}(d, q)$ be a special linear group in its natural representation. Then a *descending recognition chain* of $\text{SL}(d, q)$ is a descending chain of subgroups

$$U_k \leq U_{k-1} \leq \dots \leq U_2 \leq U_1 = \text{SL}(d, q),$$

where $U_i \cong \text{SL}(d_i, q)$ is stingray embedded U_{i-1} (and thus in $\text{SL}(d, q)$) for $i > 1$, we have $d_{i+1} \leq 4\lceil \log(d_i) \rceil$ for all $1 \leq i < k$, and $d_k = 4$.

The basic step uses stingray elements (defined in [Section 5](#)) as follows: In U_i we seek two stingray elements $s_1, s_2 \in U_i$, using [FindStingrayElement](#) described in [Section 5](#). The elements are chosen such that $\langle s_1, s_2 \rangle \cong \text{SL}(d_{i+1}, q)$ holds with high probability. Then $\langle s_1, s_2 \rangle$ is automatically stingray embedded U_i (and thus in $\text{SL}(d, q)$), and hence we can define $U_{i+1} := \langle s_1, s_2 \rangle$. The base change matrix to achieve this block structure is also computed by the algorithms of [Section 5](#).

Since the basic step relies on finding stingray elements by randomised procedure, the [GoingDown](#) algorithm is a randomised algorithm. In fact, the [GoingDown](#) algorithm returns `fail` if it does not succeed after N random element selections of elements from U_i . The probability that the [GoingDown](#) algorithm succeeds relies completely on N . We analyse this dependency in a forthcoming paper.

Remark 4.2. It is not possible to reach $\text{SL}(2, q)$ using [GoingDownBasicStep](#) because the degrees d_i of $U_i \cong \text{SL}(d_i, q)$ are too small to find stingray elements generating special linear groups. Therefore, we terminate [GoingDownBasicStep](#) when we encounter $\text{SL}(4, q)$. See [Remark 6.4](#) for details.

Remark 4.3. Note that $\text{SL}(3, q)$ in its natural representation is also not handled by our algorithm, but for this case one can e.g. use [\[21\]](#).

BaseCase algorithm

The [BaseCase](#) algorithm is the second subalgorithm of the [StandardGenerators](#) algorithm. Let $G := \text{SL}(d, q)$ be the input of [StandardGenerators](#). Then the input of the [BaseCase](#) algorithm is a generating set X of a group $\text{SL}(4, q) \leq G$. Moreover, a base change matrix $\mathcal{L} \in \text{GL}(d, q)$ is known such that $\langle X \rangle^{\mathcal{L}}$ is stingray embedded with degree 4 in $G^{\mathcal{L}}$. Since the [BaseCase](#) algorithm is also randomised we again use N as additional input to restrict the maximal number of random element selections to N . The output of the [BaseCase](#) algorithm is an MSLP $\mathfrak{S}$ and a base change matrix $\mathcal{L}' \in \text{GL}(d, q)$ such that if $\mathfrak{S}$ is evaluated in $X^{\mathcal{L}'}$, the output are the standard generators of $\text{SL}(2, q)^{\mathcal{L}'}$ as in [Definition 2.3](#).

To do this, the [BaseCase](#) algorithm uses a simplified version of the [GoingDown](#) algorithm of [\[10, 20\]](#) to find a suitable $\text{SL}(2, q)$ subgroup. It then calls an efficient constructive recognition algorithm for $\text{SL}(2, q)$, e.g. the algorithm described in [\[7\]](#).

Properties of the [BaseCase](#) algorithms e.g. whether it is randomised or requires a discrete logarithm oracle depend on the choice of the constructive recognition algorithm for the base case group. Note that a constructive recognition algorithm employed for base case groups can readily be exchanged by another should a more efficient algorithm become available.

The state of the art algorithm for constructive recognition of $\text{SL}(2, q)$ is given in [\[7\]](#) which is a randomised algorithm and uses the discrete logarithm oracle. So far, it is unknown whether it is possible to recognise $\text{SL}(2, q)$ constructively without the discrete logarithm oracle.

As for the [GoingDown](#) algorithm the success of the [BaseCase](#) algorithm depends on the choice of N and for a given $\epsilon \in (0, 1)$ we can select N such that the [BaseCase](#) algorithm succeeds with probability at least $1 - \epsilon$. The choice of N of the [BaseCase](#) algorithm is not discussed in this publication, instead we refer to the literature, see [\[7\]](#).

GoingUp algorithm

The last subalgorithm of **StandardGenerators** is the **GoingUp** algorithm. The input of this algorithm is X with $\langle X \rangle = G = \text{SL}(d, q)$ in its natural representation and the standard generating set S of a stingray embedded subgroup $\langle S \rangle = H \leq G^{\mathcal{L}}$, where H is a base case group for a known base change matrix $\mathcal{L} \in \text{GL}(d, q)$. Moreover, MSLP are known to express the standard generators S of H as words in $X^{\mathcal{L}}$, i.e. a constructive recognition algorithm has been used on H . The **GoingUp** algorithm is also randomised and, therefore, we use N as input to allow at most N random element selections. The outputs of the **GoingUp** algorithm are an MSLP $\mathfrak{S}$ and a base change matrix $\mathcal{L}'$ such that, if $\mathfrak{S}$ is evaluated in $(S \cup X)^{\mathcal{L}\mathcal{L}'}$, the output are the standard generators of $G^{\mathcal{L}\mathcal{L}'} = \text{SL}(d, q)$.

Similar to the **GoingDown** algorithm, the **GoingUp** algorithm uses a basic step repeatedly until the standard generators of G have been constructed. The input of the **GoingUp** basic step are X and $\tilde{S}$ with $\langle \tilde{S} \rangle = \tilde{H} \leq G^{\tilde{\mathcal{L}}}$ where $\tilde{H} \cong \text{SL}(n, q)$ is stingray embedded into $\text{GL}(d, q)$ for a known base change matrix $\tilde{\mathcal{L}} \in \text{GL}(d, q)$. The standard generators $\tilde{S}$ of $\tilde{H}$ can be written as words in $X^{\tilde{\mathcal{L}}}$ and are encoded in an MSLP $\tilde{\mathfrak{S}}$. Moreover, the base change matrix $\tilde{\mathcal{L}}$ as well as N to control the maximal number of random element selections are additional inputs of the **GoingUp** basic step. The output of the **GoingUp** basic step is a base change matrix $\mathcal{L} \in \text{GL}(d, q)$ and MSLP which evaluates in $\tilde{S} \cup X$ to the standard generators of another stingray embedded special linear subgroup K of $G^{\mathcal{L}}$. Since the output of the **GoingUp** basic step is an MSLP evaluating to the standard generators of a subgroup of G we denote this by saying that the input of the i -th basic step is given by $X, S_i, \mathcal{L}_i$ and N and the output group is given by S_{i+1} and $\mathcal{L}_{i+1}$ with $\langle S_{i+1} \rangle = H_{(i+1)}$ resulting in

$$S_{i+1}, \mathcal{L}_{i+1} := \text{GoingUpStep}(X, S_i, \mathcal{L}_i, N).$$

Note that this is not completely accurate as the output is not directly S_{i+1} but rather is only an MSLP which evaluates to the standard generators S_{i+1} of $H_{(i+1)}$. We ignore this small inaccuracy since we know that the MSLP evaluates to S_{i+1} . So far we only noted that $H_{(i+1)} \leq G^{\mathcal{L}_{i+1}}$ holds but we know more about the output of the **GoingUp** basic step which is $H_{(i)}^{\mathcal{L}_i^{-1}} \leq H_{(i+1)}^{\mathcal{L}_{i+1}^{-1}} \leq G$ and $H_{(i+1)} \cong \text{SL}(n_{i+1}, q)$. By setting $H_{(0)} = H$ this yields a chain of subgroups called an *ascending recognition chain*

$$H = H_{(0)}^{\mathcal{L}_0^{-1}} \leq H_{(1)}^{\mathcal{L}_1^{-1}} \leq \dots \leq H_{(\ell-1)}^{\mathcal{L}_{\ell-1}^{-1}} \leq H_{(\ell)}^{\mathcal{L}_{\ell}^{-1}} = G^{\mathcal{L}_{\ell}^{-1}}.$$

In most cases the length of an ascending recognition chain is larger than the length of the descending recognition chain. Since the standard generators of each $H_{(i)}$ are known and $H_{(\ell)} = G$, the standard generators of G are constructed by the **GoingUp** algorithm.

The **GoingUp** basic step is more complicated than the **GoingDown** basic step and consists of seven phases. Therefore, we are not discussing the details of the **GoingUp** basic step in this section and refer to a detailed description in [Section 7](#). Instead we continue this section by displaying the input and output of the **GoingUp** basic step in matrix form.

Each of the $H_{(i)}$ is a stingray embedded special linear group, i.e.

$$H_{(i)} = \begin{pmatrix} \text{SL}(n_i, q) & 0 \\ 0 & I_{d-n} \end{pmatrix} \leq G^{\mathcal{L}_i}$$

and the standard generators of $H_{(i)}$ are known. The **GoingUp** basic step then proceeds roughly as follows. We identify an element $c \in G^{\mathcal{L}_i}$ such that

$$\langle H, H^c \rangle := \begin{pmatrix} \text{SL}(\mathcal{N}(d, n), q) & 0 \\ 0 & I_{d-\mathcal{N}(d, n)} \end{pmatrix} \leq G^{\mathcal{L}_{i+1}}$$

for a base change matrix $\mathcal{L}_{i+1} \in \text{GL}(d, q)$ such that $\langle H, H^c \rangle$ is stingray embedded as displayed above. The function $\mathcal{N}(d, n)$ is given by $\min\{2n - 1, d\}$.

Clearly, $H \leq \langle H, H^c \rangle$ and the standard generators for H are known. Using this knowledge and c we can very carefully construct standard generators for $\langle H, H^c \rangle \cong \text{SL}(\mathcal{N}(d, n), q)$. Then we set $H_{(i+1)} := \langle H, H^c \rangle$ and the standard generators for $H_{(i+1)}$ can be derived. Since we want to avoid as many matrix operations as possible the standard generators of $H_{(i+1)}$ are only encoded in an MSLP instead of performing the actual matrix computations. As for the **GoingDown** algorithm we introduce a notion for a ascending recognition chain in the next definition.

Definition 4.4. Let $\langle X \rangle = G = \text{SL}(d, q)$. Then a ascending chain of subgroups of G with

$$H = H_{(0)} \leq H_{(1)} \leq \dots \leq H_{(\ell-1)} \leq H_{(\ell)} = G,$$

where $H_{(i+1)} \cong \text{SL}(n_{i+1}, q)$ of the same type as G is stingray embedded in G and H is a base case group, is a *ascending recognition chain*.

StandardGenerators algorithm

In this section we describe the fundamental structure of the constructive recognition algorithm of this publication in a single algorithm **StandardGenerators**. The **StandardGenerators** algorithm uses the three subalgorithms **GoingDown**, **BaseCase** and **GoingUp** outlined in the previous sections. The input and output of the **StandardGenerators** algorithm are as described in the introduction of [Section 4](#).

The **StandardGenerators** algorithm deals as follows with the input $\langle X \rangle = G := \text{SL}(d, q)$:

- (1) If G is a base case group, then call the **BaseCase** algorithm on G and return the output.
- (2) Call the **GoingDown** algorithm with input G to construct a base case group U with $U \leq G$.
- (3) Call the **BaseCase** algorithm with input U to recognise U constructively.
- (4) Call the **GoingUp** algorithm with input U to express the standard generators of G as words in X in an MSLP.

The **StandardGenerators** algorithm can be displayed in pseudo code as follows.

Algorithm 1: StandardGenerators

Input: ▶ $\langle X \rangle = G = \text{SL}(d, q)$ in its natural representation, with $d \geq 4$
 ▶ $(N_1, N_2, N_3) \in \mathbb{N}$
Output: *fail* OR $(\mathcal{L}, \mathfrak{S})$ where
 ▶ $\mathcal{L} \in \text{GL}(d, q)$ is a base change matrix and
 ▶ $\mathfrak{S}$ is an MSLP such that if $\mathfrak{S}$ is evaluated on $X^{\mathcal{L}}$, then the
 standard generators of $G^{\mathcal{L}}$ are computed

function **StandardGenerators**($G, (N_1, N_2, N_3)$)

```

1  |  $U, \mathcal{L}_1, \mathfrak{S}_1 := \text{GoingDown}(G, N_1)$ 
2  |  $\mathfrak{S}_2, \mathcal{L}_2 := \text{BaseCase}(U, N_2)$ 
3  |  $\mathfrak{S}_3, \mathcal{L}_3 := \text{GoingUp}(G^{\mathcal{L}_1 \mathcal{L}_2}, U^{\mathcal{L}_2}, N_3)$ 
4  | Combine  $\mathfrak{S}_1, \mathfrak{S}_2$  and  $\mathfrak{S}_3$  into an single MSLP  $\mathfrak{S}$ 
5  |  $\mathcal{L} := \mathcal{L}_1 \mathcal{L}_2 \mathcal{L}_3$ 
6  | return  $(\mathfrak{S}, \mathcal{L})$ 
```

The algorithm **StandardGenerators** yields the structure for the constructive recognition algorithms of this publication. In the next three sections we present the details for the subalgorithms **GoingDown**, **BaseCase** and **GoingUp**.

We finish this section by stating the main theorem of this publication.

Theorem 4.5. Let $\langle X \rangle = G = \text{SL}(d, q)$ and $\epsilon \in (0, 1)$. **StandardGenerators** is a one-sided Monte Carlo algorithm which given input G and ϵ outputs with probability at least $1 - \epsilon$ an MSLP $\mathfrak{S}$ and base change matrix $\mathcal{L}$ such that $\mathfrak{S}$ evaluates from $X^{\mathcal{L}}$ to the standard generators of $G^{\mathcal{L}}$.

We plan to analyse the overall complexity of this algorithm in a follow-up paper, hopefully establishing the following:

Conjecture 4.6. The complexity of **StandardGenerators** as stated in [Theorem 4.5](#) is

$$\mathcal{O}(d^3 \log(d) + d^2 \log(d) \log(\log(d)) \log(q) + \frac{\log(d)}{\log(\log(d))} \xi + \zeta(q))$$

where ξ denotes an upper bound on the number of field operations for computing a random element in $\text{SL}(d, q)$ and $\zeta(q)$ denotes an upper bound on the number of field operations for constructively recognising $\text{SL}(4, q)$.

5 Stingray elements

In this section stingray elements are defined and general properties of stingray elements are summarised. We start with the definition of stingray elements and ppd stingray elements.

Definition 5.1. Let $\mathfrak{a}, \mathfrak{b} \in \mathbb{N}$ with $\mathfrak{a}, \mathfrak{b} > 1$. A prime r which divides $(\mathfrak{a}^{\mathfrak{b}} - 1)$ is a *primitive prime divisor* (or *ppd* for short) of $\mathfrak{a}^{\mathfrak{b}} - 1$ if $r \nmid \mathfrak{a}^i - 1$ for all $i \in \mathbb{N}$ with $i < \mathfrak{b}$.

Let $q = p^f$ be a prime power and $d, m \in \mathbb{N}$. An element $g \in \text{GL}(d, q)$ is a *ppd($d, q; m$)-element* if there is a primitive prime divisor r of $q^m - 1$ such that r divides the order of g . Define $\Phi(m, q)$ to be the product of all primitive prime divisors of $q^m - 1$, counting their multiplicities.

Definition 5.2. An element $s \in \text{GL}(d, q)$ is an *m-stingray element* for $1 < m \leq d$, if s has a $(d - m)$ -dimensional 1-eigenspace $E_s = \ker(s - 1)$ and s acts irreducibly on a complementary invariant subspace $W_s = \text{im}(s - 1) \leq \mathbb{F}_q^d$ of dimension m . The space W_s is the *stingray body* and E_s is the *stingray tail*. A stingray element $s \in \text{GL}(d, q)$ is a *ppd m-stingray element* if s is a ppd($d, q; m$)-element.

Example 5.3. Consider the following matrix in $\text{GL}(10, 5)$:

$$\begin{pmatrix} 4 & 1 & 3 & 3 & 2 & 1 & 2 & 4 & 0 & 4 \\ 3 & 3 & 4 & 4 & 3 & 4 & 1 & 0 & 3 & 2 \\ 2 & 1 & 0 & 4 & 3 & 1 & 1 & 2 & 0 & 3 \\ 3 & 1 & 3 & 4 & 4 & 0 & 2 & 0 & 1 & 3 \\ 3 & 4 & 1 & 1 & 0 & 3 & 4 & 4 & 1 & 1 \\ 1 & 0 & 4 & 4 & 2 & 2 & 1 & 1 & 4 & 2 \\ 2 & 4 & 2 & 2 & 0 & 3 & 4 & 2 & 1 & 0 \\ 0 & 2 & 2 & 2 & 4 & 0 & 3 & 4 & 2 & 0 \\ 3 & 4 & 1 & 1 & 4 & 3 & 4 & 4 & 2 & 1 \\ 0 & 2 & 2 & 2 & 2 & 1 & 3 & 2 & 1 & 2 \end{pmatrix} \xrightarrow{\text{change of basis}} \left(\begin{array}{cccc|cccccc} 0 & 0 & 0 & 4 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 3 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 4 & 0 & 0 & 0 & 0 & 0 & 0 \\ \hline 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \end{array} \right)$$

This element acts irreducibly on a 4-dimensional subspace of $\mathbb{F}_5^{10}$ and fixes a 6-dimensional subspace pointwise and is therefore a stingray element.

The algorithms presented here require ppd stingray elements. As the proportion of ppd stingray elements in $\text{SL}(d, q)$ is small, we seek elements, called *ppd pre-stingray candidates*, from which ppd stingray elements can easily be constructed.

Definition 5.4. An element $\mathfrak{s} \in \text{GL}(d, q)$ is an *m-pre-stingray candidate* for $m \leq d$ if the characteristic polynomial $\chi_{\mathfrak{s}}(x)$ has an irreducible factor $P(x) \in \mathbb{F}_q[x]$ of degree m over $\mathbb{F}_q$ and no other irreducible factors of degree divisible by m . The irreducible factor $P(x)$ is a *stingray factor*. Moreover, if $\mathfrak{s}$ is a ppd($d, q; m$)-element, we say that $\mathfrak{s}$ is a *ppd m-stingray element*.

Note that the degree of a stingray factor of a pre-stingray candidate is equal to the dimension of the stingray body of a corresponding stingray element.

The following result is the key for computing ppd-stingray elements from ppd pre-stingray candidates.

Theorem 5.5. *Let $G \leq \text{GL}(d, q)$ and let $\mathfrak{s} \in G$ be an m -pre-stingray candidate, i.e. we can write $\chi_{\mathfrak{s}}(x) = P_1(x)P_2^{c_2}(x) \dots P_k^{c_k}(x)$, where $P_1, \dots, P_k \in \mathbb{F}_q[x]$ are irreducible, and $m = \deg(P_1)$ does not divide $\deg(P_i)$ for $i \geq 2$. Let $B = p^\beta \prod_{i=2}^k (q^{\deg(P_i)} - 1)$ and $\beta = \lceil \log_p(\max\{c_2, \dots, c_k\}) \rceil$. Then the following hold:*

- (1) $\mathfrak{s}^B$ has a $(d - m)$ -dimensional 1-eigenspace.
- (2) If $x^{(q^m - 1)/\Phi(m, d)} \neq 1$ in $\mathbb{F}_q[x]/\langle P_1(x) \rangle$ then $\mathfrak{s}$ is a $\text{ppd}(d, q; m)$ -element.
- (3) If $\mathfrak{s}$ is a $\text{ppd}(d, q; m)$ -element, then $\mathfrak{s}^B$ is a ppd m -stingray element, whence it acts irreducibly on $W_{\mathfrak{s}}$.

Proof. (1) and (2) are [25, Remark 3.2]. Assertion (3) follows from [22, p.578] and [27, Sec. 4.2]. $\square$

Remark 5.6. The previous theorem allows us to construct a ppd stingray element given a ppd pre-stingray candidate. The ppd pre-stingray candidates we require satisfy $m \in O(\log(d))$. The probability of finding such ppd pre-stingray candidates by random selection has been determined Niemeyer and Praeger [25, Theorem 3.3]. They show that the proportion of pre-stingray candidates in $\text{GL}(d, q)$ which are $\text{ppd}(d, q; m)$ elements for $\log(d) \leq m \leq d/2$ is at least $1 - \frac{1}{m}$. All in all this can be turned into a polynomial-time randomized algorithm **FindStingrayElement** which takes as input a generating set for our group and a bound N on the maximal number of random elements it may generate before giving up, and which returns either **fail**, or a stingray candidate g together with an MSLP describing it and the new value for N , i.e., the input N minus the number of random selections that were used to find g .

6 GoingDown algorithm

Stingray elements are key to the **GoingDown** algorithm, as they are used in the **GoingDown** basic step to find a subgroup of $\text{SL}(d, q)$ isomorphic to $\text{SL}(d', q)$ quickly, where $d' \leq 4\lceil \log(d) \rceil$. Later in this section we study how the **GoingDown** basic step can be implemented. Repeated calls to the **GoingDown** basic step yield a descending recognition chain as in Definition 4.1

$$\text{SL}(4, q) \cong U_k \leq U_{k-1} \cong \text{SL}(d_{k-1}, q) \leq \dots \leq U_1 \cong \text{SL}(d_1, q) \leq U_0 = G,$$

where $d_i \leq 4\lceil \log(d_{i-1}) \rceil$ for $2 \leq i \leq k$.

GoingDown basic step

Let $G = \text{SL}(d, q)$. In this section we describe and prove the correctness of one **GoingDown** basic step. Given a stingray embedded subgroup H of G with $H \cong \text{SL}(d', q)$ for $d' \leq d$ as in Definition 2.4, the aim of the basic step is to compute a stingray embedded subgroup U of G with $U \cong \text{SL}(d'', q)$ and $d'' \leq 4\lceil \log(d') \rceil$. The algorithm to compute the subgroup U is a randomised algorithm using stingray elements. Therefore this section relies heavily on Section 5 and the algorithms presented there.

We start with a sketch of the idea. Let $s_1, s_2 \in \text{GL}(d, q)$ be two stingray elements, let $W_{s_i} \leq \mathbb{F}_q^d$ be the stingray bodies, $\dim(W_{s_i}) = n_i$ and E_{s_i} the stingray tails for $i \in \{1, 2\}$, where

$n_1 + n_2 \leq 4\lceil \log(d) \rceil$. As in [Definition 5.2](#), there are base change matrices $\mathcal{L}_i$ such that the stingray element $s_i^{\mathcal{L}_i}$ is a matrix with a non-trivial $n_i \times n_i$ block in the upper left hand corner and 1s on the remaining diagonal. The base change matrix $\mathcal{L}_i$ can be computed by appending a basis for the stingray tail E_{s_i} to a basis for the stingray body W_{s_i} for $i \in \{1, 2\}$. With high probability the base change matrices $\mathcal{L}_1$ and $\mathcal{L}_2$ are different. However, since n_1 and n_2 are relatively small compared to d , the elements s_1 and s_2 must have a large common 1-eigenspace, namely $E_{s_1} \cap E_{s_2}$. In fact we have $\mathbb{F}_q^d = (W_{s_1} + W_{s_2}) \oplus (E_{s_1} \cap E_{s_2})$ and the two summands are both invariant under $\langle s_1, s_2 \rangle$. We consider a base change matrix $\mathcal{L}_{s_1, s_2} \in \text{GL}(d, q)$ that arises if we choose a basis for $W_{s_1} + W_{s_2}$ and append a basis for the large common 1-eigenspace $E_{s_1} \cap E_{s_2}$ of s_1 and s_2 . Let $n := \dim(W_{s_1} + W_{s_2}) = d - \dim(E_{s_1} \cap E_{s_2})$. Then the stingray elements $s_1^{\mathcal{L}_{s_1, s_2}}$ and $s_2^{\mathcal{L}_{s_1, s_2}}$ act on $W_{s_1} + W_{s_2}$. With high probability $W_{s_1} \cap W_{s_2} = \{0\}$, $\langle s_1, s_2 \rangle$ acts irreducibly on $W_{s_1} + W_{s_2}$ and $\langle s_1, s_2 \rangle \cong \text{SL}(n, q)$.

Example 6.1. Let $G = \text{SL}(6, 5)$. Then

$$s_1 := \begin{pmatrix} 1 & 1 & 2 & 4 & 2 & 3 \\ 2 & 4 & 0 & 4 & 4 & 1 \\ 3 & 3 & 3 & 0 & 3 & 2 \\ 4 & 3 & 4 & 2 & 2 & 3 \\ 1 & 4 & 0 & 2 & 3 & 3 \\ 1 & 0 & 2 & 1 & 4 & 2 \end{pmatrix}, \quad s_2 := \begin{pmatrix} 3 & 2 & 1 & 1 & 3 & 3 \\ 3 & 3 & 0 & 4 & 0 & 3 \\ 0 & 3 & 3 & 0 & 1 & 2 \\ 3 & 1 & 1 & 0 & 3 & 4 \\ 0 & 2 & 3 & 0 & 0 & 3 \\ 1 & 0 & 4 & 3 & 2 & 1 \end{pmatrix}$$

are two stingray elements with $s_1, s_2 \in G = \text{SL}(6, 5)$ and additionally $\langle s_1, s_2 \rangle \cong \text{SL}(4, 5)$. Here $W_{s_1} = \langle (2, 1, 1, 1, 0, 0), (4, 4, 1, 0, 4, 1) \rangle$ and $W_{s_2} = \langle (3, 0, 2, 4, 1, 0), (1, 4, 0, 3, 0, 1) \rangle$, i.e. $n_i := \dim(W_{s_i}) = 2$ and $\dim(E_{s_i}) = 4$. Moreover, $W_{s_1} \cap W_{s_2} = \{0\}$ thus $\dim(W_{s_1} + W_{s_2}) = 4$ and so $\dim(E_{s_1} \cap E_{s_2}) = 2$. Computing a basis for the common 1-eigenspace of s_1 and s_2 yields $E_{s_1} \cap E_{s_2} = \langle (1, 4, 0, 2, 4, 0), (0, 1, 3, 0, 2, 2) \rangle$ and hence we overall obtain the basis

$$\mathcal{B} := ((2, 1, 1, 1, 0, 0), (4, 4, 1, 0, 4, 1), (3, 0, 2, 4, 1, 0), (1, 4, 0, 3, 0, 1), (1, 4, 0, 2, 4, 0), (0, 1, 3, 0, 2, 2))$$

for $\mathbb{F}_5^6$. Representing s_1 and s_2 with respect to this basis $\mathcal{B}$ gives

$${}^{\mathcal{B}}s_1^{\mathcal{B}} = \left(\begin{array}{ccc|cc} 4 & 2 & 0 & 0 & 0 \\ 1 & 2 & 0 & 0 & 0 \\ 3 & 3 & 1 & 0 & 0 \\ 4 & 2 & 0 & 1 & 0 \\ \hline 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & 1 \end{array} \right), \quad {}^{\mathcal{B}}s_2^{\mathcal{B}} = \left(\begin{array}{ccc|cc} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 3 & 0 \\ 0 & 0 & 3 & 2 & 0 \\ 0 & 0 & 4 & 3 & 0 \\ \hline 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & 1 \end{array} \right).$$

In order to improve the run-time, it is reasonable to represent the matrices s_1 and s_2 as elements of a special linear group of degree $n_1 + n_2$. Note that in this example $\text{SL}(4, q) \cong \langle s_1, s_2 \rangle$ and that $\langle s_1, s_2 \rangle$ is stingray embedded of degree 4 in $\text{SL}(6, 5)$.

The next algorithm implements the **GoingDown** basic step, i.e. computes the next subgroup of a descending recognition chain

$$\text{SL}(4, q) \cong U_k \leq U_{k-1} \cong \text{SL}(d_{k-1}, q) \leq \dots \leq U_1 \cong \text{SL}(d_1, q) \leq U_0 = G,$$

where $d_i \leq 4\lceil \log(d_{i-1}) \rceil$ for $2 \leq i \leq k$.

Algorithm 2: GoingDownBasicStep

Input: $\blacktriangleright d_1 \in \mathbb{N}$ with $d_1 > 4$
 $\blacktriangleright \langle X \rangle = G \leq \text{GL}(d, q)$ with $G \cong \text{SL}(d_1, q)$
 $\blacktriangleright \mathcal{L} \in \text{GL}(d, q)$ a base change matrix such that $G^{\mathcal{L}}$ is stingray embedded in $\text{GL}(d, q)^{\mathcal{L}}$
 $\blacktriangleright N \in \mathbb{N}$

Output: *fail* OR $(d_2, U, \mathcal{L}', \mathfrak{S}, N')$ where
 $\blacktriangleright d_2 \in \mathbb{N}$ with $4 \leq d_2 \leq 4\lceil \log(d_1) \rceil$,
 $\blacktriangleright U \leq G$ with $U \cong \text{SL}(d_2, q)$,
 $\blacktriangleright \mathcal{L}'$ is a base change matrix such that $U^{\mathcal{L}'}$ is stingray embedded in $G^{\mathcal{L}}$,
 $\blacktriangleright \mathfrak{S}$ is an MSLP from X to generators of U and
 $\blacktriangleright N' \in \mathbb{N}$ where $N - N'$ is the number of random selections that were used

function GoingDownBasicStep($G, d_1, \mathcal{L}, N$)

```

1  while  $N > 0$  do // Remark 2.7
2     $(s_1, \mathfrak{S}_1, N) \leftarrow \text{FindStingrayElement}(G^{\mathcal{L}}, d_1, N)$  // Remark 2.8
3     $W_{s_1} \leftarrow \text{Image}(s_1 - I_{d_1})$  // compute stingray body
4    repeat
5       $(s_2, \mathfrak{S}_2, N) \leftarrow \text{FindStingrayElement}(G^{\mathcal{L}}, d_1, N)$  // Remark 2.8
6       $W_{s_2} \leftarrow \text{Image}(s_2 - I_{d_1})$  // compute stingray body
7    until  $W_{s_1} \cap W_{s_2} = \{0\}$ 
8     $d_2 \leftarrow \dim(W_{s_1}) + \dim(W_{s_2})$ 
9    if  $\langle s_1, s_2 \rangle \cong \text{SL}(d_2, q)$  then // Using a naming algorithm, see Remark 2.5
10      $\mathfrak{S} \leftarrow$  an MSLP from  $X$  to  $(s_1, s_2)$  using  $\mathfrak{S}_1$  and  $\mathfrak{S}_2$ 
11      $\mathcal{L}_n \leftarrow$  base change to concatenation of  $\text{Basis}(W_{s_1} + W_{s_2})$  and  $\text{Basis}(E_{s_1} \cap E_{s_2})$ 
12     return  $(\langle \text{diag}(s_1, I_{d-d_1}), \text{diag}(s_2, I_{d-d_1}) \rangle, d_2, \text{diag}(\mathcal{L}_n, I_{d-d_1})\mathcal{L}, \mathfrak{S}, N)$ 
13  return fail
```

Remark 6.2. (1) The input parameter N of **GoingDownBasicStep** is used to control the maximal number of random elements chosen. Even though **GoingDownBasicStep** does not compute random elements itself, **FindStingrayElement** is used which is a randomised algorithm to compute stingray elements, see Section 5. **GoingDownBasicStep** is a one-sided Monte Carlo algorithm and its success depends on the control parameter N . Thus if N is too small, then the algorithm can fail. How N has to be chosen in order to get a specific success probability $\epsilon \in (0, 1)$ will be subject of a future publication.

- (2) The condition of the if statement in line 9 of **GoingDownBasicStep**, which is $\langle s_1, s_2 \rangle \cong \text{SL}(d_2, q)$, can be verified using a naming algorithm as in Remark 2.5.
- (3) There is an immediate refinement of this algorithm: If a pair s_1, s_2 generating a group U isomorphic to $\text{SL}(d_2, q)$ has been found, then this isomorphism can be made effective using the action of U on $W_{s_1} + W_{s_2}$: since U is stingray embedded we can just project onto the stingray body. Then the next **GoingDown** step can work with much smaller matrices of degree d_2 instead of degree d . This improves the running time asymptotically while the length and memory quota of the output MSLPs remain the same.

We now establish the correctness of **GoingDownBasicStep** and that it terminates using at most N random elements.

Theorem 6.3. **GoingDownBasicStep** terminates using at most N random selections and works correctly.

Proof. We start by proving that the algorithm terminates. **GoingDownBasicStep** contains two loops which start in line 1 and in line 4. The loop starting in line 1 terminates if $N \leq 0$. For every computation of a random element, N is decreased and every call of **FindStingrayElement**

requires at least one computation of a random element. Therefore, the statement $N \leq 0$ becomes true after at most N executions of `FindStingrayElement`. In this case the subroutine ends by returning `fail`. By [Remark 2.8](#) the loop starting in line 4 also returns `fail` if $N \leq 0$ by `FindStingrayElement` in line 5.

The correctness is clear since the algorithm either returns `fail` or a subgroup which is isomorphic to $\text{SL}(d_2, q)$ as this is verified in line 9. We only have to prove that $4 \leq d_2 \leq 4\lceil \log(d_1) \rceil$. The non-trivial and irreducible subspace of the stingray element returned by `GoingDownBasicStep` has dimension bounded by 2 and $2\lceil \log(d_1) \rceil$. Since d_2 is the sum of two such integers it is bounded by 4 and $4\lceil \log(d_1) \rceil$. $\square$

Remark 6.4. Algorithm `GoingDown` terminates in a group isomorphic to $\text{SL}(4, q)$. We now explain, why the method cannot be extended to descend to $\text{SL}(2, q)$. Note that stingray elements of special linear groups with a 1-dimensional stingray body are equal to the identity matrix. To see this, apply a base change to obtain a block matrix structure as in [Example 5.3](#) where one block visualizes the stingray tail which is an identity matrix of size $(d-1) \times (d-1)$ and the other block visualizes the stingray body which has to be $(1) \in \mathbb{F}_q^{1 \times 1}$ since the stingray element is contained in $\text{SL}(d, q)$.

Let $G = \text{SL}(4, q)$ and suppose we search for two stingray elements $s_1, s_2 \in G$ with $H = \langle s_1, s_2 \rangle \cong \text{SL}(2, q)$. One idea to overcome this problem could be to use the `GoingDown` basic step, i.e. to search for two stingray elements with 1-dimensional stingray bodies which also intersect trivially and verify $\langle s_1, s_2 \rangle \cong \text{SL}(2, q)$. As we have noted, stingray elements with 1-dimensional stingray body are equal to the identity matrix. Therefore, it is not possible that $\langle s_1, s_2 \rangle \cong \text{SL}(2, q)$.

Another idea is to compute two stingray elements $s_1, s_2 \in G$ which have the same 2-dimensional stingray body. Note that there are

$$\binom{4}{2}_q = \frac{(q^4 - 1)(q^4 - q)}{(q^2 - 1)(q^2 - q)} = (q^2 + 1)(q^2 + q + 1) > q^4$$

different 2-dimensional subspaces of $\mathbb{F}_q^4$. Therefore, the probability that s_1 and s_2 have the same 2-dimensional stingray body is less than $1/q^4$. For example, if $q = 121$, then the probability that s_1 and s_2 have the same 2-dimensional stingray body is 0.0000000046 which makes finding such elements impractical.

Combining `GoingDown` basic steps

Let $G = \text{SL}(d, q)$. By repeatedly calling `GoingDownBasicStep`, we now have all the methods needed to construct a descending recognition chain as in [Definition 4.1](#) of special linear groups as

$$\text{SL}(4, q) \cong U_k \leq U_{k-1} \cong \text{SL}(d_{k-1}, q) \leq \dots \leq U_1 \cong \text{SL}(d_1, q) \leq U_0 = G,$$

where $d_i \leq 4\lceil \log(d_{i-1}) \rceil$ for $1 \leq i \leq k$. Observe that the chain reaches a $\text{SL}(4, q)$ very rapidly as the basic step reduces the dimension logarithmically. The overall number of `GoingDown` basic steps required is given by the iterated logarithm $\log^*(d)$.

Remark 6.5. Note that all state-of-the-art algorithms require a lot more steps. The currently best algorithm is an algorithm by Dietrich, Lübeck, Leedham-Green and O'Brien [10, 20], in the following referred to as DLLO algorithm. The DLLO algorithm has two variations from which one is based on a “splitting” step (called “One” in [20]) and the other on a “conjugating” step (called “Two” in [20]). In practice the variation of the DLLO algorithm with the “splitting” step is used. In each call to the “splitting” step of the DLLO algorithm two subgroups of half of the input dimension are computed in the best case. Moreover, the DLLO algorithm

has to be applied to both computed subgroups. The **GoingDown** algorithm in this publication avoids “splitting” by constructing only one subgroup which is isomorphic to $\text{SL}(4, q)$. It should be mentioned that the DLLO algorithm is also applicable for non-natural irreducible matrix representations and for black box settings and, hence, does not exploit properties of the natural representation as we do in our **GoingUp** algorithms which in turn has an enormous impact on the design of the overall algorithm.

Remark 6.6. Recall the descending recognition chain

$$\text{SL}(4, q) \cong U_k \leq U_{k-1} \cong \text{SL}(d_{k-1}, q) \leq \dots \leq U_1 \cong \text{SL}(d_1, q) \leq U_0 = G,$$

which is computed by the **GoingDown** algorithm. For that it uses **GoingDownBasicStep** which verifies that a group generated by two stingray elements is isomorphic to a special linear group using naming algorithms. Note that the number of calls to naming algorithms can be reduced by slight variations of the algorithms, e.g.

- Always use a naming algorithm, i.e. verify that $U_i \cong \text{SL}(d_i, q)$ for all $i \in \{1, \dots, k\}$,
- Only use a naming algorithm until the first subgroup is computed, i.e. only verify that $U_1 \cong \text{SL}(d_1, q)$,
- Never use a naming algorithm and restart from the input group if a maximal number of random selection is reached, i.e. restart from $U_0 = G$,
- Never use a naming algorithm but instead of restarting from the input group backtrack one step, i.e. if a maximal number of tries is reached in the process of computing U_{i+1} as a subgroup of U_i , then restart from U_{i-1} and compute another subgroup U_i .

Practical tests of implementations could be used to compare the impact on the running time which is not done in this publication. In the current implementation of the **GoingDown** algorithm in **GAP** we are using the third strategy, i.e. we never use a naming algorithm and restart from the input group if a maximal number of random selection is reached which works fine in practice.

7 GoingUp algorithm

In this section we assume that we have found a stingray embedded subgroup H of $G^\mathcal{L}$ for a known base change matrix $\mathcal{L} \in \text{GL}(d, q)$, i.e. $H \leq \langle X^\mathcal{L} \rangle = G^\mathcal{L} = \text{SL}(d, q)$, with $H \cong \text{SL}(2, q)$ and an MSLP from X to the standard generators of H . Starting from this setting, we describe an algorithm to compute standard generators of G . Similar to the **GoingDown** algorithm we present a **GoingUp** step and afterwards use the **GoingUp** step repeatedly. In this publication we present two versions of a **GoingUp** step, both of which are randomised algorithms.

The **GoingUp** step of this section uses linear algebra and relies on completely new ideas. On the one hand, every computation of this solution can be performed extremely fast in the natural representations of special linear groups which results in a very efficient **GoingUp** step. On the other hand, the computations require that the given representation of a special linear group is the natural representation and the **GoingUp** step of this section cannot easily be modified for non-natural representations. Using the **GoingUp** step repeatedly yields an ascending recognition chain

$$H = H_{(0)} \leq H_{(1)} \leq \dots \leq H_{(\ell-1)} \leq H_{(\ell)} = G.$$

as described in [Definition 4.4](#) of [Section 4](#).

An alternative solution for **GoingUp** compared to the one presented in this publication is based on ideas of [20] and makes use of involution centralizers. The advantage of the algorithm

we present here is that it is much faster when applied to a special linear group in its natural representation. However, this comes at the price that the MSLPs for the standard generators of G are longer and that it cannot be used in non-natural settings. In contrast the alternative solution is applicable to all classical groups in odd characteristic. We will present it in a forthcoming publication.

7.1 Overview of the GoingUp step

We start this section by stating the main theorem and giving a description of the `GoingUp` step in detail. The theorem is proved by the correctness of the presented `GoingUp` step of this section. The algorithm consists of seven phases. One of these phases is randomised while the others are deterministic. Since one phase is randomised, the `GoingUp` step is also randomised. The `GoingUp` step algorithm is presented as `GoingUpStep` in Section 7.5. In Section 7.6 we call the `GoingUp` step repeatedly to construct standard generators of the input group G which results in the final `GoingUp`.

We start with our hypothesis on the setting of this section and then state the main theorem. Afterwards, the theorem is divided into seven phases which we investigate in more detail and prove their correctness in the course of this section.

Hypotheses 7.1. *For the remainder of this section we assume $\langle X \rangle = G = \mathrm{SL}(d, q)$ containing a stingray embedded subgroup $H \leq \langle X^\mathcal{L} \rangle = G^\mathcal{L}$ with $H \cong \mathrm{SL}(n, q)$ for $n < d$ and for a known base change matrix $\mathcal{L} \in \mathrm{GL}(d, q)$. Moreover, standard generators Y_n of H are given as words in X . Let $V = \mathbb{F}_q^d$ and suppose that $\mathcal{B} = (v_1, \dots, v_d)$ is a basis of V and let $V_n = \langle v_1, \dots, v_n \rangle$ and $F_{d-n} = \langle v_{n+1}, \dots, v_d \rangle$. We assume that H acts on V_n as $\mathrm{SL}(n, q)$ and that H fixes F_{d-n} pointwise. Recall that $(\omega_1, \dots, \omega_f)$ is an $\mathbb{F}_p$ -basis of $\mathbb{F}_q$.*

The main theorem of the `GoingUp` step is the following.

Theorem 7.2. *Let $X \subseteq \mathrm{SL}(d, q)$ such that $\langle X \rangle = G = \mathrm{SL}(d, q)$ and let $2 \leq n < d$ with $n = 2$ or n odd, let $\mathcal{L} \in \mathrm{GL}(d, q)$ be a base change matrix. Let $Y_n^\mathcal{L}$ be a set of standard generators for the subgroup $\mathrm{SL}(n, q)$ stingray embedded into $G^\mathcal{L}$. Furthermore, let $\mathfrak{S}$ be a straight-line program from X to Y_n and let $n' := \min\{2n - 1, d\}$.*

Then there is an algorithm that computes a base change matrix $\mathcal{L}' \in \mathrm{GL}(d, q)$ together with a straight-line program $\mathfrak{S}'$ from X to a set $Y_{n'}$, which is a set of standard generators for $\mathrm{SL}(n', q)$ and $Y_{n'}^{\mathcal{L}'}$ is stingray embedded in $G^{\mathcal{L}'}$.

We prove Theorem 7.2 by stating an algorithm. The algorithm consists of seven phases, called (SL1) to (SL7), which are discussed and proven in the remainder of this section.

Remark 7.3. The general idea of the algorithm is the following. Let $H = \mathrm{SL}(V_n) \cong \mathrm{SL}(n, q)$ stingray embedded in $G^\mathcal{L}$ and $G = \mathrm{SL}(d, q)$. Given standard generators Y_n for H , we construct an element $g \in G^\mathcal{L}$ with the following properties:

$$(C1) \quad \dim(V_n + V_n g) = n',$$

$$(C2) \quad \text{if } n' < d, \text{ then } \dim(\mathrm{Fix}(H) + \mathrm{Fix}(g)) = \dim(F_{d-n} + \mathrm{Fix}(g)) = d.$$

Note that H acts on V_n as $\mathrm{SL}(V_n) \cong \mathrm{SL}(n, q)$ and similarly H^g acts on $V_n g$ as $\mathrm{SL}(V_n g) \cong \mathrm{SL}(n, q)$. Then we have

$$\dim(V_n \cap V_n g) = \dim(V_n) + \dim(V_n g) - \dim(V_n + V_n g) = 2n - n' = \max\{1, 2n - d\}.$$

In Section 7.3 we formulate an additional property (C3) which cannot be defined at this point. If g does not satisfy (C3), then we construct a new element $g \in G^\mathcal{L}$. In the remainder of this

section we prove that this setup allows us to choose a basis of the n' -dimensional subspace $V_{n'} = V_n + V_n g$ of V carefully such that we can use g -conjugates of certain transvections in H to assemble standard generators for $\text{SL}(n', q)$ with respect to the new basis. As a result this allows us to conclude that $\langle H, H^g \rangle$ is indeed isomorphic to $\text{SL}(n', q)$. When $n' \leq d$ we have roughly doubled the degree from n to $2n - 1$ using g .

Definition 7.4. Assume the setting as described in [Hypotheses 7.1](#) and let $g \in G^\mathcal{L}$.

- (1) If g satisfies (C1) and (C2) of [Remark 7.3](#), then g is a *weak doubling element* with respect to H .
- (2) If g is a weak doubling element with respect to H and additionally fixes v_n , then g is a *doubling element* with respect to H .

When the context is clear, an weak doubling element and doubling element with respect to H are only denoted by a weak doubling element and doubling element.

Remark 7.5. The next sections can roughly be summarized as follows.

- (1) **Construction of a doubling element:** Construct an element $g \in G^\mathcal{L}$ fulfilling the properties (C1) and (C2) and fixing v_n , i.e. a doubling element as in [Definition 7.4](#). This is achieved by random selection of elements of $G^\mathcal{L}$ and discussed in [Section 7.2](#).
- (2) **Construction of a new base change matrix:** Construct a new base change matrix $\mathcal{L}'$ such that $\langle H, H^g \rangle^{\mathcal{L}'}$ is stingray embedded in $G^{\mathcal{L}\mathcal{L}'}$ which is possible because of the properties (C1) and (C2). The computation of $\mathcal{L}'$ is deterministic and discussed in [Section 7.3](#). In this section we also formulate an additional property (C3) which can only be given after constructing $\mathcal{L}'$. If g does not satisfy (C3), then we start over from (1).
- (3) **Construction of transvections and standard generators:** If (2) is successful, then we can conclude that $\langle H, H^g \rangle^{\mathcal{L}'} \cong \text{SL}(n', q)$. Hence, we construct transvections and standard generators for $\langle H, H^g \rangle^{\mathcal{L}'}$. Note that we only need to compute permutation matrices corresponding to the n' and $(n' - 1)$ cycle of [Definition 2.3](#) as the transvections of the standard generators of H are also the transvections of the standard generators of $\langle H, H^g \rangle^{\mathcal{L}'}$. The computations performed in (3) are deterministic and discussed in [Section 7.4](#).

In each section the task described in [Remark 7.5](#) is divided into more phases which are discussed in detail in the corresponding section and labelled as (SL1) to (SL7). Lastly, in [Section 7.5](#) the phases (SL1) to (SL7) are combined into a single algorithm for the `GoingUp` step. Proving its correctness yields the proof for [Theorem 7.2](#).

7.2 Construction of a dimension doubling element

The goal in this section is the construction of a doubling element, i.e. an element $g \in G^\mathcal{L}$ fulfilling the properties (C1) and (C2) and fixing v_n , leading to `ComputeDoublingElement`. Recall from [Hypotheses 7.1](#) the setting for this section. We give a condensed version of what is achieved.

Remark 7.6.

- (SL1) Construct an element $t \in H$ which has a fixed space of dimension $d - n + 1$. This can be done easily as we have standard generators Y_n for H .
- (SL2) Choose random elements $a \in G^\mathcal{L}$ until $\tilde{g} := t^a$ is a weak doubling element.

(SL3) Find a conjugate $g \in G^\mathcal{L}$ of $\tilde{g}$ which is a doubling element.

Note that the **GoingUp** algorithm is randomised as in (SL2) we search for random $a \in G^\mathcal{L}$ such that $\tilde{g} := t^a$ fulfils the two properties (C1) and (C2) of Remark 7.3. We do not analyse the proportion of usable elements in this section, only prove the correctness.

The following lemma shows how (SL1) is carried out in the solution of this publication. Note that there are multiple other choices for $t \in H$ having a fixed space of dimension $d - n + 1$. Recall the permutation matrices z_1 and z_2 from Definition 2.3 which are permutation matrices corresponding to n and $n - 1$ cycles respectively.

Lemma 7.7. *An element of H which has a fixed space of dimension $d - n + 1$ is given by*

$$t := \begin{cases} E_{1,2}(1), & \text{if } n = 2, \\ z_1, & \text{if } n > 2 \text{ and } p \text{ is even,} \\ z_2, & \text{if } n > 2 \text{ and } p \text{ is odd.} \end{cases}$$

Proof. If $n = 2$, then we take $t = E_{1,2}(1)$. Its fixed space is $\langle v_2, \dots, v_d \rangle$ and thus has dimension $d - 1 = d - 2 + 1 = d - n + 1$. If $n > 2$, then by assumption in Theorem 7.2 n is odd. For t we take z_2 a $(n - 1)$ -cycle if the characteristic p is odd and z_1 a n -cycle if $p = 2$. The fixed space is $\langle v_1, v_{n+1}, v_{n+2}, \dots, v_d \rangle$ in the first case and $\langle v_1 + v_2 + \dots + v_n, v_{n+1}, \dots, v_d \rangle$ in the second case. $\square$

The element t is “constructed” as an MSLP in the given standard generators of $\text{SL}(n, q)$, but can also be written explicitly as a matrix of $\langle X \rangle^\mathcal{L}$ at a cost of $O(d^2)$.

Now that t has a fixed space of dimension $d - n + 1$, we choose a random $a \in G^\mathcal{L}$ and check whether $\tilde{g} = t^a$ fulfils the properties (C1) and (C2) of Remark 7.3. We repeat this until $\tilde{g}$ has the required properties.

Remark 7.8. Verifying (C1) and (C2) of Remark 7.3 is one of the few places in **GoingUp** step where we must multiply $(d \times d)$ -matrices, since a is created as a matrix in the same input basis as X , and we must construct the matrix of a and $\tilde{g}$ as an element of $\langle X \rangle^\mathcal{L}$. This is necessary to check (C1) and (C2).

Lemma 7.9. *Let t be as in Lemma 7.7.*

- (1) *If $\tilde{g} := t^a$ is a weak doubling element, then $\dim(V_n \cap \text{Fix}(\tilde{g})) \geq 1$ and $\dim(V_n \cap \text{Fix}(\tilde{g})) = 1$ if $n' < d$.*
- (2) *Then there is a $a \in G^\mathcal{L}$ such that $\tilde{g} := t^a$ is a weak doubling element, i.e. $\tilde{g}$ satisfies (C1) and (C2).*
- (3) *If $\tilde{g} := t^a$ is a weak doubling element, then $V_{n'}$ is invariant under the action of $\tilde{g}$.*
- (4) *If $\tilde{g} := t^a$ is a weak doubling element and $n' < d$, then $\dim(F_{d-n} \cap \text{Fix}(\tilde{g})) = d - n'$.*

Proof.

- (1) Since $\tilde{g}$ and t are conjugate we know that $\dim(\text{Fix}(\tilde{g})) = \dim(\text{Fix}(t)) = d - n + 1$. Note that $\dim(V_n + \text{Fix}(\tilde{g})) \leq \dim(V) = d$. Hence,

$$\begin{aligned} \dim(V_n \cap \text{Fix}(\tilde{g})) &= \dim(V_n) + \dim(\text{Fix}(\tilde{g})) - \dim(V_n + \text{Fix}(\tilde{g})) \\ &= n + (d - n + 1) - \dim(V_n + \text{Fix}(\tilde{g})) \\ &= d + 1 - \dim(V_n + \text{Fix}(\tilde{g})) \geq 1. \end{aligned}$$

Now let $n' < d$, i.e. $n' = 2n - 1$. Then using (C1) of Remark 7.3 it follows that

$$\begin{aligned}\dim(V_n \cap V_n \tilde{g}) &= \dim(V_n) + \dim(V_n \tilde{g}) - \dim(V_n + V_n \tilde{g}) \\ &= n + n - n' \\ &= n + n - (2n - 1) = 1.\end{aligned}$$

Notice that $V_n \cap \text{Fix}(\tilde{g}) \subseteq V_n \tilde{g}$ and thus

$$\dim(V_n \cap \text{Fix}(\tilde{g})) \leq \dim(V_n \cap V_n \tilde{g}) = 1.$$

Since $\dim(V_n \cap \text{Fix}(\tilde{g})) \geq 1$, the result follows.

- (2) Note that an element fulfilling the properties (C1) and (C2) exists as for example matrices of the form $a = \text{diag}(\tilde{a}, I_{d-n'})$ with

$$\tilde{a} = \begin{pmatrix} \overbrace{0 \ \dots \ 1}^{n-1} & \overbrace{0}^1 & \overbrace{0 \ \dots \ 1}^{n'-n} \\ \vdots & \ddots & \vdots \\ 1 & \dots & 0 \\ 0 & \dots & 0 \\ \vdots & \ddots & \vdots \\ 0 & \dots & 0 \end{pmatrix} =: \tilde{a}$$

can be chosen. It is clear that $\tilde{g} = t^a$ fulfils (C1). Note that $e_1 + e_2 + \dots + e_n \in V_n \cap \text{Fix}(\tilde{g})$ and thus (C2) also holds as $\dim(F_{d-n} + \text{Fix}(g)) = d$ is equivalent to $\dim(F_{d-n} \cap \text{Fix}(g)) \geq 1$ by 1).

- (3) If $n' = d$, then the statement is trivial. Let us assume that $n' = 2n - 1 < d$. We construct a basis of $V_{n'}$ which shows that $V_{n'}$ is invariant under the action of $\tilde{g}$. A basis of $V_{n'}$ consists of n' elements since $\dim(V_{n'}) = n'$ by (C1). First notice that using (2) it follows that

$$\begin{aligned}\dim(V_n + \text{Fix}(\tilde{g})) &= \dim(V_n) + \dim(\text{Fix}(\tilde{g})) - \dim(V_n \cap \text{Fix}(\tilde{g})) \\ &= n + (d - n + 1) - 1 = d.\end{aligned}$$

Therefore, $V_n + \text{Fix}(\tilde{g}) = V$. Since $V_n \leq V_{n'}$, it follows that $V_{n'} + \text{Fix}(\tilde{g}) = V$ which implies that

$$\begin{aligned}\dim(V_{n'} \cap \text{Fix}(\tilde{g})) &= \dim(V_{n'}) + \dim(\text{Fix}(\tilde{g})) - \dim(V_{n'} + \text{Fix}(\tilde{g})) \\ &= (2n - 1) + (d - n + 1) - d = n.\end{aligned}$$

Since $\dim(V_n \cap (V_{n'} \cap \text{Fix}(\tilde{g}))) = \dim(V_n \cap \text{Fix}(\tilde{g})) = 1$, it follows that

$$\begin{aligned}\dim(V_n + (V_{n'} \cap \text{Fix}(\tilde{g}))) &= \dim(V_n) + \dim(V_{n'} \cap \text{Fix}(\tilde{g})) - \dim(V_n \cap (V_{n'} \cap \text{Fix}(\tilde{g}))) \\ &= n + n - 1 = 2n - 1 = n' .\end{aligned}$$

Since $V_n + (V_{n'} \cap \text{Fix}(\tilde{g})) \leq V_{n'}$, it follows that $V_n + (V_{n'} \cap \text{Fix}(\tilde{g})) = V_{n'}$. Therefore, we can choose a basis of $V_{n'}$ as follows:

- Choose a non-zero vector $v_1 \in V_n \cap \text{Fix}(\tilde{g})$.
- Select $n - 1$ vectors $v_2, \dots, v_n \in V_n$ to extend this to a basis of V_n .
- Choose $n - 1$ vectors from $V_{n'} \cap \text{Fix}(\tilde{g})$ to extend this to a basis of $V_{n'}$.

Clearly this basis is invariant under the action of $\tilde{g}$ as either $v_i \tilde{g} = v_i$ or $v_i \tilde{g} \in V_n \tilde{g} \leq V_{n'}$.

(4) If $n' < d$, then $\dim(F_{d-n} + \text{Fix}(\tilde{g})) = d$ by (C2). Hence, as claimed,

$$\begin{aligned} \dim(F_{d-n} \cap \text{Fix}(\tilde{g})) &= \dim(F_{d-n}) + \dim(\text{Fix}(\tilde{g})) - \dim(F_{d-n} + \text{Fix}(\tilde{g})) \\ &= (d - n) + (d - n + 1) - d \\ &= d - 2n + 1 = d - n'. \end{aligned} \quad \square$$

Remark 7.10. If $n' = d < 2n - 1$, then it is possible that $\dim(V_n \cap \text{Fix}(\tilde{g})) > 1$ which is important in Remark 7.17.

Corollary 7.11. $V_n + V_n \tilde{g} = V_n + V_n \tilde{g}^{-1}$.

Proof. Note that $V_n + V_n \tilde{g} = V_{n'} \stackrel{7.9}{=}^{(3)} V_{n'} \tilde{g}^{-1} = (V_n + V_n \tilde{g}) \tilde{g}^{-1} = V_n \tilde{g}^{-1} + V_n$. $\square$

Remark 7.12. Note that there is one more condition (C3) which we can only be formulate in Section 7.3. If that condition is not satisfied, then we restart from (SL2) and try another element a .

Our next goal is to construct a conjugate g of $\tilde{g}$ such that g is a doubling element. We seek an element $L \in H$ with $v_n L = v$, where $0 \neq v \in V_n \cap \text{Fix}(\tilde{g})$, and write L as a word in the standard generators Y_n and finally compute $g := L \tilde{g} L^{-1}$. It is well-known that $\text{SL}(d, q)$ acts doubly transitive on the 1-dimensional subspaces of $\mathbb{F}_q^d$ (see e.g. [30, Theorem 4.1]). This implies the existence of an element $L \in H$ with the described properties, Lemma 7.13 shows that g is a doubling element and lastly we describe how L can be found. We start by proving that $L \in H \cong \text{SL}(n, q)$ exists.

Next we show that $g := L \tilde{g} L^{-1}$ is a doubling element.

Lemma 7.13. *Let t and G and H be as in Lemma 7.7 and $\tilde{g} := t^a$ a weak doubling element for a random element $a \in G^\mathbb{L}$. Let $L \in H$ such that $v_n L = v$ where $0 \neq v \in V_n \cap \text{Fix}(\tilde{g})$. Then*

(1) $L \tilde{g} L^{-1}$ fulfills (C1) and (C2).

(2) $v_n \in V_n \cap \text{Fix}(L \tilde{g} L^{-1})$.

Proof. (1) Since $L \in H$, it follows that $V_n L = V_n$ and so

$$\dim(V_n + V_n L \tilde{g} L^{-1}) = \dim(V_n L + V_n L \tilde{g}) = \dim(V_n + V_n \tilde{g}) = n'$$

and (C1) holds. Moreover, $L F_{d-n} L^{-1} = F_{d-n}$ (notice $L \in H$) and so

$$\dim(\text{Fix}(L \tilde{g} L^{-1}) + F_{d-n}) = \dim(\text{Fix}(L \tilde{g} L^{-1}) + L F_{d-n} L^{-1}) = \dim(\text{Fix}(\tilde{g}) + F_{d-n}) = d$$

and (C2) holds.

(2) $v_n \in V_n$ and $v_n L \tilde{g} L^{-1} = v \tilde{g} L^{-1} = v L^{-1} = v_n$ since $0 \neq v \in V_n \cap \text{Fix}(\tilde{g})$. $\square$

Remark 7.14. We proceed as follows to find L fulfilling the hypothesis of Lemma 7.13:

- Let $0 \neq v \in V_n \cap \text{Fix}(\tilde{g})$ and $v = \sum_{j=1}^n \lambda_j v_j$ for $\lambda_j \in \mathbb{F}$. This is possible since $v \in V_n$ and $(v_1, \dots, v_n)$ is a basis of V_n .

- If $\lambda_n \neq 0$, then we multiply v by λ_n^{-1} such that without loss of generality we may assume $\lambda_n = 1$. This allows us to write L as a product of elements of the form $E_{n,j}(\omega_i)$ for $1 \leq i \leq f$ and $1 \leq j \leq n-1$ which are easily expressed in terms of the standard generators Y_n using a rewriting procedure [9, 24].
- If $\lambda_n = 0$, then we choose j with $\lambda_j \neq 0$ and then a $L' \in H$ with $v_n L' = v E_{j,n}(1)$ as above (replacing v with a scalar multiple as needed). Finally we set $L := L' E_{j,n}(1)^{-1}$.

Remark 7.15. Notice that the matrices $E_{1,2}(\omega_i)$ and $E_{2,1}(\omega_i)$ are given as elements of $\langle X \rangle^{\mathcal{L}}$ which contains the stingray embedded subgroup H isomorphic to $\text{SL}(n, q)$ and standard generators Y_n can be written as words in $X^{\mathcal{L}}$ as described in [Hypotheses 7.1](#).

Algorithm 3: ComputeDoublingElement

Input: ▶ $\langle X \rangle = G \leq \text{SL}(d, q)$
 ▶ A base change matrix $\mathcal{L} \in \text{GL}(d, q)$
 ▶ $\text{SL}(n, q) \cong \langle Y_n \rangle = H \leq G^{\mathcal{L}}$ stingray embedded and constructively recognised
 ▶ $N \in \mathbb{N}$
Output: *fail* OR $(g, \mathfrak{S}, N')$ where
 ▶ $g \in G^{\mathcal{L}}$ is a doubling element,
 ▶ $\mathfrak{S}$ is an MSLP from $X \cup Y_n$ to g and
 ▶ $N' \in \mathbb{N}$ where $N - N'$ is the number of random selections that were used

function ComputeDoublingElement($G, H, \mathcal{L}, N$)

```

1  Choose  $t \in H$  as described in Lemma 7.7                                     // (SL1)
2  repeat                                                                    // Start of (SL2)
3       $N \leftarrow N - 1$ 
4      if  $N < 0$  then
5          return fail
6       $\tilde{g} \leftarrow t^a$  for random  $a \in G^{\mathcal{L}}$ 
7  until  $\tilde{g}$  satisfies (C1) and (C2)
8   $\mathfrak{S}_1 \leftarrow$  MSLP from  $X \cup Y_n$  to  $\tilde{g}$ 
9   $L \leftarrow$  as described in Remark 7.14
10  $\mathfrak{S}_2 \leftarrow$  MSLP from  $Y_n$  to  $L$                                            // (SL3)
11  $g \leftarrow L \tilde{g} L^{-1}$ 
12  $\mathfrak{S} \leftarrow$  Compose  $\mathfrak{S}_1$  and  $\mathfrak{S}_2$ 
13 return  $(g, \mathfrak{S}, N)$ 

```

7.3 Construction of a new base change matrix

The goal of this section is the construction of a new base change matrix $\mathcal{L}'$ such that $\langle H, H^g \rangle^{\mathcal{L}'}$ is stingray embedded in $G^{\mathcal{L}'}$. Everything done in this section is deterministic. Recall from [Hypotheses 7.1](#) the setting for this section and that $g \in G^{\mathcal{L}}$ is a doubling element, i.e. satisfies (C1) and (C2) and fixes v_n as described in [Section 7.2](#). This section only covers one phase as described in the next remark.

Remark 7.16.

(SL4) Compute a base change matrix $\mathcal{L}'$ such that $\langle H, H^g \rangle^{\mathcal{L}'}$ is stingray embedded in $G^{\mathcal{L}'}$.

The goal of (SL4) is to compute a base change matrix $\mathcal{L}' \in \text{GL}(d, q)$ such that $\langle H, H^g \rangle^{\mathcal{L}'}$ is stingray embedded in $G^{\mathcal{L}'}$ and if $\langle H, H^g \rangle \cong \text{SL}(n', q)$, then standard generators of $\langle H, H^g \rangle^{\mathcal{L}'}$ can be constructed using the steps (SL5) to (SL7) described in [Section 7.4](#). Note that we formulate an additional condition (C3) in this section which can only be defined after the construction of $\mathcal{L}'$. If g does not satisfy (C3), then we have to chose a new random element $a \in G^{\mathcal{L}}$ and restart from phase (SL2). If g satisfies (C3), then we can conclude in [Section 7.4](#) that $\langle H, H^g \rangle \cong \text{SL}(n', q)$ and construct standard generators of $\langle H, H^g \rangle$.

Remark 7.17. The base change matrix $\mathcal{L}'$ is computed by constructing a specific basis of $\mathbb{F}_q^d$. Let $\pi: V \rightarrow F_{d-n}$ be the projection map to the second summand of $V = V_n \oplus F_{d-n}$.

- The first n vectors of the new basis are equal to the vectors in the old basis, i.e. $v'_i := v_i$ for $1 \leq i \leq n$.
- The vectors $v'_{n+1}, \dots, v'_{n'}$ of the new basis are chosen as a linearly independent subset of the vectors $\pi(v_1g), \dots, \pi(v_{n-1}g)$. Notice that this is possible since $\dim(V_n + V_ng) = n'$ and $v'_n = v_n \in V_n$ is fixed by g . If $n' < d$, then we take all the vectors $\pi(v_1g), \dots, \pi(v_{n-1}g)$ and otherwise we choose a linearly independent subset.
- Finally, in the case $n' < d$, that is, $n' = 2n - 1$, we extend $(v'_1, \dots, v'_{n'})$ to a basis $\mathcal{B}' = (v'_1, \dots, v'_d)$ of V by choosing a basis of $F_{d-n} \cap \text{Fix}(g)$ which is possible by condition (C2).

The matrix $\mathcal{L}' \in \text{GL}(d, q)$ is now chosen to be the base change matrix between $\mathcal{B}$ and $\mathcal{B}'$. Note that (C1) and (C2) ensure that $\langle H, H^g \rangle$ can be stingray embedded in $G^\mathcal{L}$ using Remark 7.17.

Remark 7.18. (1) $V_n = \langle v'_1, \dots, v'_n \rangle$.

(2) $V_n + V_ng = \langle v'_1, \dots, v'_{n'} \rangle$.

(3) $\langle v'_{n+1}, \dots, v'_d \rangle \subseteq \text{Fix}(H)$

(4) Note that (1) and (3) ensure that for our stingray embedded subgroup $H \cong \text{SL}(n, q)$ in $G^\mathcal{L}$ also $H^{\mathcal{L}'}$ is a stingray embedded subgroup in $G^{\mathcal{L}\mathcal{L}'}$.

From this point on, we assume that all of our matrices are expressed as elements of $G^{\mathcal{L}\mathcal{L}'}$. For the standard generators of $\text{SL}(n, q)$, there is nothing to do, while the matrix of g must be conjugated by the base change matrix $\mathcal{L}'$ which we denote by $c := g^{\mathcal{L}'}$.

At this point we formulate the last condition (C3). If (C3) is satisfied by c , then we can conclude that $\langle H, H^g \rangle \cong \text{SL}(n', q)$ in Section 7.4. The necessity for condition (C3) is discussed in more detail in Section 7.4.

Remark 7.19. The final condition on c is the following.

(C3) The vectors $\omega_i v'_j$ and $\omega_i v'_j c^{-\text{Tr}}$ for $1 \leq i \leq f$ and $1 \leq j \leq n - 1$ span the subspace $\langle v'_1, \dots, v'_{n-1}, v'_{n+1}, \dots, v'_{n'} \rangle$.

Definition 7.20. Assume the setting as described in Hypotheses 7.1. Let $g \in G^\mathcal{L}$ be a doubling element and $c := g^{\mathcal{L}'}$, where $\mathcal{L}'$ is chosen as in Remark 7.17. If c additionally satisfies (C3), then c is a *strong doubling element*.

Note that (C3) can only be verified after computing the base change matrix $\mathcal{L}'$ which is also the reason why this condition is introduced at this point. If (C3) is not satisfied by c , then we return to (SL2) and try another random element $a \in G^\mathcal{L}$. Note that $\langle H, H^g \rangle^{\mathcal{L}'} = \langle H, H^c \rangle$. We give an algorithm to compute a strong doubling element $c \in G^{\mathcal{L}\mathcal{L}'}$ satisfying (C1), (C2) and (C3) in pseudo code as `ComputeStrongDoublingElement` using `ComputeDoublingElement` of Section 7.4.

Algorithm 4: ComputeStrongDoublingElement

Input: $\blacktriangleright \langle X \rangle = G \leq \text{SL}(d, q)$
 $\blacktriangleright$ A base change matrix $\mathcal{L} \in \text{GL}(d, q)$
 $\blacktriangleright \text{SL}(n, q) \cong \langle Y_n \rangle = H \leq G^{\mathcal{L}}$ stingray embedded and constructively recognised
 $\blacktriangleright N \in \mathbb{N}$

Output: *fail* OR $(c, \mathcal{L}', \mathfrak{S}, N')$ where
 $\blacktriangleright c \in G^{\mathcal{L}\mathcal{L}'}$ is a strong doubling element,
 $\blacktriangleright \mathcal{L}' \in \text{GL}(d, q)$ is a base change matrix as in Remark 7.17,
 $\blacktriangleright \mathfrak{S}$ is an MSLP from $X \cup Y_n$ to c and
 $\blacktriangleright N' \in \mathbb{N}$ where $N - N'$ is the number of random selections that were used

function ComputeStrongDoublingElement($G, \mathcal{L}, H, N$)

```
1  while  $N > 0$  do
2       $(g, \mathfrak{S}, N) \leftarrow \text{ComputeDoublingElement}(G, \mathcal{L}, H, N)$  // Remarks 2.7 and 2.8
3       $\mathcal{L}' \leftarrow$  as described in Remark 7.17
4       $c \leftarrow g^{\mathcal{L}'}$  // (SL4)
5      if the  $(n' - n) \times (n - 1)$ -submatrix  $(c^{-1})_{i,j}$  for  $n + 1 \leq i \leq n'$  and  $1 \leq j \leq n - 1$  has
        full rank then
6          return  $(c, \mathcal{L}', \mathfrak{S}, N)$ 
7  return fail
```

7.4 Construction of transvections and standard generators

Given a strong doubling element $c \in G^{\mathcal{L}\mathcal{L}'}$ as described in Section 7.3 the goal of this section is to conclude that $\langle H, H^c \rangle \cong \text{SL}(n', q)$ and the construction of transvections and standard generators for $\langle H, H^c \rangle$. Everything done in this section is deterministic. Recall from Hypotheses 7.1 the setting of this section and that $c \in G^{\mathcal{L}\mathcal{L}'}$ satisfies (C1), (C2) and (C3). Moreover, note that $\langle H, H^c \rangle$ is stingray embedded in $G^{\mathcal{L}\mathcal{L}'}$ by the construction of $\mathcal{L}' \in \text{GL}(d, q)$ in Section 7.3. In this section the last phases (SL5) to (SL7) are described in the next remark.

Remark 7.21.

(SL5) Using c , construct elementary matrices $E_{j,n}(\omega_i)$ for $n < j \leq n'$.

(SL6) Using c , construct elementary matrices $E_{n,j}(\omega_i)$ for $n < j \leq n'$.

(SL7) Using the elementary matrices of phases (SL5) and (SL6) construct standard generators for $\langle H, H^c \rangle \cong \text{SL}(n', q)$ by assembling permutation matrices corresponding to n' - and $(n' - 1)$ -cycles as in Definition 2.3.

In (SL5) and (SL6), the elementary matrices $E_{j,n}(\omega_i)$ and $E_{n,j}(\omega_i)$ are conjugated by g and transformed by matrix multiplications into transvections of $\text{SL}(n', q) \cong \langle H, H^c \rangle$ as stingray embedded elements of $G^{\mathcal{L}\mathcal{L}'}$. This is necessary to subsequently compute permutation matrices of $\text{SL}(n', q)$ in (SL7). For (SL6) we need the transvections computed in (SL5). Recall from Definition 2.1 the notation $T_{v,w}$ for transvections.

The purpose of (SL5) is to construct the elements $E_{j,n}(\omega_i)$ for $1 \leq i \leq f$ and $n + 1 \leq j \leq n'$ as elements of $G^{\mathcal{L}\mathcal{L}'}$. For this consider the transvections $T_{\omega_i v'_j, v'_n}^c$ for $1 \leq i \leq f$ and $1 \leq j \leq n - 1$. One readily verifies that the conjugate $T_{\omega_i v'_j, v'_n}^c$ is equal to $T_{\omega_i v'_j c^{-\text{Tr}}, v'_n}$, since $v'_n c = v'_n$. Note that the transvections $T_{\omega_i v'_j, v'_n}^c$ fix v'_n , since c and the transvections $T_{\omega_i v'_j, v'_n}$ fix v'_n . Together this implies that $\langle v'_n \mid v'_j c^{-\text{Tr}} \rangle = 0$ holds for $1 \leq j \leq n - 1$. Thus, all vectors in

$$A := \{\omega_i v'_j \mid 1 \leq i \leq f, 1 \leq j \leq n - 1\} \cup \{\omega_i v'_j c^{-\text{Tr}} \mid 1 \leq i \leq f, 1 \leq j \leq n - 1\}$$

are orthogonal to v'_n with respect to the standard scalar product, and we know an MSLP for T_{w,v'_n} for all vectors $w \in A$. By (C3) we know that the vectors in A span the subspace $\langle v'_1, \dots, v'_{n-1}, v'_{n+1}, \dots, v'_{n'} \rangle$. We can thus express any $\omega_i v'_j$ with $1 \leq i \leq f$ and $n+1 \leq j \leq n'$ as an $\mathbb{F}_p$ -linear combination $\sum_{a \in A} \mu_a a$, and from this get $T_{\omega_i v'_j, v'_n} = \prod_{a \in A} T_{a, v'_n}^{\mu_a}$. Hence we can now construct the elements $E_{j,n}(\omega_i)$ as elements of $G^{\mathcal{LL}'}$.

Remark 7.22.

1. Note that we have to perform linear algebra computations over the prime field $\mathbb{F}_p$ here, but once again we use the results of the computations only to write an MSLP for these transvections.
2. In an implementation one would check (C3) already in `ComputeStrongDoublingElement` to avoid unnecessary computations at this point.

The idea of (SL5) is compute $E_{j,n}(\omega_i)^c$ for $1 \leq i \leq f$ and $1 \leq j \leq n-1$ and somehow to construct $E_{j,n}(\omega_i)$ for $1 \leq i \leq f$ and $n+1 \leq j \leq n'$ using the elements $\{E_{j,n}(\omega_i)^c \mid 1 \leq i \leq f, 1 \leq j \leq n-1\}$. To obtain a usable algorithm we start by computing $T_{\omega_i v'_j, v'_n}^c$ as elements of $G^{\mathcal{LL}'}$, i.e. $E_{j,n}(\omega_i)^c$, which is given in Lemma 7.23.

Lemma 7.23. *Let $n' = \min\{2n-1, d\}$, and let $c \in G^{\mathcal{LL}'}$ be as constructed in the previous phases. Let*

$$a := \begin{pmatrix} 1 & 0 & \dots & 0 & \omega_i(c^{-1})_{1,j} & 0 & \dots & 0 \\ 0 & 1 & \dots & 0 & \omega_i(c^{-1})_{2,j} & 0 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & 1 & \omega_i(c^{-1})_{n-1,j} & 0 & \dots & 0 \\ 0 & 0 & \dots & 0 & 1 & 0 & \dots & 0 \\ 0 & 0 & \dots & 0 & \omega_i(c^{-1})_{n+1,j} & 1 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & 0 & \omega_i(c^{-1})_{n',j} & 0 & \dots & 1 \end{pmatrix} \in \text{SL}(n', q).$$

Then $E_{j,n}(\omega_i)^c = \text{diag}(a, I_{d-n'}) \in G^{\mathcal{LL}'}$.

Proof. If $k \in \{n'+1, \dots, d\}$, then

$$e_k E_{j,n}(\omega_i)^c = e_k c^{-1} E_{j,n}(\omega_i) c = e_k E_{j,n}(\omega_i) c = e_k c = e_k.$$

Moreover for $k \in \{1, \dots, n'\} - \{n\}$

$$\begin{aligned} e_k c^{-1} E_{j,n}(\omega_i) c &= (c^{-1})_{k,-} E_{j,n}(\omega_i) c \\ &= ((c^{-1})_{k,-} + \omega_i(c^{-1})_{k,j} e_n) c \\ &= e_k c^{-1} c + \omega_i(c^{-1})_{k,j} e_n c = e_k + \omega_i(c^{-1})_{k,j} e_n \end{aligned}$$

and

$$e_n c^{-1} E_{j,n}(\omega_i) c = e_n E_{j,n}(\omega_i) c = e_n c = e_n. \quad \square$$

Remark 7.24. Using the standard generators of $H \cong \text{SL}(n, q)$, the matrix $E_{j,n}(\omega_i)^c$ can be multiplied by transvections of H resulting in row and column operations. Using row and column operations another element of $\langle H, H^c \rangle$ can be constructed where the entries in the n -th column of $E_{j,n}(\omega_i)^c$ above the (n, n) entry are zero such that matrices of the form $\text{diag}(a_{j,n,\omega_i}, I_{d-n'})$ are

constructed where

$$a_{j,n,\omega_i} := \begin{pmatrix} 1 & 0 & \dots & 0 & 0 & 0 & \dots & 0 \\ 0 & 1 & \dots & 0 & 0 & 0 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & 1 & 0 & 0 & \dots & 0 \\ 0 & 0 & \dots & 0 & 1 & 0 & \dots & 0 \\ 0 & 0 & \dots & 0 & \omega_i(c^{-1})_{n+1,j} & 1 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & 0 & \omega_i(c^{-1})_{n',j} & 0 & \dots & 1 \end{pmatrix}.$$

In the following we denote the process of using row and column operations to construct another matrix with zeros at specific positions as “eliminating” these entries. Using (C3) the column vectors $((c^{-1})_{n+1,i}, \dots, (c^{-1})_{n',i})$ for $1 \leq i \leq n-1$ of length $(n-1)$ below the n -row entry of c^{-1} generate the full $f(n-1)$ dimensional $\mathbb{F}_p$ -vector space. Observe that the group $G_{n'} := \langle \{a_{j,n,\omega_i} \mid 1 \leq j \leq n-1, 1 \leq i \leq f\} \rangle$ is abelian and in fact isomorphic to $\mathbb{F}_q^{n-1}$ via the isomorphism given by

$$\varphi: \mathbb{F}_q^{n-1} \rightarrow G_{n'}, (\lambda_{n+1}, \dots, \lambda_{n'}) \mapsto T_{\sum_{n+1}^{n'} \lambda_i v_i, v_n} = \begin{pmatrix} 1 & 0 & \dots & 0 & 0 & 0 & \dots & 0 \\ 0 & 1 & \dots & 0 & 0 & 0 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & 1 & 0 & 0 & \dots & 0 \\ 0 & 0 & \dots & 0 & 1 & 0 & \dots & 0 \\ 0 & 0 & \dots & 0 & \lambda_{n+1} & 1 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & 0 & \lambda_{n'} & 0 & \dots & 1 \end{pmatrix}.$$

Note that our goal is the computation of the transvections $E_{j,n}(\omega_i)$ for $1 \leq i \leq f$ and $n+1 \leq j \leq n'$. By multiplying the matrices a_{j,n,ω_i} appropriately, the standard basis of $\mathbb{F}_q^{n-1}$ as an $\mathbb{F}_p$ -vector space, i.e. $\omega_1 e_1, \dots, \omega_f e_1, \dots, \omega_1 e_{n-1}, \dots, \omega_f e_{n-1}$, can be computed and thus the transvections $E_{j,n}(\omega_i)$ for $1 \leq i \leq f$ and $n+1 \leq j \leq n'$.

We combine Lemma 7.23 and Remark 7.24 into **ComputeVerticalTransvections**.

Algorithm 5: ComputeVerticalTransvections

Input: ► $\text{SL}(n, q) \cong \langle Y_n \rangle = H \leq \text{SL}(d, q)$ stingray embedded and constructively recognised
 ► $c \in \text{SL}(d, q)$ a strong doubling element
Output: ► $T_V := \{E_{j,n}(\omega_i) \mid 1 \leq i \leq f, n+1 \leq j \leq n'\} \subset \langle H, H^c \rangle$ transvections of $\text{SL}(n', q)$
 ► An MSLP $\mathfrak{S}$ from $Y_n \cup \{c\}$ to T_V

function ComputeVerticalTransvections(H, c)

```

1  // Function implements (SL5) based on Lemma 7.23 and Remark 7.24
2   $\tilde{T}_V \leftarrow []$ 
3  for  $\lambda \in \{\omega_1, \dots, \omega_f\}$  and  $j \in \{2, \dots, n-1\}$  do
4       $T \leftarrow E_{j,n}(\lambda)^c$ 
5      for  $k \in [1, \dots, n-1]$  do
6           $T \leftarrow E_{k,n}(-\lambda(c^{-1})_{k,j})T$  // Note that  $E_{k,n}(-\lambda(c^{-1})_{k,j}) \in H$ 
7          Add( $\tilde{T}_V, T$ )
8   $T_V \leftarrow []$ 
9  for  $\lambda \in \{\omega_1, \dots, \omega_f\}$  and  $j \in \{n+1, \dots, n'\}$  do
10      $E_{j,n}(\lambda) \leftarrow$  Multiply the matrices of  $\tilde{T}_V$  suitable
11     Add( $T_V, E_{j,n}(\lambda)$ )
12  $\mathfrak{S} \leftarrow$  MSLP for the computations of  $T_V$ 
return ( $T_V, \mathfrak{S}$ )

```

where $e_k + \omega_i(c^{-1})_{k,n}c_{j,-}$ is the k -th row of $E_{n,j}(1)^c$ and $\omega_i c_{j,-} + e_n$ is the n -th row of $E_{n,j}(1)^c$. Hence, the addition of these rows can be achieved by multiplying with $E_{k,n}(-(c^{-1})_{k,n})$ from the left. Note that $E_{k,n}(-(c^{-1})_{k,n}) \in \text{SL}(n, q)$ and, therefore, we can write $E_{k,n}(-(c^{-1})_{k,n})$ as a word in Y_n . After these $n - 1$ row operations, the matrix of (1) is transformed into the matrix of (2):

$$\left(\begin{array}{ccc|c|ccc} & & & * & & & \\ & & & \vdots & & & \\ & & & * & & & \\ I_{n-1} & & & & & 0 & \\ \hline * & \dots & * & * & * & \dots & * \\ * & \dots & * & * & * & \dots & * \\ \hline \vdots & \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ * & \dots & * & * & * & \dots & * \end{array} \right). \quad (2)$$

We proceed analogously with the rows below the n -th row using the same argument for $k \in \{n+1, \dots, n'\}$. Notice that this is only possible since we have already computed the transvections $E_{j,n}(\omega_i)$ for $1 \leq i \leq f$ and $n+1 \leq j \leq n'$ in (SL5). After these additional $n - 1$ row operations we transform (2) into (3).

$$\left(\begin{array}{ccc|c|ccc} & & & * & & & \\ & & & \vdots & & & \\ & & & * & & & \\ I_{n-1} & & & & & 0 & \\ \hline * & \dots & * & * & * & \dots & * \\ \hline & & & * & & & \\ 0 & & & \vdots & & I_{n-1} & \\ & & & * & & & \end{array} \right). \quad (3)$$

Notice that the green entries are known, i.e. the entry at position (k, n) is $-(c^{-1})_{k,n}$, since $(e_k + \omega_i(c^{-1})_{k,n}c_{j,-}) + (-(c^{-1})_{k,n})(\omega_i c_{j,-} + e_n) = e_k - (c^{-1})_{k,n}e_n$. By adding the columns 1 to $n - 1$ multiplying by the corresponding scalars to the n -th column, the green entries in the n -th column above the n -th entry can be eliminated. This can be performed by multiplying the matrices $E_{k,n}((c^{-1})_{k,n}) \in H$ from the right. The entry in position (n, n) is changed to 1 during these operations if this was not the case which is shown at the end of this remark. After these column operations (3) is transformed into (4).

$$\left(\begin{array}{ccc|c|ccc} & & & 0 & & & \\ & & & \vdots & & & \\ & & & 0 & & & \\ I_{n-1} & & & & & 0 & \\ \hline * & \dots & * & * & * & \dots & * \\ \hline & & & * & & & \\ 0 & & & \vdots & & I_{n-1} & \\ & & & * & & & \end{array} \right). \quad (4)$$

The rest is now trivial. The rows 1 to $n - 1$ are added to the n -th row in order to eliminate the entries to the left of the n -th entry in the n -th row. Moreover, the columns $n + 1$ to n' are added to the n -th column to eliminate the entries below the n -th entry, resulting in the final matrix given in (5).

$$\left(\begin{array}{ccc|c|ccc} & & & 0 & & & \\ & & & \vdots & & & \\ & & & 0 & & & \\ I_{n-1} & & & & & 0 & \\ \hline 0 & \dots & 0 & 1 & * & \dots & * \\ \hline & & & 0 & & & \\ 0 & & & \vdots & & I_{n-1} & \\ & & & 0 & & & \end{array} \right). \quad (5)$$

The entry in Position (n, n) of (5) must be 1 since this is an upper triangular matrix which is also contained in SL . Note that the entries in position (n, n) in this matrix and matrix in (4) are the same which is why it already was 1 before these final row and column operations. Moreover, the entries in blue are equal to $(c_{j,-})_{n+1, \dots, n'}$ which are equal to $e_1, \dots, e_{n-1}$ by choosing the basis $\mathcal{B}'$ of phase (SL4) advisedly. Overall, $E_{n,j}(1)^c$ is transformed into $E_{n,n+j}(1)$ using only

transvections for which an MSLP is known. Therefore, an MSLP evaluating to $E_{n,n+j}(1)$ is constructed.

We also give a pseudo code performing (SL6) as `ComputeHorizontalTransvections` in Algorithm 6.

Algorithm 6: `ComputeHorizontalTransvections`

Input: ▶ $\text{SL}(n, q) \cong \langle Y_n \rangle = H \leq \text{SL}(d, q)$ stingray embedded and constructively recognised
 ▶ $c \in \text{SL}(d, q)$ a strong doubling element
Output: ▶ $T_H := \{E_{n,j}(1) \mid n+1 \leq j \leq n'\} \subset \langle H, H^c \rangle$ transvections of $\text{SL}(n', q)$
 ▶ An MSLP $\mathfrak{S}$ from $Y_n \cup \{c\} \cup T_V$ to T_H

function `ComputeHorizontalTransvections`(H, c)

```

1  // Function implements (SL6) based on Lemma 7.25 and Remark 7.26
2   $T_H \leftarrow []$ 
3  for  $j \in \{2, \dots, n-1\}$  do
4     $T \leftarrow E_{n,j}(1)^c$ 
5    for  $k \in [1, \dots, n-1]$  do
6       $T \leftarrow E_{k,n}(-(c^{-1})_{k,n})T$  // As in (2) of Remark 7.26
7    for  $k \in [n+1, \dots, n']$  do
8       $T \leftarrow E_{k,n}(-(c^{-1})_{k,n})T$  // As in (3) of Remark 7.26
9    for  $k \in [1, \dots, n-1]$  do
10      $T \leftarrow TE_{k,n}((c^{-1})_{k,n})$  // As in (4) of Remark 7.26
11   for  $k \in [1, \dots, n-1]$  do
12      $T \leftarrow E_{n,k}(-(c^{-1})_{j,k})T$  // As in (5) of Remark 7.26
13   for  $k \in [n+1, \dots, n']$  do
14      $T \leftarrow TE_{k,n}((c^{-1})_{k,n})$  // As in (5) of Remark 7.26
15    $\text{Add}(T_H, T)$ 
16    $\mathfrak{S} \leftarrow \text{MSLP for the computations of } T_H$ 
17 return  $(T_H, \mathfrak{S})$ 

```

In the last and final phase, the n' and $n' - 1$ cycles are now assembled. This can easily be realized with the transvections from (SL5) and (SL6) as described in Lemma 7.27.

Lemma 7.27. *The permutation matrices z'_1, z'_2 as in Definition 2.3 for $\text{SL}(n', q)$ can be computed using the matrices of the set $X = \{z_1, z_2, E_{i,n}(1), E_{n,i}(1)\}$ for $n+1 \leq i \leq n'$.*

Proof. Transpositions can be computed easily as $E_{i,n}^{-1}(1)E_{n,i}(1)E_{i,n}^{-1}(1)$ is the permutation matrix which corresponds to $(n, i) \in S_{n'}$ for $n < i \leq n'$, where the entry in position (i, n) is equal to -1 and $E_{i,n}(1)E_{n,i}^{-1}(1)E_{i,n}(1)$ is the permutation matrix which corresponds to $(n, i) \in S_{n'}$ for $n < i \leq n'$, where the entry in position (n, i) is equal to -1 . Moreover

$$\begin{aligned}
& (n, n') \cdot (n, n' - 1) \cdot (n, n' - 2) \cdot \dots \cdot (n, n + 1) \\
&= (n, n', n' - 1) \cdot (n, n' - 2) \cdot \dots \cdot (n, n + 1) \\
&= (n, n', n' - 1, \dots, n + 1).
\end{aligned}$$

and

$$\begin{aligned}
& (n, n - 1, \dots, 1) \cdot (n, n', n' - 1, \dots, n + 1) = (n, n - 1, \dots, 1, n', n' - 1, \dots, n + 1) \\
&= (n', n' - 1, \dots, 1), \\
& (n, n - 1, \dots, 2) \cdot (n, n', n' - 1, \dots, n + 1) = (n, n - 1, \dots, 2, n', n' - 1, \dots, n + 1) \\
&= (n', n' - 1, \dots, 2).
\end{aligned}$$

Because of the position of -1 in the transpositions, the matrices correspond to the standard generators of Definition 2.3. $\square$

7.5 GoingUp step

Finally all phases and subalgorithms of this section are combined into one single algorithm which can be used for a single **GoingUp** step as stated in [Theorem 7.2](#). The seven phases of the previous sections are summarized in [Remark 7.28](#). Recall that phases (SL1) to (SL3) are formulated in [Remark 7.6](#) of [Section 7.2](#), that phase (SL4) is formulated in [Remark 7.16](#) of [Section 7.3](#) and that phases (SL5) to (SL7) are formulated in [Remark 7.21](#) of [Section 7.4](#).

Remark 7.28. The following seven phases must be performed for [Theorem 7.2](#) and, therefore, for one **GoingUp** step:

- (SL1) Construct an element $t \in H$ which has a fixed space of dimension $d - n + 1$.
- (SL2) Choose random elements $a \in G^{\mathcal{L}}$ until $\tilde{g} := t^a$ is a weak doubling element.
- (SL3) Find a conjugate $g \in G^{\mathcal{L}}$ of $\tilde{g}$ which is a doubling element.
- (SL4) Compute a base change matrix $\mathcal{L}'$ such that $\langle H, H^g \rangle^{\mathcal{L}'}$ is stingray embedded in $G^{\mathcal{L}\mathcal{L}'}$. Set $c := g^{\mathcal{L}'}$ and verify whether c is a strong doubling element.
- (SL5) Using c , construct transvections $E_{j,n}(\omega_i)$ for $n < j \leq n'$.
- (SL6) Using c , construct transvections $E_{n,j}(\omega_i)$ for $n < j \leq n'$.
- (SL7) Using the transvections of (SL5) and (SL6) construct standard generators for $\langle H, H^c \rangle \cong \text{SL}(n', q)$ by assembling permutation matrices corresponding to n' - and $(n' - 1)$ -cycles as in [Definition 2.3](#).

Note that the condition (C3) is tested by **ComputeStrongDoublingElement** in (SL4) and if c does not satisfy (C3), then we return to (SL2). An overall algorithm for one **GoingUp** step is given in pseudo code as **GoingUpStep**.

Algorithm 7: GoingUpStep

Input: ▶ $\langle X \rangle = G \leq \text{SL}(d, q)$
 ▶ A base change matrix $\mathcal{L} \in \text{GL}(d, q)$
 ▶ $\text{SL}(n, q) \cong \langle Y_n \rangle = H \leq G^{\mathcal{L}}$ stingray embedded and constructively recognised
 ▶ $N \in \mathbb{N}$
Output: *fail* OR $(Y_{n'}, \mathcal{L}', \mathfrak{S}, N')$ where
 ▶ $\text{SL}(\min\{2n - 1, d\}, q) \cong \langle Y_{n'} \rangle = \tilde{H}$,
 ▶ $\mathcal{L}'$ is a base change matrix such that $\tilde{H}$ is stingray embedded in $G^{\mathcal{L}\mathcal{L}'}$,
 ▶ $\mathfrak{S}$ is an MSLP from $X \cup Y_n$ to the standard generators $Y_{n'}$ of $\tilde{H}$ and
 ▶ $N' \in \mathbb{N}$ where $N - N'$ is the number of random selections that were used

function **GoingUpStep**($G, H, \mathcal{L}, N$)

```

1   $(c, \mathcal{L}', \mathfrak{S}_1, N) \leftarrow \text{ComputeStrongDoublingElement}(G, H, \mathcal{L}, N)$ 
2  if  $c = \text{fail}$  then
3    |   return fail
4   $T_V, \mathfrak{S}_2 \leftarrow \text{ComputeVerticalTransvections}(H, c)$ 
5   $T_H, \mathfrak{S}_3 \leftarrow \text{ComputeHorizontalTransvections}(H, c)$ 
6  Use  $T_V$  and  $T_H$  to construct  $z_1$  and  $z_2$  of  $\text{SL}(n', q)$  as an MSLP  $\mathfrak{S}_4$  using Lemma 7.27
   // (SL7)
7  Compose  $\mathfrak{S}_1, \mathfrak{S}_2, \mathfrak{S}_3, \mathfrak{S}_4$  into one MSLP  $\mathfrak{S}$ 
8  return  $(\langle H, H^c \rangle, \mathcal{L}', \mathfrak{S}, N)$ 
```

Theorem 7.29. **GoingUpStep** terminates using at most N random selections and works correctly.

Proof. The correctness is clear since the correctness of each phase has been proven in the preceding sections. It remains to show termination. Note that most lines are deterministic and can be performed in finite time. The only critical line is line 1, i.e. finding a suitable c , which is controlled by N to have only a finite number of tries. $\square$

7.6 Combining GoingUp steps

We have demonstrated how we can compute standard generators for a stingray embedded special linear group of dimension nearly twice that of a given stingray embedded special linear group with standard generators. In this section `GoingUpStep` is used to develop an algorithm which can be used to compute standard generators for $G \leq \text{SL}(d, q)$ with $G \cong \text{SL}(d, q)$, where $H \leq G$ with $H \cong \text{SL}(2, q)$ are given and standard generators of H are known.

Algorithm 8: GoingUp

Input: $\blacktriangleright \langle X \rangle = G = \text{SL}(d, q)$
 $\blacktriangleright$ A base change matrix $\mathcal{L} \in \text{GL}(d, q)$
 $\blacktriangleright \text{SL}(2, q) \cong \langle Y_2 \rangle = H \leq G^{\mathcal{L}}$ stingray embedded and constructively recognised
 $\blacktriangleright N \in \mathbb{N}$

Output: *fail* OR $(\mathcal{L}', \mathfrak{S}, N')$ where
 $\blacktriangleright \mathcal{L}'$ is a base change matrix,
 $\blacktriangleright \mathfrak{S}$ is an MSLP from $X \cup Y_2$ to the standard generators of $G^{\mathcal{L}'}$ and
 $\blacktriangleright N' \in \mathbb{N}$ where $N - N'$ is the number of random selections that were used

function `GoingUp`($G, H, \mathcal{L}, N$)

```

1   $n \leftarrow 2$ 
2   $\mathfrak{S} \leftarrow$  an MSLP from  $X \cup Y_2$  to  $X \cup Y_2$ 
3  while  $n < d$  do
4       $n \leftarrow \min\{2 \cdot n - 1, d\}$  // Nearly Double the dimension.
5       $(H, \mathcal{L}, \mathfrak{S}', N) \leftarrow \text{GoingUpStep}(G, H, \mathcal{L}, N)$  // Remarks 2.7 and 2.8
6       $\mathfrak{S} \leftarrow$  Compose  $\mathfrak{S}$  and  $\mathfrak{S}'$ 
7  return  $(\mathcal{L}, \mathfrak{S}, N)$ 
```

Theorem 7.30. `GoingUp` terminates using at most N random selections and works correctly.

Proof. Follows immediately from Theorem 7.29. $\square$

8 Implementation and timing

The `GoingDown`, `BaseCase` and `GoingUp` algorithms presented here have been implemented in GAP [12] by the fourth author. In this section we compare the run-time of this implementation with the constructive recognition algorithms [10, 20] available in Magma [4].

Since the algorithms are implemented in different computer algebra systems, which have quite different performance profiles, a fair direct comparison is difficult. Generally, the underpinning support functions for working with matrices and polynomials over finite fields in Magma outperform those in GAP. Despite this, the result of our comparison shown in Table 1 is quite favorable to our implementation.

All computations for both implementations were performed on a Linux server with two AMD EPYC 9554 64-core processors and 1.5 TB RAM, running Gentoo 2.14 with kernel version 6.1.69. For Magma version 2.28-8 was used and for GAP version 4.13.0 together with its default set of packages loaded plus the `cvec` package version 2.8.1 (for faster characteristic polynomials) with a modified version of `recog` 1.4.2, where the modification is that we inserted our new algorithms. These modifications will be part of a future `recog` release.

d	$q = 4$		$q = 5$		$q = 121$	
	GAP	Magma	GAP	Magma	GAP	Magma
100	< 1	7	< 1	3	< 1	86
200	6	20	1	8	2	436
300	11	39	4	16	7	12595 ^a
500	62	104	16	62	31	timeout
700	168	257	40	249	79	—
1000	337	515	81	16047 ^b	176	—
2000	2671	4014	532	timeout	2220	—
3000	9626	14780	2028	timeout	11637	—

^aFour runs completed, six exceeded the time limit

^bTwo runs completed, eight exceeded the time limit

Table 1: Time in seconds comparing our GAP implementation against Magma. An entry with a dash means we did not measure this computation. Entries with “timeout” indicate that no run completed within 20 000 seconds.

For Magma we used `ClassicalConstructiveRecognition(SL(d,q),"SL",d,q)`; as test command while for GAP `RECOG.FindStdGensSmallerMatrices_SL(SL(d,q))`; was used. For each used parameter pair (d, q) we run the command ten times in each system. Table 1 reports the average of these runs. Note that computations that exceeded 20 000 seconds (about 5.5 hours) were aborted. In some cases only a subset of the runs for a given pair (d, q) terminated within that time limit. In this case we treated the aborted computations as if they had completed within 20 000 seconds (which is generous; in some cases we actually waited for 15 hours before aborting).

References

- [1] Henrik Bäärnhielm, Derek Holt, Charles R. Leedham-Green, and Eamonn A. O’Brien, *A practical model for computation with matrix groups*, J. Symbolic Comput. **68** (2015), no. part 1, 27–60, DOI [10.1016/j.jsc.2014.08.006](https://doi.org/10.1016/j.jsc.2014.08.006).
- [2] László Babai, Robert Beals, and Ákos Seress, *Polynomial-time theory of matrix groups*, Proceedings of the 41st annual ACM symposium on theory of computing, STOC ’09. Bethesda, MD, USA, May 31 – June 2, 2009, 2009, pp. 55–64, DOI [10.1145/1536414.1536425](https://doi.org/10.1145/1536414.1536425).
- [3] László Babai, *Randomization in group algorithms: conceptual questions*, Groups and computation, II (New Brunswick, NJ, 1995), DIMACS Ser. Discrete Math. Theoret. Comput. Sci., vol. 28, Amer. Math. Soc., Providence, RI, 1997, pp. 1–17, DOI [10.1090/dimacs/028/01](https://doi.org/10.1090/dimacs/028/01).
- [4] Wieb Bosma, John Cannon, and Catherine Playoust, *The Magma algebra system. I. The user language*, J. Symbolic Comput. **24** (1997), no. 3-4, 235–265, DOI [10.1006/jsc.1996.0125](https://doi.org/10.1006/jsc.1996.0125). Computational algebra and number theory (London, 1993).
- [5] Frank Celler and Charles R. Leedham-Green, *A constructive recognition algorithm for the special linear group*, The atlas of finite groups: ten years on (Birmingham, 1995), 1998, pp. 11–26, DOI [10.1017/CBO9780511565830.007](https://doi.org/10.1017/CBO9780511565830.007).
- [6] Frank Celler, Charles R. Leedham-Green, Scott H. Murray, Alice C. Niemeyer, and Eamonn A. O’Brien, *Generating random elements of a finite group*, Comm. Algebra **23** (1995), no. 13, 4931–4948, DOI [10.1080/00927879508825509](https://doi.org/10.1080/00927879508825509).
- [7] Marston Conder, Charles R. Leedham-Green, and Eamonn A. O’Brien, *Constructive recognition of PSL(2, q)*, Trans. Amer. Math. Soc. **358** (2006), no. 3, 1203–1221, DOI [10.1090/S0002-9947-05-03756-6](https://doi.org/10.1090/S0002-9947-05-03756-6).

- [8] Marston Conder and Charles R. Leedham-Green, *Fast recognition of classical groups over large fields*, Ohio State Univ. Math. Res. Inst. Publ., vol. 8, de Gruyter, Berlin, 2001, pp. 113–121, DOI [10.1515/9783110872743.113](https://doi.org/10.1515/9783110872743.113).
- [9] Elliot Costi, *Constructive membership testing in classical groups*, Ph.D. Thesis, Queen Mary, University of London, 2009.
- [10] Heiko Dietrich, Charles R. Leedham-Green, Frank Lübeck, and Eamonn A. O’Brien, *Constructive recognition of classical groups in even characteristic*, J. Algebra **391** (2013), 227–255, DOI [10.1016/j.jalgebra.2013.04.031](https://doi.org/10.1016/j.jalgebra.2013.04.031).
- [11] Heiko Dietrich, Charles R. Leedham-Green, and Eamonn A. O’Brien, *Effective black-box constructive recognition of classical groups*, Journal of Algebra **421** (2015), 460–492, DOI [10.1016/j.jalgebra.2014.08.039](https://doi.org/10.1016/j.jalgebra.2014.08.039). Special issue in memory of Ákos Seress.
- [12] *GAP – Groups, Algorithms, and Programming, Version 4.13.0*, The GAP Group, 2024. <https://www.gap-system.org>.
- [13] Stephen P. Glasby, Alice C. Niemeyer, and Cheryl E. Praeger, *Random generation of direct sums of finite non-degenerate subspaces*, Linear Algebra Appl. **649** (2022), 408–432, DOI [10.1016/j.laa.2022.05.016](https://doi.org/10.1016/j.laa.2022.05.016).
- [14] ———, *The probability of spanning a classical space by two non-degenerate subspaces of complementary dimensions*, Finite Fields Appl. **82** (2022), Paper No. 102055, 31, DOI [10.1016/j.faa.2022.102055](https://doi.org/10.1016/j.faa.2022.102055).
- [15] ———, *Bipartite q -Kneser graphs and two-generated irreducible linear groups*, posted on 2023, 23 pp., DOI [10.48550/arXiv.2312.05529](https://doi.org/10.48550/arXiv.2312.05529), available at [arXiv:2312.05529](https://arxiv.org/abs/2312.05529).
- [16] ———, *The Probability that two Elements with large 1-Eigenspaces generate a Classical Group*, in preparation.
- [17] Stephen P. Glasby, Alice C. Niemeyer, Cheryl E. Praeger, and A.E. Zalesski, *Absolutely irreducible quasimple linear groups containing certain elements of prime order* (2024), in preparation.
- [18] Derek Holt, Charles R. Leedham-Green, and Eamonn A. O’Brien, *Constructing composition factors for a linear group in polynomial time*, J. Algebra **561** (2020), 215–236, DOI [10.1016/j.jalgebra.2020.02.018](https://doi.org/10.1016/j.jalgebra.2020.02.018).
- [19] William M. Kantor and Ákos Seress, *Black box classical groups*, Mem. Amer. Math. Soc. **149** (2001), no. 708, viii+168, DOI [10.1090/memo/0708](https://doi.org/10.1090/memo/0708).
- [20] Charles R. Leedham-Green and Eamonn A. O’Brien, *Constructive recognition of classical groups in odd characteristic*, J. Algebra **322** (2009), no. 3, 833–881, DOI [10.1016/j.jalgebra.2009.04.028](https://doi.org/10.1016/j.jalgebra.2009.04.028).
- [21] Frank Lübeck, Kay Magaard, and Eamonn A. O’Brien, *Constructive recognition of $SL_3(q)$* , Journal of Algebra **316** (2007), no. 2, 619–633, DOI [10.1016/j.jalgebra.2007.01.020](https://doi.org/10.1016/j.jalgebra.2007.01.020).
- [22] Peter M. Neumann and Cheryl E. Praeger, *A recognition algorithm for special linear groups*, Proc. London Math. Soc. (3) **65** (1992), no. 3, 555–603, DOI [10.1112/plms/s3-65.3.555](https://doi.org/10.1112/plms/s3-65.3.555).
- [23] Max Neunhöffer and Ákos Seress, *A data structure for a uniform approach to computations with finite groups*, Proceedings of the 2006 international symposium on symbolic and algebraic computation, ISSAC 06, Genova, Italy, July 9–12, 2006, 2006, pp. 254–261, DOI [10.1145/1145768.1145811](https://doi.org/10.1145/1145768.1145811).
- [24] Alice C. Niemeyer, Tomasz Popiel, Cheryl E. Praeger, and Daniel Rademacher, *Showcasing straight-line programs with memory via matrix Bruhat decomposition*, posted on 2024, 32 pp., DOI [10.48550/arXiv.1305.5617](https://doi.org/10.48550/arXiv.1305.5617), available at [arXiv:1305.5617](https://arxiv.org/abs/1305.5617).
- [25] Alice C. Niemeyer and Cheryl E. Praeger, *Elements in finite classical groups whose powers have large 1-eigenspaces*, Discrete Math. Theor. Comput. Sci. **16** (2014), no. 1, 303–312, DOI [10.46298/dmtcs.3908](https://doi.org/10.46298/dmtcs.3908).
- [26] ———, *A recognition algorithm for classical groups over finite fields*, Proc. London Math. Soc. (3) **77** (1998), no. 1, 117–169, DOI [10.1112/S0024611598000422](https://doi.org/10.1112/S0024611598000422).
- [27] ———, *Implementing a recognition algorithm for classical groups*, Groups and computation, II (New Brunswick, NJ, 1995), DIMACS Ser. Discrete Math. Theoret. Comput. Sci., vol. 28, Amer. Math. Soc., Providence, RI, 1997, pp. 273–296.
- [28] Eamonn A. O’Brien, *Algorithms for matrix groups*, Groups St Andrews 2009 in Bath. Volume 2, London Math. Soc. Lecture Note Ser., vol. 388, Cambridge Univ. Press, Cambridge, 2011, pp. 297–323, DOI [10.1017/CBO9780511842474.002](https://doi.org/10.1017/CBO9780511842474.002).
- [29] Cheryl E. Praeger, Ákos Seress, and Şükrü Yalçınkaya, *Generation of finite classical groups by pairs of elements with large fixed point spaces.*, J. Algebra **421** (2015), 56–101, DOI [10.1016/j.jalgebra.2014.08.020](https://doi.org/10.1016/j.jalgebra.2014.08.020).
- [30] Donald E. Taylor, *The geometry of the classical groups*, Sigma Series in Pure Mathematics, vol. 9, Heldermann Verlag, Berlin, 1992.