
ASPECT AND OPINION TERM EXTRACTION USING GRAPH ATTENTION NETWORK

Abir Chakraborty

Microsoft

Abir.Chakraborty@microsoft

ABSTRACT

In this work we investigate the capability of Graph Attention Network for extracting aspect and opinion terms. Aspect and opinion term extraction is posed as a token-level classification task akin to named entity recognition. We use the dependency tree of the input query as additional feature in a Graph Attention Network along with the token and part-of-speech features. We show that the dependency structure is a powerful feature that in the presence of a CRF layer substantially improves the performance and generates the best result on the commonly used datasets from SemEval 2014, 2015 and 2016. We experiment with additional layers like BiLSTM and Transformer in addition to the CRF layer. We also show that our approach works well in the presence of multiple aspects or sentiments in the same query and it is not necessary to modify the dependency tree based on a single aspect as was the original application for sentiment classification.

Keywords aspect · opinion · graph attention · CRF

1 Introduction

Extracting information from customer feedback is a key capability required for identifying current drawbacks and scope for further improvement. Online shoppers routinely provide feedback on their experience with the purchased product that are not just important for the other potential customers but also a critical feedback to the product manufacturers for the next cycle of iteration. Similar feedbacks are available in various other domains ranging from Manufacturing to Healthcare where granular opinions (sentiments) about various dimensions (aspects) of the used product (or service) are available in textual form but need to be understood. Due to the presence of multiple aspects (and the corresponding sentiments) extraction of these aspect-sentiment pairs is a challenging task and since its introduction in 2014 (SemEval-2014 Task-4, Pontiki et al.) Aspect Based Sentiment Analysis (ABSA) attracted various different approaches and is still under active consideration.

ABSA demands semantic understanding of the sentence where it is necessary to identify the aspect terms (defining "what") and the opinion terms (defining "why") and the connection between each related pairs (resulting in a positive, neutral or negative sentiment, i.e., "how"). A relatively simple example would be "The price is reasonable although the service is poor" where "price" and "service" are the aspects with the corresponding opinion terms "reasonable" and "poor", respectively. Here, the relative locations of the aspect and opinion word can help each other to identify these terms. However, other examples like "prices are in line" (neutral sentiment) and "For the price, you can not eat this well in Manhattan" (positive sentiment) it is not obvious which opinion terms are driving the sentiments and their linkage with the aspect terms. As a result, while it is possible to capture the syntactical structure and dependency between words it is necessary to capture a deeper meaning of each token (word) that should not be relied upon the limited number of examples (that are hallmark of all ABSA datasets) but rich representations provided by large language models like BERT and RoBERTA.

In addition to large model based initial representations, additional information from parts-of-speech and dependency structure play a critical role as can be seen in some of the previous ABSA work where the objective is to predict only the sentiment associated with a particular aspect. While it is generally understood that a confluence of deep encoders and graph-based representation of the input sentence will drive better performance it is not clear what is the optimal

Dataset		Train	Dev	Test	Total
LAPTOP	#sent	2741	304	800	4245
	#aspect	2041	256	634	2931
REST	#sent	3490	387	2158	6035
	#aspect	3893	413	2287	6593

Table 1: Statistics of the dataset in Li et al. (2019c)

graph representation of a sentence, especially for ABSA kind of task. In case of polarity detection, it can be argued that only the part of the dependency tree associated with a particular aspect is significant and the rest of the tree can be ignored. However, when we convert the task into aspect and opinion term extraction it is not clear whether any part of the sentence has higher significance compared to the rest.

In this work we address the problem of aspect and opinion term extraction from input sentences. As an example, "the weather was gloomy, but the food was tasty" has two sets of aspect-opinion-sentiment tuples, i.e., (weather, gloomy, negative) and (food, tasty, positive). We use ABSA datasets with token level labels - one set for the aspects and one set for the opinions. Thus, the aspect and opinion term extraction becomes a NER task with different types of entity classes. The tags for the aspects include the sentiment, (for opinion it is only the BIEOS tag), however, what is missing is the connection between the aspects and opinion terms. Thus, our aspect models predict (weather, negative) and (food, positive), opinion models predict (gloomy) and (tasty), without making the subsequent contractions. We encode the graph associated with the dependency parsing of the input sentence and create token (node) level representations that take care of both the neighborhood (connected edges) and dependency type (edge type) of each token.

The organization of the paper is as follows. In the next section we provide a detailed literature survey on the techniques employed for aspect and opinion extraction task of ABSA. Next, we present the details of the proposed model. Subsequently, the model predictions and comparisons with other baseline methods are discussed. Finally, conclusions are drawn and scope for future works is outlined.

2 Related Work

Most of the ABSA work concern with the sentiment polarity detection associated with a particular aspect and the approaches varied from initial SVM classifier with handcrafted features to deep learning classifiers based on RNN (Wang et al., 2016, 2018; He et al., 2018; Ma et al., 2017), Transformer (Hoang et al., 2019; Zeng et al., 2019; Xu et al., 2019) and memory network (Tang et al., 2016; Chen et al., 2017; Tay et al., 2017; Lin et al., 2019). There are few graph based approaches as well, e.g., graph convolution network (GCN) based model of Zhang et al. (2019) and Sun et al. (2019), graph attention network (GAT) based model of Huang and Carley (2019) and Wang et al. (2020) where the latter modified the original dependency tree to create an aspect-oriented dependency tree that was used further in a relational GAT (R-GAT) where different relations contributed differently in the computation of nodal representations. However, the approach assumes the presence of only one aspect at a time in the given input.

On the other hand, an end-to-end ABSA tries to extract all the aspect terms in a given query simultaneously along with the corresponding sentiments. The first approach towards E2E-ABSA was provided by Li et al. (2019c) where a unified tagging scheme (combining the position and sentiment) was used, i.e., the token labels were one of $B-\{POS, NEG, NEU\}$, $I-\{POS, NEG, NEU\}$, $E-\{POS, NEG, NEU\}$, $S-\{POS, NEG, NEU\}$ or O , denoting the beginning, inside or end of an aspect, single-word aspect, with positive, negative or neutral sentiment respectively, and finally the outside of that aspect. In this work, BERT (Devlin et al., 2019) was used to embed the tokens and other layers like, GRU, Transformer (Vaswani et al., 2017) or CRF was used on the BERT output.

Li et al. (2019c) ignored the opinion term extraction and that was addressed by Peng et al. (2020a) who proposed a two-stage pipeline framework. In the first stage, aspect-sentiment pairs were extracted using the above mentioned unified tagging scheme. In addition, opinion spans were extracted using BIEOS tagging scheme. The aspect-sentiment and opinion pairs thus extracted were matched against each other in the second stage where an MLP-based classifier was used to find the compatibility of these pairs. Zhang et al. (2020) proposed a multi-task framework to jointly detect aspects, opinions, and sentiment dependencies. However, instead of using the unified tagging scheme they used two sets of BIOS tags to identify the aspects and sentiments before connecting them with the corresponding sentiment. While all these approaches extract aspects and opinion pairs in isolation a recent approach based on pointer network is proposed by Mukherjee et al. (2021) where an encoder-decoder architecture is used to generate all the aspect-opinion-sentiment tuples.

Dataset	Train		Dev		Test		Total
	#s	#p	#s	#p	#s	#p	#s
LAPTOP'14	920	1265	228	337	339	490	1487
REST'14	1300	2145	323	524	496	862	2119
REST'15	593	923	148	238	318	455	1059
REST'16	842	1289	210	316	320	465	1372

Table 2: Statistics of the dataset ASTE-V1 as given in Peng et al. (2020b) (#s and #p denote the number of sentences and aspect-opinion pairs, respectively).

Model		Laptop			Restaurant		
		P	R	F1	P	R	F1
Existing Models	Li et al. (2019a)	61.27	54.89	57.90	68.64	71.01	69.80
	Luo et al. (2019)	-	-	60.35	-	-	72.78
	He et al. (2019)	-	-	58.37	-	-	-
LSTM-CRF	Lample et al. (2016)	58.61	50.47	54.24	66.10	66.30	66.20
	Ma and Hovy (2016)	58.66	51.26	54.71	61.56	67.26	64.29
	Liu et al. (2018)	53.31	59.40	56.19	68.46	64.43	66.38
BERT Models Li et al. (2019c)	BERT+Linear	62.16	58.90	60.43	71.42	75.25	73.22
	BERT+GRU	61.88	60.47	61.12	70.61	76.20	73.24
	BERT+SAN	62.42	58.71	60.49	72.92	76.72	<u>74.72</u>
	BERT+TFM	63.23	58.64	60.80	72.39	76.64	74.41
	BERT+CRF	62.22	59.49	60.78	71.88	76.48	74.06
Our Model	RGAT-BERT	62.17	60.08	61.11	69.70	73.29	71.45
	RGAT-BERT-CRF	64.72	59.09	61.78	73.15	69.82	71.45
	RGAT-BERT-BiLSTM-CRF	65.34	61.46	63.34	75.19	71.89	73.48
	RGAT-BERT-TRFMR-CRF	65.03	60.28	<u>62.56</u>	80.16	74.01	76.96

Table 3: Comparison of predictions on the aspect extraction dataset of Li et al. (2019c). The best F1-scores are shown in bold and the second best ones are underlined.

3 Methodology

We have modified the R-GAT approach of Wang et al. (2020) which was originally targeted for polarity prediction. The approach utilizes the dependency structure of the input sentence which captures the grammatical structure by connecting the words with the corresponding dependency type. The limitations of common approaches that do not pay attention to the parts-of-speech and the dependency structure are discussed by Wang et al. (2020) and the importance of the syntactic relations are emphasized, especially in the context of the aspect word.

3.1 Aspect Oriented Dependency Tree

To bring out the relations of different words with the aspect word(s) an Aspect Oriented Dependency Tree (AODT) was proposed where the root of the original dependency tree was shifted to the target aspect word followed by pruning some of the unnecessary relations. It is to be noted that this approach assumes that there is no more than one aspect word (with the possibility of multiple sub-words) in the sentence. As a result, this approach cannot be applied directly for sentences with multiple aspect words and sentences with no identified aspect word (say, for opinion term extraction).

3.2 Relational Graph Attention Network

AODT can be represented by a graph structure where each node is a word and the edges between them are represented by the dependency relation, e.g., nominal subject, adverbial modifier, etc. Given a neighborhood of a node $\mathcal{N}_i$, the node embeddings can be iteratively updated using multi-head attention as

$$h_{att_i}^{l+1} = \text{concat}_{k=1}^K \sum_{j \in \mathcal{N}_i} \alpha_{ij}^{lk} W_k^l h_j^l, \quad (1)$$

$$\alpha_{ij}^{lk} = \text{attention}(i, j), \quad (2)$$

where $h_{att_i}^{l+1}$ is the attention head of node- i at layer $l + 1$ and α_{ij}^{lk} is the normalized attention coefficient computed by the k -th attention at layer l and W_k^l is an input transformation matrix.

In addition to the attention head of word- i a relational head is also computed for this node as

$$h_{rel_i}^{l+1} = \text{concat}_{m=1}^M \sum_{j \in \mathcal{N}_i} \beta_{ij}^{lm} W_m^l h_j^l, \quad (3)$$

$$g_{ij}^{lm} = \sigma(\text{relu}(r_{ij} W_{m1} + b_{m1}) W_{m2} + b_{m2}) \quad (4)$$

$$\beta_{ij}^{lm} = \exp(g_{ij}^{lm}) / \sum_{j \in \mathcal{N}_i} \exp(g_{ij}^{lm}) \quad (5)$$

where r_{ij} denotes the relation embedding between node- i and j . The final representation of each word (node) is a concatenation of the attention and relational embeddings:

$$x_i^{l+1} = \text{concat}(h_{att_i}^{l+1}, h_{rel_i}^{l+1}) \quad (6)$$

$$h_i^{l+1} = \text{relu}(W_{l+1} x_i^{l+1} + b_{l+1}) \quad (7)$$

3.3 Named Entity Recognition

While the R-GAT model utilizes only the root representation to predict the sentiment polarity, here, we use the node representation h_i^{l+1} for node- i to predict the corresponding NER tag.

3.3.1 Linear Layer

In this case, h_i^{l+1} is directly fed into a fully connected layer with softmax activation function that generates probabilities over all the NER classes, $\mathbf{C}$

$$p(y_i = \mathbf{C}) = \text{softmax}(W_p h_i^{l+1} + b_p). \quad (8)$$

where y_i is NER target label for the word- i and W_p, b_p are learnable parameters.

3.3.2 RNN Layer

While Li et al. (2019c) applied GRU we have used a (Bi-directional Long Short Term Memory) BiLSTM layer on h_i^{l+1} to capture the contributions of the neighbors of each token. An LSTM layer updates the input h^{l+1} as

$$\begin{aligned} i_t &= \sigma(W_i[x_t; h_{t-1}] + b_i), \\ f_t &= \sigma(W_f[x_t; h_{t-1}] + b_f), \\ o_t &= \sigma(W_o[x_t; h_{t-1}] + b_o), \\ \tilde{c}_t &= \tanh(W_c[x_t; h_{t-1}] + b_c), \\ c_t &= f_t \odot c_{t-1} + i_t \odot \tilde{c}_t, \\ h_t &= o_t \odot \tanh(c_t), \end{aligned}$$

where $\odot$ denotes the Hadamard product, $W_i, W_f, W_o, W_c, b_i, b_f, b_o$ and b_c are learnable parameters. The input to the LSTM layer $x_t = h_t^{l+1}$ and the output is h_t^{l+2} . A Bi-LSTM layer processes both the original sequence ($\vec{x}$) and the sequence in reverse order ($\overleftarrow{x}$) together so that contexts from both left and right are captured for each token. The final representation of each token is obtained by concatenating the outputs, i.e., $h^{l+2} = [\vec{h}; \overleftarrow{h}]$ where $\vec{h} = \text{LSTM}(\vec{h}^{l+1})$ and $\overleftarrow{h} = \text{LSTM}(\overleftarrow{h}^{l+1})$.

3.3.3 Transformer Layer

While an LSTM layer processes the sequence uni-directionally and the effects of neighboring tokens are accumulated one at a time, a Transformer (Vaswani et al., 2017) computes attention between all tokens irrespective of the direction. We apply a Transformer layer that takes h^{l+1} as input and generates another sequence of token representations, h^{l+2} , which is of the same length.

3.3.4 CRF Layer

For all the three previous cases, we have a final layer that generates a score matrix $\mathbf{P}$ over all the tag classes, where P_{ij} is the score of the j -th tag for the i -th input token. The CRF layer learns a transition probability matrix $A \in \mathbb{R}^{K+2 \times K+2}$ where K is the number of tag classes (and +2 indicates one tag each for the start and the end marker). For

Model	Restaurant'14			Laptop'14		
	P	R	F1	P	R	F1
RINANTE	48.97	47.36	48.15	41.20	33.20	36.70
CMLA	67.80	73.69	70.62	54.70	59.20	56.90
Li-unified	74.43	69.26	71.75	68.01	56.72	61.86
Li-unified-R	73.15	74.44	73.79	66.28	60.71	63.38
(Li et al., 2019c)–BLSTM	70.00	74.20	72.04	65.99	54.62	59.77
(Li et al., 2019c)–TG	74.41	73.97	74.19	64.35	60.29	62.26
(Li et al., 2019c)–T	69.42	72.2	70.79	64.14	60.63	62.34
(Li et al., 2019c)	76.60	67.84	71.95	63.15	61.55	62.34
RGAT-BERT	71.70	78.80	75.08	60.69	62.74	61.69
RGAT-BERT-CRF	82.69	78.21	<u>80.39</u>	70.38	62.53	66.22
RGAT-BERT-BiLSTM-CRF	81.20	79.39	80.28	70.43	68.21	69.30
RGAT-BERT-TRFMR-CRF	86.04	78.44	82.07	68.94	68.21	<u>68.57</u>

Table 4: Comparison of predictions on the aspect extraction dataset of Peng et al. (2020b). The best F1-scores are shown in bold and the second best ones are underlined.

Model	Restaurant'15			Restaurant'16		
	P	R	F1	P	R	F1
RINANTE	46.20	37.40	41.30	49.40	36.70	42.10
CMLA	49.90	58.00	53.60	58.90	63.60	61.20
Li-unified	61.39	67.99	64.52	66.88	71.40	69.06
Li-unified-R	64.95	64.95	64.95	66.33	74.55	70.20
(Li et al., 2019c)–BLSTM	63.41	65.19	64.29	69.74	71.62	70.67
(Li et al., 2019c)–TG	59.28	61.92	60.57	64.57	66.89	65.71
(Li et al., 2019c)–T	62.28	66.35	64.25	62.65	71.4	66.74
(Li et al., 2019c)	67.65	64.02	65.79	71.18	72.30	71.73
RGAT-BERT	62.37	71.59	66.67	66.35	78.15	71.77
RGAT-BERT-CRF	73.10	70.19	71.62	84.63	80.63	<u>82.58</u>
RGAT-BERT-BiLSTM-CRF	76.03	73.71	74.85	84.61	81.76	83.16
RGAT-BERT-TRFMR-CRF	75.13	68.78	<u>71.81</u>	84.36	80.18	82.22

Table 5: Comparison of predictions on the aspect extraction dataset of Peng et al. (2020b). The best F1-scores are shown in bold and the second best ones are underlined.

an input sequence $\mathbf{x}$ of length T and the corresponding tags $\mathbf{y} = \{y_1, y_2, \dots, y_T\}$ (with the start and end tag denoted by y_0 and y_{T+1}), the probability score is modified as

$$S(\mathbf{x}, \mathbf{y}) = \sum_{i=0}^T A_{y_i y_{i+1}} + \sum_{i=1}^T P_{i, y_i} \quad (9)$$

which is used to calculate the probability of the tag sequence as

$$p(\mathbf{y}|\mathbf{x}) = e^{S(\mathbf{x}, \mathbf{y})} / \sum_{\mathbf{y}' \in \mathbf{Y}} e^{S(\mathbf{x}, \mathbf{y}')} \quad (10)$$

which replaces Eq. 8. The loss for each word is calculated by the categorical cross-entropy loss

$$\mathcal{L}(\theta) = - \sum_{S \in \mathcal{D}} \sum_{w_i \in S} \log(p_{ij}) \quad (11)$$

where p_{ij} is the probability of the word- i with label- j where the word- i appeared in sentence- S and $\mathcal{D}$ represents the entire corpus. For CRF based models, the loss is calculated using the forward-backward algorithm.

4 Experiments

4.1 Datasets

We used two datasets in our experiments. The first one is created by Li et al. (2019c), which is originating from SemEval'14 (Pontiki et al., 2014) but modified by Li et al. (2019b). The statistics of the dataset are summarized in

Model	Restaurant'14			Laptop'14		
	P	R	F1	P	R	F1
Distance rule	58.39	43.59	49.92	50.13	33.86	40.42
Dependency rule	64.57	52.72	58.04	45.09	31.57	37.14
RINANTE	81.06	72.05	76.29	78.20	62.70	69.60
CMLA	69.47	74.53	71.91	51.80	65.30	57.70
IOG	82.85	77.38	80.02	73.24	69.63	71.35
Li-unified-R	81.20	83.18	82.13	76.62	74.90	75.70
(Li et al., 2019c)-BLSTM	80.41	86.19	83.15	78.06	68.98	73.19
(Li et al., 2019c)-TG	81.77	84.80	83.21	76.87	75.31	76.03
(Li et al., 2019c)-T	80.61	85.38	82.88	76.69	73.88	75.21
(Li et al., 2019c)	84.72	80.39	82.45	78.22	71.84	74.84
RGAT-BERT	82.05	86.43	84.18	74.71	80.20	77.36
RGAT-BERT-CRF	95.43	89.56	<u>92.40</u>	93.97	79.59	86.19
RGAT-BERT-BiLSTM-CRF	95.64	91.53	93.54	93.42	84.08	88.51
RGAT-BERT-TRFMR-CRF	94.58	89.09	91.76	93.55	82.86	<u>87.88</u>

Table 6: Comparison of predictions on the opinion extraction dataset of (Peng et al., 2020b) based on the SemEval'14 (Pontiki et al., 2014) task.

Table 1 where the number of sentences (queries) and aspects are shown in two domains, namely, Laptop and Restaurant, across train, validation and test set. The second dataset is called Aspect Sentiment Triplet Extraction (ASTE) dataset (version-1) as created by Peng et al. (2020a) where each sentence has a unified aspect/target tags and opinion tags. The details of the dataset are shown in Table 2.

4.2 Implementation Details

We use the bi-affine parser (Dozat and Manning, 2016) from AllenNLP for dependency parsing. While Wang et al. (2020) used the aspect words to orient the dependency tree, in our case, we cannot use that information. Instead, we randomly choose a noun word (adjective for opinion tagging) from the input sentence, if available, otherwise, we select the middle token about which the dependency tree is re-oriented. For all experiments, the embedding dimension for the dependency relation is set to 200 and the dropout is fixed at 0.3. The last hidden state of the pre-trained BERT¹ is used for the initial token representations which is subsequently fine-tuned. All models are trained using Adam optimizer (Kingma and Ba, 2014) with the default parameters. For all experiments we have used RGAT based feature extraction and BERT based token encoding. There are four variants of our model, namely, (1) RGAT-BERT, that does not use any other layer, (2) RGAT-BERT-CRF, that additionally uses a CRF final layer, (3) RGAT-BERT-BiLSTM-CRF, that uses a Bi-LSTM layer on the output of BERT before passing the output to a CRF layer and (4) RGAT-BERT-TRFMR-CRF that uses a Transformer layer instead of a Bi-LSTM.

4.3 Results and Discussions

For all experiments we report only the F1-score (and omit precision and recall due to space limitation) across all the tags. Table 3 shows the performance of different RGAT models on the dataset of Li et al. (2019c). As can be seen, RGAT models provide the best F1 score for the Laptop (BiLSTM) and Restaurant (Transformer) domain surpassing the previous best F1 scores by more than 3% point. For the laptop domain, the second best result is also given by another RGAT model (Transformer based), whereas, for the Restaurant domain one of the prior models stand out (BERT+self-attention network from Li et al. (2019c)).

For the second dataset, we extract aspects and opinions from four domains, Laptop, Restaurant-2014, Restaurant-2015 and Restaurant-2016. Table 4 and 5 together show the results of aspect extraction for all the four domains. For aspect extraction, it can be seen that the best F1-score is obtained by the Transformer and BiLSTM models for the Restaurant-2014 and Laptop domain, respectively. The second best results are also obtained by our models, by CRF and Transformer based models. We can see substantial improvement (6-8% point) over the previously reported F1 scores for both the cases. Even larger improvement can be seen for the other two Restaurant domain data (2015 and 2016) where the BiLSTM-CRF model generates the best F1 score.

Table 6 shows the performance on the opinion extraction task where the best F1 scores are provided by the BiLSTM-CRF model for both the Restaurant-2014 and Laptop domain. Here we see 10-12 % point improvement over the

¹<https://github.com/huggingface/transformers>

Model	Restaurant'15			Restaurant'16		
	P	R	F1	P	R	F1
Distance rule	54.12	39.96	45.97	61.90	44.57	51.83
Dependency rule	65.49	48.88	55.98	76.03	56.19	64.62
RINANTE	77.40	57.00	65.70	75.00	42.40	54.10
CMLA	60.80	65.30	62.90	74.50	69.00	71.70
IOG	76.06	70.71	73.25	85.25	78.51	81.69
Li-unified-R	79.18	75.88	77.44	79.84	86.88	83.16
(Li et al., 2019c)–BLSTM	74.29	80.48	77.21	82.12	84.95	83.46
(Li et al., 2019c)–TG	75.98	76.32	76.10	82.33	85.16	83.67
(Li et al., 2019c)–T	78.13	75.22	76.60	77.14	87.10	81.77
(Li et al., 2019c)	78.07	78.07	78.02	81.09	86.67	83.73
RGAT-BERT	75.20	81.98	78.44	77.98	89.89	83.52
RGAT-BERT-CRF	92.27	83.96	<u>87.92</u>	96.07	84.09	<u>89.68</u>
RGAT-BERT-BiLSTM-CRF	94.52	90.99	92.72	95.82	93.76	94.78
RGAT-BERT-TRFMR-CRF	93.62	80.66	86.66	94.37	83.01	88.33

Table 7: Comparison of predictions on the opinion extraction dataset of (Peng et al., 2020b) for the Restaurant domain based on Pontiki et al., 2015 and Pontiki et al., 2016.

best previous F1 score. Following the same trend of aspect extraction, for Restaurant-2015 and 2016 data (shown in Table 7), we see the best performance coming from the BiLSTM-CRF model exceeding the previous best scores by more than 10% point. Overall, we can see that all the RGAT-BERT based models perform much better than all the other baseline models on all the tasks.

5 Conclusion

In this work we have applied Relational Graph Attention network which was previously used for classifying sentiment polarity associated with a specific aspect. However, here we show that the dependency structure of the input query when encoded by a Graph attention network is powerful enough to improve the performance and it is not necessary to tie to a particular aspect. We have used a surrogate aspect/opinion term by selecting a noun/adjective token if available. The strength of the approach is evident in the superior results that we have obtained for both aspect and opinion term extraction on four commonly used datasets. In addition, we have compared BiLSTM and Transformer as additional layers along with a CRF layer and found that BiLSTM layer consistently performs better than a Transformer layer.

Limitations

There are several limitations of the present methodology as shown below:

1. The success of the current approach heavily hinges on knowing the dependency structure of the queries. Thus, we cannot extend this approach easily to other languages other than English.
2. While we have extracted all the aspects and opinions from a given query we have not matched them in this work. A more complete solution is proposed by Mukherjee et al. (2021) using pointer network based decoder, which can be the next step of this work.

References

- Peng Chen, Zhongqian Sun, Lidong Bing, and Wei Yang. 2017. Recurrent attention network on memory for aspect sentiment analysis. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 452–461, Copenhagen, Denmark. Association for Computational Linguistics.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Timothy Dozat and Christopher D Manning. 2016. Deep biaffine attention for neural dependency parsing.

- Ruidan He, Wee Sun Lee, Hwee Tou Ng, and Daniel Dahlmeier. 2018. Effective attention modeling for aspect-level sentiment classification. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 1121–1131, Santa Fe, New Mexico, USA. Association for Computational Linguistics.
- Ruidan He, Wee Sun Lee, Hwee Tou Ng, and Daniel Dahlmeier. 2019. An interactive multi-task learning network for end-to-end aspect-based sentiment analysis. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 504–515, Florence, Italy. Association for Computational Linguistics.
- Mickel Hoang, Oskar Alija Bihorac, and Jacobo Rouses. 2019. Aspect-based sentiment analysis using BERT. In *Proceedings of the 22nd Nordic Conference on Computational Linguistics*, pages 187–196, Turku, Finland. Linköping University Electronic Press.
- Binxuan Huang and Kathleen Carley. 2019. Syntax-aware aspect level sentiment classification with graph attention networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5469–5477, Hong Kong, China. Association for Computational Linguistics.
- Diederik P. Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization.
- Guillaume Lample, Miguel Ballesteros, Sandeep Subramanian, Kazuya Kawakami, and Chris Dyer. 2016. Neural architectures for named entity recognition. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 260–270, San Diego, California. Association for Computational Linguistics.
- Xin Li, Lidong Bing, Piji Li, and Wai Lam. 2019a. A unified model for opinion target extraction and target sentiment prediction. In *AAAI*, pages 6714—6721.
- Xin Li, Lidong Bing, Piji Li, and Wai Lam. 2019b. A unified model for opinion target extraction and target sentiment prediction. In *AAAI*, pages 6714–6721.
- Xin Li, Lidong Bing, Wenxuan Zhang, and Wai Lam. 2019c. Exploiting BERT for end-to-end aspect-based sentiment analysis. In *Proceedings of the 5th Workshop on Noisy User-generated Text (W-NUT 2019)*, pages 34–41, Hong Kong, China. Association for Computational Linguistics.
- Peiqin Lin, Meng Yang, and Jianhuang Lai. 2019. Deep mask memory network with semantic dependency and context moment for aspect term extraction. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 5088–5094. International Joint Conferences on Artificial Intelligence Organization.
- Liyuan Liu, Jingbo Shang, Xiang Ren, Frank F Xu, Huan Gui, Jian Peng, and Jiawei Han. 2018. Empower sequence labeling with task-aware neural language model. In *AAAI*, pages 5253—5260.
- Huaishao Luo, Tianrui Li, Bing Liu, and Junbo Zhang. 2019. DOER: Dual cross-shared RNN for aspect term-polarity co-extraction. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 591–601, Florence, Italy. Association for Computational Linguistics.
- Dehong Ma, Sujian Li, Xiaodong Zhang, and Houfeng Wang. 2017. Interactive attention networks for aspect-level sentiment classification. In *Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence, IJCAI-17*, pages 4068–4074.
- Xuezhe Ma and Eduard Hovy. 2016. End-to-end sequence labeling via bi-directional LSTM-CNNs-CRF. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1064–1074, Berlin, Germany. Association for Computational Linguistics.
- Rajdeep Mukherjee, Tapas Nayak, Yash Butala, Sourangshu Bhattacharya, and Pawan Goyal. 2021. PASTE: A tagging-free decoding framework using pointer networks for aspect sentiment triplet extraction. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 9279–9291, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Haiyun Peng, Lu Xu, Lidong Bing, Fei Huang, Wei Lu, and Luo Si. 2020a. Knowing what, how and why: A near complete solution for aspect-based sentiment analysis. *Proceedings of the AAAI Conference on Artificial Intelligence*, 34(05):8600–8607.
- Haiyun Peng, Lu Xu, Lidong Bing, Fei Huang, Wei Lu, and Luo Si. 2020b. Knowing what, how and why: A near complete solution for aspect-based sentiment analysis. In *AAAI*, volume 34 (5).
- Maria Pontiki, Dimitris Galanis, Haris Papageorgiou, Ion Androutsopoulos, Suresh Manandhar, Mohammad AL-Smadi, Mahmoud Al-Ayyoub, Yanyan Zhao, Bing Qin, Orphée De Clercq, Véronique Hoste, Marianna Apidianaki, Xavier Tannier, Natalia Loukachevitch, Evgeniy Kotelnikov, Nuria Bel, Salud María Jiménez-Zafra, and Gülşen

- Eryiğit. 2016. SemEval-2016 task 5: Aspect based sentiment analysis. In *Proceedings of the 10th International Workshop on Semantic Evaluation (SemEval-2016)*, pages 19–30, San Diego, California. Association for Computational Linguistics.
- Maria Pontiki, Dimitris Galanis, Haris Papageorgiou, Suresh Manandhar, and Ion Androutsopoulos. 2015. SemEval-2015 task 12: Aspect based sentiment analysis. In *Proceedings of the 9th International Workshop on Semantic Evaluation (SemEval 2015)*, pages 486–495, Denver, Colorado. Association for Computational Linguistics.
- Maria Pontiki, Dimitris Galanis, John Pavlopoulos, Harris Papageorgiou, Ion Androutsopoulos, and Suresh Manandhar. 2014. SemEval-2014 task 4: Aspect based sentiment analysis. In *Proceedings of the 8th International Workshop on Semantic Evaluation (SemEval 2014)*, pages 27–35, Dublin, Ireland. Association for Computational Linguistics.
- Kai Sun, Richong Zhang, Samuel Mensah, Yongyi Mao, and Xudong Liu. 2019. Aspect-level sentiment analysis via convolution over dependency tree. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5679–5688, Hong Kong, China. Association for Computational Linguistics.
- Duyu Tang, Bing Qin, and Ting Liu. 2016. Aspect level sentiment classification with deep memory network. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 214–224, Austin, Texas. Association for Computational Linguistics.
- Yi Tay, Luu Anh Tuan, and Siu Cheung Hui. 2017. Dyadic memory networks for aspect-based sentiment analysis. In *Proceedings of the 2017 ACM on Conference on Information and Knowledge Management, CIKM '17*, page 107–116, New York, NY, USA. Association for Computing Machinery.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need.
- Jingjing Wang, Jie Li, Shoushan Li, Yangyang Kang, Min Zhang, Luo Si, and Guodong Zhou. 2018. Aspect sentiment classification with both word-level and clause-level attention networks. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence, IJCAI-18*, pages 4439–4445. International Joint Conferences on Artificial Intelligence Organization.
- Kai Wang, Weizhou Shen, Yunyi Yang, Xiaojun Quan, and Rui Wang. 2020. Relational graph attention network for aspect-based sentiment analysis. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 3229–3238, Online. Association for Computational Linguistics.
- Yequan Wang, Minlie Huang, Xiaoyan Zhu, and Li Zhao. 2016. Attention-based LSTM for aspect-level sentiment classification. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 606–615, Austin, Texas. Association for Computational Linguistics.
- Hu Xu, Bing Liu, Lei Shu, and Philip S. Yu. 2019. Bert post-training for review reading comprehension and aspect-based sentiment analysis.
- Biqing Zeng, Heng Yang, Ruyang Xu, Wu Zhou, and Xuli Han. 2019. Lcf: A local context focus mechanism for aspect-based sentiment classification. *Applied Sciences*, 9(16).
- Chen Zhang, Qiuchi Li, and Dawei Song. 2019. Aspect-based sentiment classification with aspect-specific graph convolutional networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 4568–4578, Hong Kong, China. Association for Computational Linguistics.
- Chen Zhang, Qiuchi Li, Dawei Song, and Benyou Wang. 2020. A multi-task learning framework for opinion triplet extraction. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 819–828, Online. Association for Computational Linguistics.