The Status of the H E S S Project

J.A.Hinton^a for the H E S S collaboration^b

^aM ax-P lanck-Institut fur K emphysik, PO Box 103980, D-69029 H eidelberg, G erm any

^bhttp://www.mpi-hd.mpg.de/HESS/collaboration

A bstract

The High Energy Stereoscopic System (H E S S) -is a system of four, 107 mmirror area, in aging Cherenkov telescopes under construction in the K hom as Highland of N am ibia (1800 m asl). The H E S S system is characterised by a low threshold (100 GeV) and a 1% C rab ux sensitivity resulting from the good angular resolution and background rejection provided by the stereoscopic technique.

The rst two telescopes are operational and rst results are reported here. The remaining two telescopes (of H E S S Phase-I) will be commissioned early in 2004.

1 System Design

H E S S is an array of 4 identical telescopes arranged in a square with 120 m sides. Each telescope has a focal length of 15 m and a 13 m diameter. The rejectors comprise 380 quartz-coated round facets (60 cm diameter), arranged with D avies-C otton optics.

The H E S S cameras consist of 960 pixels of 0 and gular size providing a total eld of view of 5 . A pixel consists of a photom ultiplier tube (PM T) with a W inston cone light collector. The PM T s (Photon is X P 2960) are organised into drawers of 16 PM T s with associated read-out electronics. All triggering and read-out electronics are contained inside the camera body.

M onte-Carlo simulations predict a sensitivity for the 4 telescope system of around 1% of the Crab ux (5, 50 hours) and an energy threshold of 100 GeV (see Fig.1).



Fig. 1. Expected point-source sensitivity of $H \in S \setminus S$ Phase I compared to that of the VER ITAS array (1) (reproduced from (2)).

2 Construction Status

The rst telescope of H E S S (referred to as CT3 for historical reasons) was completed in June 2002 and immediately began Cherenkov observations. The second telescope completed (CT2) began operations in M arch 2003. Some improvements were made to the second camera (and upgrades to the rst), primarily a reduction in digitisation and readout time (from 1.6 m s to 0.6 m s) (Fig. 2).

A sofA pril2003, the steelwork and drive system s are complete on the two remaining telescopes. The camera shelters, lightening masts, residence and control buildings are all complete. The remaining work is the installation of mirrors on CT1 and CT4 and the installation and commissioning of the cameras on these telescopes. The central trigger system for the array will be installed in June 2003. A llm irror facets and PMTs for the 4 telescope system are in hand and the two remaining cameras are mechanically complete and undergoing electronics installation and testing in Paris. C om pletion of the construction of Phase-I is expected in early 2004.

3 Telescope Perform ance

The optical support structure and positioning system of the H E S S telescopes have been designed for a high level of mechanical rigidity { we therefore expect to achieve good telescope tracking precision which can be followed by small o -line corrections based, for example, on CCD measurements. The telescope drive system s are equipped with encoders for control and monitoring. The RMS deviation from



Fig. 2. The rst two H E S S telescopes (operational M arch 2003).



Fig. 3. View of the second H E S S camera. Left Figure: the camera readout electronics seen from the rear. Central Figure: the front of the camera with lid open showing the PM Ts and W inston cones. Right Figure: with the telescope tracking.

nom inal encoder values (over a period of 9 m onths) was of the order 1 arcsecond. The slewing/positioning speed of the telescopes is 100 /m inute.

To allow rem ote alignment, each m irror is equipped with two alignment motors. The alignment procedure uses the image of a star on the closed lid of the PMT camera, viewed by a CCD camera at the centre of the dish. The optical point spread function of the telescope is measured in the same way. These procedures are described in detail in (3).

The absolute telescope pointing accuracy has been measured using images of stars on the camera lid. Uncorrected star images deviated from nominal position with an RMS error of 28". Using a 12-parameter model to correct for misalignments of the telescopes axes etc., a pointing precision of 8" is reached. Finally, using a guide telescope attached to the dish for online corrections, the pointing error can



Fig. 4. Left: The on-axis point-spread function of CT3 compared with the pixel size (hexagon). Right: the behaviour of the PSF o -axis for telescopes CT2 & CT3 (solid lines show M onte-C arb predictions).

be reduced to to 2.5" RM S.H E S S should therefore be able to locate bright -ray sources to a few arc-seconds.

Figure 4 shows the optical point spread function (PSF) for the H E S S telescopes. The 80% light contains ent radius is smaller than half the pixel diameter up to 2 o -axis. Measurements of the PSF over several months show no evidence for degradation since the installation of the camera on CT3, without need for mirror alignment. The design and performance of the optical system of H E S S is described in detail in (4) and (3).

4 Optical C rab Pulsar

A prerequisite of deep -ray observations of pulsed -ray emission from pulsars is to verify the absolute timing system and phase reconstruction algorithm used. The observation of optical pulsations from the C rab has been used by several groups to provide this veri cation (see for example (5; 6)).

O ptical pulsar observations have been m ade using a custom -built detector installed on the closed lid of the rst C herenkov cam era (CT3). This instrum ent comprises a single PMT with current sampling every 50 s and analog response time of 150 s. Each sample is accompanied by a timestamp derived from the the GPS clock of the H E S S central trigger system.

The large m irror area and narrow PSF of the H E S S telescopes allows a very high signal/noise m easurem ent of the pulsar light curve to be m ade. Fig. 5 shows the light curve derived from 3 hours of observations spread over one week in January 2003. Fig. 5b shows the m ean optical ux versus phase (relative to the peak of the prim ary radio pulse).



Fig. 5. Left: the C rab pulsar phasogram extracted from the full data-set of 3 hours of best quality observations. Right: The position of the m ain peak as a function of time during the measurement. The mean position is consistent with previous measurements (7).

5 Camera Performance

Since June 2002 the rst cam era of the H E S S system has been taking Cherenkov data { operating at typical trigger rates of 150 Hz (at 30 zenith, 4 pixels > 5 photoelectrons). The trigger rate of the telescope is seen to vary smoothly with threshold. At thresholds as low as 4 pixels > 4 photoelectrons there is no signi cant contribution of night sky background triggers to the rate. The observed night sky background level (from PMT currents and pedestal widths) is close to 100 M H z in dark regions, as expected.

M easurements of the PMT gain and at-eld coe cients (derived from laser and LED calibration systems) show variations on the 10% level over the nine months of operation. A fler at-elding the performance of the camera is measured using muon-ring images which provide the best measurement of the detector response to Cherenkov light.



Fig. 6. Left: a cleaned M uon-ring im age with the circular t shown. Right: the corresponding azim uthal distribution of intensity around the ring. The peak intensity is proportional to the detector e ciency.

Single muon in ages provide a powerful tool for absolute calibration of C herenkov Telescopes. The expected in ages are readily calculable and easily recognisable in the data (as ring-like in ages). The overall brightness of the rings (or the norm alisation of the intensity pro le azim uthally around the ring) provides a measurement of the through-put of the system, including attenuation in the lower 500 m of the atm osphere, mirror re ectivity, W inston cone collection e ciency, and PM T quantum e ciency.

Figure 6 shows a sample muon-ring in age and the azim uth distribution of intensity around the ring. The overall system e ciency can be deduced from a single ring with 10% precision; such rings occur in our data at 1 Hz. A veraging over muon rings in many runs the through-put of the rst telescope seems to be 10% less than predicted by the simulations - within the system atic errors in the calculation.

Run-to-run uctuations in the through-put deduced from muon images are at the few percent level.

6 Gamma-RayObservations

Between July 2002 and M arch 2003 m any target objects have been observed using the rst H E S S telescope. The list of targets is primarily composed of objects claim ed as sources by the Durham (8) and CANGAROO (9) groups.



Fig. 7. Left: The pointing angle -plot for single telescope C rab observations in O ctober 2002. Corresponding o -source data (norm alised by exposure time) are shown as a histogram. Right: Reconstructed sky-plot of -ray excess in the region around the C rab.

The C rab nebula is a standard candle in the VHE —ray eld and was observed during autum n 2003 to test predictions of the perform ance of a single H E S S telescope. O bservations were taken over a zenith angle range of 45 to 50 during O ctober and N ovem ber 2003. A total live-tim e of 4.7 hours on-source, and an equal am ount of o -source, data were acquired. A fler applying optim ised cuts (box cuts or supercuts) on reconstructed H illas P aram eters, a steady rate of 3.6 's/m inute is observed with a signi cance of 20:1 . Figure 7 shows a pointing angle -plot for these data. Because of the large zenith angle of these observations the post-cut energy threshold is 800 GeV. From M onte Carlo simulations (CORSIKA plus telescope simulation) we calculate a preliminary integral ux of (2:64 0:20) 10⁷ m² s¹ (> 1 TeV).

Am ongst the targeted extra-galactic objects was the BL-Lac object PKS 2155-304. Our observations in July and O ctober 2002 con m the identi cation of this object as a VHE -ray source by the Durham group (10). Observations in July with 2.2 hours of live-time on-source show an excess of 3.1 's/m inute with a signicance of 9.9 (see Fig. 8). The measured ux in O ctober was signicantly lower (1.2 's/m inute, 6.6).



Fig.8.The pointing angle -plot for PKS 2155-304 data from July (left) and O ctober (right) 2002. A signi cant excess is seen in both periods.

7 First Stereo Observations

In M arch 2003 the rst simultaneous observations with two H E S S telescopes were m ade. In the initial m ode of operation the stereoscopic events are m atched in software using GPS times. Figure 9 shows the distribution of the image length/size for single telescope and coincident events from these data. The prom inent peak in the rst plot is due to single m uon images which are clearly absent in the stereoscopic data, as expected.



Fig.9.D istributions of im age Length/Size for single telescope and coincident events. The peak due to single muon im ages is entirely absent in the stereoscopic data.

The installation of a hardware central triggering system (expected in June 2003) will allow us to substantially reduce the cam era trigger thresholds whilst maintaining acceptable levels of dead-time (< 20%).

8 Conclusions

Two of the four telescopes of H E S S P hase-I are complete and operational. The optical and mechanical perform ance of these telescopes meets all speci cations. -ray observations of the C rab con m the simulated perform ance of a single H E S S telescope. We con m the BL-Lac PKS 2155-304 as a strong V HE -ray source.

The full H E S S system should begin operations early in 2004.

References

- [1] Weeks, T.C. et al., A stropart. Phys. 17 (2002) 221.
- [2] Hofmann, W., In: Proceedings of the 27th ICRC, Hamburg (2001) OG 2.05.
- [3] Comils, R. et al., APh 20 (2003) 129.
- [4] Bemlohr, K. et al., APh 20 (2003) 111.
- [5] Lessard, R.W. et al, A strophys.J., 531 (2000) 942.
- [6] de Naurois, M et al., A strophys.J., 566 (2002) 343.
- [7] Straubm eier, C. et al., Exp. A stron. 11 (2001) 157.
- [8] A m strong, P. et al., Exp. A stron. 9 (1999) 51.
- [9] Enom oto, R. et al, In: Proceedings of the 28th ICRC, Tsukuba (2003) OG 2.2.
- [10] Chadwick, P.M. et al., A strophys.J., 513 (1999) 161.