

A Technique for Photometric Detection and Measurement of Unresolved Binary Systems

Paul Hickson

Department of Physics and Astronomy, University of British Columbia, 2219 Main Mall,
Vancouver, BC V6T 1Z4, Canada

ABSTRACT

A technique is described for the detection and measurement of close binary systems whose images are unresolved. The method is based on analysis of the moment of inertia tensor of the image, from which the product of the binary flux ratio and square of the angular separation may be determined. Intrinsic asymmetries of the point-spread function are removed by comparison with the image of a reference star. Multiple exposures may be used to increase the signal-to-noise ratio without need of image alignment. An example is given of a simulated measurement of the dwarf carbon star system G77-61.

1. INTRODUCTION

There are a number of astrophysical situations where one needs to measure either the position or the flux of a faint unresolved object which is located close to a bright star. Obvious examples are the search for extra-solar planets and low-luminosity companions to bright stars, and the study of close binary systems. If the flux ratio between the primary and secondary object is very large, coronagraphic techniques may be employed, but this is can only be effective if the separation of the images of the primary and secondary objects is substantially larger than the radius of the point-spread function (PSF). For small separations alternate techniques are needed.

When the separation between the binary components is comparable to, or smaller than, the radius of the PSF, the image of the system will be elongated to some degree. This paper describes a technique which uses the image elongation to obtain information about the photometric and astrometric parameters of the system.

2. THE ALGORITHM

There are a several conditions that are desirable in any technique which aims to measure image elongation. Some important ones are:

1. invariance to the location of the PSF
2. invariance to the orientation of the detector
3. insensitivity to the shape of the PSF
4. optimization of the signal-to-noise ratio
5. ability to co-add images to improve the signal-to-noise ratio

The method described in this paper satisfies, to a large degree, all of these conditions.

2.1. Characterizing Image Elongation

We begin by reviewing some elementary properties of the moments of the light distribution. For a Cartesian coordinate system $\mathbf{x} = (x^1, x^2)$ and intensity distribution $f(\mathbf{x})$, the zeroth, first and second moments are defined by

$$\rho = \int f(\mathbf{x}) d^2x \quad (1)$$

$$\rho^i = \int f(\mathbf{x}) x^i d^2x \quad (2)$$

$$\rho^{ij} = \int f(\mathbf{x}) x^i x^j d^2x \quad (3)$$

where $i = 1, 2$ and the function $f(\mathbf{x})$ is presumed to be vanishingly small at large values of $|\mathbf{x}|$. The integrals extend over a sufficiently large range that contributions from the end points are negligible.

A shift in the position of the image, $f(\mathbf{x}) \rightarrow f(\mathbf{x} - \mathbf{a})$, induces the following changes, which are easily obtained by the substitution $\mathbf{y} = \mathbf{x} - \mathbf{a}$,

$$\rho \rightarrow \rho \quad (4)$$

$$\rho^i \rightarrow \rho^i + a^i \rho \quad (5)$$

$$\rho^{ij} \rightarrow \rho^{ij} + a^i \rho^j + a^j \rho^i + a^i a^j \rho \quad (6)$$

from which it follows that the inertia tensor

$$I^{ij} = [\rho^{ij} - \rho^i \rho^j / \rho] / \rho \quad (7)$$

is invariant under translations of the image.

Under rotations of the coordinate system, $x'^i = \Lambda^i_j x^j$ (a summation over repeated indices is implied), it is evident from the definition that ρ and ρ^i transform as a scalar and vector respectively, and that both ρ^{ij} and I^{ij} transform as second-rank tensors, eg.

$$I'^{ij} = \Lambda^i_k \Lambda^j_l I^{kl} . \quad (8)$$

Where there is no ambiguity, we may omit the indices on vectors, tensors and matrices and use bold face type to distinguish them from scalars quantities.

2.2. Moments of a Binary Image

Let $\hat{f}(\mathbf{x})$ be proportional to the PSF. We chose the proportionality constant and the origin of the $\mathbf{x}$ coordinate system in such a way that the zeroth moment is unity and the first moments vanish, ie

$$\hat{\rho} = 1 \quad (9)$$

$$\hat{\rho}^i = 0 \quad (10)$$

where the symbol ‘ $\hat{}$ ’ indicates that these are normalized moments of the PSF. The second moments are generally nonzero and contain information about the size and shape of the PSF.

Now consider an image of the form

$$f(\mathbf{x}) = \hat{f}(\mathbf{x} + \mathbf{a}/2) + b\hat{f}(\mathbf{x} - \mathbf{a}/2) \quad (11)$$

where $b \leq 1$. This corresponds to a binary system where the secondary has a flux b , relative to the primary, and a vector separation $\mathbf{a}$. Using Eqns. 1-3 and 7, we obtain the inertia tensor of this image

$$I^{ij} = \hat{I}^{ij} + \frac{b}{(1+b)^2} a^i a^j . \quad (12)$$

From this we see that the presence of the secondary component adds a term to the inertia tensor of the PSF which, to first order, is proportional to the relative flux times the square of the separation. By subtracting the components of the inertia tensor of the PSF from that of the binary system, we obtain this term, which we denote by $\mathbf{M}$,

$$M^{ij} \equiv I^{ij} - \hat{I}^{ij} = \frac{b}{(1+b)^2} a^i a^j . \quad (13)$$

From this, if the separation vector $\mathbf{a}$ is known, we obtain the relative flux. In fact, only the magnitude a of the separation vector is needed - by taking the trace of the matrix $\mathbf{M}$ we

obtain

$$Tr(\mathbf{M}) = \frac{ba^2}{(1+b)^2} , \quad (14)$$

from which b may be determined.

Alternatively, if the relative flux is known, the diagonal terms of $\mathbf{M}$ give the components of separation vector. Even if b is not known, the position angle ϕ of the separation vector, with respect to the x^1 axis, can be found from the ratio of diagonal terms,

$$\tan \phi = a^2/a^1 = (M^{22}/M^{11})^{1/2} . \quad (15)$$

2.3. Sampling Effects

In practice we work with a digital image which consists of a discrete set of samples f_α corresponding to pixels located at positions $\mathbf{x}_\alpha$, normally on a square grid at intervals p . The values f_α are proportional to the product of the intensity and the pixel response functions $q_\alpha(\mathbf{x})$ integrated over the pixel areas. If the response function is the same for all pixels we have

$$f_\alpha = \int f(\mathbf{x})q_\alpha(\mathbf{x})d^2x \quad (16)$$

$$= \int f(\mathbf{x})q(\mathbf{x} - \mathbf{x}_\alpha)d^2x . \quad (17)$$

Thus the values f_α actually sample the image formed by smoothing the incident intensity with the pixel response function. This effect can be incorporated by employing the actual PSF of the sampled image, which includes the result of the smoothing.

From the sampling theorem (see, for example, Bracewell 1978) the function $f(\mathbf{x})$ can be uniquely reconstructed from the samples f_α only if it contains no spatial frequencies higher than the Nyquist frequency $1/p$. For a diffraction limited image, at wavelength λ , from a telescope of aperture diameter D , the pixel spacing must be no greater than $\lambda/2D$. The image is then given by

$$f(\mathbf{x}) = \sum_\alpha f_\alpha \text{sinc}(x^1 - x_\alpha^1) \text{sinc}(x^2 - x_\alpha^2) \quad (18)$$

where $\text{sinc}(x) = \sin(\pi x)/\pi x$. Substitution of this equation into Eqns. 1-3 gives the corresponding discrete expressions

$$\rho = \sum_\alpha f_\alpha , \quad (19)$$

$$\rho^i = \sum_{\alpha} f_{\alpha} x_{\alpha}^i, \quad (20)$$

$$\rho^{ij} = \sum_{\alpha} f_{\alpha} x_{\alpha}^i x_{\alpha}^j \quad (21)$$

providing that the integrals converge. Eqns. 7, 13-15 and 19-21 then provide a direct path from the observational data to the parameters b and $\mathbf{a}$ of the binary system.

While this simple technique seems plausible, in practice it does not work due to problems of convergence and noise, discussed next. However a modification of the technique, developed in Section 2.5 avoids these difficulties while at the same time optimizing the signal-to-noise ratio.

2.4. Convergence and Noise

The above algorithm fails because for real astronomical images the integrals in Eqns. 1-3 do not converge. This is a result of the PSF of an optical system being a band-limited function. The amplitude of the light in the PSF is the two-dimensional spatial Fourier transform of the optical transfer function (OTF). There is an upper limit to the spatial frequency at which the OTF can be non-zero, imposed by the finite size of the telescope entrance pupil. The OTF is the product of the instrumental and atmospheric transfer functions with the pupil function, defined as unity for points within the pupil and zero for points outside. From the convolution theorem, the amplitude of the PSF is therefore the convolution of the instrumental and atmospheric response with the Fourier transform of the pupil function. Since the square of the latter function is just the diffraction-limited PSF, it follows that the intensity of light in the PSF cannot fall off faster than the diffraction limit. For a circular aperture this has the form (eg. Born & Wolfe 1980)

$$\hat{f}(\mathbf{x}) = [2J_1(kRr)/kRr]^2 \quad (22)$$

where $r = |\mathbf{x}|$ is measured in radians, $k = 2\pi/\lambda$ is the wave number, λ the wavelength, and $R = D/2$ is the radius of the aperture. For large values of its argument, the Bessel function has the asymptotic expansion

$$J_1(x) \rightarrow \frac{1}{\sqrt{\pi x}}(\sin x - \cos x) \quad (23)$$

so $\hat{f}$ falls off no faster than r^{-3} . Since $d^2x \propto r$, the integral in Eqn. 3 is ill-defined.

Even more serious is the fact that random noise, present in the image, causes a rapid divergence of the moments. To see this, recall that both the photon noise and the read

noise is uncorrelated from pixel to pixel. The presence of such noise adds a fluctuating component to $f(\mathbf{x})$ which in turn produces fluctuations in the moments. The variance of these fluctuations is the sum of the variances of the individual pixel fluctuations, weighted by the *squares* of the coordinate terms present in Eqns. 2 and 3. Since the read noise is independent of position, the variance of all moments increases without limit over the range of integration.

2.5. Weighted Moments

The solution that we propose for these problems is to apply weight factors to the intensity values of the image before computing the moments. In order to preserve the transformation properties of the inertia tensor, the weights cannot depend on the coordinates, but can only be a function of f_α . We make the substitution $f_\alpha \rightarrow w_\alpha f_\alpha$, and ask what choice of w_α minimizes the random error in the moments. From Eqns. 19-21 we then have

$$Var(\rho) = \sum_{\alpha} Var(f_{\alpha}) \quad (24)$$

$$Var(\rho^i) = \sum_{\alpha} (x_{\alpha}^i)^2 Var(f_{\alpha}) \quad (25)$$

$$Var(\rho^{ij}) = \sum_{\alpha} (x_{\alpha}^i x_{\alpha}^j)^2 Var(f_{\alpha}) \quad (26)$$

where $Var(x)$ denotes the variance of the random variable x . We seek to minimize the ratios $Var(\rho)/(\rho)^2$, $Var(\rho^i)/(\rho^i)^2$ and $Var(\rho^{ij})/(\rho^{ij})^2$, and so equate to zero the derivatives of these ratios with respect to w_α . This leads to the result

$$w_\alpha \propto \frac{f_\alpha}{Var(f_\alpha)} . \quad (27)$$

Two possible dependencies for the noise are $Var(f_\alpha) \propto f_\alpha$ and $Var(f_\alpha) = \text{constant}$. The first case corresponds to photon (Poisson) noise. It leads to $w_\alpha = \text{constant}$ which, as we have seen, is unacceptable. The second case corresponds to a constant read noise. It leads to the choice $w_\alpha \propto f_\alpha$. As the inertia tensor is independent of the normalization of f_α , we may choose the proportionality constant to be unity. This choice of weights solves the convergence problems as the asymptotic dependence of $w_\alpha f_\alpha = f_\alpha^2$ is now proportional to r^{-6} .

While the use of weights solves the convergence and noise problems, it introduces complications in the interpretation of the results. Our choice of weights is equivalent to

performing the previous (unweighted) analysis on a new image formed by squaring the intensity values of the original image. Thus Eqn. 11 is replaced by

$$f(\mathbf{x}) = [\hat{f}(\mathbf{x} + \mathbf{a}/2) + b\hat{f}(\mathbf{x} - \mathbf{a}/2)]^2 . \quad (28)$$

After some algebra, we obtain the inertia tensor

$$I^{ij} = \hat{I}^{ij} + \frac{b}{2} \left\{ \frac{(1 + b^2)\gamma(\mathbf{a}) + 2b}{[1 + b^2 + 2b\gamma(\mathbf{a})]^2} \right\} a^i a^j + \frac{2b\gamma(\mathbf{a})}{1 + 2b\gamma(\mathbf{a}) + b^2} [\hat{I}^{ij}(\mathbf{a}) - \hat{I}^{ij}] \quad (29)$$

where

$$\gamma(\mathbf{a}) = \frac{\int \hat{f}(\mathbf{x} + \mathbf{a}/2) \hat{f}(\mathbf{x} - \mathbf{a}/2) d^2x}{\int \hat{f}^2(\mathbf{x}) d^2x} \quad (30)$$

$$\hat{I}^{ij}(\mathbf{a}) = \frac{\int \hat{f}(\mathbf{x} + \mathbf{a}/2) \hat{f}(\mathbf{x} - \mathbf{a}/2) x^i x^j d^2x}{\int \hat{f}^2(\mathbf{x}) d^2x} . \quad (31)$$

This result is similar in form to Eqn. 12 but has an extra term involving the factor $\hat{I}^{ij}(\mathbf{a}) - \hat{I}^{ij}$. This factor depends on the shape of the PSF and the separation $\mathbf{a}$. For any separation, it can be computed numerically, using the image of the reference star to estimate the PSF.

The function $\gamma(\mathbf{a})$ approaches unity for small values of a and zero for large a . For a Gaussian PSF it has the simple analytic form

$$\gamma(\mathbf{a}) = \exp(-a^2/4\sigma^2) \quad (32)$$

where σ is related to the FWHM w of the PSF by $w^2 = 8 \ln 2 \sigma^2$. For close binary systems a/σ is small and $\gamma(\mathbf{a})$ is quite close to unity.

Eqns. 29-31, which represent the generalization of Eqn. 12 in the weighted case, relate the binary system parameters to the difference in the inertia tensor components between the binary and comparison images.

2.6. Co-adding Images

The signal-to-noise ratio that can be achieved in a single image is limited by the dynamic range of the detector. However, the signal-to-noise ratio can be increased by the use of multiple exposures. A high-signal-to-noise-ratio image can be obtained by co-aligning the individual images, interpolating and summing the individual intensities. However, the complexity of this process can be avoided if one wants only to measure the image ellipticity.

The moments, Eqns. 1-3, are linear in f . Because of this, the sum of the moments of a number of individual images are equivalent to the moments of the summed image. Moreover, because $\mathbf{I}$ is independent of translations, it is not necessary or desirable to co-align the individual images. One simply computes the inertia tensor $\mathbf{I}_\alpha$ for each image and averages the corresponding components:

$$I^{ij} = \frac{1}{N} \sum_{\alpha=1}^N I_\alpha^{ij} . \quad (33)$$

This method is preferable to computing the inertia tensor for a coadded image because the latter technique is sensitive to errors in alignment of the individual images.

3. PERFORMANCE

3.1. Noise Analysis

The analysis of noise propagation in Equations (7), (19-21), and (28) is straight forward. Considerable simplification results if we make the reasonable assumption that the PSF is circularly symmetric, at least to first order. For the limiting cases in which the noise variance per pixel is either constant (read noise dominated) or proportional to the intensity (photon noise dominated) we find

$$Var(I^{ij}) = \frac{1}{s^2} [(I^{ij})^2 + I_n^{iijj}] \quad (34)$$

where s is the total signal-to-noise ratio of the image,

$$s = \rho / [Var(\rho)]^{1/2} \quad (35)$$

and

$$I_n^{ijkl} = \frac{\sum (f_\alpha)^{n/2} x_\alpha^i x_\alpha^j x_\alpha^k x_\alpha^l}{\sum (f_\alpha)^{n/2}} \quad (36)$$

where $n = 2$ for the read-noise-dominated case and $n = 3$ for the photon-noise-dominated case.

For the case of diffraction-limited imaging by a circular aperture, the tensors may be evaluated analytically. Using Eqn. 22 and replacing the summation by integration in Eqn. 36, and recalling that we are working with the square of the intensity (Section 2.5), we obtain

$$I^{11} = I^{22} = \frac{16 \int_0^{2\pi} \int_0^\infty [J_1(kRr)/kRr]^4 \cos^2(\phi) r^3 dr d\phi}{32\pi \int_0^\infty [J_1(kRr)/kRr]^4 r dr}$$

$$\begin{aligned}
&= \frac{1}{2k^2 R^2} \int_0^\infty J_1(x)^4 x^{-1} dx / \int_0^\infty J_1(x)^4 x^{-3} dx \\
&= 0.088179(kR)^{-2} .
\end{aligned} \tag{37}$$

Similarly,

$$\begin{aligned}
I_2^{1111} = I_2^{2222} = I_2^{1122} &= \frac{3}{8k^4 R^4} \int_0^\infty J_1(x)^4 x dx / \int_0^\infty J_1(x)^4 x^{-3} dx \\
&= 9.76197(kR)^{-4} ,
\end{aligned} \tag{38}$$

$$\begin{aligned}
I_3^{1111} = I_3^{2222} = I_3^{1122} &= \frac{3}{8k^4 R^4} \int_0^\infty J_1(x)^6 x^{-1} dx / \int_0^\infty J_1(x)^6 x^{-5} dx \\
&= 1.01967(kr)^{-4}
\end{aligned} \tag{39}$$

which gives

$$Var(I^{11}) = Var(I^{22}) = \left\{ \begin{array}{l} 10.53953 \\ 1.797219 \end{array} \right\} \frac{1}{s^2} \left[\frac{\lambda}{2\pi R} \right]^4 \tag{40}$$

$$Var(I^{12}) = \left\{ \begin{array}{l} 9.76197 \\ 1.01967 \end{array} \right\} \frac{1}{s^2} \left[\frac{\lambda}{2\pi R} \right]^4 \tag{41}$$

where the upper numerical values refer to the read-noise-dominated case and the lower values refer to the photon-noise-dominated case.

From Eqn. 29 it is evident that there is no simple relation between the binary system parameters and the inertia tensor. Simulations indicate that the last term in this equation typically contributes about 1/3 of the ellipticity signal. If we assume that the variance in the image of the comparison star image is comparable to that of the binary system, we expect that

$$Var(ba^i a^j) \sim 10 Var(I^{ij}) . \tag{42}$$

Eqns. 40-42 can be used to estimate the signal-to-noise ratio that would be required for any desired measurement of the binary system parameters. For example, if we assume that the magnitude a of the separation vector is known, the error in the measured flux ratio becomes, for the photon-noise-limited case,

$$\sigma(b) \equiv [Var(b)]^{1/2} \sim \frac{1}{s} \left[\frac{\lambda}{aD} \right]^2 . \tag{43}$$

Thus, in order to detect and measure, to 10% accuracy, a binary which has flux ratio 0.01 and separation comparable to the size of the diffraction-limited PSF, $a = \lambda/D$, we need $\sigma(b) = 0.001$ which implies a total signal-to-noise ratio of order $s \sim 10^3$.

3.2. Simulations

In order to verify this analysis and evaluate the performance of the method, numerical simulations were performed. In a series of Monte-Carlo runs, artificial images were created of both a binary system and a reference star, by placing a suitably-scaled PSF image at the location of each component and then adding random noise. For each run the program estimated the desired parameters. The mean values and standard errors of the parameters were then determined for the set of runs.

As an example, consider the dwarf carbon star system G77-61 (Dahn et al. 1977, Dearborn et al. 1986). The secondary is believed to be a population-II white dwarf, and a measure of its luminosity can provide a lower limit to the age of the universe (Richer et al. 1997). In the near infrared, the white dwarf is expected to be 4 to 5 magnitudes fainter than the primary star, and the maximum separation of the system is estimated to be 0.035 arcsec. For a hypothetical observation using the Hubble Space Telescope (HST) and NIC1 infrared camera, The pixel size is 0.043 arcsec and the aperture diameter is 2.4 m. Thus, to avoid aliasing, we must use filters which block wavelengths below 1.0 μm . The flux ratio is expected to be 0.009 and 0.021 at a wavelength of 1.10 μm and 1.55 μm respectively. We regard the separation as known and wish to measure the relative flux from the observations.

The results of simulations of this system are presented in Figs. 1 and 2 and Table 1. These show the estimated value of the flux ratio b , and its statistical error, as a function of the total signal-to-noise ratio s , for two different wavelengths. At low values of s , noise fluctuations dominate, producing a substantial random elongation of the image. As a result, both b and its error are large. As s increases, the noise fluctuations decrease and the image becomes more circular – both b and its error decrease. At $s \simeq 10^3$, the binary nature of the star prevents further circularization of the image, and b stabilizes at the correct flux ratio. When $s \simeq 10^4$, the relative error of b has dropped to about 0.1. From this we can conclude that in order to measure the flux ratio with an error of 10%, a total signal-to-noise ratio of order 10^4 is required. This is much greater than can be obtained in a single image, but could be achieved by coadding many exposures. The exposure time for the individual images should be chosen to maximize the signal-to-noise ratio, while remaining in the linear region of the detector. As this results in a constraint on the maximum flux in any individual pixel, it may be more convenient to work with the peak signal-to-noise ratio s_p , ie. that of the central pixel, rather than the total signal-to-noise ratio s . For the photon-noise-limited case, the two quantities are related by the square root of the fraction of the total light contained within the central pixel

$$s_p = s \frac{pR\sqrt{\pi}}{\lambda} . \quad (44)$$

Both total and peak signal-to-noise ratios are listed in Table 1.

The results of the simulation show that the analytic error estimate of Eqn. 43 is reasonably accurate. For the 1.1- μ m simulation, this equation predicts that a total signal-to-noise ratio $s \sim 8000$ would be required for a 10% measurement of b which, given the approximation in estimating the Variance from Eqn. 28, is in quite good agreement with the value $s \sim 10000$ indicated by the simulation.

4. DISCUSSION

We have described a new technique for the detection and measurement of unresolved binary systems based on the elongation of their images, in comparison to images of reference stars. The method can only work if variations the shape of the PSF, between the binary and reference observations, are smaller than the elongation to be measured. The analysis and simulations show what signal-to-noise ratio must be obtained in order to reduce the random errors to any desired level. However, one must also consider systematic errors that may not be removed by the differential measurement technique. These include optical aberrations, guiding errors, and any other effects of this nature. Aberrations can be minimized by positioning the reference star and binary at precisely the same location on the detector. Guiding errors which are the same for both reference and target observations will be removed by the analysis, but any variations will contaminate the signal. Such effects should be characterized and understood before observations are attempted. For HST, guiding errors are reported to be of order 0.001 arcsec on an individual exposure. If these are random, they can be reduced to sufficiently small levels by obtaining many exposures.

Ideally, it would be best to observe the target and reference stars simultaneously, if their separation is sufficiently small that both images can simultaneously fit on the detector. In this case asymmetries due to guiding errors should be the same for both images and will be removed by the analysis. in order to minimize optical aberrations, the stars should be placed on opposite sides of the optical field center, and equidistant from it. To further reduce systematic effects, the telescope should be rotated axially by 180 deg, if possible, to interchange the positions of target and reference stars. By exposing for equal times in the two configurations, the systematic component of the PSF will then be identical for both target and reference images.

It should be possible to apply this technique to images produced by adaptive optics systems on ground-based telescopes. The high-resolution provided by such systems facilitates the detection of close binaries, but great care will be needed to minimize

variations in the PSF between the binary system and the comparison star. Because the performance of adaptive optics systems depends the brightness of the reference star and on the atmospheric seeing, the binary system and calibration star need to be well-matched in both magnitude and sky position. We hope to test the feasibility of the method in the near future by means of adaptive-optics observations with the Canada-France-Hawaii Telescope.

I am grateful to Harvey Richer for bringing the problem of the measurement of G77-61 to my attention, and for several interesting discussions. An anonymous referee provided helpful comments and emphasized the importance of matching the comparison and target stars. This work was supported by grants from Natural Sciences and Engineering Research Council of Canada.

Table 1. Simulations of the G77-61 Binary System

s	s_p	1.10 μm $\langle b \rangle$	$\sigma(b)$	s_p	1.55 μm $\langle b \rangle$	$\sigma(b)$
10	4.03	0.507294	0.486904	2.86	0.472412	0.494915
22	8.68	0.428661	0.435401	6.16	0.460700	0.476939
46	18.71	0.136120	0.198945	13.28	0.307730	0.391819
100	40.31	0.049294	0.065857	28.61	0.125452	0.184577
215	86.84	0.023317	0.027893	61.63	0.054850	0.067542
464	187.10	0.013118	0.013616	132.78	0.030990	0.031048
1000	403.09	0.009182	0.007273	286.07	0.022006	0.016621
2154	868.43	0.008086	0.003830	616.30	0.019957	0.008461
4642	1871.00	0.007879	0.001808	1327.81	0.019566	0.003946
10000	4030.94	0.007801	0.000839	2860.67	0.019414	0.001832
21544	8684.26	0.007766	0.000389	6163.02	0.019347	0.000850
46416	18710.01	0.007750	0.000181	13278.07	0.019317	0.000395
100000	40309.41	0.007743	0.000084	28606.68	0.019304	0.000183

REFERENCES

- Born, M., Wolfe, E. 1980, *Principles of Optics*, Sixth Edition (Oxford: Pergamon Press)
- Bracewell R. 1970, *The Fourier Transform and its Applications*, (New York: McGraw-Hill)
- Dahn, C. C., Liebert, J., Kron, R. G., Spinrad, H., Hintzen, P. 1977, ApJ, 423, 723
- Dearborn, D. S. P., Liebert, J., Aaronson, M., Dahn, C. C., Harrington, R., Mould, J., Greenstein, J. L. 1986, ApJ, 300, 314
- Richer, H. Fahlman, G, Hansen, B., Hickson, P., Ibata, R., McClure, R., Walker, G. 1997, Hubble Space Telescope Cycle 7 General Observer Proposal

Figure Captions

Fig. 1.— Detecting a simulated binary system. The curves show the estimated flux ratio of the binary, and its standard error, as a function of the total signal-to-noise ratio in the image. The binary system is assumed to have a true flux ratio of 0.00909 and a separation of 0.035 arcsec. The simulation is for a 2.4-meter telescope at a wavelength of 1.10 μm .

Fig. 2.— This plot is similar to Fig. 1, but for a flux ratio of 0.02083 and a wavelength of 1.55 μm .



