PREPRINT

## Chem ical fracture statistics and universal distribution of extrem e values.

A.Baldassarri<sup>1</sup><sup>3</sup>, A.Gabrielli<sup>1;3</sup> and B.Sapoval<sup>1;2</sup>

<sup>1</sup> Lab. de Phys. de la Matiere Condensee, Ecole Polytechnique 91128 Palaiseau, France

<sup>2</sup> CM LA, Ecole Norm ale Superieure, 94235 Cachan, France

<sup>3</sup> INFM - Dipartimento di Fisica, Univ. di Roma \La Sapienza", P.le A. Moro, 2, ls I-00185 Roma, Italy

PACS.64.60.Ak { Renorm alization-group, fractal, and percolation studies of phase transitions.

PACS.81.40.Np { Fatigue, corrosion fatigue, em brittlem ent, cracking, fracture and failure.

A bstract. { When a corrosive solution reaches the limits of a solid sample, a chemical fracture occurs. An analytical theory for the probability of this chemical fracture is proposed and con meed by extensive numerical experiments on a two dimensionalmodel. This theory follows from the general probability theory of extrem e events given by Gumbel. The analytic law di ers from the W eibull law commonly used to describe mechanical failures for brittle materials. However a three parameters t with the W eibull law gives good results, con ming the empirical value of this kind of analysis.

Chem ical etching of disordered solids is an important technological problem [1], that presents as well interesting questions in the theory of random systems [2]. Strong etching solutions will eventually lead to the fracture of a nite sample, an event de ned as \chem ical fracture". In this letter we present a theory for the statistical behavior of this species of fracture mechanism. We show [3] that the deep nature of the chem ical fracture statistics relies on the probabilistic theory of extrem e events due to G um bel [4]. Interestingly it is found that our chem ical fracture statistics are not practically distinguishable from the W eibull statistics empirically introduced to t mechanical fracture statistics [5].

The problem is studied using a simple two-dimensional corrosion picture [6] inspired by an experimental study of pit corrosion of alum inum Im s [7]. The model describes the chemical etching of a random solid by a nite volume of solution. It predicts that the etching process stops spontaneously on a fractal liquid-solid interface as observed experimentally.

The two dimensional system is described in Fig. 1: The solid is made of lattice sites exhibiting random \resistances to corrosion"  $r_i 2$  [0;1] uniform ly distributed. It has a width L and a depth Y. At any time t the \etching power" of the solution is proportional to the etchant concentration C (t) : p(t) = C(t). The solution has a volume V and contains an initial number N<sub>et</sub>(0) of etchant molecules. Therefore  $p(0) = C(0) = N_{et}(0)=V$  using = 1. Hereafter we choose  $p(0) > p_c$ , where  $p_c$  is the percolation threshold of the lattice.

The solution is initially in contact with the solid through the bottom boundary y = 0. At each time-step t, all surface sites with  $r_i < p(t)$  are dissolved and a particle of etchant is

c EDP Sciences

EUROPHYSICS LETTERS




Fig. 1 { Sketch of the etching dynam ics in a square lattice: the sites 2;3;5 are etched at the st time-step as their resistances are lower than p(0). At the same time the number of etchant particles in the solution decreases by 3 units, and a new part of the solid is uncovered. The process is then iterated.

consumed for each corroded site. Hence, the solution concentration progressively decreases. For an arbitrarily large sample, the corrosion process always stops spontaneously at a certain time  $t_f$  when the etchant concentration  $p(t_f)$  is still nite [3], reaching a maximal depth  $y_M$ . However, when Y is nite, the corrosion can reach the bottom of the sample before  $\xi$ , fracturing the solid into two disconnected parts. This "chemical fracture" is a stochastic event which depends on the realization of the random resistances  $r_i$ .

Hereafter we call P (V) the fraction of samples broken by a volum e V of solution, keeping the other system parameters L,  $p_0$  and Y  $\,$  xed. Its measure is shown in Fig.2. The solution volum e represents the applied chem ical force for given  $p_0$ . Obviously the fracture event is directly related to the value of the maximal depth  $y_M\,$  relative to the sample depth Y: if  $y_M\,<\,$ Y then the fracture does not occur, otherwise the sample will be broken in two distinct pieces. Hence, in order to compute the fracture statistics we have to study the probability distribution of  $y_M\,$  in a sample with an in nite depth.

Before proceeding, it is important to remark the dimension depth of the maximal corrosion depth. The chemical fracture statistics P(V) is a parametric curve which gives the fraction of similar solid samples fractured for a given value of V. Hence P(V) is not a distribution function in the sense of probability theory. In particular V is not a random variable but an external parameter.

On the contrary, the distribution of the maximal corrosion depth is the probability distribution function (DF) of the random variable  $y_M$ , representing the maximal corrosion depth for an (in nitely deep) sample. This is a genuine probability distribution function and, accordingly, its derivative is the probability density function (pdf) of the variable  $y_M$ . O by buy the two quantities are related, but of a di erent nature. In the following we will show how it is possible to recover the rst, via a probabilistic theory of the second.

The fracture statistics P (V) of Fig. 2 has been measured numerically taking a sample of a xed depth and performing several corrosion processes for each value of the solution volume V, and recording the fraction of broken samples as a function of V (see Fig. 2).

On the other hand, the probability distribution of the maximal corrosion depth have been measured xing V and recording the maximal corrosion depth during several corrosion processes on large systems. A dimensioner of V give a dimension, but a universal scaling form can be recognized. As shown in Fig. 3 the numerical DF P ( $z_M < u$ ) for the reduced variable  $z_M$  ( $y_1$   $hy_1$  i) = (where  $hy_M$  i is the average value of  $y_M$  and its




Fig.2 { Chem ical fracture probability P ( $y_M > Y$ ) as a function of the volum e V which m easures the \chem ical force". Sm all circles are the num erical estim ated probabilities perform ing 1000 runs for each value of V applied on a solid of sizes L = 1000 and Y = 500 ( $p_0 = 0.7$ ). D iam onds represent the t of the fracture data with a W eibull law of parameters  $V_0 = 1.15 \quad 10$ ,  $V_1 = 4.08 \quad 10$ , and m = 3.89. The line is the result of the tusing Eq. (10), as explained in the text (the tted parameters A = 0.3875).

standard deviation) is the same for several choices of  ${\tt V}$  .

Since  $y_M$  is an extrem alrandom variable, we compare this num erical distribution with the standard (i.e. with zero mean and unitary variance) G um bel distribution function H (u) [4] for extrem e events:

H (u) = 
$$e^{e^{(bu+a)}}$$
; (1)

where a '  $0:5772 \text{ and } b' \frac{p}{1:64493}$ .

We recall that the G um beldistribution is the canonical distribution for the m axim alvalue of a set of random variables in the sam emanner that the G aussian distribution is the canonical distribution for the sum. More precisely if  $fx_1$ ;  $...;x_N$  g is a set of independent stochastic variables with identical distribution decaying faster than any power law for large values, then, in the large N limit, the maximum value among them can be shown to be G um beldistributed. The collapse of our data on the G um beldistribution is remarkable, rst because there are no adjustable parameters, and second because the points on the interface are correlated to som e extent.

In the following we discuss why the physics of the etching model determ ines such a G um bel behavior. As a second step we will derive from it the theoretical form of P (V). This last task is accomplished considering the probability P ( $y_M > Y$ ) and introducing the explicit dependence of  $h_{Y_M}$  i and on V (with  $p_0$ , Y and L xed), i.e.:

$$P(V) = 1 \exp \exp b \frac{hy_M i(V) Y}{(V)} a$$
 (2)

Such explicit dependence is obtained using the known scaling results of this particular etching model.

We now proceed with the derivation of the Gumbel law for this etching model. First we have to explain why the corrosion front can be reduced to a set of independent random variables. At the beginning of the dynamics [8], p(t) follows the exponential law  $p(t) = p_0 \exp(t - )$  with = V=L. The corrosion front advances layer by layer up to approximatively

EUROPHYSICS LETTERS




Fig. 3 { The numerical integrated probability distribution for reduced  $y_M$  (zero mean and unitary variance) is compared with standard Gaussian and Gumbel distributions. In the main gure, the simulation results collapse on the Gumbel distribution given by Eq. (1) (hidden by data points). In the insets we show the squared di erence between data and the Gaussian and Gumbel distributions. The data refer to simulations performed for L = 3000;5000 and N<sub>et</sub>(0) = 5 10;1 10;2 10;5 10 (1000 di erent dynam ics for each choice of L and V, p = 0.7).

t = t<sub>c</sub> when p(t) = p<sub>c</sub> and reaches a depth y<sub>lin:</sub> V=L. A fler this period the corrosion front becomes very irregular and nally stops at t =  $\frac{1}{2}$ . At t<sub>f</sub> the etching power p<sub>f</sub> = p(t<sub>f</sub>) is slightly smaller than p<sub>c</sub> and the nalcorrosion front is fractal with dimension D<sub>f</sub> = 7=4 up to a characteristic width < L. This situation is displayed in Fig. 4. As shown in [8], this phenom enon obeys the scaling law s of G radient Percolation [9] where the role of the gradient is played by the ratio L=V. This in plies that

$$(L = V)^{1 = D_{f}}$$

can be seen as a percolation correlation length.

The total nalcorrosion front, shown in Fig. 4, can then be considered as a juxtaposition of N L= nearly independent fractal boxes of lateral width (for a similar recognition of e ective independent variables in extreme statistics see [10]). Inside each box k, there is a point of maxim al penetration of the front  $y_M^{(k)}$ . Since such points belong to di erent boxes, the values  $y_M^{(k)}$  are, by construction, identically distributed and independent random variables. The extrem e position of the front is the maxim al value between such a collection of random variables. This is why a G um bel distribution is observed.

M ore precisely due to the underlying percolation phenomena, the DF for each  $y_M^{(k)}$  has exponential tail with the same characteristic scale :

$$P \quad y_{M}^{(k)} > y \qquad e^{\frac{y}{c} \frac{h_{Y_{M}^{(k)}} i}{c}} \text{ for } y \qquad y_{M}^{(k)} > ; \qquad (3)$$

where c is a constant of order 1 (see also some recent results on the size of sub-critical clusters [11]). In this case, the theory of extrem e statistics [4] in poses that, for N  $1, y_M$  is asymptotically G um bel distributed, i.e. P  $[(y_M \quad hy_M \ i)= ) < u] = H$  (u) and that:

T.

$$h\underline{y}_{M} \mathbf{i} = \underline{y}_{M}^{(k)} + \log \mathbf{N}$$
(4)

$$= 2c$$
 : (5)




Fig. 4 { Final corrosion front: It is composed of N L= independent regions of size ( can be considered as the correlation length of the system ). The extrem al front position  $y_M$  is indicated. It is the max between the N independent values of  $y_M^{(k)}$  of each region.

It is then necessary to test numerically Eqs. (4) and (5) (and speci cally the logarithmic dependence on N, i.e. on  $L = \frac{1}{D}$ , in order to con m this arguments. In the situation described in Fig. 4 one observes that  $y_M^{(k)}$  is given by the average depth  $y_f$  of the nal corrosion front (average taken over all the nal front sites) plus a positive shift of order . In turn, the average depth  $y_f$  (a directly measurable quantity in simulations) is given by the depth  $y_{lin}$ : reached during the linear part of the corrosion in addition to a shift (sub-leading) again of order . Therefore from Eq. (4) we can write:

$$h_{Y_M}$$
 i  $y_{f}$  [1 +  $k_1 \ln (L = )$ ] (6)

$$y_f \quad y_{in}$$
: (7)

$$y_{\text{lin}}$$
: V=L (8)

where  $k_1$  is a coe cient of order one. Recalling that  $(V=L)^{4=7}$ , we can substitute  $hy_M$  i and as functions of V in Eqs. (5) and (4) in order to obtain the real functional dependence of P (V) on V apart from num erical scaling coe cients.

The scaling behaviors are them selves con m ed by the extensive numerical simulations shown in Fig. 5. Note that if L = is kept constant (i.e. if L  $V^{4=11}$ ) then  $[Iy_M i y_f]$  (L=V) <sup>1=D f</sup>. The measured exponent 0:59 0:02 is consistent with this prediction. In the same gure, we also report the scaling behavior of the standard deviation and of y. These

ts con m that and that fy can be written as the sum of  $y_{lin}$ : and a shift of order . Finally, the linear logarithm ic dependence on L for xed (i.e. for xed L=V), which is the essential con m ation of Eq. (4), is shown in the inset. It has also been numerically con m ed that and  $y_f$  does not depend on L for xed sigma (not shown in the gure).

To sum marize, Eq. (2) and Eqs. (6-9) give the theoretical form for P (V), once the proportionality coe cients in Eqs. (6-9) and the coe cient  $k_1$  have been determ ined. For simplicity, it is convenient to rewrite Eq. (2) as follows:

$$P(V) = 1 \exp A \frac{L}{-} \exp \frac{b(y_f Y)}{-} :$$
 (10)

The dependence on  $k_1$ , described in Eq. (6), is now contained in the coe cient A. As a closure test of our analysis we choose to use this form to tagainst A the num erical fracture statistics (i.e. the fraction of simulation runs breaking the sample as a function of V) [12]. As shown in Fig. 2, the theoretical form of P (V) and the simulation are in excellent agreement.

EUROPHYSICS LETTERS




Fig.5 { Scaling behavior of  $y_f$ ,  $[Ty_M i y_f]$  and . The data in the main graph refer to simulations perform ed with a constant L= (range of parameters: from L = 522 and V = 5 10 to L = 11550 and V = 5 10). The numerical ts are in accordance with the theoretical behaviors. The inset shows the logarithm ic dependence of  $Hy_M$  i on L for a given (parameters range from L = 1205 and V = 120500 to L = 80000 and V = 8 10, chosen to have a constant ). In both cases the data correspond to 1000 di erent dynamics for each choice of L and V, p = 0.7.

In sum m ary, we have studied the chem ical fracture due to the extrem alpropagation of a corrosion front in a two-dimensional scalar etching m odel. It has been shown both theoretically and numerically that the statistics of the maximal depth reached by the solution is given by the well known G um belextrem al distribution function. From this it has been possible to extract theoretically the probability of a chem ical fracture.

Before concluding, we believe that it could be interesting to compare our results with the commonly analysis used for mechanical fracture statistics. In this case, even though a widely accepted theoretical frame is still lacking, the standard empirical t is offen performed using a Weibull law [5]. In our chemical fracture model, this comes to try to t the datas with:

$$P_{W}$$
 (V) = 1 e  $\frac{V V_{0}}{V_{1}}$  with V > V<sub>0</sub>; (11)

where  $V_0$  (the m inim al stress to have a nite fraction of fractures),  $V_1$  and m are suitable parameters.

The result, shown in Fig. 2, is that the chem ical fracture statistics can be tted very accurately with a W eibull law. We have also veri ed (not shown here) that the W eibull low probability tails (the test generally used by engineers) to nicely with our data. On one side, we believe that this is astonishing, since, despite the simple scalar nature of the model, we recover, for our purely chem ical process, the same empirical statistics found for m echanical failures of brittle materials, generally observed in more complex (vectorial or tensorial) frames. On the other side, it is important to remark that in the present case the W eibull law is only an empirical t, because the real analytical form of the chem ical fracture statistics is given by Eq2. Moreover a W eibull law, which is usually related to the presence of power law distributed aws, has no reason to emerge here, as Eq2 results from a theoretical calculation of the model and directly connected to known results in percolation theory.

As a nal remark, one could suggest that the correspondence between the W eibull t and the underlying G um bel distribution ( rst suggested by [13]) found here is linked more generally to G radient Percolation. G radient Percolation situations can also be present in solids which have never been etched [14]. The essential ingredients of our theory are (i) the percolation aspect linked to random ness of the system, and (ii) the existence of a gradient. In real system s gradients m ay exist in the sam ple, for exam ple the ion concentration gradient in glass bers used in communication optics. But it m ay also appear in experiments, for instance in experimental studies of ceram ic fracture. In classical exure experiments the distribution of stress is non uniform [15]. It remains to be determined speci cally if such gradient mechanisms are responsible for some of the ubiquitous apparent W eibull statistics.

Our two dimensional results could be generalized to higher dimensions, according to [16]. Therein, eld theoretic arguments show that the corrosion dynamics towards the nal state can be described as a self-organized absorbing phase transition towards the critical phase of percolation in any dimension.

W e are grateful to M.Dejnek and S.Zapperi for useful comments and we acknow ledge the support of the European Community TMR Network ERBFMRXCT 980183.

## REFERENCES

- [1] Hench L. and Clark J.D., J. Non-Cryst. Solids, 28 (1978) 83.
- [2] Herrmann H. and Roux S., Statistical models for the fracture of disordered media (North-Holland ed. Am sterdam, Netherlands) 1990.
- [3] BaldassarriA., Statistics of Extrem e Persistent Events (Ph.D.Thesis, University of Paris X I) 1999.
- [4] Gumbel E.J., Statistics of Extremes (Columbia University Press, New York) 1958; Galambos J., The Asymptotic Theory of Extreme Order Statistics (R.E.K rieger Publishing Co., Malabar, Florida) 1987.
- [5] W eibull W ., J. Appl. Phys., 18 (1951) 293.
- [6] Sapoval B., Santra S.B. and Barboux Ph., Europhys. Lett., 41 (1998) 297; Santra S.B. and Sapoval B., Physica A, 266 (1999) 160.
- [7] BalazsL., Phys.Rev.E, 54 (1996) 1183.
- [8] GabrielliA., BaldassarriA. and Sapoval B., Phys. Rev. E, 62 (2000) 3103.
- Sapoval B., Rosso M. and Gouyet J.F., J. Phys. Lett. (Paris), 46 (1985) L149; Sapoval B., Rosso M. and Gouyet J.F., The Fractal Approach to Heterogeneous Chemistry, edited by D. Avnir (John W iley and Sons Ltd., New York) 1989.
- [10] Curtin W . A ., Phys. Rev. Lett., 80 (1998) 1445.
- [11] Bazant M.Z., Phys. Rev. E, 62 (2000) 1660.
- [12] For and  $y_f$  we impose the scaling predictions Eq. (6-9) with coecients independently tted from data in Fig.5.From the same data it should be possible to get  $k_1$ , and hence A.However, the logarithm ic nature of the scaling makes this procedure delicate, and we prefer to t A instead.
- [13] Duxbury P.M., Leathand P.L. and Beale P.D., Phys. Rev. B, 36 (1987) 367.
- [14] See the breakdown m odel in ZapperiS., Herrmann H.J. and Roux S., Eur. Phys. J. B, 17 (2000) 131.
- [15] Jayat ilaka A. de S., Fracture of Engineering Brittle Materials (Applied Science Publishers, London) 1979.
- [16] A.Gabrielli, M.A.Munoz, and B.Sapoval, Phys. Rev. E, 64 (2001) 016108.