arXiv:cond-mat/0211461v1 [cond-mat.soft] 21 Nov 2002

An intrinsic route to melt fracture in polymer extrusion: a weakly nonlinear subcritical instability of viscoelastic Poiseuille flow

Bernard Meulenbroek[1],* Cornelis Storm[1],† Volfango Bertola[2],
Christian Wagner[2], Daniel Bonn[2], and Wim van Saarloos[1,2]
[1] *Instituut-Lorentz, Universiteit Leiden, Postbus 9506, 2300 RA Leiden, The Netherlands*
[2] *Laboratoire de Physique Statistique, Ecole Normale Supérieure, 24 rue Lhomond, 75231 Paris Cedex 05, France*
(Dated: March 22, 2022)

As is well known, the extrusion rate of polymers from a cylindrical tube or slit (a "die") is in practice limited by the appearance of "melt fracture" instabilities which give rise to unwanted distortions or even fracture of the extrudate. We present the results of a weakly nonlinear analysis which gives evidence for an intrinsic generic route to melt fracture via a weakly nonlinear subcritical instability of viscoelastic Poiseuille flow. This instability and the onset of associated melt fracture phenomena appear at a fixed ratio of the elastic stresses to viscous stresses of the polymer solution.

PACS numbers: 47.20.Ft, 47.50.+d, 83.60.Hc

If a polymeric fiber is produced by extruding it from a so-called die, a cylindrical tube or planar slit, the surface often exhibits undulations or irregularities at higher flow rates — see Fig 1. For increasing flow rates the undulations become progressively stronger, so much so that it can eventually cause the extrudate to break — hence the name *melt fracture*. A detailed understanding of this phenomenon has remained elusive for already over 30 years.

Depending on the geometry and type of polymer, various types of phenomena seem to occur [1, 2, 3]. The short wavelength deformations of the interface often refered to as "sharkskin" instability appear to originate at the outlet: the extrudate quasi-periodically sticks to the outlet, widens, snaps loose and narrows. In the "spurt-flow" regime, the extrudate shows intermittent bands of smooth and irregular surfaces; there is good evidence that this has to do with a stick-slip phenomenon at the wall of the die. In spite of the multitude of possibilities, there is every reason to believe that when these instabilities are absent, as in the experiments of Fig. 1, polymer flow still exhibits some elusive generic bulk flow instability: According to the engineering literature [3], a qualitative change in the flow behavior appears to occur at a more or less constant ratio of the normal stress difference of the melt over the shear stress for almost any polymer. Isolating this intrinsic mechanism is the main purpose of this paper. Our contribution also opens up new avenues for a more general understanding of the rich variety of complex fluid flow instabilities, such as polymer turbulence [6] or the fact that complex fluids such as granular media are prone to instabilities (shear banding) in standard shear configurations.

The first linear stability analysis of the flow in the die of a viscoelastic fluid described by the so-called Oldroyd-B constitutive equations [4], performed already some 25 years ago [5], showed that the flow was stable. Since then it is has been generally accepted that *Poiseuille flow of viscoelastic fluids is linearly stable*. The absence of a clear *linear instability* explains the focus on other mechanisms, like those mentioned above. In this paper we present the result of an analytical nonlinear amplitude expansion which show that *viscoelastic Poiseuille flow exhibits a weakly nonlinear (or "subcritical") instability* due to normal stress effects; this instability appears to make melt fracture phenomena unavoidable for polymer fluids with normal stress effects, even if care is taken to suppress instabilities associated with the wall or shape of the die. Recent experiments on polymers whose rheology is well captured by the Oldroyd-B model [7] confirm our scenario as well as our quantitative predictions.




FIG. 1: Illustration of the surface irregularities that occur in the extrusion of a polymer fluid from a capillary tube (the wider structure at the top) in the absence of shark-skin or spurt flow instabilities. For small speeds, the surface is smooth *(a)*, but beyond some flow speed surface irregularities develop, *(b)* and *(c)*. The wavelength is of the order of twice the diameter d of the capillary. After [7].

Although polymer fluids can exhibit all kinds of complicated relaxation phenomena, the basic feature essentially all polymer fluids (and in fact most complex fluids) share is the occurrence of elastic stress effects: when the shear rate is sufficiently strong that the polymers become stretched by the flow gradients, the forces along

the normals of a little cubical fluid element are different in different directions, unlike what happens for a Newtonian fluid where the pressure is isotropic. Microscopically, this effect is due to the fact that in sufficiently strong shear flows, the polymers get stretched (like little rubber bands) and acquire a nonisotropic orientational distribution. Thus they "pull" differently on fluid elements in the direction along the flow and along the shear gradient. The simplest model to capture this effect (and which hence has become the working horse of theoretical studies of viscoelastic polymer flow [4, 8, 9]) is the so-called Oldroyd-B model; we study it in the limit of large polymer viscosity, in which case it is refered to as the Upper Convected Maxwell (UCM) model. In this regime it is defined by the following constitutive equation for the shear stress tensor τ in terms of the velocity shear tensor $\boldsymbol{\nabla v}$ through

$$\boldsymbol{\tau} \;+\; \lambda \left[\partial\boldsymbol{\tau}/\partial t + \boldsymbol{v}\cdot\boldsymbol{\nabla\tau} - (\boldsymbol{\nabla v})^{\dagger}\cdot\boldsymbol{\tau} - \boldsymbol{\tau}\cdot(\boldsymbol{\nabla v})\right] = -\eta(\boldsymbol{\nabla v} + (\boldsymbol{\nabla v})^{\dagger}), \qquad (1)$$

This constitutive equation is characterized by one single relaxation time λ. The first two terms between square brackets together constitute the total time derivative of a fluid element moving with the flow; the other two nonlinear terms are required by frame-independence, e.g. the fact that a solid-body rotation of the fluid does not lead to elastic stress effects. For fluids given by this constitute equation, the velocity profile in Poiseuille flow is parabolic, just as in Newtonian fluids. Moreover, in a cylindrical tube with radius R and coordinates (θ, r, z), the above-mentioned Weissenberg number (also called Deborah number) which is defined as

$$\mathsf{Wi} \equiv \left.\frac{\tau_{rr}-\tau_{zz}}{\tau_{rz}}\right|_{\rm wall}, \qquad (2)$$

becomes, upon following the usual convention to denote the shear rate $\partial v_z^{\rm unp}/\partial r|_{\rm wall}$ by $\dot\gamma$,

$$\mathsf{Wi} = 2\lambda\dot\gamma = 4v_{\rm max}\lambda/R. \qquad (3)$$

Note that the Weissenberg number defined in (2) is indeed the ratio of the so-called first normal stress difference $\tau_{rr}-\tau_{zz}$ at the wall over the shear stress at the wall. Newtonian fluids are isotropic and hence the stress difference is zero; for Oldroyd-B model fluids, the normal stress difference $\tau_{rr}-\tau_{zz}\sim\dot\gamma^2$ [4] while the shear stress is linear, $\tau_{rz}\sim\dot\gamma$; as a result Wi is simply linear in $\dot\gamma$.

The weakly nonlinear instability scenario that our calculations imply is illustrated in Fig. 2a. Along the vertical axis we plot the relative perturbation of the basic flow profile (e.g. the relative shear perturbation at the wall, or the relative shear stress perturbation at the wall) as a function of Wi. Perturbations of the flow whose amplitude is bigger than the value given by the thick dashed line are unstable; their amplitude grows to some nonlinear value indicated by the full line. This line denotes




FIG. 2: Summary of our main result for the stability of viscoelastic Poiseuille flow in a cylinder in the zero Reynolds number limit. *(a)* Semi-quantitative sketch of the bifurcation scenario. See text. *(b)* Our results for the threshold values of the amplitude beyond which the flow is unstable; these curves correspond to the dashed branch in *(a)*. Dots indicate the critical value of the shear rate at the wall (normalized to the shear in the unperturbed case), squares the critical value of the relative shear stress perturbation, multiplied by 10.

nontrivial flow behavior with a characteristic wavelength. Note that the dashed line never touches the horizontal axis, in agreement with the fact that Poiseuille flow is always linearly stable [5], although the threshold amplitude becomes very small for large Wi. Furthermore, note that the full line merges with the unstable (dashed) branch (this is called a saddle-node bifurcation point in technical terms); below the corresponding value $\mathsf{Wi}_{\rm c}$, Poiseuille flow is nonlinearly stable to perturbations of any amplitude. In this paper, we focus on our results for the cylindrical die, since this is the most relevant case. For slits similar results are obtained [10].

Fig. 2b shows our analytical results for the (dashed) branch that marks the threshold amplitude beyond which the flow us unstable. As described in more detail below, our analysis is based on an expansion to third order in the perturbation amplitude; beyond some critical value $\mathsf{Wi}_{\rm c}\approx 5$, we find that the cubic terms in our expansion lead to an instability, and from this we are able to calculate the threshold value. Clearly, our results are fully consistent with the scenario of Fig. 2a: the flow is stable to arbitrarily small (linear) perturbations, but perturba-

tions as small as a few percent in the shear stress at the wall already render the flow unstable for values of Wi around 10. The critical value of Wi_c we estimate from our calculations is also in agreement with the very recent precise experimental data on a model UCM fluid [7, 11], and with the range where long polymers have been reported to show a change in the flow behavior [3].

Actually, a number of observations already made us believe that the scenario summarized in Fig.2 was a viable one before we embarked on our analysis: *(i)* For increasing Wi, the linear stability actually becomes arbitrarily weak (the damping of the linear modes decreases as 1/Wi). *(ii)* In the zero Reynolds number limit, the flow of an Oldroyd-B fluid in a Taylor Couette cell (two concentric rotating cylinders) is linearly unstable above some well-defined value of the Deborah number, which is analogous to the Weissenberg number [8, 9]. This linear instability is due to the fact that "hoop stresses" generally make flow along curved streamlines unstable [8, 12]. However, recent experimental investigations [13] have clearly demonstrated that the instability is "subcritical": as sketched qualitatively in Fig. 2a, the nonlinear flow branch corresponding to roll-type patterns in the Taylor-Couette cell has been shown [13] to extend down to about half the critical value where the linear instability occurs (the point where the dotted line intersects the horizontal axis). The subcritical character of the instability has been argued not to depend on the curvature of the streamlines which causes the linear instability in the Taylor-Couette cell. Thus, it is reasonable to assume that both in viscoelastic Poiseuille flow and in viscoelastic Taylor-Couette flow there is a subcritical instability, and that the only essential difference is that in the first case the dashed branch never intersects the horizontal axis, while in the second case it does. *(iii)* The transition to turbulence for Poiseuille flow of Newtonian fluids is also subcritical [14].

Returning to our analysis, it is based on deriving the first nontrivial nonlinear term in an amplitude expansion for the perturbation to the velocity and shear stress fields of Poiseuille flow of an UCM fluid. Conceptually, this method goes back to the classic work [14] in which the subcritical nature of the transition to turbulence of ordinary fluids was established; since then, amplitude expansions have become a standard tool in the field of nonequilibrium pattern formation [15]. We write the constitutive equation (1) and the Navier-Stokes equation (which in the zero Reynolds number limit is linear) in cylindrical coordinates and then study the evolution of the amplitude A of a perturbation $A(\delta v_r, \delta v_z, \delta\tau_{\theta\theta}, \delta\tau_{rr}, \delta\tau_{rz}, \delta\tau_{zz})e^{ikz-i\omega t}$, where the vector is normalized such that the shear perturbation $\partial\delta v_z/\partial r$ at the wall equals A [16]. To first nontrivial order we then obtain an equation of the form

$$dA/dt = -i\omega(k)A + c_3|A|^2A + \cdots \qquad (4)$$




FIG. 3: Values of the critical shear stress amplitude $\tau_c(k)$, the ratio of the perturbation in the shear stress τ_{rz} (normalized to the value $\tau_{rz}^{\rm unp}$ of the unperturbed state) at the wall above which the perturbation is nonlinearly unstable, as a function of the wavenumber k of the perturbation in the z-direction.

To linear order in A this equation simply reproduces the term $\omega(k)$ of the dispersion relation of a single mode $e^{ikz-i\omega t}$; this term is already contained in the old analysis of [5]. In particular, since we know that every mode k is linearly stable, $\mathrm{Im}\,\omega(k) < 0$ for all k.

The crucial new feature of our analysis consists of calculating the coefficient c_3 explicitly — although this is technically demanding, the analysis is standard and conceptually straightforward. It will therefore be discussed elsewhere [10]. In particular the real part of c_3 is of importance for determining whether or not the flow is nonlinearly unstable: if $\mathrm{Re}\,c_3 < 0$, then the nonlinear terms increase the damping of the amplitude and the unperturbed state is, within this approximation, also nonlinearly stable. On the other hand, if $\mathrm{Re}\,c_3 > 0$, then the nonlinear term promotes the growth of the amplitude, and in particular amplitudes

$$|A| > A_c = \sqrt{\frac{\mathrm{Im}\,\omega(k)}{\mathrm{Re}\,c_3}} \qquad (5)$$

grow without bound. Hence, in this approximation A_c constitutes the *critical amplitude beyond which the flow is nonlinearly unstable*. The results presented in Fig. 2b for A_c are obtained directly from our results for the coefficient c_3. In dimensionless units and with our normalization, A_c immediately yields the relative shear rate perturbation at the wall, necessary to make the flow unstable. With a numerical factor that we obtain from our analysis, A_c can be converted into a value for the critical relative shear stress ratio τ_c, the perturbation in the shear stress beyond which the flow is unstable.

As we already discussed in connection with Fig 2b, for $\mathsf{Wi} \gtrsim 5$, we find that there is some range of wavenumbers k for which $\mathrm{Re}\,c_3 > 0$, and hence for which the Poiseuille




FIG. 4: Plot of the width of the k-band where the corresponding modes render the basic Poiseuille flow profile unstable.

profile is nonlinearly unstable. In Fig. 3 we show for three values of Wi the relative critical shear stress amplitude $\tau_c(k)$ beyond which the flow is unstable, as a function of the wavenumber k. The further one gets above the value Wi_c where the instability sets in, the wider the band of k-values is where we find an instability; the values plotted in Fig. 2b for τ_c correspond to the minimum values of the curves in Fig. 3, but as this figure shows for larger values of Wi, the bands are very flat so that the strength of the instability does not appear to depend very sensitively on k within the unstable band.

In Fig. 4 we plot the band in which modes are nonlinearly unstable beyond some threshold amplitude. It is important to realize that k in this figure is the wavenumber of the modulation of the Poiseuille flow *inside* the tube: Since the flow changes upon exiting the tube, this is not necessarily the same as the wavenumber of the induced roughness modulation outside the die, as in Fig. 1c, but the two can be connected by equating the *frequency* of the modulations measured at a fixed position. Our numerical results show that the mode with $kR \approx 3.75$ which according to Fig. 4 emerges at $\mathsf{Wi} = \mathsf{Wi}_c \approx 5$ moves with a velocity of about $v \approx 1.9\, v_{\rm av}$ where $v_{\rm av}$ is the average flow velocity. If the nonlinearities do not change this speed to much, this suggests a frequency f at onset of about $3.75\, v/(2\pi R) \approx 1.13\, v_{\rm av}/R$. Further above threshold our amplitude expansion to cubic order neither yields the speed of the finite-amplitude modulated stress pattern nor the selected wavenumber. However, it is reasonable to assume that in the saturated nonlinear regime, the pattern moves with speed $v_{\rm av}$ in the tube. From the band of unstable wavenumbers shown in Fig. 4, we then conclude that the frequency of the extrudate modulations should then lie in the range $0.3\, v_{\rm av}/R \lesssim f \lesssim 0.72\, v_{\rm av}/R$.

The fact that the critical Weissenberg number $\mathsf{Wi}_c \approx 5$ which we find is in good agreement with the transition value noted empirically [3] is already a strong indication that the instability which we have identified lies at its origin. Further independent evidence comes from a series of new experiments which we have performed on a range of PVA Borax polymer solutions, whose rheological behavior is well described by the Oldroyd-B/UCM model (constant shear viscosity, normal stress proportional to the shear rate squared). Our scenario implies that the first transition to melt fracture should be hysteretic, i.e. occur at a higher value of Wi upon increasing the flow rate than upon decreasing the flow rate; this is indeed observed in the experiments. Likewise, the wavelength of the roughness modulations is in good agreement with the theoretical analysis. We refer to [7] for details.

In conclusion, we shown that normal stress effects drive viscoelastic Poiseuille flow unstable. We speculate that many nontrivial flow patterns of complex fluids that emerge under simple shear have a similar origin.

* Present address: CWI, Postbus 94079, 1090 GB Amsterdam, The Netherlands
† Present address: Department of Physics and Astronomy, University of Pennsylvania, Philadelphia, PA 19104, USA

[1] M. M. Denn, *Issues in viscoelastic fluid mechanics*, Annu. Rev. Fluid Mech. **13**, 13 (1990).
[2] M. M. Denn, Annu. Rev. Fluid Mech. **33**, 265 (2001).
[3] M. Pahl, W. Gleissle and H.-M. Laun, *Praktische Rheologie der Kunststoffe und Elastomere* (VDI verlag, 1991).
[4] R. B. Bird, R. C. Armstrong and O. Hassager *Dynamics of Polymeric Liquids* (Wiley, New York, 1987).
[5] T. C. Ho and M. M. Denn, J. Non-Newtonian Fluid Mechanics **3**, 179 (1978).
[6] G. V. Vinogradov and V. N. Manin, Kolloid Z. **201**, 93 (1965); A. Groisman and V. Steinberg, Nature **405**, 53 (2000); R. G. Larson, Nature **405**, 27 (2000).
[7] V. Bertola, B. Meulenbroek, C. Wagner, C. Storm, W. van Saarloos, and D. Bonn (unpublished).
[8] R. G. Larson, E. S. G. Shaqfeh and S. J. Muller, J. Fluid Mech. **218**, 573 (1990).
[9] E. S. G. Shaqfeh, Annu. Rev. Fluid Mech. **28**, 129 (1996).
[10] B. Meulenbroek, C. Storm and W. van Saarloos, submitted to Phys. Fluids.
[11] We stress that our amplitude expansion to cubic order is selfconsistent for the determining the nonlinear instability threshold for large Wi, where the threshold values are small. Near the saddle-node at Wi_c, higher order terms are expected to be important quantitatively.
[12] P. Pakdel and G. H. MacKinley, Phys. Rev. Lett. **77**, 2459 (1996).
[13] A. Groisman and V. Steinberg, Phys. Fluids **10**, 2451 (1998).
[14] P. Huerre and M. Rossi, in: *Hydrodynamics and Nonlinear Instabilities*, C. Godrèche and P. Manneville, eds. (Cambridge UP, Cambridge, 1998).
[15] M. C. Cross and P. C. Hohenberg, Rev. Mod. Phys. **65**, 851 (1993).
[16] We assume no θ-dependence of the modes; in spite of this, $\tau_{\theta\theta} \neq 0$ in cylindrical coordinates.