## Electric Field E ects on the D i use Scattering in PZN -8% PT

 $P.M.Gehring^1 K.Ohwada^2 and G.Shirane^3$ 

<sup>1</sup>N IST Center for Neutron Research, National Institute of Standards and Technology, Gaithersburg, Maryland 20899-8562

<sup>2</sup>Synchrotron Radiation Research Center (at SPring 8),

Japan Atom ic Energy Research Institute, Sayo-gun Hyogo 679-5148, Japan and

<sup>3</sup>D epartm ent of Physics, B rookhaven N ational Laboratory, Upton, New York 11973-5000

(Dated: April 14, 2024)

We report measurements of the neutron di use scattering from a single crystal of the relaxor ferroelectric  $PbZn_{1=3}Nb_{2=3}O_3$  doped with 8%  $PbTiO_3$  (PZN-8% PT) for temperatures 100K T 530K and electric elds  $0 \, kV \, / cm$  E  $10 \, kV \, / cm$ . The di use scattering is strongly suppressed transverse to the (003) B ragg peak at 400K for E =  $2 \, kV \, / cm$  applied along the [001] direction. However, no change in the di use scattering is observed transverse to (300), even for eld strengths up to  $10 \, kV \, / cm$ . Thus the application of an external electric eld in the tetragonal phase does not produce a macroscopically polarized state. This unusual behavior can be understood within the context of the H irota et al. phase-shifted polar nanoregion (PNR) m odel of the relaxor di use scattering, since an electric eld E oriented parallel to [001] would rem ove the shift of the nanoregions along [001] while preserving those along the orthogonal [100] direction.

PACS num bers: 61.12.-q, 77.65.-j, 77.84 D y

#### I. IN TRODUCTION

The shape, size, density, and orientation of the polar nanoregions (PNR) that form below the Burns temperature  ${T_d}^1$  in the lead-oxide class of relaxors Pb  $(Zn_{1=3}Nb_{2=3})O_3$  and Pb  $(Mg_{1=3}Nb_{2=3})O_3$  doped with PbT iO<sub>3</sub> (PZN-xPT and PMN-xPT, respectively) are key param eters of interest to m any researchers attem pting to clarify the various mechanisms responsible for the exceptional piezoelectric properties exhibited by these m aterials.<sup>2</sup> First identi ed through opticalm easurem ents of the index of refraction by Burns and Dacol,<sup>1</sup> the presence of PNR have been correlated with the onset of neutron diffuse scattering in PMN, a saturation of the unit cell volum e below  $T_d$ , and the overdam ping of long-wavelength phonon m odes in PZN and PZN-8% PT.<sup>5,6</sup> M ore recently an important model concerning the relationship between the PNR and the surrounding cubic lattice was presented by Hirota et al.7 Based on neutron time-of-ight measurem ents of the di use scattering in PMN at 300K perform ed by Vakhrushev et al,<sup>8</sup> H irota et al. noticed that the corresponding ionic displacem ents could be decom posed into a scalar shift (displacem ent) common to all atom s, and a pattern of shifts that satis es a center-ofm ass condition.<sup>9</sup> It was further shown that these centerofm ass shifts are consistent with neutron inelastic measurem ents of the soft TO phonon intensity in PMN above T<sub>d</sub>, thus providing compelling evidence that the polar nanoregions result from the condensation of a soft mode at the Bums tem perature.

Subsequent m easurem ents on PZN-8% PT using neutron di raction techniques by Ohwada et al. dem onstrate that the zero- eld cooled structure at low tem perature is not rhom bohedral as had been previously believed.<sup>10</sup> Instead, surprising evidence of a new phase, called phase X, was found that exhibits an average cubic unit cell structure. These ndings motivated the highenergy x-ray study by Xu et al. on pure PZN,<sup>11</sup> and the high-resolution neutron study by Gehring et al. on PMN-10% PT.<sup>12</sup> Both of these studies revealed a lowtem perature bulk phase that is not rhom bohedral, but rather consistent with the phase X observed by O hwada et al. in PZN-8% PT. It has been suggested that the phase-shifted nature of the PNR could be responsible for stabilizing phase X at low tem peratures as the uniform shift of the PNR would present a natural energy barrier in the system against the form ation of a uniform polar state.

To shed more light on this idea, we have perform ed a study of the PNR in PZN-8% PT by measuring the response of the neutron di use scattering below the cubicto-tetragonal phase transition temperature T<sub>c</sub> 470 K to an external electric eld E.As is well known, a classic ferroelectric system will break into many domains below T<sub>c</sub>, and the application of an electric eld can produce a nearly uniform polar state by aligning all of the dom ains via dom ain wall motion. In the case of the relaxor ferroelectric PZN-8% PT, however, our data show that for E oriented parallel to the [001] direction, only the diffuse scattering transverse to the (003) reciprocal lattice point decreases. The di use scattering transverse to the orthogonal (300) position is una ected. Thus a macroscopic uniform ly polarized state is not achieved. The model of phase-shifted PNR provides a possible explanation for these ndings, as an electric eld along [001] would rem ove the PNR shift along [001] while preserving that along [100].

#### II. EXPERIMENTAL DETAILS

The neutron scattering data presented here were obtained on the BT9 triple-axis spectrom eter located at the NIST Center for Neutron Research. The di use scattering near the reciprocal lattice points (300) and (003) was measured at a xed neutron energy  $E_{\rm i}$  =  $E_{\rm f}$  = 14.7 meV ( = 2:36A) using the (002) re ection of highly-oriented crystals of pyrolytic graphite (HOPG) as monochrom ator and analyzer. Horizontal beam collim ations were  $40^0\text{-}46^0\text{-}$ S-40 $^0\text{-}80^0$  (S = sam ple).

The high-quality single crystal of PZN-8% PT used in this study was grown by the ux solution  $m = 1000 \text{ m}^{-3}$  at the Pennsylvania State University. It is a sister crystal to the one used by Ohwada et al. in an earlier study, some results from which are presented in this paper.<sup>10</sup> The crystalweighs  $1.1 \text{ gm} (0.15 \text{ cm}^3)$ , and is a rectangular block with 100 faces and dimensions 72 6.9 3.0 mm<sup>3</sup>. G old electrodes were plated onto the two largest surfaces of the crystal to which thin gauge copper wires were attached using a red-on silver conductive adhesive epoxy cured at 100C for 2 hours. In this geometry the eld is always applied along a cubic [001] axis. These wires were twisted and soldered onto leads connected to a high voltage power supply. Tests were performed both before and after the experim ent to verify that the voltage set by the power supply appeared across the sam ple. The di erence between the set and measured voltage drop was always less than 1%.

The crystalw asm ounted onto an electrically insulating boron nitride post using boron nitride paste to provide a strain-free environment for the sample. The crystal [010] axis was oriented vertically, giving access to reections of the form (h0l). The sample holder assembly was then m ounted inside the vacuum space of a high-temperature closed-cycle <sup>3</sup>H e refrigerator, which was subsequently positioned and xed onto the goniom eter of the BT9 spectrom eter.

## III. DIFFUSE SCATTERING

The PZN-8% PT phase E-T diagram has been m apped out by 0 hw ada et al., and is shown in Fig. 1.<sup>10</sup> The data presented in the top panel were taken while cooling in a constant electric eld, whereas those shown in the bottom panelwere taken with increasing eld at xed tem perature after rst cooling in zero eld. The electric eld acts to stabilize the tetragonal phase as can be seen from the slope of the tetragonal (T) to cubic (C) phase boundary in Fig. 1 (a), where the transition temperature increases eld. The transition tem peratures, represented by with the circles in Fig.1, were determ ined from measurements of the lattice constants (Bragg peaks). But while this relaxor com pound clearly exhibits a tetragonally-distorted structure, the precise nature of the polar order is still. unknown.

Im portant inform ation can be obtained about the polar order in the tetragonal phase of PZN-8% PT through m easurem ents of the di use scattering. Fig.2 show sneutron scattering m easurem ents taken by O hwada et al. (on a di erent PZN-8% PT single crystal, but grown using the same technique) near the (003) reciprocal lattice




FIG.1: The E T phase diagram of PZN-8% PT determ ined by O hwada et al.<sup>10</sup> The notations C, T, M, and R refer to cubic, tetragonal, m onoclinic, and rhom bohedral phases, respectively. The arrows point in the scan direction, while the length of the arrows correspond to the scan range. The circles denote the transition tem peratures determ ined from each scan.

position, for which the di use scattering structure factor is known to be strong.<sup>10</sup> The intensity at Q = (0.04,0,3)is shown as a function of temperature at E = 0 kV/cm(solid circles) and 3 kV/cm (open circles), with the eld applied along the [001] direction. In the cubic phase at high temperature (T 520K) the di use scattering intensities are equal, indicating no eld dependence. How – ever at low er temperatures, in the tetragonal phase, the di use scattering is strongly suppressed by the eld while the zero- eld di use scattering intensity remains strong and increases with cooling. For purposes of com parison, the integrated B ragg intensity measured at (002) in zero-

eld is shown (scale on the right-hand side of Fig.2). The B ragg intensity increases sharply below 500 K, which is consistent with the slope of the T-C phase boundary in Fig.1.

The data in Fig. 2 were obtained at a xed Q value at two di erent eld values. Information about the geom etry of the di use scattering is presented in Fig. 3,




FIG.2: Tem perature dependence of the neutron di use scattering at Q = (0.04,0,3) in zero eld (solid circles) and E = 3kV/cm // [001] (open circles). The zero-eld Bragg intensity measured at (002) is shown as a function of tem perature by the solid triangles. These data were taken by 0 hwada et al. on a di erent single crystal of PZN-8% PT.

which compares the di use scattering intensity measured at several di erent reciprocal lattice points at a xed eld strength of 2 kV /cm oriented along the [001] axis. The intensities measured around the (003) position (open circles) decrease upon cooling in eld in agreem ent with the data of Fig. 2. However the striking behavior revealed in this gure is the that the di use intensities measured around the orthogonal (300) position remain high, much like the zero- eld data shown in Fig. 2. The vertical arrows in this gure indicate the phase transition tem - peratures  $T_{\rm M}$  T and  $T_{\rm T}$  c between the monoclinic and tetragonal, and tetragonal and cubic phases, respectively.

To clarify this behavior wide scans were made of the scattered neutron intensity as a function of the reduced momentum transfer q transverse to both the (300) and (003) B ragg positions as a function of eld and temperature. The resulting data are plotted on a log-intensity scale in Fig. 4. The top two panels display transverse q-scans in zero eld, and the bottom two panels show the same scans taken after cooling the sample in a 2 kV/cm

eld. In the cubic phase at 500K we observe di use scattering of roughly equal intensity in zero eld along directions transverse to both Q = (300) and (003). This scattering does not change when an external electric eld of 2 kV /cm is applied along the [001] direction. In the tetragonal phase at 400K the di use scattering in zero eld increases slightly, becom ing som ew hat stronger around (003) com pared to (300). Then when the sam ple is eld cooled, the di use scattering transverse to (003) is reduced substantially, as is suggested by the data shown in Fig. 3. Rem arkably, how ever, the di use scattering transverse to (300) is una ected. This latter result indicates that the application of a 2 kV /cm eld is insu -




FIG.3: C om parison of the di use scattering intensities measured near (300) (solid sym bols) and (003) (open sym bols) as a function of tem perature in a eld of 2kV /cm applied along [001].

cient to produce a uniform polarization in the tetragonal phase. The dotted line in the lower left panel of F ig. 4 indicates the m easured instrum ental (G aussian) resolution function. Although data are not shown, the same behavior was observed at 300K in the m onoclinic phase of PZN-8% PT as in the tetragonal phase at 400K.

An e ort was made to determ ine the eld strength  $E_c$ at which the di use scattering transverse to (300) begins to decrease. Fig. 5 shows the di use scattering intensity m easured at Q = (3,0,-0.06) at 450 K, still in the tetragonalphase, from zero to 10 kV /cm . A llof these data were taken as a function of increasing electric eld strength after rst eld cooling from 520 K in a eld of 2 kV/cm except for the zero eld data point, which was obtained after zero- eld cooling. The solid and open circles are successive m easurem ents at the sam e tem perature and Q. The solid square shows the di use scattering intensity at 450K at E = 2 kV / cm. These data clearly reveal the inability of even a strong external electric eld to dim in ish the di use scattering orthogonal to the eld direction. Hence the underlying mechanism responsible for the di use scattering in PZN-8% PT must have an energy barrier that is su ciently large in order to stabilize it against external elds of at least 10 kV/cm.

### IV. DISCUSSION

The results on PZN-8% PT presented here are signi cant not because the di use scattering m easured transverse to (003) is suppressed by an external electric eld,




FIG. 4: A log-scale comparison of the di use scattering intensities measured transverse to the (300) (open circles) and (003) (solid circles) reciprocal lattice positions at 400 K (tetragonal phase) and 500 K (cubic phase). The top panels show data in zero eld, and the bottom panels show data in an electric eld of 2 kV /cm (bottom panels) applied along [001]. The dashed line in the lower left panel represents the instrum ental transverse q-resolution.




FIG. 5: Plot of the di use scattering intensity measured in the tetragonal phase at (3,0,-0.06) at  $450 \,\text{K}$  as a function of increasing eld strength applied along the [001] direction. The open and solid circles represent independent measurements. The solid square corresponds to the di use scattering intensity at  $2 \,\text{kV}$  /cm at (0.06,0,3) for comparison.

but rather because the di use scattering m easured transverse to (300) is not. Independent of any model, our data provide unam biguous evidence that the eld-induced polar state in this important relaxorm aterial is not m acroscopically uniform. This unusual nding must therefore be explained by any model that purports to address the fundam ental properties of these lead-oxide relaxor com pounds. W hile not unique, we believe that the concept of the phase-shifted polar nanoregions provides a natural explanation for the observed eld and Q -dependence of the di use scattering in PZN 8% PT. This phase shift, or uniform displacement, of the PNR occurs with respect to the surrounding cubic lattice at the Burns temperature  $T_{\rm d}$  where the PNR condense from the soft TO phonon mode (see the top panel in Fig. 6). This soft TO mode is in fact coupled to the TA mode as st shown by Naberezhnov et al., and later studied by W akimoto et al.<sup>3,14</sup> The uniform phase shift is believed to result from the fact that the soft TO mode is actually a soft-coupled mode that contains a signi cant transverse acoustic component, an idea originally proposed by Yam ada and Takakura.<sup>15</sup>

The results of our study can be explained quite sim ply on the basis of the shifted nature of the PNR, as illustrated by the three-panel schematic diagram shown in Fig. 6. In the top panel, the system is in the cubic phase, below the Burns tem perature. The white squares represent the non-polar regions of the lattice (note that these are not individual unit cells), while the PNR are shown as the red hatched regions (corresponding to som ething of the order of 10 unit cells), which are slightly displaced in di erent directions from the cubic lattice. The arrows represent the direction and size of the uniform shift, which occurs in the direction of the PNR polarization. In the tetragonal phase  $(T < T_c)$  the lattice develops its own polarization as indicated by the red dotted shading, while the uniform shift of the PNR remains intact (see the upper left panel of Fig. 4). Under the application of an external electric eld, the shifts antiparallel to E are rem oved, thereby reducing the local disorder, and in turn suppressing the di use scattering. (As it is unclear how much of the di use scattering transverse to the (003) reciprocal lattice position remains (see the lower left-hand panelofFig.4), we can only speculate that parallel shifts may be una ected.) But the orthogonal PNR shifts are una ected, and hence the corresponding di use scattering is also una ected. Thus a macroscopically ordered polar phase is not achieved in this system, even under applied electric eld strengths up to  $10 \, \text{kV} \, / \text{cm}$ .

Interesting high-q resolution studies in zero eld have now been performed by G ehring et al. on PMN-10% PT, and Xu et al. on PMN-20% PT and PMN-27% PT.<sup>12,16</sup> These studies have exam ined the low-tem perature phase in the PMN-xPT system, and docum ent the existence of phase X up to PbTiO<sub>3</sub> concentrations as high as 20%. The 27% sample nally exhibits the expected rhom bohedral phase. The stability of this new phase X against the formation of a global rhom bohedral polar phase at




FIG.6: Top panel: Phase-shifted PNR embedded in a nonpolar cubic lattice for  $T > T_c$ . Middle panel: Below  $T_c$  the lattice achieves a polarization of its own, but the phase shift remains. Bottom panel: An applied electric eld removes shifts along E, while preserving those that are orthogonal.

tem peratures below  $T_c$  can also be understood in term s of the phase-shifted PNR m odel. The latter study by X u et al. in particular demonstrates that phase X is both undistorted and rhom ohedrally polarized.

# V. ACKNOW LEDGMENTS

W e would like to thank R.Erwin, Y.Fujii, K.Hirota, C.Stock, and S.Wakim oto, for stimulating discussions, and P.W. Rehrig for supplying the high quality PZN-8% PT single crystal. W e acknow ledge nancial support from the U.S.Dept. of Energy under contract No.DE-AC 02-98C H 10886. W e also acknow ledge the U.S.Dept. of Commerce, NIST Center for Neutron Research, for providing the neutron scattering facilities used in this study.

- <sup>1</sup> G.Burns and F.H.Dacol, Solid State Commun. 48, 853 (1983); ibid, Phys. Rev. B 28, 2527 (1983).
- <sup>2</sup> S.E. Park and T.R. Shrout, J. Appl. Phys. 82, 1804 (1997).
- <sup>3</sup> A. Naberezhnov, S. B. Vakhrushev, B. Domer, and H. Moudden, Eur. Phys. J. B 11, 13 (1999).
- <sup>4</sup> J. Zhao, A. E. G lazounov, Q. M. Zhang, and B. Toby, Appl.Phys.Lett. 72, 1048 (1998).
- <sup>5</sup> P.M. Gehring, S.-E. Park, and G. Shirane, Phys. Rev. B 63, 224109 (2001).
- <sup>6</sup> P.M. Gehring, S.E. Park, and G. Shirane, Phys. Rev. Lett. 84, 5216 (2000).
- <sup>7</sup> K.Hirota, Z.-G.Ye, S.W akim oto, P.M.Gehring, and G. Shirane, Phys. Rev. B 65, 104105 (2002).
- <sup>8</sup> S.B.Vakhrushev, B.E.K vyatkovksy, A.A.N aberezhnov, N.M.Okuneva, and B.Toperverg, Ferroelectrics 90, 173 (1989).

- <sup>9</sup> J.Harada, J.D.Axe, and G.Shirane: Phys. Rev. B 4, 155 (1971).
- <sup>10</sup> K.Ohwada, K.Hirota, P.W. Rehrig, Y.Fujii, and G. Shirane, Phys.Rev.B 67, 094111 (2003).
- <sup>11</sup> G. Xu, Z. Zhong, Y. Bing, Z.-G. Ye, C. Stock, and G. Shirane, Phys. Rev. B 67, 104102 (2003).
- <sup>12</sup> P.M. Gehring, W. Chen, Z.-G. Ye, and G. Shirane, condmat/0304289.
- <sup>13</sup> M.-L. Mulvihill, S.-E. Park, G. Risch, Z. Li, K. Uchino, and T.-R. Shrout, Jpn. J. Appl. Phys. 35, 3984 (1996).
- <sup>14</sup> S.W akim oto, C.Stock, Z.-G.Ye, W.Chen, P.M.Gehring, and G.Shirane, Phys. Rev. B 66, 224102 (2002).
- <sup>15</sup> Y.Yam ada and T.Takakura, cond-m at/0209573.
- <sup>16</sup> G.Xu, D.Viehland, J.Li, P.M.Gehring, and G.Shirane, cond-m at/0307144.