Sharp-interface projection of a uctuating phase-eld model

R.Ben tez and L.Ram rez-Piscina Departament de F sica Aplicada, Universitat Politecnica de Catalunya, Doctor Maranon 44, E-08028 Barcelona, Spain. (Dated: April 14, 2024)

Abstract

We present a derivation of the sharp-interface limit of a generic uctuating phase-ekl model for solidi cation. As a main result, we obtain a sharp-interface projection which presents noise terms in both the di usion equation and in the moving boundary conditions. The presented procedure does not rely on the uctuation-dissipation theorem, and can therefore be applied to account for both internal and external uctuations in either variational or non-variational phaseeld formulations. In particular, it can be used to introduce therm odynam ical uctuations in non-variational formulations of the phase- eld model, which perm it to reach better computational e ciency and provide more exibility for describing some features of speci c physical situations. This opens the possibility of perform ing quantitative phase- eld simulations in crystal grow the while accounting for the proper uctuations of the system.

PACS num bers: 81.10 A j81.30 Fb,05.40.-a,68.08.-p,64.70 D v

I. IN TRODUCTION

In recent years, phase-eld models have emerged as an e cient technique to simulate interfacial phenomena in non-equilibrium systems [1]. This method has mainly been developed for solidi cation [2, 3, 4], but has also successfully been applied to other problems, such as grain boundaries [5], crack propagation [6], viscous ngering [7] or vesicle dynam ics [8]. The phase-eld approach introduces an equation for a continuous variable (r;t), which appears as an order parameter, and takes distinct, constant values in the di erent phases. The interface is then described by the level set = constant, and the transition between both phases takes place in a di use interface of thickness W . The model is completed by coupling the equation with a di usion eld which acts as a driving force for the motion of the front. The behavior of the di use interface can then be computed by the integration of a set of partial di erential equations for the whole system, therefore avoiding the explicit tracking of the interface position. This has practical advantages over using the free boundary conditions that are characteristic of a moving boundary description. Phase-eld models are usually constructed to recover the classical moving boundary dynamics in the so called sharp-interface lim it as W ! 0 [9]. This lim it is taken by means of a system atic asymptotic expansion on the interface width, and allows the model parameters to be determined in term s of the physical properties of the system .

In early phase- eld form ulations, the model equations were derived from the variational m inimization of a global free-energy functional for the heterogeneous system. Such variational form ulations, however, in spite of their appealing structure, presented poor computational e ciency and did not permit to obtain truly quantitative results. For this reason, recently proposed phase- eld models are not derived from a variational principle, but are speci cally constructed to recover a certain moving boundary problem in the sharp-interface limit [7, 10]. Besides presenting a better computational behavior, non-variational phase- eld form ulations provide for more exibility in the description of some particular features such as di erent transport properties in the solid and liquid phases [11, 12].

On the other hand, the presence of uctuations has always been an important issue in the study of pattern-form ing instabilities in crystal grow th [13, 14]. Indeed, internal or external noises play the role of an initiation mechanism for the morphological deformations of the interface [15, 16]. Thermal or solute uctuations, for instance, must be taken into account

2

in order to study important problem s such as the dynam ical selection of the primary spacing in directional solidi cation [16] or the form ation of secondary instabilities (sidebranches) in dendritic growth [17]. Fluctuations were soon introduced into phase- eld models in an ad hoc way as a controlled source of interfacial perturbations [18]. However, phase eld models accounting for internal therm odynam ical uctuations have not been proposed until recently, and in the context of variational formulations [19, 20, 21, 22]. In such variational cases, the statistical properties of the uctuating terms can straightforwardly be determined by using the uctuation-dissipation theorem, following the lines applied by Hohenberg and Halperin within the context of critical dynamics [23]. In non-variational formulations, how ever, the uctuation-dissipation relation becom es useless for this purpose because the dynam ics of the system cannot be derived from a single free-energy functional.

The aim of this work is to present a system atic procedure to account for the introduction of generic sources of noise in either variational or non-variational phase- eld models. To this end, we will perform the sharp-interface limit of a uctuating phase- eld model for solidication and explicitly obtain the properties of the projected noise terms that will appear in the moving boundary equations. This projection, which does not rely on the uctuationdissipation theorem, will be carried out by means of a hybrid asymptotic expansion which combines a standard sharp-interface limit with a small noise assumption for the intensities of the noise terms in the model. The structure of the resulting sharp-interface projection takes the form of a moving boundary problem, which now includes bulk and interfacial stochastic terms. The statistical properties of these new terms are related to those of the noises appearing in the starting phase- eld equations. The extension of our procedure to thin-interface asymptotics [4] is straightforward and is not presented here for the sake of clarity.

A s a particular case, this analytical technique will enable a prescription for the introduction of internal therm odynam ical uctuations in non-variational phase- eld models, subject only to the constraint of providing the correct interface equilibrium uctuations. This approach will also allow for the consideration of more general noise sources of an external origin, such as experimental in perfections or controlled perturbations, which do not follow equilibrium statistics. It is worth pointing out that while the calculations will be performed within the framework of the symmetric solidication model, the approach can be easily extended to one-sided formulations [12].

3

This work has been organized as follows: The stochastic model equations are presented in Sec. II. The asymptotic stochastic procedure is developed in Sec. III, which has been divided in four di erent subsections: Sec. IIIA and IIIB are dedicated to nd solutions of the equations in the inner and outer asymptotic regions, respectively. The solvability conditions for the inner expansion are in posed in Sec. IIIC, whereas in Sec. IIID we perform the asymptotic matching between the inner and outer stochastic elds in order to obtain the form of the projected equations. The projected problem is then compared in Sec. IV with the standard Lanvegin formulation for solidi cation [13, 14], allowing for the determ ination of the model parameters in the case of having internal noises of a therm odynamical origin. A num erical test for the validity of the approach is reported in Sec. V I is devoted to present som e discussion and concluding remarks.

II. MODELEQUATIONS

Our approach starts from a generic non-variational phase-eld model, which applies for both the solidi cation of a pure substance and for the symmetric solidi cation of a dilute alloy with a constant miscibility gap [4],

$$"^{2} \Theta_{t} = "^{2} r^{2} f^{0}() " g^{0}() u + "^{\frac{3}{2}}(r;t)$$
(2.1)

$$\theta_t u = r^2 u + \frac{1}{2} \theta_t h() r q(r;t);$$
(2.2)

where is a parameter determining the time scale of the phase-eld dynamics and accounts for the coupling strength between and the di usion eld $u \cdot W = chooseg()$ and h() to be odd polynomial functions of satisfying the limiting conditions $g^0(1) = 0$ and h(1) = 1, and f() to be given by the standard double-well potential

$$f() = \frac{1}{4} + \frac{1}{2} + \frac{1}{2}$$

In the model equations Eqs. (2.1), (2.2), u is a reduced di usive eld de ned by $u = (T - T_M) = (L=c)$ in the case of pure substances and by $u = (c - \frac{1}{2}(c_S^0 + c_L^0)) = c_0 + \frac{1}{2}g()$ for symmetric alloys, where T_M is the melting temperature, L the latent heat per unit volume, c the speci c heat per unit volume and $c_0 - c_L^0 - c_S^0$, being $c_S^0; c_L^0$ the solid and liquid equilibrium concentrations of the alloy, respectively. The two minim a = 1 of f() in Eq. (2.3) correspond respectively to the solid and liquid phases of the system, so the

interface will be represented by the transition zone between these two values. Space and times in Eqs. (2.1), (2.2) have been scaled out using a characteristic length 1 and a time scale = \hat{f} =D, where D is the therm alor chem icaldi usivity of the substance. The control parameter " = W =1 is the scaled interface thickness, and will be the sm all parameter in which the form alexpansions will be carried out.

F luctuations appear in the model as a non-conserved noise term in the equation for the phase-eld, and as a conserved stochastic current q in the di usion equation. These uctuations account for generic noise sources of either an internal or an external origin. W e assume that the noises are white and G aussian with correlations given by

h (r;t) $(r_{i}^{0};t^{0})i = 2^{2}$ (r r) (t t); (2.4)

$$hq_{i}(r;t)q_{j}(r^{0};t^{0})i = 2 \frac{2}{u} \frac{1}{ij} (r r^{0}) (t t^{0}): \qquad (2.5)$$

In the proposed phase eld model, parameters such as , , and the noise amplitudes , $_{\rm u}$, are intended to represent (or to be directly related to) physical parameters. On the contrary, the scaled interface width " has been introduced as an expansion parameter. As a matter of fact, Eqs. (2.1), (2.2) have been constructed so that the resulting dynamics (in the double limit of sharp interface and small noise) will be independent of ". In particular, the scaling factor ³⁼² of the the noise term in Eq. (2.1) has been introduced in order to make the uctuations of the interfacial dynamics, as will be obtained below, independent of

. The details of this calculation and the presentation of the results are given in the next section.

III. HYBRID ASYMPTOTIC EXPANSION

In order to deal with uctuating phase-eld models, the standard asymptotic expansion, performed in terms of a small interface thickness, should be complemented with a small noise assumption. The combination of these approaches will give rise to a hybrid asymptotic procedure. To this end, the small noise assumption will be imposed by assuming that ; u obey some order relations with the interface thickness ". Namely, we take

$$_{\rm u}$$
 O ("²); (3.2)

which will perm it along the expansion procedure to maintain the uctuating terms as small perturbations at the desired order in a consistent way. Relations (3.1), (3.2) should not be understood as any explicit dependence of these parameters on ", but only as a way to form alize a double expansion in term s of a single vanishing parameter, the interface thickness, "! 0.

O urm ethod closely follows the standard asymptotic procedure described in R ef. [11]. We start by dividing the system into two di erent regions: an outer region far from the interface at distances much greater than ", where the phase eld presents the two constant values

= 1 representing the solid and liquid phases at each side of the interface, and an inner region located around the interface up to distances of order ", where the phase eld varies between these two values. In the limit "! 0, solutions for the elds in both regions should m atch order by order in " at some intermediate distance r_M , which can be taken of order r_M "¹⁼².

A. Outer region

In the outer region, the equations can be solved at each order by expanding the elds in powers of " as

$$u = u_0 + "u_1 + "^2 u_2 + O ("^3);$$
(3.3)

$$= {}_{0} + {}^{"}{}_{1} + {}^{"^{2}}{}_{2} + O ({}^{"^{3}});$$
(3.4)

and by expanding in Taylor series around $= _0$ the functions f;g appearing in the model equations. If we use the order relations Eqs. (3.1), (3.2), the noise term s can be assumed to be of orders

$$O(1^{\beta=2});$$
 (3.5)

$$q = O(\mathbf{m}^2);$$
 (3.6)

and the outer equations can then be obtained at each order in ".

1. Zero Order

At the leading order $({\tt "}^0)$, the outer equations are given by

$$f^{0}(_{0}) = 0; (3.7)$$

$$Q_t u_0 = r^2 u_0 + \frac{1}{2} Q_t h(_0)$$
: (3.8)

Introducing the function f () into Eq. (3.7), we obtain $_0 = 1$, and using that h (1) = 1, Eq. (3.8) adopts the form

$$\theta_t u_0 = r^2 u_0$$
(3.9)

2. First Order

At rstorder in ", we nd

$$f^{0}(_{0})_{1} = g^{0}(_{0})u_{0}; \qquad (3.10)$$

$$Q_t u_1 = r^2 u_1 + \frac{1}{2} Q_t [_1 h (_0)]:$$
 (3.11)

From Eq. (3.10) we determ ine $_1 = 0$ by noting that the functions f, g satisfy $f^{(0)}(1) \notin 0$ and $g^0(1) = 0$, and introducing $_1 = 0$ into Eq. (3.11) we get

$$\theta_t u_1 = r^2 u_1$$
(3.12)

3. Second Order

At second order ("²), and using that $_1 = 0$, the random current q appears in the equation for the outer di usive eld

$$f^{(0)}(_{0})_{2} = g^{(0)}(_{0})u_{1}; \qquad (3.13)$$

$$\varrho_{t}u_{2} = r^{2}u_{2} + \frac{1}{2}\varrho_{t}[h^{0}(_{0})_{2}] \quad r \quad q:$$
(3.14)

U sing that $g^0(1) = 0$ and $f^0(1) \notin 0$, equation (3.13) is solved by $_2 = 0$, and the second term at the right hand side of Eq. (3.14) can be neglected. Collecting the results obtained at the three rst orders, the outer elds are given, up to second order in ", by

$$= 1 + 0 ("^{3}); (3.15)$$

$$Q_t u = r^2 u r q(r;t) + O(i'):$$
(3.16)

B. Inner region

For the inner region, we write Eqs. (2.1), (2.2) in a curvilinear coordinate system centered at the interface. The idea is that the solvability condition for the very existence of solutions of these transformed equations will provide the evolution of the coordinate system, i.e. of the interface, which in fact constitutes the solution we are looking for. To de ne this coordinate system by maintaining it smooth at small scales, we use an auxiliary coarse grained eld de ned as a local spatial and tem poral average of the uctuating eld

. The surface corresponding to the level set of this coarse grained eld h (r;t)i = 0 allows to de ne the 3D orthogonal curvilinear coordinate system (r;s₁;s₂), where r is a norm all distance from the surface and s_1 , s_2 are the arclength distances measured along the principal curvature directions of the surface. Furtherm ore, we introduce in the inner region the scaled norm all coordinate = r=" and the scaled time = t=". We use capital letters to refer to all the elds when written in the inner region. A fler some manipulation, and keeping terms up to second order in ", we obtain the inner equations in the frame of the moving interface

$$\frac{1}{"}\begin{bmatrix}\frac{d}{d} & v@ \end{bmatrix}U = \frac{1}{"2}@^{2}U + \frac{1}{"}\begin{bmatrix} & " & (^{2} & 2)\end{bmatrix}@ U \\ + & X \\ & \sum_{i=1,2} @^{2}_{S_{i}}U & \frac{v}{2"}@ h() + \frac{1}{2"}\frac{dh()}{d} & \frac{1}{"2}@ Q (;s;); \end{bmatrix}$$
(3.18)

where v = v(s;) is the local norm all velocity of the interface, and we have introduced = $_1 + _2$ and = $_1 _2$ as the mean and Gaussian curvatures of the surface, being $_1(s;), _2(s;)$ its principal curvatures.

The uctuating functions H (;s;) = " (r;t) and Q (;s;) = "q(r;t) in Eqs. (3.17), (3.18) stand for the renorm alized noises in the inner region, and Q corresponds to the norm al component of the stochastic current Q. The correlations of these noise terms are given by

hH (;s;)H (
0
;s 0 ; 0)i = 2² (0) (s s) (0); (3.19)

$$hQ_{i}(;s;)Q_{j}(^{0};s^{0};^{0})i = 2^{2}_{uij}(^{0})(ss^{0})(^{0}); \qquad (3.20)$$

so that the orders in "of H (;s;) and Q (;s;) are those of and _u respectively. Note that the renorm alization of the noise term s is a direct consequence of the scaling of the t;r coordinates in the inner region. Indeed, noise term s give rise to an factor when written in the inner region due to the rescaling in both tim e and norm aldistances of the delta functions

() = " (r) and () = " (t).

Now we can see how the small noise assumption has been in plemented in our approach. With the choice given by Eqs. (3.1), (3.2) for the orders in "of the noise am plitudes, " ^{1+2}H is O ("²) in Eq. (3.17) and "²@Q is O ("⁰) in Eq. (3.18), i.e. one order higher than the temporal derivatives in these equations. In other words, both noise terms are rst order perturbations for the dynamics in their respective inner equations.

At this point, we proceed as in the outer region by expanding the inner elds and param eters in powers of "

$$U = U_0 + "U_1 + "^2U_2 + O ("^3); \qquad (3.21)$$

$$= _{0} + "_{1} + "^{2}_{2} + O ("^{3}); \qquad (3.22)$$

$$i = i_0 + "i_1 + 0 ("^2); i = 1;2$$
 (3.23)

$$= _{0} + "_{1} + O ("^{2}); \qquad (3.24)$$

$$v = v_0 + "v_1 + O("^2);$$
 (3.25)

and inserting the expansions into the inner equations Eqs. (3.17), (3.18). The inner solutions will be obtained by m atching with the outer solutions for ! 1 and r ! 0, respectively. In the phase eld equations, direct m atching with the outer $_{i}$ solutions Eq. (3.15) provides the limiting boundary conditions for the $_{i}$ term s of the inner expansion

$$_{0}(! 1) = 1;$$
 (3.26)

$$_{i}(! 1) = 0; \text{ for } i = 1;2:$$
 (3.27)

Sim ilarly, the matching condition for the inner di usion eld requires that, at leading order, the gradients of U_0 vanish

$$\lim_{i \to 1} 0 U_0 = 0:$$
(3.28)

At higher orders, the matching conditions for the discussed in detail in Sec. IIID.

1. Zero order

At leading order (" 0 for the equation, " 2 for the U equation), the inner equations are given by

$$Q^2 U_0 = 0: (3.30)$$

Inserting the double-well potential Eq. (2.3) into Eq. (3.29), we obtain the standard kink solution for the phase- eld at zero-order

$$_{0}() = \tanh \frac{p_{-}}{2};$$
 (3.31)

which satis es the matching condition Eq. (3.26) for ! 1. Integrating Eq. (3.30) twice over , we have

$$U_0(;s;) = A(s;) + B(s;);$$
 (3.32)

where A and B are integration constants. In posing the matching condition Eq. (3.28), we determ in B (s;) = 0 and obtain a -independent solution for the dision eld at zero order

$$U_0(s;) = A(s;):$$
 (3.33)

2. First Order

U sing the solutions obtained at zero-order, the rst-order inner equations ("1 for the equation, "1 for the U equation) read

$$_{1} = (v_{0} + _{0})@_{0} + g^{0}(_{0})U_{0}; \qquad (3.34)$$

$$Q^{2}U_{1} = \frac{dU_{0}}{d} + \frac{v_{0}}{2}Q h(_{0}); \qquad (3.35)$$

where is the self-adjoint operator $Q^2 = f^{(0)}(_0)$ and we have used that $d_0 = d = 0$ from Eq. (3.31). As described by A in gren [11], an expression for $_1$ can be obtained from

Eq. (3.34) by inverting the operator , leading to

$$_{1} = {}^{1} [(v_{0} + {}_{0})@ {}_{0} + g^{0}({}_{0})U_{0}]:$$
 (3.36)

Since is an even operator and $(0, g^0(0))$ are even functions of (1, 1) is an even function of . Integrating Eq. (3.35) twice over (1, 1), we get

$$U_{1} = D (s;) + C (s;) + \frac{v_{0}}{2} \int_{0}^{Z} d^{0}h(_{0}) + \frac{1}{2} \frac{dU_{0}}{d}^{2}; \qquad (3.37)$$

where D and C are integration constants and we have used that $(U_0 = 0 \text{ (cf. Eq. (3.33))})$.

3. Second order

The stochastic terms appear in the inner equations at second order ($"^2$ for the equation, "⁰ for the U equation), which are given by

$${}_{2} = (v_{1} + {}_{1})@ {}_{0} (v_{0} + {}_{0})@ {}_{1} + \frac{d}{d}$$

$$+ \frac{1}{2}f^{00}({}_{0}){}_{1}^{2} + ({}_{0}^{2} 2 {}_{0})@ {}_{0}$$

$$+ g^{0}({}_{0})U_{1} + g^{0}({}_{0}){}_{1}U_{0} "^{3=2}H;$$
(3.38)

$$\begin{aligned} \theta^{2} U_{2} &= (v_{0} + {}_{0}) \theta U_{1} + \frac{dU_{1}}{d} + \frac{v_{1}}{2} \theta h({}_{0}) + \frac{v_{0}}{2} \theta [h^{0}({}_{0}) {}_{1}] \\ & X \\ & \theta_{s_{1}}^{2} U_{0} - \frac{1}{2} h^{0}({}_{0}) \frac{d}{d} + \frac{1}{2} \theta Q : \end{aligned}$$
(3.39)

The rst equation Eq. (3.38) will be used in the next section when imposing the second order solvability condition of the problem. Integrating Eq. (3.39) twice over , we nd

7

where F and E are again -independent integration constants.

C. Solvability conditions

We impose now the solvability conditions for the inner problem, which at rst and second orders are respectively given by

$$Z_{1}$$

(@ ₀) _jd = 0; for j = 1;2: (3.41)

Inserting Eq. (3.34) into the rst order solvability condition, we get

7

$$(v_0 + _0)I_1 = I_2U_0 = 0;$$
 (3.42)

which allows to determ ine U_0 as

$$U_{0}(s;) = \frac{I_{1}}{I_{2}}v_{0} \frac{I_{1}}{I_{2}} {}_{0};$$
 (3.43)

where I_1 and I_2 are new integral constants given by

$$I_{1} = \begin{pmatrix} 2 & 1 \\ 1 & 0 \end{pmatrix}^{2}; \qquad (3.44)$$

$$I_{2} = \int_{1}^{-1} d g^{0}(_{0}) (@_{0}): \qquad (3.45)$$

In posing the second order solvability condition Eq. (3.41), and taking into account the parity of the potentials f;g;h and of the inner solutions $_{0}$; $_{1}$, we determ ine an expression for the constant D in Eq. (3.37)

D (s;) =
$$(v_1 + 1) \frac{I_1}{I_2} + v_0 \frac{I_3}{2I_2} + \frac{I_4}{2I_2} + \frac{I_5}{I_2} = \frac{3}{I_2} \frac{Z(s;)}{I_2};$$
 (3.46)

where I_3 , I_4 and I_5 are de ned by

$$I_{3} = \begin{array}{c} Z_{1} & Z \\ d_{0} & Q_{0} & Q_{0} \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & & \\ & & & & \\ & & & & & \\ & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & \\ & & & & & \\ & & & & & \\ &$$

$$I_{4} = \frac{dU_{0}}{Z_{1}} \int_{1}^{1} d (0) g^{0}(0)^{2}; \qquad (3.48)$$

$$I_{5} = \int_{1}^{1} d (0 _{0}) \frac{d_{1}}{d}; \qquad (3.49)$$

and Z is a stochastic term given by

$$Z (s;) = d (@ _{0}) H (;s;); \qquad (3.50)$$

whose statistical properties are given by

hZ (s;)Z (
$$\hat{s}; \hat{}^{0}$$
) $i = 2I_{1}^{2}$ (s \hat{s}) ($\hat{}^{0}$): (3.51)

D. Matching of uctuating elds

At this point, we continue by in posing the remaining asymptotic matching conditions of the problem. However, the matching of the di usion eld presents some subtleties due to its uctuating character. The main problem is that, at second order in ", the U eld uctuates in the normal direction (cf. Eq. (3.40)), and hence cannot be written as a simple asymptotic expansion for ! 1, preventing the matching with the outer eld. This di culty can be overcome by introducing an auxiliary matching function de ned in both regions as $\frac{Z}{2}$.

$$(r;s;t) = u(r;s;t) \int_{t}^{t} dr^{0}q_{r}(r^{0};s^{0};t);$$
 (3.52)

X (;s;) = U (;s;)
$$d^{0}Q$$
 (⁰;s;): (3.53)

In view of Eq. (3.40), it is easy to see that the inner auxiliary function X introduced in Eq. (3.53) is smooth up to order "² in the matching region r_M . Explicitly, if X is asymptotically expanded for ! 1 as

$$X T + S + R^{2} + O(^{3}); \qquad (3.54)$$

and the outer m atching function is expanded in Taylor around r = 0 by

$$(0) + \theta_{r} (0) r + \frac{1}{2} \theta_{r}^{2} (0) r + 0 (r^{3});$$
 (3.55)

the inner and outer term s can be matched at r_M "¹⁼² in the limit"! O to obtain the matching relations

$$T = (0);$$
 (3.56)

$$S = "Q_r (0);$$
 (3.57)

$$R = \frac{\pi^2}{2} \theta_r^2 \quad (0): \qquad (3.58)$$

The last step is to expand the previous Equations (3.56), (3.57) and (3.58) in powers of "to complete the matching at each order in ".

1. First Order

At rst order in ", the inner eld U_1 given by Eq. (3.37) can be asymptotically expanded for ! 1 as

$$U_{1} = \frac{1}{2} \frac{dU_{0}}{d}^{2} + C = \frac{v_{0}}{2} + D + \frac{v_{0}}{2} J_{1}; \qquad (3.59)$$

where D is given by Eq. (3.46) and

$$J_{1} = \int_{0}^{Z_{1}} d[h(_{0}()) 1]; \qquad (3.60)$$

where we have used that h satisfies h(1) = 1 and the far eld condition Eq. (3.26). Since h($_0$) is an odd function of , we have

$$J_1^+ = J_1 \qquad J_1$$
: (3.61)

2. Second Order

Similarly, the second order inner solution for the di usive eld Eq. (3.40) can be expanded asymptotically for ! 1 as

$$U_{2} F + E (v_{0} + {}_{0}) d^{0} \frac{dU_{1}}{d} + {}_{0} d^{0} d^{0} \frac{dU_{1}}{d}$$

$$= \frac{1}{2} Q_{s}^{2} U_{0}^{2} d^{0} d^{0} d^{0} h^{0} ({}_{0}) \frac{d}{d}$$

$$= \frac{1}{2} Q_{s}^{2} U_{0}^{2} d^{0} d^{0} d^{0} h^{0} ({}_{0}) \frac{d}{d}$$

$$= \frac{1}{2} Q_{s}^{2} U_{0}^{2} d^{0} d^{0} d^{0} d^{0} h^{0} ({}_{0}) \frac{d}{d}$$

$$= \frac{1}{2} Q_{s}^{2} U_{0}^{2} d^{0} d$$

where

$$J_{2} = \int_{0}^{Z} d^{0}h^{0}(_{0})_{1}; \qquad (3.63)$$

and we have used the far eld conditions Eqs. (3.26) and (3.27). Inserting the expressions Eqs. (3.43), (3.59) and (3.62) into the right hand side of Eq. (3.53), we can determ ine the parameters R; S and T in the far eld expansion of the matching function X (cf. Eq. (3.54)) and perform the matching with the outer function (cf. Eq. (3.55)).

Im posing the third m atching condition Eq. (3.58) at rst order in ", we determ ine that

$$\frac{dU_0}{d} = 0; (3.64)$$

which, using the relation Eq. (3.36), brings to

$$\frac{d_{1}}{d} = 0;$$
 (3.65)

and therefore the integral constants I_4 and I_5 de ned in Eqs. (3.48), (3.49) vanish

$$I_4 = I_5 = 0$$
: (3.66)

From the two rst orders of Eq. (3.56), we get an expression for the outer di usive eld at the interface valid up to rst order

$$u(0) = \frac{I_1}{I_2}(v+) + \frac{"v_0}{2}(\frac{I_3}{I_2} + J_1) - \frac{z(s;t)}{I_2} + O("^2); \qquad (3.67)$$

where z(s;t) = Z(s;)¹⁼² is a stochastic term whose statistical properties can be determined from Eq. (3.51) and are given by

Note that the projected interfacial noise term has neither in Eq. (3.67) nor in Eq. (3.68) any explicit dependence in ", which is a direct consequence of the "³⁼² factor introduced in the noise term of Eq. (2.1). Indeed, this is the reason why such factor was introduced in the formulation of the model.

The calculation is completed by imposing the matching condition Eq. (3.57) up to second order, which can be written as

$$v_0 + "v_1 = \theta_r \ \dot{j} + O ("^2)$$
: (3.69)

Inserting Eq. (3.52) into Eq. (3.69), we get a heat/m ass conservation equation valid up to rst order in ",

$$v = v_0 + "v_1 = [Q_r u]_+ [Q_r]_+ + O("^2);$$
 (3.70)

where q_r accounts for a norm all stochastic current across the interface. This term, although being of order "², has not been neglected in Eq. (3.70) in order to not break m ass conservation in the stochastic di usion equation Eq. (3.16), which is valid up to second order.

This last equation completes the sharp-interface projection of the stochastic phase-eld m odel of Eqs. (2.1)-(2.5). This projection constitutes the main result of this paper, and is given by the di usion equation Eq. (3.16), with the noise of Eq. (2.5), supplemented with two moving boundary conditions at the interface: the conservation condition Eq. (3.70), and the G ibbs-Thom son Eq. (3.67), where a new projected interfacial noise appears with correlation given by Eq. (3.68). Note that the projected boundary conditions at the interface Eqs. (3.70), (3.67) are obtained at the order in mediately lower than the order at which the asymptotic expansion is performed.

W hile the general lines of the calculation follow the standard sharp-interface asym ptotics, we have included the uctuation terms during all the procedure, which have been projected

in the weak noise lim it. This calculation is thus sim ilar to the front dynam ics projection perform ed in Ref. [24]. Indeed, the projected interfacial noise appearing in Eq. (3.67) is the analogous counterpart of the noise term of the projected eikonal front equation of Ref. [24].

IV. INTERNAL FLUCTUATIONS IN A GENERIC PHASE FIELD MODEL

Thus far, the noises considered in this work are intended to account for both external and internal sources of uctuations. Nevertheless, it is worth pointing out that the resulting stochastic sharp-interface equations are sim ilar to those postulated in the Langevin form ulation of solidi cation due to K arm a [13, 14] (see also R ef. [25]), which was constructed to follow equilibrium statistics. This o ers the possibility of using the results above to provide generic (not necessarily variational) phase- eld m odels with the correct equilibrium uctuations. To illustrate this, let us consider the Langevin sharp-interface equations [13, 14]

$$v_{SI} = [e_r u_{SI}]_{+} [q_r^{SI}]_{+};$$
 (4.2)

$$u_{SI}(0) = d_0 \qquad v + (r;t);$$
 (4.3)

where q^{SI} and are uctuating term s with correlations given by

$$hq_{i}^{SI}(r;t)q_{j}^{SI}(r^{0};t^{0})i = \frac{2K_{B}T_{M}^{2}c}{L^{2}t^{d}} i (r r^{0}) (t t^{0}); \qquad (4.4)$$

h (s;t)
$$(\overset{0}{s};t^{0})i = \frac{2K_{B}T_{M}^{2}c}{L^{2}t^{d}}$$
 (s $\overset{0}{s}$) (t $\overset{0}{t}$): (4.5)

The G ibbs-Thom pson equation Eq. (4.3) can be compared with Eq. (3.67) and the di usion equation Eq. (4.1) with Eq. (3.16). This comparison enables the determination of the phaseeld parameters in terms of physical and substance parameters, which are given by the equations

$$= \frac{I_1}{I_2 d_0}; \qquad (4.6)$$

$$= \frac{1}{d_0}; \qquad (4.7)$$

$${}_{u}^{2} = \frac{K_{B} T_{M}^{2} c}{L^{2} I^{d}}; \qquad (4.8)$$

$${}^{2} = \frac{I_{1}K_{B}T_{M}^{2}c}{d_{0}^{2}L^{2}L^{d}};$$
(4.9)

In the last relations, the two rst equations Eqs. (4.6), (4.7) are the usual expressions determ ined by the standard asymptotic procedure, whereas Eq. (4.8) rejects the identification between the conserved stochastic currents of both phase eld model and sharp interface projection. In this sense, a major result of our approach has been the derivation of an expression for the noise strength of the phase-eld, that is Eq. (4.9), from the above calculations.

W ith this election of the model parameters, the phase-eld simulations will present the correct equilibrium statistics in the limit of small interface thickness "! 0. Therefore, the non-variational phase-eld formulation of Eqs. (2.1), (2.2) can be used to quantitatively account for therm odynamical uctuations in solidication processes.

V. TEST OF THE APPROACH

In order to test the validity of our approach, we have perform ed 2D phase- eld simulations to obtain the power spectrum of the interfacial uctuations of a solid-liquid stationary at interface. Introducing the Fourier transform of the interface position (r;t) as $_{k}(t) = R^{R}$ dk $(r;t) e^{ikr}$, the power spectrum of a stationary planar front in scaled variables is given by

$$S(k) = h_{k} \quad ki = \frac{Z}{2} \frac{dk^{0}}{2} h_{k} \quad k^{0}i = \frac{K_{B}T_{M}}{k^{2}} \frac{1}{k^{2}};$$
 (5.1)

where = $fL^2d_0=T_M$ c is the scaled interfacial surface energy. In the simulations, space and times have been scaled using length and time scales of $l = 10^8$ m and $= 9 \ 10^{10}$ s, respectively. The functions h;g have been chosen to be h() = and g^0 () = $(1 \ 2)^2$ so that the model does not have a variational structure. The substance parameters used in the simulations correspond to the values of the pure SCN in the 3D case, and are given by $d_0 = 0.2817$, = 3.0331 [26, 27] and $\frac{2}{u} = 0.001432$. For this choice, and using Eqs. (4.6)-(4.9), the phase- eld parameters take the values = 3.13, = 10.76 and $^2 = 0.05158$. The interface thickness has been taken to be " = 0.3.

The simulations have been in plemented with a nite di erences scheme on a 50 512 lattice with x = y = 0.2 and t = 0.005. We have used the initial conditions $(x;y;0) = \tanh(x="2")$, u(x;y;0) = 0. Non-ux and periodic boundary conditions have been in posed in the x and y directions respectively.

The num erical in plem entation of the stochastic term shas been carried out by generating



FIG.1: C on parison between the theoretical power spectrum of the stationary interface and the results from the phase-eld simulations.

G aussian-distributed random numbers at each of the lattice sites. The correlations of these numbers can be determined by discretizing the time and spatial delta functions in Eqs. (2.4), (2.5) by substituting $(x \ x^0) \ ! \ _{ii^0} = x$ and $(t \ t^0) \ ! \ _{nn^0} = t$. The divergence of the stochastic current in Eq. (2.2) has been discretized by using a forward di erences scheme $r \ q(r;t)_{ij} = (q_x(i+1;j) \ q_x(i;j)) = x + (q_y(i;j+1) \ q_y(i;j)) = y$.

The power spectrum statistics has been obtained as a time average among the last 3 10^6 time steps in a long-term simulation of 3.5 10^6 steps, and is represented by a dashed line in Fig. 1. The solid line in Fig. 1 depicts the theoretical prediction given by Eq. (5.1) and, as it can be seen, an excellent agreement is found between theoretical and numerical results. The vertical dashed line in the gure represents the wavelength associated with the elective thickness of the interface, and determines the expected breakdown of the phase-eld description.

VI. DISCUSSION AND CONCLUSIONS

To sum m arize, we have obtained an asymptotic projection of the uctuating phase-eld equations (2.1), (2.2) to a sharp interface description. This has been worked out by m eans of a hybrid asymptotic procedure, combining sharp interface and sm all noise limits. As a result, the projected equations adopt the form of a moving boundary problem with a conserved stochastic force q in the equations for the di usion eld Eqs. (3.16) and (3.70), and an interfacial noise z(s;t) in the G ibbs-Thompson condition Eq. (3.67). O ther authors have previously introduced uctuations in phase-eld models [20, 21, 22], but their approaches applied only for the case of variational formulations and were restricted to noises from a therm odynamical origin.

In this context, it has been claimed [20] that the presence of a non-conserved noise such in the equation for the phase eld is not relevant for the dynamics of the phase eld as model, and thus could be omitted in simulations. In order to check the importance of the non-conserved phase eld noise, we have carried out a num erical test with the same parameters reported in section V but taking = 0. In this case, the power spectrum is plotted as a dotted line in Fig. 1. The clear disagreem ent with both the theoretical prediction and the simulations of the complete model indicates that the phase eld noise is indeed necessary in order to obtain quantitative results. This can be explained by noting that Eq. (3.67) establishes a direct relation between the non-conserved phase- eld noise and the interfacial uctuations appearing in the G ibbs-Thompson equation, usually associated to kinetic attachment e ects [13]. Thus, the small signi cance of the noise reported in Ref. [20] is probably due to the fact that the stationary power spectrum was calculated in the limit of vanishing kinetics = 0. Therefore, we conclude that, in the presence of kinetic e ects, the phase eld noise is relevant for a quantitative description of the solidi cation process.

It is interesting to discuss the scaling of the noise term s as proposed on the one hand in Eqs. (3.1), (3.2) and on the other hand in the "³⁻² factor explicitly appearing in the equation for the phase eld, Eq. (2.1). A s it has already been commented, the assumption of the order relations Eqs. (3.1), (3.2) has permitted to manage a double expansion (sharp interface and sm all noise) by form ally using a single sm all parameter. The speci c powers of " appearing in these relations have been chosen for maintaining uctuations as sm all perturbations for the dynamics of both inner and outer equations. On the contrary, the multiplicative factor of the noise term of the equation for the phase eld, Eq. (2.1), has a di erent motivation. It is well known that there are problems in the form ulation of stochastic eld equations when the noise term s are delta-correlated in space. I such cases, som e kind of regularization is required. In Ref. [24], for instance, this regularization was provided by the correlation length of the noise, in such a way that the results did depend on that parameter. In the present case, the regularization is provided by the interface width ". The projection of the bulk

19

noise into the interface gives a uctuation term that in principle should diverge as goes to zero. The $^{3=2}$ factor of the noise term in Eq. (2.1) exactly cancels out this divergence, and has been introduced in the formulation of the model precisely to make results independent of , speci cally regarding the new interfacial noise term z in Eqs. (3.67), (3.68).

In conclusion, we have proposed an asymptotic procedure to obtain the sharp-interface projection of a generic (not necessarily variational) phase-ekl model with uctuations. We have tested the validity of our approach by comparing the phase-ekl results with the theoretical prediction for the interfacial uctuations in a simple solidi cation problem. This procedure can be useful both in situations where the uctuation-dissipation theorem does not hold, such as in presence of external uctuations, and when the phase- ekl model has a non-variational nature. An important example of this latter case corresponds to e cient phase- ekl models for the solidi cation of alloys [4, 12], which with our method can incorporate internal uctuations. The availability of these models for quantitative simulations in the uctuating case appears as a promising step towards the study of complex situations such as the apparition of dendritic sidebranching or the wavelength selection during initial redistribution transients in the directional solidi cation of alloys [28, 29].

VII. ACKNOW LEDGMENTS

This work was nancially supported by Direccion General de Investigacion Cient ca y Tecnica (Spain) (Project BFM 2003-07850-C 03-02) and Com issionat per a Universitats i Recerca (Spain) (Project 2001/SGR/00221). We also acknow ledge computing support from Fundacio Catalana per a la Recerca through C4 and CESCA (Spain).

- [1] R. Gonzalez-Cinca, R. Folch, R. Ben tez, L. Ram rez-Piscina, J. Casademunt, and A. Hernandez-Machado, in Advances in Condensed Matter and Statistical Mechanics, edited by E. Korutcheva and R. Cuerno (Nova Science Publishers, 2004), pp. 203{236, (condmat/0305058).
- [2] A.A.W heeler, W.J.Boettinger, and G.B.McFadden, Phys. Rev. A 45, 7424 (1992).
- [3] A.A.W heeler, W.J.Boettinger, and G.B.McFadden, Phys. Rev. E 47, 1893 (1992).
- [4] A.Kamma and W.J.Rappel, Phys. Rev. E 57, 4323 (1998).

- [5] J.A.Warren, R.Kobayashi, A.E.Lobkovsky, and W.C.Carter, Acta Materialia 51, 6035 (2003).
- [6] I.S.Aranson, V.A.Kalatsky, and V.M.Vinokur, Phys. Rev. Lett. 85, 118 (2000).
- [7] R.Folch, J.Casademunt, A.Hemandez-Machado, and L.Ram rez-Piscina, Phys.Rev.E 60, 1724 (1999).
- [8] T.Biben and C.Misbah, Phys. Rev. E 67, 031908 (2003).
- [9] G.Caginalp and P.Fife, SIAM J.Appl.Math. 48, 506 (1988).
- [10] K.R.Elder, M.Grant, N.Provatas, and J.M.Kosterlitz, Phys.Rev.E 64, 021604 (2001).
- [11] R.F.Alm gren, SIAM J.Appl.Math. 59, 2086 (1999).
- [12] A.Kama, Phys. Rev. Lett. 87, 115701 (2001).
- [13] A.Kamma, Phys.Rev.E 48, 3441 (1993).
- [14] A.Kama, Phys.Rev.Lett. 70, 3439 (1993).
- [15] J.A.W arren and J.S.Langer, Phys. Rev. A 42, 3518 (1990).
- [16] J.A.W arren and J.S.Langer, Phys. Rev. A 47, 2702 (1993).
- [17] J.Langer, Phys. Rev. A 36, 3350 (1987).
- [18] R.Kobayashi, Physica D 63, 410 (1993).
- [19] K.R.Elder, F.D rolet, J.M. Kosterlitz, and M. Grant, Phys. Rev. Lett. 72, 677 (1994).
- [20] A.Kamma and W.J.Rappel, Phys.Rev.E 60, 3614 (1999).
- [21] S.G. Pavlik and R.F. Sekerka, Physica A 268, 283 (1999).
- [22] S.G. Pavlik and R.F. Sekerka, Physica A 277, 415 (2000).
- [23] P.C. Hohenberg and B.I. Halperin, Rev. Mod. Phys. 49, 435 (1977).
- [24] A.Rocco, L.Ram rez-Piscina, and J.Casadem unt, Phys. Rev. E 65, 056116 (2002).
- [25] T.A.Cherepanova, Sov.Phys.Dokl.21,109 (1976).
- [26] A.Chemov, J.CrystalG row th 264, 499 (2004).
- [27] M. Aziz and W. Boettinger, Acta Metall. Mater. 42, 527 (1994), the value of has been determined by assuming a dision-limited kinetic attachment $\sim = v^d L = R T_M^2$, where $v^d = D = d_0$, being D the thermaldisistic and d_0 the capillary length, written in physical units.
- [28] R.Ben tez and L.Ram rez-Piscina, Fluct. Noise Lett. 4, L505 (2004).
- [29] R.Ben tez and L.Ram rez-Piscina, in preparation.