## Load distribution in smallworld networks

M. diBernardo, F. Garofalo, S. Manfredi, F. Sorrentino <sup>y</sup> Faculty of Engineering, University Federico II, Naples, Italy

### Abstract

In this paper we introduce a new model of data packet transport, based on a stochastic approach with the aim of characterizing the load distribution on com – plex networks. Moreover we analyze the load standard deviation as an index of uniform ity of the distribution of packets within the network, to characterize the e ects of the network topology. We measure such index on the model proposed by W atts and Strogatz as the redirection probability is increased. We

nd that the uniform ity of the load spread is maxim ized in the interm ediate region, at which the sm all world e ect is observed and both global and local ef-

ciency are high. M oreover we analyze the relationship between load centrality and degree centrality as an approximate measure of the load at the edges. A nalogous results are obtained for the load variance computed at the edges as well as at the vertices.

### 1 Introduction

Congestion in real networks is a complex phenomenon that depends on a large number of variables. Here we are interested in understanding how the underlying structure of the network can itself have an in uence on congestion. The network is supposed to be crossed by information units or packets. W e will consider a packet transport model on a given graph and will study the e ects of changes in the graph topology on the packets distribution. W ith the aim of understanding the e ects of the network topology on congestion, we will keep constant other

variables as the rate at which packets are generated, the distribution of sources and destinations within the network, and the routing algorithm to go from the former to the latter. We will show that each vertex can draw toward itself an higher or lower ow of packets, according to its own position within the graph.

# 2 The network as a Markov Chain

In the recent literature on networks several dynam ic packet transport m odels were analyzed with the aim of describing realistic communication over the network  $\beta$  [12] [9][7] [11]. On the other hand in [5] [6] some static parameters were introduced in order to characterise the load distribution over the network without considering explicitly its dynam ics.

W e will suggest here an alternative and interm ediate packet transport model based on a stochastic approach.

We consider a network with N vertices. We make the hypothesis that the origin and the destination of each packet are chosen with uniform probability within all the vertices in the network. We suppose that at each time step, each vertex generates N 1 packets, each one addressed to every other node in the network so that the total number of packets generated at each time step is equal to N (N 1).

Then packets are supposed to be routed from origin to destination along the geodesic, i.e. according to a m inim um distance criterion. We suppose that packets are delivered according to a dynam ic process that takes into account the actual time needed for packets to travel across the network. We consider the case

Corresponding author. Em ail: fsorrent@unina.it

<sup>&</sup>lt;sup>y</sup>The authors are listed in alphabetical order

of a parallel process, in which at each time unit all packets m ove sim ultaneously, every one crossing one edge. We assume that the time in which a packet goes through exactly one edge is equal to one time unit. Speci cally we assume that at each time step:

- 1. Packets are generated at every vertex.
- 2. Packets in a given node but not delivered yet to their naldestinations, are routed to the neighbors of that node that are nearest to the destination.
- 3. Packets delivered to their nal destination are Figure 1: A parallel m odel of packets exchange in a rem oved from the network.

In [5], the load at a given vertex v, (v), was deof nodes crossing it. A nalogously we will de ne here the load at the edges '(e), as the num ber of shortest paths crossing a given edge.


Let J (i) be the subgraph of the vertices j adjacent to i. As a packet is crossing i, it can take one of the directed edges  $e_{ij}$ , j 2 J (i). We assume that each edge eij in the graph is crossed with frequency proportional to its load l(e). Consistently with that assumption, we will estimate the conditional probability of a packet starting from i, going through one of the edges  $e_{ij}$ , as:

$$p(e_{ij}=i) = \frac{p'(e_{ij})}{j'(e_{ij})}$$
: (1)

Using (1), we can now associate to the network of interest a M arkov C hain; each node being represented as a state of the chain with the probability of going from a state i to a state j being given by  $p(e_{ij}=i)$  for j2J(i).

The Markov Chain represents a dynamicm odel describing the evolution of the packets distribution in time. We can obtain num erically the lim it distribution , i.e. the probability of being asymptotically in a certain state/node of the Markov Chain. We wish to emphasize that can be used as an alterna– tive measure of the bad at vertices. In particular, we tween vertices in plies that packets travel from origin found load at vertices [5].

W e can give a physical explanation of that, according to the parallel nature of the packets exchange over the network.



sam ple network of three nodes. We represent with the sam e color packets generated at a given vertex. In the left panel we represent the distribution of packets after their ned as the num ber of shortest paths between pairs generation. It is worth noticing that the distribution does not change if we look at it after packets have been delivered. A swe can see, packets just having been generated and the ones delivered to destination are never present simultaneously in the same node at any given time.

Fig.1 shows the load distribution of packets in a representative network on which packets are exchanged in a parallel way. We observe that for each packet travelling from a vertex i to a vertex j, there is another one travelling from j to i. This implies that packets just having been generated and the ones delivered to destination are never present simultaneously in the same node at any given time.

Let's de ne v the total bad at the vertices in the network, computed as the sum of the loads over all the vertices within the network, i.e. v = v'(v). W e have that:

$$v = d N (N 1);$$
 (2)

where d is the characteristic path length associated to the graph. From (2), we have that the average load at vertices is given by l = d (N 1). We observe that the average load is proportional to the characteristic path length of the graph: shortening m ean distances beto di er from the previous estimation of the to destination in fewer steps. Hence, a load reduction is observed on the whole network.

sion (2) is identical to Little's Law [10] in queueing theory, i.e.

$$V = N (N 1);$$

where the total number of packets in the network V is replaced with  $v_{\rm v}$  and , the mean time spent by a packet going from origin to destination in Little's law, is replaced with d, under the hypothesis that each edge is crossed within the sam e am ount of time.

Note that, according to the new ly introduced load de nition, we nd that, contrary to what presented in [5], the total load at the vertices is equal to the total load at the edges  $_{\rm e}$  = \_l(e), ie. \_e = This is expected as in our model, the total amount of packets within the network at any time has to be the sam e.

#### 3 Uniform ity of load distribution in sm all world networks

W e will try now to assess whether the network topology can itself cause a more or less uniform distribution of packets in the network. In [2] the effects of variations of load distribution in random and scale free networks were analyzed. The form er are characterized by a Poisson degree distribution while the second have a degree distribution of the form P(k) k . From a communication point of view, it would be desirable to have a uniform load distribution in order to exploit evenly the network resources (nodes and edges). In particular we will try to understand how uniform over a given network the load distribution is, because of its topology.

Speci cally, an high variance of that distribution should indicate an unfair use of the network, and could therefore point out a possible cause of congestion.

In [1], the maximum load  $`_{m \mbox{ ax}}$  was proposed as a main index for characterizing the network structure and an high value of this param eter was claim ed re-

M oreover, it is worth m entioning here that expres- For that reason here we will evaluate the load standard deviation as de ned in [2], that refers to the network as a whole. In order to make it insensitive to the average values of ', we will evaluate  $\sim$  ('), the (3) standard deviation of the load appropriately norm alized with respect to its mean.

> The standard deviation of the load distribution (') was shown to have an e ect on network perform ances in term s of throughput and delivery time. Namely an high value of the load variance, that is typical of scale-free networks was seen to be able to worsen strongly the network perform ances.

> W e analyze here the variation of load distribution both at the edges and at the vertices due to changes in the underlying topology.

> A common feature of most real networks is that they are small world, i.e. the average distance between random ly chosen nodes is generally low and increases only logarithm ically with the network size. M oreover real networks show high clustering or transitivity, that is, high probability that two random ly selected neighbors of a node are also neighbors of each other. W atts and Strogatz (W S) [4] showed that, starting from a regular nearest neighbor circle, a few random redirection were su cient to get the small world e ect, without com prom ising the clustering.

> We will repeat the experiment in [4], measuring also the norm alized standard deviation of the vertices  $bad_{\prime} \sim ((v))$  and the edges  $bad \sim ((e))$ .

> In Fig. 2 the average load in the graph is shown as the redirection probability p is varied. It can be observed that the average load behaves as the characteristic path length of the graph, decreasing as p increases.

> The norm alized standard deviation of the vertices load is shown in Fig. 3. Here, we see that such quantity increases at st, then over a certain threshold value of the redirection probability, it is progressively reduced. In fact, as the redirected edges are few, the global reduction of the characteristic path length is achieved through the exploitation of the sam e shortcuts and the vertices situated at their endpoints.

A further increase ofp (i.e. of the num ber of redisponsible for congestion. Nevertheless, this parame- rected edges) causes an increase of the number of ter does not describe the whole structure of the graph, di erent paths linking pairs of nodes in fewer steps. giving inform ation only on the load level at the hub. Thus, for higher p, an higher load uniform ity (lower




Figure 2: The W S model. A regular lattice with 1000 vertices and 10 links per vertex is rewired with probability p. A verage vertices load  $\overline{} = d (N 1)$  is reported as a function of p. The results are obtained over 100 diverse experiments.




Figure 3: Normalized standard deviation of vertices load ~ ((v)) is reported as varying the redirection probability, under the same hypothesis of gure 2

~(`(v)) is observed. In other words we observe that, starting from a regular conguration, and adding progressively some disorder to it, the parameter increases at rst and then decreases after a critical point. So we have that at intermediate p, at which local and globale ciency are both maximized [14], we get the least uniform load distribution between vertices. In Fig. 4 we report the median (in blue) of the load distribution with the 25th and 75th percentile (in red), showing that the interquartile range of the sample is larger for intermediate values of p.

We can argue thus that the smallworld e ect, ie. the reduction of the average distance between vertices caused by the addition of a relatively smallnum ber of shortcuts, can be associated with an unfair spread of the bad distribution across the network. This would cause an unfair exploitation of some of the network resources, making some areas of the network more likely to be interested by higher tra c and therefore by congestion phenomena.

As shown in Fig. 5, sim ilar results are obtained when the load standard deviation at the edges (rather than at the vertices) is computed.

## 4 Load Distribution And Degree

As discussed above, by adding shortcuts at a given vertex, a load increase is observed at the node as well as at the edges leaving from it. So we can notice two di erent e ects of rew iring links on the load at the edges: (i) a bigger am ount of packets is routed by the starting node through the outgoing edges; (ii) the load is shared between an higher num ber of edges. Therefore, the load distribution at the edges is in uenced by both the load and the degree at the vertices which they leave from .

From this point of view, it is worth understanding the relationship between the two main measures of point centrality [13], the one based on the degree and the other on the betweenness.

A rst contribution in that sense was given in [B], where it was shown that, in the case of a power law degree distribution, the load scaling were character-




Figure 4: The median of bad distribution is reported as varying the redirection probability (blue line), under the same hypothesis of gure 2. Upper and lower red circles represent the 25th and the 75th percentile, with the length of the red segments indicating the interquartile range.




Figure 5: Normalized STD of edges load  $\sim$  ('(e)) is reported as varying the redirection probability, under the same hypothesis of gure 2

ized by a function of the degree  $k\!:$ 

r

This means that nodes with more incident edges are the ones that draw on them selves more load, according to an assigned power of the degree.

Here, to de ne a more general link between load and degree, we introduce a new index, the load-degree ratio r(i) at each vertex i, de ned as

$$(i) = \frac{(i)}{k(i)} = \frac{P_{j2J(i)}(i)}{k(i)} = (5)$$

This parameter measures the number of packets at each vertex, with respect to the number of incident links and moreover it is an average value of the load at the edges incoming or outgoing from i.

We observe that, when the redirection procedure is applied, the degree of som e vertices increases (as new edges are connected to them). Correspondingly a signi cant increase of the bad at vertices is also detected. Therefore, the bad-degree ratio of those vertices increases as well. On average thism eans that the bad at the edges leaving from overbaded vertices becom es larger. This explains the behavior of  $\sim$  (`(e)) in Fig. 5 below the threshold value of p.

On the contrary, for further variations of the redirection probability, as the network approaches a random con guration,  $\sim(`(e))$  decreases similarly to what observed for  $\sim(`(v))$ .

## 5 CONCLUSION

In this work we have introduced a new load de nition m ore suitable in the case of a dynam ical process in which packets travel across the network in parallel. This new formulation di ers from previous ones as it takes into account in the computation alternatively the contribution of the packets yet generated or of the ones delivered to destination; in fact in a parallel process packets outgoing from a given vertex m ove at the sam e tim e as the incom ing ones arrive.

M oreover we have introduced two new indices with the aim of evaluating the role of the network topology in in uencing the packets distribution within the network, the standard deviation of the load at the vertices  $\sim(`(v))$ , and at the edges  $\sim(`(e))$ . We have reworked through the W S experiment, computing the new quantities. We have noticed that as the smallworld e ect can be obtained by the addition of a relatively low number of shortcuts, this is made at the expenses of the uniform ity of the load distribution within the network.

### References

- [1] A Arenas, A Cabrales, A Diaz-Guilera, R Guinera, and F Vega-Redondo. Search and congestion in complex networks. cond-m at, 1 (0301124), 2003.
- [2] D.K. Arrowsmith, M. di Bernardo, and F.Sorrentino. E ects of variation of load distribution on network performance. Proc. IEEE ISCAS, Kobe, Japan, 2005.
- [3] D.K. A rrow sm ith, R.J. M ondragn, J.M. P ittsy, and M.W oolf. P hase transitions in packet trafc on regular networks: a comparison of source types and topologies. 2004.
- [4] D.J.W atts and S.H. Strogatz. Collective dynamics of 'sm all world' networks. Nature, 393:440{ 442, 1998.
- [5] K.-I.Goh, B.Kahng, and D.Kim. Universal behavior of load distribution in scale-free networks. Phys.Rev.Lett., 87 (27), 2001.
- [6] K.-I.G oh, B K ahng, and D K in . Packet transport and load distribution in scale-free network m odels. Physica A, 318:72 (79, 2003.
- [7] S. Manfredi, M. di Bernardo, and F.G. arofalo. Small world e ects in networks: An engineering interpretation. Proceedings of IEEE International Symposium on Circuits and System s Vancouver, 2004.
- [8] M Berthlem y. Betweenness centrality in large com plex networks. cond-m at, 1 (0309436), 2003.

- [9] T.Ohira and R.Sawatari. Phase transition in a computer network tra cmodel. Phys. Rev. E, (58):193(195, 1998.
- [10] R Nelson. Probability, stochastic processes and queueing theory: the mathematics of computer performance modeling. Springer-Verlag, New York, 1995.
- [11] S M anfredi. An agm routing control for reducing congestion in communication networks. International Symposium on C incuits and Systems K obe Japan, 2005.
- [12] R.V. Sole and S.Valverde. Information transfer and phase transition in a model of data tra c. Physica A, 289 (595), 2001.
- [13] SW assemman and K Faust. Social Network Analysis. Cambridge University Press, 1994.
- [14] V Latora and M M archiori. E conom ic sm allworld behaviour in weighted networks. condm at, 1 (0204089), 2002.