## Dynamic e ective mass of granular media

Chaur-Jian H su<sup>1</sup>, D avid L. Johnson<sup>1</sup>, R ohit A. Ingale<sup>2</sup>, John J. Valenza<sup>1</sup>, N icolas G land<sup>2</sup>, and H eman A. M akse<sup>2</sup>

<sup>1</sup>Schlum berger-Doll Research, One Ham pshire Street, Cam bridge, MA 02139

<sup>2</sup>Levich Institute and Physics Department, City College of New York, New York, NY 10031

(D ated: Septem ber 1, 2022)

We develop the concept of frequency dependent e ective mass, M (!), of jam med granular materials which occupy a rigid cavity to a lling fraction of 48%, the remaining volume being air of normal room condition or controlled hum idity. The dominant features of M (!) provide signatures of the dissipation of acoustic modes, elasticity and aging e ects in the granular medium. We perform hum idity controlled experiments and interpret the data in terms of a continuum model and a \trap" model of thermally activated capillary bridges at the contact points. The results suggest that attenuation in the granular materials studied here can be in-uenced signi cantly by the kinetics of capillary condensation between the asperities at the contacts.

PACS: 45.70.-n, 46.40.-f, 81.05 Rm

A distinct feature of jam med or loosely packed granular materials made of a variety of di erent materials such as sand, steel, polymer or glass is the ability to dissipate acoustic energy through the network of interparticle contacts or viscous dissipation through the surrounding medium. Indeed, loose grains dam p acoustic modes very e ciently [1, 2, 3, 4, 5] and they are routinely used as an e ective method to optimize the damping of unwanted structure-bome acoustic signals [1]. Despite its fundam ental importance and practical applications, the microscopic origins of the mechanisms of dissipation in jammed granularmaterials are still unknown.

In this Letter, we pursue the concept of a frequency dependent e ective mass, M' (!), of a bose granular aggregate contained within a rigid cavity [5]. The e ective mass M' (!) is complex valued; its real part refects the inertial and elastic properties while its in aginary part re-

ects the dissipative properties of the granular m edium . We demonstrate how the features of M (!) allow the study of some of the m echanism s of dam ping of acoustic m odes, aging and elasticity in granular m atter.

Generally speaking, the real part of M (!) exhibits a sharp resonance which we interpret in terms of an elective sound speed. The imaginary part of M (!) shows a broad resonance peak which quantiles the attenuation of acoustic waves in the system. We observe significant changes in the still ness and attenuation as a function of hum idity. By monitoring the elective mass in time, we

nd a logarithm ic aging e ect in the resonance frequency as well as an increase of the dam ping upon hum idi cation. These e ects can be modeled as capillary condensation occurring between the asperities at the contact surfaces between the grains during hum idity-dry cycles. W e interpret this phenom enon in the context of a \trap m odel" of therm ally activated liquid bridges. O ur results suggest that, in the granularm aterials investigated in the present study, dissipation of acoustic energy is dom inated by the asperities at the interparticle contact surfaces. In addition, hum idity drastically a ects the attenuation of the m aterial through the capillary condensation of liquid bridges.

Experiments. A cylindrical cavity (of diameter D = 25.4 mm) excavated in a rigid alum inum cup is led with tungsten particles up to a height of 30.7 mm. We use tungsten particles due to their large density, which maxim izes the e ects we are studying. Each of these particles consists of four or ve equal-axis particles, of nom inal size 100 m, fused together (see inset of Fig. 1). Such irregular arrangem ent produces low volum e fractions (in this case 48%, in comparison with random close packing of spherical particles, 64% ) and allows to study the loose packings of interest in the present work. To investigate the applicability of our results to other materials we perform experiments with spherical glass beads as well as lead beads, see below. The cup is mounted on a B&K shaker and subjected to a vertical sinu soldal vibration at frequency ! = 2 f, with the frequency scan from sub kH z to 10 kH z. Since the bulk behavior depends on the contacts between the grains, the way of lling the gran-



FIG.1: E ective m ass of tungsten particles in a rigid cavity as a function of driving frequency. Inset: Scanning Electron M icroscope in age of the tungsten particles used in our experiments. The scale at the bottom of the image corresponds to 300 m.

ular m edium in the container is in portant. Prior to the m easurem ent, we pour the grains into the cup and then shake the cup near its resonance frequency (see below) at large am plitudes up to 3g for 30 m inutes to allow the com paction of the m aterial. During the m easurem ent, the granular m edium is driven with cup acceleration of approximately 2 to 3 m s<sup>2</sup>. The am plitude of vibration is approximately 1 m for the lower frequencies and decreases to below 1 nm for the higher frequencies.

Force F (!) and acceleration a (!) are independently m easured with a force gauge and an accelerom eter attached to the bottom of the cup. The signals are analogically ltered with a lock-in amplier, which is synchronized with the driving signal. These Itered signals are then digitally recorded. The force gauge is sandwiched between the shaker and the cup container. At each frequency, the force and acceleration are averaged over a 500 m s or longer tim e w indow . P rior to this tim e window, there is a 3 sec waiting time following the onset of the driving frequency in order to allow the system to reach a steady state, and achieve accurate measurements. Since F (!) and a (!) are the net force exerted on and the response of the cup-granules assembly, their ratio, the e ective mass, is independent of the shakers frequency response. Taking into account the mass of the empty cup, M<sub>c</sub>, we have M<sup>(!)</sup> + M<sub>c</sub> =  $\frac{F(!)}{a(!)}$ ; where,  $M^{\circ}(!) + iM^{\circ}(!)$ , re ects the partially in-phase, M~(!) M°, partially out-ofphase, M°, motion of the individualgrains, relative to the driving force. Thus M carries inform ation about the inertia and elastic response while " relates to attenuation of particle response. М

Fig. 1 shows the result for a frequency sweep of M'(!). We note that in the low frequency lim it, M'(!)0) ! 149g, the static mass of the grains. More interestingly, there is a relatively sharp resonance peak around  $f_0 : !_0=2 = 1.8$  kHz and a relatively broad tail that diminishes with increasing frequency. M'' exhibits a broad peak centered at  $w_0$ . We have conducted the experiments with other granular materials. Fig. 2(a)-(b) shows the results for spherical lead beads of the size 180-250 m and glass beads of 150 m. These results are qualitatively similar to those of tungsten particles, in both the real and imaginary parts; the tungsten particles exhibit larger e ects.

W e also applied the e ective m ass technique to liquid samples. Fig. 2c shows a typical plot for the e ective m ass of one such liquid ( uorocarbon uid, density 1800 kg/m<sup>3</sup>) asm easured by the e ective m asstechnique. M<sup>°</sup>(!) shows a sharp resonance while the M<sup>°°</sup>(!) curve is alm ost zero over the whole frequency range (except near resonance) indicating negligible dissipation. We can extract a value for the e ective com pressional sound speed from the resonance frequency as  $v_s(L) = 4L f_0$ , where L is the depth of the m edium. The values of density and sound speed for a variety of liquids, asm easured with the e ective m ass technique, are cross-plotted against those determ ined by m ore conventional m eans [6] in Fig. 2d.

The density of the liquids is measured using Archimedes principle and buoyancy (accuracy of 0.1%). The sound speed is measured with ultrasonic (centered at 500 kH z) through-transmission method (accuracy of 1%). The grain density of the tungsten sample is measured with a M icromeritics helium pycnometer (accuracy 1%) and the bulk density is calculated from the measured weight of tungsten grains lling a cup of a known volume. Volume fraction is then estimated from the grain and bulk density. The results in Fig. 2d suggests that our technique for measuring M (!) is an accurate one.

We investigate how the elective sound speed changes with the lling depth L, based on the peak frequency  $f_0$ . The sound speed of the granularm edia is estimated based on the hypothesis of 1/4 wavelength resonance frequency. Fig. 2e shows the trend of greater speed with greater depth. The values we are reporting are of the same order of magnitude as those reported in the literature [1, 3, 5, 7]. In the range studied here, the linear relation  $v_s$  (L) L seem s to hold up to L = 61 mm as seen in Fig. 2e.

W e may model the general features of Fig. 1 in terms of a simplied continuum model. The granular



FIG.2: (a) Real (M<sup> $\circ$ </sup>) and (b) Im aginary part (M<sup> $\circ$ </sup>) of effective m ass for spherical lead and glass beads. (c) E ective m ass of uorocarbon uid. (d) Crossplot of m easured values and book values of densities and sound speeds for various liquids: M ethanol (o and , rst sym bol density, second sound speed), Ethanol (+ and ), Fluorocarbon uid ( and 0), Silicon oil, (viscosity 10 m Pa-s, M and ). (e) E ective speed of sound in tungsten granules as a function of lling depth, L, for constant cavity diam eter, D = 25:4m m. (f) Continuum m odel prediction of M<sup> $\circ$ </sup> (!).

medium is considered to be a lossy uid, with negligible viscous e ects at the walls. The acoustic pressure in the uid is described by a one-dimensional model: P (z) = A sin (qz) + B cos(qz). The boundary conditions are: (a) The displacement of the uid at z = 0 matches that of the cup,  $u(z = 0) = u_{cup}$ . (b) The acoustic pressure at the top of the uid vanishes, P (z = L) = 0. Thus, P (z) =  $u_{cup}$ !<sup>2</sup> [sin (qz) tan (qL) cos(qz)]=q. The force the cup exerts on the uid is  $F = a^2P(z = 0)$  and the acceleration of the cup is !<sup>2</sup> $u_{cup}$  from which we obtain the e ective mass:

$$M'(!) = a^{2^{D}} K = ! \tan(qL);$$
 (1)

where  $K = K_0 [1 \quad i!_p]$  is the (lossy) bulk modulus of the medium, and q = ! = K is the complex wave vector with the density of the medium. This model shows that resonance peaks, as seen in Fig. 2f, occur when L equals odd multiples of 1/4 wavelength of the acoustic wave in the p edium, with the main resonance peak at  $f_0 = 1 = (4L) K_0 = .$  Encouraged by these results, we interpret the main resonance in Fig. 1 as being a 1/4 wavelength resonance of the compressional sound speed.

Next, we use the features in M'(!) to investigate the dissipation in the granular medium. The dissipation mechanisms can be grouped into two categories: 1) Local damping throughout the contact network that includes asperity deform ation and bulk attenuation [8], and wetting dynamics in the liquid bridges caused by relative motion of neighboring particles [9]. Wetting dynamics also results in greater contact sti ness [10]. If large interparticle tangential displacements occur then, there exist dissipation through C oulom b friction as well. 2) G lobal damping due to drag caused by particle motion in a surrounding viscous medium [11].

Next, we perform further experimentation by changing the ambient conditions. Ambient hum idity can modify the dissipation and the sti ness at the grain to grain surface contacts [10]. For instance, sm all amounts of liquid greatly a ects the maximum angle of stability in sandpiles [12], while capillary action of the interstitial liquid results in increased cohesion [10], modi ed friction [13] and aging in the angle of repose of granular materials [14]. We place the elective mass apparatus in a chamber where hum idity is controlled by rst using an aqueous saturated salt solution [15] and subsequently a dessicant. We measure the relative hum idity as the ratio of the partial pressure of water to the saturating vapor pressure  $H_R = p_{vap}=p_{sat}$ .

We follow a hum id-dry cycling process as follows: we start from room hum idity  $H_R = 26\%$  att< 0, and then we hum idity att= 0 to  $H_R = 75\%$  until t= 126 hr, and then we dry to  $H_R = 0\%$  until t= 174 hr. Fig. 3 shows the e ective m assme easurem ents under the hum idity controlled environment carried out at various time intervals. We observe a very slow shift in resonant frequency during the hum idi cation cycle, followed by a further positive shift upon drying. The e ect is more im portant when we repeat the same cycling but to 95% hum idity.



FIG.3: Im aginary part of M (f) m easured under hum idity controlled conditions (the real part shows sim ilar behavior). The solid lines represent m easurements under  $H_R = 75$ % and the dashed lines are for the dry state,  $H_R = 0$ %. Top inset: Frequency shift vs time for  $H_R = 75$ % (o) and 95% (). Bottom inset: D amping rate () vs time for  $H_R = 75$ %. The dashed lines in the insets are logarithm ic ts. The up and down arrows indicates the large variations in sti ness and damping upon drying, respectively.

During hum idi cation, we observe an aging phenom enon as evidenced by the approximate logarithm ic behavior of the shift in resonant frequency  $f_0(t)$  (top inset of Fig. 3),  $f_0(t) = C (H_R) \log(t=t_i)$ ; where  $C (H_R)$  is a constant that increases with hum idity, C (75%) = 292 Hz and C (95%) = 494 Hz and  $t_i = 2$  hr for both m easures.

Furtherm ore, the hum id system shows a large increase in the attenuation as illustrated by the increase in dam ping rate (bottom inset of Fig. 3). Based on the experimental elective mass data, we search for poles in M<sup>°</sup>( $\frac{1}{2}$ ) for  $\frac{1}{2}$  in the complex plane. Once the complex resonance frequency ( $\frac{1}{2}_{0} = \frac{1}{0}^{0} + \frac{1}{0}^{0}$ ) is found, the dam ping rate is given by  $= \frac{1}{0}^{0}$ . The dam ping rate at am bient hum idity is 300 s<sup>-1</sup>, which rises to 1200 s<sup>-1</sup> under prolonged hum idi cation (see bottom inset of Fig. 3). The dam ping data suggests logarithm ic increase with tim e.

A possible interpretation of the observed behavior suggests that contact forces through capillary liquid bridges are important for damping, stiness and aging. As demonstrated in [14], the hum idi cation process leads to the formation of capillary bridges around the roughness asperities at the interparticle contact surfaces. The aging e ect observed in the logarithm ic variation of the frequency shift with time can be interpreted as originating from capillary condensation. The key quantity to calculate is the time dependence of the num ber of wetted asperities  $n_a$  (t). Capillary condensation at the surface asperities can be seen as a therm ally activated process following a model proposed in [14]. The energy barrier to form a liquid bridge of cross sectional area A between two asperities separated by a gap h is  $E = {}_1Ah$ , where  ${}_1$  is the molecular density of the condensing liquid,  $= k_B T \ln (1=H_R)$  is the undersaturation of the chemical potential, and T the room temperature. The activation process follows an Arrhenius dynamics such that the time to create a bridge is  $= t_0 \exp (E = k_B T)$ , with  $t_0$  the microscopic condensation time.

D ue to the roughness of the particles we expect a distribution of gaps P (h), which leads to a distribution of energy barriers, P ( E ). The calculation of the probability distribution P ( ) is then analogous to obtaining the probability of the tim e to escape from a trap with energy barrier E for a therm ally activated particle in a random energy potential. Such a process corresponds to the \trap m odel" used to describe the phenom enology of glasses [16]. The probability P ( ) satis es P ( )d = P (h)dh. W hile the probability P (h) is unknown, we expect it to be a bounded distribution determ ined by the surface roughness of the particles. The two m ost com m on cases lead to the sam e result: for an exponential or G aussian distribution of gaps, we md P ( )  $^{1}$ .

The number of activated wetted asperities at time t is  $n_a$  (t) /  $\frac{R_t}{t_0} P$  ()d. Then  $n_a$  (t)  $\log$  (t=t\_0). Liquid bridges induce a signi cant cohesion between the particles which for loss grains under gravity and large humidity outweigh the weight of the grains. Therefore, the logarithm ic increase in  $n_a$  leads to an additional sti ness with the concomitant increase in the compressional sound speed. Since the resonance frequency is proportional to the sti ness of the contact, the logarithm ic aging can be interpreted as arising from the wetted asperities.

Upon drying the particles to  $H_R = 0$ % after hum idi – cation, the physics is very di erent from the hum id process. As shown by the experiments of [10], the capillary

rings dry out and the asperities are sucked down by the increasing capillary pressure in the evaporating lm leading to an even larger increase in sti ness of the contacts. Thus, in the dried out state there is much more solid on solid contact and the sound speed is increased. This increase in sti ness upon drying results in even larger positive shifts in resonant frequency as seen in the top inset of Fig. 3.

We also nd important changes in the dissipation in the dry state. Upon drying, the decrease in overall attenuation is evident from the much sharper resonance in M<sup> $\infty$ </sup> (we nd a very large mass at resonance M<sup> $\infty$ </sup> (f<sub>0</sub>) 3500 g). A coordingly, the damping rate decreases to = 50 s<sup>1</sup> in the dry case from = 1200 s<sup>1</sup> at H<sub>R</sub> = 75% (see bottom inset of Fig. 3). In the driest state, no liquids bridges are left and the dissipation is purely through asperities deform ation with the concom itant lower dam p-ing strength. These results suggest that, for the granular media studied here when hum id conditions prevail (including am bient), liquid bridges provide larger attenuation of acoustic waves than the viscoelastic dissipation in the bulk of the particles or viscous global dam ping.

In conclusion, we have dem onstrated the usefulness of the e ective m ass technique to study the dissipation of acoustic waves, sti ness and aging in granularm edia. Experiments and theoretical models suggest that capillary condensation at the interparticle contacts is an important mechanism for dissipation and aging. The kinetics of aging can be modeled in terms of a trap model for the form ation of liquid bridges at the asperities. The large variations in dissipation found in this study demonstrate the conditions for e ective particle damping and are relevant to a variety of applications for optim izing attenuation of structure-borne acoustic waves.

A cknow ledge ents. We are grateful to L.M of ow an for technical assistance. We acknow ledge nancial support from  $D \circ E$ , Geosciences D ivision.

- L. Cremer and M. Heckl, Structure Borne Sound (Springer, Berlin, 1973).
- [2] J.D uran.Sands, powders and grains.An introduction to the physics of granular materials (Springer-Verlag, 2000).
- [3] C.-h.Liu and S.Nagel, Phys. Rev. Lett. 68, 2301 (1992).
- [4] J.M. Bourinet and D. Le Houedec, C om puters and Structures 73, 395 (1999).
- [5] J.M.Bourinet and D.Le Houedec, Powders & Grains 97 eds. R.Behringer and J.Jenkins (Balkema, Rotterdam, 1997).
- [6] H andbook of Chem istry and Physics, 81st Edition (CRC Press, Cleveland, 2000).
- [7] F.D. Shields, J.M. Sabatier and M.W ang, J. Acoust. Soc. Am. 108, 1998 (2000).
- [8] N. V. Brilliantov, F. Spahn, J.-M. Hertzsch, and T. Poschel, Phys. Rev E 53, 5382 (1996).
- [9] J. Crassous, E. Charlaix, H. Gayvallet, and J.-L. Loubet, Langmuir 9, 1995 (1993); J. Crassous, E. Charlaix,

and J.L.Loubet, Phys. Rev. Lett 78, 2425 (1997); M.J. A dam s and V.Perchard, Inst. Chem. Engr. Symp. 91, 147 (1985).

- [10] J.N.D 'Am our, et al. Phys. Rev. Lett. 96, 058301 (2006).
- [11] J.Schafer, S.D ippel, and D.E.W olf, J.Phys. I (France) 6, 5 (1996).
- [12] D. J. Hombaker, R. A bert, I. A bert, A.-L. Barabasi, P. Schier, Nature 387, 765 (1997).
- [13] E. Riedo, F. Levy, and H. Brune, Phys. Rev. Lett. 88, 185505 (2002).
- [14] L.Bocquet, E.Charlaix, S.Ciliberto and J.Crassous, Nature 396, 735 (1998).
- [15] F. Restagno, C. Ursini, H. Gayvallet, and E. Charlaix, Phys. Rev. E 66, 021304 (2002).
- [16] C. M onthus and J.P. Bouchaud, J. Phys. A 29, 3847 (1996).