

A Possible Nanometer-scale Computing Device Based on an Adding Cellular Automaton

Simon C. Benjamin^{a)} and Neil F. Johnson

Physics Department, Clarendon Laboratory, Oxford University, Oxford OX1 3PU, England

Abstract

We present a simple one-dimensional Cellular Automaton (CA) which has the property that an initial state composed of two binary numbers evolves quickly into a final state which is their sum. We call this CA the Adding Cellular Automaton (ACA). The ACA requires only $2N$ two-state cells in order to add any two $N-1$ bit binary numbers. The ACA could be directly realized as a wireless nanometer-scale computing device – a possible implementation using coupled quantum dots is outlined.

PACS numbers: 89.80, 85.42, 02.40.S

^{a)} correspondence to: sbenjamin@physics.ox.ac.uk

For more than thirty years the processing power associated with a single silicon chip has increased exponentially. This growth results from the continual increase in the number of transistors integrated into the chip. State-of-the-art chips now have features of the order of 1000 atoms wide. Before this number is reduced by a single order, we may expect quantum effects to become sufficiently strong that they must be explicitly allowed for in the design.

One is naturally led to ask the question, may there not be some wholly different computational architecture that is more efficient (in some sense more 'natural') in the quantum mechanical regime? A number of theoretical studies (e.g. [1-4]) have proposed novel processing systems of this kind. These structures have a certain feature in common: they consist of a large number of identical cellular units. Systems of this kind are related to the mathematical idea of cellular automata.

The basic cellular automaton [5] is a D -dimensional lattice of identical cells, each of which is in one of a finite set of possible internal states (called the 'state alphabet'). The entire lattice, which may be infinite or periodic, is updated in discrete time steps. On each update, each cell assumes a new state determined by its own present state, and the state of a certain set of local cells (the cell's 'neighborhood'). For example, in a one-dimensional CA a cell's neighborhood might consist of just the cell itself and its immediate neighbors. The update rule, which specifies what internal state to assume for each possible arrangement of states in the neighborhood, is referred to as the 'table'. The neighborhood, and the 'table', are the same for all the cells.

In the first part of this letter we introduce a one-dimensional CA designed to have the property that an initial state composed of two binary numbers evolves into a final state which is their sum. We call this CA the Adding Cellular Automaton (ACA). We have designed the ACA to include certain features that make direct physical realization possible. We expect that there are many physical systems capable of implementing the ACA scheme. In the second part of the letter we provide one example, a modified version of the quantum dot architecture proposed in Ref. [3].

The ACA has excellent efficiency; the addition of two N bit numbers requires only

$2N$ cells (with an alphabet of just two states) and a maximum of $2N$ updates. Furthermore, the final state is such that a third number may be encoded onto the ACA, and the addition process repeated. Hence the ACA may sum a whole sequence of numbers.

There are two possible geometries for the ACA, a simple line of cells and a closed circle. Figure 1 shows the states through which a 10 cell ACA passes as it performs an addition; a circular geometry is assumed so that the right-most cell of each line is adjacent to the left-most cell. The figure indicates how two numbers, A and B , must be encoded to form the ACA's initial state. The subscripts indicate a particular bit in the binary representation of the number, $A = \sum_{i=0}^P A_i 2^i$, and similarly for B and the output $C = A + B$. The ACA is unusual in that it has two different tables (update rules), the 'add' and the 'carry' table, which are applied alternately. There are also two interlaced subsets of cells, the ϕ set and the ψ set; whilst one set is being updated the other remains static. The two update tables are defined in Figure 1, and the grid shows that 'carry' and 'add' are applied to first one cell subgroup and then the other. This pattern is repeated until a total of $2N$ individual updates have been performed (for a system with $2N$ cells). The sum is then in the indicated cells; note that it is rotated (by N cells) with respect to the input A . It is because of this rotation that the circular geometry has an advantage over the linear design; the latter would require an additional N cells so that the answer should not 'fall off the end'. Regardless of the choice of input numbers, the answer $A + B$ always occupies the same cells after all $2N$ steps have been performed. This assertion can easily be proved for an ACA of reasonable size (≤ 30 cells or less) by exhaustive computer simulation for all possible A and B . Readers can verify the validity for any specific A and B using the interactive version of Fig. 1 [6].

From the grid in Fig. 1 it is clear why the division into two subsets of cells is useful. On any single update the new state of a cell depends only on its own current state and the state of a neighboring static cell, i.e. one which is not subject to the current update. Thus the cells that are to be updated on a given step are independent of one-another. This means that in the physical system, each cell may change its state at a random instant within some given time interval (this would occur for a system driven by photonic excitation, for

example). Clearly, this spread of instants would randomize the behavior of a simple CA in which inter-dependent cells are updated together.

The physical implementation of the ACA requires an array of cells, each cell having at least two stable states and being sensitive to the state of its neighbors. One possible cell would be the bistable double-quantum-dot, driven through its internal states by laser pulses [3]. The beam would encompass the whole ACA and update all cells that respond to its frequency; a single laser could drive a large number of independent ACA devices. The potential for such structures as a realization of a CA has been considered in some detail in Ref. [3] and will be briefly summarized here. We use the notation $x-y-z$ to refer to a cell in state y whose left and right neighbors are in states x and z respectively (for a circular CA, the sequence of cells $x-y-z$ runs clockwise).

Consider the basic cell as comprising a coupled pair of quantum dots as suggested above; the low-lying single particle states are those for which the electron is localized on one or other of the dots. The lowest energy state within each of the two localizations are the physical representations of $|1\rangle$ and $|0\rangle$. One dot is assumed to be slightly smaller than the other, so that the two localizations are non-degenerate. The energy difference is slight and the wavefunction overlap is very small so that the rate of spontaneous decay from one dot to the other is much slower than the total computation time. The CA is built up from such cells simply by producing a string of them (see e.g. the upper part of Fig. 2). There is no tunneling allowed between the cells; they 'feel' the states of their neighbors via the Coulomb interaction. The Coulomb repulsion is greater for a pair of cells in the same state than for a pair in opposite states; the energy difference has a r^{-3} dipole-like form, where r is the cell-cell separation. If the distance to a cell's neighbor on the right is not equal to the distance to its left neighbor, then the two stable energy levels for an isolated cell split into eight levels, one for each combination of neighbor states. This is shown in Figure 3. The idea of having two species of cell and updating them alternately is realized by using two different sizes of double-dot. The size difference shifts the double-dot's energy levels and thus makes it possible to address one type at a time.

In order to produce the desired updates of the CA, a third transient state is employed. This is a single-particle state in which the electron probability distribution is spread over both dots. The transient state spontaneously decays very quickly into one of the stable states. As shown in Fig. 3, an update is produced by pumping the system with light of a frequency that will excite cells of one size from a given stable state (say 1-0-0) into the transient state. The cell may decay from the transient state into either the original state (1-0-0) or the flip state (1-1-0). However, if the former occurs the electron will be re-excited by the pump, so that we can flip the state with any desired certainty (< 1) simply by using a pulse of sufficient duration. Note that the frequency width of the pulse must be sufficiently narrow to excite from only one of the levels shown in Fig. 3, yet sufficiently broad to cover the sub-splitting (shown shaded gray) due to non-neighboring cells.

A difficulty arises with the above system which is associated with the bottom two lines in the 'add' table of Fig. 1. The states $X-1-0$ and $X-1-1$ (where $X = 0$ or 1) transform into each other; this swap cannot be directly translated into a sequence of pulses, as required by the physical process described above [7]. We must make one of the following modifications: use N extra cells of a third size, use triple rather than double dots, employ next-nearest neighbor interactions, or use a coherent switching process. These possibilities will be elaborated upon elsewhere [8]. Here we will focus on the first solution as it seems the least difficult experimentally.

We will modify the system proposed in Ref. [3] by using three rather than two sizes of cell and correspondingly three inter-cell distances. A system of this kind is shown schematically in Fig. 2. We will also need a third update rule; this rule is 'Shift'. Its effect is simply to make the target cell's state equal to the state of its immediate clockwise neighbor. In the lower part of Fig. 2 we tabulate the stages the ACA evolves through in terms of the light pulses to which it is subjected. The notation \uparrow_{γ_5} denotes a pulse of the correct frequency to pump the cells of size 5 from the state $\backslash 7 = 1 \ 1 \ 1$, via the transient state to $\backslash 5 = 1 \ 0 \ 1$. The letters C, S, and A denote 'carry', 'Shift' and 'add' operations respectively. At first glance the grids in Figs. 1 and 2 seem quite different, however the latter actually contains

the former. Removing the shaded squares in Fig. 2 recovers the grid in Fig. 1 (excluding the first line). Thus $2N$ update steps in the abstract ACA correspond to $8N$ light pulses in this chosen physical implementation. If we assume a pulse duration of 100 fs [3], then a few picoseconds would be required to add two 8 bit numbers. It is important to note that the proposed device, being composed of bistable units, is a nanometer-scale classical computer rather than a true quantum computer. It does not need to maintain wavefunction coherence, and is therefore far less delicate than a quantum computer.

Possible methods exist for reading and writing the states on the cells in parallel. One might exploit recent experimental work [9] in which fluctuations of 1 in the number of electrons on a quantum dot were measured using the pico-amp current flowing through a nearby constriction. Alternatively one might employ single-electron transistors; these devices have recently been made to work at room temperature [10]. We expect it will prove possible to use one such technique to read all the states in the ACA at once (by having one current probe for each ACA cell, as shown in Fig. 2). By careful manipulation of the potential in the probe elements, it should prove possible to use them to write data onto the ACA device as well [8]. We stress again that the double quantum dot system described above represents only one possible implementation; quite different systems (for example, the Single-Electron Parametron [4]) could prove equally well suited.

A modest structure of just two or three cells and probe elements would suffice to test the principles upon which the full ACA is based. In particular, it is important to experimentally measure the various time scales involved. If unwanted spontaneous decay should prove to be an obstacle, a solution would be to embed the ACA device in a photonic band gap material [11]. The ACA may also be kept 'on-course' through the addition process by making measurements of the ACA's state during the computation. Each measurement collapses the quantum state of the cells into $|1\rangle$ or $|0\rangle$, thus preventing a slow drift from the intended evolution [12].

This work was funded by an EPSRC Photonic Materials Grant.

REFERENCES

- [1] P.D .Tougaw and C .S.Lent, J.Appl.Phys., 75 1818 (1994).
- [2] A .N .K orotkov, Appl.Phys.Lett. 67 2412 (1995).
- [3] K .O berm ayer, W .G .Teich and G .M ahler, Phys.Rev.B 37 8096 and 8111 (1988).
- [4] K .K .L ikharev and A .N .K orotkov, Science 273 763 (1996).
- [5] J.von Neum ann, Theory of SelfReproducing Autom ata, Univ.of Illinois P ress (1966).
- [6] The web page \http://cm -th.physics.ox.ac.uk/Sim onB /adder/add.htm l" allow s Java en-abled brow sers to generate Fig.1 with any desired A and B .
- [7] This restriction was noted in Ref. [3].
- [8] S.C .Benjam in and N .F .Johnson, (unpublished).
- [9] M .Field, C .G .Sm ith, M .Pepper, D .A .R itchie, J.E .Frost, G .A .C .Jones and D .G .Hasko, Phys.Rev.Lett. 70 1311 (1993).
- [10] K .M atsum oto, M .Ishii, K .Segawa, and Y .O ka, App.Phys.Lett. 68 34 (1996).
- [11] P .M .Hui and N .F .Johnson, Solid State Physics Vol.49, edited by H .Ehrenreich and F .Spaepen (Academ ic P ress, New York, 1995) p.151.
- [12] B .M isra and E .C .G .Sudershan, J.M ath.Phys. 18 756 (1977).

Figure Captions

Figure 1. The 'add' and 'carry' tables for the ACA, together with a grid showing the example of $15 + 3$. Circular geometry is assumed, hence right-most column is adjacent to the left-most column. See Ref. [6] for an interactive version.

Figure 2. Above: Possible physical realization of the circular ACA using double quantum dots. Radial lines represent channels for a probe current, with a quantum constriction near each double-dot. Table: Second line shows two 4-bit numbers, A and B, must be loaded into initial state of ACA. Body of table shows the example $A = 15$, $B = 3$. Deleting the shaded squares recovers fundamental ACA table in Fig. 2.

Figure 3. Left side: Energies of the $0'$ and $1'$ states of the double quantum dot, and of the transient state T' (electron localization is shown schematically). Middle: Splitting of the levels as the states of the neighboring cells are resolved. Right side: Shaded bands show splitting due to non-adjacent cells. Vertical lines show implementation of 'add' operation; straight lines: excitation by laser, wiggly lines: spontaneous decay.

Fig.1





