

# The central nature of the Hidden Subgroup problem

Stephen Fenner  
University of South Carolina

Yong Zhang<sup>y</sup>  
Eastern Mennonite University

September 18, 2006

## Abstract

We show that several problems that figure prominently in quantum computing, including Hidden Coset, Hidden Shift, and Orbit Coset, are equivalent or reducible to Hidden Subgroup for a large variety of groups. We also show that, over permutation groups, the decision version and search version of Hidden Subgroup are polynomial-time equivalent. For Hidden Subgroup over dihedral groups, such an equivalence can be obtained if the order of the group is smooth. Finally, we give nonadaptive program checkers for Hidden Subgroup and its decision version.

Topic Classification: Computational Complexity, Quantum Computing.

## 1 Introduction

The Hidden Subgroup problem generalizes many interesting problems that have efficient quantum algorithms but whose known classical algorithms are inefficient. While we can solve Hidden Subgroup over abelian groups satisfactorily on quantum computers, the nonabelian case is more challenging. Until now only limited success has been reported. For a recent survey on the progress of solving nonabelian Hidden Subgroup, see Lomont [Lom04]. People are particularly interested in solving Hidden Subgroup over two families of nonabelian groups| permutation groups and dihedral groups| since solving them will immediately give solutions to the Graph Isomorphism problem [Joz00] and the Shortest Lattice Vector problem [Reg04], respectively.

To explore more fully the power of quantum computers, researchers have also introduced and studied several related problems. Van Dam, Hallgren, and Ip [vdHI03] introduced the Hidden Shift problem and gave efficient quantum algorithms for some instances. Their results provide evidence that quantum computers can help to recover shift structure as well as subgroup structure. They also introduced the Hidden Coset problem to generalize Hidden Shift and Hidden Subgroup. Recently, Childs and van Dam [CvD05] introduced the Generalized Hidden Shift problem, which extends Hidden Shift from a different angle. They gave efficient quantum algorithms for Generalized Hidden Shift over cyclic groups where the number of functions is large (see Definition 2.2 and the subsequent discussion). In an attempt to attack Hidden Subgroup

---

Department of Computer Science & Engineering, Columbia, SC 29208 USA. fenner@cse.sc.edu. Partially supported by NSF grant CCF-0515269.

<sup>y</sup>Department of Mathematical Sciences, 1200 Park Road, Harrisonburg, VA 22802-2462 USA. yong.zhang@emu.edu. Partially supported by an EMU Summer Research Grant, 2006.

using a divide-and-conquer approach over subgroup chains, Friedl et al. [FM<sup>+</sup>03] introduced the Orbit Coset problem, which they claimed to be an even more general problem including Hidden Subgroup and Hidden Shift<sup>1</sup> as special instances. They called Orbit Coset a quantum generalization of Hidden Subgroup and Hidden Shift, since the definition of Orbit Coset involves quantum functions.

In Section 3, we show that all these related problems are equivalent or reducible to Hidden Subgroup. In particular,

1. Hidden Coset is polynomial-time equivalent to Hidden Subgroup,
2. Orbit Coset is equivalent to Hidden Subgroup if we allow functions in the latter to be quantum functions, and
3. Hidden Shift and Generalized Hidden Shift reduce to instances of Hidden Subgroup over a family of wreath product groups.

Some special cases of these results are already known. It is well-known that Hidden Shift over the cyclic group  $Z_n$  is equivalent to Hidden Subgroup over the dihedral group  $D_n = Z_n \circ Z_2$  (see [vd05] for example), and this fact easily generalizes to any abelian group. Our results apply to general groups, however, including nonabelian groups where a nontrivial semidirect product with  $Z_2$  may not exist. Regarding the relationship between Hidden Shift and Generalized Hidden Shift, Childs and van Dam observed that it is trivial to reduce any instance of Generalized Hidden Shift to Hidden Shift over the same group (and thence to dihedral Hidden Subgroup in the case of abelian groups) in polynomial-time [vd05]. They left open the question, however, of whether any versions of Generalized Hidden Shift with more than two functions are equivalent to any versions of Hidden Subgroup. We make progress towards answering this question in the affirmative. We give a direct "embedding" reduction from Generalized Hidden Shift to Hidden Subgroup such that the original input instances of Generalized Hidden Shift can be recovered efficiently from their images under the reduction. Our reduction runs in polynomial-time provided the number of functions of the input instance is relatively small.

There are a few results in the literature about the complexity of Hidden Subgroup. It is well-known that Hidden Subgroup over abelian groups is solvable in quantum polynomial-time with bounded error [Kita95, Mos99]. Ettinger, Hoyer, and Knill [EHK04] showed that Hidden Subgroup (over arbitrary finite groups) has polynomial quantum query complexity. Arvind and Kunur [AK02] showed that Hidden Subgroup over permutation groups is in the class  $FP^{SP}$  and is thus low for the counting complexity class  $PP$ . In Section 4 we study the relationship between the decision and search versions of Hidden Subgroup, denoted  $HS_D$  and  $HS_S$ , respectively. It is well-known that NP-complete sets such as SAT are self-reducible, which implies that the decision and search versions of NP-complete problems are polynomial-time equivalent. We show this is also the case for Hidden Subgroup and Hidden Shift over permutation groups. Kempe and Shalev have recently given evidence that  $HS_D$  over permutation groups is a difficult problem [KS05]. They showed that under general conditions, various forms of the Quantum Fourier Sampling method are of no help (over classical exhaustive search) in solving  $HS_D$  over permutation groups. Our results yield evidence of a different sort that this problem is difficult; namely, it is just as hard as the search version.

---

<sup>1</sup>They actually called it the Hidden Translation problem.

For Hidden Subgroup over dihedral groups, our results are more modest. We show the search-decision equivalence for dihedral groups of smooth order, i.e., where the largest prime dividing the order of the group is small.

Combining our results in Sections 3 and 4, we obtain nonadaptive program checkers for Hidden Subgroup and Hidden Subgroup<sub>D</sub> over permutation groups. We give the details in Section 5.

## 2 Preliminaries

### 2.1 Group Theory

Background on general group theory and quantum computation can be found in textbooks such as [Sco87] and [NC00].

The wreath product of groups plays an important role in several proofs in this paper. We only need to define a special case of the wreath product.

**Definition 2.1** For any finite group  $G$ , the wreath product  $G \circ \mathbb{Z}_n$  of  $G$  and  $\mathbb{Z}_n = \{0; 1; \dots; n-1\}$  is the set  $\{(g_1; g_2; \dots; g_n; \gamma) \mid g_i \in G; \gamma \in \mathbb{Z}_n\}$  equipped with the group operation such that

$$(g_1; g_2; \dots; g_n; \gamma) \cdot (g'_1; g'_2; \dots; g'_n; \gamma') = (g_{\gamma(1)}g'_1; g_{\gamma(2)}g'_2; \dots; g_{\gamma(n)}g'_n; \gamma + \gamma').$$

We abuse notation here by identifying  $\gamma$  and  $\gamma'$  with cyclic permutations over the set  $\{1; \dots; n\}$  sending  $x$  to  $x + \gamma \bmod n$  and to  $x + \gamma' \bmod n$ , respectively, and identifying 0 with  $n$ .

If  $Z$  is a set, then  $S_Z$  is the symmetric group of permutations of  $Z$ . We define the composition order to be from left to right, i.e., for  $g_1, g_2 \in S_Z$ ,  $g_1 g_2$  is the permutation obtained by applying  $g_1$  first and then  $g_2$ . For  $n \geq 1$ , we abbreviate  $S_{\{1; 2; \dots; n\}}$  by  $S_n$ . Subgroups of  $S_n$  are the permutation groups of degree  $n$ . For a permutation group  $G \leq S_n$  and an element  $i \in \{1; \dots; n\}$ , let  $G^{(i)}$  denote the pointwise stabilizer subgroup of  $G$  that fixes the set  $\{1; \dots; i\}$  pointwise. The chain of the stabilizer subgroups of  $G$  is  $\text{id}_G = G^{(n)} \leq G^{(n-1)} \leq \dots \leq G^{(1)} \leq G^{(0)} = G$ . Let  $C_i$  be a complete set of right coset representatives of  $G^{(i)}$  in  $G^{(i-1)}$ ,  $1 \leq i \leq n$ . Then the cardinality of  $C_i$  is at most  $n - i + 1$  and  $\{c_i \mid c_i \in C_i\}$  forms a strong generator set for  $G$  [Sim70]. Any element  $g \in G$  can be written uniquely as  $g = g_n g_{n-1} \dots g_1$  with  $g_i \in C_i$ . Furst, Hopcroft, and Luks [FHL80] showed that given any generator set for  $G$ , a strong generator set can be computed in polynomial time. For  $X \subseteq \mathbb{Z}$  and  $G \leq S_{\mathbb{Z}}$ , we use  $G_X$  to denote the subgroup of  $G$  that stabilizes  $X$  setwise. It is evident that  $G_X$  is the direct sum of  $S_X$  and  $S_{\mathbb{Z} \setminus X}$ . We are particularly interested in the case when  $G$  is  $S_n$ . In this case, a generating set for  $G_X$  can be easily computed.

Let  $G$  be a finite group. Let  $\mathcal{X}$  be a set of mutually orthogonal quantum states. Let  $\rho : G \rightarrow \mathcal{X}$  be a group action of  $G$  on  $\mathcal{X}$ , i.e., for every  $x \in \mathcal{X}$  the function  $\rho_x : G \rightarrow \mathcal{X}$  mapping  $j$  to  $\rho(x; j)$  is a permutation over  $\mathcal{X}$ , and the map  $h$  from  $G$  to the symmetric group over  $\mathcal{X}$  defined by  $h(x) = \rho_x$  is a homomorphism. We use the notation  $\rho_x$  instead of  $\rho(x; j)$ , when  $\rho$  is clear from the context. We let  $G(j)$  denote the orbit of  $j$  with respect to  $\rho$ , i.e., the set  $\{\rho(x; j) \mid x \in G\}$ , and we let  $G_{j,i}$  denote the stabilizer subgroup of  $j$  in  $G$ , i.e.,  $\{x \in G \mid \rho(x; j) = \rho(x; i)\}$ . Given any positive integer  $t$ , let  $\rho^t$  denote the group action of  $G$  on  $\mathcal{X}^t = \{f(j) \mid j \in \mathcal{X}\}$  defined by  $\rho^t(x; j) = \rho(x; j)^t$ . We need  $\rho^t$  because the input superpositions cannot be cloned in general.

**Definition 2.2** Let  $G$  be a finite group.

1. Given a generating set for  $G$  and a function  $f$  that maps  $G$  to some finite set  $S$  such that the values of  $f$  are constant on a subgroup  $H$  of  $G$  and distinct on each left (right) coset of  $H$ , the Hidden Subgroup problem is to find a generating set for  $H$ . The decision version of Hidden Subgroup, denoted as Hidden Subgroup<sub>D</sub>, is to determine whether  $H$  is trivial. The search version, denoted as Hidden Subgroup<sub>S</sub>, is to find a nontrivial element of  $H$  if there is one.
2. Given a generating set for  $G$  and  $n$  injective functions  $f_1; f_2; \dots; f_n$  defined on  $G$ , with the promise that there is a (necessarily unique) "shift"  $u \in G$  such that for all  $g \in G$ ,  $f_1(g) = f_2(ug)$ ,  $f_2(g) = f_3(ug)$ , ...,  $f_{n-1}(g) = f_n(ug)$ , the Generalized Hidden Shift problem [CvD05] is to find  $u$ . We sometimes denote this problem as  $(n; G)$ -GHS for short. If  $n = 2$ , this problem is called the Hidden Shift problem. The functions  $f_1; \dots; f_n$  are given uniformly via a single function  $F$  such that  $f_i(g) = F(i; g)$  for all  $g \in G$  and  $1 \leq i \leq n$ .
3. Given a generating set for  $G$  and two functions  $f_1$  and  $f_2$  defined on  $G$  such that for some shift  $u \in G$ ,  $f_1(g) = f_2(gu)$  for all  $g$  in  $G$ , the Hidden Coset problem [vdHI03] is to find the set of all such shifts  $u$ . This set is a coset  $Hu$  of a subgroup  $H$  of  $G$ , and we can represent it by giving generators for  $H$  together with one of the  $u$ .
4. Given a generating set for  $G$  and two quantum states  $|j_0\rangle; |j_1\rangle \in \mathbb{C}^G$ , the Orbit Coset problem [FIM<sup>+</sup>03] is to either reject the input if  $G(j_0) \setminus G(j_1) \neq \emptyset$ , or else output both a  $u \in G$  such that  $|j_{-1}\rangle = |j_0\rangle$  and also a generating set for  $G_{j_1}$ .

Van Dam, Hallgren, and Ip give efficient quantum algorithms for various instances of Hidden Coset using Fourier sampling [vdHI03]. Childs and van Dam give a polynomial-time quantum algorithm for  $(M; \mathbb{Z}_N)$ -GHS when  $M \leq N$  for any fixed  $\epsilon > 0$  [CvD05]. Friedl, et al. [FIM<sup>+</sup>03] give polynomial-time quantum algorithms for (among others)  $(2; \mathbb{Z}_p^n)$ -GHS where  $p$  is a fixed prime, and more generally for  $(2; G)$ -GHS if  $G$  is "smoothly solvable," a class of groups that includes solvable groups of bounded exponent and bounded derived series length. The latter results come via algorithms for Orbit Coset.

## 2.2 Program checkers

Let  $\mathcal{P}$  be a computational decision or search problem. Let  $x$  be an input to  $\mathcal{P}$  and  $\mathcal{P}(x)$  be the output of  $\mathcal{P}$ . Let  $P$  be a deterministic program (supposedly) for  $\mathcal{P}$  that halts on all inputs. We are interested in whether  $P$  has any bug, i.e., whether there is some  $x$  such that  $P(x) \neq \mathcal{P}(x)$ . A efficient program checker  $C$  for  $P$  is a probabilistic expected-polynomial-time oracle Turing machine that uses  $P$  as an oracle and takes  $x$  and a positive integer  $k$  (presented in unary) as inputs. The running time of  $C$  does not include the time it takes for the oracle  $P$  to do its computations.  $C$  will output CORRECT with probability  $1 - 1/2^k$  if  $P$  is correct on all inputs (no bugs), and output BUGGY with probability  $1 - 1/2^k$  if  $P(x) \neq \mathcal{P}(x)$ . This probability is over the sample space of all finite sequences of coin flips  $C$  could have tossed. However, if  $P$  has bugs but  $P(x) = \mathcal{P}(x)$ , we allow  $C$  to behave arbitrarily. If  $C$  only queries the oracle nonadaptively, then we say  $C$  is a nonadaptive checker. See Blum and Kannan [BK95] for more details.

### 3 Several Reductions

The Hidden Coset problem is to find the set of all shifts of the two functions  $f_1$  and  $f_2$  defined on the group  $G$ . If  $Hu$  is the coset of all shifts, then  $f_1$  is constant on  $Hu$  (see [vdH03] Lemma 6.1). If we let  $f_1$  and  $f_2$  be the same function chosen appropriately, we get Hidden Subgroup as a special case. On the other hand, if  $f_1$  and  $f_2$  are injective functions, this is Hidden Shift.

**Theorem 3.1** Hidden Coset is polynomial-time equivalent to Hidden Subgroup.

**Proof.** Let  $G$  and  $f_1; f_2$  be the input of Hidden Coset. Let the set of shifts be  $Hu$ , where  $H$  is a subgroup of  $G$  and  $u$  is a coset representative. Define a function  $f$  with domain  $G \times \mathbb{Z}_2$  as follows: for any  $(g_1; g_2; i) \in G \times \mathbb{Z}_2$ ,

$$f(g_1; g_2; i) = \begin{cases} (f_1(g_1); f_2(g_2)) & \text{if } i = 0, \\ (f_2(g_2); f_1(g_1)) & \text{if } i = 1. \end{cases}$$

The values of  $f$  are constant on the set  $K = (Hu^{-1}Hu \cup f_0g) \cup (u^{-1}Hu \cup f_1g)$ , which is a subgroup of  $G \times \mathbb{Z}_2$ . Furthermore, the values of  $f$  are distinct on all left cosets of  $K$ . Given a generating set of  $K$ , there is at least one generator of the form  $(k_1; k_2; 1)$ . Pick  $k_2$  to be the coset representative  $u$  of  $H$ . Form a generating set  $S$  of  $H$  as follows:  $S$  is initially empty. For each generator of  $K$ , if it is of the form  $(k_1; k_2; 0)$ , then add  $k_1$  and  $uk_2u^{-1}$  to  $S$ ; if it is of the form  $(k_1; k_2; 1)$ , then add  $uk_1$  and  $k_2u^{-1}$  to  $S$ . 2

**Corollary 3.2** Hidden Coset has polynomial quantum query complexity.

It was mentioned in Friedl et al. [FM<sup>+</sup>03] that Hidden Coset in general is of exponential (classical) query complexity.

Using a similar approach, we show Generalized Hidden Shift essentially addresses Hidden Subgroup over a different family of groups. We directly embed an instance of  $(n; G)$ -GHS into an instance of Hidden Subgroup over the group  $G \times \mathbb{Z}_n$ . When  $n = 2$ , we get a polynomial-time reduction from Hidden Shift over  $G$  to Hidden Subgroup over  $G \times \mathbb{Z}_2$  (Corollary 3.4). This reduction was claimed independently (without proof) by Childs and Wocjan [CW05].

**Proposition 3.3** For  $n \geq 2$  and  $G$  a group,  $(n; G)$ -GHS reduces to Hidden Subgroup over  $G \times \mathbb{Z}_n$  in time polynomial in  $n + s$ , where  $s$  is the size of the representation of an element of  $G$ . Further, each instance of  $(n; G)$ -GHS can be recovered in polynomial time from its image under the reduction.

**Proof.** The input for Generalized Hidden Shift is a group  $G$  and  $n$  injective functions  $f_1; f_2; \dots; f_n$  defined on  $G$  such that for all  $g \in G$ ,  $f_1(g) = f_2(ug); \dots; f_{n-1}(g) = f_n(ug)$ . Consider the group  $G \times \mathbb{Z}_n$ . Define a function  $f$  such that for any element in  $(g_1; \dots; g_n; i) \in G \times \mathbb{Z}_n$ ,  $f((g_1; \dots; g_n; i)) = (f_{(1)}(g_1); \dots; f_{(n)}(g_n))$ . The function values of  $f$  will be constant and distinct for right cosets of the  $n$ -element cyclic subgroup generated by  $(u; u; \dots; u; u^{1-n}; 1)$ .

Given the  $f$  defined in the last paragraph, it is trivial to recover the original functions  $f_1; \dots; f_n$  by noting that  $f_i(g)$  is the  $i$ 'th component of  $f((g; \dots; g; 0))$ . 2

Corollary 3.4 Hidden Shift reduces to Hidden Subgroup in polynomial time (for arbitrary groups).

Proof. This is the  $n = 2$  case of Proposition 3.3.

2

Van Dam, Hallgren, and Ip [vdHI03] introduced the Shifted Legendre Symbol problem as a natural instance of Hidden Shift. They claimed that assuming a conjecture this problem can also be reduced to an instance of Hidden Subgroup over dihedral groups. By Corollary 3.4, this problem can be reduced to Hidden Subgroup over wreath product groups without any conjecture.

The case where  $n > 2$  in Proposition 3.3 may be more interesting from a structural point of view than a complexity theoretic one. We already know [CvD05] that  $(n;G)$ -GHS reduces to  $(2;G)$ -GHS, simply by ignoring the information provided by the functions  $f_3, \dots, f_n$ . One then gets a polynomial-time reduction from  $(n;G)$ -GHS to Hidden Subgroup over  $G \wr \mathbb{Z}_2$ . Therefore, the reduction in Proposition 3.3 of  $(n;G)$ -GHS to Hidden Subgroup over  $G \wr \mathbb{Z}_n$  only tells us something complexitywise if the instances of Hidden Subgroup over  $G \wr \mathbb{Z}_n$  produced by the reduction turn out to be easier than those of Hidden Subgroup over  $G \wr \mathbb{Z}_2$ . This is conceivable, albeit unlikely. Nonetheless, the fact that  $(n;G)$ -GHS embeds into Hidden Subgroup over  $G \wr \mathbb{Z}_n$  in a natural way is interesting in itself, and may suggest other reductions in a similar vein.

We also note that, unfortunately, it does not seem as though Proposition 3.3 translates the results of [CvD05] into fast quantum algorithms for any new family of instances of Hidden Subgroup over wreath product groups of the form  $\mathbb{Z}_N \wr \mathbb{Z}_M$ , because their algorithm is efficient only if  $M \leq N^{\epsilon}$  for fixed  $\epsilon > 0$ , and our reduction is efficient only if  $M$  is polylogarithmic in  $N$ .

Next we show that Orbit Coset is not a more general problem than Hidden Subgroup either, if we allow the function in Hidden Subgroup to be a quantum function. We need this generalization since the definition of Orbit Coset involves quantum functions, i.e., the ranges of the functions are sets of orthogonal quantum states. In Hidden Subgroup, the function is implicitly considered by most researchers to be a classical function, mapping group elements to a classical set. For the purposes of quantum computation, however, this generalization to quantum functions is natural and does not affect any existing quantum algorithms for Hidden Subgroup.

Proposition 3.5 Orbit Coset is quantum polynomial-time equivalent to Hidden Subgroup.

Proof. Let  $G$  and two orthogonal quantum states  $|j_0\rangle, |j_1\rangle \in \mathbb{C}^2$  be the inputs of Orbit Coset. Define the function  $f : G \wr \mathbb{Z}_2 \rightarrow \mathbb{C}^2$  as follows:

$$f(g_1; g_2) = \begin{cases} |j_1\rangle & \text{if } g_1 = g_2, \\ |j_0\rangle & \text{if } g_1 \neq g_2. \end{cases}$$

The values of the function  $f$  are identical and orthogonal on each left coset of the following subgroup  $H$  of  $G \wr \mathbb{Z}_2$ : If there is no  $u \in G$  such that  $j_1 = j_0 u$ , then  $H = \{g_1, g_2 \mid f(g_1) = f(g_2)\}$ . If there is such a  $u$ , then  $H = \{g_1, g_2 \mid f(g_1) = f(g_2 u)\}$ . For  $i, j \in \{0, 1\}$ , let  $g_i \in G$  be the  $i$ 'th coset representative of  $G_{j_0}$  (i.e.,  $g_i = j_0 g_i$ ), and let  $g_j \in G$  be the  $j$ 'th coset representative of  $G_{j_1}$  (i.e.,  $g_j = j_1 g_j$ ). Then elements of the left coset of  $H$  represented by  $(g_i; g_j)$  will all map to the same value  $|j_i\rangle$  via  $f$ .

2

## 4 Decision versus Search

For any NP-complete problem, its decision version and search version are polynomial-time equivalent. Another problem having this property is Graph Isomorphism [Mat79].

### 4.1 Hidden Subgroup over permutation groups

We adapt techniques in Arvind and Toran [AT01] to show that over permutation groups, Hidden Subgroup also has this property.

**Lemma 4.1** Given (generating sets for) a group  $G = S_n$ , a function  $f : G \rightarrow S$  that hides a subgroup  $H \leq G$ , and a sequence of subgroups  $G_1, \dots, G_k \leq S_n$ , an instance of Hidden Subgroup can be constructed to hide the group  $D = \{f(g; g_1, \dots, g_k) \mid g \in H \setminus G_1 \setminus \dots \setminus G_k\}$  inside  $G \setminus G_1 \setminus \dots \setminus G_k$ .

**Proof.** Define a function  $f^0$  over the direct product group  $G \times G_1 \times \dots \times G_k$  so that for any element  $(g; g_1, \dots, g_k)$ ,  $f^0(g; g_1, \dots, g_k) = (f(g); g_1^{-1}; \dots; g_k^{-1})$ . The values of  $f^0$  are constant and distinct over left cosets of  $D$ . 2

In the following, we will use the tuple  $hG; fi$  to represent a standard Hidden Subgroup input instance, and  $hG; f; G_1, \dots, G_k i$  to represent a Hidden Subgroup input instance constructed as in Lemma 4.1.

We define a natural isomorphism that identifies  $S_n \times \mathbb{Z}_2$  with a subgroup of  $S$ , where  $\phi(i; j) = f(i; j)$  for  $j \in \{1, \dots, ng\}$  and  $\phi(i; j) = f(i; j)$  for  $j \in \{1, 2ng\}$ . This isomorphism can be viewed as a group action, where the group element  $(g_1; g_2)$  maps  $(i; j)$  to  $(g_1(i); (j)g_2)$ . Note that this isomorphism can be efficiently computed in both directions.

**Theorem 4.2** Over permutation groups, Hidden Subgroups is truth-table reducible to Hidden Subgroup<sub>D</sub> in polynomial time.

**Proof.** Suppose  $f$  hides a nontrivial subgroup  $H$  of  $G$ , first we compute a strong generating set for  $G$ , corresponding to the chain  $\text{id}g = G^{(n)} \triangleright G^{(n-1)} \triangleright \dots \triangleright G^{(1)} \triangleright G^{(0)} = G$ . Define  $f^0$  over  $G \times \mathbb{Z}_2$  such that  $f^0$  maps  $(g_1; g_2)$  to  $(f(g_1); f(g_2))$  if  $i$  is 0, and  $(f(g_2); f(g_1))$  otherwise. It is easy to check that for the group  $G^{(i)} \times \mathbb{Z}_2$ ,  $f^0|_{G^{(i)} \times \mathbb{Z}_2}$  hides the subgroup  $H^{(i)} \times \mathbb{Z}_2$ .

Query the Hidden Subgroup<sub>D</sub> oracle with inputs

$$\begin{array}{c} D \\ G^{(i)} \times \mathbb{Z}_2; f^0|_{G^{(i)} \times \mathbb{Z}_2}; (S)_{f(i;1);(j;2)g}; (S)_{f(i;2);(j^0;1)g}; (S)_{f(k;1);(i^0;2)g} \end{array} \quad E$$

for all  $1 \leq i \leq n$ , all  $j; j^0 \in \{1, \dots, ng\}$ , and all  $k; i^0 \in \{1, \dots, ng\}$ .

**Claim 4.3** Let  $i$  be such that  $H^{(i)} = \text{id}g$  and  $H^{(i-1)} \neq \text{id}g$ . For all  $i < j; j^0 \leq n$  and all  $i^0; k; l \leq n$ , there is a (necessarily unique) permutation  $h \in H^{(i-1)}$  such that  $h(i) = j$ ,  $h(j^0) = i$  and  $h(k) = l$  if and only if the query

$$\begin{array}{c} D \\ G^{(i-1)} \times \mathbb{Z}_2; f^0|_{G^{(i-1)} \times \mathbb{Z}_2}; (S)_{f(i;1);(j;2)g}; (S)_{f(i;2);(j^0;1)g}; (S)_{f(k;1);(l^0;2)g} \end{array} \quad E$$

to the Hidden Subgroup<sub>D</sub> oracle answers "nontrivial."

**Proof of Claim .** For any  $j > i$ , there is at most one permutation in  $H^{(i-1)}$  that maps  $i$  to  $j$ . To see this, suppose there are two distinct  $h, h^0 \in H^{(i-1)}$  both of which map  $i$  to  $j$ . Then  $h^0 h^{-1} \in H^{(i)}$  is a nontrivial permutation, contradicting the assumption  $H^{(i)} = \text{fidg}$ . Let  $h \in H^{(i-1)}$  be a permutation such that  $h(i) = j$ ,  $h(j^0) = i$ , and  $h(k) = \cdot$ . Then  $(h; h^{-1}; 1)$  is a nontrivial element in the group  $H^{(i-1)} \cap Z_2 \setminus (S)_{f(i;1);(j;2)g} \setminus (S)_{f(i;2);(j^0;1)g} \setminus (S)_{f(k;1);(\cdot;2)g}$ , and thus the oracle answers "nontrivial."

Conversely, if the oracle answers "nontrivial," then the nontrivial element must be of the form  $(h; h^0; 1)$  where  $h, h^0 \in H^{(i-1)}$ , since the other form  $(h; h^0; 0)$  will imply that  $h$  and  $h^0$  both fix  $i$  and thus are in  $H^{(i)} = \text{fidg}$ . Therefore,  $h$  will be a nontrivial element of  $H^{(i-1)}$  with  $h(i) = j$ ,  $h(j^0) = i$ , and  $h(k) = \cdot$ . This proves the Claim .

Find the largest  $i$  such that the query answers "nontrivial" for some  $j; j^0 > i$  and some  $k; \cdot < i$ . Clearly this is the smallest  $i$  such that  $H^{(i)} = \text{fidg}$ . A nontrivial permutation in  $H^{(i-1)}$  can be constructed by looking at the query results that involve  $G^{(i-1)} \cap Z_2$ . 2

**Corollary 4.4** Over permutation groups, Hidden Subgroup<sub>D</sub> and Hidden Subgroup<sub>S</sub> are polynomial-time equivalent.

Next we show that the search version of Hidden Shift, as a special case of Hidden Subgroup, also reduces to the corresponding decision problem .

**Definition 4.5** Given a generating set for a group  $G$  and two injective functions  $f_1, f_2$  defined on  $G$ , the problem Hidden Shift<sub>D</sub> is to determine whether there is a shift  $u \in G$  such that  $f_1(g) = f_2(gu)$  for all  $g \in G$ .

**Theorem 4.6** Over permutation groups, Hidden Shift<sub>D</sub> and Hidden Shift<sub>S</sub> are polynomial-time equivalent.

**Proof.** We show that if there is a translation  $u$  for the two injective functions defined on  $G$ , we can find  $u$  with the help of an oracle that solves Hidden Shift<sub>D</sub>. First compute the strong generator set  $[ \bigcup_{i=1}^n C_i ]$  of  $G$  using the procedure in [FHL80]. Note that  $[ \bigcup_{i=k}^n C_i ]$  generates  $G^{(k-1)}$  for  $1 \leq k \leq n$ . We will proceed in steps along the stabilizer subgroup chain  $G = G^{(0)} \supset G^{(1)} \supset \dots \supset G^{(n)} = \text{fidg}$ .

**Claim 4.7** With the help of the Hidden Shift<sub>D</sub> oracle, finding the translation  $u_i$  for input  $(G^{(i)}; f_1; f_2)$  reduces to finding another translation  $u_{i+1}$  for input  $(G^{(i+1)}; f_1^0; f_2^0)$ . In particular, we have  $u_i = u_{i+1} \cdot i$ .

**Proof of Claim .** Ask the oracle whether there is a translation for input  $(G^{(i+1)}; f_1 \cdot i_{G^{(i+1)}}; f_2 \cdot i_{G^{(i+1)}})$ . If the answer is yes, then we know  $u_i \in G^{(i+1)}$  and therefore set  $\cdot_i = \text{id}$  and  $u_i = u_{i+1} \cdot i$ .

If the answer is no, then we know that  $u$  is in some right coset of  $G^{(i+1)}$  in  $G^{(i)}$ . For every  $\cdot \in G_{i+1}$ , define a function  $f$  such that  $f(x) = f_2(x \cdot)$  for all  $x \in G^{(i+1)}$ . Ask the oracle whether there is a translation for input  $(G^{(i+1)}; f_1 \cdot i_{G^{(i+1)}}; f)$ . The oracle will answer yes if and only if  $u$  and  $\cdot$  are in the same right coset of  $G^{(i+1)}$  in  $G^{(i)}$ , since

- ( )  $u$  and  $\cdot$  are in the same right coset of  $G^{(i+1)}$  in  $G^{(i)}$
- ( )  $u = u^0 \cdot$  for some  $\cdot^0 \in G^{(i+1)}$
- ( )  $f_1(x) = f_2(xu) = f_2(xu^0) = f(xu^0)$  for all  $x \in G^{(i)}$
- ( )  $u^0$  is the translation for  $(G^{(i+1)}; f_1 \cdot i_{G^{(i+1)}}; f)$ .



Then we set  $i = 1$ .

We apply the above procedure  $n - 1$  times until we reach the trivial subgroup  $G^{(n)}$ . The translation  $u$  will be equal to  $n - n - 1 = 1$ . Since the size of each  $C_i$  is at most  $n - i$ , the total reduction is in classical polynomial time. 2

## 4.2 Hidden Subgroup over dihedral groups

For Hidden Subgroup over dihedral groups  $D_n$ , we can efficiently reduce search to decision when  $n$  has small prime factors. For a fixed integer  $B$ , we say an integer  $n$  is  $B$ -smooth if all the prime factors of  $n$  are less than or equal to  $B$ . For such an  $n$ , the prime factorization can be obtained in time polynomial in  $B + \log n$ . Without loss of generality, we assume that the hidden subgroup is an order-two subgroup of  $D_n$  [EH00].

**Theorem 4.8** Let  $n$  be a  $B$ -smooth number, Hidden Subgroup over the dihedral group  $D_n$  reduces to Hidden Subgroup<sub>D</sub> over dihedral groups in time polynomial in  $B + \log n$ .

**Proof.** Without loss of generality, we assume the generator set for  $D_n$  is  $\langle r, g \rangle$ , where the order of  $r$  and  $g$  are  $n$  and  $2$ , respectively. Let  $p_1^{e_1} p_2^{e_2} \dots p_k^{e_k}$  be the prime factorization of  $n$ . Since  $n$  is  $B$ -smooth,  $p_i \leq B$  for all  $1 \leq i \leq k$ . Let the hidden subgroup  $H$  be  $\langle r^a \rangle$  for some  $a < n$ .

First we find  $a \bmod p_1^{e_1}$  as follows. Query the Hidden Subgroup<sub>D</sub> oracle with input groups (we will always use the original input function  $f$ )  $\langle r^{p_1}; i; \dots; r^{p_1}; r^{p_1-1}i \rangle$ . It is not hard to see that the Hidden Subgroup<sub>D</sub> oracle will answer "nontrivial" only for the input group  $\langle r^{p_1}; r^{m_1}i \rangle$  where  $m_1 = a \bmod p_1$ . The next set of input groups to the Hidden Subgroup<sub>D</sub> oracle are  $\langle r^{p_1^2}; r^{m_1}i; \dots; r^{p_1^2}; r^{(p_1-1)p_1+m_1}i \rangle$ . From the oracle answers we obtain  $m_2 = a \bmod p_1^2$ . Repeat the above procedure until we find  $a \bmod p_1^{e_1}$ .

Similarly, we can find  $a \bmod p_2^{e_2}; \dots; a \bmod p_k^{e_k}$ . A simple usage of the Chinese Remainder Theorem will then recover  $a$ . The total number of queries is  $e_1 p_1 + e_2 p_2 + \dots + e_k p_k$ , which is polynomial in  $\log n + B$ . 2

## 5 Nonadaptive Checkers

An important concept closely related to self-reducibility is that of a program checker, which was first introduced by Blum and Kannan [BK95]. They gave program checkers for some group-theoretic problems and selected problems in  $P$ . They also characterized the class of problems having polynomial-time checkers. Arvind and Toran [AT01] presented a nonadaptive NC checker for Group Intersection over permutation groups. In this section we show that Hidden Subgroup<sub>D</sub> and Hidden Subgroup over permutation groups have nonadaptive checkers.

For the sake of clarity, we give the checker for Hidden Subgroup<sub>D</sub> first. Let  $P$  be a program that solves Hidden Subgroup<sub>D</sub> over permutation groups. The input for  $P$  is a permutation group  $G$  given by its generating set and a function  $f$  that is defined over  $G$  and hides a subgroup  $H$  of  $G$ . If  $P$  is a correct program, then  $P(G; f)$  outputs TRIVIAL if  $H$  is the trivial subgroup of  $G$ , and NONTRIVIAL otherwise. The checker  $C^P(G; f; 0^k)$  checks the program  $P$  on the input  $G$  and  $f$  as follows:

```

Begin
  Compute  $P(G; f)$ .
  if  $P(G; f) = \text{NONTRIVIAL}$ , then
    Use Theorem 4.2 and  $P$  (as if it were bug-free) to search for a nontrivial element  $h$  of  $H$ .
    if  $f(h) = f(\text{id})$ , then
      return CORRECT
    else
      return BUGGY
  if  $P(G; f) = \text{TRIVIAL}$ , then
    Do  $k$  times (in parallel):
      generate a random permutation  $u \in G$ .
      define  $f^0$  over  $G$  such that  $f(g) = f^0(gu)$  for all  $g \in G$ , use  $(G; f; f^0)$  to be an input instance of
Hidden Shift
      use Theorem 3.1 to convert  $(G; f; f^0)$  to an input instance  $(G \rtimes \mathbb{Z}_2; f^0)$  of Hidden Subgroup
      use Theorem 4.2 and  $P$  to search for a nontrivial element  $h$  of the subgroup of  $G \rtimes \mathbb{Z}_2$  that  $f^0$ 
hides.
      if  $h \notin (u^{-1}; u; 1)$ , then return BUGGY
    End-do
    return CORRECT
End

```

**Theorem 5.1** If  $P$  is a correct program for Hidden Subgroup<sub>D</sub>, then  $C^P(G; f; 0^k)$  always outputs CORRECT. If  $P(G; f)$  is incorrect, then  $\Pr[C^P(G; f; 0^k) \text{ outputs CORRECT}] \leq 2^{-k}$ . Moreover,  $C^P(G; f; 0^k)$  runs in polynomial time and queries  $P$  nonadaptively.

**Proof.** If  $P$  is a correct program and  $P(G; f)$  outputs NONTRIVIAL, then  $C^P(G; f; 0^k)$  will find a nontrivial element of  $H$  and outputs CORRECT. If  $P$  is a correct program and  $P(G; f)$  outputs TRIVIAL, then the function  $f^0$  constructed by  $C^P(G; f; 0^k)$  will hide the two-element subgroup  $\{f(\text{id}; \text{id}; 0); (u; u^{-1}; 1)g\}$ . Therefore,  $C^P(G; f; 0^k)$  will always recover the random permutation  $u$  correctly, and output CORRECT.

On the other hand, if  $P(G; f)$  outputs NONTRIVIAL while  $H$  is actually trivial, then  $C^P(G; f; 0^k)$  will fail to find a nontrivial element of  $H$  and thus output BUGGY. If  $P(G; f)$  outputs TRIVIAL while  $H$  is actually nontrivial, then the function  $f^0$  constructed by  $C^P(G; f; 0^k)$  will hide the subgroup  $(H \cup u^{-1}H \cup f^0g) \cup (u^{-1}H \cup H \cup \text{times } f)g$ .  $P$  correctly distinguishes  $u$  and other elements in the coset  $Hu$  only by chance. Since the order of  $H$  is at least 2, the probability that  $C^P(G; f; 0^k)$  outputs CORRECT is at most  $2^{-k}$ .

Clearly,  $C^P(G; f; 0^k)$  runs in polynomial time. The nonadaptiveness follows from Theorem 4.2.  $\square$

Similarly, we can construct a nonadaptive checker  $C^P(G; f; 0^k)$  for a program  $P(G; f)$  that solves Hidden Subgroup over permutation groups. The checker makes  $k$  nonadaptive queries.

```

Begin
  Run  $P(G; f)$ , which outputs a generating set  $S$ .
  Verify that elements of  $S$  are indeed in  $H$ .
  Do  $k$  times (in parallel):
    generate a random element  $u \in G$ .
    define  $f^0$  over  $G$  such that  $f(g) = f^0(gu)$  for all  $g \in G$ , use  $(G; f; f^0)$  to be an input instance of
Hidden Coset

```

```

    use Theorem 3.1 to convert  $(G; f; f^0)$  to an input instance  $(G \circ \mathbb{Z}_2; f^0)$  of Hidden Subgroup
    P  $(G \circ \mathbb{Z}_2; f^0)$  will output a set  $S^0$  of generators and a coset representative  $u^0$ 
    if  $S$  and  $S^0$  don't generate the same group or  $u$  and  $u^0$  are not in the same coset of  $S$ , then
    return BUGGY
End-do
return CORRECT
End

```

The proof of correctness for the above checker is very similar to the proof of Theorem 5.1.

## 6 Further Research

Each of the problems we have looked at in this paper can vary widely in complexity, depending on the type underlying group. So it is, for instance, with Hidden Subgroup, which yields to quantum computation in the abelian case but remains apparently hard in all but a few nonabelian cases. The reductions of these problems to Hidden Subgroup given in this paper all involve taking wreath products, which generally increases both the size and the "difficulty" of the group considerably. (For example,  $G \circ H$  is never abelian unless one of the groups is abelian and the other is trivial, whence  $G \circ H = G$  or  $G \circ H = H$ .) It is useful in general to find reductions between these problems that map input groups to output groups that are of similar difficulty, e.g., abelian  $\nleftrightarrow$  abelian, solvable  $\nleftrightarrow$  solvable, etc. This would provide a finer classification of the complexities of these problems.

The embedding aspect of the reduction in Proposition 3.3 suggests a stronger question: given any function  $f$  on  $G \circ \mathbb{Z}_n$  that hides some subgroup generated by  $(u; ::; u; u^{1/n}; 1)$  for some  $u$  (where the function is not necessarily the one constructed by the reduction), can one efficiently recover an instance of  $(n; G)$ -GHS that maps via the reduction to an instance of Hidden Subgroup over  $G \circ \mathbb{Z}_n$  with the same hidden subgroup? A yes answer would show that Generalized Hidden Shift is truly a special case of Hidden Subgroup, and as a corollary would show that these instances of Hidden Subgroup over  $G \circ \mathbb{Z}_n$  for small  $n$  (polynomial in the size of elements of  $G$ ) reduces to Hidden Subgroup over  $G \circ \mathbb{Z}_2$ .

## 7 Acknowledgments

We thank Andrew Childs and Wim van Dam for valuable comments on a preliminary version of this paper.

## References

- [AK02] V. Arvind and Piyush P. Kurur. Graph Isomorphism is in SPP. In Proceedings of the 43rd IEEE Symposium on Foundations of Computer Science, New York, 2002. IEEE.
- [AT01] V. Arvind and J. Toran. A nonadaptive NC checker for permutation group intersection. Theoretical Computer Science, 259:597{611, 2001.
- [BK95] M. Blum and S. Kannan. Designing programs that check their work. Journal of the ACM, 42(1):269{291, 1995.

- [CvD 05] A. Childs and W. van Dam. Quantum algorithm for a generalized hidden shift problem. quant-ph/0507190, 2005. To appear in SODA 2007.
- [CW 05] A. Childs and P. Wocjan. On the quantum hardness of solving isomorphism problems as nonabelian hidden shift problems. quant-ph/0510185, 2005.
- [EH 00] M. Ettinger and P. Hoyer. On quantum algorithms for noncommutative hidden subgroups. *Advances in Applied Mathematics*, 25:239{251, 2000.
- [EHK 04] M. Ettinger, P. Hoyer, and E. Knill. The quantum query complexity of the hidden subgroup problem is polynomial. *Information Processing Letters*, 91(1):43{48, 2004.
- [FHL80] M. L. Furst, J. E. Hopcroft, and E. M. Luks. Polynomial-time algorithms for permutation groups. In *Proceedings of the 21st IEEE Symposium on Foundations of Computer Science*, pages 36{41, 1980.
- [FM<sup>+</sup> 03] K. Friedl, G. Ivanyos, F. Magniez, M. Santha, and P. Sen. Hidden translation and orbit coset in quantum computing. In *Proceedings of the 35th ACM Symposium on the Theory of Computing*, pages 1{9, 2003.
- [Joz00] R. Jozsa. Quantum factoring, discrete algorithm and the hidden subgroup problem, 2000. Manuscript.
- [Kit95] A. Yu. Kitaev. Quantum measurements and the Abelian Stabilizer problem. quant-ph/9511026, 1995.
- [KS05] J. Kempe and A. Shalev. The hidden subgroup problem and permutation group theory. In *Proceedings of the Sixteenth Annual ACM-SIAM Symposium on Discrete algorithms*, pages 1118{1125, 2005.
- [Lom 04] C. Lomont. The hidden subgroup problem - review and open problems. quant-ph/0411037, 2004.
- [Mat79] R. Mathon. A note on the graph isomorphism counting problem. *Information Processing Letters*, 8:131{132, 1979.
- [Mos99] M. Mosca. Quantum Computer Algorithms. Ph.D. thesis. University of Oxford, 1999.
- [NC 00] M. A. Nielsen and I. L. Chuang. *Quantum Computation and Quantum Information*. Cambridge University Press, 2000.
- [Reg04] O. Regev. Quantum computation and lattice problems. *SIAM Journal on Computing*, 33(3):738{760, 2004.
- [Sco87] W. R. Scott. *Group Theory*. Dover Publications, Inc., 1987.
- [Sim 70] C. C. Sims. Computational methods in the study of permutation groups. *Computational problems in abstract algebra*, pages 169{183, 1970.
- [vDHI03] W. van Dam, S. Hallgren, and L. Ip. Quantum algorithms for some hidden shift problems. In *Proceedings of the 14th annual ACM-SIAM symposium on Discrete algorithms*, pages 489{498, 2003.