

UG-FT-63/96
 hep-ph/9607311
 July 1996

Invariant analysis of CP violation

F. del Aguila, J. A. Aguilar-Saavedra
Departamento de Física Teórica y del Cosmos
Universidad de Granada
18071 Granada, Spain

M. Zralek
Field Theory and Particle Physics Dept.
University of Silesia
40-007 Katowice, Poland

Abstract

The invariant formulation of CP violation involves the generation of sets of invariant constraints for CP conservation, the manipulation of their expressions and the identification of complete and minimal subsets of such constraints. In this paper we present a collection of subroutines to deal with these three tasks in a fast, reliable and systematic way, with examples for the leptonic sector.

PACS: 11.30.Er, 12.15.Ff, 14.60.Pq, 14.80.-j

Keywords: CP violation, quark and lepton masses and mixings

1 Introduction

The observed CP violation in the $K^0 - \bar{K}^0$ system [1] is related to the presence of complex phases in the mixing matrix describing the quark gauge couplings in the mass-eigenstate basis in the Standard Model (SM) [2]. However, not all the phases in the mixing matrices are CP violating. Some of them can be eliminated redefining the fermion phases. In the SM with three quark generations, the 6 phases of the 3×3 unitary mixing matrix V reduce to 1 after an appropriate field redefinition. For this case it has been identified a quantity invariant under weak quark basis transformations whose vanishing characterizes CP conservation [3]:

$$\begin{aligned} \det [M_u M_u^\dagger, M_d M_d^\dagger] &= -2i(m_t^2 - m_c^2)(m_t^2 - m_u^2)(m_c^2 - m_u^2)(m_b^2 - m_s^2) \\ &\times (m_b^2 - m_d^2)(m_s^2 - m_d^2) \operatorname{Im} (V_{ud} V_{cd}^* V_{cs} V_{us}^*) = 0, \end{aligned} \quad (1)$$

where m_i is the mass of the quark i and V_{ij} is the ij entry of the Cabibbo-Kobayashi-Maskawa (CKM) matrix [2]. This invariant formulation of CP violation makes apparent

the necessary and sufficient conditions for CP conservation, giving the size of CP violation. It also allows to decide if CP is conserved in any weak basis, motivating model building and helping to understand eventually the origin of CP violation if a definite model (weak basis) is physically distinguished.

In general, *i.e.* in extended models with extra generations and/or vector-like quarks and/or right-handed (Majorana) neutrinos, it is difficult to find such a minimal set of necessary and sufficient invariant conditions. In this paper we present a collection of subroutines for *Mathematica* [4] which carries out this task in a fast and systematic way. They are used (i) to calculate products of mass (sub)matrices giving rise to expressions invariant under weak fermion basis transformations, (ii) to do the symbolic manipulations and to solve the constraints resulting from equating these invariants to zero, and (iii) to verify that the set of necessary conditions for CP conservation generated in this way is sufficient and minimal (this is to say that this set does not contain any smaller subset of sufficient conditions). Although these subroutines are written for the leptons including Majorana neutrinos, they can be easily adapted to analyze CP violation in the quark sector [5, 6]. They can be also generalized to study extended gauge theories as left-right models, and/or (supersymmetric) scalar gauge couplings. On the other hand, the computer calculations use to be more reliable than the manual ones. For example, we have revised the two more complicated cases studied in Ref. [7]. In both cases we find CP violating solutions which were overlooked there. In Section 2 we comment on the main theoretical features and in Section 3 we describe the subroutines and apply them to these two cases.

2 Theory and general features

Let us assume the SM with n_L left-handed and n_R right-handed neutrinos and define

$$\psi_L = \begin{pmatrix} \nu_L \\ (\nu^c)_L \end{pmatrix}, \quad \psi_R = \begin{pmatrix} (\nu^c)_R \\ \nu_R \end{pmatrix}, \quad (2)$$

where $\nu^c = i\gamma^2\nu^*$ and $\psi_{L,R}$ are $n_L + n_R$ component vectors describing the n_L left-handed and n_R right-handed neutrinos. Then the mass term reads

$$-\mathcal{L}_{mass} = \bar{l}_L M_l l_R + \frac{1}{2} \bar{\psi}_L M_\nu \psi_R + \text{h.c.}, \quad (3)$$

where $l_{L,R}$ are n_L component vectors describing the n_L charged leptons and M_l an arbitrary $n_L \times n_L$ complex matrix, whereas

$$M_\nu = \begin{matrix} n_L \{ \\ n_R \{ \end{matrix} \begin{pmatrix} \overbrace{M_L}^{n_L} & \overbrace{M_D}^{n_R} \\ \overbrace{M_D^T}^{n_R} & \overbrace{M_R}^{n_R} \end{pmatrix} \quad (4)$$

is an arbitrary $(n_L + n_R) \times (n_L + n_R)$ complex symmetric matrix. This Lagrangian is invariant under a CP transformation leaving the gauge $SU(2)_L \times U(1)_Y$ interactions unchanged [8]

$$l_L \rightarrow U_L C l_L^*, \quad l_R \rightarrow U_R^l C l_R^*, \quad \nu_L \rightarrow U_L C \nu_L^*, \quad \nu_R \rightarrow U_R^\nu C \nu_R^*, \quad (5)$$

where C is the Dirac charge conjugation matrix and $U_L, U_R^l (U_R^\nu)$ are $n_L \times n_L$ ($n_R \times n_R$) unitary matrices, if

$$U_L^\dagger M_l U_R^l = M_l^*, \quad U_L^\dagger M_L U_L^* = M_L^*, \quad U_L^\dagger M_D U_R^\nu = M_D^*, \quad U_R^{\nu T} M_R U_R^\nu = M_R^*. \quad (6)$$

Eqs. (6) are necessary and sufficient conditions for CP conservation. From these equations, one can write necessary conditions for CP conservation which do not require the knowledge of the unitary matrices involved in the definition of the CP transformation. Thus, the products of mass matrices M_l, M_L, M_D, M_R are classified in three classes $G_1 \equiv G_L, G_2 \equiv G_R^l, G_3 \equiv G_R^\nu$, depending under which unitary matrix (U_L, U_R^l, U_R^ν , respectively) transform,

$$\begin{aligned} G_1 &= \{A_{L1} \equiv M_l M_l^\dagger, A_{L2} \equiv M_L M_L^\dagger, A_{L3} \equiv M_D M_D^\dagger, A_{Li} A_{Lj}, M_L M_l^* M_l^T M_L^\dagger, \\ &\quad M_L M_D^* M_D^T M_L^\dagger, M_L M_D^* M_R M_D^\dagger, M_D M_R^\dagger M_D^T M_L^\dagger, M_D M_R^\dagger M_R M_D^\dagger, \dots\}, \\ G_2 &= \{A_l \equiv M_l^\dagger M_l, A_l^2, M_l^\dagger M_L M_L^\dagger M_l, M_l^\dagger M_D M_D^\dagger M_l, \dots\}, \\ G_3 &= \{A_{\nu 1} \equiv M_D^\dagger M_D, A_{\nu 2} \equiv M_R^\dagger M_R, A_{\nu i} A_{\nu j}, M_D^\dagger M_l M_l^\dagger M_D, M_D^\dagger M_L M_L^\dagger M_D, \\ &\quad M_D^\dagger M_L M_D^* M_R, M_R^\dagger M_D^T M_L^\dagger M_D, M_R^\dagger M_D^T M_D^* M_R, \dots\}. \end{aligned} \quad (7)$$

The trace and determinant of any of such products or their sums within the same class do not change under unitary transformations due to their cyclic and factorization properties, respectively. Then CP conservation (Eq. (6)) implies that the trace and the determinant of any linear combination g of elements of the same class is real,

$$\text{Im tr } g = 0, \quad \text{Im det } g = 0. \quad (8)$$

To find which subsets of these conditions are also sufficient has to be worked out case by case. In practice, we are interested in identifying minimal subsets with these properties. We proceed as follows.

2.1 Generation of invariant products with the same transformation properties

The elements of G_i in Eq. (7) must be generated using the mass matrices

$$\{M_l, M_l^T, M_l^*, M_l^\dagger, M_L, M_L^\dagger, M_D, M_D^T, M_D^*, M_D^\dagger, M_R, M_R^\dagger\}. \quad (9)$$

(Note that $M_{L,R}$ are symmetric.) A sequence S of order n is an allowed product of n of such matrices. A product of two sequences $S_a S_b$ is allowed if $S'_a = V_a S_a V_a^\dagger$, $S'_b = V_b S_b V_b^\dagger$ and $V'_a = V_b$. Hence the sequences of order 2 are

$$\begin{aligned} & \{M_l M_l^\dagger, M_l^T M_l^*, M_l^T M_L^\dagger, M_l^T M_D^*, M_l^* M_l^T, M_l^\dagger M_l, M_l^\dagger M_L, M_l^\dagger M_D, \\ & M_L M_l^*, M_L M_L^\dagger, M_L M_D^*, M_L^\dagger M_l, M_L^\dagger M_L, M_L^\dagger M_D, M_D M_D^\dagger, M_D M_R^\dagger, \\ & M_D^T M_l^*, M_D^T M_L^\dagger, M_D^T M_D^*, M_D^* M_D^T, M_D^* M_R, M_D^\dagger M_l, M_D^\dagger M_L, M_D^\dagger M_D, \\ & M_R M_D^\dagger, M_R M_R^\dagger, M_R^\dagger M_D^T, M_R^\dagger M_R\}. \end{aligned} \quad (10)$$

A sequence S , with $S' = V S V^\dagger$ is an element of $G_{1,2,3}$ in Eq. (7) if $V = V' = U_L, U_R^l, U_R^\nu$, respectively. Then Eq. (6) implies that the order of the elements of G_i is even and that the sequences in G_i can be constructed with the biproducts in Eq. (10). These elements are generated order by order. The elements of order n are the allowed products of the sequences of order $n-2$ which begin with M_l , M_L or M_D for G_1 , M_l^\dagger for G_2 and M_D^\dagger or M_R^\dagger for G_3 (see Eq. (6)), times the biproducts in Eq. (10) which end with M_l^\dagger , M_L^\dagger or M_D^\dagger for G_1 , M_l for G_2 and M_D or M_R for G_3 .

2.2 Solution of invariant constraints

Once the elements of G_i are generated, we have to solve the nontrivial conditions in Eq. (8) up to a given order. This means to find the relations among the parameters fixing $M_{l,L,D,R}$ implied by these conditions. The order is increased until there is no CP violating solution. In the examples discussed later we need to consider conditions involving sequences of order 4, 6 and 8. These constraints are easier to solve if the mass matrices are conveniently parametrized. Under a change of weak basis,

$$\begin{aligned} M'_l &= W_L M_l W_R^{l\dagger}, \quad M'_L = W_L M_L W_L^T, \\ M'_D &= W_L M_D W_R^{\nu\dagger}, \quad M'_R = W_R^{\nu\dagger} M_R W_R^{\nu\dagger}. \end{aligned} \quad (11)$$

Hence, as the constraints do not depend on the choice of weak basis, we can choose the unitary matrices $W_L, W_R^{l,\nu}$ appropriately and assume M_l and M_R diagonal with nonnegative real elements, whereas M_L is complex and symmetric and M_D complex and arbitrary. The number and difficulty of the equations grow with the order of the sequences. Generically *Mathematica* uses too much memory and time to solve simultaneously more than 5 conditions. In this case one solves the equations of lowest order first and inserts the solutions in the remaining equations, which can then be solved more easily.

2.3 Minimal subset of invariant constraints

The last subroutine verifies if a solution of a set of conditions in Eq. (8) is CP conserving. A solution s is a set of relations among the parameters fixing the mass matrices $M_{l,L,D,R}$. Let $M_{l,L,D,R}^{(s)}$ be the mass matrices satisfying these relations. We generate random numbers for their independent parameters denoting the corresponding mass matrices $\tilde{M}_{l,L,D,R}^{(s)}$. These matrices conserve CP if it exists a unitary matrix $\tilde{U}^{(s)}$ preserving $\tilde{M}_l^{(s)}$ and such that

$$\tilde{U}^{(s)} \tilde{M}_\nu^{(s)} \tilde{U}^{(s)T} = \tilde{M}_\nu^{(s)*}. \quad (12)$$

If this matrix can be constructed, we say that s conserves CP. It is highly improbable that there is a relation among the random parameters in $\tilde{M}_{l,L,D,R}^{(s)}$ such that the matrices $M_{l,L,D,R}^{(s)}$ violate CP but $\tilde{M}_{l,L,D,R}^{(s)}$ do not. On the other hand, if Eq. (12) is not satisfied, the solution s is said to violate CP.

Let us drop the superscripts from now on. The existence of U is determined in two steps. Step 1 guarantees that if U exists, it is diagonal, and step 2 checks if there is a diagonal unitary matrix satisfying Eq. (12). In the convenient basis and for a given solution s , U is block diagonal with diagonal submatrices of dimension the multiplicity m_i and μ_i of the eigenvalues of M_l and M_R respectively,

$$U = \begin{pmatrix} \boxed{(m_1 \times m_1)} & & & & & \\ & \boxed{(m_2 \times m_2)} & & & & \\ & & \ddots & & & \\ & & & \boxed{(\mu_1 \times \mu_1)} & & \\ & & & & \boxed{(\mu_2 \times \mu_2)} & \\ & & & & & \ddots \end{pmatrix}, \quad (13)$$

with $\sum m_i = n_L$, $\sum \mu_i = n_R$.

If there is no degeneracy U is diagonal and we go to step 2: Eq. (12) is fulfilled if $\forall i > j$,

$$\Delta_{ij} \equiv \arg M_{ii} - \arg M_{ij} + \arg M_{jj} - \arg M_{ji} = 0, \pi. \quad (14)$$

If any $M_{ij} = 0$, Δ_{ij} is zero for $\arg M_{ij}$ ($= \arg M_{ji}$) is conventionally defined by Eqs. (14). On the other hand, if some diagonal elements $M_{i_1 i_1} = \dots = M_{i_k i_k} = 0$, we consider $\arg M_{i_1 i_1}, \dots, \arg M_{i_k i_k}$ arbitrary but fixed. We regard Eqs. (14) as a system of equations in the variables $\delta_i \equiv \arg M_{ii}$. Then CP is conserved if and only if the full system of Eqs. (14) is compatible.

If there is degeneracy we can fix the weak basis to ensure that U is diagonal and then go to step 2. This involves the most delicate casuistry, and it has to be done and

programmed for each dimension n_L, n_R . For small dimensions it can be easier to do it by hand. Let us discuss the simplest case: $n_L = 1, n_R = 2$, and the 2×2 matrix M_R diagonal, real, nonnegative and degenerate. Then U has the general form

$$U = \begin{pmatrix} e^{-i\delta_L} & 0 \\ 0 & U_R^T \end{pmatrix}. \quad (15)$$

- If M_R is identically zero, U_R is an arbitrary unitary matrix. There are different ways to fix the weak basis and guarantee that U_R is diagonal. We choose to diagonalize $M_D^\dagger M_D$.
 - If $M_D^\dagger M_D$ is nondegenerate, we transform M accordingly and go to step 2.
 - If $M_D^\dagger M_D$ is degenerate, it is identically zero because M_D is a 1×2 matrix. Then M_D is also identically zero and there is an extra flavour symmetry, and Eq. (12) is satisfied taking U_R equal to the identity.
- If M_R is nonzero, U_R is a real orthogonal matrix. In this case we choose to diagonalize $(\text{Im } M_D)^T (\text{Im } M_D)$ or $(\text{Re } M_D)^T (\text{Re } M_D)$ if the former is degenerate.
 - If one of them is nondegenerate, we transform M accordingly and go to step 2. (For convenience only, if $M_L = 0$ we also require $M_D M_D^T$ to be real and positive. This fixes δ_L . If $M_D M_D^T = 0$ there is a flavour symmetry.)
 - If both are degenerate, as above they are identically zero. M_D is also zero and there is again an extra flavour symmetry. Similarly Eq. (12) is fulfilled with U_R equal to the identity.

3 Examples

In this section we present a description of the different subroutines in the package **CPllep**. Some of them require the subroutines **DiagonalizeH** and **DiagonalizeS** defined in the package **Diagon** [9]. **DiagonalizeH** is a subroutine which diagonalizes hermitian matrices, returning orthonormal eigenvectors even in the case of degenerate eigenvalues¹. **DiagonalizeS** diagonalizes general complex symmetric matrices M_s with a congruent transformation $M_s \rightarrow U M_s U^T = D$. Let us show how **CPllep** works in two examples. (Definitions are given in the *Appendix*.)

¹The built-in function **Eigensystem** may give non-orthogonal eigenvectors

3.1 Case $n_L = 1, n_R = 2$

The list

```
l1={a[10],a[11],a[12],a[13],a[20],a[23],a[30],a[31],a[32],a[33],
a[40],a[43]}
```

is the computer representation of the mass matrices in Eq. (9). We define an adequate output format for $\mathbf{a}[i]$ so that the expressions can be more easily understood. The rules for the generation of invariants are embodied in the definition of an associative function \mathbf{f} , with an arbitrary number of arguments $\mathbf{a}[i_1], \dots, \mathbf{a}[i_m]$ ordered as the corresponding matrix product $\mathbf{a}[i_1] \cdots \mathbf{a}[i_m]$. \mathbf{f} is taken to be zero if any of the products $\mathbf{a}[i_1]\mathbf{a}[i_2], \dots, \mathbf{a}[i_{m-1}]\mathbf{a}[i_m]$ is not allowed (see Eq. (10)). Then the function \mathbf{inv} checks if the product $\mathbf{f}[\mathbf{a}[i_1], \dots, \mathbf{a}[i_m]]$ transforms with a matrix and its adjoint, and returns again its argument if it does or 0 if it does not. The lists obtained in this way are multiplied with \mathbf{Outer} .

```
<<cplep.m;
l2[1]=Union[Flatten[Outer[f,cl1ini,l1]]];
l2[2]=Union[Flatten[Outer[f,cl2ini,l1]]];
l2[3]=Union[Flatten[Outer[f,cl3ini,l1]]];
l3[1]=Union[Flatten[Outer[f,l2[1],l1]]];
l3[2]=Union[Flatten[Outer[f,l2[2],l1]]];
...
l6[3]=Union[Flatten[Outer[f,l5[3],l1]]];

i4[1]=Union[inv[l4[1]]];
i4[2]=Union[inv[l4[2]]];
i4[3]=Union[inv[l4[3]]];
i6[1]=Union[inv[i6[1]]];
i6[2]=Union[inv[i6[2]]];
i6[3]=Union[inv[i6[3]]];
```

In this example it is necessary to consider only sequences up to order 6. In order to obtain the invariant constraints for $n_L = 1, n_R = 2$, we introduce the convenient parametrization for $\mathbf{M}_L, \mathbf{M}_L, \mathbf{M}_D, \mathbf{M}_R$ and define \mathbf{M}_n , the neutrino mass matrix in Eq. (4). Random numerical values for the parameters are also generated for later use.

```
Ml:={{e1}};ML={{n1}};MD={{Re[n2]+I Im[n2],Re[n3]+I Im[n3]}};
MR={{n4,0},{0,n5}}; Mn=Transpose[Join[Transpose[Join[ML,
Transpose[MD]]], Transpose[Join[MD,MR]]]]];
```

```

ev1={e1->Random[],n1->Random[],Re[n2]->Random[Real,{-1,1}],
Im[n2]->Random[Real,{-1,1}],Re[n3]->Random[Real,{-1,1}],
Im[n3]->Random[Real,{-1,1}],n4->Random[],n5->Random[]}

```

Now to identify those constraints in Eq. (8) which are not identically zero, we define the functions `Looktrace` and `Lookdet`. Their first argument `l` is a list of sequences, whereas the other arguments are the mass matrices with random entries. These are required to check if the constraint is identically zero. `Looktrace` looks for the elements g of `l` which satisfy $\text{Im tr } g \neq 0$. `Lookdet` first finds all non-hermitian combinations $g - g'$ and then, returns those with $\text{Im det}(g - g') \neq 0$. Finally `Newecs` calculates the non-trivial constraints returned by `Looktrace` and `Lookdet` as a function of the convenient parameters (see the *Appendix* for a detailed description of its arguments). Thus

```

Looktrace[i4[1],Ml/.ev1,ML/.ev1,MD/.ev1,MR/.ev1];
Newecs[{},%,Ml,ML,MD,MR,{e1,n1,n2,n3,n4,n5},{n2,n3}]
ecs={%[[3,2]]};

```

returns

$$\text{Im tr } (M_D M_R^\dagger M_D^T M_L^\dagger) = 2n_1(n_4 \text{Im } n_2 \text{Re } n_2 + n_5 \text{Im } n_3 \text{Re } n_3). \quad (16)$$

The traces of the other elements of `i4[1]`, `i4[2]` and `i4[3]` are proportional to the trace in Eq. (16). Similarly,

```

Looktrace[i6[1],Ml/.ev1,ML/.ev1,MD/.ev1,MR/.ev1];
Newecs[ecs,%,Ml,ML,MD,MR,{e1,n1,n2,n3,n4,n5},{n2,n3}]
AppendTo[ecs,%[[3,2]]];

```

gives

$$\text{Im tr } (M_D M_R^\dagger M_R M_R^\dagger M_D^T M_L^\dagger) = 2n_1(n_4^3 \text{Im } n_2 \text{Re } n_2 + n_5^3 \text{Im } n_3 \text{Re } n_3). \quad (17)$$

The traces of the remaining sequences in `i6[1]`, `i6[2]` and `i6[3]` do not give new equations. Finally

```

Lookdet[i4[3],Ml/.ev1,ML/.ev1,MD/.ev1,MR/.ev1];
Newecs[ecs,%,Ml,ML,MD,MR,{e1,n1,n2,n3,n4,n5},{n2,n3},det->True]
AppendTo[ecs,%[[3,3]]];

```

returns

$$\begin{aligned}
\text{Im det}(M_D^\dagger M_D M_R^\dagger M_R - M_R^\dagger M_D^T M_D^* M_R) &= 2n_4 n_5 (n_4 - n_5) (n_4 + n_5) \\
&\times (\text{Im } n_2 \text{Re } n_3 - \text{Im } n_3 \text{Re } n_2) \\
&\times (\text{Im } n_2 \text{Im } n_3 + \text{Re } n_2 \text{Re } n_3). \quad (18)
\end{aligned}$$

When we consider that the set of constraints may be complete, we use **Reduce** to find all the solutions. In this case we try with Eqs. (16–18) equal to zero. **Reduce** gives a lot of redundant solutions, often repeated, for instance $n1==0 \ \&\& \ n4==0$ and $n1==0 \ \&\& \ n4==0 \ \&\& \ n5==0$, and some inconsistent solutions, like $\text{Re}[n3]==I \ \text{Re}[n2]$. The function **Eliminatesols** gets rid of the redundant solutions; whereas the inconsistent solutions are eliminated by inspection.

```
sol0=Reduce[ecs=={0,0,0}];
<<Algebra/ReIm.m;
e1/: Positive[e1] = True;n1/: Positive[n1] = True;
n4/: Positive[n4] = True;n5/: Positive[n5] = True;
sol1=Eliminatesols[sol0/._!=0->True];
sol2=sol1/.{(Re[_]==Complex[_,_] x_/;Im[x]==0)->False,
(Im[_]==Complex[_,_] x_/;Im[x]==0)->False};
```

In this case, **Reduce** gives us 198 solutions (**sol0**). Many of them are redundant and we need to keep only 32 (**sol1**). 6 of them are inconsistent and are eliminated in **sol2**. To verify whether the former set is complete, we use the subroutines **Red12** and **LookCP**. **Red12** writes the mass matrix **Mn** in the basis in which *U* is diagonal, if it exists. **LookCP** then returns **True** or **False** depending on whether *U* exists.

Although the whole process has been described in the previous section, we want to point out a little trick used in **LookCP**. When trying to solve the system of equations $\Delta_{ij} = 0, \pi$ in Eqs. (14), one could consider instead to solve the system of equations $\sin \Delta_{ij} = 0$. However, *Mathematica* does not give correct results in this case. For this reason we look for a subset of *linearly independent* equations in Eqs. (14), and solve these equations equated to zero (it can be done always if the equations are independent, because we can always redefine the variables $\delta_i = \arg M_{ii}$ conveniently). Then the solution is substituted in the complete set of equations, checking whether they are equal to $0, \pi$.

We check if any of the 26 solutions in **sol2** violates CP using a loop. It is initialized with

```
m[number_] := Mn/.ToRules[sol2[[number]]]/.ev1;
i=0;
```

and for each solution we run

```
++i;LookCP[Red12[m[i]]]
```

The result is that none of the solutions in **sol2** violates CP. So the set of invariant constraints is complete. We could try to take away any of the equations in **ecs** and repeat the same process, but we would find CP violating solutions. So the set is also minimal.

3.2 Case $n_L = 2, n_R = 1$

This case is more difficult to solve because more invariant constraints are necessary. As we pointed out in Section 2, the computer memory required to solve all the equations simultaneously is too big, so we have to use a different approach. First we solve the condition

$$\text{Im det}(M_L M_L^\dagger M_l M_l^\dagger - M_L M_l^* M_l^T M_L^\dagger) = 0. \quad (19)$$

Then for each solution of Eq. (19) we proceed as in the former example but restricting the general form of the mass matrices to fulfill this particular solution. For this case we have found that

$$\begin{aligned} \text{Im tr}(M_D^\dagger M_L M_D^* M_R) &= 0, \\ \text{Im tr}(M_R^\dagger M_D^T M_L^\dagger M_L M_L^\dagger M_D) &= 0, \\ \text{Im tr}(M_l M_l^\dagger M_L M_l^* M_l^T M_D^* M_R M_D^\dagger) &= 0, \\ \text{Im det}(M_L M_L^\dagger M_l M_l^\dagger - M_L M_l^* M_l^T M_L^\dagger) &= 0, \\ \text{Im det}(M_D M_D^\dagger M_L M_L^\dagger - M_L M_D^* M_D^T M_L^\dagger) &= 0, \\ \text{Im det}(M_D M_D^\dagger M_l M_l^\dagger - M_L M_D^* M_D^T M_L^\dagger) &= 0, \\ \text{Im det}(M_D M_D^\dagger M_l M_l^\dagger - M_l M_l^\dagger M_L M_L^\dagger) &= 0, \\ \text{Im det}(M_D M_D^\dagger M_l M_l^\dagger - M_L M_l^* M_l^T M_L^\dagger) &= 0, \\ \text{Im det}(M_L M_D^* M_R M_D^\dagger - M_l M_l^\dagger M_l M_l^\dagger) &= 0 \end{aligned} \quad (20)$$

form a complete set of constraints. This set is also minimal by construction, as long as Eq. (19) is included.

Acknowledgements

We thank G. Branco for discussions. This work was partially supported by CICYT under contract AEN94-0936, by the Junta de Andalucía and by the European Union under contract CHRX-CT92-0004.

A Appendix

```
(*  
This package is available by anonymous ftp at deneb.ugr.es  
in directory pub/packages  
)
```

```
BeginPackage["CPlep'", "Diagon'"]
```

```
(*  
This package needs the functions DiagonalizeS, DiagonalizeH  
defined in the package Diagon, available by anonymous ftp at  
deneb.ugr.es
```

```
DiagonalizeS[m] gives a list {v,u} where m is a square matrix,  
v is a row vector and u is a matrix fulfilling  
u.m.Transpose[u]=DiagonalMatrix[v]
```

```
DiagonalizeH[m] is a modification of Eigensystem which gives a  
list {v,u}, with the eigenvalues and eigenvectors of the  
hermitian matrix m, such that  
u.m.Transpose[Conjugate[u]]=DiagonalMatrix[v]. The list of  
eigenvalues v is ordered by increasing absolute value  
)
```

```
cl1ini::usage =  
"cl1ini is a list with the possible first elements of a product in  
the class G1"  
cl2ini::usage =  
"cl2ini is a list with the possible first elements of a product in  
the class G2"  
cl3ini::usage =  
"cl3ini is a list with the possible first elements of a product in  
the class G3"  
cl1fin::usage =  
"cl1fin is a list with the possible last elements of a product in  
the class G1"  
cl2fin::usage =  
"cl2fin is a list with the possible last elements of a product in
```

```

the class G2"
cl3fin::usage =
  "cl3fin is a list with the possible last elements of a product in
  the class G3"
l1::usage =
  "l1 is a list with all the possible elements of a product"
f::usage =
  "f[expr] is 0 if expr is not an allowed product"
inv::usage =
  "inv[expr] returns expr if it is an invariant product, or 0 if not"
Looktrace::usage =
  "Looktrace[lf,Ml,ML,MD,MR] returns the elements in a list lf of
  f-products with trace nonzero when evaluated with the numerical
  matrices Ml,ML,MD,MR. The output is in the form of Dot products"
Lookdet::usage =
  "Lookdet[lf,Ml,ML,MD,MR] calculates all possible non-hermitian
  combinations x-y of elements of a list lf of f-products and then
  returns those with nonzero determinant when evaluated with the
  numerical matrices Ml,ML,MD,MR. The output is in the form of Dot
  products"
Newecs::usage =
  "Newecs[oldecs,ld,Ml,ML,MD,MR,vars,comp] looks for equations not
  present in oldecs, generated with a list ld of Dot products and the
  matrices Ml,ML,MD,MR with variables vars, of which comp are complex.
  It returns a list containing four lists: the list oldecs, possibly
  improved with simpler equations, the list of elements of ld that
  improve oldecs, a list of new equations not present in oldecs and a
  list of elements of ld that generate the new equations"
det::usage =
  "det is an option for Newecs with default value False which select
  to calculate the trace or the determinant"
Eliminatesols::usage =
  "Eliminatesols[sols] eliminates redundant solutions in sols"
Red12::usage =
  "Red12[M] reduces a neutrino mass matrix M in the case nL=1,nR=2 by
  changes of basis to a form in which CP is a diagonal matrix if it
  exists"
Red21::usage =
  "Red21[M,Me] reduces a neutrino mass matrix M in the case nL=2,nR=1

```

```

    by changes of basis to a form in which CP is a diagonal matrix if it
    exists. Me is the charged lepton mass matrix"
LookCP::usage =
    "LookCP[M] tests if a diagonal unitary matrix U exists such that
    U.M.Transpose[U]=Conjugate[M] and yields True or False"

Begin["Private`"]

(* Definitions for internal use only *)

(* No comments needed *)

trace[x_?MatrixQ]:=Sum[x[[i,i]],
{i,Length[x]}}/;Length[x]==Length[Transpose[x]];

Adj[m_]:=Transpose[Conjugate[m]]

(* Enlarge the dimension of a matrix with the identity *)

IncDim1[m_]:=Transpose[Prepend[Transpose[Prepend[m,Table[0,
{Length[m]}]]],Join[{1},Table[0,{Length[m]}]]]]

IncDim[m_,n_]:=Nest[IncDim1,m,n]

(* adjoint of a matrix *)

ad1[a[x_]]:=a[10 Floor[x/10]+3-Mod[x,10]];

(* Adjoint of an f-product *)

ad[f[x_]]:=Apply[f,Reverse[Thread[ad1[Apply[ff,f[x]],ff]]];
ad[0]=0;

(* Take hermitian elements of a list *)

auto[l_List]:=Block[{lt},(
For[lt={},n=1,n<=Length[l],n++,If[l[[n]]==ad[l[[n]]],
AppendTo[lt,l[[n]]]]];lt));

```

```

(* Take non-hermitian elements of a list *)

autono[l_List]:=Block[{lt},(
For[lt={},n=1,n<=Length[l],n++,If[l[[n]]==ad[l[[n]]],,
AppendTo[lt,l[[n]]],AppendTo[lt,l[[n]]]]];lt));

(* Imtr and Imdet are used by Newecs and just substitute the
symbolic expressions of the mass matrices and calculate the
imaginary part of the trace/determinant *)

Imtr[expr_,x_,y_,u_,v_,comp_]:=Block[{sust},(
sust={a[10]->x,a[20]->y,a[30]->u,a[40]->v,
a[13]->Adj[x],a[23]->Adj[y],a[33]->Adj[u],a[43]->Adj[v],
a[11]->Transpose[x],a[31]->Transpose[u],
a[12]->Conjugate[x],a[32]->Conjugate[u]};
Factor[ComplexExpand[Im[trace[expr/.sust]],comp] ] ])

Imdet[expr_,x_,y_,u_,v_,comp_]:=Block[{sust},(
sust={a[10]->x,a[20]->y,a[30]->u,a[40]->v,
a[13]->Adj[x],a[23]->Adj[y],a[33]->Adj[u],a[43]->Adj[v],
a[11]->Transpose[x],a[31]->Transpose[u],
a[12]->Conjugate[x],a[32]->Conjugate[u]};
Factor[ComplexExpand[Im[Det[expr/.sust]],comp] ] ])

(* minors calculates the set of invariant phases \Delta_{ij} of a
matrix. Used by LookCP *)

minor[m_,i_,j_]:=m[[i,i]]+m[[j,j]]-m[[i,j]]-m[[j,i]]

minors[m_]:=Flatten[Table[If[m[[i,j]]==0,0,minor[m,i,j],
minor[m,i,j]],{i,1,Length[m]},{j,i+1,Length[m]}]]

(* vec and linealindep check if a susbset of invariant phases is
linearly independent. Used by LookCP *)

vec[expr_,d_]:=Table[Coefficient[expr,delta[i]],{i,d}]

linealindep[exprs_,d_]:=MemberQ[Complement[Flatten[Minors[Thread[

```

```
vec[exprs,d]],Length[exprs]]],{0}],_]
```

```
(* Output format with standard notation *)
```

```
Format[f[x_,y_]]:={x,y};
Format[a[10]]=ColumnForm[{" ","M"," 1"},Left,Center];
Format[a[13]]=ColumnForm[{" "+"","M"," 1"},Left,Center];
Format[a[12]]=ColumnForm[{" *","M"," 1"},Left,Center];
Format[a[11]]=ColumnForm[{" T","M"," 1"},Left,Center];
Format[a[20]]=ColumnForm[{" ","M"," L"},Left,Center];
Format[a[23]]=ColumnForm[{" "+"","M"," L"},Left,Center];
Format[a[30]]=ColumnForm[{" ","M"," D"},Left,Center];
Format[a[33]]=ColumnForm[{" "+"","M"," D"},Left,Center];
Format[a[32]]=ColumnForm[{" *","M"," D"},Left,Center];
Format[a[31]]=ColumnForm[{" T","M"," D"},Left,Center];
Format[a[40]]=ColumnForm[{" ","M"," R"},Left,Center];
Format[a[43]]=ColumnForm[{" "+"","M"," R"},Left,Center];
```

```
(* Definition of f: not allowed products are 0 *)
```

```
f[a[10],a[x_]]:=0/(x!=13);
f[a[13],a[x_]]:=0/(x!=10 && x!=20 && x!=30);
f[a[12],a[x_]]:=0/(x!=11);
f[a[11],a[x_]]:=0/(x!=12 && x!=23 && x!=32);
f[a[20],a[x_]]:=0/(x!=12 && x!=23 && x!=32);
f[a[23],a[x_]]:=0/(x!=10 && x!=20 && x!=30);
f[a[30],a[x_]]:=0/(x!=33 && x!=43);
f[a[33],a[x_]]:=0/(x!=10 && x!=20 && x!=30);
f[a[32],a[x_]]:=0/(x!=31 && x!= 40);
f[a[31],a[x_]]:=0/(x!=12 && x!=23 && x!=32);
f[a[40],a[x_]]:=0/(x!=33 && x!=43);
f[a[43],a[x_]]:=0/(x!=31 && x!=40);

f[f[x_,y_],z_]:=If[f[y,z]==0,0,f[x,y,z],f[x,y,z]];
f[x_,f[y_,z_]]:=If[f[x,y]==0,0,f[x,y,z],f[x,y,z]];
f[f[x_,y_],f[u_,v_]]:=If[f[y,u]==0,0,f[x,y,u,v],f[x,y,u,v]];
f[0,x_]:=0;f[x_,0]:=0;
```

```

(* Definition of inv *)

inv[f[x_,y___,z_]]:=If[f[z,x]==0,0,f[x,y,z],f[x,y,z]];
inv[0]:=0;
SetAttributes[inv,Listable];

(* Definitions of lists *)

l1={a[10],a[13],a[12],a[11],a[20],a[23],a[30],a[33],a[32],a[31],
a[40],a[43]};
cl1ini={a[10],a[20],a[30]};
cl2ini={a[13]};
cl3ini={a[33],a[43]};
cl1fin={a[13],a[23],a[33]};
cl2fin={a[10]};
cl3fin={a[30],a[40]};

(* Definitions of Looktrace and Lookdet *)

Looktrace[l_List,x_,y_,u_,v_]:=Block[{n,sust,lev,lt,ls},(
ls=Apply[Dot,1,1];
sust={a[10]->x,a[20]->y,a[30]->u,a[40]->v,a[13]->Adj[x],
a[23]->Adj[y],a[33]->Adj[u],a[43]->Adj[v],a[11]->Transpose[x],
a[31]->Transpose[u],a[12]->Conjugate[x],a[32]->Conjugate[u]};
lev=ls/.sust;
For[lt={},n=1,n<=Length[ls],n++,
If[Chop[trace[lev[[n]]]]!=Conjugate[Chop[trace[lev[[n]]]]],
AppendTo[lt,ls[[n]]] ] ];
lt)];

Lookdet[l_List,x_,y_,u_,v_,sgn_:-1]:=Block[{i,cm,sust,cev,lt},(
cm=Complement[Union[Flatten[Outer[Plus,Apply[Dot,autono[1],1],
sgn Apply[Dot,1,1] ] ] ],{0}];
sust={a[10]->x,a[20]->y,a[30]->u,a[40]->v,
a[13]->Adj[x],a[23]->Adj[y],a[33]->Adj[u],a[43]->Adj[v],
a[11]->Transpose[x],a[31]->Transpose[u],
a[12]->Conjugate[x],a[32]->Conjugate[u]};
cmev=cm/.sust;
For[lt={},i=1,i<=Length[cm],i++,

```



```

If[Chop[Det[cmev[[i]]]]!=Conjugate[Chop[Det[cmev[[i]]]]],
AppendTo[lt,cm[[i]] ] ];lt));

(* Definition of Newecs *)

Newecs[oldecs_,list_,x_,y_,u_,v_,vars_,complexvars_,ops___]:=
Block[{ecs2,ecs3,i,j,lts,lt,newec,end,what,detyn,trordet,vars2},(
detyn=(det/.{ops})/.Options[Newecs];
If[detyn,trordet[args_]:=Imdet[args],trordet[args_]:=Imtr[args],
trordet[args_]:=Imtr[args] ];
ecs2=oldecs;
ecs3={};
vars2=Join[vars,Re[complexvars],Im[complexvars]];
For[lts={};i=1,i<=Length[list],i++,(
newec=trordet[list[[i]],x,y,u,v,complexvars];
For[j=1;end=False;what=0,j<=Length[ecs2] && !end,j++,
If[PolynomialQ[Factor[ecs2[[j]]/newec],vars2] && !(NumberQ[Factor
[ecs2[[j]]/newec]]),what=j;end=True] ];
If[end,ecs2[[what]]=newec;AppendTo[lts,list[[i]] ] ];
For[lt={};i=1,i<=Length[list],i++,(
newec=trordet[list[[i]],x,y,u,v,complexvars];
For[j=1;end=False,j<=Length[ecs2] && !end,j++,
If[PolynomialQ[Factor[newec/ecs2[[j]]],vars2],end=True] ];
If[!end,AppendTo[ecs3,newec];AppendTo[lt,list[[i]] ] ];
{ecs2,lts,ecs3,lt} );

Options[Newecs]={det->False}

(* Definition of Eliminatesols *)

Eliminatesols[sols_]:=Block[{i,j,sols2,inter},(
sols2=Union[sols];
For[i=1,i<=Length[sols2],i++,If[Head[sols2[[i]]]==And,,
sols2[[i]]=And[sols2[[i]],sols2[[i]] ],
sols2[[i]]=And[sols2[[i]],sols2[[i]] ] ];
i=1;
While[i<Length[sols2],(
j=i+1;
While[j<=Length[sols2],(

```

```

inter=Intersection[sols2[[i]],sols2[[j]] ];
If[inter==Union[sols2[[i]]],sols2=Delete[sols2,j],,
  If[inter==Union[sols2[[j]]],
    sols2=Delete[sols2,i];j=i+1,,j++ ] )];
i++);
For[i=1,i<=Length[sols2],i++,sols2[[i]]=Union[sols2[[i]]] ];
sols2 );

```

(* Definitions of Red12 and Red21 *)

```

Red12[m0_]:=Block[{lu,m,m12,m21,m22,w2,w,delta,n},{
  lu={};
  m=m0;
  m12:={m[[1,2]],m[[1,3]]};
  m21:=Transpose[m12];
  m22:={m[[2,2]],m[[2,3]]},{m[[3,2]],m[[3,3]]};
  w2=DiagonalizeS[m22][[2]];
  w=IncDim1[w2];
  m=Chop[w.m.Transpose[w]];
  If[Chop[m[[2,2]]-m[[3,3]]]==0,
    If[m12=={0,0},
      AppendTo[lu,2];AppendTo[lu,3],
    (* else *)
    If[m22=={0,0},{0,0},
      w2=DiagonalizeH[m21.Adj[m21]][[2]];
      w=IncDim1[w2];
      m=Chop[w.m.Transpose[w]],
    (* else *)
    If[m[[1,1]]!=0,
      delta=-Arg[m[[1,1]]]/2;
      w=DiagonalMatrix[{Exp[I delta],1,1}];
      m=w.m.Transpose[w],
    (* else *)
    n=(Chop[m12.Transpose[m12]])[[1,1]];
    If[n==0,
      AppendTo[lu,1],
    (* else *)
    delta=-Arg[n]/2;
    w=DiagonalMatrix[{Exp[I delta],1,1}];

```

```

        m=w.m.Transpose[w]
    ]
];
If[Im[m12]=={0,0},
    w2=DiagonalizeH[Re[m21].Transpose[Re[m21]]][[2]];
    w=IncDim1[w2];
    m=Chop[w.m.Transpose[w]],
(* else *)
    w2=DiagonalizeH[Im[m21].Transpose[Im[m21]]][[2]];
    w=IncDim1[w2];
    m=Chop[w.m.Transpose[w]]
]
]
] (* end m12=0 *)
(* else 1st if *) ];
m
)];

Red21[m_,me_]:=Block[{m2},
If[Chop[Abs[me[[1,1]]]-Abs[me[[2,2]]]]!=0,
    m,
(* else *)
    m2=Reverse[Transpose[Reverse[m]]];
    Reverse[Transpose[Reverse[Red12[m2]]]]
]];

(* Definition of LookCP *)

LookCP[m_]:=Block[{m2,dim,i,ecsdeg0,ecsdeg1,ecsdeg2,allecs,sol},(
m2=Chop[Arg[m]];
dim=Length[m];
For[i=1,i<=dim,i++,If[m[[i,i]]==0,m2[[i,i]]=delta[i] ] ];
ecsdeg0=Part[Minors[m2],
    Flatten[Position[Apply[Plus,Thread[vec[Minors[m2],dim]],1],0]]];
ecsdeg1=Part[Minors[m2],
    Flatten[Position[Apply[Plus,Thread[vec[Minors[m2],dim]],1],1]]];
ecsdeg2=Part[Minors[m2],
    Flatten[Position[Apply[Plus,Thread[vec[Minors[m2],dim]],1],2]]];
allecs=Join[ecsdeg1,ecsdeg2];

```

```

If[Complement[Chop[Sin[ecsdeg0]],{0}]=={},
If[allecs=={},True,(* there aren't equations *)
For[i=2;indeps={allecs[[1]]},i<=dim && i<=Length[allecs],i++,
  If[linealindep[Append[indeps,allecs[[i]] ],dim],
  AppendTo[indeps,allecs[[i]] ] ] ];
sol=Flatten[Solve[indeps==Table[0,{Length[indeps]}] ] ];
Complement[Chop[Chop[Sin[allecs/.sol]]],{0}]=={}],False]
)]

End[]

EndPackage[]

```

References

- [1] Review of Particle Properties, Phys. Rev. **D50** (1994)
- [2] N. Cabibbo, Phys. Rev. Lett. **10**, 531 (1963); M. Kobayashi and T. Maskawa, Prog. Theor. Phys. **49**, 652 (1973)
- [3] C. Jarlskog, Phys. Rev. Lett. **55**, 1039 (1985); Z. Phys. **C29**, 491 (1985)
- [4] S. Wolfram, Mathematica, a System for Doing Mathematics by Computer (Addison-Wesley Publishing Company, Redwood City, California, 1988)
- [5] F. del Aguila and J. A. Aguilar-Saavedra, UG-FT-62/96, hep-ph/9605418 and references there in.
- [6] F. del Aguila, J. A. Aguilar-Saavedra and G. C. Branco, in preparation.
- [7] F. del Aguila and M. Zralek, Nucl. Phys. **B447**, 211 (1995); Acta Physica Polonica **B27**, 971 (1996) and references there in.
- [8] J. Bernabéu, G. C. Branco and M. Gronau, Phys. Lett. **169B**, 243 (1986)
- [9] J. A. Aguilar-Saavedra, UG-FT-67/96, hep-ph/9607313. Package available by anonymous ftp at deneb.ugr.es, directory pub/packages/