

LAG TIMES AND PARAMETER MISMATCHES IN SYNCHRONIZATION OF UNIDIRECTIONALLY COUPLED CHAOTIC EXTERNAL CAVITY SEMICONDUCTOR LASERS

E.M. Shahverdiev¹, S. Sivaprakasam and K.A. Shore²

School of Informatics, University of Wales, Bangor, Dean Street, Bangor, LL57 1UT, Wales, UK

ABSTRACT

We report an analysis of synchronization between two unidirectionally coupled chaotic external cavity master/slave semiconductor lasers with two characteristic delay times, where the delay time in the coupling is different from the delay time in the coupled systems themselves. We demonstrate for the first time that parameter mismatches in photon decay rates for the master and slave lasers can explain the experimental observation that the lag time is equal to the coupling delay time.

PACS number(s): 05.45.Xt, 05.45.Vx, 42.55.Px, 42.65.Sf

Chaos synchronization [1] is of fundamental importance in a variety of complex physical, chemical and biological systems [2]. Application of chaos synchronization has been advanced in secure communications, optimization of non-linear systems' performance, modeling brain activity and pattern recognition [2]. Time-delay systems are ubiquitous in nature, technology and society because of finite signal transmission times, switching speeds and memory effects [3]. Therefore the study of chaos synchronization in these systems is of considerable practical significance. Because of their ability to generate high-dimensional chaos, time-delay systems are good candidates for secure communications based on chaos synchronization. In this context particular emphasis is given to the use of chaotic external cavity semiconductor lasers, because laser systems with optical feedback are prominent representatives of time-delay systems which can generate hyperchaos [4].

Most experimental investigations of chaos synchronization in unidirectionally coupled external cavity semiconductor lasers [4] have found that the lag time between the master and slave lasers' intensities is equal to the coupling delay, whereas numerical results [5] show that the lag time should be equal to the difference between the delay time in the coupling and round-trip time of the light in the transmitter's external cavity. Knowledge of the exact lag time is of considerable practical importance, as experiments on message transmission using fibre lasers and diode lasers have shown that the recovery of message at the receiver critically depends on the correction made for the lag time [4,6].

Recently there have been several attempts to explain the coupling-delay lag time synchronization in unidirectionally coupled external cavity semiconductor lasers. In [7] this phenomenon was related to a strong coupling and/or frequency detuning between the two lasers. However in a recent paper [8], where a numerical study of two unidirectionally coupled single-mode semicon-

¹Permanent address: Institute of Physics, 370143 Baku, Azerbaijan

²Electronic address: alan@sees.bangor.ac.uk

ductor lasers subject to optical feedback is reported, it was shown that such a phenomenon can be observed without any frequency detuning between the two lasers. In [8] it was found that two fundamentally different types of chaotic synchronization can occur depending on the relation between the strengths of the coupling and of the feedback of the lasers. In the first type of synchronization, when the feedback rates of the transmitter and receiver lasers are equal, the lag time is equal to the coupling delay between the transmitter and receiver lasers; in the second type of synchronization, when the feedback rate of the transmitter is equal to the sum of the feedback rate of the receiver and coupling strength, the lag time is the difference between the coupling delay and the round-trip time of the light in the transmitter. In numerical investigations of the first type of synchronization reported in [8] it was found that the synchronization error does not decay to zero but rather shows small oscillations even when the authors consider modified synchronization manifolds for the electric field amplitude and the carrier density by the introduction of a constant correction coefficient. Thus as the authors of [8] themselves acknowledge, the synchronization manifold introduced in [8] is not perfect but is approximate in nature.

In this paper we derive existence conditions for two types of perfect synchronization between unidirectionally coupled master external cavity lasers: 1) for the first time we demonstrate that parameter mismatches in photon decay rates for the master and slave lasers can explain the experimental observation that the lag time is equal to the coupling delay time. We compare our analytical findings with numerical simulations in [8] and discuss why the first type of synchronization numerically investigated in [8] was not perfect; 2) we recover the well-known result that for identical lasers the lag time in synchronization of master and slave systems is the difference between the coupling delay time and the time delay in the coupled systems themselves. An appropriate framework for treating the evolution of the electric field of external cavity laser diodes is provided by the widely utilised Lang-Kobayashi equations [9]. Suppose that the master laser described by equations

$$\begin{aligned}\frac{dE_1}{dt} &= \frac{(1 + \gamma_1)}{2} \left(\frac{G_1(N_1 - N_{01})}{1 + s_1 E_1^2} - \gamma_1 \right) E_1(t) + k_1 E_1(t - \tau_1) \exp(-\gamma_1 \tau_1); \\ \frac{dN_1}{dt} &= J_1 - e_1 N_1 - \frac{G_1(N_1 - N_{01})}{1 + s_1 E_1^2} E_1^2;\end{aligned}\quad (1)$$

is coupled unidirectionally with the slave laser described by equations

$$\begin{aligned}\frac{dE_2}{dt} &= \frac{(1 + \gamma_2)}{2} \left(\frac{G_2(N_2 - N_{02})}{1 + s_2 E_2^2} - \gamma_2 \right) E_2(t) + k_2 E_2(t - \tau_1) \exp(-\gamma_1 \tau_1) + k_3 E_1(t - \tau_2) \exp(-\gamma_2 \tau_2); \\ \frac{dN_2}{dt} &= J_2 - e_2 N_2 - \frac{G_2(N_2 - N_{02})}{1 + s_2 E_2^2} E_2^2;\end{aligned}\quad (2)$$

where $E_{1,2}$ are the slowly varying complex fields for the master and slave lasers, respectively; $N_{1,2}$ are the carrier densities; $\gamma_{1,2}$ are the cavity losses; $\gamma_{1,2}$ are the linewidth enhancement factors; $G_{1,2}$

are the optical gains; $k_{1,2}$ are the feedback levels; k_3 is the coupling rate; ω is the optical frequency without feedback (no frequency detuning between the two lasers); τ_1 is the round-trip time in the external cavity; τ_2 is the time of light between the master laser and the slave laser-coupling delay time; $J_{1,2}$ are the injection currents; $\tau_{e1,2}$ are the carrier lifetimes; $s_{1,2}$ are the gain saturation coefficients.

Now we shall demonstrate that depending on the laser system's parameters eqs.(1-2) can allow for two regimes of lag synchronization between the the lasers' intensities (which are related to the electric field amplitudes by $I = E^2$).

First we explore the possibility of perfect synchronization between the chaotic intensities of the master and slave lasers with the lag time equal to the coupling delay time – as is found in most experimental cases:

$$I_{1,2} = I_2; \quad (3)$$

(throughout this paper $x = x(t)$). We also assume an analogous synchronization manifold for the carrier densities $N_{1,2} = N_2$. As was numerically shown in [8] such a synchronization manifold (with some modifications) can exist if $k_1 = k_2$. However as mentioned above, the modified synchronization manifold studied in [8] was not perfect even after introducing a constant scaling factor $a = 1.016$ for the electric field amplitudes. In our notation the synchronization manifold considered in [8] would have been written as $a^2 I_{1,2} = I_2$. We also note the following further difference between the synchronization manifolds considered in this work and those in paper [8]: namely above we assume the synchronization manifold $N_2 = N_{1,2}$, the analogous synchronization manifold in [8] is of the form $N_2 = N_{1,2} + N$, where N is some constant. We would like to emphasize that assumption of (even the slightest) structurally different forms of synchronization manifolds for the dynamical variables of the systems to be synchronized is rather unusual. At the same time we underline that even after such a modifications of the synchronizations manifolds made in [8], synchronization was not perfect. The authors of [8] with reference to C.R. Mirasso (Ref.[13] in [8]) indicate that perfect synchronization is possible if different photon lifetimes are assumed for the master and slave lasers. A similar idea for achieving perfect synchronization between master and slave lasers with coupling-delay lag time is indicated in our recent work [10].

In this paper we show that perfect synchronization can be achieved without the above mentioned modifications of the synchronization manifolds. Following [10], suppose that there are parameter mismatches between the master and slave laser photon decay rates: $\gamma_1 \neq \gamma_2$. Using eq.(2) we write the dynamical equation for the E_2 in the following manner:

$$\frac{dE_{1,2}}{dt} = \frac{(1 + \gamma_1)}{2} \left(\frac{G_1(N_{1,2} - N_{01})}{1 + s_1 E_{1,2}^2} - \gamma_1 E_{1,2} + k_1 E_{1,1+\tau_2} \exp(-\gamma_1 \tau_1) \right);$$

Assuming that the lasers parameters are identical (except for photon decay rates and feedback rates) we find that if $E_{1,2}$ and E_2 are related by $E_{1,2} = E_2$ (consistent with the synchronization

manifold (3)), then under the conditions

$$k_1 = k_2; \quad (4)$$

and

$$\frac{(1 + \{\})}{2} \tau_1 = \frac{(1 + \{\})}{2} \tau_2 - k_3 \exp(-\{\tau_2\}); \quad (5)$$

(where $\tau = \tau_1 = \tau_2$) the equations for $E_{1;2}$ and E_2 become identical and the lag synchronization manifold (3) exists. We notice that the existence condition (4) of coupling-delay lag time synchronization (3) found here analytically is confirmed by numerical simulations in [8], where such a type of synchronization is demonstrated with identical feedback rates for the master and slave lasers: $k_1 = k_2 = 20\text{ns}^{-1}$. But as was already mentioned above, in that paper it was also acknowledged that synchronization was not perfect. Our analytical approach demonstrates that for perfect synchronization in addition to condition (4), condition (5) is also required. Here we again recall that we use the generally accepted synchronization manifold: $I_{1;2} = I_2$ and $N_{1;2} = N_2$. Thus in this paper we have demonstrated analytically for the first time that by taking into account difference in the photon lifetimes for the master and slave lasers one can obtain perfect synchronization. We have also established the relationship between the difference in the photon lifetimes and the coupling rate between the lasers to achieve such perfect synchronization. The fact that most experimental work on the subject has reported synchronization with lag time of the coupling delay time between the lasers is indicative of the fact that the lasers being synchronized had different cavity losses.

Next we show that for identical lasers (except for the feedback rates k_1 and k_2)

$$I_1 = I_{2;1-2}; \quad (6)$$

is the lag synchronization manifold (we recall that for the lag synchronization $\tau_2 > \tau_1$.)

We note that the synchronization manifold (6) is well-studied both numerically and analytically, see, e.g. [5] and we consider this case here only for completeness of our comparison with the results of [8]. For transparency of the analysis we again write the equation for $E_{2;1-2}$ explicitly:

$$\frac{dE_{2;1-2}}{dt} = \frac{(1 + \{\tau_2\})}{2} \left(\frac{G_2 (N_{2;1-2} - N_{02})}{1 + s_2 E_{2;1-2}} - \tau_2 \right) E_{2;1-2} + k_2 E_{2;2-1-2} \exp(-\{\tau_1\}) + k_3 E_{1;1} \exp(-\{\tau_2\});$$

Now suppose that $E_1 = E_{2;1-2} \exp(-\{\tau_1(1 - \tau_2)\})$, which is consistent with the synchronization manifold (6). Then it follows that under the condition

$$k_1 = k_2 + k_3; \quad (7)$$

equations for E_1 and $E_{2;1-2}$ become identical (naturally we also assume that $N_1 = N_{2;1-2}$) and perfect synchronization is possible. Thus under the condition (7) synchronization occurs with the

lag time $\tau_1 = \tau_2$. This analytical result is also confirmed by numerical simulations in [8], where it was demonstrated that perfect synchronization when the synchronization error $E_1 = E_2$; $\tau_1 = \tau_2$ after short transient decays to zero is possible for the identical master and slave lasers with (in our notation) $k_1 = 20\text{ns}^{-1}$; $k_2 = 5\text{ns}^{-1}$; $k_3 = 15\text{ns}^{-1}$.

To summarize, we have studied synchronization between unidirectionally coupled chaotic external cavity semiconductor lasers with two characteristic delay times, where the delay time in the coupling is different from the delay time in the coupled systems themselves. We have demonstrated for the first time that parameter mismatches in photon decay rates for the master and slave lasers can explain the experimental observation that the lag time is equal to the coupling delay time and derived relevant existence conditions.

This work is supported by UK EPSRC under grants GR/R22568/01 and GR/N63093/01.

References

- [1] L. M. Pecora and T. L. Carroll, Phys. Rev. Lett. 64, 821 (1990); E. Ott, C. Grebogi and J. A. Yorke, Phys. Rev. Lett. 64, 1196 (1990).
- [2] CHAOS, Special issue on chaos synchronization, 7, No 4 (1997); Handbook of Chaos Control, Ed. H. G. Schuster (Wiley-VCH, Weinheim, 1999).
- [3] J. K. Hale and S. M. Verduyn Lunel, Introduction to Functional Differential Equations (Springer, New York, 1993); L. E. El'sgol'ts and S. B. Norkin, Introduction to the theory and applications of differential equations with deviating arguments (Academic Press, New York, 1973).
- [4] S. Sivaprakasam and K. A. Shore, Optics Letters 24, 466 (1999); S. Sivaprakasam and K. A. Shore, IEEE J. Quantum Electron. 36, 35 (2000); H. Fujino and J. Ohtsubo, Opt. Lett. 25, 625 (2000); S. Sivaprakasam and K. A. Shore, Optics Letters 26, 253 (2001).
- [5] V. Ahlers, U. Parlitz and W. Lauterborn, Phys. Rev. E 58, 7208 (1998); C. Masoller, Phys. Rev. Lett. 86, 2782 (2001).
- [6] G. D. Van Wiggeren and R. Roy, Science 279, 1198 (1998); Phys. Rev. Lett. 81, 3547 (1998).
- [7] Y. Liu, H. F. Chen, J. M. Liu, P. Davis and T. Aida, Phys. Rev. A 63, 031802(R) (2001).
- [8] A. Locquet, F. Rogister, M. Sciamanna, P. Mégret and M. Blondel, Phys. Rev. E 64, 045203(R) (2001).
- [9] R. Lang and K. Kobayashi, IEEE J. Quantum Electron. 16, 347 (1980).
- [10] E. M. Shahverdiev, S. Sivaprakasam and K. A. Shore, Phys. Lett. A 292, 320 (2002).