## Self-Similar Evolution of Parabolic Pulses in a Laser

F.O. Ilday<sup>1;</sup>, J.R. Buckley<sup>1</sup>, W.G. Clark<sup>2</sup>, and F.W. Wise<sup>1</sup> <sup>1</sup>D epartment of Applied Physics, Cornell University, 212 Clark Hall, Ithaca, NY 14853, USA. <sup>2</sup>Clark-MXR Inc., Dexter, MI 48130. Corresponding author. Electronic address: ilday@ccmr.cornell.edu

Self-sim ilar propagation of ultrashort, parabolic pulses in a laser resonator is observed theoretically and experim entally. This constitutes a new type of pulse-shaping in modelocked lasers: in contrast to the well-known static (soliton-like) and breathing (dispersion-managed soliton) pulse evolutions, asymptotic solutions to the nonlinear wave equation that governs pulse propagation in most of the laser cavity are observed. Stable self-sim ilar pulses exist with energies much greater than can be tolerated in soliton-like pulse shaping, and this will have im plications for practical lasers.

PACS numbers: 42.55 W d, 42.65 Re, 42.65 Sf, 42.65 Jg, 42.81 Dp, 05.45 Yv

Self-sim ilarity is a recurring them e in the description of many natural phenomena. The emergence of selfsimilarity in complicated, nonlinear systems can be particularly inform a tive about the internal dynam ics: selfsim ilarity arises after the in uences of initial conditions have faded away, but the system is still far from its ultimate state [1]. Furthermore, the presence of selfsim ilarity in plies an inherent spatial and/ortem poralorder that can be exploited in the mathematical treatment of the governing equations. For example, reduction-ofsymmetry techniques e ectively reduce the dimensionality of the system, [2] which facilitates analysis. In the eld of nonlinear optics, a limited number of self-similar (SS) phenom ena have been reported. As examples, SS behavior in stimulated R am an scattering [3] and the formation of Cantor-set fractals in materials that support spatial solitons [4] were investigated. The most pertinent prior work is the theoretical dem onstration of SS propagation of short pulses of parabolic intensity pro le in optical bers with norm al group-velocity dispersion (GVD) and strong nonlinearity [5]. Recently, this concept has been extended to an optical ber am plier. By use of the technique of symmetry reduction, parabolic pulses were shown to propagate self-sim ilarly in the am pli er, and the predicted evolution was veri ed experimentally [6, 7, 8]. Considering that the solutions of the nonlinear Schrodinger equation that governs pulse propagation in a ber are well-known, it is remarkable that the SS solutions were discovered only recently.

In addition to the scienti c interest in SS pulse propagation, there is practical motivation: the energy of ultrashort optical pulses is generally limited by wave-breaking, which is a consequence of excessive nonlinearity. The limitation is particularly stringent in short-pulse ber devices, where small modes produce high intensities and therefore large nonlinear phase shifts. In contrast to solitons, SS pulses (or \similaritons" [9]) can to lerate strong nonlinearity without wave-breaking. The presence of normalGVD tends to \linearize" the phase accum ulated by the pulse, which increases the spectral bandwidth but does not destabilize the pulse [5]. O wing to their compact size and excellent stability, ber lasers are appealing alternatives to bulk solid-state lasers. If the pulse energy available from ber lasers can be increased to that of solid-state lasers, ber lasers could nd widespread application, so the possibility of achieving SS propagation in a laser is very attactive.

However, experimental studies of SS optical phenomena are generally restricted to the observation of evolution over a limited number of characteristic propagation lengths, due to practical limitations. Furthermore, we are not aware of any experimental observations of asymptotic SS evolution in an optical system with feedback, such as a laser. A symptotic solutions of a wave equation would appear to be incompatible with the periodic boundary condition of a laser resonator.

Here we report num erical predictions of the existence of stable pulses that indeed propagate self-sim ilarly in a laser cavity, along with clear experim ental evidence of SS pulses in a ber laser. This regime of operation constitutes a new type of pulse shaping in a modelocked laser, qualitatively distinct from the well-known soliton [10] and dispersion-m anaged soliton [11] regimes. The main features of SS pulses in a laser will be presented, and the im plications for practical devices will be discussed brie y.

Pulse formation in a fem to second laser is typically dominated by the interplay between dispersion and nonlinearity [12]. An elective saturable absorber (SA) is required for initiation of pulsed operation from intra-cavity noise and subsequent stabilization of the pulse. Hence, the laser constitutes a dissipative system and its basic features can be understood within the formalism of a complex G inzburg-Landau equation or related formulations [13].

Soliton ber lasers are limited to low pulse energies (100 pJ or less) [10]. At higher energies, nonlinear effects cause wave-breaking [14], which leads to multiple-pulsing (m ore than one pulse circulates in the cavity). The pulse can tolerate only a sm all nonlinear phase shift ( $^{NL}$  << ) before such instabilities occur. Stretched-pulse ber lasers consist of segments of anom alous and norm alGVD [11]. These in plem ent the concept of dispersion m anagement (DM) [15], and support the analog of DM solitons. DM solitons can tolerate nonlinear



FIG.1: Top: schem atic diagram of the main components of the laser. SMF: single mode ber, DDL: dispersive delay line, SA: saturable absorber. The cavity is a ring, so after the DDL the pulse goes into the SMF. Bottom: variation of the tim e-bandwidth product and spectral width in the cavity.

phase shifts an order of m agnitude larger than ordinary solitons, and the pulse energy thus exceeds the soliton energy by the sam e factor.

Solitons are static solutions of a nonlinear wave equation, and DM solitons are breathing solutions. In contrast, SS pulses are asymptotic solutions to the governing equation. The evolution of their properties (e.g., the pulse duration) is monotonic. Such a solution cannot be a stable solution in a cavity; a mechanism to reverse any changes and thus restore the solution after traversal of the cavity must be provided. A nother issue must be addressed for SS propagation to occur in a laser: in general, pulses will evolve to ll available gain bandwidth. How ever, self-sim ilar propagation of intense pulses is disrupted if the pulse encounters a limitation to its spectral bandwidth [16].

The conceptual model for a ber laser illustrated in Fig. 1 addresses these issues. A segment of single-mode ber (SMF) with norm alGVD form sthem a prity of the cavity. Amplication is provided by the minimum length of gain ber required to provide adequate gain. The pulse will experience negligible GVD and nonlinearity during amplication, which e ectively decouples bandwidth ltering from the nonlinear evolution in the SMF. The gain ber is followed by a SA, which also serves as the output coupler. The nalelement is a dispersive delay line (DDL) that provides anom alous GVD with negligible nonlinearity. The cavity is a ring: after the DDL, the pulse returns to the SMF. In a time-domain view, chirp accumulated in the desired SS propagation will be compensated by the DDL. In the frequency domain, generated bandwidth will be ltered by the gain m edium, to produce a self-consistent solution in the resonator. The pulse evolution is illustrated by the plots of tim e-bandwidth product and spectralwidth versus cavity position (Fig. 1, details to be provided below).

Numerical simulations of the model laser were em – ployed to search for SS solutions, and to verify that such



FIG.2: Results of num erical simulations. (a) Output power spectrum. (b) Temporal intensity prole (solid curve), instantaneous frequency (dash-dotted curve), and a parabolic t (dotted curve) to the intensity prole. (c) Equal-intensity contours of the pulse evolution within the SM F.

solutions are accessible from intracavity noise. The param eters of the num erical model correspond to the experimental setup. A segment of SMF 6 m in length is connected to a 23-cm -long gain ber, and a grating pair is used for the DDL.Propagation within each section is modeled by

$$\frac{\partial A(;)}{\partial t} + i_{2} \frac{\partial^{2}}{\partial t^{2}} A(;) =$$

$$i \dot{A}(;) \dot{f} A(;) + g(E_{pulse}) A(;); \qquad (1)$$

where A (; ) is the envelope of the eld, is the propagation coordinate, is time scaled to the pulse duration,  $_2 = 23fs^2 = mm$  is the GVD, and  $= 0.0047 (Mm)^{-1}$ is the coe cient of cubic nonlinearity for the ber section. The pulse energy is  $E_{pulse} = \frac{R_{T_R}=2}{T_R=2} A(;)^2 d$ and  $T_R$  40 ns is the cavity roundtrip time.  $g(E_{pulse})$ is the net gain, which is non-zero only for the ampli er ber. The gain saturates with total energy according to

$$g(E_{pulse}) = \frac{g_0}{1 + E_{pulse} = E_{sat}};$$
 (2)

where  $g_0$  30 dB is the small-signal gain with an inplicit parabolic frequency dependence and a bandwidth of 45 nm. The gain saturation energy,  $E_{sat}$ , is determined by the pump power. The SA is modeled by a transfer function that describes its (monotonic) transmittance T = 1  $l_0=(1 + P()=P_{sat})$ , where  $l_0 = 0.3$ is the unsaturated loss, P() is the instantaneous pulse power and  $P_{sat}$  is the saturation power. All signi cant linear losses occur in the DDL and in coupling into the SMF. The pulse amplitude is reduced by a factor of 10 after the SA to account for these losses, which can be lum ped together without loss of generality.

The num erical model is solved with a standard sym metric split-step beam propagation algorithm and the initial eld is white noise. The simulations are nun until the eld becomes constant after a nite num ber of traversals of the cavity. We have veried num erical accuracy



FIG. 3: (a) Calculated maximum pulse energy versus totaldispersion for the self-sim ilar (up-triangles) and stretchedpulse (down-triangles) schemes. (b) Intra-cavity breathing ratio with respect to total dispersion for the self-sim ilar scheme. The lines are to guide the eye.

by checking that the results are unchanged after doubling each of the sam pling resolutions. The simulations exhibit stable pulse form ation over a reasonably-wide range of param eters. For xed param eters, exactly the sam e stable solutions are reached from distinct initial noise elds. Thus, these solutions appear to be true attractors. A typical solution obtained with  $_{net} = 0.007 \text{ ps}^2$ ,  $P_{sat} = 15$ kW , and E  $_{\rm sat}$  = 4:0 nJ is shown in Fig. 2. The pulse energy is 15 nJ. The approxim ately-parabolic tem poral pro le, nearly-linear chirp, shape of the power spectrum, and the evolution of the intensity pro le are all signatures of SS pulse form ation. For increasing norm alGVD (  $_{net}$  > 0) the pulse energy increases dram atically (see Fig. 3). The stretching ratio decreases exponentially at xed pulse energy as the net GVD is increased (inset of Fig. 3). Thus, the energy-scaling can be understood intuitively: the (exponential) increase in pulse energy with increasing GVD maintains a xed stretching ratio.

Encouraged by the simulation results, we constructed a Y b: ber laser with the parameters listed above. Modelocked operation is initiated and stabilized by nonlinear polarization evolution (NPE) [17], and the output is taken from the NPE rejection port. The laser modelocks easily upon adjustment of the wave-plates that control the NPE. The experiments are performed at low pulse energies (2 nJ) to avoid over-driving NPE and thus isolate the SS pulse-shaping. Results obtained with net =  $0.004 \text{ ps}^2$  will be presented and are representative of those obtained in the range net =  $0.003 \quad 0.015 \text{ ps}^2$ .

The characteristics of the generated pulses are consistent with SS evolution. The power spectrum exhibits the unique shape that is predicted num erically: parabolic near the peak, with a transition to a steep decay (Fig. 4 (a)). The pulse is extracted from the cavity where it is expected to have maximum positive chirp. The intensity autocorrelation reveals that the pulse duration is

42 ps. A fler dechipping the pulse with di raction gratings external to the cavity, the pulse duration is 130 fs (Fig. 4 (b)). The dechipped pulse duration is close to the transform -lim it, which im plies an approximately linear chipp on the generated pulse, as expected theoretically.

The magnitude of anom alous GVD required to dechirp



FIG.4: Experimental results. (a) Power spectrum on semilog scale. Inset: spectrum on linear scale. (b) Intensity autocorrelation of the chirped and the dechirped pulses.



FIG. 5: (a) Cross-correlation of the chipped and the dechipped pulses. (b) Calculated intensity pro le. Parabolic (dashed curves) and sech<sup>2</sup> (dotted curves) ts are also shown.

the output pulse is an important diagnostic of pulse evolution in the laser. From the experimental value ( $0.170 \text{ ps}^2$ , approximately equal to that provided by the intracavity gratings) we conclude that the pulse chirp is positive throughout the cavity, with a minimum at the beginning of the SM F.W e estimate a minimum pulse duration of 250 fs. Thus, the overall stretching ratio within the cavity is 17.

Finally, the measured shape of the chirped pulses generated by the laser further supports the SS nature of the pulse evolution. The pulse shape was obtained by cross-correlation with the dechirped pulse, which is 32 tim esnarrow er and thus a good approxim ation to a deltafunction. The pulse shape (Fig. 5) agrees well with the num erical simulations and the parabolic intensity pro le expected analytically. The small secondary pulse could develop during interm ediate asymptotic evolution [8]. However, it does not appear in the simulations. Qualitatively, such structure is expected when the pulse is taken from the NPE rejection port. The simulated results shown above are for the pulse that continues to propagate in the cavity, so this m inor discrepancy is not surprising.

The pulse energy was intentionally limited as a control on the experiments reported above. An important aspect of the SS regime is the prediction of stable pulses with much higher energies than can be contained in DM solitons. This prediction is based on the assumed m onotonically-saturating absorber. NPE is interferom etric in nature, so it can be overdriven (i.e., the transm ission eventually decreases at high intensity) and this may well lim it the pulse energy. A laser with lower repetition rate was constructed, so that high-energy pulses were possible energetically given the available pump power. W ith  $net = 0.003 \text{ ps}^2$ , stable pulses with autocorrelation and spectrum similar to those shown above are generated. The chirped-pulse energy is 10 nJ, which is 3 times the maximum obtained from a DM -soliton laser [18]. More system atic studies of the SS pulse energy are needed, but this initial result is encouraging. A laser operated close to the SS regime has exhibited wave-breaking-free operation with peak powers 5 times that of a DM -soliton laser [20].

The experimental results conm the essential features of the SS regime of laser operation, which can be placed in context with prior lasers. In contrast to static soliton solutions and breathing DM solitons, the nonlinear pulse evolution is monotonic in each segment of the dispersion m ap. DM solitons stretch and compress twice per cavity round-trip, while SS pulses stretch and compress once. True solitons are unchipped. DM solitons acquire both negative and positive chips as they propagate, while SS pulses are positively-chipped throughout the cavity. D etailed distinctions include the approximately parabolic temporal prole, which contrasts with the hyperbolicsecant soliton solution and gaussian DM soliton, and the unique spectral prole of the SS pulse. In this report we have focused on ber lasers, which perhaps provide the most natural environment for SS pulses. However, the concept is more broadly applicable. SS operation of solid-state lasers would extend the previously-observed operation with normal GVD [19], where the pulse duration is nearly static, to stretching ratios > 1. Initial simulations with parameters close to those of existing T isapphire lasers that produce 10fs pulses exhibit some of the features of SS propagation (including stable chirped solutions and increased pulse energy) when the net GVD is normal. It is also reasonable to expect that the conditions for SS pulse formation could be met in sem iconductor lasers.

In conclusion, we have observed self-sim ilar pulse evolution in a laser resonator. This new type of pulse formation is qualitatively distinct from previously-identi ed mode-locking techniques. Chirped pulses with parabolic temporal (and spectral) pro les exist throughout the laser cavity. The pulses can be dechirped to nearly the Fourier-transform limit outside of the laser, so the dem onstration of self-sim ilar pulse form ation m ay have major implications for short-pulse lasers. The initial experim ental results reported here already represent at least twice the pulse energy of prior fem to second ber lasers. If overdriving of the elective saturable absorber can be avoided, pulse energies one to two orders of magnitude larger than those of existing lasers should be possible. Current e orts are aim ed at identifying the lim its of NPE and exploring monotonic saturable absorbers.

This work was supported by the N ational Institutes of H ealth under grant EB 002019 and the A ir Force R essarch Laboratory under contract F 29601-00-C -0049.

- G.I.Barenblatt, Scaling, Self-sim ilarity, and Interm ediate A sym ptotics (C am bridge U niversity, 1996), and P.L. Sachdev, Self-sim ilarity and Beyond: Exact Solutions of N onlinear Problem s (CRC, New York 2000).
- [2] For example, W .F.Ames, Nonlinear PartialDi erential Equations (A cadem ic, New York, 1967).
- [3] C R. Menyuk, D. Levi, and P. W intermitz, Phys. Rev. Lett. 69, 3048 (1992).
- [4] M. Soljacic, M. Segev, and C. R. Menyuk, Phys. Rev. E 61, R1048 (2000).
- [5] D. Anderson, M. Desaix, M. Karlsson, M. Lisak, and M. L.Quiroga-Teixeiro, J.Opt.Soc.Am. B 10, 1185 (1993).
- [6] M.E.Fermann, V.I.Knuglov, B.C.Thomsen, J.M. Dudley, and J.D.Harvey, Phys. Rev. Lett. 84, 6010 (2000)
- [7] V. I. K nugbv, A. C. Peacock, J. M. Dudley, and J. D. Harvey, Opt.Lett. 25, 1753 (2000).
- [8] V. I. Kruglov, A. C. Peacock, J. D. Harvey, and J. M. Dudley, J. Opt. Soc. Am. B 19, 461 (2002).
- [9] C. Finot, G. Millot, C. Billet, and J. M. Dudley, Opt. Express 11, 1547 (2003).
- [10] I.N.Duling III, Electron.Lett. 27, 544 (1991).

- [11] K. Tam ura, E. P. Ippen, H. A. Haus, and L. E. Nelson, Opt.Lett. 18, 1080 (1993).
- [12] H.A.Haus, J.G.Fujim oto, and E.P. Ippen, IEEE J. Quantum Electron., 28, 2086 (1992).
- [13] J.M. Soto-C respo, and N.Akhmediev, Phys. Rev. E 66, 066610 (2002), and references therein.
- [14] D. Anderson, M. Desaix, M. Lisak, and M. L. Quiroga-Teixeiro, Opt. Lett. 9, 1358 (1992).
- [15] N.J.Smith, N.J.Doran, W.Forysiak, and F.M.Knox, J.Lightwave Technol. 15, 1808 (1997).
- [16] A.C.Peacock, R.J.K nuhlak, J.D.Harvey, and J.M. Dudley, Opt.Comm. 206, 171 (2002).
- [17] M. Hofer, M. E. Ferm ann, F. Harberl, M. H. Ober, and A. J. Schmidt, Opt. Lett. 16, 502 (1991).
- [18] L.E.Nelson, S.B.Fleischer, G.Lenz, and E.P. Ippen, Opt.Lett. 21, 1759 (1996).
- [19] B.Proctor, E.W estwig, and F.W ise, Opt.Lett. 18, 1654 (1993).
- [20] F.O. Ilday, J.R. Buckley, H. Lim, F.W. W ise, and W. G.Clark, Opt. Lett. 28, 1365 (2003).