

Comment on "Quantum Optimization for Combinatorial Searches"

Christof Zalka

zalka@uwaterloo.ca

Department of Combinatorics and Optimization,
University of Waterloo, Waterloo, Ontario, Canada N2L 3G1

Todd Brun

tbrun@ias.edu

Institute for Advanced Study,
Einstein Drive, Princeton, NJ 08540

January 25, 2002

In a recent publication [1] C. A. Trugenberger claims to have found a "quantum optimization" algorithm which outperforms known algorithms for minimizing some "cost function". Unfortunately, this algorithm does not work. It is no better than choosing a state at random and checking whether it has low cost; in fact, carrying out the procedure can do considerably worse than this.

In the given algorithm, a particular state is prepared on a quantum computer. One then makes two measurements in sequence. Only if the first measurement results in a desired outcome, do we proceed; otherwise we start over from the state preparation stage. The probability of obtaining the desired final state is the product of the success probability in the first measurement and the probability of obtaining the desired state in the second measurement, given success in the first. But it is easy to see that for any state, this overall success probability is at most one over the number of possible states.

The author constructs a uniform amplitude superposition of all N states (his Eq. 8):

$$|j_0\rangle = \frac{1}{\sqrt{N}} \sum_{k=1}^N |j^k\rangle$$

Upon measuring, we would obtain each state $|j^k\rangle$ with equal probability $1/N$. Now the author adds an auxiliary register and performs a unitary transformation, based on a particular cost function, which produces a final state of the

from (his Eq. 15):

$$j_{\text{fin}} = \frac{1}{N} \sum_{k=1}^N j^k; \quad (I^k)_i$$

He first measures the second (auxiliary) register. If this is found to be j_0 (0), he then measures the first register, obtaining a state I^k , which he hopes to be the state I^{min} which minimizes the cost function. More generally, he wants to find a state I^k which is close to optimal, i.e., which has cost $C(I^k) < C^{\text{tol}}$ for some low value C^{tol} . Let's suppose there are M such states.

The two-step procedure, however, is unnecessary | it could just as well be done in one go by measuring both registers simultaneously, and possibly rejecting the result depending on what is found in the second register. The probability of one attempt being successful is then

$$\begin{aligned} p(C(I^k) < C^{\text{tol}} | j_0 = 0) &= p(0 = j_0 | C(I^k) < C^{\text{tol}}) \\ &= p(C(I^k) < C^{\text{tol}}) \cdot p(0 = j_0 | C(I^k) < C^{\text{tol}}) \\ &= (M/N) \cdot p(0 = j_0) \cdot p(C(I^k) < C^{\text{tol}}) \\ &= M/N; \end{aligned}$$

(where $p(A \& B)$ denotes the probability of outcomes A and B both occurring, and $p(A | B)$ the probability of A given that B has occurred). The probability of a successful outcome is less than or equal to M/N , which is just the probability of measuring the first register and randomly getting an I^k with $C(I^k) < C^{\text{tol}}$. The algorithm is therefore worse than a random search | possibly much worse.

In the paper, the success probabilities for the two measurements to yield any fixed state I^k are given by P_b^0 (Eq. 16) and $P_b(I^k)$ (Eq. 17), and clearly their product is less than (or equal to) $1/N$.

Finally we would like to point out that any algorithm with an interesting performance for minimizing a cost function, has to exploit some structure of this function. Heuristics typically rely on the tendency of "neighboring" states to have similar cost. But the author doesn't exploit anything like that. He considers the states as a set without any structure, in particular without a metric.

References

- [1] Quantum Optimization for Combinatorial Searches, C.A. Trugenberger, New Journal of Physics 4 (2002) 1.1-1.7 (also quant-ph/0107081)