

# A summary on two new algorithms for Grover's unsorted database search problem

Bin Shang\*

*School of Computer Science & Technology, Beijing Institute of Technology,  
No. 5, Zhongguancun Nandajie, Haidian District, Beijing 100081, P. R. China*  
(Dated: April 1, 2022)

In this summary we discuss two new algorithms for Grover's unsorted database search problem that claimed to have reached exponential speedup over Grover's original algorithm. One is in the quantum setting with "power queries" that allow for exponential reduction in the number of queries over Grover's original algorithm with "bit queries". The other is to use "dubit queries" on a duality computer - a new computing model uses a quantum system's wave-particle duality, which is able to achieve even greater computing power and better capability than existent quantum computers we have been discussing. We discuss the shortages and difficulties of both schemes as well.

## INTRODUCTION

Grover's unsorted database search problem has been extensively studied in the past decade for its wide use and great significance in computational theory. Grover's problem is related to many famous and important problems including the satisfiability problem, the traveling salesman problem, the minimization problem of choosing the smallest number out of  $N$  real numbers, the Boolean mean problem, the integration problem, and the Sturm-Liouville eigenvalue problem. If any one of those problems can be effectively solved it will be a great progress to quantum computation and computer science.

Since 1996 people have worked on Grover's algorithm from different aspects. Some authors have tried to solve the search problem with a polynomial algorithm. But people never achieved, without consumption of exponentially more computing resources and spaces, an exponential speedup over classical algorithms or Grover's original algorithm, as Shor's factoring and discrete logarithm algorithms did. Nearly all those who claimed to have improved Grover's algorithm to an exponential speedup have been wrong.

## THE ALGORITHM ON A QUANTUM COMPUTER WITH POWER QUERIES

Unlike such methods that people used before, Papageorgiou et al, during these two or three years, have found a new way for the search problem, which is possible to be implemented. They use "power queries" ("power query" is defined in [1]), which have been applied in phase estimation algorithms and Shor's factoring algorithm, instead of "bit queries" applied in Grover's original algorithm. They first [1] studied the complexity of the Sturm-Liouville eigenvalue problem on a quantum computer using power queries, and showed that their algorithm had achieved an exponential reduction in

the number of power queries over that of bit queries. Then [2] they showed that some famous NP-hard and NP-complete problems including Grover's Search Problem can be reduced to the Sturm-Liouville eigenvalue problem in the quantum setting with power queries. They solved Grover's search problem—to find single marked state from an unsorted database with  $N = 2^n$  states in all—with probability  $1 - \delta$ , using  $n \log \delta^{-1}$  power queries and  $n$  qubits.

However, contrary to Shor's algorithm, it is doubtful that whether power queries used in Papageorgiou et al's search algorithm can be implemented by a number of existing elementary quantum gates that is polylog in  $n$ . A recent paper [3] discussed the relation between Grover's and Shor's algorithms, and showed that Grover's algorithm can be viewed as a quantum algorithm which solves a non-abelian hidden subgroup problem (HSP) but the standard non-abelian quantum hidden subgroup algorithm can not find a solution to this particular HSP. That work would be helpful to studying on how to build a new method to solve Grover's search problem with power queries without the exponentially increasing difficulties in constructing the quantum gates. If such method is found, we can affirm that quantum computers are able to solve efficiently NP problems.

## THE ALGORITHM FOR GROVER'S SEARCH PROBLEM ON A DUALITY COMPUTER

### 1. Introduction

Almost simultaneously, Long has spent more than three years thinking on his brand new computing model using the wave-particle duality of quantum systems: the duality computer [4][5]. From a physician's view, he considered the principles of quantum interference between both quantum particles and quantum systems. He stood on convictive physical basis, by generalizing series of principles of quantum interference, and proposed two

implementations for the duality computer.

A duality computer is such a computing machine that uses both particle and wave property of quanta. Analogous to qubit, Long uses “dubit” (duality bit) as the basic information unit. Such is a sequent process of a computation on a duality computer (duality computation for short): first, we make the initial quantum states of the quantum system for the computation; second, we divide the quantum wave of the system into multiple paths (i.e. sub-waves) using a setting called quantum wave divider (QWD for short); third, we perform different quantum gate operations on corresponding paths; fourth, we recombine all the sub-waves to get the resultant wave using another setting called quantum wave combiner (QWC for short); at last, we measure the readouts of the computation.

## 2. Complexity

Now let us see the complexity of Long’s algorithm for Grover’s unsorted database search problem—to find single marked state from an unsorted database with  $N = 2^n$  states in all—with a single query on a duality computer. Here we ignore all errors that may occur. It is shown in [5] that we can find the marked item with certainty.

(1) Dubit complexity

The algorithm can be implemented using only dubits. So the dubit complexity is  $\log N = n$ .

(2) Query complexity

Only one query is needed for one dubit for the problem. In randomized cases, the lower and upper bounds of the algorithm are  $\Omega(\log N)$  and  $\mathcal{O}(\log N)$ . So the query complexity is  $\Theta(n)$ .

Obviously, Long’s algorithm has achieved an even greater speedup over Papageorgiou et al’s.

## 3. Difficulties

Although the proposal of duality computer is exciting, and algorithms on a duality computer can achieve outstanding efficiency on the unsorted database search problem, it has both theoretical and practical difficulties.

Unlike in a quantum computer, Long used the generalized interference principles which are not currently accepted by most physicians. If the hypothesis that interference will occur to quantum systems with several constituent particles, no matter loose or bound as Long proposed, is proved wrong, the duality computer can be of only theoretical interest.

Besides, it is unknown yet whether we can in the near future succeed in constructing such a computer that is able to subtly operate dubits’ (such as photons) both particle and wave properties. The difficulty may be much more than what we are suffering in constructing (optical) quantum computers.

## CONCLUSION

We showed two completely different algorithms for Grover’s unsorted database search problem in quantum settings with power queries and in duality computers. We viewed the complexities of both algorithms, and found either algorithm achieves an exponential speedup than any former algorithms and either way may be a great innovation on quantum computation.

We studied shortcoming of the two schemes as well. Both methods are in theory, and not yet implemented in practice, or perhaps will never be. However, in the author’s opinion, studies on both methods are meaningful. Even if they are of only theoretical value, we may find other helpful ways related to them to solve Grover’s search and other NP hard problems. And if only one of them can be implemented some day, we will have progress a great step in computing.

---

\* binshang@bit.edu.cn

## REFERENCES

- [1] Papageorgiou, A. and Woźniakowski, H. (2005), Classical and quantum complexity of the Sturm-Liouville eigenvalue problem. *Quantum Information Processing*, 4(2):87-127, 2005. Also <http://arXiv.org/quant-ph/0502054>.
- [2] Papageorgiou, A. and Woźniakowski, H. (2005), The Sturm-Liouville eigenvalue problem and NP-complete problems in the quantum setting with queries. <http://arXiv.org/quant-ph/0504194>
- [3] SAMUEL J. LOMONACO, JR. AND LOUIS H. KAUFFMAN. (2006), IS GROVER’S ALGORITHM A QUANTUM HIDDEN SUBGROUP ALGORITHM?. <http://arXiv.org/quant-ph/0603140>
- [4] Long, G.L. (2002), Quantum computation using nonlinear quantum optics, unpublished manuscript, submitted to *Fluctuations and Noise in Photonics and Quantum Optics 2002*.
- [5] Long, G.L. The general quantum interference principle and the duality computer (2005), to appear in *Communications in Theoretical Physics*. Also <http://arXiv.org/quant-ph/0512120>.